

Source: SA1
Title: TR 22.979 (v1.0.0) on Feasibility study on Combined CS Calls and IMS Sessions (Rel-7)
Document for: Information/Approval
Agenda Item: 7.1.3

TSG-SA WG1 #26
Sophia Antipolis, France, 11th to 15th October

S1-040988
Agenda Item:

Presentation of Specification to TSG or WG

Presentation to: TSG SA Meeting #26
Document for presentation: TR 22.979, Version 1.0.0
Presented for: Information and Approval

Abstract of document:

TR 22.979 studies the service requirements associated with a multimedia service combining a CS call with one or more IMS services (or vice versa), while appearing as a single service to both end-users. The feasibility study addresses the high-level requirements and use cases such for combinational service including charging and user experience.

Changes since last presentation to TSG-SA:

The document is presented for information and approval.

Outstanding Issues:

It remains to be decided if the first listed requirement in section 9.2, "It shall be possible to add a CS speech call to an IMS session, thereby creating a combinational service.", actually belongs to phase 2 or if it instead should be part of phase 1 requirements.

Contentious Issues:

None

3GPP TR 22.979 V1.0.0 (2004-12)

Technical Report

3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Feasibility study on Combined CS Calls and IMS Sessions; (Release 7)



The present document has been developed within the 3rd Generation Partnership Project (3GPPTM) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPPTM system should be obtained via the 3GPP Organizational Partners' Publications Offices.

Keywords

<keyword[, keyword]>

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2004, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TTA, TTC).
All rights reserved.

Contents

Foreword.....	4
1 Scope	5
2 References	5
3 Definitions, symbols and abbreviations.....	5
3.1 Definitions	5
3.3 Abbreviations	5
4 Introduction to Combinational Service.....	5
5 User experience of combinational services	6
6 Service Capability Detection	6
7 Impacts on IP Multimedia and Supplementary Services	7
7.1 Supplementary services during a combinational call.....	7
7.2 Service behaviour during a Combinational Session	7
7.3 Support of teleservices during a combinational call.....	8
8 Charging aspects for Combinational Service	8
9 Suggested high-level Requirements	8
9.1 Suggested requirements for phase 1	8
9.2 Suggested requirements for phase2	9
10 Conclusions and Recommendations.....	10
Annex A (Informative): “Use cases”	11
A.1 Enriching Communications	11
A.1.1 Enriched call session with multimedia.....	11
A.1.2 Voice enhanced chatting	12
Annex B: Change history	13

Foreword

This Technical Report has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

This document studies the service requirements associated with a multimedia service combining a CS call with one or more IMS services (or vice versa), while appearing as a single service to both end-users. The feasibility study addresses the high-level requirements and use cases such for combinational service including charging and user experience.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TS 22.115: "Charging and Billing".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Combinational Service: A combinational service is created by adding one or more IP multimedia component(s) to a CS call (or vice versa). The CS and IMS components are established between the same participants.

Combinational call: this is the name given to the service in which a circuit switched speech teleservice is enriched by adding an IMS session where both services (session and CS call) are originated in one single UE and are terminated in another single UE.

Combinational Session: this is the name given to the service in which an ongoing IMS session between two users is enriched by adding a circuit switched based call. The individual service instances that form the combinational session are originated in a single UE and terminated in another single UE.

CSICS capable UE: UE that supports Combinational Service.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CSICS Circuit Switched IMS Combinational Service

4 Introduction to Combinational Service

- Combinational services are applicable to both UTRAN and GERAN.
- The service shall enable the unidirectional exchange of PS data within the context of an IMS session

- The service shall enable the bi-directional (simultaneous send receive) exchange of PS data within the context of a IMS session.
- The communication between user A and user B and the related charging shall continue even if a component drops

A specific subscription for combinational services is not foreseen as being necessary.

- The preconditions for a combinational service are
 - Users A and B have valid subscriptions for voice calls as well as for accessing the IMS
- The service shall enable the communication:
 - between a user (A) using a UE with CSICS capability and a user (B) using a UE with CSICS capability within the same PLMN and different PLMNs;
 - between users camping on different RATs
- An IMS capable UE that also supports CS service should also be CSICS capable.
- The service has to be available when roaming.
- Interoperability between CSICS capable UE and IMS Core/Application server needs to be guaranteed

According to different UE implementations, it is expected that the following two service modes will exist in regards to IMS registration:

- 1) IMS pre established state: the CSICS capable UE performs the IMS registration at switch on.
- 2) IMS on demand state: the CSICS capable UE performs the IMS registration:
 - to start the communication, or
 - to add a IMS component to an existing CS call.

Interoperability between UEs that implement such different approaches shall be enabled.

It shall be possible to successfully invite a user to join an IMS session whether the invited UE is IMS registered or not. The invited user shall be able to accept/refuse the IMS Registration request.

5 User experience of combinational services

The existing address context is reused when the combined service is established. There is no need for the user to “redial”, which makes the combined service simple to invoke for the user.

When one of the participating users terminates the CS call of a combinational service, the IMS session may continue.

When one of the participating users terminates the IMS component of a combinational service, the CS call may continue.

When the user A sends a multimedia content to a user B, the user B can accept or reject the multimedia content (confirmation from the receiving party is needed) and vice versa.

It shall be possible to initiate a combinational service with a CS call and to add an IMS/PS session later.

It shall be possible to initiate a combinational service with an IMS/PS session and to add a CS call later

6 Service Capability Detection

The Service Capability Detection may indicate to the user that the UEs have interoperable CSICS capability and that the network(s) the users are attached to have the necessary network functionality to carry the combinational service.

- Before or during the combined service establishment between user A and user B the recipient (user B) UE capabilities may need to be checked
- The detection of the capabilities of the recipient terminal shall ensure that information is updated in case of change of terminal
- The (CSICS capable) UEs should have the information, prior to initiating a combinational service, regarding the type of capabilities, e.g. in terms of MMS classes, which are jointly supported by both UEs.
- An operator should have the mechanism to inhibit the capability check, or at least indicate to UE that it should not be performed.

7 Impacts on IP Multimedia and Supplementary Services

7.1 Supplementary services during a combinational call

The following supplementary services should be provided. The expected behaviour of the IMS session forming the combinational call is also described:

- Call hold: when the user decides to place the circuit switched call on hold, the user should be able to decide whether the IMS session of the combinational service should be suspended. If the IMS session has been suspended it may be resumed once the circuit switched call is resumed.
- Call waiting: the user should be able to receive an indication and provided with the option to switch between one call and the new incoming call. The IMS session should continue during the alerting of the subscriber and the user may decide to put the IMS session on hold when switching to the new CS.
- Call forwarding unconditional, on subscriber busy, on no reply, on not reachable: it should be possible to add IMS components to a CS call that has been forwarded, subject to the capability of such recipient.
- BAIC, BOIC, BAOC, BOIC-exHC, BIC-Roam: All the barring supplementary services should remain applicable.
- Calling line identity presentation: Existing rules apply to both CS and IMS components independently.
- Calling line identity restriction: Existing rules apply to both CS and IMS session independently, even if this results in the called party being unable to establish a combinational service.
- Connected line identity presentation: Existing rules apply to both CS and IMS components independently.
- Connected line identity restriction: Existing rules apply to both CS and IMS session independently, even if this results in the called party being unable to establish a combinational service.

7.2 Service behaviour during a Combinational Session

There is no standardised supplementary service defined for IMS session, however mechanisms exist (service capabilities) to emulate the behaviour of some of the most common supplementary services that exist in the circuit switched domain. The intention in this section is NOT to define "supplementary services" for IMS, just to explain the service behaviour during a combinational session for some specific cases as indicated below:

- IMS session hold: the user may decide to place the IMS session on hold, e.g. due to the wish of using the data capabilities of the UE for other purposes, or to initiate a different service. When this service is invoked the user should be able to decide whether the CS call of the combinational service should also be put on hold.
- IMS session waiting: The user should be able to receive an alert of an incoming IMS session (not part of the active combinational service) towards his UE. Subject to the capability of the UE, the user should be provided with the option to switch between the ongoing session and the new incoming one, or accept the new one in parallel with the existing one. The CS call of the combinational service should continue during the alerting of the subscriber and the user may decide to put the CS call on hold when switching to the new IMS session.

- IMS session redirect: It should be possible to add CS call to a redirected IMS session, subject to the capability of the recipient.
- Identity presentation: Existing rules apply to both CS and IMS components independently.
- Identity restriction: Existing rules apply to both CS and IMS components independently, even if this results in the called party being unable to establish a combinational session.

7.3 Support of teleservices during a combinational call

It should be possible to receive an SMS while engaged in a combinational call.

8 Charging aspects for Combinational Service

As a requirement for Phase 1 of combinational services, it must be possible to charge as follows:

- Each media component is a chargeable event on it's own also when roaming, which can e.g. be charged to the party originating the media. The principles of such charging are outlined in TS 22.115 [1] section 4.3.1., except for the charging option "charge for individual components of sessions even if there is no identifiable service".
- To provide charging information of CS call and IMS session for correlation purposes in order to allow off-line charging.
- To continue producing charging information for any remaining multimedia components or the CS call, when a multimedia component or the CS call drops during the communication between the two parties.

As a requirement for Phase 2 of combinational services, it must be possible to charge as follows:

Correlation between the charged media components and CS call should be possible to perform by the home operator in order to introduce dedicated charging schemes, e.g. discounts. This applies to on-line charging as well as off-line charging.

9 Suggested high-level Requirements

Considering the urgent need for advanced multimedia mobile applications, the specification of the *Combining CS calls and IMS sessions* is separated into Phase1 and Phase2:

Requirements for Phase 1: These requirements show the basic needs for *Combining CS calls and IMS sessions*. They shall introduce the required capabilities as simple as possible, i.e. meaning without major changes to the current set of specifications or networks, while keeping the time aspect in mind. They shall also describe the required features that will allow deploying Combinational Services across operator domains, i.e. operator interoperability and roaming.

Requirements for Phase 2: These requirements show the additional needs for Combining CS calls and IMS sessions. They shall introduce more advanced features that can enhance the combinational services.

9.1 Suggested requirements for phase 1

It shall be possible to add an IMS session to a CS speech call, thereby creating a combinational call.

An IMS capable UE that also supports CS service should also be CSICS capable.

The service shall enable the communication between a user (A) using a UE with CSICS capability and a user (B) using a UE with CSICS capability.

The (CSICS capable) UEs should have the information, prior to initiating a combinational service, regarding the type of capabilities, e.g. in terms of MMS classes, which are jointly supported by both UEs.

The detection of the capabilities of the recipient terminal shall ensure that information is updated in case of change of terminal.

An operator should have the mechanism to inhibit the capability check, or at least indicate to UE that it should not be performed.

It shall be possible to request establishment of the IMS session whether the invited UE is IMS registered or not.

Interoperability between CSICS capable UE and IMS Core/Application server needs to be guaranteed.

When the user A sends a multimedia content to a user B, the user B can accept or reject the multimedia content (confirmation from the receiving party is needed) and vice versa.

A combinational call shall enable both unidirectional and bi-directional exchange of PS data within the context of the IMS session.

Call hold: when the user decides to place the circuit switched call on hold, the user should be able to decide whether the IMS session of the combinational service should be suspended. If the IMS session has been suspended it may be resumed once the circuit switched call is resumed

Call waiting: the user should be able to receive an indication and provided with the option to switch between one call and the new incoming call. The IMS session should continue during the alerting of the subscriber and the user may decide to put the IMS session on hold when switching to the new CS.

Calling line identity restriction: Existing rules apply to both CS and IMS session independently, even if this results in the called party being unable to establish a combinational service.

Connected line identity restriction: Existing rules apply to both CS and IMS session independently, even if this results in the called party being unable to establish a combinational service.

Call forwarding unconditional, on subscriber busy, on no reply, on not reachable: it should be possible to add IMS components to a CS call that has been forwarded, subject to the capability of such recipient.

Note: The above requirement will be reviewed by SA1 in case it would delay specification of phase 1.

It shall be possible to receive an SMS while engaged in a combinational call.

It shall be possible to charge any ongoing media component(s) of the combinational call according to TS 22.115 [1] section 4.3.1, except for the charging option "charge for individual components of sessions even if there is no identifiable service".

It shall also be possible to provide charging information on the CS call and IMS session for correlation purposes in order to allow off-line charging.

The charging information shall continue to be produced for any remaining multimedia components or the CS call when a multimedia component or the CS call drops during the communication between the two parties.

It shall be possible to establish a combinational call between two users within the same PLMN or within different PLMNs.

It shall be possible to establish a combinational call between two users camped on identical or different RATs.

It shall be possible to establish a combinational call when roaming, assuming the visited operator supports GPRS roaming.

9.2 Suggested requirements for phase2

The following service requirements have been identified:

It shall be possible to add a CS speech call to an IMS session, thereby creating a combinational service.

The home operator shall be able to correlate charged media components and CS call in order to introduce dedicated charging schemes, e.g. discounts. This applies to on-line charging as well as off-line charging.

All the requirements in section 7.2 apply for phase 2.

10 Conclusions and Recommendations

Phase 1 requirements are intended for operator's initial service offer.

In Phase 1 a minimum of network support should be needed to accomplish service capability detection. This will allow the capability detection to work in e.g. roaming scenarios, although operators in general may not have introduced support for CSICS. However, if terminal complexity is overly increased by this recommendation, then SA1 will review it.

Phase 2 requirements are intended for providing more advanced features, e.g. online charging and correlated charging between the CSICS elements.

Both Phase1 and Phase 2 requirements are intended for Rel-7 timeframe.

Annex A (Informative): “Use cases”

A.1 Enriching Communications

This category captures those combinational services where an ongoing communication is enriched.

A.1.1 Enriched call session with multimedia

Description:

The “enriched call session with multimedia” service enables a user participating in a mobile-to-mobile Circuit Switched (CS) conversation with another user to take a picture/video with the inbuilt camera in the mobile and transmit the picture to the other party during this conversation. Either party in the conversation may initiate a picture/video transmission to the other party.

Procedures:

- **Discover service authorization**
At power on the UE performs a discovery of the service capability. The purpose of the discovery is for the UE to verify that the user is authorized by the IMS system to use this service.
- **Discover Service capability**
This may be initiated from a UE that is involved in a CS call that has reached an active state. The purpose of this step is to allow a UE to discover the capabilities of the remote terminal.
- **Establish message session**
A message session has to be established before an image transfer can take place. The UE that has taken the picture initiates setting up the message session.
- **Transfer message**
This is performed when one of the users involved in a CS call, initiates the sending of multimedia content (e.g. image, clips or video) to the other user, using the message session established prior to the image transfer.
- **Release message session**
This is to allow the release of a message session.

User Scenario:

Alice registers her SIP contact to the IMS system and indicates her subscription to the “enriched call session with multimedia” service. Right after her registration the UE will send a request to the network to authorize the service. The IMS system validates the service subscription and sends a response to the UE.

Alice establishes a call with Bob and starts talking with Bob. While the conversation is established, Alice’s UEs will attempt to discover the Service capabilities of Bob’s UE in the background of the ongoing call. Alice’s UE will contact an ENUM server that translate Bob’s E.164 number into Bob’s SIP address. Alice’s UE will send discover Service capability request to Bob’s UE. Bob’s UE responds to this message indicating that it is also subscribed to the “enriched call session with multimedia” service. The “discover Service capability” function will also be initiated from Bob’s UE.

After the discovery of the Service capability the UEs are ready to share any multimedia content with the other UEs. This will be displayed to the users via the UE display.

Scenario A (session initiated by Alice):

While discussing with Bob, Alice notes a beautiful sports car on the road that is Bob’s favorite. She takes a picture of the car and sends it to Bob. Alice’s UE will send a message to Bob’s UE and request to initiate a “enriched call session with multimedia” service with Bob. An icon is highlighted on Bob’s UE for Bob to accept or reject the

invitation to the service. Once Bob accepts the service request, Bob's UE responds to Alice's UE that the service is accepted by Bob and the message session is established between the UEs.

Alice will be offered a menu on her UE to send the picture of the sport car to Bob (knowing that this will mean that the content will be delivered to Bob's terminal) and initiate the sending of the picture. Alice starts to talk about the sports car with Bob and enjoys a very nice continuation of her conversation with Bob.

After termination of the CS call Alice's UE will immediately release the message session.

Any party may release the message session at any time during the CS call.

Scenario B (session initiated by Bob):

While talking Bob suddenly notices Alice's favorite film star acting within a movie clip on the film festival of Cannes and Bob obtains the trailer of this movie clip to his mobile. During the call, Bob's UE requests an enriched call session with multimedia, Alice accepts the enriched call session request, and an icon on Bob's UE will be highlighted. Bob notes the activation of the "enrichment" icon and sends the video clip towards the Alice's UE. Bob and Alice starts to talk about this video clip and Alice asks Bob to request the movie stand for more video clips.

After termination of the CS call Bob's UE will immediately release the message session.

Any party may release the message session at any time during the CS call.

A.1.2 Voice enhanced chatting

Description:

A user is engaged within a multi party chat session and notes that his buddy is entering the chat session as well. To gain a level of privacy on his conversation with his buddy, the user establishes a CS voice session with his buddy. During the CS voice session, both users are still engaged in the chat service exchange messages with the other chat users.

Annex B: Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2004-06					Draft skeleton		0.0.0
2004-07					Output from SA1 #25 Montreal	0.0.0	0.1.0
2004-08					Output from SA1 SWG Vienna (S1-040800)	0.1.0	0.2.0
2004-10					Editorial modifications of Tdoc.800	0.2.0	0.2.1
2004-10					Output from first day's SWG in Sophia Antipolis (SA1#26)	0.2.1	0.3.0
2004-10					Output from second day's SWG SA1#26	0.3.0	0.4.0
2004-10					Revised based on comments received at SA1#26 plenary	0.4.0	0.4.1
2004-12					Version 1.0.0 created for presentation to SA #26	0.4.1	1.0.0