
Source: SA WG3
Title: 2 CRs to 33.107: Reporting of Secondary PDP context (R99, Rel-4)
Document for: Approval
Agenda Item: 7.3.3

Spec	CR	Rev	Phase	Cat	Subject	Version-Current	Version-New	Doc-2nd-Level
33.107	007	1	R99	F	Reporting of Secondary PDP context	3.2.0	3.3.0	S3-010371
33.107	008	1	Rel-4	A	Reporting of Secondary PDP context	4.0.0	4.1.0	S3-010372

CR-Form-v3

CHANGE REQUEST

⌘ **33.107 CR 007** ⌘ rev **1** ⌘ Current version: **3.2.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ Reporting of Secondary PDP context		
Source:	⌘ SA WG3		
Work item code:	⌘ Security	Date:	⌘ June 7, 2001
Category:	⌘ F	Release:	⌘ R99
Use <u>one</u> of the following categories: F (essential correction) A (corresponds to a correction in an earlier release) B (Addition of feature), C (Functional modification of feature) D (Editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900.		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) REL-4 (Release 4) REL-5 (Release 5)	

Reason for change:	⌘ Ambiguity related to reporting of secondary PDP context		
Summary of change:	⌘ Clarify that secondary PDP context is to be reported.		
Consequences if not approved:	⌘ Ambiguity remains		

Clauses affected:	⌘ 7.4.3 and 7.4.5		
Other specs affected:	⌘ <input type="checkbox"/> Other core specifications <input type="checkbox"/> Test specifications <input type="checkbox"/> O&M Specifications	⌘	
Other comments:	⌘		

****** FIRST MODIFIED SECTION ******

7.4.3 Packet Data PDP context activation

For primary PDP context activation and for secondary PDP context activation a PDP context activation-event is generated. When a PDP context activation is generated from the mobile to 3G GSN this event is generated. These fields will be delivered to the DF2P if available:

Observed MSISDN
Observed IMSI
Observed IMEI
PDP address of observed party
Event Type
Event Time
Event Date
Correlation number
Access Point Name
PDP Type
Routing area code
Failed context activation reason
IAs (if applicable)

NOTE: Each primary and secondary PDP context uses a unique Correlation number.

****** SECOND MODIFIED SECTION ******

7.4.5 Packet Data PDP context deactivation

At PDP context deactivation of a primary PDP context and at deactivation of a secondary PDP context a PDP context deactivation-event is generated. These fields will be delivered to the DF2P if available:

Observed MSISDN
Observed IMSI
Observed IMEI
PDP address of observed party
Event Type
Event Time
Event Date
Correlation number
Access point name
Routing area code
IAs (if applicable)

CR-Form-v3

CHANGE REQUEST

⌘ **33.107 CR 008** ⌘ rev **1** ⌘ Current version: **4.0.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ Reporting of Secondary PDP context		
Source:	⌘ SA WG3		
Work item code:	⌘ SEC1-LI	Date:	⌘ June 7, 2001
Category:	⌘ A	Release:	⌘ REL-4
Use <u>one</u> of the following categories: F (essential correction) A (corresponds to a correction in an earlier release) B (Addition of feature), C (Functional modification of feature) D (Editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900.		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) REL-4 (Release 4) REL-5 (Release 5)	

Reason for change:	⌘ Ambiguity related to reporting of secondary PDP context		
Summary of change:	⌘ Clarify that secondary PDP context is to be reported.		
Consequences if not approved:	⌘ Ambiguity remains		

Clauses affected:	⌘ 7.4.3 and 7.4.5		
Other specs affected:	⌘ <input type="checkbox"/> Other core specifications <input type="checkbox"/> Test specifications <input type="checkbox"/> O&M Specifications	⌘	
Other comments:	⌘		

****** FIRST MODIFIED SECTION ******

7.4.3 Packet Data PDP context activation

For primary PDP context activation and for secondary PDP context activation a PDP context activation-event is generated. When a PDP context activation is generated from the mobile to 3G GSN this event is generated. These fields will be delivered to the DF2 if available:

Observed MSISDN
Observed IMSI
Observed IMEI
PDP address of observed party
Event Type
Event Time
Event Date
Correlation number
Access Point Name
PDP Type
Network Element Identifier
Location Information
Failed context activation reason
IAs (if applicable)

NOTE: Each primary and secondary PDP context uses a unique Correlation number.

****** SECOND MODIFIED SECTION ******

7.4.5 Packet Data PDP context deactivation

At PDP context deactivation of a primary PDP context and at deactivation of a secondary PDP context a PDP context deactivation-event is generated. These fields will be delivered to the DF2 if available:

Observed MSISDN
Observed IMSI
Observed IMEI
PDP address of observed party
Event Type
Event Time
Event Date
Correlation number
Access point name
Network Element Identifier
Location Information
IAs (if applicable)

At PDP context deactivation a PDP context deactivation-event is generated. These fields will be delivered to the DF2 if available:

Observed MSISDN
Observed IMSI
Observed IMEI
PDP address of observed party
Event Type
Event Time
Event Date
Correlation number
Access point name
Network Element Identifier
Location Information
IAs (if applicable)