

**Technical Specification Group, Radio Access Network
Meeting #4, Miami, 17-19 June 1999**

TSGR#4(99)316

Source: RAN WG2

Title: TR 25.922 "RRM Strategies"

Document for:

Agenda Item: 7

3G TR 25.922 V0.2.0 (1999-06)

Technical Report

**3rd Generation Partnership Project;
Technical Specification Group RAN;
Working Group 2 (WG2)
Radio Resource Management Strategies
(3G TR 25.922 version 0.2.0)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organisational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organisational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organisational Partners' Publications Offices.

Reference

DTS/TSG<name abbrev>-0<WG no><spec no> U

Keywords

<keyword[, keyword]>

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Contents

Foreword.....	6
1 Scope.....	7
2 References	7
3 Definitions, symbols and abbreviations.....	7
3.1 Definitions	7
3.2 Symbols	7
3.3 Abbreviations.....	7
4 General Description of Radio Resource Management	9
5 Idle Mode Tasks	10
5.1 Overview.....	10
5.2 Service type in Idle mode	10
5.3 Criteria for Cell Selection and Reselection	10
5.4 Cell Selection Monitoring Frequency or Cell Set.....	10
5.5 Cell Re-Selection Monitoring Frequency or Cell Set.....	10
5.5 Broadcast information receiving.....	10
6 RRC Connection Mobility.....	10
6.1 General Description of Connected Mode.....	10
6.1.1 Handover.....	10
6.1.1.1 Strategy.....	10
6.1.1.2 Causes.....	11
6.1.1.3 Cell Set for the Handover Preparation.....	11
6.1.1.4 Hard Handover	11
6.1.1.4.1 Hard Handover (FDD and TDD Hard)	11
6.1.1.5 Soft Handover.....	11
6.1.1.6 Inter System Handover	13
6.1.1.6.1 Handover 3G to 2G.....	13
6.1.2 Radio Link Management	14
7 Admission Control.....	14
7.1 Overall strategies	14
7.2 Scenarios.....	15
7.2.1 CAC performed in SRNS	15
7.2.2 CAC performed in DRNC.....	15
7.2.2.1 Case of DCH.....	16
7.2.2.2 Case of Common Transport Channels	16
8 Radio Access Bearer Control	17
8.1 Radio Access Bearer Control – Overview of Procedures	17
8.2 Usage of RAB control procedures	17
8.2.1 Examples of Radio Access Bearer Setup	17
8.2.2 Examples of Physical Channel Reconfiguration.....	18
8.2.2.1 Increased UL data, with switch from RACH/FACH to DCH/DCH.....	18
8.2.2.2 Increased DL data, no Transport channel type switching	18
8.2.2.3 Decrease DL data, no Transport channel type switching	19
8.2.2.4 Decreased UL data, with switch from DCH/DCH to RACH/FACH	19
8.2.3 Examples of Transport Channel Reconfiguration	20
8.2.3.1 Increased UL data, with no transport channel type switching.....	20
8.2.3.2 Decreased DL data, with switch from DCH/DCH to RACH/FACH	20
8.2.4 Examples of RAB and Signalling link Reconfiguration	21
9 Dynamic Channel Allocation	22
9.1 DCA (FDD)	22
9.2 DCA (TDD).....	22
9.2.1 Channel Allocation.....	22

9.2.1.1	Resource allocation to cells (slow DCA).....	22
9.2.1.2	Resource allocation to bearer services (fast DCA).....	22
9.2.2	Measurements Reports from UE to the UTRAN.....	23
10	Power Management	24
10.1	Variable Rate Packet Transmission	24
10.1.1	Downlink Power Management	24
10.1.2	Uplink Power Management.....	24
11	Radio Link Surveillance	24
12	Appendix A - (Simulations on Fast Dynamic Channel Allocation).....	25
12.1	Simulation environment.....	25
12.2	Results	25
12.2.1	Macro UDD 144	25
12.2.2	Micro UDD 384	26
12.2.2.1	Code rate 1	26
12.2.2	Code rate 2/3	26
12.3	Conclusions.....	27
13	Appendix B (Radio Access Bearer Control – Overview of Procedures: message exchange and parameters used).....	27
13.1	Examples of Radio Access Bearer Setup.....	27
13.1.1	RRC Parameters in RAB Setup.....	27
13.1.2	RRC Parameters in RAB Setup Complete.....	27
13.2	Examples of Physical Channel Reconfiguration	28
13.2.1	Increased UL data, with switch from RACH/FACH to DCH/DCH	28
13.2.1.1	RRC Parameters in Measurement Report.....	28
13.2.1.2	RRC Parameters in Physical Channel Reconfiguration	28
13.2.1.3	RRC Parameters in Physical Channel Reconfiguration Complete	28
13.2.2	Increased DL data, no Transport channel type switching.....	29
13.2.2.1	RRC Parameters in Physical Channel Reconfiguration	29
13.2.2.2	RRC Parameters in Physical Channel Reconfiguration Complete.....	29
13.2.3	Decrease DL data, no Transport channel type switching	29
13.2.3.1	RRC Parameters in Physical Channel Reconfiguration	29
13.2.3.2	RRC Parameters in Physical Channel Reconfiguration Complete	29
13.2.4	Decreased UL data, with switch from DCH/DCH to RACH/FACH.....	30
13.2.4.1	RRC Parameters in Physical Channel Reconfiguration	30
13.2.4.2	RRC Parameters in Physical Channel Reconfiguration Complete.....	30
13.3	Examples of Transport Channel Reconfiguration	30
13.3.1	Increased UL data, with no transport channel type switching	30
13.3.1.1	RRC Parameters in Measurement Report.....	31
13.3.1.2	RRC Parameters in Transport Channel Reconfiguration	31
13.3.1.3	RRC Parameters in Transport Channel Reconfiguration Complete.....	31
13.3.2	Decreased DL data, with switch from DCH/DCH to RACH/FACH.....	31
13.3.2.1	RRC Parameters in Transport Channel Reconfiguration	32
13.3.2.2	RRC Parameters in Transport Channel Reconfiguration Complete.....	32
13.4	Examples of RAB and Signalling link Reconfiguration.....	32
13.4.1	RRC Parameters in Radio access bearer reconfiguration.....	32
13.4.2	RRC Parameters in Radio access bearer reconfiguration Complete.....	32
14	History	32

Foreword

This Technical Specification has been produced by the 3GPP.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of this TS, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows;

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 Indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the specification;

1 Scope

The present document shall describe RRM strategies supported by UTRAN specifications and typical algorithms.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

[1] 3GPP Homepage: www.3gpp.org

[2] TS25.301, Radio Interface Protocol Architecture

[3] TS25.302, Layer 1; General requirements

[4] TS25.303, UE States and Procedures in Connected Mode

[5] TS25.304, Description of procedures in idle Mode

[6] TS25.322, Description of RLC protocol

[7] TS25.331, Description of RRC protocol

[8] TS25.391, Description of principles for error handling and message description

[9] ETSI UMTS 25.XX: "Vocabulary for the UTRAN"

[10] S25.231, Physical layer Measurements

3 Definitions, symbols and abbreviations

3.1 Definitions

See [9] for a definition of fundamental concepts and vocabulary.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ARQ Automatic Repeat Request

BCCH Broadcast Control Channel

BCH Broadcast Channel

C- Control-

CC Call Control

CCCH Common Control Channel

CCH	Control Channel
CCTrCH	Coded Composite Transport Channel
CN	Core Network
CRC	Cyclic Redundancy Check
DC	Dedicated Control (SAP)
DCA	Dynamic Channel Allocation
DCCH	Dedicated Control Channel
DCH	Dedicated Channel
DL	Downlink
DRNC	Drift Radio Network Controller
DSCH	Downlink Shared Channel
DTCH	Dedicated Traffic Channel
FACH	Forward Link Access Channel
FAUSCH	Fast Uplink Signalling Channel
FCS	Frame Check Sequence
FDD	Frequency Division Duplex
GC	General Control (SAP)
HO	Handover
ITU	International Telecommunication Union
kbps	kilo-bits per second
L1	Layer 1 (physical layer)
L2	Layer 2 (data link layer)
L3	Layer 3 (network layer)
LAC	Link Access Control
LAI	Location Area Identity
MAC	Medium Access Control
MM	Mobility Management
Nt	Notification (SAP)
OCCCH	ODMA Common Control Channel
ODCCH	ODMA Dedicated Control Channel
ODCH	ODMA Dedicated Channel
ODMA	Opportunity Driven Multiple Access
ORACH	ODMA Random Access Channel
ODTCH	ODMA Dedicated Traffic Channel

PCCH	Paging Control Channel
PCH	Paging Channel
PDU	Protocol Data Unit
PHY	Physical layer
PhyCH	Physical Channels
RACH	Random Access Channel
RLC	Radio Link Control
RNC	Radio Network Controller
RNS	Radio Network Subsystem
RNTI	Radio Network Temporary Identity
RRC	Radio Resource Control
SAP	Service Access Point
SCCH	Synchronization Control Channel
SCH	Synchronization Channel
SDU	Service Data Unit
SRNC	Serving Radio Network Controller
SRNS	Serving Radio Network Subsystem
TCH	Traffic Channel
TDD	Time Division Duplex
TFCI	Transport Format Combination Indicator
TFI	Transport Format Indicator
TMSI	Temporary Mobile Subscriber Identity
TPC	Transmit Power Control
U-	User-
UE	User Equipment
UE _R	User Equipment with ODMA relay operation enabled
UL	Uplink
UMTS	Universal Mobile Telecommunications System
URA	UTRAN Registration Area
UTRA	UMTS Terrestrial Radio Access
UTRAN	UMTS Terrestrial Radio Access Network

4 General Description of Radio Resource Management

5 Idle Mode Tasks

5.1 Overview

[A complete overview of idle mode tasks is contained in section 4.1 of S25.304. For the purpose of this recommendation some specific test will be developed.]

5.2 Service type in Idle mode

[In this section, the impact of service type on RRM strategies will be addressed, also based on section 4.3 of S25.304]

5.3 Criteria for Cell Selection and Reselection

5.4 Cell Selection Monitoring Frequency or Cell Set

5.5 Cell Re-Selection Monitoring Frequency or Cell Set

5.5 Broadcast information receiving

[In this section the possible uses of broadcast system information on RRM strategies will be addressed also based on section 6 of S25.304]

6 RRC Connection Mobility

6.1 General Description of Connected Mode

[The overall description of the connected mode is contained in section 4 of S25.303. For the purpose of this recommendation some specific test will be developed.]

6.1.1 Handover

6.1.1.1 Strategy

The handover strategy employed by the network for radio link control determines the handover decision that will be made based on the measurement results reported by the UE/RNC and various parameters set for each cell. Network directed handover might also occur for reasons other than radio link control, e.g. to control traffic distribution between cells. The network operator will determine the exact handover strategies.. Possible types of Handover are as follows:

- Handover 3G -3G:
- FDD soft/softer handover;
- FDD inter-frequency hard handover;
- FDD/TDD Handover;
- TDD/FDD Handover;
- TDD/TDD Handover;
- Handover 3G - 2G:
- Handover to GSM

6.1.1.2 Causes

The following is a non-exhaustive list for causes for the initiation of a handover process.

- Uplink quality
- Uplink signal strength
- Downlink quality
- Downlink signal strength
- Distance
- Change of service
- Better cell
- O&M intervention
- Directed retry
- Traffic
- Pre-emption

6.1.1.3 Cell Set for the Handover Preparation

6.1.1.4 Hard Handover

6.1.1.4.1 Hard Handover (FDD and TDD Hard)

[Test to be deployed also based on section 7.3.7 of S25.303]

6.1.1.5 Soft Handover

The serving cell (s) (the cells in the active set) are expected to have knowledge of the service used by the UE. The new cell decided to be added to the active set shall be informed that a new connection is desired, and it needs to have the following minimum information forwarded to it via UTRAN.

- Maximum data rate of the connection and other service parameters, such as coding schemes, number of parallel code channels etc. parameters which form the set of parameters describing the different transport channel configurations in use both uplink and downlink.
- The UE ID and uplink scrambling code
- The relative timing information of the new cell, in respect to the timing UE is experiencing from the existing connections (as measured by the UE at its location). Based on this the new cell can determine what should be the timing of the transmission initiated in respect to the timing of the common channels (BCCH) of the new cell.

As a response the UE needs to know via the existing connections:

- From which frame (assuming active set update accepted) does the new cell initiate the transmission to the UE
- What channelisation code(s) are used for that transmission. The channelisation codes from different cells are not required to be the same as they are under different scrambling code anyway.
- The relative timing information, which needs to be made available at the new cell is indicated in Figure 1 (shows the case where the two involved cells are managed by different Node Bs).




Figure 1. Making transmissions capable to be combined in the Rake receiver from timing point of view.

At the start of diversity handover, the reverse link dedicated physical channel transmitted by the MS, and the forward link dedicated physical channel transmitted by the diversity handover source BTS will have their radio frame number and scrambling code phase counted up continuously as usual, and they will not change at all. Naturally, the continuity of the user information mounted on them will also be guaranteed, and will not cause any interruption.

[Editor's Note: it is F.F.S if the following parts on synchronization are relevant for TR 25.922]

<Editor's note : text from ARIB, volume 3>

The synchronization timing upon starting diversity handover are presented in Fig. 3.2.5-4. The synchronisation establishment flow upon intra/inter-cell diversity handover is described in Fig. 3.2.6-4.

The MS measures the frame time difference of the radio frame at the same frame number between the reverse link dedicated physical channel and the perch channel transmitted at the handover destination BTS. These measurements shall be notified to the network. The measured value is the time difference of the frame timing of the reverse link dedicated physical channel against the frame timing of the perch channel. The values shall always be positive values in chip units, and the range shall be 0 ~ "reverse link scrambling code cycle-1" chip.

The MS notifies the frame time difference measurement values as layer 3 signals to the BSC via the diversity handover source BTS with the DCH of the reverse link dedicated physical channel.

The BSC notifies the frame time difference measurement result, together with the frame offset and slot offset set up upon originating/ terminating call connection, to the diversity handover destination BTS with layer 3 signals. Furthermore, the BSC notifies radio parameters such as the spreading codes used at the handover destination BTS etc., to the MS via the handover source BTS.

The MS starts the chip synchronisation establishment process of forward link channel from the handover destination BTS with the notified radio parameters. The reverse link channels being transmitted shall continue transmission without any operations performed.

The handover destination BTS receives the notification of the above frame time difference frame offset, and slot offset. Utilising these informations, the BTS starts the transmission of forward link dedicated physical channels and starts the synchronization establishment process of reverse link dedicated physical channel transmitted by the MS. See chapter 3.2.5.1 for the specific transmission timing of forward link dedicated physical channels, and the reception timing of reverse link dedicated physical channel. As soon as chip synchronisation and frame synchronisation using Frame Synchronization Word are established, hard wired transmission shall be started.

Based on the handover destination perch channel reception timing, the MS establishes chip synchronisation of forward link channel from handover destination BTS. As soon as chip synchronisation is established, maximal ratio combining with the forward link channel from handover source BTS shall be started.




Figure 2 Synchronisation Establishment Flow Upon Intra/Inter-cell Diversity Handover

6.1.1.6 Inter System Handover

6.1.1.6.1 Handover 3G to 2G

The handover between UTRA and GSM system offering world-wide coverage already today has been one of the main design criteria taken into account in the UTRA frame timing definition. The GSM compatible multi-frame structure, with the super-frame being multiple of 120 ms, allows similar timing for inter-system measurements as in the GSM system itself. The compatibility in timing is important, that when operating in UTRA mode, a multi-mode UE is able to catch the desired information from the synchronization bursts in the synchronization frame on a GSM carrier with the aid of the frequency correction burst. This way the relative timing between a GSM and UTRA carriers is maintained similar to the timing between two asynchronous GSM carriers.

UTRA/FDD-GSM dual mode UEs can be implemented without simultaneous use of two receiver chains. Although the frame length is different from GSM frame length, the GSM traffic channel and UTRA FDD channels use similar 120 ms multi-frame structure. Similar timing can be naturally done with UTRA TDD mode as well.

A UE can do the measurements by using idle periods in the downlink transmission, where such idle periods are created by using the downlink slotted mode as defined in reference [2]. In addition to downlink slotted frames for measurements, the UTRAN will provide uplink slotted frames to allow the UE to GSM cells on frequencies closed to the FDD uplink band. The slotted mode is under the control of the UTRAN, and the UTRAN should communicate to the UE which frame is slotted. .

Alternatively independent measurements not relying on the slotted mode, but using a dual receiver approach can be performed, where the GSM receiver branch can operate independently of the UTRA FDD receiver branch.

For smooth inter-operation between the systems, information needs to be exchanged between the systems, in order to allow the UTRAN to notify the UE of the existing GSM frequencies in the area (see section 6.1.1.2.1.4). Further more integrated operation is needed for the actual handover where the current service is maintained, taking naturally into account the lower data rate capabilities in GSM when compared to UTRA maximum data rates reaching all the way to 2 Mbits/s.

UTRA/TDD-GSM dual mode terminals can be implemented without simultaneous use of two receiver chains. Although the frame length is different from GSM frame length, the GSM traffic channel and UTRA TDD channels rely on similar 120 ms multi-frame structure.

A UE can do the measurements either by efficiently using idle slots or by requesting free continuous periods in the downlink part obtained by reducing the spreading factor and compressing in time TS occupation in a form similar to the FDD slotted mode. The low-cost constraint excludes the dual receiver approach.

For smooth inter-operation, inter-system information exchanges are needed in order to allow The UTRAN to notify the UE of the existing GSM frequencies in the area and vice versa. Further more integrated operation is needed for the actual handover where the current service is maintained, taking naturally into account the lower data rate capabilities in GSM when compared to UMTS maximum data rates reaching all the way to 2 Mbits/s.

Basic requirements to correctly perform a handover in GSM are described in GSM 05.08 "Radio subsystem link control".

6.1.2 Radio Link Management

[Test to be deployed also based on sections 7.3.4, 7.3.5, 7.3.6 of S25.303]

7 Admission Control

7.1 Overall strategies

Principle 1: Admission Control is performed according to the type of required QoS.

"Type of service" is to be understood as an implementation specific category derived from standardized QoS parameters.

The following table illustrates the concept :

Service	Domain	Transport Channel	Type of service	CAC performed
Voice	CS	DCH	Premium*	YES
	IP	DCH	Premium*	YES
Web	IP	DSCH	Assured Service**	YES
	IP	DSCH	Best Effort***	NO

* *Premium service:* Low delay, high priority.

* *Assured Service*: A minimum rate below the mean rate is guaranteed, service may use more bandwidth if available, medium priority.

* *Best Effort*: No guaranteed QoS, low priority.

Other mapping are possible like for instance:

PSTN domain: Premium service, IP domain: Best Effort.

Assumption: Admission Control is performed by CRNC under request from SRNC.

[Editor's note, other criteria/principles are FFS]

7.2 Scenarios

7.2.1 CAC performed in SRNS

Figure 3 is to be taken as an example. It describes the general scheme that involves Admission Control.




Figure 3: This model shows how standardized RANAP and RRC layers are involved in the CAC process. The dashed box represents a proprietary entity.

1. CN requests SRNC for establishing a RAB, indicating QoS parameters.
2. According to QoS parameters the requested service is assigned a type of service. CAC is performed according to the type of service.
3. Resources are allocated according to the result of CAC.
4. Acknowledgement is sent back to CN according to the result of CAC. Sub_layers are configured accordingly.

Steps 2 to 4 may also be triggered by SRNC for reconfiguration purpose within the SRNC (handovers intra-RNC, channels reconfigurations, location updates).

7.2.2 CAC performed in DRNC

As CAC is always performed in CRNC it occurs in DRNC when Iur is to be used (soft handover, Cell/URA Update). [Editor's note please clarify the content of this sentence]

7.2.2.1 Case of DCH




Figure 4: This model shows how standardized RNSAP and RRC layers are involved in the CAC process. The dashed box represents a proprietary entity.

1. SRNC requests DRNC for establishing a Radio Link, indicating DCH characteristics. These implicitly contains all QoS requirements and are enough as inputs to the CAC algorithm.
2. CAC is performed according to DCH characteristics.
3. Resources are allocated according to the result of CAC.
4. Acknowledgement is sent back to CN according to the result of CAC.

7.2.2.2 Case of Common Transport Channels

When transmitting packets on Common Transport Channels a UE may camp on a new cell managed by a new RNC. SRNC is notified by UE through RRC messages that connection will be set up through a new DRNC. Subsequently SRNC initiates connection through new DRNC.




Figure 5: This model shows how standardized RNSAP and RRC layers are involved in the CAC process. The dashed box represents a proprietary entity.

1. SRNC requests DRNC for establishing a Radio Link. A RNSAP message contains the QoS parameters and the type of Common Transport Channel to be used.
2. According to QoS parameters the requested service is assigned a type of service. CAC is performed according to the type of service and to the type of Common Transport Channel requested by SRNC.
3. Resources are allocated according to the result of CAC.

4. Acknowledgement is sent back to CN according to the result of CAC. L1 and MAC are configured accordingly by RRC layer.

The RNSAP procedure is to be handled if a certain QoS is required. It may be avoided if the service just needs Best Effort. The decision to trigger the RNSAP procedure is to be taken by SRNC.

8 Radio Access Bearer Control

8.1 Radio Access Bearer Control – Overview of Procedures

[Test to be deployed also based on section 6.1 of S25.303]

8.2 Usage of RAB control procedures

Radio access bearer control procedures are used to control the UE and system resources. This section explains how the system works with respect to these procedures and how e.g. traffic volume measurements could trigger these procedures.

First a Radio access bearer setup is shown, where pre-configuration of transport channels are exemplified. Further, the procedures Physical channel reconfiguration and Transport channel reconfiguration are shown in several examples. It is also explained how these last two procedures are used in the system for resource control of services with variable bitrate, i.e. transport channel type switching. Finally, usage of Radio access bearer reconfiguration is shown in an example where the MAC multiplexing is changed.

8.2.1 Examples of Radio Access Bearer Setup

In order to set up a new Radio access bearer a RRC connection must have been established, and some NAS negotiation has been performed. The Radio access bearer setup message comes from UTRAN and depending on the requirement of the service a common or a dedicated transport channel could be used. In the example below the UE is using a common transport channel for the RRC connection and stays on the common transport channel after the RAB setup.

However, transport channel parameters such as transport formats and transport format combinations are configured not only for the used common transport channel, but also for dedicated transport channel for future use.

All physical parameters are the same before and after the RAB setup in this example.




Figure 6 Configuration of L2 in the UTRAN DL before and after the RAB setup.

Detailed examples of messages exchange and parameters used is reported in Appendix B, Section. 13.1.

8.2.2 Examples of Physical Channel Reconfiguration

This RRC procedure is used to reconfigure the Physical channel and can by that also trigger Transport channel type switching.

Below several examples of Physical Channel reconfigurations are shown, triggered by different amount of UL or DL data.

8.2.2.1 Increased UL data, with switch from RACH/FACH to DCH/DCH

A UE that is in the RACH/FACH substate can transmit a small amount of user data using the common transport channels. For larger amounts it is more appropriate to use a dedicated transport channel. Since each UE doesn't know the total load situation in the system UTRAN decides if a UE should use common transport channels or a dedicated transport channel.

The monitoring of UL capacity need is handled by a UTRAN configured measurement in the UE. When the amount of data in the RLC buffer to be transmitted in the UL increases over a certain threshold the UE sends a measurement report to UTRAN. This threshold to trigger the report is normally given in System Information, but UTRAN can also control the threshold in a UE dedicated Measurement Control message.

Since, UTRAN has the current status of the total UL need it can decide which UEs that should be switched to a dedicated transport channel. If UTRAN has pre-configured the transport formats and transport format combinations to be used on the dedicated transport channel for the UE, a Physical channel reconfiguration procedure could be used to assign dedicated physical resources.

The spreading factor for the physical channels assigned then give, which transport format combinations that are allowed to use.




Figure 7 Configuration in the UTRAN UL before and after the Physical channel reconfiguration.

Detailed examples of messages exchange and parameters used is reported in Appendix B, Section. 13.2.1.

8.2.2.2 Increased DL data, no Transport channel type switching

If the RLC buffer increases above a certain threshold [Note: This is only one of many possible implementations of the network] in the network the UTRAN can do a physical channel reconfiguration. Here the UE uses a dedicated transport channel, and this procedure is used to decrease the spreading factor of the physical dedicated channel. This way this variable bitrate service increases the throughput on the downlink.

A variable bitrate service that has large traffic variations should have transport formats and transport format

combinations defined for lower spreading factors than currently used on the physical channel. Then after the physical channel reconfiguration that lowers the spreading factors these transport formats and transport format combinations could be used to increase the throughput for this user.

However, if the transport formats and transport format combinations have not been previously defined to support a lower spreading factor, a Transport channel reconfiguration must be used instead in order to get any increased throughput.

Only downlink physical parameters are changed here since the uplink in this scenario doesn't need to increase its capacity.

Detailed examples of messages exchange and parameters used is reported in Appendix B, Section. 13.2.2.

8.2.2.3 Decrease DL data, no Transport channel type switching

Since downlink channelization codes are a scarce resource a UE with a too high, allocated gross bit rate (low spreading factor) must be reconfigured and use a more appropriate channelization code (with higher spreading factor). This could be triggered by a threshold for the RLC buffer content and some inactivity timer, i.e. that the buffer content stays a certain time below this threshold. *[Note: This is only one of many possible implementations of the network].*

After the physical channel has been reconfigured, some of the transport formats and transport format combinations that require a low SF can not be used. However, these are stored and could be used if the physical channel is reconfigured later to use a lower spreading factor.

Detailed examples of messages exchange and parameters used is reported in Appendix B, Section. 13.2.3.

8.2.2.4 Decreased UL data, with switch from DCH/DCH to RACH/FACH

In the network the UE traffic can be evaluated and the network can observe which transport format combinations that are used in the UL. The network could also simply look at how much data the UE transmits or use measurement reports *[Note: Which way for the network to trigger this is a matter of implementation].*

If the UE is transmitting a low amount of data in the uplink and there is little traffic in the downlink, this could trigger a switch from a dedicated transport channel to a common transport channel. Depending on if the already defined RACH/FACH configuration is possible/preferred in the cell that the UE will be in after the switch, a Transport channel reconfiguration or a Physical channel reconfiguration procedure is used.

In the example below the UE has stayed in cells with a similar RACH and FACH configuration when using a dedicated transport channel. Therefore, the Physical channel reconfiguration procedure can be used. In 8.2.3.2 this is not the case and a Transport channel reconfiguration is used instead.

After the UE has performed the transport channel type switch to the RACH/FACH substate, all transport channel parameters such as transport formats for the dedicated transport channel are stored. The same configuration of the dedicated transport channels could then be reused if the UE switches back to the DCH/DCH substate.




Figure 8 Configuration in the UTRAN UL before and after the Physical channel reconfiguration.

Detailed examples of messages exchange and parameters used is reported in Appendix B, Section. 13.2.4.

8.2.3 Examples of Transport Channel Reconfiguration

This RRC procedure is used to reconfigure the transport channel and the physical channels, and can by that also trigger Transport channel type switching.

Below, several examples of Transport channel reconfiguration are shown, triggered by different amount of UL or DL data.

8.2.3.1 Increased UL data, with no transport channel type switching

When a UE RLC buffer content increases above a certain threshold, a measurement report is sent to UTRAN. Depending on the overall load situation in the network the UTRAN could decide to increase the uplink capacity for a UE. Since every UE has its "own" code tree, there is no shortage of UL codes with a low spreading factor, and all UEs can have a low spreading factor code allocated.

Therefore, instead of channelization code assignment as used in the DL, load control in the UL is handled by the allowed transport formats and transport format combinations for each UE. To increase the throughput for a UE in the uplink, UTRAN could send a Transport channel reconfiguration or a TFC Control message.

Here a Transport channel reconfiguration is used. Although, the TFC Control procedure is believed to require less signalling it can only restrict or remove restrictions of the assigned transport format combinations and that may not always be enough. If a reconfiguration of the actual transport formats or transport format combinations is required, the Transport channel reconfiguration procedure must be used instead.

In the example below, the UE is allowed to send more data in the UL when on dedicated transport channel, although the common transport channel configuration is still the same. To make use of the new transport format combinations the physical channel must also be reconfigured to allow a lower spreading factor.

Detailed examples of messages exchange and parameters used is reported in Appendix B, Section. 13.3.1.

8.2.3.2 Decreased DL data, with switch from DCH/DCH to RACH/FACH

In the network the downlink traffic to a UE can be evaluated and the network can observe which transport format combinations that are used [*Note: This is only one of many possible implementations of the network*].

If a low amount of data is sent to the UE in the downlink and there is little traffic in the uplink, this could trigger a switch from a dedicated transport channel to a common transport channel. Depending on if the already defined RACH/FACH configuration is possible/preferred in the cell that the UE will be connected to after the switch, a Transport channel reconfiguration or a Physical channel reconfiguration procedure is used. In this example the UE has moved to cells with a different FACH or RACH configuration when using a dedicated transport channel, so a Transport channel reconfiguration procedure must be used.

When the UE do the switch from a dedicated transport to a common transport channel the RACH and FACH transport channels are reconfigured with new transport formats if the old configuration is not supported in the new cell. What physical common channel to be used is pointed out in the physical channel parameters.




Figure 9 Configuration in the UTRAN DL before and after the Transport channel reconfiguration.

Detailed examples of messages exchange and parameters used is reported in Appendix B, Section. 13.3.2.

8.2.4 Examples of RAB and Signalling link Reconfiguration

A Radio access bearer reconfiguration is here used to change how the MUX in MAC of logical channels belonging to different RABs is configured.

The RAB Reconfiguration message includes parameters for the new multiplexing configuration in MAC, and a reconfiguration of the Transport channel that both RABs will use. The old obsolete transport channel is also removed (here DCH3 is removed). All other parameters associated with the RABs are unchanged.




Figure 10 Configuration in the UTRAN DL before and after the RAB reconfiguration.

Detailed examples of messages exchange and parameters used is reported in Appendix B, Section. 13.4.

9 Dynamic Channel Allocation

9.1 DCA (FDD)

9.2 DCA (TDD)

9.2.1 Channel Allocation

<not covered in ARIB TDD>

For the UTRA-TDD mode a physical channel is characterised by a combination of its carrier frequency, time slot, and spreading code as explained in the chapter on the physical channel structure

Channel allocation covers both :

- resource allocation to cells (slow DCA)

resource allocation to bearer services (fast DCA)

9.2.1.1 Resource allocation to cells (slow DCA)

<not covered in ARIB TDD>

Channel allocation to cells follows the rules below:

- A reuse one cluster is used in the frequency domain. In terms of an interference-free DCA strategy a timeslot-to-cell assignment is performed, resulting in a time slot clustering. A reuse one cluster in frequency domain does not need frequency planning. If there is more than one carrier available for a single operator also other frequency reuse patterns >1 are possible.
- Any specific time slot within the TDD frame is available either for uplink or downlink transmission . UL/DL resources allocation is thus able to adapt itself to time varying asymmetric traffic.
- In order to accommodate the traffic load in the various cells the assignment of the timeslots (both UL and DL) to the cells is dynamically (on a coarse time scale) rearranged (slow DCA) taking into account that strongly interfering cells use different timeslots. Thus resources allocated to adjacent cells may also overlap depending on the interference situation.
- Due to idle periods between successive received and transmitted bursts, UEs can provide the network with interference measurements in time slots different from the one currently used. The availability of such information enables the operator to implement the DCA algorithm suited to the network.
- For instance, the prioritized assignment of time slots based on interference measurements results in a clustering in the time domain and in parallel takes into account the demands on locally different traffic loads within the network.

9.2.1.2 Resource allocation to bearer services (fast DCA)

<not covered in ARIB TDD>

Fast channel allocation refers to the allocation of one or multiple physical channels to any bearer service Resource units (RUs) are acquired (and released) according to a cell-related preference list derived from the slow DCA scheme.

1. The following principles hold for fast channel allocation: The basic RU used for channel allocation is one code / timeslot / (frequency).
2. Multirate services are achieved by pooling of resource units. This can be made both in the code domain (pooling of multiple codes within one timeslot = **multicode** operation) and time domain (pooling of multiple timeslots within one frame = **multislot** operation). Additionally, any combination of both is possible. Simulation results reported in

Appendix A, recommend that the DCA prefers code pooling , over time slot pooling, for UDD packet data; the use of code pooling in fact results in lower number of unsatisfied users.

3. Since the maximal number of codes per time slot in UL/DL depends on several physical circumstances like , channel characteristics, environments, etc. (see description of physical layer) and whether additional techniques to further enhance capacity are applied (for example smart antennas),. the DCA algorithm has to be independent of this number. Additionally, time-hopping can be used to average inter-cell interference in case of low-medium bit rate users.
 - 4. Channel allocation differentiates between RT and NRT bearer services:
 - RT services: Channels remain allocated for the whole duration the bearer service is established . The allocated resources may change because of a channel reallocation procedure (e.g. VBR).
 - NRT services: Channels are allocated for the period of the transmission of a dedicated data packet only UDD channel allocation is performed using ‘best effort strategy’, i.e. resources available for NRT services are distributed to all admitted NRT services with pending transmission requests. The number of channels allocated for any NRT service is variable and depends at least on the number of current available resources and the number of NRT services attempting for packet transmission simultaneously. Additionally, prioritisation of admitted NRT services is possible.
5. Channel reallocation procedures (intra-cell handover) can be triggered for many reasons:
 - To cope with varying interference conditions.
 - In case of high rate RT services (i.e. services requiring multiple resource units) a ‘channel reshuffling procedure’ is required to prevent a fragmentation of the allocated codes over to many timeslots. This is achieved by freeing the least loaded timeslots (timeslots with minimum used codes) by performing a channel reallocation procedure.
 - When using smart antennas, channel reallocation is useful to keep spatially separated the different users in the same timeslot.

9.2.2 Measurements Reports from UE to the UTRAN

While in active mode the DCA needs measurements for the reshuffling procedure (intra-cell handover). The specification of the measurements to be performed is contained in Section 7.4 in [10]. In this section the relevant measurement reports are presented:

- Pathloss of a sub-set of cells (pathloss is quantized in N_{PL} [e.g. 128] intervals ; [max. number of cells is 30].
- Inter-cell interference measurements of all DL time slots requested by the UTRAN (interference is quantized in N_{ICI} [e.g. 32] intervals, due to asymmetry up to 14 time slots are possible)
- BER of serving link (quantized in N_{BER} [e.g. 16] intervals)
- Transmission power of the UE on serving link (separated in N_{TX} [e.g. 64] intervals)
- DTX flag link
- ffs

Further measurements and reports can be requested by the UTRAN.

The RLC informs the DCA about transmission errors. The interaction between DCA and RLC depends on the RLC operation mode. Details are for further study.

10 Power Management

10.1 Variable Rate Packet Transmission

10.1.1 Downlink Power Management

When the connection for packet services is established, the RRC considers the down-link traffic conditions, then assigns the TFCS to MAC and allowable transmission power to L1. The allowable transmission power is determined according to the service requirements and the traffic conditions, and is updated for each user when the traffic conditions change.

During a call, the physical layer averages the transmission power for that UE over one or several frames. If the averaged transmission power for the UE becomes higher than the allowable transmission power, that is, the channel conditions are bad, L1 indicates with the primitive MPHY-STATUS to the MAC that the "Allowable transmission power has been reached". The MAC in response reduces the data rate within TFCS, and the power control procedure then reduces the total transmission power for that UE and excess interference to other UEs is avoided.

When channel conditions improve and the averaged transmission power falls [x] dB below than the allowable transmission power the physical layer indicates with the primitive MPHY-STATUS to the MAC that the "Average transmission power is

below allowable transmission power by xdB" (the values for [x] are chosen to match the power requirements of different increments for the transport channels within the TFCS). The MAC in response increases the data rate by increasing the number of transport blocks delivered to L1 and the physical layer increases the total transmission power to the UE by the predefined amount. This allows data that was buffered during bad channel conditions to be delivered to the UE.

10.1.2 Uplink Power Management

When the connection for packet services is established, the RRC assigns the TFCS to MAC and the allowable transmission power to L1. The allowable transmission power corresponds to the UE capability class. During a call, the physical layer averages the transmission power over one or several frames. If the averaged transmission power becomes higher than the allowable transmission power, L1 indicates with the primitive MPHY-STATUS to the MAC that the "Allowable transmission power has been reached". The MAC in response reduces the data rate within TFCS, and the power control procedure then reduces the total transmission power.

When channel conditions improve and the averaged transmission power falls [x] dB below than the allowable transmission power the physical layer indicates with the primitive MPHY-STATUS to the MAC that the "Average transmission power is below allowable transmission power by xdB" (the values for [x] are chosen to match the power requirements of different increments in the number of transport channels within the TFCS). The MAC in response increases the data rate by increasing the number of transport blocks delivered to L1 and the physical layer increases the total transmission power by the predefined amount. This allows data that was buffered during bad channel conditions to be transmitted to Node B.

11 Radio Link Surveillance

12 Appendix A - (Simulations on Fast Dynamic Channel Allocation)

12.1 Simulation environment

The presented simulations are performed in the following environments and services according to the requirements in the following documents:

- ETSI TR 101 112, Selection procedures for the choice of radio transmission technologies of the Universal Mobile Telecommunications System UMTS (UMTS 30.03), version 3.2.0, April 1998.
- Seppo Hämäläinen, Peter Slanina, Magnus Hartman, Antti Lappeteläinen, Harri Holma, Oscar Salonaho, A Novel Interface Between Link and System Level Simulations, Acts Mobile Communications Summit '97, pp. 599-604, Aalborg/Denmark, Oct 7-10, 1997.

Absolute capacities [kbit/s/MHz/cell] were published in:

- ETSI Tdoc SMG2 306/98, UTRA TDD Link Level and System Level Simulation Results for ITU Submission, Source: Siemens, Helsinki, Sep 8-11, 1998.


1. Macro (Vehicular) environment for the UDD 144 kbit/s service.
2. Micro (Outdoor-to-Indoor Pedestrian) environment for the UDD 384 kbit/s service.

12.2 Results

The relative load of the cell is used for the abscissa (horizontal axis) in all of the plots. Here, a relative load of 100% refers to the maximum cell load obtainable with code-pooling under the ETSI unsatisfied user criterion (in accordance with ETSI TR 101 112). Vertically, the percentage of unsatisfied users is shown.

12.2.1 Macro UDD 144


In the Macro environment the UDD 144 service is simulated with Hybrid ARQ Type II-III using an adaptive code-rate between 1 and $\frac{1}{2}$.




12.2.2 Micro UDD 384

In the Micro environment the UDD 384 service is simulated with Hybrid ARQ I using code-rates 1 and 2/3.

12.2.2.1 Code rate 1



12.2.2 Code rate 2/3



12.3 Conclusions

With both Hybrid ARQ I and Hybrid ARQ II code pooling performs better than time slot pooling. This is explained as follows: Code-pooling performs better in conjunction with the initial transmission of Hybrid ARQ Type II-III. Timeslot pooling suffers from a high probability of low CIR in at least one of the used timeslots of the PDU. This leads to a high initial transmission failure probability because the initial transmission is sent almost uncoded. When code-pooling is applied, the whole PDU depends on the same interference level on all codes: the probabilities of low CIR on each spreading-code within the same timeslot are strongly coupled.

- The probability of PDU transmission failure for code-pooling is approximately the same as the probability of low CIR in a single timeslot.
- The probability of PDU transmission failure for timeslot-pooling is approximately the same as the probability of low CIR in at least one of the used timeslots.

This advantage of code-pooling results in lower numbers of unsatisfied users. These results clearly recommend that the DCA prefers code pooling over timeslot pooling for UDD packet data in TDD mode.

13 Appendix B (Radio Access Bearer Control – Overview of Procedures: message exchange and parameters used)

13.1 Examples of Radio Access Bearer Setup




Figure 11 Radio access bearer setup on common transport channel.

13.1.1 RRC Parameters in RAB Setup

This message includes **RAB identity** for the new RAB and **RLC info**. It also includes **two different multiplexing configurations** giving the transport channel this RAB could be mapped onto. One configuration to be used on a common transport channel and one for a dedicated transport channel.

For the common transport channel this message includes a new **Transport format set for FACH**, and a **Transport format set for RACH**.

For the dedicated transport channel (pre-configured, not yet used) this message includes the **transport formats for DCH1 and DCH2**, and also the **transport format combinations** used in e.g. 13.2.1, after the switch.

13.1.2 RRC Parameters in RAB Setup Complete

This message includes the identity of the new RAB, **RAB1**.

13.2 Examples of Physical Channel Reconfiguration

This RRC procedure is used to reconfigure the Physical channel and can by that also trigger Transport channel type switching.

Below several examples of Physical Channel reconfigurations are shown, triggered by different amount of UL or DL data.

13.2.1 Increased UL data, with switch from RACH/FACH to DCH/DCH




Figure 12 Physical channel reconfiguration triggered by increased UL data and with a switch from RACH/FACH to DCH/DCH.

13.2.1.1 RRC Parameters in Measurement Report

This message includes a **Measurement Identity number** so that UTRAN can associate this report with a Measurement control message. It also includes the **Measurement result** stating what triggered the report and optionally the RLC buffer payload.

13.2.1.2 RRC Parameters in Physical Channel Reconfiguration

This message includes **DL channelization codes** and **DL scrambling code** for the DPCH. It also includes **UL channelization codes** and **scrambling code** for the DPCH.

13.2.1.3 RRC Parameters in Physical Channel Reconfiguration Complete

No identified parameters

13.2.2 Increased DL data, no Transport channel type switching




Figure 13 Physical channel reconfiguration triggered by increased DL data and configuration in UTRAN DL.

13.2.2.1 RRC Parameters in Physical Channel Reconfiguration

This message includes **new DL channelization codes** for the DPCH with lower spreading factor for all cells that the UE is connected to.

13.2.2.2 RRC Parameters in Physical Channel Reconfiguration Complete

No identified parameters

13.2.3 Decrease DL data, no Transport channel type switching




Figure 14 Physical channel reconfiguration triggered by decreased DL data and configuration in UTRAN DL.

13.2.3.1 RRC Parameters in Physical Channel Reconfiguration

This message includes **new DL channelization codes** for DPCH with higher spreading factor for all cells that the UE is connected to.

13.2.3.2 RRC Parameters in Physical Channel Reconfiguration Complete

No identified parameters

13.2.4 Decreased UL data, with switch from DCH/DCH to RACH/FACH




Figure 15 Physical channel reconfiguration triggered by decreased UL data and with a switch from DCH/DCH to RACH/FACH. Note: Whether the Physical Channel Reconfiguration Complete message is sent before or after entering RACH/FACH substate is FFS.

13.2.4.1 RRC Parameters in Physical Channel Reconfiguration

This message includes a **PRACH spreading factor** for the UL i.e. stating the minimum spreading factor to be used, and the **preamble signatures** that are allowed. Further, for the PRACH which **access slots** that are allowed and the **preamble spreading code** is included.

For the DL the message includes **scrambling code**, i.e. indicating to which cells FACH the UE should be connected to, and a **channelization code** for the secondary CCPCH.

[Note: The common channel parameters are the same that is transmitted on the BCCH. The reason to send it in this message is to remove the necessity for the UE to read BCCH at this switch.]

[Note: The necessity of an immediate cell-update when moving to RACH/FACH or if a valid RNTI is given to the UE before making the switch to allow immediate usage of DCCH is FFS.]

13.2.4.2 RRC Parameters in Physical Channel Reconfiguration Complete

No identified parameters

13.3 Examples of Transport Channel Reconfiguration

13.3.1 Increased UL data, with no transport channel type switching

In the example below, the UE is allowed to send more data in the UL when on dedicated transport channel, although the common transport channel configuration is still the same. To make use of the new transport format combinations the physical channel must also be reconfigured to allow a lower spreading factor.




Figure 16 Transport channel reconfiguration triggered by increased UL data and configuration in UTRAN DL.

13.3.1.1 RRC Parameters in Measurement Report

This message includes a **Measurement Identity number** so that UTRAN can associate this report with a Measurement control message. It also includes the **Measurement result** stating what triggered the report and optionally the RLC buffer payload.

13.3.1.2 RRC Parameters in Transport Channel Reconfiguration

This message includes a new **Transport format set** for DCH2 and a new **Transport format combination set**. An **Activation time** must also be included if the different TFCIs can not coexist during the reconfiguration.

It also includes **UL channelization codes** for the DPCH.

13.3.1.3 RRC Parameters in Transport Channel Reconfiguration Complete

This message includes the identity of the reconfigured Transport channel, **DCH2**.

13.3.2 Decreased DL data, with switch from DCH/DCH to RACH/FACH




Figure 17 Transport channel reconfiguration triggered by decreased DL data and with a switch from DCH/DCH to RACH/FACH. Note: Whether the Transport Channel Reconfiguration Complete message is sent before or after entering RACH/FACH substate is FFS.

13.3.2.1 RRC Parameters in Transport Channel Reconfiguration

This message includes new **Transport format set for RACH**, a **PRACH spreading factor** i.e. stating the minimum spreading factor to be used, and the **preamble signatures** that are allowed. Further, for the PRACH which **access slots** that are allowed and the **preamble spreading code** is included.

For the DL the message includes a new **Transport format set for FACH**, the **scrambling code**, i.e. indicating to which cells FACH the UE should be connected to, and a **channelization code** for the secondary CCPCH.

[Note: The common channel parameters are the same that is transmitted at the BCCH. The reason to send it in this message is to remove the necessity for the UE to read BCCH at this switch.]

[Note: The necessity of an immediate cell-update when moving to RACH/FACH or if a valid RNTI is given to the UE before making the switch to allow immediate usage of DCCH is FFS.]

13.3.2.2 RRC Parameters in Transport Channel Reconfiguration Complete

This message includes the identity of the reconfigured transport channels, **RACH** and **FACH**.

13.4 Examples of RAB and Signalling link Reconfiguration




Figure 18 RAB reconfiguration.

13.4.1 RRC Parameters in Radio access bearer reconfiguration

This message includes a multiplexing option with **Transport channel identity DCH2 for both RAB1 and RAB2**, stating that both these RABs should use the same transport channel. For each of these two RABs a **Logical channel identity value** and a **priority** must be given to define the MAC MUX.

Also included is a new **Transport format set** for DCH2 and a new **Transport format combination set** (both for UL and DL if the multiplexing is changed both in UL and DL).

It is also possible to reconfigure the physical channel and include new **channelization codes** for the DPCH with different spreading factor for all cells that the UE is connected to.

13.4.2 RRC Parameters in Radio access bearer reconfiguration Complete

This message includes the **identities RAB1 and RAB2** to indicate that these RABs have been reconfigured. It also includes **transport channel identity DCH3** to indicate that this transport channel has been removed.

14 History

Document history		
Date	Version	Comment
June 1999	0.2.0	The document was approved by e-mail and version raised to 0.2.0 for submission to TSG RAN.
May 1999	0.1.2	Message exchange and parameters used described for RAB control procedures from R299-251 were included in Appendix B; procedures related to power management for Variable Rate Packet Transmission from R2-99426 were included in Section 10.
April 1999	0.1.1	Inclusion of the input contributions 99/270, 99/246, 99/251. Approved by WG2. This document was submitted to TSG RAN and noted as version 0.1.1
April 1999	0.1.0	Document approved at Yokohama meeting
April 1999	0.0.3	Document reviewed after the comments provided during the meeting of Yokohama,
April 1999	0.0.2	Different parts from various documents of TSG RAN were included in the first draft version of TR R2.02.
March 1999	0.0.1	Document was created. A Scope and an index were added on the basis of td R2-99-182
Rapporteur for 3GPP TSG RAN WG2 TR 25.922 is:		
CSELT		
Daniele Franceschini		Nicola Pio Magnani
Tel.: +39 011 228 5203		Tel.: +39 011 228 7089
Fax: +39 011 228 7613		Fax: +39 011 2287613
e-mail: daniele.franceschini@cselt.it		e-mail: nicola.magnani@cselt.it
This document is written in Microsoft Word Version 97 SR-1 and saved in Rich Text Format.		