3GPP TSG RAN Meeting #16 Marco Island, FL, U.S.A., 4 – 7, June 2002

CHANGE REQUEST													
*	25.	221	CR	080	% I	rev	2	Ж	Current	versi	ion:	5.0.0	¥
For <u>HELP</u> on using this form, see bottom of this page or look at the pop-up text over the % symbols.													
Proposed change affects: # (U)SIM ME/UE X Radio Access Network X Core Network													
Title: ૠ	Cla	rification	on of sl	nared ch	annel fur	nctiona	ality fo	or TD	D				
Source: #	Sie	mens /	AG										
Work item code: Ж	TEI	5							Date	e: Ж	4.6	.2002	
Category:	Detai	F (corr A (corr B (add C (fund D (edit	rection) respond dition of ctional re torial mo olanation	feature), nodification odification	rrection in on of featu n) above cate	ıre)		lease	2	<u>ne</u> of t 3 3 3 3 4	the fol (GSN (Rele (Rele (Rele (Rele	L-5 Illowing real 1 Phase 2, ase 1996, ase 1998, ase 1999, ase 4) ase 5))))
Reason for change: Current description of the UE selection procedure for the PDSCH exmentions the release, when saying that this procedure is not support cause regular CRs for each new release of the specification, as long feature is not supported.									ipported.	This will			
Summary of chang	Je: ₩	defer		ater relea	ore gener ases, the								for
Consequences if not approved:	*	This will cause regular CRs for each new release of the specification, as long the feature is not supported. Isolated Impact Analysis: This is an isolated impact CR that corrects a functionality where the specifical contained contradictions. This CR would not affect implementations behaving indicated in the CR, would affect implementations supporting the corrected functionality otherwise.									cification having as		
Clauses affected:	ж	5.3.6)										
Other specs affected:		Ot Te	ther cor	re specif cification ecificatio	ıs	ж							
Other comments:	\mathbf{x}												

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: http://www.3gpp.org/3G Specs/CRs.htm. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked **#** contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under ftp://ftp.3gpp.org/specs/ For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

5.3.6 Physical Downlink Shared Channel (PDSCH)

The DSCH as described in subclause 4.1.2 is mapped onto one or more physical downlink shared channels (PDSCH).

5.3.6.1 PDSCH Spreading

The PDSCH uses either spreading factor SF = 16 or SF = 1 as described in subclause 5.2.1.1.

5.3.6.2 PDSCH Burst Types

Burst types 1 or 2 as described in subclause 5.2.2 can be used for PDSCH. TFCI can be transmitted on the PDSCH.

5.3.6.3 PDSCH Training Sequences

The training sequences as described in subclause 5.2.3 are used for the PDSCH.

5.3.6.4 UE Selection

To indicate to the UE that there is data to decode on the DSCH, three signalling methods are available:

- 1) using the TFCI field of the associated channel or PDSCH;
- 2) using on the DSCH user specific midamble derived from the set of midambles used for that cell;
- 3) using higher layer signalling.

When the midamble based method is used, the UE specific midamble allocation method shall be employed (see subclause 5.6), and the UE shall decode the PDSCH if the PDSCH was transmitted with the midamble assigned to the UE by UTRAN. For this method no other physical channels may use the same time slot as the PDSCH and only one UE may share the PDSCH time slot within one TTI.

Note: From the above mentioned signalling methods, only the higher layer signalling method is supported by higher layers in this Release Release 4.