

2019/5/27

Motivation for new SI proposal on NR sidelink support for non-V2X

Background for commercial NR Sidelink

- SA1 studied on “Network Controlled Interactive Service” (*FS_NCIS*) focusing *Commercial interactive services over local wireless link*
 - Existing smartphones or new forms of 5G portable devices (e.g. VR/AR devices, robot, etc.) for entertainment and education (e.g. interactive gaming or conferences) over PC5 interface → **power efficiency** needs to be addressed for portable UEs
 - General requirements from **TR22.842**, interactive service with less than [10ms] End-to-End latency and at least [1 Gbps] data rate → **resource efficiency** would be critical to achieve high data rate
 - **TR 22.842** V1.2.0 2019-05 (final version)
 - SA1 Study item reported **100% completion** in SA#84
 - SA1 work item approved in S1-191636
 - ✓ Target completion by **2019-11**



Local Gaming



Local Conference


SA2 kicked-off *Proximity based services in 5GS*

- Two sets of objectives are pursued pertaining to specifically commercial and public safety related services (S2-1906727)
 - Set-A objectives for Public Safety related ProSe;
 - Set-B objectives for commercial related ProSe, where set-B is stage-2 continuation of FS_NCIS (SA1 requirements);
- Based on a common framework, NR sidelink design should additionally support commercial (TR22.842 for NCIS) and Public Safety (TS22.278) use cases and requirements.
- Further stage-3 work is expected to follow in RAN and SA

Background of sidelink and applications

- In Rel-12/13, ProSe was introduced and mainly optimized for voice type traffic (MCPTT), i.e., lower data rate, relaxed delay requirement
- In Rel-14/15/16, V2X was introduced for ITS operation, mainly target at low latency and high reliability in high-speed scenarios,
 - Vehicle UEs assumed to have “unlimited power supply” , i.e., UE power efficiency is not considered
 - ✓ Constant resource sensing and data reception operation are essential for safety and reliability, but not battery friendly
 - Low data rate typically required for V2X (e.g.10-90 Mbps), i.e., resource efficiency is not critical

Deployment scenarios



- NR sidelink is always under network Uu control
 - For network:
 - ✓ **Efficient spectrum utilization and cost reduction:** Massive deployment of FR2 cells to support high data rate applications everywhere **VS** adopting FR1 Uu to provide control over FR2 SL
 - ✓ **Effective traffic offloading between Uu and SL:** Whenever possible, comm between nearby UEs offload to SL to free-up UL/DL resources and capacity for other eMBB and URLLC services
 - For UE:
 - ✓ **More utilization of high-frequency band module:** Further explore costly high-frequency band module for more scenarios, and not limited by the hot-spot coverage via Uu interface
 - ✓ **Minimize UE battery consumption:** Reduction of Tx power for direct data transfer over SL compared to propagation distance to BS over Uu

New features and enhancement for ProSe in 5GS

- Energy and resource efficiency operations
 - Dynamic CL power control for close proximity transmissions
 - Sidelink DRX for energy efficient reception
 - Higher order modulation and multi-layer transmissions for high data rate
- Coverage enhancement and service continuation
 - UE-to-Network relay
 - UE-to-UE relay
- UE discovery and group management
 - Sidelink transmission and reception managed by group header UE

Expected studies in RAN (objectives)

For commercial services:

- Study / evaluation of NR sidelink Rel-16 design to support NCIS use cases and identify necessary enhancements (RAN1)
- Study mechanism(s) to improve **energy-efficiency** for sidelink
 - Enhancements of [PSCCH/PSSCH multiplexing] and power setting procedure to enable **closed-loop power control** (RAN1)
 - Support of **sidelink DRX** (RAN2/1)
 - Support of **UE-to-UE relay** (RAN2/RAN1)
 - Support of SL Tx and Rx of member UEs **managed by group header UE** (RAN1/RAN2)
- Study mechanism(s) to improve **resource-efficiency** for sidelink
 - [Support of **256QAM** on sidelink assisted with channel feedback (RAN1/4)]
 - Feasibility to enhance **MIMO (up to [4] layers) / beamforming** assisted with channel feedback in low mobility (RAN1)
- Study interference from sidelink transmission to UL reception in adjacent channel environment (if any), and identify mitigation solution(s) (RAN4, RAN1)

For Public Safety services [RAN2/RAN1]:

- Study mechanism(s) to support **UE discovery** (RAN1/RAN2)
- Study mechanism(s) to support **UE-to-Network relay** (RAN2/RAN1)

Timeline for enhance SL study for non-V2X in RAN

- The work targets for Release 17
- Main working group: RAN1 (primary), RAN2 (secondary)
- Study item phase
 - RAN plenary approval in December 2019
 - *Duration 6~9 months*
 - *TUs per meeting: 1.5*
- Work item phase
 - After SI completion (e.g. from September 2020)
 - *Duration: 6~9 months*
 - *TUs per meeting: 1.5*

Thank you

oppo