


3GPP TSG RAN Meeting #85
Newport Beach, USA, September 16-20, 2019

Document for: Approval
Agenda Item: 9.1.4

RP-192101

Views on introduction of NB-IoT in AAS specification

Huawei, HiSilicon



Security Level:



Background

- [1] was submitted for information during RAN4#92 meeting. It proposes to introduce NB-IoT into AAS specification to enable the usage of AAS BS for bands around and above 2 GHz. In this paper we provide our views on the new WI proposal.

Discussion on the request

- NB-IoT feature was introduced in Rel-13, towards low complexity and low throughput radio access technology to address the requirements of cellular internet of things.
- AAS as the platform for advanced array technologies (e.g. MIMO) was also introduced in Rel-13.
- Both features were enhanced in Rel-14 and Rel-15 WIs. During Rel-13 ~ Rel-15 phase, there was no desire to include NB-IoT into AAS specifications, with the following reasons
 - NB-IoT is designed for narrow bandwidth with low throughput for low frequency band but not for multi-stream and high data-rate service scenarios, i.e. NB-IoT only supports one or two antenna ports
 - AAS is suitable for high frequency band for MBB service
- **Observation 1: AAS is not suitable to support NB-IoT compared to non-AAS**

Discussion on the impact on AAS BS

- To support NB-IoT, the power consumption may be increased significantly.
 - The physical layer common channel overhead of the NB-IoT is much higher than that of the LTE, and the possibility of OFF power symbol is much lower compare to LTE, e.g. compared LTE+NB case to LTE only case there can be 35% gap in theory (no load) and ~20% in low load scenario.
 - The power consumption is essential for AAS BS which has much more transceiver units and higher power consumption than non-AAS.

Observation 2: To support NB-IoT for AAS BS, the probability of OFF power symbol will be much lower and affects the energy saving effect.

- To support NB-IoT, the implementation complexity will be increased.
 - Power boosting need more implementation margin to fulfil the unwanted emission mask
 - Additional antenna calibration is needed for NB-IoT.

- **Observation 3:** To support NB-IoT, the implementation complexity will be increased.

Proposals

- Considering no concrete gain, significant impact to power saving and increased implementation complexity, we propose,
- Proposal : NB-IoT is not introduce into AAS specification.

Reference

[1] R4-1908060, On NB-IoT requirement coverage, Ericsson

Thank you.

Bring digital to every person, home and organization for a fully connected, intelligent world.

**Copyright©2018 Huawei Technologies Co., Ltd.
All Rights Reserved.**

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

