3GPP TSG RAN Rel-19 workshop
Taipei, June 15 - 16, 2023
Agenda Item: 5
Source: TOYOTA InfoTechnology Center

RWS-230484

Views on Sidelink Positioning Enhancements for Rel-19

TOYOTA
InfoTech
Envisioning Mobility

NR Sidelink Positioning Enhancements for Rel-19

TOYOTA INFOTECH Envisioning Mobility

- Background
  - NR sidelink positioning features in Rel-18 Expanded and Improved NR Positioning (RP-230328):
    - SL PRS for support of sidelink positioning (SL PRS bandwidths of up to 100 MHz in FR1 spectrum. SL PRS transmission in FR2 is not precluded but no FR2 specific aspects will be specified.)
    - Measurements to support RTT-type solutions using SL, SL-AoA, and SL-TDOA
    - Resource allocation for SL PRS for shared and dedicated resource pools for Scheme 1 and Scheme 2
    - Procedures for transmit power control for SL PRS transmissions
    - Signalling and associated UE behavior for support of unicast, groupcast (not including many to one) and broadcast of SL PRS transmissions
    - Reporting signalling and procedures to facilitate support of SL positioning in all coverage scenarios and for PC5-only and joint PC5-Uu scenarios
    - Signalling to NG-RAN for sidelink positioning and ranging service authorizations
    - Corresponding new core requirements, as well as identifying and specify the impact on the existing RAN4 specification, including RRM measurements and procedures

- Motivation for Rel-19 NR sidelink positioning
  - Available bandwidth on FR1 V2X band is limited in some regions/countries. NR sidelink positioning on FR1 unlicensed bands and FR2 bands should be supported.
  - NR sidelink positioning with power saving features (e.g., DRX) should be supported for battery-limited devices (e.g., pedestrian devices).

NR Sidelink Positioning Enhancements for Rel-19

TOYOTA INFOTECH Envisioning Mobility

- Potential Rel-19 scope
  - NR sidelink positioning on FR1 unlicensed bands
  - NR sidelink positioning on FR2 bands
  - NR sidelink positioning with power saving features (e.g., DRX)