A UE shall upon detection of a PDCCH with a configured DCI format 1_0, 1_1 or 1_2 decode the corresponding PDSCHs as indicated by that DCI. For any HARQ process ID(s) in a given scheduled cell, the UE is not expected to receive a PDSCH that overlaps in time with another PDSCH. The UE is not expected to receive another PDSCH for a given HARQ process until after the end of the expected transmission of HARQ-ACK for that HARQ process, where the timing is given by Clause 9.2.3 of [6]. Except for the case when a UE is configured by higher layer parameter *PDCCH-Config* that contains two different values of *coresetPoolIndex* in *ControlResourceSet* and PDCCHs that schedule two PDSCHs are associated to different *ControlResourceSets* having different values of *coresetPoolIndex,* in a given scheduled cell, the UE is not expected to receive a first PDSCH and a second PDSCH, starting later than the first PDSCH, with its corresponding HARQ-ACK assigned to be transmitted on a resource ending before the start of a different resource for the HARQ-ACK assigned to be transmitted for the first PDSCH, where the two resources are in different slots for the associated HARQ-ACK transmissions, each slot is composed of N_{sym}^{slot} symbols [4] or a number of symbols indicated by *subslotLengthForPUCCH* if provided, and the HARQ-ACK for the two PDSCHs are associated with the HARQ-ACK codebook of the same priority. Except for the case when a UE is configured by higher layer parameter *PDCCH-Config* that contains two different values of *coresetPoolIndex* in *ControlResourceSet* and PDCCHs that schedule two PDSCHs are associated to different *ControlResourceSets* having different values of *coresetPoolIndex,* in a given scheduled cell, the UE is not expected to receive a first PDSCH, and a second PDSCH, starting later than the first PDSCH, with its corresponding HARQ-ACK assigned to be transmitted on a resource ending before the start of a different resource for the HARQ-ACK assigned to be transmitted for the first PDSCH if the HARQ-ACK for the two PDSCHs are associated with HARQ-ACK codebooks of different priorities. For any two HARQ process IDs in a given scheduled cell, if the UE is scheduled to start receiving a first PDSCH starting in symbol *j* by a PDCCH ending in symbol *i*, the UE is not expected to be scheduled to receive a PDSCH starting earlier than the end of the first PDSCH with a PDCCH that ends later than symbol *i*. In a given scheduled cell, for any PDSCH corresponding to SI-RNTI, the UE is not expected to decode a re-transmission of an earlier PDSCH with a starting symbol less than *N* symbols after the last symbol of that PDSCH, where the value of *N* depends on the PDSCH subcarrier spacing configuration μ, with N=13 for μ=0, N=13 for μ=1, N=20 for μ=2, and N=24 for μ=3.