

3GPP TS 38.521-1 V17.6.1 (2022-10)

Technical Specification

**3rd Generation Partnership Project;
Technical Specification Group Radio Access Network;
NR;
User Equipment (UE) conformance specification;
Radio transmission and reception;
Part 1: Range 1 Standalone;
(Release 17)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and Reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2022, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Foreword.....	17
1 Scope.....	18
2 References.....	18
3 Definitions, symbols and abbreviations	19
3.1 Definitions	19
3.2 Symbols	20
3.3 Abbreviations.....	22
4 General	24
4.1 Relationship between minimum requirements and test requirements.....	24
4.2 Applicability of minimum requirements.....	24
4.3 Specification suffix information	25
4.4 Test points analysis.....	25
4.5 Applicability and test coverage rules.....	25
4.6 Pass fail decision rule of test case.....	25
5 Operating bands and Channel arrangement.....	26
5.1 General.....	26
5.2 Operating bands	26
5.2A Operating bands for CA.....	29
5.2A.1 Intra-band CA.....	29
5.2A.2 Inter-band CA.....	30
5.2A.2.1 Inter-band CA (two bands).....	31
5.2A.2.2 Inter-band CA (three bands).....	33
5.2A.2.3 Inter-band CA (four bands)	33
5.2B Operating bands for DC.....	33
5.2C Operating band combination for SUL.....	33
5.2D Operating bands for UL MIMO.....	35
5.2E Operating band for V2X	35
5.2E.1 V2X operating bands.....	35
5.2E.2 V2X operating bands for concurrent operation	35
5.3 UE channel bandwidth.....	36
5.3.1 General.....	36
5.3.2 Maximum transmission bandwidth configuration.....	36
5.3.4 RB alignment	38
5.3.5 UE channel bandwidth per operating band	39
5.3.6 Asymmetric channel bandwidths	43
5.3A UE channel bandwidth for CA.....	44
5.3A.1 General	44
5.3A.2 Maximum transmission bandwidth configuration for CA.....	44
5.3A.3 Minimum guard band and transmission bandwidth configuration for CA	44
5.3A.4 Void.....	46
5.3A.5 UE channel bandwidth per operating band for CA	46
5.3E Channel bandwidth for V2X.....	47
5.3E.1 General.....	47
5.3E.2 Channel bandwidth for V2X concurrent operation	48
5.3I Channel bandwidth for RedCap.....	48
5.4 Channel arrangement	48
5.4.1 Channel spacing	48
5.4.1.1 Channel spacing for adjacent NR carriers	48
5.4.2 Channel raster.....	48
5.4.2.1 NR-ARFCN and channel raster.....	48
5.4.2.2 Channel raster to resource element mapping	49
5.4.2.3 Channel raster entries for each operating band.....	49
5.4.3 Synchronization raster.....	51
5.4.3.1 Synchronization raster and numbering	51

5.4.3.2	Synchronization raster to synchronization block resource element mapping	52
5.4.3.3	Synchronization raster entries for each operating band	52
5.4.4	TX–RX frequency separation	54
5.4A	Channel arrangement for CA	54
5.4A.1	Channel spacing for CA	54
5.4A.2	Channel raster for CA	55
5.4A.3	Synchronization raster for CA	55
5.4A.4	Tx-Rx frequency separation for CA	55
5.4E	Channel arrangement for V2X	55
5.4E.1	Channel spacing	55
5.4E.2	Channel raster	55
5.4E.2.1	NR-ARFCN and channel raster	55
5.4E.2.2	Channel raster to resource element mapping	55
5.4E.2.3	Channel raster entries for each operating band	55
5.4E.3	Synchronization raster for V2X	56
5.5	Void	56
5.5A	Configurations for CA	56
5.5A.0	General	56
5.5A.1	Configurations for intra-band contiguous CA	56
5.5A.2	Configurations for intra-band non-contiguous CA	60
5.5A.3	Configurations for inter-band CA	60
5.5A.3.1	Configurations for inter-band CA (two bands)	61
5.5A.3.2	Configurations for inter-band CA (three bands)	68
5.5A.3.3	Configurations for inter-band CA (four bands)	70
5.5B	Configurations for DC	71
5.5C	Configurations for SUL	72
6	Transmitter characteristics	74
6.1	General	74
6.1A	General	76
6.1E	General	93
6.2	Transmitter power	99
6.2.1	UE maximum output power	99
6.2.2	UE maximum output power reduction	106
6.2.3	UE additional maximum output power reduction	133
6.2.4	Configured transmitted power	320
6.2A	Transmitter power for CA	327
6.2A.1	UE maximum output power for CA	327
6.2A.1.0	Minimum conformance requirements	327
6.2A.1.0.1	Void	327
6.2A.1.0.2	Void	327
6.2A.1.0.3	UE maximum output power for Inter-band CA	327
6.2A.1.0.4	UE maximum output power for Intra-band contiguous CA	330
6.2A.1.0.5	UE maximum output power for Intra-band non-contiguous CA	331
6.2A.1.1	UE maximum output power for CA (2UL CA)	331
6.2A.2	UE maximum output power reduction for CA	337
6.2A.2.0	Minimum conformance requirements	337
6.2A.2.0.1	FFS	337
6.2A.2.0.2	FFS	337
6.2A.2.0.3	Maximum Power Reduction for Inter-band CA	337
6.2A.2.0.4	Maximum Power Reduction for Intra-band contiguous CA	337
6.2A.2.0.5	Maximum Power Reduction for Intra-band non-contiguous CA	341
6.2A.2.1	UE maximum output power reduction for CA (2UL CA)	342
6.2A.3	UE additional maximum output power reduction for CA	366
6.2A.3.0	Minimum conformance requirements	366
6.2A.3.0.1	FFS	366
6.2A.3.0.2	FFS	366
6.2A.3.0.3	UE additional maximum output power reduction for inter-band CA	366
6.2A.3.1	UE additional maximum output power reduction for CA (2UL CA)	369
6.2A.4	Configured output power for CA	378
6.2A.4.0	Minimum conformance requirements	378
6.2A.4.0.1	Configured transmitted power level	378

6.2A.4.0.2	$\Delta T_{IB,c}$ for CA.....	383
6.2A.4.0.2.1	FFS.....	384
6.2A.4.0.2.2	FFS.....	384
6.2A.4.0.2.3	$\Delta T_{IB,c}$ for Inter-band CA	384
6.2A.4.1	Configured transmitted power for CA (2UL CA).....	386
6.2B	Transmitter power for NR-DC.....	392
6.2B.0	General	392
6.2B.1	UE maximum output power for NR-DC	393
6.2B.1.0	Minimum conformance requirements.....	393
6.2B.1.0.1	FFS.....	393
6.2B.1.0.2	FFS.....	393
6.2B.1.0.3	UE maximum output power for inter-band NR-DC.....	393
6.2B.1.1	UE maximum output power for NR-DC.....	393
6.2B.2	UE maximum output power reduction for NR-DC	396
6.2B.2.0	Minimum conformance requirements.....	396
6.2B.2.0.1	FFS.....	396
6.2B.2.0.2	FFS.....	396
6.2B.2.0.3	UE maximum output power reduction for Inter-band NR-DC	396
6.2B.2.1	UE maximum output power for NR-DC.....	396
6.2B.3	UE additional maximum output power reduction for NR-DC	397
6.2B.3.0	Minimum conformance requirements.....	397
6.2B.3.0.1	FFS.....	397
6.2B.3.0.2	FFS.....	397
6.2B.3.0.3	UE additional maximum output power reduction for inter-band NR-DC.....	397
6.2B.3.1	UE additional maximum output power reduction for NR-DC.....	398
6.2B.4	Configured output power for NR-DC.....	399
6.2B.4.0	Minimum conformance requirements.....	399
6.2B.4.0.1	Configured transmitted power level for NR-DC.....	399
6.2B.4.0.2	$\Delta T_{IB,c}$ for NR-DC	403
6.2B.4.0.2.1	FFS.....	403
6.2B.4.0.2.2	FFS.....	403
6.2B.4.0.2.3	$\Delta T_{IB,c}$ for Inter-band NR-DC	403
6.2B.4.1	Configured transmitted power level for NR-DC	403
6.2C	Transmitter power for SUL.....	406
6.2C.1	Configured transmitted power for SUL.....	406
6.2C.2	$\Delta T_{IB,c}$	409
6.2C.3	UE maximum output power for SUL	409
6.2C.3_1	UE maximum output power for SUL with UL MIMO	412
6.2C.4	UE maximum output power reduction for SUL	417
6.2C.5	UE additional maximum output power reduction for SUL	427
6.2D	Transmitter power for UL MIMO.....	463
6.2D.1	UE maximum output power for UL MIMO	463
6.2D.2	UE maximum output power reduction for UL MIMO	468
6.2D.3	UE additional maximum output power reduction for UL MIMO	493
6.2D.4	Configured transmitted power for UL MIMO.....	535
6.2E	Transmitter power for V2X	538
6.2E.1	UE maximum output power for V2X.....	538
6.2E.1.0	Minimum conformance requirements.....	538
6.2E.1.1	UE maximum output power for V2X / non-concurrent operation.....	539
6.2E.1.1D	UE maximum output power for V2X / non-concurrent operation / SL-MIMO.....	540
6.2E.2	UE maximum output power reduction for V2X.....	542
6.2E.2.0	Minimum conformance requirements.....	542
6.2E.2.1	UE maximum output power reduction for V2X / non-concurrent operation.....	543
6.2E.2.1D	UE maximum output power reduction for V2X / non-concurrent operation / SL-MIMO.....	548
6.2E.2.2	UE maximum output power reduction for V2X / concurrent operation	550
6.2F	Transmitter power for shared spectrum channel access.....	554
6.2F.1	UE maximum output power for shared spectrum channel access	554
6.2F.2	UE maximum output power reduction	557
6.2F.3	UE additional maximum output power reduction for shared spectrum access.....	557
6.2G	Transmitter power for Tx Diversity	563
6.2G.1	UE maximum output power for Tx Diversity	563

6.2G.2	UE maximum output power reduction for Tx Diversity	567
6.2G.3	UE additional maximum output power reduction for Tx Diversity.....	583
6.2I	Transmitter power for RedCap	594
6.2I.1	UE maximum output power for RedCap.....	594
6.2I.2	UE maximum output power reduction for RedCap.....	596
6.2I.3	UE additional maximum output power reduction for RedCap.....	596
6.2I.4	Configured transmitted power for RedCap	636
6.3	Output power dynamics	637
6.3.1	Minimum output power.....	637
6.3.2	Transmit OFF power	640
6.3.3	Transmit ON/OFF time mask.....	641
6.3.3.1	General	641
6.3.3.2	General ON/OFF time mask.....	642
6.3.3.3	Transmit power time mask for slot and short or subslot boundaries	646
6.3.3.4	PRACH time mask	646
6.3.3.5	Void	653
6.3.3.6	SRS time mask	653
6.3.3.7	PUSCH-PUCCH and PUSCH-SRS time masks.....	663
6.3.3.8	Transmit power time mask for consecutive slot or long subslot transmission and short subslot transmission boundaries	663
6.3.3.9	Transmit power time mask for consecutive short subslot transmissions boundaries.....	663
6.3.4	Power control	664
6.3.4.1	General	664
6.3.4.2	Absolute power tolerance	664
6.3.4.3	Relative power tolerance	667
6.3.4.4	Aggregate power tolerance	686
6.3A	Output power dynamics for CA.....	690
6.3A.1	Minimum output power for CA.....	690
6.3A.1.0	Minimum conformance requirements.....	690
6.3A.1.1	Minimum output power for CA (2UL CA)	690
6.3A.2	Transmit OFF power for CA.....	693
6.3A.2.0	Minimum conformance requirements.....	693
6.3A.2.1	Transmit OFF power for CA (2UL CA).....	693
6.3A.3	Transmit ON/OFF time mask for CA.....	694
6.3A.3.0	Minimum conformance requirements.....	694
6.3A.3.0.1	Transmit ON/OFF time mask for intra-band contiguous CA.....	694
6.3A.3.0.2	Transmit ON/OFF time mask for intra-band non-contiguous CA	694
6.3A.3.0.3	Transmit ON/OFF time mask for inter-band CA	694
6.3A.3.1	Transmit ON/OFF time mask for CA (2UL CA)	695
6.3A.3.1_1	Time mask for switching between two uplink carriers.....	701
6.3A.4	Power control for CA	706
6.3A.4.1	Absolute power tolerance for CA	706
6.3A.4.1.0	Minimum conformance requirements	706
6.3A.4.1.1	Absolute power tolerance for CA (2UL CA).....	706
6.3A.4.2	Relative power tolerance for CA	709
6.3A.4.2.0	Minimum conformance requirements	709
6.3A.4.2.1	Relative power tolerance for CA (2UL CA)	710
6.3A.4.3	Aggregate power tolerance for CA	718
6.3A.4.3.0	Minimum conformance requirements	718
6.3A.4.3.1	Aggregate power tolerance for CA (2UL CA).....	718
6.3B	Output power dynamics for NR-DC	723
6.3B.1	Minimum output power for NR-DC.....	723
6.3B.2	Transmit OFF power for NR-DC	723
6.3B.3	Transmit ON/OFF time mask for NR-DC.....	723
6.3C	Output power dynamics for SUL	723
6.3C.1	Minimum output power for SUL.....	723
6.3C.2	Transmit OFF power for SUL	725
6.3C.3	Transmit ON/OFF time mask for SUL.....	726
6.3C.3.0	Minimum conformance requirements.....	726
6.3C.3.0.1	General ON/OFF time mask for SUL	726
6.3C.3.0.2	Time mask for switching between two uplink carriers	726

6.3C.3.1	General transmit ON/OFF time mask for SUL.....	727
6.3C.3.2	General transmit ON/OFF time mask for switching between two uplink carriers	729
6.3C.4	Power control for SUL	733
6.3C.4.1	Absolute power tolerance for SUL	733
6.3C.4.2	Relative power tolerance for SUL	736
6.3C.4.3	Aggregate power tolerance for SUL.....	744
6.3D	Output power dynamics for UL MIMO	747
6.3D.1	Minimum output power for UL MIMO.....	747
6.3D.2	Transmit OFF power for UL MIMO	749
6.3D.3	Transmit ON/OFF time mask for UL MIMO.....	751
6.3D.4	Power control for UL MIMO	757
6.3D.4.1	Absolute power tolerance for UL MIMO	757
6.3D.4.2	Relative power tolerance for UL MIMO	761
6.3D.4.3	Aggregate power tolerance for UL MIMO	774
6.3E	Output power dynamics for V2X.....	777
6.3E.1	Minimum output power for V2X	777
6.3E.1.0	Minimum conformance requirements.....	777
6.3E.1.1	Minimum output power for V2X / non-concurrent operation	777
6.3E.1.1D	Minimum output power for V2X / non-concurrent operation / SL-MIMO	779
6.3E.2	Transmit OFF power for V2X.....	782
6.3E.2.0	Minimum conformance requirements.....	782
6.3E.2.1	Transmit OFF power for V2X / non-concurrent operation.....	782
6.3E.2.1D	Transmit OFF power for V2X / non-concurrent operation / SL-MIMO	783
6.3E.2.2	Transmit OFF power for V2X / con-current operation.....	784
6.3F	Output power dynamics for shared spectrum channel access	785
6.3F.1	Minimum output power.....	785
6.3F.2	Transmit OFF power for shared spectrum channel access	787
6.3F.3	Transmit ON/OFF time mask for shared spectrum channel access	788
6.3F.3.1	General	788
6.3F.3.2	General ON/OFF time mask	788
6.3G	Output power dynamics for Tx Diversity	792
6.3G.1	Minimum output power for Tx Diversity	792
6.3G.2	Transmit OFF power for Tx Diversity	793
6.3G.3	Transmit ON/OFF time mask for Tx Diversity	794
6.3G.3.1	General ON/OFF time mask for Tx Diversity	794
6.3G.3.2	PRACH time mask for Tx Diversity	797
6.3G.3.3	SRS time mask for Tx Diversity.....	800
6.3G.4	Power control for Tx Diversity	801
6.3G.4.1	Absolute power tolerance for Tx Diversity	801
6.3G.4.2	Relative power tolerance for Tx Diversity	801
6.3G.4.3	Aggregate power tolerance for Tx Diversity	811
6.4	Transmit signal quality	812
6.4.1	Frequency error	812
6.4.2	Transmit modulation quality	814
6.4.2.1	Error Vector Magnitude.....	814
6.4.2.1a	Error Vector Magnitude including symbols with transient period.....	822
6.4.2.2	Carrier leakage.....	826
6.4.2.3	In-band emissions	829
6.4.2.4	EVM equalizer spectrum flatness.....	835
6.4.2.5	EVM equalizer spectrum flatness for Pi/2 BPSK	839
6.4A	Transmit signal quality for CA	843
6.4A.1	Frequency error for CA	843
6.4A.1.0	Minimum conformance requirements.....	843
6.4A.1.1	Frequency error for CA (2UL CA).....	843
6.4A.2	Transmit modulation quality for CA	845
6.4A.2.1	Error Vector Magnitude for CA	846
6.4A.2.1.0	Minimum conformance requirements	846
6.4A.2.1.1	Error Vector Magnitude for CA (2UL CA)	846
6.4A.2.2	Carrier leakage for CA	849
6.4A.2.2.0	Minimum conformance requirements	849
6.4A.2.2.1	Carrier leakage for CA (2UL CA)	850

6.4A.2.3	In-band emissions for CA.....	853
6.4A.2.3.0	Minimum conformance requirements.....	853
6.4A.2.3.1	In-band emissions for CA (2UL CA).....	854
6.4B	Transmit signal quality for NR-DC.....	857
6.4B.1	Frequency error for NR-DC.....	857
6.4B.2	Transmit modulation quality for NR-DC.....	858
6.4B.2.1	Error Vector Magnitude for NR-DC.....	858
6.4B.2.2	Carrier leakage for NR-DC.....	858
6.4B.2.3	In-band emissions for NR-DC.....	858
6.4C	Transmit signal quality for SUL.....	858
6.4C.1	Frequency error for SUL.....	858
6.4C.2	Transmit modulation quality for SUL.....	859
6.4C.2.1	Error Vector Magnitude for SUL.....	859
6.4C.2.2	Carrier leakage for SUL.....	862
6.4C.2.3	In-band emissions for SUL.....	863
6.4C.2.4	EVM equalizer spectrum flatness for SUL.....	864
6.4C.2.5	EVM equalizer spectrum flatness for Pi/2 BPSK for SUL.....	865
6.4D	Transmit signal quality for UL MIMO.....	868
6.4D.1	Frequency error for UL MIMO.....	868
6.4D.2	Transmit modulation quality for UL MIMO.....	870
6.4D.2.1	Error Vector Magnitude for UL MIMO.....	870
6.4D.2.2	Carrier leakage for UL MIMO.....	873
6.4D.2.3	In-band emissions for UL MIMO.....	876
6.4D.2.4	EVM equalizer spectrum flatness for UL MIMO.....	879
6.4D.3	Time alignment error for UL MIMO.....	882
6.4D.4	Requirements for coherent UL MIMO.....	884
6.4E	Transmit signal quality for V2X.....	886
6.4E.1	Frequency error for V2X.....	886
6.4E.2	Transmit modulation quality for V2X.....	886
6.4E.2.1	General.....	886
6.4E.2.2	Error Vector Magnitude for V2X.....	886
6.4E.2.2.1	Error Vector Magnitude for V2X / non-concurrent operation.....	886
6.4E.2.2.1D	Error Vector Magnitude for V2X / non-concurrent operation / SL-MIMO.....	888
6.4E.2.4	In-band emissions for V2X.....	890
6.4E.2.4.1	In-band emissions for V2X / non-concurrent operation.....	890
6.4E.2.4.1D	In-band emissions for V2X / non-concurrent operation / SL-MIMO.....	893
6.4E.2.4.2	In-band emissions for V2X / con-current operation.....	894
6.4E.2.5	EVM equalizer spectrum flatness for V2X.....	896
6.4E.2.5.1	EVM equalizer spectrum flatness for V2X / non-concurrent operation.....	896
6.4E.2.5.1D	EVM equalizer spectrum flatness for V2X / non-concurrent operation / SL-MIMO.....	898
6.4E.2.5.2	EVM equalizer spectrum flatness for V2X / con-current operation.....	900
6.4F	Transmit signal quality for shared spectrum channel access.....	901
6.4F.1	Frequency error.....	901
6.4G	Transmit signal quality for Tx Diversity.....	902
6.4G.1	Frequency error for Tx Diversity.....	902
$ \Delta f \leq (0.1 \text{ PPM} + 15 \text{ Hz})$	6.4G.2 Transmit modulation quality for Tx Diversity.....	903
6.4G.2.1	Error Vector Magnitude for Tx Diversity.....	903
6.4G.2.2	Carrier leakage for Tx Diversity.....	903
6.4G.2.3	In-band emissions for Tx Diversity.....	904
6.4G.2.4	EVM equalizer spectrum flatness for Tx Diversity.....	906
6.5	Output RF spectrum emissions.....	908
6.5.0	General.....	908
6.5.1	Occupied bandwidth.....	909
6.5.2	Out of band emission.....	911
6.5.2.1	General.....	911
6.5.2.2	Spectrum emission mask.....	911
6.5.2.3	Additional spectrum emission mask.....	921
6.5.2.4	Adjacent channel leakage ratio.....	928
6.5.2.4.1	NR ACLR.....	928
6.5.2.4.2	UTRA ACLR.....	932
6.5.3	Spurious emissions.....	934

6.5.3.1	General spurious emissions	934
6.5.3.2	Spurious emissions for UE co-existence	937
6.5.3.3	Additional spurious emissions	965
6.5.4	Transmit intermodulation	993
6.5A	Output RF spectrum emissions for CA	996
6.5A.1	Occupied bandwidth for CA	996
6.5A.1.0	Minimum conformance requirements.....	996
6.5A.1.0.1	Void	996
6.5A.1.0.1a	Occupied bandwidth for Intra-band contiguous CA	996
6.5A.1.0.2	Occupied bandwidth for Intra-band non-contiguous CA	996
6.5A.1.0.3	Occupied bandwidth for Inter-band CA.....	996
6.5A.1.1	Occupied bandwidth for CA (2UL CA)	996
6.5A.2	Out of band emission for CA	1000
6.5A.2.1	General	1000
6.5A.2.2	Spectrum emission mask	1000
6.5A.2.2.0	Minimum conformance requirements	1000
6.5A.2.2.1	Spectrum emission mask for CA (2UL CA)	1001
6.5A.2.4	Adjacent channel leakage ratio	1008
6.5A.2.4.1	NR ACLR	1008
6.5A.2.4.1.0	Minimum conformance requirements	1008
6.5A.2.4.1.0.3	NR ACLR for Inter-band CA	1009
6.5A.2.4.1.1	NR ACLR for CA (2UL CA)	1009
6.5A.2.4.2	UTRA ACLR	1012
6.5A.2.4.2.0	Minimum conformance requirements	1012
6.5A.2.4.2.1	UTRA ACLR for CA (2UL CA).....	1012
6.5A.3	Spurious emission for CA	1014
6.5A.3.1	General spurious emissions for CA	1014
6.5A.3.1.0	Minimum conformance requirements	1015
6.5A.3.1.1	General spurious emissions for CA (2UL CA)	1015
6.5A.3.2	Spurious emission for UE co-existence	1020
6.5A.3.2.0	Minimum conformance requirements	1021
6.5A.3.2.0.1	Spurious emissions for UE co-existence for intra-band contiguous CA	1021
6.5A.3.2.0.2	Void.....	1023
6.5A.3.2.0.3	Spurious emissions for UE co-existence for Inter-band CA.....	1023
6.5A.3.2.1	Spurious emissions for UE co-existence for CA (2UL CA)	1034
6.5A.4	Transmit intermodulation for CA.....	1053
6.5A.4.0	Minimum conformance requirements.....	1053
6.5A.4.1	Transmit intermodulation for CA (2UL CA).....	1053
6.5B	Output RF spectrum emissions for NR-DC	1056
6.5B.1	Occupied bandwidth for NR-DC.....	1056
6.5B.2	Out of band emission for NR-DC.....	1056
6.5B.2.1	General	1056
6.5B.2.2	Spectrum emission mask	1056
6.5B.2.4	Adjacent channel leakage ratio	1056
6.5B.3	Spurious emission for NR-DC	1056
6.5B.4	Transmit intermodulation for NR-DC.....	1056
6.5C	Output RF spectrum emissions for SUL	1056
6.5C.1	Occupied bandwidth for SUL.....	1057
6.5C.2	Out of band emission for SUL	1058
6.5C.2.1	General	1058
6.5C.2.2	Spectrum emission mask for SUL	1058
6.5C.2.3	Additional spectrum emission mask for SUL.....	1063
6.5C.2.4	Adjacent channel leakage ratio for SUL.....	1064
6.5C.2.4.1	NR ACLR for SUL	1064
6.5C.2.4.2	UTRA ACLR for SUL.....	1065
6.5C.3	Spurious emissions for SUL.....	1066
6.5C.3.1	General spurious emissions for SUL	1066
6.5C.3.2	Spurious emissions for UE co-existence for SUL	1068
6.5C.3.3	Additional spurious emissions for SUL.....	1070
6.5C.4	Transmit intermodulation for SUL.....	1087
6.5D	Output RF spectrum emissions for UL MIMO	1089

6.5D.1	Occupied bandwidth for UL MIMO	1089
6.5D.1_1	Void.....	1091
6.5D.2	Out of band emission for UL MIMO	1091
6.5D.2.1	General	1091
6.5D.2.2	Spectrum emission mask for UL MIMO	1091
6.5D.2.3	Additional spectrum emission mask for UL MIMO.....	1098
6.5D.2.4	Adjacent channel leakage ratio for UL MIMO.....	1102
6.5D.2.4.1	NR ACLR for UL MIMO	1102
6.5D.2.4.2	UTRA ACLR for UL MIMO.....	1104
6.5D.2_1	Void.....	1108
6.5D.3	Spurious emissions for UL MIMO.....	1108
6.5D.3.1	General spurious emissions for UL MIMO	1108
6.5D.3.2	Spurious emissions for UE co-existence for UL MIMO	1110
6.5D.3.3	Additional spurious emissions for UL MIMO.....	1112
6.5D.3_1	Spurious emissions for UL MIMO (Rel-16 onward)	1118
6.5D.3_1.1	General spurious emissions for UL MIMO (Rel-16 onward).....	1118
6.5D.3_1.2	Spurious emission for UE co-existence for UL MIMO (Rel-16 onward)	1120
6.5D.3_1.3	Additional spurious emissions for UL MIMO (Rel-16 onward)	1121
6.5D.4	Transmit intermodulation for UL MIMO.....	1123
6.5E	Output RF spectrum emissions for V2X.....	1125
6.5E.1	Occupied bandwidth for V2X	1125
6.5E.2	Out of band emission for V2X.....	1125
6.5E.2.1	General	1125
6.5E.2.2	Spectrum emission mask for V2X.....	1125
6.5E.2.2.1	Spectrum emission mask for V2X / non-concurrent operation	1125
6.5E.2.2.1D	Spectrum emission mask for V2X / non-concurrent operation / SL-MIMO.....	1130
6.5E.2.3	Additional Spectrum emission mask for V2X.....	1133
6.5E.2.3.1	Additional Spectrum emission mask for V2X / non-concurrent operation	1133
6.5E.2.3.1D	Additional Spectrum emission mask for V2X / non-concurrent operation / SL-MIMO.....	1136
6.5E.2.4	Adjacent channel leakage ratio for V2X.....	1138
6.5E.2.4.1	Adjacent channel leakage ratio for V2X / non-concurrent operation.....	1138
6.5E.2.4.1D	Adjacent channel leakage ratio for V2X / non-concurrent operation / SL-MIMO	1140
6.5E.3	Spurious emissions for V2X	1142
6.5E.3.1	General spurious emissions for V2X.....	1142
6.5E.3.2	Spurious emissions for UE co-existence for V2X	1142
6.5E.3.2.1	Spurious emissions for UE co-existence for V2X / non-concurrent operation	1142
6.5E.3.2.1D	Spurious emissions for UE co-existence for V2X / non-concurrent operation / SL-MIMO.....	1144
6.5E.3.3	Additional spurious emissions requirements for V2X.....	1145
6.5E.3.3.1	Additional spurious emissions requirements for V2X / non-concurrent operation	1145
6.5F	Output RF spectrum emissions for shared spectrum channel access	1147
6.5F.1	Occupied bandwidth for shared spectrum channel access.....	1147
6.5F.2	Out of band emission for shared spectrum channel access.....	1147
6.5F.2.1	General	1147
6.5F.2.2	Spectrum emission mask for operation with shared spectrum channel access	1147
6.5F.2.4	Adjacent channel leakage ratio for operation with shared spectrum channel access.....	1151
6.5F.2.4.1	Shared spectrum channel access ACLR.....	1151
6.5F.3	Spurious emissions for shared spectrum channel access	1153
6.5F.3.1	General spurious emissions	1153
6.5F.3.2	Spurious emissions for UE co-existence	1155
6.5G	Output RF spectrum emissions for Tx Diversity	1155
6.5G.1	Occupied bandwidth for Tx Diversity	1155
6.5G.2	1156	
6.5G.2.1	1156	
6.5G.2.2	1156	
6.5G.2.3	Adjacent channel leakage ratio for Tx Diversity	1156
6.5G.2.3.1	NR ACLR for Tx Diversity	1156
6.5G.3	Spurious emission for Tx Diversity.....	1158
6.5G.3.1	General spurious emissions for Tx Diversity	1158
6.5G.4	Transmit intermodulation for Tx Diversity	1159
7	Receiver characteristics.....	1161
7.1	General.....	1161

7.1A	General.....	1162
7.1I	General.....	1162
7.2	Diversity characteristics.....	1162
7.3	Reference sensitivity.....	1162
7.3.1	General.....	1162
7.3.2	Reference sensitivity power level.....	1162
7.3.3	$\Delta R_{IB,c}$	1196
7.3A	Reference sensitivity for CA.....	1196
7.3A.0	Minimum conformance requirements.....	1196
7.3A.0.1	General.....	1196
7.3A.0.2	Reference sensitivity power level for CA.....	1196
7.3A.0.2.1	Reference sensitivity power level for Intra-band contiguous CA.....	1196
7.3A.0.2.2	Reference sensitivity power level for Intra-band non-contiguous CA.....	1197
7.3A.0.2.3	Reference sensitivity power level for Inter-band CA.....	1197
7.3A.0.2.4	Reference sensitivity power level for SDL bands.....	1197
7.3A.0.3	$\Delta R_{IB,c}$ for CA.....	1200
7.3A.0.3.1	General.....	1200
7.3A.0.3.2	$\Delta R_{IB,c}$ for Inter-band CA.....	1200
7.3A.0.4	Reference sensitivity exceptions due to UL harmonic interference for CA.....	1202
7.3A.0.5	Reference sensitivity exceptions due to intermodulation interference due to 2UL CA.....	1206
7.3A.0.6	Reference sensitivity exceptions due to cross band isolation for CA.....	1224
7.3A.1	Reference sensitivity power level for 2DL CA without exception.....	1226
7.3A.1_1	Reference sensitivity power level for 2DL CA exceptions.....	1234
7.3A.2	Reference sensitivity power level for 3DL CA.....	1256
7.3A.3	Reference sensitivity power level for 4DL CA.....	1261
7.3A.4	Reference sensitivity power level for 5DL CA.....	1268
7.3B	Reference sensitivity for NR-DC.....	1268
7.3C	Reference sensitivity for SUL.....	1268
7.3C.0	Minimum conformance requirements.....	1268
7.3C.0.1	General.....	1268
7.3C.0.2	Minimum conformance requirements for Reference sensitivity power level.....	1268
7.3C.0.3	$\Delta R_{IB,c}$ for SUL.....	1271
7.3C.1	General.....	1272
7.3C.2	Reference sensitivity power level for SUL.....	1272
7.3C.3	Reference sensitivity power level for SUL (3CC).....	1287
7.3D	Reference sensitivity for UL MIMO.....	1287
7.3D.1	General.....	1287
7.3D.2	Reference sensitivity power level for UL MIMO.....	1288
7.3E	Reference sensitivity for V2X.....	1289
7.3E.1	General.....	1289
7.3E.2	Reference sensitivity for V2X / non-concurrent operation.....	1289
7.3F	Reference sensitivity for shared spectrum channel access.....	1292
7.3F.1	General.....	1292
7.3F.2	Reference sensitivity power level.....	1292
7.3F.3	$\Delta R_{IB,c}$	1296
7.3G	Reference sensitivity for Tx Diversity.....	1297
7.3I	Reference sensitivity for RedCap.....	1297
7.3I.1	General.....	1297
7.3I.2	Reference sensitivity power level.....	1297
7.4	Maximum input level.....	1321
7.4A	Maximum input level for CA.....	1323
7.4A.0	Minimum conformance requirements.....	1323
7.4A.0.1	Maximum input level for Intra-band contiguous CA.....	1323
7.4A.0.2	Maximum input level for Intra-band non-contiguous CA.....	1324
7.4A.0.3	Maximum input level for Inter-band CA.....	1324
7.4A.1	Maximum input level for CA (2DL CA).....	1324
7.4A.2	Maximum input level for CA (3DL CA).....	1328
7.4A.3	Maximum input level for CA (4DL CA).....	1333
7.4B	Maximum input level for NR-DC.....	1338
7.4D	Maximum input level for UL MIMO.....	1338
7.5	Adjacent channel selectivity.....	1340

7.5A	Adjacent channel selectivity for CA	1347
7.5A.0	Minimum conformance requirements	1347
7.5A.0.1	Adjacent channel selectivity for Intra-band contiguous CA	1347
7.5A.0.2	Adjacent channel selectivity Intra-band non-contiguous CA	1349
7.5A.0.3	Adjacent channel selectivity Inter-band CA	1350
7.5A.1	Adjacent channel selectivity for CA (2DL CA)	1350
7.5A.2	Adjacent channel selectivity for 3DL CA	1365
7.5A.3	Adjacent channel selectivity for 4DL CA	1374
7.5B	Adjacent channel selectivity for NR-DC	1384
7.5D	Adjacent channel selectivity for UL MIMO	1384
7.5F	Adjacent channel selectivity	1386
7.5F.1	Adjacent channel selectivity for shared spectrum channel access	1386
7.6	Blocking characteristics	1389
7.6.1	General	1389
7.6.2	In-band blocking	1389
7.6.3	Out-of-band blocking	1395
7.6.4	Narrow band blocking	1401
7.6A	Blocking characteristics for CA	1404
7.6A.1	General	1404
7.6A.2	Inband blocking for CA	1404
7.6A.2.0	Minimum requirements	1404
7.6A.2.0.1	In-band blocking for Intra-band contiguous CA	1404
7.6A.2.0.2	In-band blocking for Intra-band non-contiguous CA	1406
7.6A.2.0.3	In-band blocking for Inter-band CA	1406
7.6A.2.1	In-band blocking for CA (2DL CA)	1407
7.6A.2.2	In-band Blocking for CA (3DL CA)	1415
7.6A.2.3	In-band Blocking for CA (4DL CA)	1423
7.6A.3	Out-of-band blocking for CA	1431
7.6A.3.0	Minimum conformance requirements	1431
7.6A.3.0.1	Out-of-band blocking for Intra-band contiguous CA	1431
7.6A.3.0.2	Out-of-band blocking for Intra-band non-contiguous CA	1432
7.6A.3.0.3	Out-of-band blocking for Inter-band CA	1432
7.6A.3.1	Out-of-band blocking for CA (2DL CA)	1433
7.6A.3.2	Out-of-band blocking for CA (3DL CA)	1441
7.6A.3.3	Out-of-band blocking for CA (4DL CA)	1448
7.6A.4	Narrow band blocking for CA	1453
7.6A.4.0	Minimum conformance requirements	1453
7.6A.4.0.1	Narrow band blocking for Intra-band contiguous CA	1453
7.6A.4.0.2	Narrow band blocking for Intra-band non-contiguous CA	1453
7.6A.4.0.3	Narrow band blocking for Inter-band CA	1454
7.6A.4.1	Narrow band blocking for CA (2DL CA)	1454
7.6A.4.2	Narrow band blocking for CA (3DL CA)	1459
7.6A.4.3	Narrow band blocking for CA (4DL CA)	1462
7.6B	Blocking characteristics for NR-DC	1465
7.6C	Blocking characteristics for SUL	1465
7.6C.1	General	1465
7.6C.2	In-band blocking for SUL	1465
7.6C.2_1	Inband Blocking for SUL with DL CA	1467
7.6C.2_1.1	Inband Blocking for SUL with 2 DL CA	1467
7.6C.3	Out-of-band blocking for SUL	1470
7.6C.3_1	Out-of-band blocking for SUL with DL CA	1472
7.6C.3_1.1	Out-of-band Blocking for SUL with 2 DL CA	1472
7.6D	Blocking characteristics for UL MIMO	1476
7.6D.1	General	1476
7.6D.2	In-band blocking for UL MIMO	1476
7.6D.3	Out-of-band blocking for UL MIMO	1478
7.6D.4	Narrow band blocking for UL MIMO	1479
7.6E	Blocking characteristics for V2X	1480
7.6E.1	General	1480
7.6E.2	In-band blocking for V2X	1481
7.6E.2.0	Minimum conformance requirements	1481

7.6E.2.1	In-band blocking for V2X / non-concurrent operation	1481
7.6E.2.2	In-band blocking for V2X / con-current operation	1481
7.6E.3	Out-of-band blocking for V2X.....	1482
7.6E.3.0	Minimum conformance requirements.....	1482
7.6E.3.1	Out-of-band blocking for V2X / non-concurrent operation.....	1482
7.6E.3.2	Out-of-band blocking for V2X / con-current operation.....	1482
7.6F	Blocking characteristics for shared spectrum channel access	1482
7.6F.1	General	1482
7.6F.2	In-band blocking	1483
7.6F.2.1	In-band blocking for shared spectrum channel access.....	1483
7.6F.2.1.1	Test purpose.....	1483
7.6F.2.1.2	Test applicability.....	1483
7.6F.2.1.3	Minimum conformance requirements	1483
7.6F.2.1.4	Test description.....	1484
7.6F.2.1.5	Test requirement	1485
7.6F.2.2	In-band blocking for Intra-band contiguous shared spectrum channel access CA	1486
7.6F.3	7.6F.3 Out-of-band blocking.....	1486
7.7	Spurious response	1489
7.7A	Spurious response for CA	1492
7.7A.0	Minimum conformance requirements	1492
7.7A.0.1	Minimum conformance requirements for intra-band contiguous CA.....	1492
7.7A.0.2	Void.....	1492
7.7A.0.3	Minimum conformance requirements for inter-band CA	1492
7.7A.0.4	Minimum conformance requirements for intra-band non-contiguous CA.....	1493
7.7A.1	Spurious response for CA (2DL CA)	1493
7.7A.2	Spurious response for 3DL CA	1494
7.7A.3	Spurious response for 4DL CA	1495
7.7B	Spurious response for NR-DC	1496
7.7D	Spurious response for UL MIMO	1496
7.7E	Spurious response for V2X.....	1497
7.7E.0	Minimum conformance requirements	1497
7.7E.1	Spurious response for V2X / non-concurrent operation.....	1498
7.7E.2	Spurious response for V2X / con-current operation.....	1498
7.7F	Spurious response for shared spectrum channel access	1498
7.7F.1	Spurious response for shared spectrum channel access.....	1498
7.7F.1.1	Test Purpose	1498
7.7F.1.2	Test Applicability	1498
7.7F.1.3	Minimum Conformance Requirements	1498
7.7F.1.4	Test Description.....	1499
7.7F.1.5	Test Requirements	1499
7.7F.2	Intra-band contiguous shared spectrum channel access CA.....	1500
7.8	Intermodulation characteristics.....	1500
7.8.1	General	1500
7.8.2	Wide band Intermodulation.....	1500
7.8A	Intermodulation characteristics for CA.....	1505
7.8A.1	General	1505
7.8A.2	Wide band Intermodulation for CA.....	1505
7.8A.2.0	Minimum conformance requirements.....	1505
7.8A.2.0.1	Wide band Intermodulation for Intra-band contiguous CA	1505
7.8A.2.0.2	Wide band intermodulation for Intra-band non-contiguous CA	1506
7.8A.2.0.3	Wide band Intermodulation for Inter-band CA.....	1506
7.8A.2.1	Wide band Intermodulation for CA (2DL CA).....	1507
7.8A.2.2	Wide band Intermodulation for CA (3DL CA).....	1513
7.8A.2.2.5.2	Wide band intermodulation for Inter-band CA	1517
7.8A.2.3	Wide band Intermodulation for CA (4DL CA).....	1518
7.8A.2.3.5.1	Wide band intermodulation for Inter-band CA	1520
7.8B	Intermodulation characteristics for NR-DC	1522
7.8D	Intermodulation characteristics for UL MIMO.....	1522
7.8D.1	General	1522
7.8D.2	Wide band Intermodulation for UL MIMO.....	1522
7.8E	Intermodulation characteristics for V2X.....	1524

7.8E.1	General	1524
7.8E.2	Wide band Intermodulation for V2X	1524
7.8E.2.0	Minimum conformance requirements.....	1524
7.8E.2.1	Wide band Intermodulation for V2X / non-concurrent operation	1524
7.8E.2.2	Wide band Intermodulation for V2X / con-current operation	1524
7.8F	Intermodulation characteristics for shared spectrum channel access	1525
7.8F.1	General	1525
7.8F.2	Wide band Intermodulation.....	1525
7.8.2.1	Test purpose.....	1525
7.8F.2.2	Test applicability	1525
7.8F.2.3	Minimum conformance requirements.....	1525
7.8F.2.4	Test description	1526
7.8F.2.5	Test requirement.....	1528
7.9	Spurious emissions	1528
7.9A	Spurious emissions for CA	1531
7.9A.0	Minimum conformance requirements	1531
7.9A.1	Spurious emissions for CA (2DL CA)	1531
7.9B	Spurious emissions for NR-DC	1533
Annex A (normative): Measurement channels.....		1534
A.1	General	1534
A.2	UL reference measurement channels	1534
A.2.1	General.....	1534
A.2.2	Reference measurement channels for FDD	1535
A.2.2.1	DFT-s-OFDM Pi/2-BPSK.....	1535
A.2.2.2	DFT-s-OFDM QPSK	1536
A.2.2.3	DFT-s-OFDM 16QAM	1537
A.2.2.4	DFT-s-OFDM 64QAM	1538
A.2.2.5	DFT-s-OFDM 256QAM	1539
A.2.2.6	CP-OFDM QPSK.....	1540
A.2.2.7	CP-OFDM 16QAM.....	1542
A.2.2.8	CP-OFDM 64QAM.....	1543
A.2.2.9	CP-OFDM 256QAM.....	1544
A.2.3	Reference measurement channels for TDD	1546
A.2.3.1	DFT-s-OFDM Pi/2-BPSK.....	1546
A.2.3.2	DFT-s-OFDM QPSK	1546
A.2.3.3	DFT-s-OFDM 16QAM	1546
A.2.3.4	DFT-s-OFDM 64QAM	1546
A.2.3.5	DFT-s-OFDM 256QAM	1546
A.2.3.6	CP-OFDM QPSK.....	1546
A.2.3.7	CP-OFDM 16QAM.....	1546
A.2.3.8	CP-OFDM 64QAM.....	1546
A.2.3.9	CP-OFDM 256QAM.....	1546
A.3	DL reference measurement channels	1546
A.3.1	General.....	1546
A.3.2	DL reference measurement channels for FDD.....	1547
A.3.2.1	General	1547
A.3.2.2	FRC for receiver requirements for QPSK	1548
A.3.2.3	FRC for maximum input level for 64QAM.....	1551
A.3.2.4	FRC for maximum input level for 256 QAM.....	1554
A.3.3	DL reference measurement channels for TDD	1557
A.3.3.1	General.....	1557
A.3.3.2	FRC for receiver requirements for QPSK	1559
A.3.3.3	FRC for maximum input level for 64QAM.....	1562
A.3.3.4	FRC for maximum input level for 256 QAM.....	1566
A.4	CSI reference measurement channels.....	1570
A.5	OFDMA Channel Noise Generator (OCNG).....	1570
A.5.1	OCNG Patterns for FDD.....	1570

A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused REs	1570
A.5.2	OCNG Patterns for TDD	1570
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	1570
A.6	1571	
A.7	V2X reference measurement channels	1571
A.7.1	General.....	1571
A.7.2	FRC for V2X receiver requirements for QPSK	1571
A.7.3	FRC for maximum input level for 64QAM	1573
A.7.4	FRC for maximum input level for 256QAM	1574
A.7.5	FRC for transmitter requirements	1576
Annex B (normative):	Propagation Conditions.....	1581
B.0	No interference.....	1581
Annex C (normative):	Downlink physical channels.....	1581
C.0	Downlink signal levels	1581
C.1	General	1582
C.2	Setup.....	1582
C.3	Connection	1583
C.3.0	Measurement of Transmitter Characteristics	1583
C.3.1	Measurement of Receiver Characteristics.....	1584
Annex D (normative):	Characteristics of the Interfering Signal	1585
D.1	General	1585
D.2	Interference signals	1585
Annex E (normative):	Global In-Channel TX-Test	1586
E.1	General	1586
E.2	Signals and results	1586
E.2.1	Basic principle	1586
E.2.2	Output signal of the TX under test.....	1586
E.2.3	Reference signal.....	1587
E.2.4	Measurement results	1587
E.2.5	Measurement points.....	1587
E.3	Signal processing.....	1588
E.3.1	Pre FFT minimization process	1588
E.3.2	Timing of the FFT window.....	1588
E.3.3	Post FFT equalisation	1589
E.4	Derivation of the results	1590
E.4.1	EVM	1590
E.4.2	Averaged EVM.....	1591
E.4.3	In-band emissions measurement	1591
E.4.4	EVM equalizer.....	1594
E.4.4.1	EVM equalizer spectrum flatness	1594
E.4.4.2	EVM equalizer spectral shaping filter.....	1594
E.4.5	Frequency error and Carrier leakage.....	1595
E.4.6	EVM of Demodulation reference symbols (EVM _{DMRS}).....	1595
E.4.6.1	1 st average for EVM _{DMRS}	1596
E.4.6.2	Final average for EVM _{DMRS}	1596
E.4.7	Modified signal under test	1596
E.5	EVM and inband emissions for PUCCH.....	1599
E.5.1	Basic principle	1599
E.5.2	Output signal of the TX under test.....	1599

E.5.3	Reference signal.....	1599
E.5.4	Measurement results	1599
E.5.5	Measurement points.....	1599
E.5.6	Pre FFT minimization process	1600
E.5.7	Timing of the FFT window.....	1600
E.5.8	Post FFT equalisation	1600
E.5.9	Derivation of the results.....	1601
E.5.9.1	EVM _{PUCCH}	1601
E.5.9.2	Averaged EVM _{PUCCH}	1601
E.5.9.3	In-band emissions measurement	1602
E.6	EVM for PRACH.....	1603
E.6.1	Basic principle	1603
E.6.2	Output signal of the TX under test.....	1603
E.6.3	Reference signal.....	1603
E.6.4	Measurement results	1603
E.6.5	Measurement points.....	1604
E.6.6	Pre FFT minimization process	1604
E.6.7	Timing of the FFT window.....	1604
E.6.8	Post FFT equalisation	1605
E.6.9	Derivation of the results.....	1605
E.6.9.1	EVM _{PRACH}	1605
E.6.9.2	Averaged EVM _{PRACH}	1606
Annex F (normative): Measurement uncertainties and Test Tolerances		1606
F.1	Acceptable uncertainty of Test System (normative)	1606
F.1.1	Measurement of test environments	1606
F.1.2	Measurement of transmitter	1608
F.1.3	Measurement of receiver	1621
F.2	Interpretation of measurement results (normative)	1625
F.3	Test Tolerance and Derivation of Test Requirements (informative).....	1626
F.3.1	Measurement of test environments	1626
F.3.2	Measurement of transmitter	1627
F.3.3	Measurement of receiver	1636
F.4	Uplink power window.....	1639
F.4.1	Introduction.....	1639
F.4.2	Setting the power window above a requirement	1639
F.4.2.1	NR FR1	1639
F.4.3	Setting the power window below a requirement.....	1639
F.4.3.1	NR FR1	1639
F.4.4	Setting the power window centred on a target value	1640
F.4.4.1	NR FR1	1640
Annex G (normative): Uplink Physical Channels		1640
G.0	Uplink Signal Levels.....	1640
G.1	General	1640
G.2	Set-up	1643
G.3	Connection	1643
G.3.0	Measurement of Transmitter Characteristics	1643
G.3.1	Measurement of Receiver Characteristics.....	1643
G.3.2	Measurement of Performance Requirements	1643
Annex H (normative): Statistical Testing.....		1645
H.1	General	1645
H.2	Statistical testing of receiver characteristics	1645
H.2.1	General.....	1645

H.2.2	Mapping throughput to error ratio	1645
H.2.3	Design of the test	1646
H.2.4	Numerical definition of the pass fail limits	1647
H.2.5	Pass fail decision rules	1648
H.2.6	Theory to derive the pass fail limits (Informative)	1648
H.2.6.1	Numerical definition of the pass-fail limits	1648
H.2.6.2	Simulation to derive the pass-fail limits for testing 95% throughput	1649
H.2A	Statistical testing of receiver characteristics with CA	1650
H.2A.1	General	1650
H.2A.2	Mapping throughput to error ratio	1650
H.2A.3	Design of the test	1650
H.2A.4	Pass fail decision rules	1650
Annex I (informative):	Change history	1652