

3GPP TS 38.521-4 V17.0.0 (2022-09)

Technical Specification

**3rd Generation Partnership Project;
Technical Specification Group Radio Access Network;
NR;
User Equipment (UE) conformance specification;
Radio transmission and reception;
Part 4: Performance requirements
(Release 17)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and Reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2022, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners
GSM® and the GSM logo are registered and owned by the GSM Association

Contents

Foreword.....	16
1 Scope.....	17
2 References.....	17
3 Definition of terms, symbols and abbreviations.....	18
3.1 Terms.....	18
3.2 Symbols.....	19
3.3 Abbreviations.....	19
4 General.....	20
4.1 Relationship between minimum requirements and test requirements.....	20
4.2 Applicability of minimum requirements.....	21
4.3 Specification suffix information.....	21
4.4 Conducted requirements.....	21
4.4.1 Reference point.....	21
4.4.2 SNR definition.....	21
4.4.3 Noc.....	22
4.4.3.1 Introduction.....	22
4.4.3.2 Noc for NR operating bands in FR1.....	22
4.4.3.2.1 Derivation of Noc values for NR operating bands in FR1.....	22
4.4.4 Es.....	23
4.4.4.1 Introduction.....	23
4.4.4.2 Es for NR operating bands in FR1.....	23
4.4.4.2.1 Derivation of Es values for NR operating bands in FR1.....	23
4.5 Radiated requirements.....	23
4.5.1 Reference point.....	24
4.5.2 SNR definition.....	24
4.5.3 Noc.....	24
4.5.3.1 Introduction.....	24
4.5.3.2 Noc for NR operating bands in FR2.....	25
4.5.3.3 Derivation of Noc values for NR operating bands in FR2.....	25
4.5.4 Angle of arrival.....	26
4.5.5 Es.....	26
4.6 Test coverage across 5G NR connectivity options.....	26
5 Demodulation performance requirements (Conducted requirements).....	26
5.1 General.....	26
5.1.1 Applicability of requirements.....	26
5.1.1.1 General.....	26
5.1.1.2 Applicability of requirements for different number of RX antenna ports.....	27
5.1.1.3 Applicability of requirements for optional UE features.....	27
5.1.1.4 Applicability of requirements for mandatory UE features with capability signalling.....	29
5.1.1.5 Applicability of CA requirements.....	33
5.1.1.5.1 Definition of CA capability.....	33
5.1.1.5.2 Applicability and test rules for different CA configurations and bandwidth combination sets.....	33
5.1.1.5.3 Applicability rule and antenna connection for CA tests with 4 RX.....	35
5.1.1.6 Applicability and test rules for PDSCH performance requirements with power imbalance for intra-band contiguous CA.....	35
5.1.1.7 Applicability of different requirements for HST.....	35
5.1.1.8 Applicability of different requirements with Multi-TRxP.....	36
5.2 PDSCH demodulation requirements.....	36
5.2.1 1RX requirements (Void).....	40
5.2.2 2RX requirements.....	40
5.2.2.1 FDD.....	40
5.2.2.1.1 2Rx FDD FR1 PDSCH mapping Type A performance.....	40
5.2.2.1.1_1 2Rx FDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	41

5.2.2.1.1_2	2Rx FDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with enhanced receiver type 1 for both SA and NSA.....	45
5.2.2.1.2	2Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance.....	46
5.2.2.1.2_1	2Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	47
5.2.2.1.3	2Rx FDD FR1 PDSCH mapping Type B performance	49
5.2.2.1.3_1	2Rx FDD FR1 PDSCH mapping Type B performance - 2x2 MIMO with baseline receiver for both SA and NSA	50
5.2.2.1.4	2Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance	52
5.2.2.1.4_1	2Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x2 MIMO with baseline receiver for both SA and NSA	53
5.2.2.1.5	2Rx FDD FR1 PDSCH 0.001% BLER performance.....	58
5.2.2.1.5_1	2Rx FDD FR1 PDSCH 0.001% BLER performance - 1x2 MIMO with baseline receiver for both SA and NSA	59
5.2.2.1.6	2Rx FDD FR1 PDSCH repetitions over multiple slots performance.....	60
5.2.2.1.6_1	2Rx FDD FR1 PDSCH repetitions over multiple slots performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	61
5.2.2.1.7	2Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance	63
5.2.2.1.7_1	2Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x2 MIMO with baseline receiver for both SA and NSA	64
5.2.2.1.8	2Rx FDD FR1 PDSCH pre-emption performance.....	66
5.2.2.1.8_1	2Rx FDD FR1 PDSCH pre-emption performance - 2x2 MIMO with baseline receiver for both SA and NSA	67
5.2.2.1.9	2Rx FDD FR1 HST-SFN performance.....	70
5.2.2.1.9_1	2Rx FDD FR1 HST-SFN performance - 2x2 MIMO with baseline receiver for both SA and NSA	71
5.2.2.1.10	2Rx FDD FR1 HST DPS performance	73
5.2.2.1.10_1	2Rx FDD FR1 HST-DPS performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	76
5.2.2.1.11	2Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance	82
5.2.2.1.11_1	2Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x2 MIMO for both SA and NSA.....	83
5.2.2.1.12	2Rx FDD FR1 PDSCH Multi-DCI based transmission scheme performance	87
5.2.2.1.12_1	2Rx FDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x2 MIMO for both SA and NSA	89
5.2.2.1.13	2Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance	93
5.2.2.1.13_1	2Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x2 MIMO for both SA and NSA.....	94
5.2.2.1.14	2Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance.....	98
5.2.2.1.14_1	2Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x2 MIMO for both SA and NSA	99
5.2.2.2	TDD.....	104
5.2.2.2.1	2Rx TDD FR1 PDSCH mapping Type A performance	104
5.2.2.2.1_1	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	106
5.2.2.2.1_2	2Rx TDD FR1 PDSCH mapping Type A performance - 2x2 MIMO with enhanced receiver type 1 for both SA and NSA.....	113
5.2.2.2.2	2Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance ...	113
5.2.2.2.2_1	2Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	113
5.2.2.2.3	2Rx TDD FR1 PDSCH mapping Type B performance	118
5.2.2.2.3_1	2Rx TDD FR1 PDSCH mapping Type B performance - 2x2 MIMO with baseline receiver for both SA and NSA	119
5.2.2.2.4	2Rx TDD FR1 PDSCH mapping Type A and LTE-NR coexistence performance.....	121
5.2.2.2.4_1	2Rx TDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x2 MIMO with baseline receiver for both SA and NSA	122
5.2.2.2.5	2Rx TDD FR1 PDSCH 0.001% BLER performance.....	127
5.2.2.2.5_1	2Rx TDD FR1 PDSCH 0.001% BLER performance - 1x2 MIMO with baseline receiver for both SA and NSA	128
5.2.2.2.6	2Rx TDD FR1 PDSCH repetitions over multiple slots performance.....	129
5.2.2.2.6_1	2Rx TDD FR1 PDSCH repetitions over multiple slots performance - 2x2 MIMO with baseline receiver for both SA and NSA.....	130

5.2.2.2.7	2Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance	132
5.2.2.2.7_1	2Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x2 MIMO with baseline receiver for both SA and NSA	133
5.2.2.2.8	2Rx TDD FR1 PDSCH pre-emption performance	135
5.2.2.2.8_1	2Rx TDD FR1 PDSCH pre-emption performance - 2x2 MIMO with baseline receiver for both SA and NSA	136
5.2.2.2.9	2Rx TDD FR1 HST-SFN performance	137
5.2.2.2.9_1	2Rx TDD FR1 HST-SFN performance - 2x2 MIMO with baseline receiver for both SA and NSA	138
5.2.2.2.10	2Rx TDD FR1 HST DPS performance	140
5.2.2.2.10_1	2Rx TDD FR1 HST-DPS performance - 2x2 MIMO with baseline receiver for both SA and NSA	143
5.2.2.2.11	2Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance	149
5.2.2.2.11_1	2Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x2 MIMO for both SA and NSA	150
5.2.2.2.12	2Rx TDD FR1 PDSCH Multi-DCI based transmission scheme performance	154
5.2.2.2.12_1	2Rx TDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x2 MIMO for both SA and NSA	156
5.2.2.2.13	2Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance	157
5.2.2.2.13_1	2Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x2 MIMO for both SA and NSA	158
5.2.2.2.14	2Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance	159
5.2.2.2.14_1	2Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x2 MIMO for both SA and NSA	161
5.2.3	4RX requirements	162
5.2.3.1	FDD	162
5.2.3.1.1	4Rx FDD FR1 PDSCH mapping Type A performance	162
5.2.3.1.1_1	4Rx FDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with baseline receiver for both SA and NSA	164
5.2.3.1.1_2	4Rx FDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with baseline receiver for both SA and NSA	167
5.2.3.1.1_3	FFS	168
5.2.3.1.1_4	4Rx FDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced receiver type 1 for both SA and NSA	168
5.2.3.1.2	4Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance	169
5.2.3.1.2_1	4Rx FDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 4x4 MIMO with baseline receiver for both SA and NSA	170
5.2.3.1.3	4Rx FDD FR1 PDSCH mapping Type B performance	173
5.2.3.1.3_1	4Rx FDD FR1 PDSCH mapping Type B performance - 2x4 MIMO with baseline receiver for both SA and NSA	174
5.2.3.1.4	4Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance	176
5.2.3.1.4_1	4Rx FDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x4 MIMO with baseline receiver for both SA and NSA	177
5.2.3.1.5	4Rx FDD FR1 PDSCH 0.001% BLER performance	178
5.2.3.1.5_1	4Rx FDD FR1 PDSCH 0.001% BLER performance - 1x4 MIMO with baseline receiver for both SA and NSA	179
5.2.3.1.6	4Rx FDD FR1 PDSCH repetitions over multiple slots performance	180
5.2.3.1.6_1	4Rx FDD FR1 PDSCH repetitions over multiple slots performance - 2x4 MIMO with baseline receiver for both SA and NSA	181
5.2.3.1.7	4Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance	183
5.2.3.1.7_1	4Rx FDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x4 MIMO with baseline receiver for both SA and NSA	184
5.2.3.1.8	4Rx FDD FR1 PDSCH pre-emption performance	186
5.2.3.1.8_1	4Rx FDD FR1 PDSCH pre-emption performance - 2x4 MIMO with baseline receiver for both SA and NSA	187
5.2.3.1.9	4Rx FDD FR1 HST-SFN performance	189
5.2.3.1.9_1	4Rx FDD FR1 HST-SFN performance - 2x4 MIMO with baseline receiver for both SA and NSA	190
5.2.3.1.10	4Rx FDD FR1 HST DPS performance	192
5.2.3.1.10_1	4Rx FDD FR1 HST-DPS performance - 2x4 MIMO with baseline receiver for both SA and NSA	195
5.2.3.1.11	4Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance	201

5.2.3.1.11_1	4Rx FDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x4 MIMO for both SA and NSA	202
5.2.3.1.12	4Rx FDD FR1 PDSCH Multi-DCI based transmission scheme performance	206
5.2.3.1.12_1	4Rx FDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x4 MIMO for both SA and NSA	208
5.2.3.1.13	4Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance	212
5.2.3.1.13_1	4Rx FDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x4 MIMO for both SA and NSA	214
5.2.3.1.14	4Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance.....	218
5.2.3.1.14_1	4Rx FDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x4 MIMO for both SA and NSA	219
5.2.3.2	TDD.....	224
5.2.3.2.1	4Rx TDD FR1 PDSCH mapping Type A performance	224
5.2.3.2.1_1	4Rx TDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	227
5.2.3.2.1_2	4Rx TDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with baseline receiver for both SA and NSA.....	234
5.2.3.2.1_3	4Rx TDD FR1 PDSCH mapping Type A performance - 2x4 MIMO with enhanced receiver type 1 for both SA and NSA.....	235
5.2.3.2.1_4	4Rx TDD FR1 PDSCH mapping Type A performance - 4x4 MIMO with enhanced receiver type 1 for both SA and NSA.....	235
5.2.3.2.2	4Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance ...	236
5.2.3.2.2_1	4Rx TDD FR1 PDSCH mapping Type A and CSI-RS overlapped with PDSCH performance - 2x4 MIMO with baseline receiver for both SA and NSA	237
5.2.3.2.3	4Rx TDD FR1 PDSCH mapping Type B performance	239
5.2.3.2.3_1	4Rx TDD FR1 PDSCH mapping Type B performance - 2x4 MIMO with baseline receiver for both SA and NSA	240
5.2.3.2.4	4Rx TDD FR1 PDSCH mapping Type A performance	242
5.2.3.2.4_1	4Rx TDD FR1 PDSCH Mapping Type A and LTE-NR coexistence performance - 4x4 MIMO with baseline receiver for both SA and NSA	243
5.2.3.2.5	4Rx TDD FR1 PDSCH 0.001% BLER performance.....	244
5.2.3.2.5_1	4Rx TDD FR1 PDSCH 0.001% BLER performance - 1x4 MIMO with baseline receiver for both SA and NSA	245
5.2.3.2.6	4Rx TDD FR1 PDSCH repetitions over multiple slots performance.....	247
5.2.3.2.6_1	4Rx TDD FR1 PDSCH repetitions over multiple slots performance - 2x4 MIMO with baseline receiver for both SA and NSA.....	248
5.2.3.2.7	4Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance	250
5.2.3.2.7_1	4Rx TDD FR1 PDSCH Mapping Type B and UE processing capability 2 performance - 2x4 MIMO with baseline receiver for both SA and NSA	251
5.2.3.2.8	4Rx TDD FR1 PDSCH pre-emption performance	253
5.2.3.2.8_1	4Rx TDD FR1 PDSCH pre-emption performance - 2x4 MIMO with baseline receiver for both SA and NSA	254
5.2.3.2.9	4Rx TDD FR1 HST-SFN performance.....	255
5.2.3.2.9_1	4Rx TDD FR1 HST-SFN performance - 2x4 MIMO with baseline receiver for both SA and NSA	256
5.2.3.2.10	4Rx TDD FR1 HST DPS performance	258
5.2.3.2.10_1	4Rx TDD FR1 HST DPS performance - 2x4 MIMO with baseline receiver for both SA and NSA	260
5.2.3.2.11	4Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance	265
5.2.3.2.11_1	2Rx TDD FR1 PDSCH Single-DCI based SDM scheme performance - 2x2 MIMO for both SA and NSA	267
5.2.3.2.12	4Rx TDD FR1 PDSCH Multi-DCI based transmission scheme performance.....	271
5.2.3.2.12_1	4Rx TDD FR1 PDSCH Multiple-DCI based transmission scheme performance - 2x4 MIMO for both SA and NSA	272
5.2.3.2.13	4Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance	273
5.2.3.2.13_1	4Rx TDD FR1 PDSCH Single-DCI based FDM scheme A performance - 2x4 MIMO for both SA and NSA	275
5.2.3.2.14	4Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance	276
5.2.3.2.14_1	4Rx TDD FR1 PDSCH Single-DCI based Inter-slot TDM scheme performance - 2x4 MIMO for both SA and NSA	278
5.2A	PDSCH demodulation requirements for CA.....	278
5.2A.1	1RX requirements (Void).....	280

5.2.A.2	2RX requirements	280
5.2.A.2.1	Requirements for 2RX normal PDSCH.....	280
5.2.A.2.1.0	Minimum conformance requirements for 2RX normal PDSCH.....	280
5.2.A.2.1.1	2Rx Normal PDSCH Demodulation Performance for CA (2DL CA)	281
5.2.A.2.1.2	2Rx Normal PDSCH Demodulation Performance for CA (3DL CA)	284
5.2.A.2.1.3	2Rx Normal PDSCH Demodulation Performance for CA (4DL CA)	285
5.2.A.2.2	Requirements for 2RX PDSCH carrier aggregation with power imbalance.....	286
5.2.A.2.2.0	Minimum conformance requirements for 2RX PDSCH CA with power imbalance	286
5.2.A.2.2.1	2Rx PDSCH Demodulation Performance for CA with power imbalance (2DL CA)	287
5.2.A.2.2.2	2Rx PDSCH Demodulation Performance for CA with power imbalance (3DL CA)	289
5.2.A.2.2.3	2Rx PDSCH Demodulation Performance for CA with power imbalance (4DL CA)	289
5.2.A.2.4	Requirements for 2RX HST-SFN CA	289
5.2.A.2.4.0	Minimum conformance requirements for 2RX HST-SFN CA PDSCH	289
5.2.A.2.4.1	2Rx Normal Demodulation Performance for HST-SFN CA	292
5.2.A.2.5	Requirements for 2RX PDSCH HST-DPS CA PDSCH.....	295
5.2.A.2.5.0	Minimum conformance requirements for 2RX HST-DPS CA PDSCH	295
5.2.A.2.5.1	2RX PDSCH Demodulation Performance for HST-DPS CA	301
5.2.A.3	4RX requirements	305
5.2.A.3.1	Requirements for 4RX normal PDSCH.....	305
5.2.A.3.1.0	Minimum conformance requirements for 4RX normal PDSCH.....	305
5.2.A.3.1.1	4Rx Normal PDSCH Demodulation Performance for CA (2DL CA)	307
5.2.A.3.1.2	4Rx Normal PDSCH Demodulation Performance for CA (3DL CA)	310
5.2.A.3.1.3	4Rx Normal PDSCH Demodulation Performance for CA (4DL CA)	311
5.2.A.3.2	Requirements for 4RX PDSCH carrier aggregation with power imbalance.....	311
5.2.A.3.2.0	Minimum requirements for carrier aggregation with power imbalance.....	311
5.2.A.3.2.1	4Rx PDSCH Demodulation Performance for CA with power imbalance (2DL CA)	313
5.2.A.3A	2Rx-4RX requirements	314
5.2.A.3A.1	Requirements for 2Rx-4RX normal PDSCH.....	314
5.2.A.3A.1.0	Minimum conformance requirements for 2Rx-4RX normal PDSCH.....	314
5.2.A.3A.1.1	2Rx-4Rx Normal PDSCH Demodulation Performance for CA (2DL CA)	315
5.2.A.3A.1.2	2Rx-4Rx Normal PDSCH Demodulation Performance for CA (3DL CA)	318
5.2.A.3A.1.3	2Rx-4Rx Normal PDSCH Demodulation Performance for CA (4DL CA)	319
5.3	PDCCH demodulation requirements	319
5.3.1	1RX requirements	321
5.3.2	2RX requirements	321
5.3.2.1	FDD.....	321
5.3.2.1.1	2Rx FDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA.....	321
5.3.2.1.2	2Rx FDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA.....	324
5.3.2.1.3	2Rx FDD FR1 PDCCH 1 Tx antenna performance for power saving	327
5.3.2.2	TDD.....	333
5.3.2.2.1	2Rx TDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA	333
5.3.2.2.2	2Rx TDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA	336
5.3.2.2.3	2Rx TDD FR1 PDCCH 1 Tx antenna performance for power saving.....	338
5.3.3	4RX requirements	344
5.3.3.1	FDD.....	344
5.3.3.1.1	4Rx FDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA.....	344
5.3.3.1.2	4Rx FDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA.....	347
5.3.3.1.3	4Rx FDD FR1 PDCCH 1 Tx antenna performance for power saving	350
5.3.3.2	TDD.....	356
5.3.3.2.1	4Rx TDD FR1 PDCCH 1 Tx antenna performance for both SA and NSA	356
5.3.3.2.2	4Rx TDD FR1 PDCCH 2 Tx antenna performance for both SA and NSA	359
5.3.3.2.3	4Rx TDD FR1 PDCCH 1 Tx antenna performance for power saving.....	362
5.4	PBCH demodulation requirements	368
5.5	Sustained downlink data rate provided by lower layers.....	368
5.5.1	FR1 Sustained downlink data rate performance for single carrier	368
5.5.A.1	FR1 Sustained downlink data rate performance for carrier aggregation	376
5.5.A.1.1	FR1 SDR performance for CA (2DLCA)	376
6	CSI reporting requirements (Conducted requirements)	384
6.1	General.....	384
6.1.1	Applicability of requirements.....	384
6.1.1.1	General	384

6.1.1.2	Applicability of requirements for different number of RX antenna ports	384
6.1.1.3	Applicability of requirements for optional UE features	384
6.1.1.4	Applicability of requirements for mandatory UE features with capability signalling	385
6.1.1.5	Applicability of Channel Quality Indicator (CQI) reporting requirements for CA	386
6.1.1.5.1	Applicability and test rules for different duplex modes and SCS combinations	386
6.1.1.5.2	Applicability and test rules for different CA configurations and bandwidth combination sets	386
6.1.1.5.3	Test coverage for different number of component carriers	387
6.1.1.5.4	Applicability rule and antenna connection for CA tests with 4 RX	387
6.1.2	Common test parameters	387
6.2	Reporting of Channel Quality Indicator (CQI)	390
6.2.1	1RX requirements (Void)	390
6.2.2	2RX requirements	390
6.2.2.1	FDD	390
6.2.2.1.1	CQI reporting definition under AWGN conditions	390
6.2.2.1.1.1	2Rx FDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	390
6.2.2.1.1.2	2Rx FDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA	393
6.2.2.1.2	CQI reporting under fading conditions	398
6.2.2.1.2.1	2Rx FDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	398
6.2.2.1.2.2	2Rx FDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	405
6.2.2.2	TDD	410
6.2.2.2.1	CQI Reporting definition under AWGN conditions	410
6.2.2.2.1.1	2Rx TDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	410
6.2.2.2.1.2	2Rx TDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA	413
6.2.2.2.2	CQI reporting under fading conditions	418
6.2.2.2.2.1	2Rx TDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	418
6.2.2.2.2.2	2Rx TDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	422
6.2.3	4RX requirements	426
6.2.3.1	FDD	426
6.2.3.1.1	CQI reporting definition under AWGN conditions	426
6.2.3.1.1.1	4Rx FDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	426
6.2.3.1.1.2	4Rx FDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA	429
6.2.3.1.2	CQI reporting definition under fading conditions	433
6.2.3.1.2.1	4Rx FDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	433
6.2.3.1.2.2	4Rx FDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	437
6.2.3.2	TDD	440
6.2.3.2.1	CQI reporting definition under AWGN conditions	440
6.2.3.2.1.1	4Rx TDD FR1 periodic CQI reporting under AWGN conditions for both SA and NSA	440
6.2.3.2.1.2	4Rx TDD FR1 periodic CQI reporting with Table 3 under AWGN conditions for both SA and NSA	443
6.2.3.2.2	CQI reporting under fading conditions	446
6.2.3.2.2.1	4Rx TDD FR1 periodic wideband CQI reporting under fading conditions for both SA and NSA	446
6.2.3.2.2.2	4Rx TDD FR1 aperiodic subband CQI reporting under fading conditions for both SA and NSA	449
6.2A	Reporting of Channel Quality Indicator (CQI) for CA	452
6.2A.1	General	452
6.2A.2	1RX requirements	452
6.2A.3	2RX requirements	452
6.2A.3.1	CQI reporting definition under AWGN conditions	452
6.2A.3.1.0	Minimum requirement for periodic CQI reporting	452
6.2A.3.1.1	2Rx CQI reporting accuracy under AWGN conditions for CA (2DL CA)	455
6.2A.3.1.2	2Rx CQI reporting accuracy under AWGN conditions for CA (3DL CA)	458
6.2A.3.1.3	2Rx CQI reporting accuracy under AWGN conditions for CA (4DL CA)	459

6.3	Reporting of Precoding Matrix Indicator (PMI)	460
6.3.0	General	460
6.3.1	1RX requirements (Void)	461
6.3.2	2RX requirements	461
6.3.2.1	FDD	461
6.3.2.1.1	2Rx FDD FR1 Single PMI with 4Tx TypeI-SinglePanel codebook for both SA and NSA	461
6.3.2.1.2	2Rx FDD FR1 Single PMI with 8Tx TypeI-SinglePanel codebook for both SA and NSA	466
6.3.2.1.3	2Rx FDD FR1 Multiple PMI with 16Tx Type I – SinglePanel Codebook for both SA and NSA	471
6.3.2.1.4	2Rx FDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA	475
6.3.2.1.5	2Rx FDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA	479
6.3.2.1.6	2Rx FDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA	483
6.3.2.2	TDD	487
6.3.2.2.1	2Rx TDD FR1 Single PMI with 4Tx TypeI-SinglePanel codebook for both SA and NSA	487
6.3.2.2.2	2Rx TDD FR1 Single PMI with 8Tx TypeI-SinglePanel codebook for both SA and NSA	492
6.3.2.2.3	2Rx TDD FR1 Multiple PMI with 16Tx Type1 - SinglePanel codebook for both SA and NSA	497
6.3.2.2.4	2Rx TDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA	502
6.3.2.2.5	2Rx TDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA	507
6.3.2.2.6	2Rx TDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA	511
6.3.3	4RX requirements	516
6.3.3.1	FDD	516
6.3.3.1.1	4Rx FDD FR1 Single PMI with 4Tx TypeI-SinglePanel codebook for both SA and NSA	516
6.3.3.1.2	4Rx FDD FR1 Single PMI with 8Tx TypeI-SinglePanel codebook for both SA and NSA	521
6.3.3.1.3	4Rx FDD FR1 Multiple PMI with 16Tx Type I – SinglePanel Codebook for both SA and NSA	526
6.3.3.1.4	4Rx FDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA	530
6.3.3.1.5	4Rx FDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA	534
6.3.3.1.6	4Rx FDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA	538
6.3.3.2	TDD	542
6.3.3.2.1	4Rx TDD FR1 Single PMI with 4Tx TypeI-SinglePanel codebook for both SA and NSA	542
6.3.3.2.2	4Rx TDD FR1 Single PMI with 8Tx TypeI-SinglePanel codebook for both SA and NSA	548
6.3.3.2.3	4Rx TDD FR1 Multiple PMI with 16Tx Type1 - SinglePanel codebook for both SA and NSA	553
6.3.3.2.4	4Rx TDD FR1 Single PMI with 32Tx Type1 - SinglePanel codebook for both SA and NSA	558
6.3.3.2.5	4Rx TDD FR1 Multiple PMI with 16Tx TypeII codebook for both SA and NSA	563
6.3.3.2.6	4Rx TDD FR1 Multiple PMI with 16Tx Enhanced TypeII codebook for both SA and NSA	567
6.4	Reporting of Rank Indicator (RI)	572
6.4.1	1RX requirements (Void)	572
6.4.2	2RX requirements	572
6.4.2.1	FDD	572
6.4.2.1_1	2Rx FDD FR1 RI reporting for both SA and NSA	572
6.4.2.2	TDD	576
6.4.2.2_1	2Rx TDD FR1 RI reporting for both SA and NSA	576
6.4.3	4RX requirements	581
6.4.3.1	FDD	581
6.4.3.1_1	4Rx FDD FR1 RI reporting for both SA and NSA	581
6.4.3.2	TDD	586
6.4.3.2_1	4Rx TDD FR1 RI reporting for both SA and NSA	586
7	Demodulation performance requirements (Radiated requirements)	591
7.1	General	591
7.1.1	Applicability of requirements	591
7.1.1.1	General	591
7.1.1.2	Applicability of requirements for different number of RX antenna ports	591
7.1.1.3	Applicability of requirements for optional UE features	591
7.1.1.4	Applicability of requirements for mandatory UE features with capability signaling	592
7.1.1.5	Applicability of CA requirements	592
7.1.1.5.1	Definition of CA capability	592
7.1.1.5.2	Applicability and test rules for different CA configurations and bandwidth combination sets	592
7.1.1_1	Applicability of test requirements due to maximum achievable SNR	593
7.2	PDSCH demodulation requirements	594
7.2.1	1RX requirements (Void)	597
7.2.2	2RX requirements	597

7.2.2.1	FDD (Void)	597
7.2.2.2	TDD.....	597
7.2.2.2.1	2Rx TDD FR2 PDSCH mapping Type A performance	597
7.2.2.2.1_1	2Rx TDD FR2 PDSCH mapping Type A performance - 2x2 MIMO with baseline receiver for SA and NSA.....	599
7.2.2.2.1_2	2Rx TDD FR2 PDSCH mapping Type A performance - 2x2 MIMO with enhanced type 1 receiver for SA and NSA.....	603
7.2.2.2.1_3	2Rx TDD FR2 PDSCH mapping Type A performance - 2x2 MIMO with 256QAM for SA and NSA (Rel-16 and forward)	604
7.2.2.2.2	2Rx TDD FR2 PDSCH repetitions over multiple slots.....	606
7.2.2.2.2_1	2Rx TDD FR2 PDSCH repetitions over multiple slots - 2x2 MIMO with baseline receiver for SA and NSA	607
7.2.2.2.3	2Rx TDD FR2 PDSCH Mapping Type B.....	609
7.2.2.2.3_1	2Rx TDD FR2 PDSCH mapping Type B performance - 2x2 MIMO with baseline receiver for SA and NSA	610
7.2A	PDSCH demodulation requirements for CA.....	612
7.2A.1	1RX requirements (Void).....	612
7.2A.2	2RX requirements	612
7.2A.2.1	2Rx TDD FR2 CA requirements for normal PDSCH Demodulation Performance for both SA and NSA (2DLCA).....	613
7.2A.2.2	2Rx TDD FR2 CA requirements for normal PDSCH Demodulation Performance for both SA and NSA (3DLCA).....	615
7.3	PDCCH demodulation requirements	616
7.3.1	1RX requirements	618
7.3.2	2RX requirements	618
7.3.2.1	FDD.....	618
7.3.2.2	TDD.....	618
7.3.2.2.1	2Rx TDD FR2 PDCCH 1 Tx antenna performance for both SA and NSA	618
7.3.2.2.2	2Rx TDD FR2 PDCCH 2 Tx antenna performance for both SA and NSA	621
7.3.2.2.3	2Rx TDD FR2 PDCCH 1 Tx antenna performance for power saving.....	624
7.4	PBCH demodulation requirements	628
7.5	Sustained downlink data rate provided by lower layers.....	628
7.5.1	FR2 Sustained downlink data rate performance for single carrier	628
7.5A.1	FR2 Sustained downlink data rate performance for carrier aggregation	636
7.5A.1.1	FR2 SDR performance for CA	636
8	CSI reporting requirements (Radiated requirements).....	639
8.1	General.....	639
8.1.1	Applicability of requirements.....	639
8.1.1.1	General	639
8.1.1.2	Applicability of requirements for different number of RX antenna ports	639
8.1.1.3	Applicability of requirements for optional UE features	639
8.1.1.4	Applicability of requirements for mandatory UE features with capability signalling	640
8.1.1.5	Applicability of Channel Quality Indicator (CQI) reporting requirements for CA	640
8.1.1.5.1	Applicability and test rules for different CA configurations and bandwidth combination sets	640
8.1.1.5.2	Test coverage for different number of component carriers.....	640
8.1.1_1	Applicability of test requirements due to maximum achievable SNR.....	640
8.1.2	Common test parameters.....	641
8.2	Reporting of Channel Quality Indicator (CQI)	644
8.2.1	1RX requirements	644
8.2.2	2RX requirements	644
8.2.2.1	FDD.....	644
8.2.2.2	TDD.....	644
8.2.2.2.1	CQI reporting under AWGN conditions	644
8.2.2.2.1.1	2Rx TDD FR2 periodic wideband CQI reporting under AWGN performance for both SA and NSA	644
8.2.2.2.2	CQI reporting under fading conditions	648
8.2.2.2.2.1	2Rx TDD FR2 aperiodic wideband CQI reporting under fading performance for both SA and NSA	648
8.2.2.2.2.1_1	2Rx TDD FR2 aperiodic CQI wideband reporting under fading performance for both SA and NSA – 256QAM (Rel-16 and forward)	655
8.2A	Reporting of Channel Quality Indicator (CQI) for CA	659

8.2A.1	General	659
8.2A.2	1RX requirements	659
8.2A.3	2RX requirements	659
8.2A.3.1	CQI reporting definition under AWGN conditions	659
8.2A.3.1.0	Minimum requirement for periodic CQI reporting	659
8.2A.3.1.1	2Rx CQI reporting accuracy under AWGN conditions for CA (2DL CA)	661
8.2A.3.1.2	2Rx CQI reporting accuracy under AWGN conditions for CA (3DL CA)	663
8.2A.3.1.3	2Rx CQI reporting accuracy under AWGN conditions for CA (4DL CA)	664
8.3	Reporting of Precoding Matrix Indicator (PMI)	665
8.3.0	General	665
8.3.1	1RX requirements (Void)	665
8.3.2	2RX requirements	665
8.3.2.1	FDD	665
8.3.2.2	TDD	665
8.3.2.2.1	2Rx TDD FR2 Single PMI with 2TX Type1-SinglePanel codebook for both SA and NSA	665
8.4	Reporting of Rank Indicator (RI)	671
8.4.1	1RX requirements	671
8.4.2	2RX requirements	671
8.4.2.1	FDD	671
8.4.2.2	TDD	671
8.4.2.2.1	2Rx TDD FR2 RI reporting for both SA and NSA	671
9	Demodulation performance requirements for interworking	677
9.1	General	677
9.1.1	Applicability of requirements	677
9.1.1.1	Applicability of requirements for optional UE features	678
9.1.1.2	Applicability of requirements for mandatory UE features with capability signalling	678
9.1.2	E-UTRA Cell setup	678
9.1.2.1	FDD	678
9.1.2.2	TDD	679
9.2	Void	680
9.2A	PDSCH Demodulation for CA	680
9.2A.1	NR CA between FR1 and FR2	680
9.2B	PDSCH Demodulation for DC	681
9.2B.1	EN-DC	681
9.2B.1.1	EN-DC within FR1	681
9.2B.1.2	EN-DC including FR2 NR carrier only	681
9.2B.1.3	EN-DC including FR1 and FR2 NR carriers	681
9.2B.2	NR DC between FR1 and FR2	681
9.3	Void	681
9.3A	PDCCH Demodulation for CA	681
9.3A.1	NR CA between FR1 and FR2	681
9.3B	PDCCH Demodulation for DC	681
9.3B.1	EN-DC	681
9.3B.1.1	EN-DC within FR1	681
9.3B.1.2	EN-DC including FR2 NR carrier only	681
9.3B.1.3	EN-DC including FR1 and FR2 NR carriers	682
9.3B.2	NR DC between FR1 and FR2	682
9.4	Void	682
9.4A	SDR test for CA	682
9.4B	SDR test for DC	682
9.4B.1	EN-DC	682
9.4B.1.1	Sustained downlink data rate performance for EN-DC within FR1	682
9.4B.1.2	Sustained downlink data rate performance for EN-DC including FR2 NR carrier	695
9.4B.2	704	
9.4B.3	NE-DC	704
9.4B.3.1	Sustained downlink data rate performance for NE-DC within FR1	704
10	CSI reporting requirements for interworking	704
10.1	General	704
10.1.1	Applicability of requirements	704
10.1.1.1	Applicability of requirements for optional UE features	705

10.1.1.2	Applicability of requirements for mandatory UE features with capability signalling	705
10.2	Void	705
10.2A	Reporting of Channel Quality Indicator (CQI) for CA	705
10.2B	Reporting of Channel Quality Indicator (CQI) for DC	705
10.2B.1	EN-DC	705
10.2B.1.1	EN-DC within FR1	705
10.2B.1.2	EN-DC including FR2 NR carrier	705
10.2B.1.3	EN-DC including FR1 and FR2 NR carriers	705
10.2B.2	NR DC between FR1 and FR2	705
10.3A	Reporting of Precoding Matrix Indicator (PMI) for CA	705
10.3B	Reporting of Precoding Matrix Indicator (PMI) for DC	706
10.3B.1	EN-DC	706
10.3B.1.1	EN-DC within FR1	706
10.3B.1.2	EN-DC including FR2 NR carrier	706
10.3B.1.3	EN-DC including FR1 and FR2 NR carriers	706
10.3B.2	NR DC between FR1 and FR2	706
10.4A	Reporting of Rank Indicator (RI) for CA	706
10.4B	Reporting of Rank Indicator (RI) for DC	706
10.4B.1	EN-DC	706
10.4B.1.1	EN-DC within FR1	706
10.4B.1.2	EN-DC including FR2 NR carrier	706
10.4B.1.3	EN-DC including FR1 and FR2 NR carriers	706
10.4B.2	NR DC between FR1 and FR2	707
11	V2X requirements	707
11.1	Demodulation performance requirements (Conducted requirements)	707
11.1.1	General	707
11.1.1.1	Applicability of requirements	707
11.1.1.1.1	General	707
11.1.1.1.2	Applicability of requirements for mandatory UE V2X features with capability signalling	707
11.1.1.2	Common test parameters	707
11.1.2	PSSCH demodulation requirements	708
11.1.2.1	2Rx requirements	708
11.1.2.1.1	2Rx FR1 PSSCH performance	708
11.1.3	PSCCH demodulation requirements	711
11.1.3.1	2Rx requirements	711
11.1.3.1.1	2Rx FR1 PSCCH performance	711
11.1.4	PSBCH demodulation requirements	713
11.1.4.1	2Rx requirements	713
11.1.4.1.1	2Rx FR1 PSBCH performance	713
11.1.5	PSFCH demodulation requirements	714
11.1.5.1	2Rx requirements	714
11.1.5.1.1	2Rx FR1 PSFCH performance	714
11.1.6	Power imbalance performance with two links	716
11.1.6.1	2Rx requirements	716
11.1.6.1.1	2Rx FR1 Power imbalance performance	716
11.1.7	HARQ buffer soft combining	719
11.1.7.1	2Rx requirements	719
11.1.7.1.1	2Rx FR1 HARQ buffer soft combining performance	719
11.1.8	PSCCH decoding capability test	722
11.1.8.1	2Rx requirements	722
11.1.8.1.1	2Rx FR1 PSCCH decoding capability	722
11.1.9	PSFCH decoding capability Test	725
11.1.9.1	2Rx requirements	725
11.1.9.1.1	2Rx FR1 PSFCH decoding capability	725
Annex A (normative):	Measurement channels	730
A.1	General	730
A.1.1	Throughput definition	730
A.1.2	TDD UL-DL configurations for FR1	730
A.1.3	TDD UL-DL configurations for FR2	733

A.2	UL Reference measurement channels	735
A.2.1	General.....	735
A.2.2	Reference measurement channels for FDD	736
A.2.2.1	RMC for Sustained downlink data rate	736
A.2.2.1.1	CP-OFDM 64QAM	736
A.2.3	Reference measurement channels for TDD	738
A.2.3.1	RMC for Sustained downlink data rate	738
A.2.3.1.1	CP-OFDM 16QAM	738
A.3	DL reference measurement channels	740
A.3.1	General.....	740
A.3.2	Reference measurement channels for PDSCH performance requirements.....	740
A.3.2.1	FDD.....	740
A.3.2.1.1	Reference measurement channels for SCS 15 kHz FR1	740
A.3.2.1.2	Reference measurement channels for SCS 30 kHz FR1	750
A.3.2.1.3	Reference measurement channels for SCS 60 kHz FR1	751
A.3.2.1.4	Reference measurement channels for E-UTRA.....	751
A.3.2.2	TDD	757
A.3.2.2.1	Reference measurement channels for SCS 15 kHz FR1	757
A.3.2.2.2	Reference measurement channels for SCS 30 kHz FR1	758
A.3.2.2.3	Reference measurement channels for SCS 60 kHz FR1	774
A.3.2.2.4	Reference measurement channels for SCS 60 kHz FR2.....	774
A.3.2.2.5	Reference measurement channels for SCS 120 kHz FR2.....	776
A.3.2.2.6	Reference measurement channels for E-UTRA.....	786
A.3.2_1	Reference measurement channels for Sustained downlink data rate performance requirements.....	792
A.3.2_1.1	FDD.....	792
A.3.2_1.1.1	Reference measurement channels for SCS 15 kHz FR1	792
A.3.2_1.2	TDD	793
A.3.2_1.2.1	Reference measurement channels for SCS 30 kHz FR1	793
A.3.3	Reference measurement channels for PDCCH performance requirements	797
A.3.3.1	FDD.....	797
A.3.3.1.1	Reference measurement channels for SCS 15 kHz FR1	797
A.3.3.1.2	Reference measurement channels for SCS 30 kHz FR1	799
A.3.3.2	TDD	799
A.3.3.2.1	Reference measurement channels for SCS 15 kHz FR1	799
A.3.3.2.2	Reference measurement channels for SCS 30 kHz FR1	800
A.3.3.2.3	Reference measurement channels for SCS 60 kHz FR1	802
A.3.3.2.4	Reference measurement channels for SCS 60 kHz FR2.....	802
A.3.3.2.5	Reference measurement channels for SCS 120 kHz FR2.....	802
A.3.4	Reference measurement channels for PBCH demodulation requirements.....	804
A.3.4.1	Reference measurement channels for FR1	804
A.3.4.2	Reference measurement channels for FR2	804
A.4	CSI reference measurement channels.....	804
A.5	OFDMA Channel Noise Generator (OCNG).....	808
A.5.1	OCNG Patterns for FDD.....	808
A.5.1.1	OCNG FDD pattern 1: Generic OCNG FDD Pattern for all unused REs	808
A.5.2	OCNG Patterns for TDD	808
A.5.2.1	OCNG TDD pattern 1: Generic OCNG TDD Pattern for all unused REs	808
A.6	SL reference measurement channels	809
A.6.1	General.....	809
A.6.2	Reference measurement channels for PSSCH performance requirements.....	809
A.6.2.1	Reference measurement channels for SCS 15 kHz FR1	809
A.6.2.2	Reference measurement channels for SCS 30 kHz FR1	809
A.6.3	Reference measurement channels for PSCCH performance requirements.....	809
A.6.3.1	Reference measurement channels for SCS 15 kHz FR1	809
A.6.3.2	Reference measurement channels for SCS 30 kHz FR1	810
A.6.4	Reference measurement for PSBCH performance requirements	810
A.6.4.1	Reference measurement channels for SCS 15 kHz FR1	810
A.6.4.2	Reference measurement channels for SCS 30 kHz FR1	810

Annex B (normative):	Propagation conditions.....	810
B.0	No interference.....	810
B.1	Static propagation condition.....	811
B.1.1	UE Receiver with 2Rx.....	811
B.1.2	UE Receiver with 4Rx.....	811
B.2	Multi-path fading propagation conditions.....	812
B.2.1	Delay profiles.....	812
B.2.1.1	Delay profiles for FR1.....	813
B.2.1.2	Delay profiles for FR2.....	814
B.2.2	Combinations of channel model parameters.....	815
B.2.3	MIMO Channel Correlation Matrices.....	816
B.2.3.1	MIMO Correlation Matrices using Uniform Linear Array (ULA).....	816
B.2.3.1.1	Definition of MIMO Correlation Matrices.....	816
B.2.3.1.2	MIMO Correlation Matrices at High, Medium and Low Level.....	819
B.2.3.2	MIMO Correlation Matrices using Cross Polarized Antennas (X-pol).....	823
B.2.3.2.1	Definition of MIMO Correlation Matrices using cross polarized antennas.....	823
B.2.3.2.2	MIMO Correlation Matrices using cross polarized antennas.....	825
B.2.3.2.3	Beam steering approach.....	828
B.2.3.2.3A	Beam steering approach with dual cluster beams.....	829
B.2.4	Two-tap propagation conditions for CQI tests.....	830
B.3	High Speed Train Scenario.....	831
B.3.1	Single Tap Channel Profile.....	831
B.3.2	HST-SFN Channel Profile.....	834
B.3.3	HST-DPS Channel Profile.....	837
B.4	Physical signals, channels mapping and precoding.....	839
B.4.1	General.....	839
Annex C (normative):	Downlink physical channels.....	841
C.0	Downlink signal levels.....	841
C.0.1	FR1 Downlink Signal Levels (Conducted).....	841
C.0.2	FR2 Downlink Signal Levels (Radiated).....	841
C.1	Setup.....	842
C.1.1	FR1 Setup.....	842
C.1.2	FR2 Setup.....	844
C.2	Connection.....	846
C.2.1	FR1 Measurement of Performance Characteristics.....	846
C.2.2	FR2 Measurement of Performance Characteristics.....	846
Annex D (normative):	E-UTRA link setup config for NSA testing.....	847
D.0	General.....	847
D.1	E-UTRA test parameters.....	847
D.2	E-UTRA configuration.....	849
D.3	E-UTRA link common physical channel setup.....	850
D.4	E-UTRA power level.....	850
D.4.1	E-UTRA power level (conducted).....	850
D.4.2	E-UTRA power level (radiated).....	850
Annex E (normative):	Environmental conditions.....	851
Annex F (normative):	Measurement uncertainties and test tolerances.....	851
F.1	Measurement uncertainties and test tolerances for FR1.....	851
F.1.1	Acceptable uncertainty of test system (normative).....	851
F.1.1.1	Measurement of test environments.....	851

F.1.1.2	Measurement of Demod Performance requirements	851
F.1.1.3	Measurement of Channel State Information reporting	861
F.1.2	Interpretation of measurement results (normative)	865
F.1.3	Test Tolerance and Derivation of Test Requirements (informative)	865
F.1.3.1	Measurement of test environments.....	866
F.1.3.2	Measurement of Demod Performance requirements	866
F.1.3.3	Measurement of Channel State Information reporting	871
F.2	Measurement uncertainties and test tolerances for FR2.....	875
F.2.1	Acceptable uncertainty of test system (normative)	875
F.2.1.1	Measurement of test environments.....	875
F.2.1.2	Measurement of Demod Performance requirements	875
F.2.1.3	Measurement of Channel State Information reporting	878
F.2.2	Interpretation of measurement results (normative)	881
F.2.3	Test Tolerance and Derivation of Test Requirements (informative)	882
F.2.3.1	Measurement of test environments.....	882
F.2.3.2	Measurement of Demod Performance requirements	882
F.2.3.3	Measurement of Channel State Information reporting	884
Annex G (normative): Statistical Testing.....		885
G.1	Statistical testing of Performance Requirements with throughput	885
G.1.1	General.....	885
G.1.2	Mapping throughput to error ratio	885
G.1.3	Design of the test	886
G.1.4	Pass Fail limit	886
G.1.5	Minimum Test time	887
G.2	Theory to derive the numbers for statistical testing (informative).....	890
G.2.1	Error Ratio (ER)	890
G.2.2	Test Design	890
G.2.3	Confidence level	890
G.2.4	Introduction: Supplier Risk versus Customer Risk	890
G.2.5	Supplier Risk versus Customer Risk.....	891
G.2.6	Introduction: Standard test versus early decision concept	891
G.2.7	Standard test versus early decision concept	892
G.2.8	Selectivity	892
G.2.9	Design of the test	893
G.2.10	Simulation to derive the pass fail limits	894
G.3	Measuring throughput ratio.....	895
G.3.1	General.....	895
G.3.2	Establishing SNR.....	895
G.3.3	Measuring T-put	895
G.3.4	Number of samples for throughput ratios	896
G.4	Statistical testing of Performance Requirements with BLER limit.....	896
G.4.1	General.....	896
G.4.2	Design of the test	896
G.4.3	Numerical definition of the pass fail limits for 0.001% BLER.....	896
G.4.4	Simulation to derive the pass-fail limits for 0.001% BLER	902
G.5	Statistical Testing of NR sidelink Performance Requirements – Non concurrent	903
G.5.1	General.....	903
G.5.2	Test method for PSCCH/PSSCH performance using sidelink HARQ feedback	903
G.5.3	Test method for PSFCH performance.....	905
G.5.4	Test time for PSSCH performance requirements with throughput	907
G.5.5	Test time for PSCCH performance requirements with miss-detection probability.....	907
G.5.6	Test time for PSFCH performance requirements with miss-detection probability	908
Annex H: Approach for finding UE direction for FR2 Demod and CSI Testing....		909
H.0	Normative criteria for determining UE direction for Demod and CSI.....	909
H.1	Procedure for finding UE direction.....	909
H.1.1	Using Rx beam peak direction search	909

H.1.2 RSRPB based scan with fallback option to Rx beam peak direction search 909
H.1.3 Isolation based scan with fallback option to Rx beam peak direction search..... 910
H.2 Wireless cable mode isolation procedure..... 911
Annex I (informative): Change history912