

3GPP2 C.S0014-B

Version 1.0

Date: May 2006



3RD GENERATION
PARTNERSHIP
PROJECT 2
"3GPP2"

1

2

3

4

***Enhanced Variable Rate Codec, Speech Service
Option 3 and 68 for Wideband Spread Spectrum
Digital Systems***

COPYRIGHT

3GPP2 and its Organizational Partners claim copyright in this document and individual Organizational Partners may copyright and issue documents or standards publications in individual Organizational Partner's name based on this document. Requests for reproduction of this document should be directed to the 3GPP2 Secretariat at secretariat@3gpp2.org. Requests to reproduce individual Organizational Partner's documents should be directed to that Organizational Partner. See www.3gpp2.org for more information.

FOREWORD

1
2
3
4
5
6
7
8
9
10
11

These technical requirements form a standard for Service Options 3 and 68, enhanced variable rate, two way speech service options known as EVRC and EVRC-B respectively. These service options communicate at one of four channel rates corresponding to the 9600 bps, 4800 bps, 2400, and 1200 bps frame rates. However, Service Option 3 does not use 2400 bps channel frame rate. The speech coder source bit-rate corresponding to the above mentioned 4 channel rate are 8550, 4000, 2000, and 800 bps. Service Option 68 has the capability to operate in multiple operating points at different average rates of operation that can be used for obtaining different system capacity while trading off speech quality gracefully.

This standard does not address the quality or reliability of Service Options 3 and 68, nor does it cover equipment performance or measurement procedures.

NOTES

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25

- 21. The appropriate version of the Minimum Performance Standard for the enhanced variable rate codecs, EVRC, and EVRC-B, provides specifications and measurement methods.
- 42. "Base station" refers to the functions performed on the landline side, which are typically distributed among a cell, a sector of a cell, a mobile switching center, and a personal communications switching center.
- 73. This document uses the following verbal forms: "Shall" and "shall not" identify requirements to be followed strictly to conform to the standard and from which no deviation is permitted. "Should" and "should not" indicate that one of several possibilities is recommended as particularly suitable, without mentioning or excluding others; that a certain course of action is preferred but not necessarily required; or that (in the negative form) a certain possibility or course of action is discouraged but not prohibited. "May" and "need not" indicate a course of action permissible within the limits of the standard. "Can" and "cannot" are used for statements of possibility and capability, whether material, physical, or causal.
- 154. Footnotes appear at various points in this specification to elaborate and further clarify items discussed in the body of the specification.
- 175. Unless indicated otherwise, this document presents numbers in decimal form.

Binary numbers are distinguished in the text by the use of single quotation marks. In some tables, binary values may appear without single quotation marks if table notation clearly specifies that values are binary. The character 'x' is used to represent a binary bit of unspecified value. For example 'xx00010' represents any 8-bit binary value such that the least significant five bits equal '00010'.

Hexadecimal numbers (base 16) are distinguished in the text by use of the form 0x...h, where h...h represents a string of hexadecimal digits. For example, 0x2FA1 represents a number whose binary value is '10111110100001' and whose decimal value is 12913.

NOTES

26. The following conventions apply to mathematical expressions in this standard:

- 3 • $\lfloor x \rfloor$ indicates the largest integer less than or equal to x : $\lfloor 1.1 \rfloor = 1$, $\lfloor 1.0 \rfloor = 1$, and $\lfloor -1.1 \rfloor = -2$.
- 4 • $\lceil x \rceil$ indicates the smallest integer greater than or equal to x : $\lceil 1.1 \rceil = 2$, $\lceil 2.0 \rceil = 2$, and $\lceil -1.1 \rceil = -1$.
- 5
- 6 • $|x|$ indicates the absolute value of x : $|-17| = 17$, $|17| = 17$.
- 7 • \oplus indicates exclusive OR.
- 8 • $\min(x, y)$ indicates the minimum of x and y .
- 9 • $\max(x, y)$ indicates the maximum of x and y .
- 10 • In figures, \times indicates multiplication. In formulas within the text, multiplication is implicit. For
- 11 example, if $h(n)$ and $p_L(n)$ are functions, then $h(n) p_L(n) = h(n) \times p_L(n)$.
- 12 • $x \bmod y$ indicates the remainder after dividing x by y : $x \bmod y = x - (y \lfloor x / y \rfloor)$.
- 13 • $\text{round}(x)$ is traditional rounding: $\text{round}(x) = \text{sign}(x) \lfloor |x| + 0.5 \rfloor$, where

$$\text{sign}(x) = \begin{cases} 1 & x \geq 0 \\ -1 & x < 0 \end{cases}$$

- 15 • \sum indicates summation. If the summation symbol specifies initial and terminal values, and the
- 16 initial value is greater than the terminal value, then the value of the summation is 0. For example,
- 17 if $N=0$, and if $f(n)$ represents an arbitrary function, then

$$\sum_{n=1}^N f(n) = 0.$$

- 19 • The bracket operator, $[]$, isolates individual bits of a binary value. $\text{VAR}[n]$ refers to bit n of the
- 20 binary representation of the value of the variable VAR , such that $\text{VAR}[0]$ is the least significant bit
- 21 of VAR . The value of $\text{VAR}[n]$ is either 0 or 1.
- 22 • Unless otherwise specified $\log(x)$ denotes logarithm at base 10 throughout this document.

1

NORMATIVE REFERENCES

Ref.	Document	
Standards		
N1	<i>Upper Layer (Layer 3) Signalling Standard for cdma2000 Spread Spectrum Systems</i>	C.S0005-A, July, 2000
N2	<i>Discontinuous Transmission (DTX) of Speech in cdma2000® Systems</i>	C.S0076-0 v1.0, December 2005

2

INFORMATIVE REFERENCES

3

Ref.	Document	
Standards		
S1	<i>Telecommunications Telephone Terminal Equipment Transmission Requirements for Digital Wireline Telephones</i>	ANSI/EIA/TIA-579-A-98
S2	<i>Pulse Code Modulation (PCM) of Voice Frequencies</i>	ITU-T Recommendation G.711, Vol. III, Geneva 1972
S3	<i>Transmission Performance Characteristics of Pulse Code Modulation</i>	ITU-T Recommendation G.712, November 1996
S4	<i>IEEE Standard Methods for Measuring Transmission Performance of Analog and Digital Telephone Sets</i>	IEEE Standard 269-2002, 2002
S5	<i>Method for Determining Objective Loudness Ratings of Telephone Connections</i>	IEEE Standard 661-1979, 1979
S6	<i>Medium Access Control (MAC) Standard for cdma2000 Spread Spectrum Systems</i>	C.S0003-A, July, 2000
S7	<i>Minimum Performance Specification for the Enhanced Variable Rate Codec, Speech Service Option 3 for Spread Spectrum Digital Systems</i>	C.S0018-0 v1.0, December, 1999
S8	<i>Enhanced Variable Rate Codec, Speech Service Option 3 for Wideband Spread Spectrum Digital Systems</i>	C.S0014-A, May, 2004,
S9	<i>Digital network echo cancellers</i>	ITU-T G.168
S10	<i>Operational and interworking requirements for DCEs operating in the text telephone mode</i>	ITU-T V.18
Resources		
R1	<i>Proakis, J. G. and Manolakis, D. G., Introduction to Digital Signal Processing, New York, Macmillan</i>	1988, pp. 721-722
R2	<i>Rabiner, L. R. and Schafer, R. W., Digital Processing of Speech Signals</i>	New Jersey, Prentice-Hall Inc., 1978

Ref.	Document	
R3	<i>Crochiere, R. E. and Rabiner L. R., Multirate Digital Signal Processing</i>	New Jersey, Prentice-Hall Inc., 1983
R4	<i>Oppenheim, A. V. and Schaffer, R. W., Digital Signal Processing</i>	New Jersey, Prentice-Hall Inc., 1975
R5	<i>Proakis, J. G. and Manolakis, D. G., Introduction to Digital Signal Processing</i>	New York, Macmillan, 1988
R6	<i>Dellar, J. R., Proakis, J. G., Hansen, J. H. L., Discrete-Time Processing of Speech Signals</i>	New York, Macmillan, 1993
R7	<i>Alejandro, A., Acoustical and Environmental Robustness in Automatic Speech Recognition</i>	Boston, Kluwer Academic Publishers, 1993
R8	<i>Kleijn, W. B., Kroon, P., and Nahumi, D., The RCELP Speech-Coding Algorithm,</i>	European Transactions on Telecommunications, Vol 5, Number 5. Sept/Oct 1994, pp 573-582
R9	<i>Nahumi, D and Kleijn, W. B., An Improved 8 kb/s RCELP Coder,</i>	IEEE Workshop on Speech Coding, 1995
R10	<i>Atal, B. S. and Schroeder, M. R., Stochastic coding of speech at very low bit rates</i>	Proc Int. Conf. Comm., Amsterdam, 1984, pp 1610-1613
R11	<i>Laflamme, C., Adoul, J-P., Salami, R., Morissette, S., and Mabillean, P., 16 kbps wideband speech coding technique based on algebraic CELP</i>	Proc. ICASSP 1991, pp. 13-16
R12	<i>Salami, R., Laflamme, C., Adoul, J-P., et.al, A Toll Quality 8 kbits Speech coder for Personal Communication Systems (PCS)</i>	IEEE Trans. on Vehicle Technology, 1994
R13	<i>Ashley, J.P., Cruz-Zeno, E.M., Mittal, U., Peng, W., "Wideband coding of speech using a scalable pulse codebook",</i>	2000 IEEE Workshop on Speech Coding, September 2000, pp 148-150.

1
2
3
4

Revision History

Revision	Description	Date
C.S0014-0 v1.0	Release 0, Enhanced Variable Rate Coder Algorithm Description for Service Option 3	December, 1999
C.S0014-A v1.0	Release A, Enhanced Variable Rate Coder Algorithm Description for Service Option 3	May, 2004
C.S0014-B v1.0	Release B, Enhanced Variable Rate Coder Algorithm Description for Service Options 3 and 68	March, 2006

1	Table of Contents	
2	1 GENERAL.....	1-1
3	1.1 General Description	1-1
4	1.2 Service Option Number	1-1
5	1.3 Allowable Delays	1-1
6	1.3.1 Allowable Transmitting Speech Codec Encoding Delay	1-1
7	1.3.2 Allowable Receiving Speech Codec Decoding Delay	1-1
8	1.4 Special Cases.....	1-2
9	1.4.1 Blanked Packets	1-2
10	1.4.2 Null Traffic Channel Data	1-2
11	1.4.3 All Zeros Packet.....	1-2
12	1.5 Terms and Numeric Information.....	1-2
13	2 Required Multiplex Option Support	2-1
14	2.1 Interface to Multiplex Option 1.....	2-1
15	2.1.1 Transmitted Packets	2-1
16	2.1.2 Received Packets	2-1
17	2.2 Negotiation for Service Option 3	2-2
18	2.2.1 Procedures Using Service Option Negotiation	2-2
19	2.2.1.1 Initialization and Connection	2-2
20	2.2.1.1.1 Initialization and Connection in the Mobile Station.....	2-2
21	2.2.1.1.2 Initialization and Connection in the Base Station	2-3
22	2.2.1.2 Service Option Control Orders	2-4
23	2.2.2 Procedures Using Service Negotiation	2-5
24	2.2.2.1 Initialization and Connection	2-6
25	2.2.2.1.1 Mobile Station Requirements	2-6
26	2.2.2.1.2 Base Station Requirements.....	2-6
27	2.2.2.2 Service Option Control Messages.....	2-6
28	2.2.2.2.1 Mobile Station Requirements	2-6
29	2.2.2.2.2 Base Station Requirements	2-7
30	2.3 Service Option Group Assignments.....	2-9
31	2.4 Negotiation for Service Option 68	2-9
32	2.4.1 Procedures using service negotiation.....	2-9

1	2.4.1.1	Initialization and connection.....	2-10
2	2.4.1.2	Service option control messages.....	2-11
3	3	Audio Interfaces.....	3-1
4	3.1	Input Audio Interface.....	3-1
5	3.1.1	Input Audio Interface in the Mobile Station.....	3-1
6	3.1.1.1	Conversion and Scaling.....	3-1
7	3.1.1.2	Digital Audio Input.....	3-1
8	3.1.1.3	Analog Audio Input.....	3-1
9	3.1.1.3.1	Transmit Level Adjustment.....	3-1
10	3.1.1.3.2	Band Pass Filtering.....	3-1
11	3.1.1.3.3	Echo Return Loss.....	3-1
12	3.1.2	Input Audio Interface in the Base Station.....	3-2
13	3.1.2.1	Sampling and Format Conversion.....	3-2
14	3.1.2.2	Transmit Level Adjust.....	3-2
15	3.1.2.3	Line Echo Canceling.....	3-2
16	3.2	Output Audio Interface.....	3-2
17	3.2.1	Output Audio Interface in the Mobile Station.....	3-2
18	3.2.1.1	Band Pass Filtering.....	3-2
19	3.2.1.2	Receive Level Adjustment.....	3-2
20	3.2.2	Output Audio Interface in the Base Station.....	3-2
21	3.2.2.1	Receive Level Adjustment.....	3-3
22	4	Overview.....	4-1
23	4.1	Service Option 3.....	4-1
24	4.2	Service Option 68.....	4-3
25	4.2.1	Pre-processing.....	4-6
26	4.2.2	Rate/coding scheme decision.....	4-7
27	4.2.2.1	Open-loop decision.....	4-7
28	4.2.2.2	Closed-loop decision.....	4-7
29	4.2.2.3	Operating point-switching and dimming.....	4-7
30	4.2.2.4	Arbitrary capacity operating point operation.....	4-8
31	4.2.3	Full-rate CELP and half-rate CELP.....	4-9
32	4.2.4	Full-rate PPP and quarter-rate PPP and special Half-rate PPP.....	4-10

1	4.2.4.1	Background.....	4-10
2	4.2.4.2	PPP Model.....	4-11
3	4.2.4.3	Further processing of PPP frames.....	4-12
4	4.2.4.4	Amplitude Quantization.....	4-12
5	4.2.4.5	Phase Quantization.....	4-14
6	4.2.4.6	Special half-rate PPP frame.....	4-16
7	4.2.4.7	Detection of outliers.....	4-17
8	4.2.5	Frame erasure handling.....	4-17
9	4.2.6	Bad rate/packet handling.....	4-17
10	4.3	Input Signal Preprocessing.....	4-17
11	4.3.1	High-Pass Filter.....	4-17
12	4.3.2	Noise Suppression.....	4-18
13	4.3.2.1	Frequency Domain Conversion.....	4-19
14	4.3.2.2	Channel Energy Estimator.....	4-20
15	4.3.2.3	Channel SNR Estimator.....	4-21
16	4.3.2.4	Voice Metric Calculation.....	4-21
17	4.3.2.5	Spectral Deviation Estimator.....	4-21
18	4.3.2.6	Background Noise Update Decision.....	4-22
19	4.3.2.7	SNR Estimate Modification.....	4-24
20	4.3.2.8	Channel Gain Computation.....	4-24
21	4.3.2.9	Frequency Domain Filtering.....	4-25
22	4.3.2.10	Background Noise Estimate Update.....	4-25
23	4.3.2.11	Time Domain Signal Reconstruction.....	4-25
24	4.4	Model Parameter Estimation.....	4-26
25	4.4.1	Formant Filter Parameter Calculation.....	4-27
26	4.4.1.1	Direct Form LPC Parameter Calculation.....	4-27
27	4.4.1.2	Generation of Spectral Transition Indicator (<i>LPCFLAG</i>).....	4-29
28	4.4.1.3	Direct Form LPC to LSP Conversion.....	4-29
29	4.4.2	Generation of the Short-Term Prediction Residual.....	4-30
30	4.4.2.1	LSP Interpolation.....	4-31
31	4.4.2.2	LSP to Direct Form LPC Conversion.....	4-31
32	4.4.2.3	Generation of Residual Samples.....	4-32

1	4.4.3	Calculation of the Delay Estimate and Long-Term Prediction Gain	4-32
2	4.4.3.1	Non-exhaustive Open Loop Delay Search.....	4-33
3	4.4.3.2	Refinement of open loop delay estimate for SO 3	4-33
4	4.4.3.3	Refinement of open loop delay estimate for SO 68.....	4-34
5	4.4.3.4	Long-Term Prediction Gain Calculation	4-34
6	4.4.3.5	Smoothed Delay Estimate and LTP Gain for SO3	4-35
7	4.4.3.6	Smoothed delay estimate and LTP gain for SO 68.....	4-35
8	4.4.3.7	Composite Delay and Gain Calculations for SO 3	4-36
9	4.4.3.8	Composite delay and gain calculations for SO 68.....	4-36
10	4.5	Determining the Data Rate for SO 3 and Voice Activity Detection for SO 68.....	4-37
11	4.5.1	Estimating the Data Rate Based on Current Signal Parameters.....	4-38
12	4.5.1.1	Computing Band Energy	4-38
13	4.5.1.2	Calculating Rate Determination Thresholds.....	4-39
14	4.5.1.2.1	SO 3.....	4-40
15	4.5.1.2.2	SO 68.....	4-40
16	4.5.1.3	Comparing Thresholds.....	4-41
17	4.5.1.4	Performing Hangover	4-41
18	4.5.1.4.1	Hangover Table for SO 3	4-42
19	4.5.1.4.2	Hangover Table for SO 68	4-42
20	4.5.1.5	Constraining Rate Selection.....	4-44
21	4.5.2	Updating RDA Parameters.....	4-44
22	4.5.2.1	Updating the Smoothed Band Energy.....	4-44
23	4.5.2.2	Updating the Background Noise Estimate.....	4-44
24	4.5.2.3	Updating the Signal Energy Estimate	4-45
25	4.6	Mode decision and Rate decision for SO 68.....	4-45
26	4.6.1	Pitch-based NACF	4-45
27	4.6.2	Pitch based NACF computation.....	4-47
28	4.6.2.1	Decimation of formant residual (current frames and look-ahead frames).....	4-47
29	4.6.2.2	NACF Computation for the two subframes of current frame	4-47
30	4.6.2.3	NACF computation for the look-ahead frame	4-47
31	4.6.3	Speech Coding Mode decision algorithm	4-48
32	4.6.3.1	Energy and zero crossing rate.....	4-49

1	4.6.4	Rate-decision for SO 68.....	4-59
2	4.6.4.1	Constraining Rate Selection.....	4-59
3	4.7	Quantization of LSP Parameters for SO 3	4-59
4	4.7.1	Computation of Weights.....	4-60
5	4.7.2	Error Matrix Computation	4-61
6	4.7.3	Adjustment of Quantization Error.....	4-61
7	4.7.4	Quantization Search	4-61
8	4.7.5	Generation of Quantized LSP Parameters.....	4-61
9	4.8	Quantization of LSP Parameters for SO 68	4-62
10	4.8.1	Full-rate, half-rate, and quarter-rate unvoiced: delta LSP VQ.....	4-62
11	4.8.2	Full rate LSP VQ	4-63
12	4.8.3	Half Rate LSPVQ	4-65
13	4.8.4	Quarter rate unvoiced LSPVQ	4-66
14	4.8.5	Quarter-rate Voiced LSPVQ.....	4-67
15	4.8.5.1	QPPP LSP quantization Weight Computation.....	4-67
16	4.8.5.2	Constructing the MAVQ memory during frames that are not QPPP	4-68
17	4.8.6	Eighth-rate LSPVQ.....	4-69
18	4.9	Encoding at Rates 1/2 and 1 for SO 3 and SO 68	4-69
19	4.9.1	LSP Quantization	4-70
20	4.9.2	RCELP Shift State Update.....	4-70
21	4.9.3	Delay Encoding.....	4-71
22	4.9.4	Rates 1/2 and 1 Subframe Processing	4-71
23	4.9.4.1	Interpolation of LSP Parameters.....	4-72
24	4.9.4.2	LSP to LPC Conversion.....	4-72
25	4.9.4.3	Zero Input Response Calculation.....	4-72
26	4.9.4.4	Impulse Response Calculation.....	4-72
27	4.9.4.5	Interpolated Delay Estimate Calculation	4-73
28	4.9.4.6	Calculation of the Adaptive Codebook Contribution	4-73
29	4.9.4.7	Modification of the Original Residual	4-73
30	4.9.4.8	Generation of the Weighted Modified Original Speech Vector	4-73
31	4.9.4.9	Closed-Loop Gain Calculation	4-73
32	4.9.4.10	Fixed Codebook Search Target Vector Generation	4-75

1	4.9.4.10.1	Perceptual Domain Target Vector.....	4-75
2	4.9.4.10.2	Conversion of the Target Vector to the Residual Domain.....	4-75
3	4.9.4.10.3	Delay Calculation for Current Subframe.....	4-75
4	4.9.4.11	Fixed Codebook Search.....	4-76
5	4.9.4.12	Fixed codebook gain quantization.....	4-76
6	4.9.4.13	Combined Excitation Vector Computation.....	4-76
7	4.9.4.14	Encoder State Variable Update.....	4-76
8	4.9.5	Computation of the Adaptive Codebook Contribution.....	4-77
9	4.9.5.1	Delay Contour Computation.....	4-77
10	4.9.5.2	Mapping of the Adaptive Codebook to the Delay Contour.....	4-77
11	4.9.6	Modification of the Residual.....	4-78
12	4.9.6.1	Mapping of the Past Modified Residual to the Delay Contour.....	4-79
13	4.9.6.2	Calculation of the Residual Shift Frame Parameters.....	4-79
14	4.9.6.2.1	Search for Pulses in the Subframe Residual.....	4-79
15	4.9.6.2.2	Location of the First Pulse in the Residual.....	4-80
16	4.9.6.2.3	Location of a Pulse Inside of the Lag Window.....	4-81
17	4.9.6.2.4	Shift Frame Boundary Calculation.....	4-81
18	4.9.6.2.5	Shift Decision.....	4-82
19	4.9.6.2.6	Peak to Average Ratio Calculation.....	4-82
20	4.9.6.3	Matching the Residual to the Delay Contour.....	4-83
21	4.9.6.3.1	Computation of the Shift Range.....	4-83
22	4.9.6.3.2	Generation of a Temporary Modified Residual Signal for Matching.....	4-83
23	4.9.6.3.3	Matching the Temporary Modified Residual to the Target Residual.....	4-84
24	4.9.6.3.4	Adjustment of the Accumulated Shift.....	4-84
25	4.9.6.4	Modification of the Residual.....	4-85
26	4.9.6.5	Modified Target Residual Update.....	4-85
27	4.9.7	Computation of the ACELP Fixed Codebook Contribution for SO 3.....	4-86
28	4.9.7.1	Algebraic Codebook Structure, Rate 1.....	4-86
29	4.9.7.2	Algebraic Codebook Search.....	4-87
30	4.9.7.2.1	Pre-setting of Pulse Signs.....	4-89
31	4.9.7.2.2	Non-Exhaustive Pulse Position Search.....	4-89
32	4.9.7.3	Codeword Computation of the Algebraic Codebook.....	4-90

1	4.9.7.4	Algebraic Codebook Structure, Rate 1/2	4-90
2	4.9.8	Computation of the Factorial fixed codebook contribution	4-92
3	4.9.8.1	Fixed codebook structure, Rate 1	4-93
4	4.9.8.2	Codebook search.....	4-94
5	4.9.8.2.1	Pre-setting of pulse signs.....	4-95
6	4.9.8.2.2	Non-exhaustive pulse position search	4-95
7	4.9.8.3	Codeword computation of the factorial codebook.....	4-95
8	4.9.8.4	Converting a code-word to a code-vector.....	4-98
9	4.9.8.5	Codebook structure, Rate 1/2.....	4-99
10	4.9.8.5.1	Converting a Rate 1/2 code-word to a code-vector.....	4-102
11	4.9.8.6	Fixed Codebook Gain Calculation.....	4-103
12	4.10	Voiced encoding (full-rate PPP and quarter-rate PPP).....	4-103
13	4.10.1	Modification of the original residual.....	4-103
14	4.10.2	Prototype pitch period processing	4-103
15	4.10.3	Alignment extraction between two DFS, X_1 , and X_2	4-104
16	4.10.4	Pole-filtering a DFS.....	4-104
17	4.10.5	Zero-filtering a DFS	4-105
18	4.10.6	Applying a phase shift to a DFS.....	4-105
19	4.10.7	Energy of a DFS, X	4-106
20	4.10.8	Converting a DFS from Cartesian to polar representation	4-106
21	4.10.9	Converting a DFS from polar to Cartesian representation	4-106
22	4.10.10	Normalizing the band energy of a DFS in polar representation	4-106
23	4.10.11	Converting the DFS amplitudes to equivalent rectangular bandwidth (ERB) amplitudes ..	4-107
24	4.10.12	LPC power-spectrum.....	4-107
25	4.10.13	Current to previous PPP energy ratio	4-107
26	4.10.14	Full search alignment between two DFS.....	4-108
27	4.10.15	Fine search alignment between two DFS	4-108
28	4.10.16	Weighted alignment search between two DFS, X_1 and X_2	4-108
29	4.10.17	Zero padding a DFS to have the same lag as another DFS	4-109
30	4.10.18	Band-limited correlation between two DFS	4-109
31	4.10.19	Speech domain energy of a DFS	4-109
32	4.10.20	Grouping DFS harmonics into ERB slots	4-110

1	4.10.21	Zero inserting into a DFS	4-110
2	4.10.22	Peak to average ratio of PPP from its DFS.....	4-111
3	4.10.23	Converting ERB amplitudes to DFS amplitudes	4-111
4	4.10.24	Prototype pitch period extraction	4-111
5	4.10.25	Restoring PPP memories if last frame is non-PPP or full-rate PPP.....	4-113
6	4.10.26	Correlation between current and previous PPP	4-113
7	4.10.27	Open-loop coding scheme change.....	4-113
8	4.10.28	Quarter-rate PPP quantization	4-114
9	4.10.28.1	Delta delay quantization	4-114
10	4.10.28.2	ERB differential amplitude quantization	4-114
11	4.10.28.3	ERB differential amplitude dequantization.....	4-117
12	4.10.28.4	Evaluating the quality of quantization	4-118
13	4.10.28.5	Obtaining the dequantized current PPP DFS	4-118
14	4.10.28.6	Copying the phase spectrum of previous PPP DFS	4-119
15	4.10.28.7	Closed loop bump-up from QPPP to full-rate CELP coding scheme	4-119
16	4.10.29	FPPP DFS amplitude vector quantization	4-120
17	4.10.29.1	ERB amplitude dequantization	4-122
18	4.10.29.2	Phase quantization	4-122
19	4.10.29.2.1	Global alignment	4-123
20	4.10.29.2.2	Band alignment	4-123
21	4.10.30	PPP synthesis.....	4-125
22	4.10.30.1	Calculating the expected alignment shift	4-126
23	4.10.30.2	Computing the actual alignment shift and shifting the current PPP	4-126
24	4.10.30.3	Computation of the cubic phase track for the synthesis of one frame of residual	4-126
25	4.10.30.4	Generating the whole frame of residual.....	4-127
26	4.10.31	Perceptual weighting filter update.....	4-127
27	4.11	Encoding at Rate $\frac{1}{4}$ unvoiced for SO 68	4-128
28	4.11.1	Computation and quantization of gains.....	4-128
29	4.11.2	Random number generation	4-129
30	4.11.3	Creation of sparse nonzero excitation	4-130
31	4.11.4	Shaping the excitation	4-130
32	4.11.5	Perceptual weighting filter update.....	4-132

1	4.12	Encoding at Rate 1/8	4-132
2	4.12.1	LSP Quantization	4-132
3	4.12.2	Interpolation of LSP Parameters	4-132
4	4.12.3	LSP to LPC Conversion	4-132
5	4.12.4	Impulse Response Computation	4-133
6	4.12.5	Calculation of the Frame Energy Gain for SO 3	4-133
7	4.12.6	Gain Quantization for SO 3	4-133
8	4.12.7	Calculation of the frame energy gain	4-134
9	4.12.8	Gain quantization	4-135
10	4.12.9	Generation of Rate 1/8 Excitation	4-135
11	4.12.10	Perceptual Weighting Filter Update	4-136
12	4.13	Random Number Generation.....	4-136
13	4.13.1	Uniform Pseudo-Random Number Generation Algorithm.....	4-136
14	4.13.2	Gaussian Pseudo-Random Number Generator.....	4-136
15	4.14	Discontinuous Transmission.....	4-137
16	4.15	Packet Formatting for SO 3	4-138
17	4.16	Packet Formatting for SO 68.....	4-141
18	4.16.1	Special Half NELP frame.....	4-146
19	4.16.2	Packet Level Signaling Interworking Function.....	4-146
20	5	Speech Decoder	5-1
21	5.1	Frame Error Detection.....	5-1
22	5.1.1	Received Packet Type Processing for SO 3.....	5-2
23	5.1.2	Received Packet Type Processing for SO 68.....	5-3
24	5.1.3	Packet Sanitycheck for Badrate Detection for SO 3	5-4
25	5.1.3.1	Delay Parameter Checking	5-4
26	5.1.3.2	Delta Delay Parameter Checking.....	5-4
27	5.1.4	Packet Sanitycheck for Badrate Detection for SO 68	5-4
28	5.1.4.1	Delay parameter checking.....	5-4
29	5.1.4.2	Delta delay parameter checking.....	5-4
30	5.1.4.3	LSP checking	5-4
31	5.1.4.4	Unused bit checking	5-4
32	5.1.4.5	Invalid filter ID.....	5-5

1	5.1.4.6	Invalid transition.....	5-5
2	5.2	Rate 1/2 and 1 CELP Decoding for SO 3 and SO 68.....	5-5
3	5.2.1	Decoding of the LSP Parameters.....	5-6
4	5.2.2	Delay Decoding and Frame Erasure Delay Contour Reconstruction.....	5-6
5	5.2.2.1	Delay Decoding.....	5-6
6	5.2.2.2	Frame Erasure Delay Contour Reconstruction for Rate 1 for SO 3.....	5-6
7	5.2.2.3	Frame erasure delay contour reconstruction for Rate 1 good frame following an Erased Frame	
8		for SO 68	5-6
9	5.2.2.3.1	Delay Reconstruction.....	5-7
10	5.2.2.3.2	Reconstruction of the Delay Contour.....	5-7
11	5.2.2.3.3	Warping of the Adaptive Codebook Memory.....	5-7
12	5.2.2.4	Frame erasure delay contour reconstruction for Rate 1 good frame following a QPPP frame	
13		which follows an Erased Frame in SO 68.....	5-8
14	5.2.2.4.1	Delay reconstruction.....	5-8
15	5.2.2.4.2	Reconstruction of the delay contour.....	5-8
16	5.2.2.4.3	Warping of the adaptive codebook memory.....	5-9
17	5.2.2.5	Smoothing of the Decoded Delay.....	5-9
18	5.2.3	Rates 1/2 and 1 Subframe Decoding.....	5-9
19	5.2.3.1	Interpolation of LSP Parameters.....	5-9
20	5.2.3.2	LSP to LPC Conversion.....	5-9
21	5.2.3.3	Bandwidth Expansion.....	5-9
22	5.2.3.4	Interpolated Delay Estimate Calculation.....	5-10
23	5.2.3.5	Calculation of the Adaptive Codebook Contribution.....	5-10
24	5.2.3.5.1	SO 3.....	5-10
25	5.2.3.5.2	SO 68.....	5-10
26	5.2.3.6	Calculation of the Fixed Codebook Gain.....	5-11
27	5.2.3.7	Computing of the Reconstructed ACELP Fixed Codebook Excitation for SO 3.....	5-11
28	5.2.3.8	Computing of the reconstructed fixed codebook excitation in SO 68.....	5-12
29	5.2.3.9	Decoder Total Excitation Generation.....	5-12
30	5.2.3.10	Adaptive Codebook Memory Update.....	5-12
31	5.2.3.11	Additional Excitation Frame Processing.....	5-12
32	5.2.3.12	Frame expansion or compression in CELP frames in SO 68.....	5-13
33	5.2.3.13	PPP smoothing of CELP frame after erasure in SO 68.....	5-13

1	5.2.3.14	Synthesis of the decoder output signal	5-14
2	5.2.3.15	Synthesis of the Decoder Output Signal	5-14
3	5.3	Rate 1 and Rate 1/4 PPP decoding (FPPP and QPPP) for SO 68	5-14
4	5.3.1	Decoding of the LSP parameters in FPPP	5-14
5	5.3.2	Decoding of the LSP parameters in QPPP	5-14
6	5.3.3	Delay decoding in FPPP	5-15
7	5.3.4	Delay decoding in QPPP	5-15
8	5.3.5	Previous frame delay PPP (QPPP and FPPP)	5-15
9	5.3.6	Interpolation of LSP parameters and LSP to LPC conversion	5-15
10	5.3.7	Restoring PPP memories if last frame is non-PPP or full-rate PPP	5-16
11	5.3.8	ERB amplitude dequantization of full-rate PPP	5-16
12	5.3.9	Phase dequantization of full-rate PPP or Special Half-rate PPP (packet level signaling) frame	5-16
13	5.3.10	Obtaining the dequantized current DFS in QPPP	5-17
14	5.3.11	Copying the phase spectrum of previous PPP DFS	5-17
15	5.3.12	PPP synthesis	5-18
16	5.3.12.1	Frame expansion or compression in PPP synthesis	5-18
17	5.3.13	Synthesis of the decoder output signal in PPP	5-18
18	5.4	Decoding of rate 1/4 unvoiced decoding or special rate-1/2 NELP decoding	5-18
19	5.4.1	Frame expansion or compression in Rate 1/4 NELP decoding	5-19
20	5.5	Rate 1/8 Decoding	5-19
21	5.5.1	Decoding of the LSP parameters	5-19
22	5.5.2	Decoding of the Frame Energy Vector for SO 3	5-19
23	5.5.3	Decoding of the Frame Energy Gain for SO 68	5-20
24	5.5.4	Rate 1/8 Subframe Decoding	5-20
25	5.5.4.1	Rate 1/8 Excitation Generation	5-20
26	5.5.4.2	Interpolation of LSP Parameters	5-21
27	5.5.4.3	LSP to LPC conversion	5-21
28	5.5.4.4	Synthesis of Decoder Output Signal	5-21
29	5.6	Suppressed/Blanked Rate 1/8 decoding	5-21
30	5.6.1	Synthesizing comfort noise	5-22

$$5.6.2 \quad w_g(n) = \begin{cases} \sin^2(\pi(n+0.5)/2D) & ; 0 \leq n < D \\ 1 & ; D \leq n < L \\ \sin^2(\pi(n-L+D+0.5)/2D) & ; L \leq n < L+D \end{cases} \quad (5.6.2-1) \text{ Generating encoded}$$

packet from synthesized noise..... 5-23

5.7 Adaptive Postfilter for SO 3..... 5-24

5.7.1 Tilt Compensation Filter..... 5-24

5.7.2 The Short Term Residual Filter..... 5-25

5.7.3 The Long-term Postfilter..... 5-25

5.7.4 Gain Normalization and Short-Term Postfilter..... 5-26

5.8 Adaptive post filter for SO 68..... 5-26

5.8.1 The short-term residual filter..... 5-28

5.8.2 The long-term post filter..... 5-28

5.8.3 Gain normalization and short-term post filter..... 5-28

5.9 Background Noise Estimation..... 5-29

5.9.1 Frequency Domain Conversion..... 5-30

5.9.2 Channel Energy Estimator..... 5-30

5.9.3 Background Noise Estimate..... 5-31

6 TTY/TDD Extension for SO 3..... 6-1

6.1 Introduction..... 6-1

6.2 Overview..... 6-1

6.3 TTY/TDD Extension..... 6-2

6.3.1 TTY Onset Procedure..... 6-2

6.3.1.1 Encoder TTY Onset Procedure..... 6-2

6.3.1.2 Decoder TTY Onset Procedure..... 6-2

6.3.1.3 TTY_MODE PROCESSING..... 6-3

6.3.1.4 TTY_SILENCE Processing..... 6-3

6.3.2 TTY Header, Baud Rate, and Character Format..... 6-3

6.3.3 Transporting the TTY Information in the Speech Packet..... 6-4

6.3.3.1 Half Rate TTY Mode..... 6-5

6.3.3.2 Interoperability with 45.45 Baud-Only TTY Extensions..... 6-5

6.3.3.3 Reflected Baudot Tones..... 6-6

6.3.4 TTY/TDD Processing Recommendation..... 6-6

1	6.3.5	TTY Encoder Processing	6-7
2	6.3.5.1	TTY Encoder Inputs	6-8
3	6.3.5.2	Dit Classification	6-8
4	6.3.5.3	Dits to Bits	6-8
5	6.3.5.4	TTY Character Classification	6-9
6	6.3.5.5	TTY Baud Rate Determination	6-9
7	6.3.5.6	TTY State Machine.....	6-9
8	6.3.6	TTY/TDD Decoder Processing.....	6-10
9	6.3.6.1	TTY Decoder Inputs	6-10
10	6.3.6.2	Decoding the TTY/TDD Information.....	6-10
11	6.3.6.3	Baudot Generator	6-11
12	6.3.6.4	Tone Generator	6-11
13	7	EVRC-B Data Capabilities	7-1
14	7.1	EVRC-B data capabilities	7-1
15	7.2	TTY/TDD payload format	7-2
16	7.3	Baudot code payload	7-2
17	7.4	DTMF payload format	7-4
18	7.5	TTY/TDD operation	7-4
19	7.5.1	TTY header and character format	7-6
20	7.5.2	TTY encoder processing.....	7-7
21	7.5.2.1	TTY encoder inputs	7-7
22	7.5.2.2	Dit classification	7-8
23	7.5.2.3	Dits to bits.....	7-8
24	7.5.2.4	TTY character classification	7-9
25	7.5.2.5	TTY baud rate determination.....	7-9
26	7.5.2.6	TTY state machine.....	7-10
27	7.5.3	TTY/TDD decoder processing.....	7-10
28	7.5.3.1	TTY decoder inputs	7-10
29	7.5.3.2	Decoding the TTY/TDD information	7-10
30	7.5.3.3	Baudot generator.....	7-11
31	7.5.3.4	Tone generator	7-12
32	7.6	DTMF	7-12

1	7.6.1	DTMF detector.....	7-12
2	7.6.1.1	Description of the DTMF detector.....	7-12
3	7.6.1.2	Input.....	7-12
4	7.6.1.3	Output.....	7-13
5	8	SUMMARY OF NOTATION.....	8-13
6	9	CODEBOOK MEMORIES AND CONSTANTS.....	9-1
7	10	Change History for C.S0014-0 V1.0 EVRC.....	10-1
8			

1	List of Figures	
2	Figure 4.1-1. Speech Encoder Top-Level Diagram.....	4-2
3	Figure 4.2-1 Speech encoder top-level diagram.....	4-5
4	Figure 4.2-2 Speech decoder top-level diagram.....	4-6
5	Figure 4.2-3 Continuous range of COPs.....	4-8
6	Figure 4.2-4 Illustration of the principles of PPP coding.....	4-11
7	Figure 4.2-5 Block diagram of PPP coding scheme.....	4-12
8	Figure 4.2-6 A block diagram of amplitude quantization and dequantization modules.....	4-13
9	Figure 4.2-7 An illustrative non-uniform band partition used PPP quantization.....	4-13
10	Figure 4.2-8 Illustration of the effect of spectral downsampling and upsampling.....	4-14
11	Figure 4.2-9 Demonstration of the effect of a single-band alignment on a single PPP.....	4-15
12	Figure 4.2-10 Demonstration of the effect of multi-band alignments on a single PPP.....	4-16
13	Figure 4.3-1 Noise Suppression Block Diagram.....	4-19
14	Figure 4.6-1 Pitch-based NACF computation.....	4-46
15	Figure 4.6-2 High level diagram of mode decision.....	4-50
16	Figure 4.6-3 $nac_at_pitch[2] > VOICEDTH$ – second subframe NACF of the current frame is high.....	4-50
17	Figure 4.6-4 $nac_at_pitch[2] < UNVOICEDTH$ – second subframe NACF of the current frame is low.....	4-52
18	Figure 4.6-5 $nac_at_pitch[2] = UNVOICEDTH$ && $nac_at_pitch[2] \leq VOICEDTH$	4-55
19	Figure 4.9-1. RCELP Encoding Block Diagram.....	4-70
20	Figure 4.16-1. Speech Decoder Top-Level Diagram.....	5-1
21	Figure 5.4-1 Excitation decoding for rate 1/4 NELP or rate 1/2 special NELP.....	5-18
22	Figure 5.6-1 Comfort Noise Synthesizer Block Diagram.....	5-22
23	Figure 5.9-1 Background Noise Estimator Block Diagram.....	5-30
24	Figure 7.5-1 TTY/TDD processing block diagram.....	7-6
25	Figure 7.5-2 TTY bit history buffer.....	7-9
26	Figure 7.5-3 <code>tty_dec()</code> history buffer.....	7-10

27

1

2 List of Tables

3	Table 2-1 Service Option Group Assignments.....	2-9
4	Table 2-2 Valid service configuration attributes for Service Option 68	2-10
5	Table 2-3 Service Option 68 Encoding rate control parameters	2-12
6	Table 2-4 Service Option Control message type-specific fields	2-12
7	Table 2-5 Service Option Control message type-specific fields	2-13
8	Table 2-6 Service Option 68 encoding rate control parameters	2-14
9	Table 4-1. Bit Allocations by Packet Type.....	4-1
10	Table 4-2 EVRC-B coding schemes.....	4-3
11	Table 4-3 Bit allocations by packet type	4-4
12	Table 4-4. LSP Interpolation Constants	4-31
13	Table 4-5. FIR Filter Coefficients Used for Band Energy Calculations.....	4-38
14	Table 4-6. Threshold Scale Factors as a Function of SNR.....	4-40
15	Table 4-7 Threshold scale factors as a function of SNR	4-40
16	Table 4-8 Threshold scale factors as a function of SNR	4-40
17	Table 4-9 Threshold scale factors as a function of SNR	4-41
18	Table 4-10. Hangover Frames as a Function of SNR.....	4-42
19	Table 4-11 Hangover frames as a function of SNR	4-42
20	Table 4-12 Hangover frames as a function of SNR	4-43
21	Table 4-13 Hangover frames as a function of SNR	4-43
22	Table 4-14 Features used in mode decision	4-49
23	Table 4-15 Mapping of speech mode decision to encoding rate and mode.....	4-59
24	Table 4-16. LSP Parameter Splits	4-60
25	Table 4-17. Number of LSP Codebooks	4-60
26	Table 4-18 LSPVQ parameters for full-rate.....	4-63
27	Table 4-19 Multiple candidate search in full-rate LSPVQ.....	4-65
28	Table 4-20 LSPVQ parameters for half-rate	4-65
29	Table 4-21 Multiple candidate search in half-rate LSPVQ	4-66
30	Table 4-22 LSPVQ parameters for quarter-rate unvoiced.....	4-67
31	Table 4-23. Adaptive Codebook Gain Quantization Table	4-74
32	Table 4-24 Positions of Individual Pulses in the Rate 1 Algebraic Codebook.....	4-86

1	Table 4-25. Codeword for the Track Orders	4-89
2	Table 4-26. Positions of Individual Pulses in the Rate 1/2 Algebraic Codebook.....	4-91
3	Table 4-27 Definitions for full-rate CELP factorial codebook.....	4-96
4	Table 4-28 Pulse positions for half-rate CELP codebook	4-100
5	Table 4-29 Skew table for half-rate CELP codebook	4-101
6	Table 4-30 Pulse positions for half-rate CELP codebook	4-101
7	Table 4-31. Packet Formats.....	4-138
8	Table 4-32: Packet formatting for Full-rate CELP	4-141
9	Table 4-33: Packet formatting for Full-rate PPP	4-142
10	Table 4-34: Packet formatting for Half-rate CELP	4-143
11	Table 4-35: Packet formatting for Special Half-rate CELP.....	4-144
12	Table 4-36: Packet formatting for Special Half-rate PPP.....	4-144
13	Table 4-37: Packet formatting for Special Half-rate NELP	4-145
14	Table 4-38: Packet formatting for Quarter-rate NELP	4-145
15	Table 4-39: Packet formatting for Quarter-rate PPP	4-146
16	Table 4-40: Packet formatting for Eighth-Rate	4-146
17	Table 5-1 Received Packet Type Decoding	5-2
18	Table 5-2 Received Packet Type Decoding	5-3
19	Table 5-3. Postfilter Coefficients	5-25
20	Table 7-1 Bit allocation for rate 1/2 data frames.....	7-1
21	Table 7-2 Illegal codeword value.....	7-1
22	Table 7-3 Data header description.....	7-2
23	Table 7-4 TTY Type field	7-2
24	Table 7-5 Rate 1/2 packet for TTY/TDD baudot code payload.....	7-3
25	Table 7-6 Rate 1/2 packet with DTMF payload	7-4
26	Table 7-7 DTMF data values.....	7-4
27	Table 7-8 Range of values for TTY/TDD Baudot header field.....	7-7
28	Table 7-9 Range of values for TTY/TDD Baudot character field.....	7-7
29	Table 7-10 Range of values for TTY/TDD baud rate field	7-7
30	Table 7-11 Touch-tone telephone keypad	7-12
31	Table 8-1. Summary of Noise Suppression Notation	8-13
32	Table 8-2. Summary of Model Parameter Estimation Notation	8-3

1 Table 8-3. Summary of Rate Determination Algorithm Notation 8-4

2 Table 9-1. LSP Quantization Table, Rate 1, Codebook 1 9-1

3 Table 9-2. LSP Quantization Table, Rate 1, Codebook 2 9-1

4 Table 9-3. LSP Quantization Table, Rate 1, Codebook 3 9-2

5 Table 9-4. LSP Quantization Table, Rate 1, Codebook 4 9-7

6 Table 9-5. LSP Quantization Table, Rate 1/2, Codebook 1 9-8

7 Table 9-6. LSP Quantization Table, Rate 1/2, Codebook 2 9-10

8 Table 9-7. LSP Quantization Table, Rate 1/2, Codebook 3 9-11

9 Table 9-8. LSP Quantization Table, Rate 1/8, Codebook 1 9-16

10 Table 9-9. LSP Quantization Table, Rate 1/8, Codebook 2 9-17

11 Table 9-10a. Interpolation Filter Coefficients, Cutoff=0.5 (1/2)..... 9-17

12 Table 9-11a. Interpolation Filter Coefficients, Cutoff=0.9 (1/3)..... 9-18

13 Table 9-12. Fixed Codebook Gain Quantization, Rate 1 9-18

14 Table 9-13. Fixed Codebook Gain Quantization, Rate 1/2 9-19

15 Table 9-14. Residual Shift Interpolation Filter Coefficients 9-19

16 Table 9-15. Rate 1/8 Frame Energy Quantization 9-19

17

18

1 GENERAL

1.1 General Description

Service Options 3 and 68 provide two-way voice communications between the base station and the mobile station using the dynamically variable data rate speech codec algorithm described in this standard. The transmitting speech codec takes voice samples and generates an encoded speech packet for every Traffic Channel frame.[†] The receiving station generates a speech packet from every Traffic Channel frame and supplies it to the speech codec for decoding into voice samples.

Speech codecs communicate at one of four rates corresponding to the 9600 bps, 4800 bps, 2400, and 1200 bps frame rates. However, Service Option 3 does not use 2400 bps frame rate.

The specifications defined in Sections 4 and 5 of this document provide the detailed algorithmic description of the EVRC. In the case of a discrepancy between the floating point and algorithmic descriptions, the reference floating point c-code will prevail. The specifications defined in Input Signal Preprocessing (see 4.3), Determining the Data Rate (see 4.5), and Adaptive Postfilter (see 5.7 and 5.8) are optional for implementations intended for varying operational environments (such as in-vehicle hands-free). Any implementations which deviate from the algorithms specified in this standard, shall meet the minimum performance requirements defined in the associated Minimum Performance Specifications.

1.2 Service Option Number

The variable data rate two-way voice service option using the speech codec algorithm described by this standard shall use service option numbers 3 and 68 and shall be called Service Option 3 and 68 respectively.

1.3 Allowable Delays

1.3.1 Allowable Transmitting Speech Codec Encoding Delay

The transmitting speech codec shall supply a packet to the multiplex sublayer no later than 20 ms after it has obtained the last input sample for the current speech frame.

1.3.2 Allowable Receiving Speech Codec Decoding Delay

The receiving decoder shall generate the first sample of speech using parameters from a packet supplied to it by the multiplex sublayer not later than 3 ms after being supplied the packet.

[†] IS-95-A uses the term frame to represent a 20 ms grouping of data on the Traffic Channel. Common speech codec terminology also uses the term frame to represent a quantum of processing. For Service Option 3 and 68, the speech codec frame corresponds to speech sampled over 20 ms. The speech samples are processed into a packet. This packet is transmitted in a Traffic Channel frame.

1 **1.4 Special Cases**

2 1.4.1 Blanked Packets

3 A blanked frame occurs when the transmitting station uses the entire frame for either signaling traffic or
4 secondary traffic. The EVRC does no special encode processing during the generation of a blank packet, i.e.,
5 the generated voice packet is simply not used. The decoder, in turn, treats a blank packet in the same manner as
6 a frame erasure.

7 1.4.2 Null Traffic Channel Data

8 A Rate 1/8 packet with all bits set to '1' is considered as null Traffic Channel data. This packet is declared an
9 erased packet and handled as described in Section 5. If more than 2 consecutive all-ones Rate 1/8 packets are
10 received, the decoder's output shall be muted until a valid packet is received.

11 1.4.3 All Zeros Packet

12 Rate 1 and Rate 1/2 packets with all bits set to '0' shall be considered erased frames and shall be handled as
13 described in Section 5.

14 **1.5 Terms and Numeric Information**

15 **ACB.** Adaptive Codebook.

16 **ACELP.** Algebraic Code Excited Linear Predictive Coding, the algorithm that is used by the EVRC to
17 generate the stochastic component of the excitation.

18 **Autocorrelation Function.** A function showing the relationship of a signal with a time-shifted version of
19 itself.

20 **Base Station.** A station in the Domestic Public Radio Telecommunications Service, other than a mobile
21 station, used for radio communications with mobile stations.

22 **CCITT.** New revisions of CCITT standards will have an ITU designation.

23 **CELP.** See Code Excited Linear Predictive Coding.

24 **Codec.** The combination of an encoder and decoder in series (encoder/decoder).

25 **Code Excited Linear Predictive Coding (CELP).** A speech coding algorithm. CELP codecs use codebook
26 excitation, a long-term pitch prediction filter, and a short-term formant prediction filter.

27 **Codebook.** A set of vectors used by the speech codec in Service Option 3. For each speech codec codebook
28 subframe, one particular vector is chosen and used to excite the speech codec's filters. The codebook vector is
29 chosen to minimize the weighted error between the original and synthesized speech after the pitch and formant
30 synthesis filter coefficients have been determined.

31 **Decoder.** Generally, a device for the translation of a signal from a digital representation into an analog format.
32 For this standard, a device which converts speech encoded in the format specified in this standard to analog or
33 an equivalent PCM representation.

34 **DFS.** Discrete Fourier Series

35 **DFT.** See Discrete Fourier Transform.

- 1 **Discrete Fourier Transform (DFT).** A method of transforming a time domain sequence into a corresponding
2 frequency domain sequence.
- 3 **Encoder.** Generally, a device for the translation of a signal into a digital representation. For this standard, a
4 device which converts speech from an analog or its equivalent PCM representation to the digital representation
5 described in this standard.
- 6 **EVRC.** Enhanced Variable Rate Codec.
- 7 **FCB.** Fixed Codebook.
- 8 **FFT.** See Fast Fourier Transform.
- 9 **Fast Fourier Transform (FFT).** An efficient implementation of the Discrete Fourier Transform.
- 10 **Formant.** A resonant frequency of the human vocal tract causing a peak in the short-term spectrum of speech.
- 11 **IDFT.** See Inverse Discrete Fourier Transform.
- 12 **IIR Filter.** An infinite-duration impulse response filter is a filter for which the output, in response to an
13 impulse input, never totally dies away. This term is usually used in reference to digital filters.
- 14 **Interpolation.** In the speech coder context, a means of smoothing the transitions of estimated parameters from
15 one set to another. Usually a linear function.
- 16 **Inverse Discrete Fourier Transform (IDFT).** A method of transforming a frequency domain sequence into a
17 corresponding time domain sequence.
- 18 **ITU.** International Telecommunication Union.
- 19 **Linear Predictive Coding (LPC).** A method of predicting future samples of a sequence by a linear
20 combination of the previous samples of the same sequence. Linear Predictive Coding is frequently used in
21 reference to a class of speech codecs.
- 22 **Line Spectral Pair (LSP).** A representation of digital filter coefficients in a pseudo-frequency domain. This
23 representation has good quantization and interpolation properties.
- 24 **LPC.** See Linear Predictive Coding.
- 25 **LSB.** Least significant bit.
- 26 **LSP.** See Line Spectral Pair.
- 27 **Mobile Station.** A station in the Domestic Public Radio Telecommunications Service intended to be used
28 while in motion or during halts at unspecified points. It is assumed that mobile stations include portable units
29 (e.g., hand-held personal units) and units installed in vehicles
- 30 **MSB.** Most significant bit.
- 31 **Packet.** The unit of information exchanged between service option applications in the base station and the
32 mobile station.
- 33 **Pitch.** The fundamental frequency in speech caused by the periodic vibration of the human vocal cords.
- 34 **PPP.** Prototype Pitch Period
- 35 **PSTN.** Public Switched Telephone Network.

- 1 **Quantization.** A process that allows one or more data elements to be represented at a lower resolution for the
2 purpose of reducing the effective bandwidth required for transmission or storage of the respective data
3 elements.
- 4 **RCELP.** Relaxed Code Excited Linear Predictive Coding, the speech coding algorithm on which the EVRC is
5 based.
- 6 **Receive Objective Loudness Rating (ROLR).** A measure of receive audio sensitivity. ROLR is a frequency-
7 weighted ratio of the line voltage input signal to a reference encoder to the acoustic output of the receiver.
8 IEEE 269 defines the measurement of sensitivity and IEEE 661 defines the calculation of objective loudness
9 rating.
- 10 **ROLR.** See Receive Objective Loudness Rating.
- 11 **TOLR.** See Transmit Objective Loudness Rating.
- 12 **Transmit Objective Loudness Rating (TOLR).** A measure of transmit audio sensitivity. TOLR is a
13 frequency-weighted ratio of the acoustic input signal at the transmitter to the line voltage output of the
14 reference decoder. IEEE 269 defines the measurement of sensitivity and IEEE 661 defines the calculation of
15 objective loudness rating.
- 16 **WAEPL.** Weighted Acoustic Echo Path Loss. A measure of the echo performance under normal
17 conversation. ANSI/EIA/TIA-579 defines the measurement of WAEPL.
- 18 **Zero Input Response (ZIR).** The filter output caused by the non-zero initial state of the filter when no input is
19 present.
- 20 **Zero State Response (ZSR).** The filter output caused by an input when the initial state of the filter is zero.
- 21 **ZIR.** See Zero Input Response.
- 22 **ZSR.** See Zero State Response.

2 REQUIRED MULTIPLEX OPTION SUPPORT

Service Options 3 and 68 shall support an interface with Multiplex Option 1. Speech packets for Service Options 3 and 68 shall only be transported as primary traffic.

2.1 Interface to Multiplex Option 1

2.1.1 Transmitted Packets

The speech codec shall generate and supply exactly one packet to the multiplex sublayer every 20 milliseconds. The packet contains the service option information bits, which are transmitted as primary traffic. The packet shall be one of four types as shown in Table 2.1.1-1. The number of bits supplied to the multiplex sublayer for each type of packet shall also be as shown in Table 2.1.1-1. Unless otherwise commanded, the speech codec may supply a Rate 1, Rate 1/2, Rate 1/4 or Rate 1/8 packet. Upon command, the speech codec shall generate a Blank packet. Also upon command, the speech codec shall generate a non-blank packet with a maximum rate of Rate 1/2.

A Blank packet contains no bits and is used for blank-and-burst transmission of signaling traffic or secondary traffic (see 6.1.3.3.11 of TIA/EIA/IS-95-A).

Table 2.1.1-1 Packet Types Supplied by Service Options 3 and 68 to the Multiplex Sublayer

Packet Type	Bits per Packet
Rate 1	171
Rate 1/2	80
Rate 1/4	40
Rate 1/8	16
Blank	0

2.1.2 Received Packets

The multiplex sublayer in the receiving station categorizes every received Traffic Channel frame, and supplies the packet type and accompanying bits, if any, to the speech codec as shown in Table 2.1.1-1. The speech codec processes the bits of the packet as described in Section 4. The received packet types shown in Table 2.1.2-1 correspond to the transmitted packet types shown in Table 2.1.1-1. The Blank packet type occurs when the receiving station determines that a blank-and-burst frame for signaling traffic or secondary traffic was transmitted. The Rate 1 with bit errors packet type occurs when the receiving station determines that the frame was transmitted at 9600 bps and the frame has one or more bit errors. The insufficient frame quality packet type occurs when the mobile station is unable to decide upon the data rate of the received frame or when the mobile station detects a frame in error, which does not belong to the Rate 1 with bit errors packet type. Although the Service Option 3 does not utilize Rate 1/4 packets, Multiplex Option 1 is not required to

1 recognize this fact; Service Option 3 is, therefore, responsible for declaring Rate 1/4 frames as having
 2 insufficient frame quality (erasure). Service Option 68 utilizes Rate 1/4 packets.

3
 4 **Table 2.1.2-1 Packet Types Supplied by the Multiplex Sublayer to Service Options 3, and 68**

Packet Type	Bits per Packet
Rate 1	171
Rate 1/2	80
Rate 1/4	40
Rate 1/8	16
Blank	0
Rate 1 with bit errors	171
Insufficient frame quality (erasure)	0

5
 6 **2.2 Negotiation for Service Option 3**

7 The mobile station and base station can negotiate for Service Option 3 using either service option negotiation,
 8 as described in TIA/EIA/IS-95, or service negotiation, as described in IS-95 and ANSI J-STD-008.

9 2.2.1 Procedures Using Service Option Negotiation

10 The mobile station shall perform service option negotiation for Service Option 3 as described in 6.6.4.1.2 of IS-
 11 95-A. The base station shall perform service option negotiation for Service Option 3 as described in 7.6.4.1.2
 12 of IS-95-A.

13 2.2.1.1 Initialization and Connection

14 2.2.1.1.1 Initialization and Connection in the Mobile Station

15 If the mobile station sends a *Service Option Response Order* accepting Service Option 3 in response to
 16 receiving a *Service Option Request Order*, (see 6.6.4.1.2.2.1 of IS-95-A), the mobile station shall initialize and
 17 connect Service Option 3 according to the following:

- 18 • If the mobile station is in the *Conversation Substate*, the mobile station shall complete the initialization
 19 and connection of the transmitting and receiving sides within 200 ms of:
 - 20 • The implicit or explicit action time associated with the *Service Option Request Order* (see
 21 6.6.4.1.5 of IS-95-A), or
 - 22 • The time that the mobile station sends the *Service Option Response Order* accepting Service
 23 Option 3,

24 whichever is later.

- 25 • If the mobile station is not in the *Conversation Substate*, the mobile station shall complete the
 26 initialization and connection of the transmitting side within 200 ms of:
 - 27 • The implicit or explicit action time associated with the *Service Option Request Order*,

- 1 • The time that the mobile station sends the *Service Option Response Order* accepting Service
- 2 Option 3, or
- 3 • The time that the mobile station enters the *Conversation Substate*, whichever is later.
- 4 • If the mobile station is not in the *Conversation Substate*, the mobile station shall complete the
- 5 initialization and connection of the receiving side within 200 ms of:
- 6 • The implicit or explicit action time associated with the *Service Option Request Order*,
- 7 • The time that the mobile station sends the *Service Option Response Order* accepting Service
- 8 Option 3, or
- 9 • If not in the *Conversation Substate*, the time that the mobile station enters the *Waiting for Answer*
- 10 *Substate e*, whichever is later.

11 If the mobile station receives a *Service Option Response Order* accepting its request for Service Option 3 (see
 12 6.6.4.1.2.2.2 of IS-95-A), the mobile station shall initialize and connect Service Option 3 according to the
 13 following:

- 14 • If the mobile station is in the *Conversation Substate e*, the mobile station shall complete the
- 15 initialization and connection of the transmitting and receiving sides within 200 ms of:
- 16 • The implicit or explicit action time associated with the *Service Option Response Order* (see
- 17 6.6.4.1.5 of IS-95-A).
- 18 • If the mobile station is not in the *Conversation Substate*, the mobile station shall complete the
- 19 initialization and connection of the transmitting side within 200 ms of:
- 20 • The implicit or explicit action time associated with the *Service Option Response Order*, or
- 21 • The time that the mobile station enters the *Conversation Substate*, whichever is later.
- 22 • If the mobile station is not in the *Conversation Substate*, the mobile station shall complete the
- 23 initialization and connection of the receiving side within 200 ms of:
- 24 • The implicit or explicit action time associated with the *Service Option Response Order*, or
- 25 • The time that the mobile station enters the *Waiting for Answer Substate*, whichever is later.

26 Service Option 3 initializations are described in Sections 4 and 5.

27 When the transmitting side of Service Option 3 is connected, Service Option 3 shall generate and transfer
 28 packets to the multiplex sublayer. When the receiving side is connected, Service Option 3 shall transfer and
 29 process packets from the multiplex sublayer. Refer to 6.1.3.3.11.3 of IS-95-A when the transmitting side of a
 30 service option is not connected.

31 2.2.1.1.2 Initialization and Connection in the Base Station

32 The base station should wait until the action time associated with the most recently transmitted *Service Option*
 33 *Response Order* or *Service Option Request Order* before initializing and connecting Service Option 3.

34 If the base station accepts Service Option 3 (by sending a *Service Option Response Order* as described in
 35 7.6.4.1.2.2.1 of IS-95-A), it should initialize and connect both the transmitting and receiving side of Service
 36 Option 3 before the called party is connected, so that both the base station and mobile station speech codecs can
 37 stabilize. The base station may defer connecting the land party audio to the speech codec.

38 If the base station receives an acceptance of its request for Service Option 3 (by receiving a *Service Option*
 39 *Response Order* as described in 7.6.4.1.2.2.2 of IS-95-A), it should initialize and connect both the transmitting

1 and receiving side of Service Option 3 before the called party is connected so that both the base station and
 2 mobile station speech codecs can stabilize. The base station may defer connecting the land party audio to the
 3 speech codec.

4 When the transmitting side of Service Option 3 is connected, Service Option 3 shall generate and transfer
 5 packets to the multiplex sublayer. When the receiving side is connected, Service Option 3 shall transfer and
 6 process packets from the multiplex sublayer. Refer to 7.1.3.5.11.3 of IS-95-A when the transmitting side of a
 7 service option is not connected.

8 **2.2.1.2 Service Option Control Orders**

9 The base station may send a *Service Option Control Order* to the mobile station on the Forward Traffic
 10 Channel (see 7.7.4 of IS-95-A). In addition to pending ACTION_TIMES for messages or orders not related to
 11 the *Service Option Control Order* for Service Option 3, the mobile station shall support at least one pending
 12 ACTION_TIME for *Service Option Control Orders* for Service Option 3. The mobile station shall not send a
 13 *Service Option Control Order* for this service option.

14 If Service Option 3 is active, the mobile station shall treat the ORDQ field in the *Service Option Control Order*
 15 as follows:

16 If ORDQ equals 'xxx000x1', then the mobile station shall initialize both the transmitting and receiving sides of
 17 the speech codec as described in Section 4 and 5. The initializations shall begin at the implicit or explicit action
 18 time (see 6.6.4.1.5 of IS-95-A) and shall be completed within 40 ms. In addition, if ORDQ equals 'xxx00011'
 19 then the mobile station should disable the audio output of the speech codec for 1 second after initialization.

20 If Service Option 3 is active and the mobile station receives a *Service Option Control Order* having an ORDQ
 21 field in which the 3 MSBs have values given in Table 2.2.1.2-1, then the mobile station shall generate the
 22 fraction of those packets normally generated as Rate 1 packets (see 4.3) at either Rate 1 or Rate 1/2 as specified
 23 by the corresponding line in the table. The mobile station shall continue to use these fractions until either of the
 24 following events occurs:

- 25 • While Service Option 3 is active, the mobile station receives a *Service Option Control Order* that
- 26 specifies different fractions, or
- 27 • Service Option 3 is initialized.

28 **Table 2.2.1.2-1. Fraction of Packets at Rate 1 and Rate 1/2 with Rate Reduction**

ORDQ (binary)	Fraction of Normally Rate 1 Packets to be Rate 1	Fraction of Normally Rate 1 Packets to be Rate 1/2
000XXXXX	1	0
001XXXXX	3/4	1/4
010XXXXX	1/2	1/2
011XXXXX	1/4	3/4
100XXXXX	0	1

29

The mobile station may use the following procedure to perform this rate reduction: Sequences of N packets as are formed as shown in Table 2.2.1.2-2. The first L packets in this sequence are allowed to be at Rate 1, the next $N-L$ packets are forced to be Rate 1/2. Whenever the rate determination process (see 4.3) selects a rate other than Rate 1, the sequence is reset. This ensures that the first packet in a talk spurt will be at Rate 1, unless ORDQ equals '100XXXXX' or the speech codec has been commanded by the multiplex sublayer to generate other than a Rate 1 packet (see 2.1.1).

Table 2.2.1.2-2. Sequence Parameters for Rate Reduction

ORDQ (binary)	Sequence Length, N	Maximum Number of Contiguous Rate 1 Packets in a Sequence, L	Number of Contiguous Rate 1/2 Packets in a Sequence, N-L
000XXXXX	1	1	0
001XXXXX	4	3	1
010XXXXX	2	1	1
011XXXXX	4	1	3
100XXXXX	1	0	1

Any other *Service Option Control Order* referring to Service Option 3 and having an ORDQ field other than those described in this section shall be rejected using the *Mobile Station Reject Order* with an ORDQ field equal to '00000100' (see Table 6.7.3-1 of IS-95-A).

2.2.2 Procedures Using Service Negotiation

The mobile station and base station shall perform service negotiation for Service Option 3 as described in IS-95 or J-STD-008, and the negotiated service configuration shall include only valid attributes for the service option as specified in Table 2.2.2-1.

Table 2.2.2-1. Valid Service Configuration Attributes for Service Option 3

Service Configuration Attribute	Valid Selections
Forward Multiplex Option	Multiplex Option 1
Reverse Multiplex Option	Multiplex Option 1
Forward Transmission Rates	Rate Set 1 with all rates enabled
Reverse Transmission Rates	Rate Set 1 with all rates enabled
Forward Traffic Type	Primary Traffic
Reverse Traffic Type	Primary Traffic

1 2.2.2.1 Initialization and Connection

2 2.2.2.1.1 Mobile Station Requirements

3 If the mobile station accepts a service configuration, as specified in a *Service Connect Message*, that includes a
4 service option connection using Service Option 3, the mobile station shall perform the following:

- 5 • If the service option connection is new (that is, not part of the previous service configuration), the
6 mobile station shall perform speech codec initialization (see Sections 4 and 5) at the action time
7 associated with the *Service Connect Message*. The mobile station shall complete the initialization
8 within 40 ms.
- 9 • Commencing at the action time associated with the *Service Connect Message* and continuing for as long
10 as the service configuration includes the service option connection, Service Option 3 shall process
11 received packets and generate and supply packets for transmission as follows:
 - 12 • If the mobile station is in the *Conversation Substate*, Service Option 3 shall process the received
13 packets and generate and supply packets for transmission in accordance with this standard.
 - 14 • If the mobile station is not in the *Conversation Substate*, Service Option 3 shall process the
15 received packets in accordance with this standard, and shall generate and supply Rate 1/8 Packets
16 with all bits set to '1' for transmission, except when commanded to generate a Blank packet.

17 2.2.2.1.2 Base Station Requirements

18 If the base station establishes a service configuration, as specified in a *Service Connect Message*, that includes a
19 service option connection using Service Option 3, the base station shall perform the following:

- 20 • If the service option connection is new (that is, not part of the previous service configuration), the base
21 station shall perform speech codec initialization (see Sections 4 and 5) no later than the action time
22 associated with the *Service Connect Message*.
- 23 • Commencing at the action time associated with the *Service Connect Message* and continuing for as long
24 as the service configuration includes the service option connection, Service Option 3 shall process
25 received packets and generate and supply packets for transmission in accordance with this standard.
26 The base station may defer enabling the audio input and output.

27 2.2.2.2 Service Option Control Messages

28 2.2.2.2.1 Mobile Station Requirements

29 The mobile station shall support one pending *Service Option Control Message* for Service Option 3.

30 If the mobile station receives a *Service Option Control Message* for Service Option 3, then, at the action time
31 associated with the message, the mobile station shall process the message as follows:

- 32 1. If the MOBILE_TO_MOBILE field is equal to '1', the mobile station should disable the audio output
33 of the speech codec for 1 second after initialization.
34 If the MOBILE_TO_MOBILE field is equal to '0', the mobile station shall process each received
35 packet as described in Section 5.
- 36 2. If the INIT_CODEC field is equal to '1', the mobile station shall perform speech codec initialization
37 (see Sections 4 and 5). The mobile station shall complete the initialization within 40 ms.

3. If the RATE_REDU_C field is equal to a value defined in Table 2.2.2.2-2, Service Option 3 shall generate the fraction of those packets normally generated as Rate 1 packets (see 4.3) at either Rate 1 or Rate 1/2 as specified by the corresponding line in Table 2.2.2.2-2. Service Option 3 shall continue to use these fractions until either of the following events occur:
- The mobile station receives a *Service Option Control Message* specifying a different RATE_REDU_C, or
 - Service Option 3 is initialized.

Service Option 3 may use the following procedure to perform this rate reduction: Sequences of *N* packets as are formed as shown in Table 2.2.2.1-1. The first *L* packets in this sequence are allowed to be at Rate 1, the next *N-L* packets are forced to be Rate 1/2. Whenever the rate determination process (see 4.3) selects a rate other than Rate 1, the sequence is reset. This ensures that the first packet in a talk spurt will be at Rate 1, unless RATE_REDU_C equals ‘100’ or the speech codec has been commanded by the multiplex sublayer to generate other than a Rate 1 packet (see 2.1.1).

Table 2.2.2.1-1. Sequence Parameters for Rate Reduction

RATE_REDU _C (binary)	Sequence Length, N	Maximum Number of Contiguous Rate 1 Packets in a Sequence, L	Number of Contiguous Rate 1/2 Packets in a Sequence, N-L
‘000’	1	1	0
‘001’	4	3	1
‘010’	2	1	1
‘011’	4	1	3
‘100’	1	0	1

If the RATE_REDU_C field is not equal to a value defined in Table 2.2.2.1-1, the mobile station shall reject the message by sending a *Mobile Station Reject Order* with the ORDQ field set equal to ‘00000100’.

2.2.2.2.2 Base Station Requirements

The base station may send a *Service Option Control Message* to the mobile station. If the base station sends a *Service Option Control Message*, the base station shall include the following type-specific fields for Service Option 3:

Table 2.2.2.2.1-1. Service Option Control Message Type-Specific Fields

Field	Length (bits)
RATE_REDUCE	3
RESERVED	3
MOBILE_TO_MOBILE	1
INIT_CODEC	1

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20

- RATE_REDUCE - Rate reduction.
The base station shall set this field to the RATE_REDUCE value from Table 2.2.2.2.1-1 corresponding to the rate reduction that the mobile station is to perform.
- RESERVED - Reserved bits.
The base station shall set this field to '000'.
- MOBILE_TO_MOBILE - Mobile-to-mobile processing.
If the mobile station is to perform mobile-to-mobile processing (see 2.2.2.2.1), the base station shall set this field to '1'. In addition, if the mobile station is to disable the audio output of the speech codec for 1 second after initialization, the base station shall set the INIT_CODEC field and the MOBILE_TO_MOBILE field to '1'. If the mobile station is not to perform mobile-to-mobile processing, the base station shall set the MOBILE_TO_MOBILE field to '0'.
- INIT_CODEC - Initialize speech codec.
If the mobile station is to initialize the speech codec (see Sections 4 and 5), the base station shall set this field to '1'. Otherwise, the base station shall set this field to '0'.

1 **Table 2.2.2.2.2-2. Fraction of Packets at Rate 1 and Rate 1/2 with Rate Reduction**

RATE_REDUC (binary)	Fraction of Normally Rate 1 Packets to be Rate 1	Fraction of Normally Rate 1 Packets to be Rate 1/2
'000'	1	0
'001'	3/4	1/4
'010'	1/2	1/2
'011'	1/4	3/4
'100'	0	1
All other RATE_REDUC values are reserved.		

2 **2.3 Service Option Group Assignments**

3 3GPP2 C.R1001 specifies a service option group which is a bit map that identifies a logically related set of
4 service options. The bit map may contain 4, 8, or 12 bits, depending upon the number of logically related
5 service options in the group. Each bit in the bit map corresponds to one service option.

6 A mobile station or a base station indicates that it supports a service option in the group by setting the bit
7 corresponding to the service option to '1'. A mobile station or base station can also indicate that it does not
8 support a service option by setting the bit to '0'. All reserved bits are set to '0'.

9 Table 2.3-1 shows the service option group for SO68. The most significant bit of the service option group map
10 is on the left, and the least significant bit is on the right.

11
12 **Table 2-1 Service Option Group Assignments**

Service Option Group (Decimal)	Type of Services in the Group	Service Option Group Bit Map and Associated Service Option Assignments
0	Voice Services	--- x ---- SO 68

13 **2.4 Negotiation for Service Option 68**

14 The MS and base station can negotiate for Service Option 68 service negotiation, as described in [N1].

15 **2.4.1 Procedures using service negotiation**

16 The MS and base station shall perform service negotiation for Service Option 68 as described in [N1], and the
17 negotiated service configuration shall include only valid attributes for the service option as specified in Table
18 2-2.

Table 2-2 Valid service configuration attributes for Service Option 68

Service Configuration Attribute	Valid Selections
Forward Multiplex Option	Multiplex Option 1
Reverse Multiplex Option	Multiplex Option 1
Forward Transmission Rates	Rate Set 1 with all rates enabled
Reverse Transmission Rates	Rate Set 1 with all rates enabled
Forward Traffic Type	Primary Traffic
Reverse Traffic Type	Primary Traffic

2.4.1.1 Initialization and connection

MS requirements

If the MS accepts a service configuration, as specified in a Service Connect message, General Handoff Direction message, or Universal Handoff Direction message that includes a service option connection using Service Option 68, the MS shall perform the following:

- If the service option connection is new, i.e., not part of the previous service configuration, the MS shall perform speech codec initialization at the time specified by the maximum of the action time associated with the message carrying the service configuration record, and the time that the corresponding call control instance is instantiated. The MS shall initialize its EVRC-B encoder mode of operation to a default value of 0. The MS shall complete the initialization within 40 ms.
- Beginning at the time specified by the maximum of the action time associated with the message carrying the service configuration record, and the time that the corresponding call control instance is instantiated, and continuing for as long as the service configuration includes the service option connection, Service Option 68 shall process received packets and generate and supply packets for transmission as follows:
 - If the call control instance is in the conversation substate, Service Option 68 shall process the received packets and generate and supply packets for transmission in accordance with this standard.
 - If the Call Control Instance is not in the conversation substate, Service Option 68 shall process the received packets in accordance with this standard, and shall generate and supply Rate 1/8 packets with all bits set to 1 for transmission, except when commanded to generate a blank packet.

1 Base station requirements

2 If the base station establishes a service configuration, as specified in a Service Connect message, General
3 Handoff Direction message, or Universal Handoff Direction message that includes a service option connection
4 using Service Option 68, the base station shall perform the following:

- 5 ○ If the service option connection is new, i.e., not part of the previous service configuration, the
6 base station shall perform speech codec initialization no later than the time specified by the
7 maximum of the action time associated with the message carrying the service configuration
8 record, and the time that the corresponding call control instance is instantiated. The base
9 station shall initialize its EVRC-B encoder mode of operation to a default value of 0.
- 10 ○ Commencing at the time specified by the maximum of the action time associated with the
11 message carrying the service configuration record, and the time that the corresponding call
12 control instance is instantiated, and continuing for as long as the service configuration
13 includes the service option connection, Service Option 68 shall process received packets, and
14 shall generate and supply packets for transmission in accordance with this standard. The base
15 station may defer enabling the audio input and output.

16 2.4.1.2 Service option control messages

17 MS requirements

18 The MS shall support one pending Service Option Control message for Service Option 68.

19 If the MS receives a Service Option Control message for Service Option 68, then, at the action time associated
20 with the message, the MS shall process the message as follows:

21
22 If the MS has an application which requires the reverse link to operate at operating point 0, the MS may reject
23 the message by sending an MS Reject Order with an ORDQ of 00000100 while that application is active.

24 If the MS accepts the Service Option Control message the following occurs:

- 25
26 1. If the MOBILE_TO_MOBILE field is equal to 1, the MS should disable the audio output of the
27 speech codec for 1 sec after initialization.
- 28 2. If the MOBILE_TO_MOBILE field is equal to 0, the MS shall process each received packet as
29 described in Chapter 6.
- 30 3. If the INIT_CODEC field is equal to 1, the MS shall perform speech codec initialization. The MS shall
31 complete the initialization within 40 ms.
- 32 4. EVRC-B accepts as input, an encoder operating point through the RATE_REDUC field as defined in
33 Table 2-3. Using this operating point, EVRC-B generates Rate 1, Rate 1/2, and Rate 1/4 packets in a
34 proportion that results in the average data rate given by Table 2-3.
- 35 5. Service Option 68 shall continue to use these fractions until either of the following events occur:
 - 36 a. The MS receives a Service Option Control message specifying a different RATE_REDUC, or
 - 37 b. Service Option 68 is initialized.

6. Service Option 68 was developed using reduced rate operation (encoder operating point) as a network control criteria. Unlike the rate reduction mechanism in EVRC, Service Option 68 does not use a deterministic pattern of Rate 1 and Rate 1/2 to reduce the average encoding rate. Instead, the EVRC-B codec selects the encoding rate based upon the characteristics of the input speech; voiced unvoiced, transient, stationary, as well as the encoding mode selected.

Table 2-3 Service Option 68 Encoding rate control parameters

RATE_REDUCE (binary)	encoder operating point	Estimated average encoding rate for active speech (channel encoding rates)	Estimated average encoding rate for active speech (source encoding rates)
'000'	0	9.3	8.3 kbps
'001'	1	8.5	7.57 kbps
'010'	2	7.5	6.64 kbps
'011'	3	7.0	6.18 kbps
'100'	4	6.6	5.82 kbps
'101'	5	6.2	5.45 kbps
'110'	6	5.8	5.08 kbps
'111'	7 (1/2 rate max)	4.8	4.0 kbps

Quarter-rates are not used when RATE_REDUCE = '000' and RATE_REDUCE = '111'. Therefore, RATE_REDUCE = '000' and RATE_REDUCE = '111' could be used in IS-95 systems where quarter-rate frames are sometimes disallowed.

The mobile station may send a Service Option Control message for Service Option 68 to the BS ordering the BS to utilize operating point 0 in the forward direction under the following condition:

1. The mobile has an application for which the BS needs to use operating point 0 in the forward direction, and
2. The mobile has successfully received a service connect message or has successfully completed a hard handoff.

If the mobile station sends a Service Option Control message, the mobile station shall include the following type-specific fields for Service Option 68.

Table 2-4 Service Option Control message type-specific fields

Field	Length (bits)
RATE_REDUCE	3
RESERVED	5

- o RATE_REDUCE – Service Option 68 mode of operation; the mobile station shall set this field to value '000', corresponding to the mode 0, in which the BS is to operate on the forward link.
- o RESERVED – reserved bits; the mobile station shall set this field to 00000

1 **Base station requirements**

2 The base station may send a Service Option Control message to the MS. If the base station sends a Service
3 Option Control message, the base station shall include the following type-specific fields for Service Option 68.

4 **Table 2-5 Service Option Control message type-specific fields**

Field	Length (bits)
RATE_REDUCE	3
RESERVED	3
MOBILE_TO_MOBILE	1
INIT_CODEC	1

- 5
- 6 ○ RATE_REDUCE – Service Option 68 encoder operating point; the base station shall set this
7 field to the value from Table 2-6 corresponding to the operating point in which the MS is to
8 operate
- 9 ○ RESERVED – reserved bits; the base station shall set this field to 000
- 10 ○ MOBILE_TO_MOBILE – mobile-to-mobile processing; if the MS is to perform mobile-to-
11 mobile processing, the base station shall set this field to 1; in addition, if the MS is to disable
12 the audio output of the speech codec for 1 sec after initialization, the base station shall set the
13 INIT_CODEC field and the MOBILE_TO_MOBILE field to 1; if the MS is not to perform
14 mobile-to-mobile processing, the base station shall set the MOBILE_TO_MOBILE field to 0
- 15 ○ INIT_CODEC – initialize speech codec; if the MS is to initialize the speech codec, the base
16 station shall set this field to 1; otherwise, the base station shall set this field to 0
- 17
- 18

Table 2-6 Service Option 68 encoding rate control parameters

RATE_REDUCE (binary)	encoder operating point	Estimated average encoding rate for active speech (channel encoding rates)	Estimated average encoding rate for active speech (source encoding rates)
'000'	0	9.3	8.3 kbps
'001'	1	8.5	7.57 kbps
'010'	2	7.5	6.64 kbps
'011'	3	7.0	6.18 kbps
'100'	4	6.6	5.82 kbps
'101'	5	6.2	5.45 kbps
'110'	6	5.8	5.08 kbps
'111'	7 (1/2 rate max)	4.8	4.0 kbps

Quarter-rates are not used when RATE_REDUCE = '000' and RATE_REDUCE = '111'. Therefore, RATE_REDUCE = '000' and RATE_REDUCE = '111' could be used in IS-95 systems where quarter-rate frames are sometimes disallowed.

- 2 The BS should support one pending Service Option Control message for Service Option 68.
- 3 If the BS receives a Service Option Control message for Service Option 68, then, at the action time associated
- 4 with the message, the BS should process the message as follows:
- 5 The BS shall use mode 0 and begin transmission to the MS in the forward direction using this mode.
- 6 The BS shall continue to use this mode for Service Option 68 with the MS for the duration of the call.

7
8

3 AUDIO INTERFACES

3.1 Input Audio Interface

3.1.1 Input Audio Interface in the Mobile Station

The input audio may be either an analog or digital signal.

3.1.1.1 Conversion and Scaling

Whether the input is analog or digital, the signal presented to the input of the speech codec shall be sampled at a rate of 8000 samples per second and shall be quantized to a uniform PCM format with at least 13 bits of dynamic range.

The quantities in this standard assume a 16-bit integer input normalization with a range from -32,768 through +32,767. The following speech codec discussion assumes this 16-bit integer normalization. If an input audio interface uses a different normalization scheme, then appropriate scaling should be used.

3.1.1.2 Digital Audio Input

If the input audio is an 8-bit μ law PCM signal, it shall be converted to a uniform PCM format according to Table 2 in CCITT Recommendation G.711 "Pulse Code Modulation (PCM) of Voice Frequencies.

3.1.1.3 Analog Audio Input

If the input is in analog form, the mobile station shall sample the analog speech and shall convert the samples to a digital format for speech codec processing. This shall be done by either the following or an equivalent method. First, the input gain audio level is adjusted. Then, the signal is bandpass filtered to prevent aliasing. Finally, the filtered signal is sampled and quantized (see 3.1.1.1).

3.1.1.3.1 Transmit Level Adjustment

The mobile station shall have a transmit objective loudness rating (TOLR) equal to -46 dB, when transmitting to a reference base station. The loudness ratings are described in IEEE Standard 661-1979 "IEEE Standard Method for Determining Objective Loudness Ratings of Telephone Connections." Measurement techniques and tolerances are described in appropriate revision of 3GPP2 C.S0018.

3.1.1.3.2 Band Pass Filtering

Input anti-aliasing filtering shall conform to CCITT Recommendation G.714 "Separate Performance Characteristics for the Encoding and Decoding Sides of PCM Channels Applicable to 4-Wire Voice-Frequency Interfaces." Additional anti-aliasing filtering may be provided by the manufacturer.

3.1.1.3.3 Echo Return Loss

Provision shall be made to ensure adequate isolation between receive and transmit audio paths in all modes of operation. When no external transmit audio is present, the speech codec shall not generate packets at rates higher than Rate 1/8 due to acoustic coupling of the receive audio into the transmit audio path (specifically with the receive audio at full volume). Target levels of 45 dB WAEPL should be met. See ANSI/EIA/TIA Standard 579 "Acoustic-to-Digital and Digital-to-Acoustic Transmission Requirements for ISDN Terminals." Refer to the requirements stated in appropriate revision of 3GPP2 C.S0018.

1 3.1.2 Input Audio Interface in the Base Station

2 3.1.2.1 Sampling and Format Conversion

3 The base station converts the input speech (analog, μ law companded Pulse Code Modulation, or other format)
4 into a uniform quantized PCM format with at least 13 bits of dynamic range. The sampling rate is 8000
5 samples per second. The sampling and conversion process shall be as in 3.1.1.1.

6 3.1.2.2 Transmit Level Adjust

7 The base station shall set the transmit level so that a 1004 Hz tone at a level of 0 dBm0 at the network interface
8 produces a level 3.17 dB below maximum amplitude at the output of the quantizer. Measurement techniques
9 and tolerances are described in appropriate revision of C.S0018.

10 3.1.2.3 Line Echo Canceling

11 The base station shall provide a method to cancel echoes returned by the PSTN interface.[†] The echo canceling
12 function should provide at least 30 dB of echo return loss enhancement. The echo canceling function should
13 work over a range of PSTN echo return delays from 0 to 48 ms; however, the latter requirement is subject to
14 local PSTN configuration demands, i.e., a 64 ms (or greater) echo canceling capability may be required in cases
15 where the PSTN does not provide echo cancellation for long distance service.

16 **3.2 Output Audio Interface**

17 3.2.1 Output Audio Interface in the Mobile Station

18 3.2.1.1 Band Pass Filtering

19 Output reconstruction filtering shall conform to CCITT Recommendation G.714 "Separate Performance
20 Characteristics for the Encoding and Decoding Sides of PCM Channels Applicable to 4 -Wire Voice-Frequency
21 Interfaces." Additional reconstruction filtering may be provided by the manufacturer.

22 3.2.1.2 Receive Level Adjustment

23 The mobile station shall have a nominal receive objective loudness rating (ROLR) equal to 51 dB when
24 receiving from a reference base station. The loudness ratings are described in IEEE Standard 661-1979 "IEEE
25 Standard Method for Determining Objective Loudness Ratings of Telephone Connections." Measurement
26 techniques and tolerances are described in appropriate revision of C.S0018.

27 3.2.2 Output Audio Interface in the Base Station

28 Details of the digital and analog interfaces to the network are outside the scope of this document.

[†] Because of the relatively long delays inherent in the speech coding and transmitting processes, echoes that are not sufficiently suppressed are noticeable to the mobile station user.

1 3.2.2.1 Receive Level Adjustment

2 The base station shall set the audio level so that a received 1004 Hz tone 3.17 dB below maximum amplitude
3 produces a level of 0 dBm0 at the network interface. Measurement techniques and tolerances are described in
4 appropriate revision of C.S0018.

1 **4 OVERVIEW**

2 **4.1 Service Option 3**

3 The Enhanced Variable Rate Codec (EVRC) is based upon the RCELP algorithm, appropriately modified for
 4 variable rate operation and for robustness in the CDMA environment. RCELP is a generalization of the Code-
 5 Excited Linear Prediction (CELP) algorithm. Unlike conventional CELP encoders, RCELP does not attempt to
 6 match the original speech signal exactly. Instead of attempting to match the original residual signal, RCELP
 7 matches a time-warped version of the original residual that conforms to a simplified pitch contour. The pitch
 8 contour is obtained by estimating the pitch delay once in each frame and linearly interpolating the pitch from
 9 frame to frame. One benefit of using this simplified pitch representation is that more bits are available in each
 10 packet for the stochastic excitation and for channel impairment protection than would be if a traditional
 11 fractional pitch approach were used. This results in enhanced error performance without impacting perceived
 12 speech quality in clear channel conditions.

13 The encoder uses 3 of the 4 primary traffic packet types permitted by IS-95 Multiplex Option 1: Rate 1 (171
 14 bits/packet), Rate 1/2 (80 bits/packet), and Rate 1/8 (16 bits/packet). Upon command, the encoder will produce
 15 a blank packet (which contains no bits) or other than a Rate 1 packet (i.e., Rate 1/2 maximum); otherwise, the
 16 encoder makes its own determination about what type of packet to generate. Bit allocations for each packet
 17 type are given in Table 4-1.

18
 19 **Table 4-1. Bit Allocations by Packet Type**

Field (see 4.8)	Packet Type			
	Rate 1	Rate 1/2	Rate 1/8	Blank
Spectral Transition Indicator	1			
LSP	28	22	8	
Pitch Delay	7	7		
Delta Delay	5			
ACB Gain	9	9		
FCB Shape	105	30		
FCB Gain	15	12		
Frame Energy			8	
(reserved)	1			
Total	171	80	16	0

The algorithms in the sections that follow are presented in terms of block diagrams, mathematical equations where appropriate, and in pseudo-code where equations would be cumbersome. Inputs, outputs, and processing are defined for each processing block or module. Internal variables for each module are defined when used. Modules are decomposed into sub-modules at increasing levels of detail until a defining equation or block of pseudo-code describing the lowest level of processing is reached. The algorithm descriptions are designed to maximize clarity, not to illustrate the most efficient implementation. For example, no attempt is made to illustrate memory conserving techniques such as reuse of scratch variables or buffers. Operations such as Discrete Fourier Transforms (DFTs) or Finite Impulse Response (FIR) filters are described in terms of a defining equation rather than in terms of one of the fast algorithms available to carry them out.

Figure 4-1 is a high-level view of the EVRC speech encoder showing all major modules. Inputs to the encoder are the speech signal vector, $\{s(n)\}$, and an external rate command signal. The external rate command may direct the encoder to produce a blank packet or a packet other than Rate 1. If an external rate command is received, it will supersede the encoder's internal rate selection mechanism.




Figure 4.1-1. Speech Encoder Top-Level Diagram

The input speech vector, $\{s(n)\}$, is presented to the signal pre-processing module (see 4.1), which performs high-pass and adaptive noise suppression filtering. The pre-processed speech vector, $\{s'(n)\}$, is then presented to the model parameter estimation module. The model parameter estimation module (see 4.2) performs LPC analysis to determine a set of linear prediction coefficients (LPCs) and the optimal pitch delay (τ). It also converts the LPCs to line spectral pairs (LSPs) and calculates the long and short-term prediction gains. The rate determination module (see 4.3) applies a voice activity detection (VAD) algorithm and rate selection logic in order to determine the type of packet to generate.

After estimating the model parameters, the encoder will characterize the excitation signal and quantize parameters in a way appropriate to the selected rate (see 4.4 through 4.6). If Rate 1/8 is selected, the encoder will not attempt to characterize any periodicity in the speech residual, but will instead just characterize its energy contour. At Rates 1/2 and 1 the encoder will apply the RCELP algorithm to match a time-warped version of the original speech residual.

A number of parameters are included at Rate 1 to provide enhanced performance in poor channel conditions. These include the spectral transition indicator and the delay difference ($\Delta\tau$). The packet formatting module (see 4.8) accepts all of the parameters calculated and quantized in the rate-specific encoding modules, and formats a packet appropriate to the selected rate. The formatted packet is then presented to the multiplex sub-layer. The rate decision is also presented to the multiplex sub-layer. Sections 4.1 through 4.8 describe each of the encoder modules in detail.

4.2 Service Option 68

The EVRC-B coder uses an operating point and speech-type dependent coding scheme selection. Primarily it consists of Code-Excited-Linear-Prediction (CELP), Prototype-Pitch-Period (PPP), Noise-Excited-Linear-Prediction (NELP) coding methods. CELP is used for full-rate and half-rate, PPP is used for full-rate and quarter-rate, NELP is used for quarter-rate, and eighth-rate.

Table 4-2 lists where the different coding schemes are used. Full-rate CELP (FCELP) is used to code transitions, poorly voiced frames and certain normal voiced frames as well. Half-rate CELP (HCELP) is used to code ends of words mostly and dimmed frames. Full-rate PPP (FPPP) and quarter-rate PPP (QPPP) are used to code strongly voiced frames. Quarter-rate NELP (QNELP) is used for unvoiced frames. Silence is coded by a simple single-gain shaped random noise waveform as in [S8].

Table 4-2 EVRC-B coding schemes

Coding scheme	Type of speech
FCELP (Full-rate CELP)	Transient, bump-up and some voiced frames
HCELP (1/2-Rate CELP)	Ends of words, Dim-and-burst signaling
Special HCELP	Packet level dimming of FCELP
FPPP/QPPP (Full/Quarter rate Prototype Pitch Period)	Voiced frames
Special HPPP	Packet level dimming of FPPP
QNELP (1/4-Rate Noise Excited LP)	Unvoiced frames
Special HNELP	Half-rate frame containing NELP frame for use in situations not allowing quarter-rate (e.g., in IS-95 systems)
1/8 Rate	Silence frames

The encoder uses the 4 primary traffic packet types permitted by IS-95 Multiplex Option 1: Rate 1 (171 bits/packet), Rate 1/2 (80 bits/packet), Rate 1/4 (40 bits/packet), and Rate 1/8 (16 bits/packet). Upon command, the encoder will produce a blank packet (which contains no bits) or other than a Rate 1 packet, i.e., Rate 1/2 maximum; otherwise, the encoder makes its own determination about what type of packet to generate. Bit allocations for each packet type are given in Table 4-3.


1
2
3**Table 4-3 Bit allocations by packet type**

Parameter	Full-rate CELP	Half-rate CELP	Special half-rate CELP	Full-rate PPP	Special half-rate PPP	Quarter-rate PPP	Special half-rate NELP	Quarter-rate NELP	Silence encoder
Mode Bit	1		1	1	1	1		1	
Special half-rate ID			2		2		2		
LSP	28	22	28	28	28	16	16	16	8
Lag/Special Packet ID	7	7	7	7	7	4	7		
Additional Lag			7		7				
ACB Gain	9	9	9						
FCB Index	105	30							
FCB Gain	15	12							
Delta lag	5								
Amplitude				28	28	18			
Global Alignment				7	7	0			
Band Alignments				99					
Energy VQ							17	17	6
Filter Shape							2	2	
Reserved	1		26	1		1	36	4	2
Total	171	80	80	171	80	40	80	40	16

4

5 All the reserved bits shall be set to 0. The algorithms in the sections that follow are presented in terms of block
6 diagrams, mathematical equations where appropriate, and in pseudo-code where equations would be
7 cumbersome. Inputs, outputs, and processing are defined for each processing block or module. Internal
8 variables for each module are defined when used. Modules are decomposed into sub-modules at increasing
9 levels of detail until a defining equation or block of pseudo-code describing the lowest level of processing is
10 reached. The algorithm descriptions are designed to maximize clarity, not to illustrate the most efficient
11 implementation. For example, no attempt is made to illustrate memory conserving techniques such as reuse of
12 scratch variables or buffers. Operations such as Discrete Fourier Transforms (DFTs) or Finite Impulse
13 Response (FIR) filters are described in terms of a defining equation rather than in terms of one of the fast
14 algorithms available to carry them out.

1 Figure 4.2-1 is a high-level view of the EVRC-B speech encoder showing all major modules. Inputs to the
 2 encoder are the speech signal vector, $\{s(n)\}$, and an external rate command signal. The external rate command
 3 may direct the encoder to produce a blank packet or a packet other than Rate 1. If an external rate command is
 4 received, it will supersede the encoder's internal rate selection mechanism.



5

6

Figure 4.2-1 Speech encoder top-level diagram

Figure 4.2-2 is a speech decoder top-level diagram.




Figure 4.2-2 Speech decoder top-level diagram

After usual front-end pre-processing and voiced activity decision, the input speech and residual are analyzed to compute open-loop-pitch information as well as periodicity information. This information along with other features is used to categorize speech into transition, voiced, unvoiced, end-of-word, silence.

Then there is a further categorization of frames into one of the above coding schemes and rates which is operating point-dependent.

The linear-prediction-coefficients (LPCs) are quantized according to the rate and coding scheme. The residual is computed using these quantized LPCs and modified to get a target waveform matching as perfectly as possible to a pitch contour without losing perceptual quality, as in [S8]. After this encoding of either this target waveform or a representative period of it or an energy contour of it is done with appropriate quantization and corresponding unquantization at the decoder, synthesis and update of memories. A perceptual quality enhancing adaptive postfilter is applied to the output of the decoder.

4.2.1 Pre-processing

The input speech is processed through a high-pass-filter and noise-suppressor, after which certain parameters such as LPC, Normalized-Auto-Correlation-Function (NACF) are extracted. Voice-activity decision is made before any further processing. Pitch lag and NACF for the current frame are estimated based on the residual of

1 the current frame, previous frame and part of the next frame. Some additional features are also estimated for use
2 in rate/coding scheme decision which follows.

3 The High-Pass-Filter and Noise-Suppressor are similar to [S8]. The LPC analysis, pitch lag estimation, LPC to
4 LSP conversion, and residual computation are similar to [S8]. New parameters computed NACF and certain
5 other rate decision specific features. Voice-activity decision is similar to that in [S8].

6 4.2.2 Rate/coding scheme decision

7 The rate/coding scheme decision is of two kinds, open-loop and closed-loop, the former being invoked prior to
8 any quantization being done (except for LPC in case of some open-loop decisions), the latter after. The open-
9 loop rate decision is based mostly on parameters and features of input speech, both current and previous. The
10 closed-loop rate decision is based on quarter-rate PPP quantizer performance.

11 The input operating point controls EVRC-B to operate at an arbitrarily desired average-rate. This is first
12 mapped onto one of three Anchor Operating Points, called AOP 0, 1, and 2 respectively. These anchor
13 operating points control the basic behavior of EVRC-B rate-selection while the final rate-selection enables the
14 average rate output of EVRC-B to match the input operating point.

15 4.2.2.1 Open-loop decision

16 First of all the input signal is classified broadly into speech, end-of-speech and silence. If the anchor operating
17 point chosen is Anchor operating point-0, these classifications are correspondingly encoded with full-rate
18 CELP, half-rate CELP, and silence-encoder. Otherwise, the non-silence part of the input is further classified
19 using multi-level decision logic into transition, voiced, unvoiced and end-of-word. Additional features
20 computed are SNR of previous and current frames, ZCR, high-band and low-band energies of current and
21 previous frame. Each voiced segment is made sure to be preceded by a transition frame to get good initial
22 memories. Transitions are encoded with full-rate CELP, end-of-word is encoded with half-rate CELP, unvoiced
23 is encoded with quarter-rate NELP, and voiced is further mapped into pattern sets of three frames. If the anchor
24 operating point chosen is anchor operating point-1 the repetitive three-frame pattern set is encoded successively
25 with full-rate CELP, quarter-rate PPP, and full-rate CELP. If the anchor operating point chosen is Anchor
26 operating point-2, this three-frame pattern set is encoded successively with quarter-rate PPP, quarter-rate PPP
27 and full-rate PPP.

28 Further, if inside the PPP scheme some waveform changes are extreme, the coding scheme is changed either
29 from full-rate PPP to full-rate CELP or quarter-rate PPP to full-rate PPP/CELP.

30 4.2.2.2 Closed-loop decision

31 If the quarter-rate PPP encoding fails either in its phase representation or amplitude quantization, the Closed-
32 Loop Rate Decision is used to change the rate to full-rate PPP (if anchor operating point-2) or full-rate CELP
33 (if anchor operating point-1) and the voiced frame rate pattern is reset.

34 4.2.2.3 Operating point-switching and dimming

35 To handle operating point-switching and dimming, the pattern of coding voiced frames is reset in certain
36 conditions. In anchor operating point-1 or anchor operating point-2, if a full-rate frame is dimmed to half-rate,
37 the voiced frame pattern begins afresh with full-rate (either PPP or CELP depending on anchor operating point-
38 2 or anchor operating point-1 respectively). This holds true in the case of operating point-switching as well
39 where the voiced frame pattern is reset to the usual pattern of choice for the new operating point.

4.2.2.4 Arbitrary capacity operating point operation

EVRC-B has the capability to operate at an arbitrary average rate. This in turn means that the CDMA network using EVRC-B can achieve an arbitrary capacity operating point (COP) in the forward link as shown in Figure 4.2-3. The open-loop and the closed-loop rate decision thresholds are dynamically adjusted in order to achieve this arbitrary average rate, as shown in Figure 4.2-3.




Figure 4.2-3 Continuous range of COPs

The channel average rate for active speech, T , is computed as follows,

$$T = \frac{9600N_{full} + 4800N_{half} + 2400N_{quarter}}{N_{full} + N_{half} + N_{quarter}}$$

Given a target average rate for active speech, in channel rate bits-per-second, say $T_{ActiveAvgChRate}$, EVRC-B encoder first determines an anchor operating point according to the following algorithm:

```

if ( $T_{ActiveAvgChRate} > 7500$ )  $OP_{anchor} = 0$ 
else if ( $T_{ActiveAvgChRate} > 6600$ )  $OP_{anchor} = 1$ 
else  $OP_{anchor} = 2$ 
    
```

Once the anchor operating point has been determined, EVRC-B attempts to meet the average rate-target by adjusting the fraction of quarter-rate frames to meet the target average rate. This adjustment is done dynamically by comparing the actual average rate in a window of past 600 active speech frames to the target average rate, and computing an appropriate fraction of frames that would be sent from quarter-rate to full-rate coding.

A fraction, p , of frames that would be sent from quarter-rate to full-rate is given by,

$$p = \begin{cases} \frac{(T_{next} - 7.5)}{(9.0 - 7.5)}; & OP_{anchor} = 0 \\ \frac{(T_{next} - 6.6)}{(7.5 - 6.6)}; & OP_{anchor} = 1 \\ \frac{(T_{next} - 5.75)}{(6.6 - 5.75)}; & OP_{anchor} = 2 \end{cases}$$

Where T_{next} is the dynamic target active speech channel average rate for the next *RATEWIN* active frames given by,

$$T_{next} = 1.98T_{ActiveAvgChRate} - T_{prev}$$

Where T_{prev} is the active speech channel average rate for the previous *RATEWIN* active frames.

Once the fraction, p , has been determined, the following algorithm is used to send the fraction, p , quarter-rate frames to full-rate in an almost uniformly distributed manner.

For every active frame,

```

10   If (OP_anchor = 0) {
11     If (open loop mode-decision EQUAL to UNVOICED) {
12       Patterncount = Patterncount + 1000 x p
13       If (patterncount > 1000){
14         Encode unvoiced frame using full-rate
15         Patterncount = patterncount - 1000
16       }
17     }
18   If (OP_anchor = 1) {
19     If (voiced frame is determined using the open-loop and closed-loop
20     decision to be coded using QPPP) {
21       Patterncount = Patterncount + 1000 x p
22       If (patterncount > 1000){
23         Encode QPPP frame using full-rate CELP
24         Patterncount = patterncount - 1000
25       }
26     }
27   If (OP_anchor = 2) {
28     If (voiced frame is determined using the open-loop and closed-loop
29     decision to be coded using QPPP and if previous frame was a QPPP frame) {
30       Patterncount = Patterncount + 1000 x p
31       If (patterncount > 1000){
32         Encode QPPP frame using full-rate CELP
33         Patterncount = patterncount - 1000
34       }
35     }
36   }

```

4.2.3 Full-rate CELP and half-rate CELP

The CELP algorithms are similar to those in [S8] except for the following exceptions.

1 The fixed codebook in case of full rate is more efficient and is with one pulse fewer per subframe. This is
2 achieved by exploring and covering all possible combinations of 7 pulses and two signs on each possible
3 location in a subframe. Packing and unpacking is slightly more complex than in [S8]. The fixed codebook of
4 half rate (used for end-of-word only) also is made somewhat more efficient by discarding undesirable pulse
5 combinations from [S8] and adding some new pulse combinations.


6 The full-rate CELP decoder is different in the way it handles the frame after erasure or the frame after a
7 quarter-rate PPP which in turn would have followed an erasure. In the latter case, the previous quarter-rate PPP
8 frame is re-synthesized with the proper lag and this is used for the adaptive codebook memories. In either case,
9 after reconstruction of the residual of the current CELP frame, it could be replaced with a waveform-
10 interpolated version of the representative prototypes of the current and previous reconstructed prototypes to
11 eliminate clicks after erasure.

12 The special half-rate CELP frame is used when a full-rate CELP frame is converted by a packet-level signaling
13 interworking function to a half-rate frame. The packet-level conversion is done by discarding the FCB index
14 and gain bits in the full-rate, and repacking the remaining bits into a special half-rate frame. To indicate to the
15 EVRC-B decoder that it is a special half-rate CELP frame, the 7 lag bits of the HCELP frame are set to 0x6E—
16 a value that is never produced at the EVRC-B encoder.

17 4.2.4 Full-rate PPP and quarter-rate PPP and special Half-rate PPP

18 4.2.4.1 Background

19 It was the perceptual importance of the periodicity in voiced speech that motivated the development of the
20 (Prototype Pitch Period) PPP coding technique. PPP exploits the fact that pitch-cycle waveforms in a voiced
21 segment do not change quickly in a frame. This suggests that we do not have to transmit every pitch-cycle
22 to the decoder; instead, we could transmit just a representative prototype pitch period. At the decoder, the
23 nontransmitted pitch-cycle waveforms could then be derived by means of interpolation. In this way, very low-
24 bit-rate coding can be achieved while maintaining high quality reconstructed voiced speech. Figure 4.2-4
25 illustrates an example of how the pitch-cycle waveforms are extracted and interpolated. We will refer these
26 pitch-cycle waveforms as Prototype Pitch Periods (abbreviated as PPPs).



1
2 **Figure 4.2-4 Illustration of the principles of PPP coding**

3 In EVRC-B, PPP operates at two rates – full-rate (FPPP) and quarter-rate (QPPP). They both share the same
4 fundamental concepts but differ in their bit-allocation schemes. In the context of this implementation, the
5 quantization of PPP is carried out in frequency domain. Hence the time-domain signal is converted to a
6 discrete-Fourier series (DFS), whose amplitudes and phases are independently quantized. The description of the
7 PPP model will be first given.

8 **4.2.4.2 PPP Model**

9 Figure 4.2-5 presents a high-level schematic diagram of PPP coding scheme. Front-end processing including
10 LPC analysis is same for this scheme. However, the LSP quantization for the QPPP is a Moving-Average
11 predictive quantizer which exploits the stationarity of voiced speech.




Figure 4.2-5 Block diagram of PPP coding scheme

4.2.4.3 Further processing of PPP frames

Then, the corresponding residual is obtained which in turn is modified the same way as in CELP to follow a pitch contour similar to RCELP in [S8].

Next, a PPP is extracted from the modified residual signal on a frame-wise basis. The length of the PPP is determined by the lag estimate supplied by the pitch estimator. Special attention needs to be paid to the boundaries of the PPP during the extraction process. Since each PPP will undergo circular rotation in the alignment process (as will be seen later), the energy around the PPP boundaries needs to be minimized to prevent discontinuities after circular rotation (where the left side of the PPP meets the right side). Such minimization can be accomplished by slightly jittering the location of the extraction.

After the extraction, the PPP of the current frame needs to be time-aligned with the PPP extracted from the previous frame. Specifically, the current PPP is circularly shifted until it has the maximum cross-correlation with the previous PPP. The alignment process serves two purposes: (1) facilitates PPP quantization especially in low-bit-rate predictive quantization schemes (2) facilitates the construction of the whole frame of excitation in the synthesis procedure which will be discussed next.

The aligned PPPs are then quantized and transmitted to the decoder. To create a full-frame of excitation from the current and previous PPPs, we need to compute an instantaneous phase track which is designed carefully so as to achieve maximum time-synchrony with the original residual signal. For this purpose, a cubic phase track can be employed along with four boundary conditions: (1) the initial lag value, (2) the initial phase offset, (3) the final lag value and (4) the final phase offset. At low bit rates, the final phase offset can be computed by the RCELP pitch contour.

Having created the entire frame of quantized residual, the decoder concludes its operation with LPC synthesis filter and memory updates.

4.2.4.4 Amplitude Quantization

Figure 4.2-6 shows the block diagram of the amplitude quantizer used in EVRC-B.




Figure 4.2-6 A block diagram of amplitude quantization and dequantization modules

As a first step, an amplitude spectrum is first normalized by two scaling factors at the encoder – one for the low band and one for the high band. The two resulting scaling factors are vector-quantized in the logarithmic domain and transmitted to the decoder. Next, the normalized spectrum is then non-uniformly downsampled to 22 spectral values according to the bin partition shown in Figure 4.2-7.




Figure 4.2-7 An illustrative non-uniform band partition used PPP quantization

Specifically, each harmonic is first associated with a bin. Then, an average magnitude of the harmonics falling in each bin is computed and hence, a vector of 22 values is produced. Figure 4.2-8 demonstrates an example of such non-uniform downsampling process.




Figure 4.2-8 Illustration of the effect of spectral downsampling and upsampling.

The vertical grid lines are based on the non-uniform band partition shown in Figure 4.2-8 – (a): the original amplitude spectrum of a PPP; (b): the normalized version of the spectrum; and (c): the non-uniformly-downsampled version of the spectrum.


The significance of this downsampling/averaging process is to transform a variable dimension vector to a fixed dimension vector. It also takes advantage of the frequency-dependent frequency resolution of the human auditory system and removes perceptually irrelevant information existed in the spectra. Finally, the downsampled spectrum is split into two spectra (the low and high bands) and each of which is separately quantized. At the decoder, the low and the high band spectra are first reconstructed from the bit-stream transmitted from the encoder. The two spectra are then combined and sent to a non-uniform spectral upsampler. Afterwards, the scaling factors recovered from the bit-stream are used to denormalize the upsampled spectrum to reconstruct the quantized spectrum.

In QPPP, both the scaling factors and the spectra are quantized differentially whereas in FPPP, they are done so in a nondifferential manner.

4.2.4.5 Phase Quantization

For QPPP, no bit is spent on phase quantization. The phase spectrum of the current PPP can be readily derived from combining the phase spectrum of the previous PPP and the contribution from the RCELP pitch contour.

- 1 For FPPP, we adopted a novel multi-band alignment approach to code phase spectrum. As demonstrated in
 2 Figure 4.2-9, the effect of applying one linear phase-shift to a PPP is equivalent to its circular rotation in time-
 3 domain.



4
 5 **Figure 4.2-9 Demonstration of the effect of a single-band alignment on a single PPP**

- 6 By extending the same idea to multiple sub-bands, one can begin controlling the “shape” details of a PPP by
 7 applying different phase-shifts to different sub-bands. An example of which is illustrated in Figure 4.2-10 for
 8 the case $N=6$ (six sub-bands).




Figure 4.2-10 Demonstration of the effect of multi-band alignments on a single PPP

Hence, the problem of phase quantization has been transformed into quantization of a series of linear phase shifts. Similar to the conventional alignment process, the search of these linear-phase shifts can be performed in the time-domain. The resulting linear-phase shifts are quantized in a scalar manner. The resolution and the range of each phase shift are chosen such that it achieves the target bit rate.

4.2.4.6 Special half-rate PPP frame

The special half-rate PPP frame is used when a full-rate PPP frame is converted by a packet-level signaling interworking function to a half-rate frame. The packet-level conversion is done by discarding the band alignment bits in the full-rate, and repacking the remaining bits into a special half-rate frame. To indicate to the EVRC-B decoder that it is a special half-rate PPP frame, the 7 lag bits of the HPPP frame are set to 0x6E—a value that is never produced at the EVRC-B encoder.

1 4.2.4.7 Detection of outliers

2 One peculiarity of the PPP scheme is the detection and treatment of unsuitable frames. If the shape/length of the
3 current PPP is deemed to change too much from the PPP of the previous frame (not enough periodicity), PPP is
4 abandoned in favor of FCELP. As briefly mentioned before, a separate closed-loop measure is also devised to
5 capture the outliers of the amplitude and phase quantizers in QPPP. When an outlier is detected in a particular
6 frame, the rate of that frame is then increased to full rate (FCELP or FPPP).

7 4.2.5 Frame erasure handling

8 Whenever a frame is lost due to erasure, relevant parameters from the previous frame are used and a simple
9 frame repeat mechanism is performed on the lines of the previous frame's decoding mechanism.

10 4.2.6 Bad rate/packet handling

11 If incorrect rate is received, checks which are always performed on certain parameters would fail and this
12 would be the detection of bad rate/packet and an erasure would be flagged and this packet would be treated as
13 lost and a frame erasure handling mechanism replaces the regular decoder.

15 4.3 Input Signal Preprocessing

16 Input preprocessing is needed to condition the input signal against excessive low frequency and other
17 background noises that can degrade the codec voice quality. Refer to 1.1 for guidelines concerning potential
18 variations of the Input Signal Preprocessing functions.

19 4.3.1 High-Pass Filter

20 The input sampled speech shall be high-pass filtered as described below:

21 **Inputs:**

- 22 • The input sampled speech signal, $\{s(n)\}$

23 **Outputs:**

- 24 • The high-pass filtered speech signal, $\{s_{hp}(n)\}$

25 **Initialization:**

- 26 • The filter memory is set to all zeros at initialization.

27 **Processing:**

28 The High-Pass Filter for Service Option 3 is a sixth order Butterworth filter implemented as three cascaded
29 biquadratic sections. The cutoff frequency of the filter is 120 Hz. The transfer function of the filter is:

$$30 \quad H_{hpf} = \prod_{j=1}^3 H_j(z) \quad (4.3.1-1)$$

31 where each section, $H_j(z)$, is given by:

$$H_j(z) = \frac{a_{j0} + a_{j1}z^{-1} + a_{j2}z^{-2}}{1 + b_{j1}z^{-1} + b_{j2}z^{-2}}. \quad (4.3.1-2)$$

The filter coefficients are given as:

$$\begin{aligned} a_{10} &= 1.0, & a_{11} &= -2.000125721, & a_{12} &= 1.000125737, \\ b_{11} &= -1.943779252, & b_{12} &= 0.952444269, \\ a_{20} &= 1.0, & a_{21} &= -1.999873569, & a_{22} &= 0.999873585, \\ b_{21} &= -1.866892280, & b_{22} &= 0.875214548, \\ a_{30} &= 0.833469450, & a_{31} &= -1.666939491, & a_{32} &= 0.833470028, \\ b_{31} &= -1.825209384, & b_{32} &= 0.833345838. \end{aligned}$$

The High-Pass Filter for SO 68 is a fourth order filter. The cutoff frequency of the filter is 80 Hz. The transfer function of the filter is:

$$H_{hpf} = \frac{\left((0.9329833984375) + (-2.7984619140625)z^{-1} + (2.7984619140625)z^{-2} \right) + (-0.9329833984375)z^{-3}}{\left(1 + (2.86181640625)z^{-1} + (-2.7315673828125)z^{-2} \right) + (0.869384765625)z^{-3}} \quad (4.3.1-3)$$

4.3.2 Noise Suppression

Noise Suppression is used to improve the signal quality that is presented to the Model Parameter Estimator. The procedures by which the Noise Suppression shall be implemented are described in this section.

Input:

- The output of the High-Pass Filter, $\{s_{hp}(n)\}$

Output:

- The output of the Noise Suppressor is designated as $\{s'(n)\}$.

Initialization:

The following variables shall be set to zero at initialization (frame $m = 0$):

- The overlapped portion of the input frame buffer, $\{d(m)\}$
- The pre-emphasis and de-emphasis memories
- The overlap-and-add buffer, $h(n)$
- The output buffer history, $s'(n) ; 0 \leq n < 160$

The following shall be initialized to a startup value other than zero:

- The channel energy estimate, $E_{ch}(m)$, (see 4.3.2.2)
- The long-term power spectral estimate, $\bar{\mathbf{E}}_{dB}(m)$, (see 4.3.2.5)
- The channel noise estimate, $E_n(m)$, (see 4.3.2.10)

1 where $\zeta_p = -0.8$ is the pre-emphasis factor. This results in the input buffer containing $L + D = 104$ samples in
 2 which the first D samples are the pre-emphasized overlap from the previous frame, and the following L samples
 3 are pre-emphasized input from the current frame.

4 Next, a smoothed trapezoidal window is applied to the input buffer to form the DFT data buffer, $\{g(n)\}$,
 5 defined as:

$$6 \quad g(n) = \begin{cases} d(m,n) \sin^2(\pi(n+0.5)/2D) & ; 0 \leq n < D, \\ d(m,n) & ; D \leq n < L, \\ d(m,n) \sin^2(\pi(n-L+D+0.5)/2D) & ; L \leq n < D+L, \\ 0 & ; D+L \leq n < M, \end{cases} \quad (4.3.2-3)$$

7 where $M = 128$ is the DFT sequence length and all other terms are previously defined.

8 The transformation of $g(n)$ to the frequency domain is performed using the Discrete Fourier Transform (DFT)
 9 defined[†] as:

$$10 \quad G(k) = \frac{2}{M} \sum_{n=0}^{M-1} g(n) e^{-j2\pi nk/M} ; \quad 0 \leq k < M , \quad (4.3.2-4)$$

11 where $e^{j\omega}$ is a unit amplitude complex phasor with instantaneous radial position ω .

12 4.3.2.2 Channel Energy Estimator

13 Calculate the channel energy estimate $E_{ch}(m)$ for the current frame, m , as:

$$14 \quad E_{ch}(m,i) = \max \left\{ E_{\min}, \alpha_{ch}(m) E_{ch}(m-1,i) + (1 - \alpha_{ch}(m)) \frac{1}{f_H(i) - f_L(i) + 1} \sum_{k=f_L(i)}^{f_H(i)} |G(k)|^2 \right\} ; 0 \leq i < N_c, (4.3.2-5)$$

15 where $E_{\min} = 0.0625$ is the minimum allowable channel energy, $\alpha_{ch}(m)$ is the channel energy smoothing factor
 16 (defined below), $N_c = 16$ is the number of combined channels, and $f_L(i)$ and $f_H(i)$ are the i -th elements of the
 17 respective low and high channel combining tables, which are defined as:

$$18 \quad f_L = \{ 2, 4, 6, 8, 10, 12, 14, 17, 20, 23, 27, 31, 36, 42, 49, 56 \},$$

$$19 \quad f_H = \{ 3, 5, 7, 9, 11, 13, 16, 19, 22, 26, 30, 35, 41, 48, 55, 63 \}.$$

20 The channel energy smoothing factor, $\alpha_{ch}(m)$, is defined as:

[†] This atypical definition is used to exploit the efficiencies of the complex Fast Fourier Transform (FFT). The $2/M$ scale factor results from preconditioning the M point real sequence to form an $M/2$ point complex sequence that is transformed using an $M/2$ point complex FFT. Details on this technique can be found in Proakis, J. G. and Manolakis, D. G., *Introduction to Digital Signal Processing*, New York, Macmillan, 1988, pp. 721-722.

$$\bar{E}_{dB}(m) = E_{dB}(m); \quad m=1. \quad (4.3.2-11)$$

Calculate the total channel energy estimate, $E_{tot}(m)$, for the current frame, m , according to the following:

$$E_{tot}(m) = 10 \log_{10} \left(\sum_{i=0}^{N_c-1} E_{ch}(m, i) \right). \quad (4.3.2-12)$$

Calculate the exponential windowing factor, $\alpha(m)$, as a function of total channel energy, $E_{tot}(m)$, as:

$$\alpha(m) = \alpha_H - \left(\frac{\alpha_H - \alpha_L}{E_H - E_L} \right) (E_H - E_{tot}(m)), \quad (4.3.2-13)$$

and then limit the result to be between α_H and α_L by

$$\alpha(m) = \max \{ \alpha_L, \min \{ \alpha_H, \alpha(m) \} \}, \quad (4.3.2-14)$$

where E_H and E_L are the energy endpoints (in dB) for the linear interpolation of $E_{tot}(m)$, that is transformed to $\alpha(m)$ which has the limits $\alpha_L \leq \alpha(m) \leq \alpha_H$. The values of these constants are defined as: $E_H = 50$, $E_L = 30$, $\alpha_H = 0.99$, $\alpha_L = 0.50$. As an example, a signal with relative energy of 40 dB would use an exponential windowing factor of $\alpha(m) = 0.745$ for the following calculation.

Update the average long-term power spectral estimate for the next frame by:

$$\bar{E}_{dB}(m+1, i) = \alpha(m) \bar{E}_{dB}(m, i) + (1 - \alpha(m)) E_{dB}(m, i); \quad 0 \leq i < N_c, \quad (4.3.2-15)$$

where all the variables are previously defined.

4.3.2.6 Background Noise Update Decision

The following logic, as shown in pseudo-code, demonstrates how the noise estimate update decision is ultimately made:

```

21  /* Normal update logic */
22  update_flag = FALSE
23  if ( v(m) ≤ UPDATE_THLD ) {
24      update_flag = TRUE
25      update_cnt = 0
26  }
27  /* Forced update logic */
28  else if (( E_tot(m) > NOISE_FLOOR_DB ) and ( Δ_E(m) < DEV_THLD )) {
29      update_cnt = update_cnt + 1
30      if ( update_cnt ≥ UPDATE_CNT_THLD )

```

```
1         update_flag = TRUE
2     }
3     /* "Hysteresis" logic to prevent long-term creeping of update_cnt */
4     if ( update_cnt == last_update_cnt )
5         hyster_cnt = hyster_cnt + 1
6     else
7         hyster_cnt = 0
8         last_update_cnt = update_cnt
9         if ( hyster_cnt > HYSTER_CNT_THLD )
10            update_cnt = 0
```

11 The values of the previously used constants are UPDATE_THLD = 35, NOISE_FLOOR_DB = $10\log_{10}(E_{floor})$
12 (see 4.1.2.8), DEV_THLD = 28, UPDATE_CNT_THLD = 50, HYSTER_CNT_THLD = 6.

1 4.3.2.7 SNR Estimate Modification

2 Next, determine whether the channel SNR modification should take place, then proceed to modify the
3 appropriate SNR indices:

```

4  /* Set or reset modify flag */
5  index_cnt = 0
6  for ( i = NM to Nc - 1 step 1 ) {
7      if ( σq(i) ≥ INDEX_THLD )
8          index_cnt = index_cnt + 1
9      }
10  if ( index_cnt < INDEX_CNT_THLD )
11      modify_flag = TRUE
12  else
13      modify_flag = FALSE
14
15  /* Modify the SNR indices to get {σ'q} */
16  if ( modify_flag == TRUE )
17      for ( i = 0 to Nc - 1 step 1 )
18          if ( ( ν(m) ≤ METRIC_THLD ) or ( σq(i) ≤ SETBACK_THLD ) )
19              σ'q(i) = 1
20          else
21              σ'q(i) = σq(i)
22  else
23      {σ'q} = {σq}
24
25  /* Limit {σ''q(i)} to SNR threshold σth */
26  for ( i = 0 to Nc - 1 step 1 )
27      if ( σ'q(i) < σth )
28          σ''q(i) = σth
29      else
30          σ''q(i) = σ'q(i)

```

31 The previous constants and thresholds are given to be: N_M = 5, INDEX_THLD = 12, INDEX_CNT_THLD = 5,
32 METRIC_THLD = 45, SETBACK_THLD = 12, σ_{th} = 6.

33 4.3.2.8 Channel Gain Computation

34 Compute the overall gain factor for the current frame as:

$$35 \quad \gamma_n = \max \left\{ \gamma_{\min}, -10 \log_{10} \left\{ \frac{1}{E_{\text{floor}}} \sum_{i=0}^{N_c-1} E_n(m, i) \right\} \right\}, \quad (4.3.2-16)$$

1 where $\gamma_{\min} = -13$ is the minimum overall gain, $E_{\text{floor}} = 1$ is the noise floor energy, and $E_n(m)$ is the estimated
2 noise spectrum (see 4.3.2.10) calculated during the previous frame.

3 Next, calculate channel gains (in dB) as:

$$4 \quad \gamma_{dB}(i) = \mu_g (\sigma_g''(i) - \sigma_{th}) + \gamma_n; \quad 0 \leq i < N_c, \quad (4.3.2-17)$$

5 where $\mu_g = 0.39$ is the gain slope, and then convert to linear channel gains:

$$6 \quad \gamma_{ch}(i) = \min \left\{ 1, 10^{\gamma_{dB}(i)/20} \right\}; \quad 0 \leq i < N_c, \quad (4.3.2-18)$$

7 4.3.2.9 Frequency Domain Filtering

8 Now, apply the channel gains to the transformed input signal $G(k)$:

$$9 \quad H(k) = \begin{cases} \gamma_{ch}(i)G(k) & ; f_L(i) \leq k \leq f_H(i), 0 \leq i < N_c, \\ G(k) & ; 0 \leq k < f_L(0), f_H(N_c - 1) < k \leq M/2, \end{cases} \quad (4.3.2-19)$$

10 where the bottom part of the equation represents the frequencies that are not altered by the channel gains. But,
11 it is also required that the magnitude of $H(k)$ be even, and the phase be odd, so that the following condition is
12 also imposed:

$$13 \quad H(M - k) = H^*(k); \quad 0 < k < M/2, \quad (4.3.2-20)$$

14 where * denotes complex conjugate. This guarantees that the imaginary part of the inverse DFT of $H(k)$ will be
15 zero (in Equation 4.1.2.11-1).

16 4.3.2.10 Background Noise Estimate Update

17 If (and only if) the update flag is set (*update_flag* == TRUE), then update the channel noise estimate for the
18 next frame by:

$$19 \quad E_n(m+1, i) = \max \{ E_{\min}, \alpha_n E_n(m, i) + (1 - \alpha_n) E_{ch}(m, i) \}; \quad 0 \leq i < N_c, \quad (4.3.2-21)$$

20 where $E_{\min} = 0.0625$ is the minimum allowable channel energy, and $\alpha_n = 0.9$ is the channel noise smoothing
21 factor. The channel noise estimate shall be initialized for each of the first four frames to the estimated channel
22 energy, i.e.:

$$23 \quad E_n(m, i) = \max \{ E_{\text{init}}, E_{ch}(m, i) \}; \quad 1 \leq m \leq 4, 0 \leq i < N_c, \quad (4.3.2-22)$$

24 where $E_{\text{init}} = 16$ is the minimum allowable channel noise initialization energy.

25 4.3.2.11 Time Domain Signal Reconstruction

26 Convert the filtered signal to the time domain using the inverse DFT:

$$27 \quad h(m, n) = \frac{1}{2} \sum_{k=0}^{M-1} H(k) e^{j2\pi nk/M}; \quad 0 \leq n < M. \quad (4.3.2-23)$$

1 Complete the frequency domain filtering process by applying overlap-and-add:

$$2 \quad h'(n) = \begin{cases} h(m, n) + h(m-1, n+L) & ; \quad 0 \leq n < M-L, \\ h(m, n) & ; \quad M-L \leq n < L. \end{cases} \quad (4.3.2-24)$$

3 Finally, apply signal de-emphasis by:

$$4 \quad s'(n+240) = h'(n) + \zeta_d s'(n+239); \quad 0 \leq n < L, \quad (4.3.2-25)$$

5 where $\zeta_d = 0.8$ is the de-emphasis factor and $\{s'(n)\}$ is the 320 element output buffer. Since the 10 ms per
6 frame Noise Suppression is performed twice per 20 ms speech frame, the output presented to Model Parameter
7 Estimation comprises $s'(n)$; $160 \leq n < 320$.

8 **4.4 Model Parameter Estimation**

9 Model Parameter Estimation comprises the linear predictive analysis, residual calculation and long-term
10 prediction that must be performed for each frame, independent of the rate decision.

11 **Inputs:** The inputs to model parameter estimation are:

- 12 • The current 20 ms frame number, m
- 13 • The pre-processed speech output vector, $\{s'(n)\}$
- 14 • The unquantized line spectral pairs, $\Omega(m-1)$, calculated in the previous frame
- 15 • The LPC prediction gain, $\gamma_{pc}(m-1)$, calculated in the previous frame

16 The pre-processed speech buffer, $\{s'(n)\}$, contains 320 pre-processed speech samples, i.e., $0 \leq n < 320$.
17 Samples 0 through 79 are “lookback” from the previous frame, samples 80 through 239 are the current frame,
18 and samples 240 through 319 are “lookahead” to the next frame. The last 160 samples from the preprocessing
19 modules, then, constitute 80 samples for the last half of the “current” frame and 80 samples “lookahead” to the
20 next frame.

21 **Outputs:** The outputs of model parameter estimation are:

- 22 • The unquantized linear predictive coefficients for the current frame, $\{a\}$
- 23 • The unquantized LSPs for the current frame, $\Omega(m)$
- 24 • The LPC prediction gain, $\gamma_{pc}(m)$
- 25 • The prediction residual, $\{a(n)\}$
- 26 • The long-term pitch delay estimate, τ
- 27 • The long-term prediction gain, β
- 28 • The spectral transition indicator, $LPCFLAG$
- 29 • The bandwidth expanded correlation coefficients, \mathbf{R}_w

30 **Processing:** The model parameter estimation module performs three major functions:

- 31 • Calculation of the formant filter parameters and prediction gain
- 32 • Generation of the short-term prediction residual signal

- Calculation of the delay estimate and long-term prediction gain

In addition to these functions, this module also generates a spectral transition indicator, which is used to improve channel impairment performance. The following sections describe each of the major model parameter estimation functions in detail.

4.4.1 Formant Filter Parameter Calculation

Inputs: The inputs to the formant filter parameter calculation are:

- The pre-processed speech input signal, $\{s'(n)\}$
- The LPC prediction gain from the previous frame, $\gamma_{lpc}(m-1)$

Outputs: The outputs of the formant filter parameter calculation are:

- The unquantized LPCs for the current frame $\{a\}$
- The unquantized LSPs for the current frame, $\Omega(m)$
- The LPC prediction gain, $\gamma_{lpc}(m)$
- The impulse response of the formant filter, $h(n)$
- The spectral transition indicator, $LPCFLAG$

Initialization:

- The LPC prediction gain, $\gamma_{lpc}(m) = 1$, for $m = 0$

Processing: The formant filter parameters are calculated from the pre-processed speech buffer, $\{s'(n)\}$, using the autocorrelation method and Durbin's Recursion. The details of the computation shall be executed as described in 4.4.1.1 through 4.4.1.3.

4.4.1.1 Direct Form LPC Parameter Calculation

For Service Option 3, the pre-processed speech buffer is windowed using a Hamming window centered at the end of the current frame, i.e., on sample 239. The equation for the Hamming window is:

$$W_H(k) = 0.54 - 0.46 \cos\left(\frac{2\pi}{160}(k-160)\right); \quad 160 \leq k < 320, \quad (4.4.1-1)$$

and the expression for the windowed speech is:

$$s'_H(k-160) = W_H(k)s'(k); \quad 160 \leq k < 320. \quad (4.4.1-2)$$

The first 17 terms of the autocorrelation function of $\{s'_H(n)\}$, \mathbf{R} , are calculated directly using:

$$R(k) = \sum_{i=0}^{159-k} s'_H(i)s'_H(i+k); \quad 0 \leq k < 16. \quad (4.4.1-3)$$

For Service Option 68, the pre-processed speech buffer is windowed using the assymmetric window given by

$$W_H(k) = \frac{\left(0.5 - 0.5 \cos\left(\frac{2\pi}{320}k\right)\right) e^{\frac{8.4k}{320}}}{286.5}; \quad 0 \leq k < 320 \quad (4.4.1-4)$$

and the expression for the windowed speech is:

$$s'_H(k) = W_H(k)s'(k); \quad 0 \leq k < 320 \quad (4.4.1-5)$$

The first 17 terms of the autocorrelation function of $\{s'_H(n)\}$, \mathbf{R} , are calculated directly using:

$$R(k) = \sum_{i=0}^{320-k} s'_H(k)s'_H(i+k); \quad 0 \leq k < 16 \quad (4.4.1-6)$$

The first 11 are used for LPC analysis, while all 17 terms are used by the Rate Determination Algorithm (see 4.3). The autocorrelation terms are then spectrally smoothed by windowing as follows:

$$R_w(k) = \begin{cases} 1.00003R(k); & k = 0, \\ \exp\left[-\frac{1}{2}\left(\frac{40\pi k}{8000}\right)^2\right]R(k); & 1 \leq k \leq 16. \end{cases} \quad (4.4.1-7)$$

The unquantized, unweighted LPCs, $\{\alpha\}$ are then calculated from \mathbf{R}_w using Durbin's Recursion[†], as follows:

$$\begin{aligned} & \{ \\ & E^{(0)} = R_w(0) \\ & i = 1 \\ & \text{while } (i \leq 10) \\ & \{ \\ & k_i = \frac{1}{E^{(i-1)}} \left[R_w(i) - \sum_{j=1}^{i-1} \alpha_j^{(i-1)} R_w(i-j) \right] \\ & \alpha_i^{(i)} = k_i \\ & j = 1 \\ & \text{while } (j < i) \\ & \{ \\ & \alpha_j^{(i)} = \alpha_j^{(i-1)} - k_i \alpha_{i-j}^{(i-1)} \\ & j = j + 1 \\ & \} \\ & E^{(i)} = (1 - k_i^2) E^{(i-1)} \\ & i = i + 1 \\ & \} \end{aligned}$$

[†] See Rabiner, L. R. and Schafer, R. W., *Digital Processing of Speech Signals*, (New Jersey: Prentice-Hall Inc, 1978), pp. 411-412. The superscripts in parentheses represent the stage of Durbin's recursion. For example $\alpha_j^{(i)}$ refers to α_j at the i th stage.

1 }
 2 }

3 The LPC coefficients are $\alpha_j^{(10)}$, for $1 \leq j \leq 10$, or $\{\alpha\} = \{\alpha_1, \alpha_2, \dots, \alpha_{10}\}$.

4 In SO 68, two additional parameters called “stoporder15”, and “stoporder30” are monitored during the
 5 Levinson Durbin recursion. These correspond to the iteration numbers where the prediction gains first cross 15
 6 dB and 30 dB respectively, and are defined by.

7 Stoporder15 = iteration index when $\frac{E^i}{E^0} > 10^{\frac{15}{10}}$, and

8 Stoporder30 = iteration index when $\frac{E^i}{E^0} > 10^{\frac{30}{10}}$.

9 If Stoporder30 ≤ 4 , the frame is encoded using Full-rate CELP.

10 If Stoporder15 ≤ 4 , and the frame is chosen for Half-rate CELP coding by the Voice Activity Detection
 11 function, then the frame is encoded using Full-rate CELP.

12 4.4.1.2 Generation of Spectral Transition Indicator (*LPCFLAG*)

13 The impulse response, $\{h_{raw}\}$, of the unweighted, unquantized formant filter is calculated to 54 terms. The
 14 unweighted, unquantized formant filter is given by:

15
$$\frac{1}{A_{raw}(z)} = \frac{1}{1 - \sum_{k=1}^{10} \alpha_k z^{-k}}, \quad (4.4.1-8)$$

16 where k is the LPC index. The energy of the raw impulse response is then calculated as an estimate of the LPC
 17 prediction gain. This is given by:

18
$$\gamma_{lpc}(m) = \sum_{k=0}^{53} h_{raw}^2(k). \quad (4.4.1-9)$$

19 If the ratio $\gamma_{lpc}(m)/\gamma_{lpc}(m-1) > 10$ (where $\gamma_{lpc}(m-1)$ is the LPC prediction gain from the previous frame), then the
 20 spectral transition indicator, *LPCFLAG*, is set to 1, indicating that a large spectral transition has occurred.
 21 Otherwise, *LPCFLAG* is set to 0.

22 4.4.1.3 Direct Form LPC to LSP Conversion

23 The raw LPCs are bandwidth expanded using an exponential window:

24
$$\alpha_k = (0.994)^k \alpha_k \quad ; 0 < k \leq 10 \quad (4.4.1-10)$$

25 The unquantized, bandwidth expanded LPCs are then converted to LSPs. Here, $A(z)$ is given by:

26
$$A(z) = 1 - \sum_{k=1}^{10} \alpha_k z^{-k}, \quad (4.4.1-11)$$

1 where $\{a\}$ are the bandwidth expanded LPC coefficients.

2 Next, define $P_A(z)$ and $Q_A(z)$ as follows:

$$3 \quad P_A(z) = A(z) + z^{-11} A(z^{-1}) = 1 + \sum_{i=1}^5 p_i z^{-i} + \sum_{i=6}^{10} p_{11-i} z^{-i} + z^{-11} \quad , \quad (4.4.1-12)$$

$$4 \quad Q_A(z) = A(z) - z^{-11} A(z^{-1}) = 1 + \sum_{i=1}^5 q_i z^{-i} - \sum_{i=6}^{10} q_{11-i} z^{-i} - z^{-11} \quad , \quad (4.4.1-13)$$

5 where $p_i = -a_i - a_{11-i}$; $1 \leq i \leq 5$, and $q_i = -a_i + a_{11-i}$; $1 \leq i \leq 5$. The LSP frequencies are the ten roots which exist
6 between $\omega = 0$ and $\omega = 0.5$ in the following two equations:

$$7 \quad P'(\omega) = \cos 5(2\pi\omega) + p'_1 \cos 4(2\pi\omega) + \dots + p'_4 \cos (2\pi\omega) + p'_5/2 \quad , \quad (4.4.1-14)$$

$$8 \quad Q'(\omega) = \cos 5(2\pi\omega) + q'_1 \cos 4(2\pi\omega) + \dots + q'_4 \cos (2\pi\omega) + q'_5/2 \quad , \quad (4.4.1-15)$$

9 where the p' and q' values are computed recursively as follows from the p and q values:

$$10 \quad p'_0 = q'_0 = 1 \quad , \quad (4.4.1-16)$$

$$11 \quad p'_i = p_i - p'_{i-1} \quad 1 \leq i \leq 5 \quad , \quad (4.4.1-17)$$

$$12 \quad q'_i = q_i + q'_{i-1} \quad 1 \leq i \leq 5. \quad (4.4.1-18)$$

13 Since the formant synthesis (LPC) filter is stable, the roots of the two functions alternate; the smallest root, ω_1 is
14 the lowest root of $P'(\omega)$, the next smallest root, ω_2 is the lowest root of $Q'(\omega)$, etc. Thus, $\omega_1, \omega_3, \omega_5, \omega_7$, and ω_9
15 are the roots of $P'(\omega)$, and $\omega_2, \omega_4, \omega_6, \omega_8$, and ω_{10} are the roots of $Q'(\omega)$. The corresponding unquantized LSP
16 parameter vector is defined as:

$$17 \quad \Omega(m) = \{ \omega_1, \omega_2, \dots, \omega_{10} \} \quad . \quad (4.4.1-19)$$

18 4.4.2 Generation of the Short-Term Prediction Residual

19 **Inputs:** The inputs to the short-term prediction residual calculation are:

- 20 • The unquantized LSPs from the previous frame, $\Omega(m-1)$
- 21 • The unquantized LSPs calculated for the current frame, $\Omega(m)$
- 22 • The pre-processed speech input vector, $\{s'(n)\}$

23 **Output:** The output of short-term prediction residual calculation is:

- 24 • The residual vector, $\{\varepsilon(n)\}$

25 This vector contains 320 elements, partitioned in the same way as the pre-processed speech input vector. The
26 first 80 samples represent the last 10 ms of the previous frame; the next 160 samples represent the current 20
27 ms frame, and the last 80 samples represent the 10 ms look-ahead.

1 **Initialization:** The unquantized LSPs, $\Omega(m, i) = 0.048i$; $m = 0, 1 \leq i \leq 10$.
 2 **Processing:** The short-term prediction residual signal, $\{\varepsilon(n)\}$, is generated by passing $\{s'(n)\}$ through the
 3 inverse filter created by interpolating between $\Omega(m-1)$ and $\Omega(m)$. The $\{s'(n)\}$ vector is divided into five
 4 segments, and a different set of interpolated LSPs is computed for each corresponding segment. The
 5 interpolated LSPs are converted to LPCs, and the appropriate segment of $\{s'(n)\}$ is convolved with the resulting
 6 filter to generate the corresponding samples of $\{\varepsilon(n)\}$. The initial state of the inverse filter shall be zero for
 7 each frame, m , i.e., this is a zero state filter. Also, throughout the following discussion, variables with a “dot”
 8 are implied to be interpolated, e.g., $\dot{\Omega}(m, k)$.

9 4.4.2.1 LSP Interpolation

10 For each segment k , the unquantized, interpolated LSP vector is:

11
$$\dot{\Omega}(m, k) = (1 - \mu_k)\Omega(m-1) + \mu_k\Omega(m) \quad ; 0 \leq k \leq 4 \tag{4.4.2-1}$$

12 where the interpolator constants, $\{\mu_k\}$, and their corresponding sets of sample indices for each segment of
 13 $\{s'(n)\}$ are given in Table 4-4.

14
 15

Table 4-4. LSP Interpolation Constants

k	segment start sample	segment end sample	μ_k
0	0	79	0.0
1	80	132	0.1667
2	133	185	0.5
3	186	239	0.8333
4	240	319	1.0

16

17 4.4.2.2 LSP to Direct Form LPC Conversion

18 For each segment, $0 \leq k \leq 4$, the following process is executed. First, $\dot{P}_A(z)$ and $\dot{Q}_A(z)$ are computed from a
 19 set of interpolated LSP frequencies, $\dot{\Omega}(m, k)$, as follows:

20
$$\dot{P}_A(z) = (1 + z^{-1}) \prod_{j=1}^5 \left(1 - 2z^{-1} \cos \left(2\pi \dot{\omega}_{(2j-1)} \right) + z^{-2} \right), \tag{4.4.2-2}$$

21
$$\dot{Q}_A(z) = (1 - z^{-1}) \prod_{j=1}^5 \left(1 - 2z^{-1} \cos \left(2\pi \dot{\omega}_{(2j)} \right) + z^{-2} \right), \tag{4.4.2-3}$$

1 where $\{\dot{\omega}_1, \dot{\omega}_2, \dots, \dot{\omega}_{10}\} = \dot{\Omega}(m, k)$, and the k is implied. These equations can also be expressed as:

$$2 \quad \dot{P}_A(z) = 1 + \sum_{i=1}^5 \dot{p}_i z^{-i} + \sum_{i=6}^{10} \dot{p}_{11-i} z^{-i} + z^{-11}, \quad (4.4.2-4)$$

$$3 \quad \dot{Q}_A(z) = 1 + \sum_{i=1}^5 \dot{q}_i z^{-i} - \sum_{i=6}^{10} \dot{q}_{11-i} z^{-i} - z^{-11}. \quad (4.4.2-5)$$

4 Then the LPC coefficients are computed from the coefficients of $\dot{P}_A(z)$ and $\dot{Q}_A(z)$ as follows:

$$5 \quad \dot{A}(z) = \frac{\dot{P}_A(z) + \dot{Q}_A(z)}{2}, \quad (4.4.2-6)$$

$$6 \quad = 1 + \sum_{i=1}^5 \frac{(\dot{p}_i + \dot{q}_i)}{2} z^{-i} + \sum_{i=6}^{10} \frac{(\dot{p}_{11-i} + \dot{q}_{11-i})}{2} z^{-i}, \quad (4.4.2-7)$$

$$7 \quad \dot{A}(z) = 1 - \sum_{i=1}^{10} \dot{a}_i z^{-i}. \quad (4.4.2-8)$$

8 So, the interpolated LPC coefficients for segment k of the current frame are given by:

$$9 \quad \dot{a}_i(k) = \begin{cases} \frac{\dot{p}_i + \dot{q}_i}{2} & ; 1 \leq i \leq 5 \\ -\frac{\dot{p}_{11-i} + \dot{q}_{11-i}}{2} & ; 6 \leq i \leq 10 \end{cases} \quad (4.4.2-9)$$

10 4.4.2.3 Generation of Residual Samples

11 The short-term prediction residual, $\dot{\varepsilon}(n)$, is generated by passing $s'(n)$ through the inverse filter using the
12 appropriate LPCs:

$$13 \quad \dot{\varepsilon}(n) = s'(n) - \sum_{i=1}^{10} \dot{a}_i(k) s'(n-i), \quad (4.4.2-10)$$

14 where the value for k in $\dot{a}_i(k)$ is determined by the segment in which n lies as determined by the starting and
15 ending sample numbers indicated in Table Table 4-4. All values of $s'(n)$ for $n < 0$ are zero.

16 4.4.3 Calculation of the Delay Estimate and Long-Term Prediction Gain

17 **Inputs:** The input to the delay estimate and long-term prediction gain calculation is:

- 18 • The short-term residual vector, $\{\dot{\varepsilon}(n)\}$

1 **Outputs:** The outputs of the delay estimate and long-term prediction gain calculation are:

- 2 • The pitch delay estimate, τ
- 3 • The long-term prediction gain, β

4 **Initialization:** The values of all local state variables and buffers are set to zero at start-up.

5 **Processing:** The pitch delay shall be calculated using the method described in this section. The pitch delay is
6 the delay that maximizes the autocorrelation function of the short-term prediction residual signal, subject to
7 certain constraints. This calculation is carried out independently over two estimation windows. The first of
8 these comprises the entire current frame; the second comprises the second half of the current frame and the
9 look-ahead. Rules are then applied to combine the delay estimates and gains for the two estimation windows.
10 The constrained search for the optimal delay in each window shall be carried out as follows:
11 The processes in 4.4.3.1 through 4.4.3.3 shall be performed once for each of the two estimation windows of
12 each frame.

13 4.4.3.1 Non-exhaustive Open Loop Delay Search

14 The residual signal, $\{x(n)\}$, is filtered and decimated by a factor of four to generate the decimated residual
15 signal, $\{\varepsilon_d(n)\}$, by applying:

$$16 \quad x(n) = \varepsilon(n + n_{start}) + 2.2875x(n-1) - 1.956x(n-2) + 0.5959x(n-3); \quad 0 \leq n < 80, \quad (4.4.3-1)$$

17 then:

$$18 \quad \varepsilon_d(n') = \varepsilon_d(n' + 20), \quad 0 \leq n' < 20, \quad (4.4.3-2)$$

19 and finally:

$$20 \quad \varepsilon_d(n') = x(4n' - 77) - 0.312[x(4n' - 78) + x(4n' - 79)] + x(4n' - 80), \quad 20 \leq n' < 40 \quad (4.4.3-3)$$

21 where $\{x(n)\}$ is the decimator filter memory, $\{\varepsilon_d(n)\}$ is the decimated residual buffer, and n_{start} is 160 for the
22 first estimation window and 240 for the second estimation window. The autocorrelation function of this
23 decimated residual signal is generated using:

$$24 \quad r(d) = \sum_{k=0}^{40-d} \varepsilon_d(k) \varepsilon_d(k+d) \quad ; 5 \leq d \leq 30, \quad (4.4.3-4)$$

25 and the delay, d_{max} , corresponding to the maximum positive correlation, r_{max} , is found.

26 4.4.3.2 Refinement of open loop delay estimate for SO 3

27 The following operations are then performed to determine whether to use d_{max} as the decimated delay estimate,
28 or to use an estimate in the neighborhood of the smoothed delay estimate, $\tilde{\tau}$, instead:

$$29 \quad \text{if } (\tilde{\tau} \neq 0 \text{ AND } |\tilde{\tau} - 4d_{max}| > 2) \{$$

$$30 \quad \quad \text{if } (r'_{max} > 0.835 r_{max}) \{$$

$$31 \quad \quad \quad d_{max} = d'_{max}$$

$$32 \quad \quad \quad \}$$

$$33 \quad \quad \}$$

34 where d'_{max} is calculated as the delay corresponding to the maximum positive value of $\{r(d)\}$ in the range: $\max\{$
35 $5, \lfloor \tilde{\tau} / 4 \rfloor - 2 \} \leq d \leq \min\{ 30, 4 + \max\{ 5, \lfloor \tilde{\tau} / 4 \rfloor - 2 \} \}$, and $\tilde{\tau}$ is updated per Equation 4.4.3-11.

36 The optimal delay estimate, D_{max} , is calculated as the index corresponding to R_{max} , which is the maximum
37 positive value of:

$$R(D) = \sum_{n=0}^{159-D} \varepsilon(n+n_0)\varepsilon(n+n_0+D) ; \max\{20, 4d_{\max}-3\} \leq D \leq \min\{120, 4d_{\max}+3\}, \quad (4.4.3-5)$$

where $n_0 = 80$ and 160 for the respective first and second estimation windows.

4.4.3.3 Refinement of open loop delay estimate for SO 68

The original residual, $\varepsilon(n)$, is then used to compute additional correlation around d_{\max}

$$rr(d) = \sum_{k=0}^{160-d} \varepsilon(k)\varepsilon(k+d); \quad M1 \leq d \leq M2$$

where, $M1 = \max(20, d_{\max}-3)$, and $M2 = \min(120, d_{\max}+3)$.

and the delay, dd_{\max} , corresponding to the maximum positive correlation, rr_{\max} , is found, and the normalized correlation is.

$$\beta = \min \left(\max \left(\frac{rr_{\max}}{\text{sqrt} \left(\left(\sum_{k=0}^{160-dd_{\max}-1} (\varepsilon(k))^2 \right) \left(\sum_{k=dd_{\max}}^{160-1} (\varepsilon(k))^2 \right) \right)} \right) \right)$$

The following operations are then performed to determine whether to use dd_{\max} as the decimated delay estimate, or to use an estimate in the neighborhood of the smoothed delay estimate, $\hat{\tau}$, instead:

Similar to above, an estimate of the delay dp_{\max} within 6 samples of smoothed delay estimate $\hat{\tau}$, the corresponding maximum positive correlation, rp_{\max} , and the normalized correlation, βp are determined.

If $\tilde{\tau} \neq 0$ AND $|\tilde{\tau} - dd_{\max}| > 6$, and if the normalized correlation around the smoothed delay estimate is greater than a weighted version of the normalized correlation of the current frame, then the delay estimate around the smoothed delay is used for the current frame. That is, if $\beta p > w \cdot \beta$ (where $w=0.6$ if $dd_{\max} > \hat{\tau} + 6$, $w=1.2$ if $dd_{\max} > \hat{\tau} - 6$, $w=10$ otherwise) then $\beta = \beta p$, and $dd_{\max} = dp_{\max}$.

A further check for pitch halving is performed to further refine the delay estimate if $dd_{\max} > 40$. Similar to above, an estimate of the delay dh_{\max} within 2 samples of smoothed delay estimate $dd_{\max}/2$, the corresponding maximum positive correlation, rh_{\max} , and the normalized correlation, βh are determined. If $\beta h > 0.8 \cdot \beta$

then $\beta = \beta h$, and $dd_{\max} = dh_{\max}$

4.4.3.4 Long-Term Prediction Gain Calculation

The energy of the undecimated residual is calculated as follows:

$$R_{\varepsilon}(d) = \sqrt{\sum_{i=0}^{159-D_{\max}} \varepsilon^2(i+n_0) \sum_{j=0}^{159-D_{\max}} \varepsilon^2(j+n_0+D_{\max})}, \quad (4.4.3-6)$$

1 from which the long-term prediction gain can be derived by:

$$2 \quad \beta = \max \left\{ 0, \min \left\{ 1, \frac{R_{\max}}{R_{\varepsilon}(0)} \right\} \right\}. \quad (4.4.3-7)$$

3 4.4.3.5 Smoothed Delay Estimate and LTP Gain for SO3

4 The following operations are performed to determine whether to replace the values of β and D_{\max} calculated in
5 4.4.3.1 and 4.4.3.2 by values obtained in the neighborhood of the smoothed delay estimate, $\tilde{\tau}$:

$$6 \quad \text{if} (\tilde{\tau} > 0) \{$$

$$7 \quad \quad \text{if} ((D_{\max} > \min \{120, \tilde{\tau} + 6\} \text{ AND } \beta' > 0.6\beta) \text{ OR}$$

$$8 \quad \quad (D_{\max} < \min \{20, \tilde{\tau} - 6\} \text{ AND } (\beta' > 1.2\beta)) \{$$

$$9 \quad \quad \quad \beta = \beta'$$

$$10 \quad \quad \quad D_{\max} = D'_{\max}$$

$$11 \quad \quad \quad \}$$

$$12 \quad \quad \}$$

13 where D'_{\max} is the index of R'_{\max} , the maximum positive value of:

$$14 \quad R'(D) = \sum_{n=0}^{159-D} \varepsilon(n+n_0)\varepsilon(n+n_0+D) \quad ; \quad \max \{20, \tilde{\tau} - 6\} \leq D \leq \min \{120, \tilde{\tau} + 6\} \quad (4.4.3-8)$$

15 and:

$$16 \quad \beta' = \max \left\{ 0, \min \left\{ 1, \frac{R'_{\max}}{\sum_{i=0}^{159-D'_{\max}} \varepsilon^2(i+n_0) \sum_{j=0}^{159-D'_{\max}} \varepsilon^2(j+n_0+D'_{\max})} \right\} \right\}. \quad (4.4.3-9)$$

17 The smoothed delay and long-term prediction gain estimates are updated as follows:

$$18 \quad \tilde{\beta} = \begin{cases} \beta & ; \beta > 0.4, \\ 0.75\tilde{\beta} & ; \text{otherwise,} \end{cases} \quad (4.4.3-10)$$

19 then:

$$20 \quad \tilde{\tau} = \begin{cases} D_{\max} & ; \beta > 0.4, \\ \tilde{\tau} & ; \beta \leq 0.4 \text{ AND } \tilde{\beta} \geq 0.3, \\ 0 & ; \text{otherwise} \end{cases} \quad (4.4.3-11)$$

21 4.4.3.6 Smoothed delay estimate and LTP gain for SO 68

22 The smoothed delay and long-term prediction gain estimates are updated as follows:

$$\tilde{\beta} = \begin{cases} \beta & ; \beta > 0.4, \\ 0.75\tilde{\beta} & ; \text{otherwise,} \end{cases} \quad (4.4.3-12)$$

then:

$$\tilde{\tau} = \begin{cases} dd_{\max}; & \beta > 0.4 \\ \tilde{\tau}; & \beta \leq 0.4 \text{ AND } \tilde{\beta} \geq 0.3 \\ 0; & \text{otherwise} \end{cases} \quad (4.4.3-13)$$

4.4.3.7 Composite Delay and Gain Calculations for SO 3

The delay estimates and long-term prediction gains for the two estimation windows are combined as follows:

Let (D_0, β_0) be the optimal delay and gain found for the window comprising the current frame, and let (D_1, β_1) be the optimal delay and gain found for the window comprising the second half of the current frame and the look-ahead. Then:

```

if (  $\beta_0 > \beta_1 + 0.4$  ) {
  if (  $|D_0 - D_1| > 15$  ) {
     $\tau = D_0$ 
     $\beta = \beta_0$ 
  }
  else {
     $\tau = (D_0 + D_1) / 2$ 
     $\beta = (\beta_0 + \beta_1) / 2$ 
  }
}
else {
   $\tau = D_1$ 
   $\beta = \beta_1$ 
}

```

4.4.3.8 Composite delay and gain calculations for SO 68

The delay estimates and long-term prediction gains for the two estimation windows are combined as follows:

Let (D_0, β_0) be the optimal delay and gain found for the window comprising the current frame, and let (D_1, β_1) be the optimal delay and gain found for the window comprising the second half of the current frame and the look-ahead. Then:

```

1
2     if (  $\beta_0 > \beta_1 + 0.4$  ) {
3         if (  $|D_0 - D_1| > 15$  ) {
4              $\tau = D_0$ 
5              $\beta = \beta_0$ 
6         }
7         else {
8              $\tau = (D_0 + D_1) / 2$ 
9              $\beta = (\beta_0 + \beta_1) / 2$ 
10        }
11    }
12    else if (  $\beta_0 > \beta_1 + 0.05$  AND  $|D_0 - last\_delay| < 7$  ) {
13        if (  $|D_0 - D_1| > 15$  ) {
14             $\tau = D_0$ 
15             $\beta = \beta_0$ 
16        }
17        else {
18            
$$\tau = \arg \max_d \left( \sum_{k=40}^{160-d} \varepsilon(k) \varepsilon(k+d) \right);$$

19            
$$\left( \frac{D_0 + D_1}{2} - 1 \right) \leq d \leq \left( \frac{D_0 + D_1}{2} + 1 \right)$$

20             $\beta = (\beta_0 + \beta_1) / 2$ 
21        }
22    }
23    else {
24         $\tau = D_1$ 
25         $\beta = \beta_1$ 
26    }
27

```

4.5 Determining the Data Rate for SO 3 and Voice Activity Detection for SO 68

For SO 3, the rate determination algorithm (RDA) is used to select one of three encoding rates: Rate 1, Rate 1/2, and Rate 1/8. Active speech is encoded at Rate 1 or Rate 1/2, and background noise is encoded at Rate 1/8.

For SO 68, The RDA that is described here is essentially a Voice Activity Detector that first separates active speech from background noise. Mode-decision, and a final rate-determination described in Section 4.6, and Section 4.6.4 are used to determine the final coding rate, and type of speech coding.

The actual data rate used for encoding the input signal may be modified to be Rate 1/2 maximum for the purpose of inserting a signaling message (see 2.2.1). Refer to 1.1 for guidelines concerning potential variations of the RDA.

Inputs:

- The bandwidth expanded correlation coefficients, R_W
- The long-term prediction gain, β

Outputs:

- 1 • The speech encoder rate for the current frame, $Rate(m)$

2 **Initialization:**

- 3 • The rate histories, $Rate(m-1)$ and $Rate(m-2)$, are set to Rate 1/8 frames.
- 4 • The band energy, $E_{f(i)}^{sm}(m)$, initialization is given in 4.5.2.1.
- 5 • The background noise estimate, $B_{f(i)}(m)$, initialization is given in 4.5.2.2.
- 6 • The signal energy estimate, $S_{f(i)}(m)$, initialization is given in 4.5.2.3.

7 **Processing:**

- 8 • The data rate shall be determined by the processing steps defined in 4.5.1 and 4.5.2.

9 4.5.1 Estimating the Data Rate Based on Current Signal Parameters

10 The encoding rate is determined by comparing the current frame energy in each of two frequency bands, $f(1)$
 11 and $f(2)$, to background noise estimates in these respective bands. Thresholds above the background noise in
 12 each band are determined by an estimated signal-to-noise ratio in each band. These thresholds are set for Rate
 13 1, Rate 1/2, and Rate 1/8 encoding. The highest rate calculated from the two frequency bands is then selected
 14 as the encoding rate for the current frame.

15 4.5.1.1 Computing Band Energy

16 The rate determination algorithm uses energy thresholds to determine the encoding rate for the current frame.
 17 The input speech is divided into two distinct bands: band $f(1)$ spans 0.3-2.0 kHz, band $f(2)$ spans 2.0-4.0 kHz.†
 18 The band energy for band $f(i)$, $BE_{f(i)}$, is calculated as

$$19 \quad BE_{f(i)} = R_w(0)R_{f(i)}(0) + 2.0 \sum_{k=1}^{L_h-1} R_w(k)R_{f(i)}(k) \quad (4.5.1-1)$$

20 where:

$$21 \quad R_{f(i)}(k) = \sum_{n=0}^{L_h-1-k} h_i(n)h_i(n+k) \quad ; 0 \leq k < L_h \quad (4.5.1-2)$$

22 and $h_i(n)$ is the impulse response of the band-pass filter i , where $i = 1, 2$. $R_w(k)$ is the autocorrelation sequence
 23 defined in Equation 4.4.1-7, and $L_h = 17$ is the length of the impulse response of the band-pass filters.

24 The band-pass filters used for both frequency bands are defined in Table 4-5.

25 **Table 4-5. FIR Filter Coefficients Used for Band Energy Calculations**

† Whenever a variable (or symbol or value) with a subscript $f(i)$ appears in any equation or pseudocode in 4.5, it refers to a variable (or symbol or value) associated with either band $f(1)$ or band $f(2)$.

n	$h_1(n)$ (lower band)	n	$h_2(n)$ (upper band)
0	-5.557699E-02	0	-1.229538E-02
1	-7.216371E-02	1	4.376551E-02
2	-1.036934E-02	2	1.238467E-02
3	2.344730E-02	3	-6.243877E-02
4	-6.071820E-02	4	-1.244865E-02
5	-1.398958E-01	5	1.053678E-01
6	-1.225667E-02	6	1.248720E-02
7	2.799153E-01	7	-3.180645E-01
8	4.375000E-01	8	4.875000E-01
9	2.799153E-01	9	-3.180645E-01
10	-1.225667E-02	10	1.248720E-02
11	-1.398958E-01	11	1.053678E-01
12	-6.071820E-02	12	-1.244865E-02
13	2.344730E-02	13	-6.243877E-02
14	-1.036934E-02	14	1.238467E-02
15	-7.216371E-02	15	4.376551E-02
16	-5.557699E-02	16	-1.229538E-02

1 4.5.1.2 Calculating Rate Determination Thresholds

2 The rate determination thresholds for each frequency band $f(i)$ are a function of both the background noise
3 estimate, $B_{f(i)}(m-1)$, and the signal energy estimate, $S_{f(i)}(m-1)$, of the previous or $(m-1)$ th frame. Two
4 thresholds for each band are computed as

5
$$T_1(B_{f(i)}(m-1), SNR_{f(i)}(m-1)) = k_1(SNR_{f(i)}(m-1))B_{f(i)}(m-1), \quad (4.5.1-3)$$

6
$$T_2(B_{f(i)}(m-1), SNR_{f(i)}(m-1)) = k_2(SNR_{f(i)}(m-1))B_{f(i)}(m-1), \quad (4.5.1-4)$$

7 where the integer $SNR_{f(i)}(m-1)$ is:

8
$$SNR_{f(i)}(m-1) = \begin{cases} 0 & ; QSNRU_{f(i)}(m-1) < 0, \\ QSNRU_{f(i)}(m-1) & ; 0 \leq QSNRU_{f(i)}(m-1) \leq 7 \\ 7 & ; QSNRU_{f(i)}(m-1) > 7 \end{cases} \quad (4.5.1-5)$$

9 and where:

10
$$QSNRU_{f(i)}(m-1) = round\left\{\left(10\log_{10}\left(S_{f(i)}(m-1)/B_{f(i)}(m-1)\right) - 20\right)/5\right\}. \quad (4.5.1-6)$$

1 4.5.1.2.1 SO 3

2 The functions $k1(\bullet)$ and $k2(\bullet)$ are defined in Table 4-6, and $B_{f(i)}(m-1)$ and $S_{f(i)}(m-1)$ are defined in 4.5.2.2 and
 3 4.5.2.3, respectively.

4

5

Table 4-6. Threshold Scale Factors as a Function of SNR

$SNR_{f(i)}(m-1)$	$k1(SNR_{f(i)}(m-1))$	$k2(SNR_{f(i)}(m-1))$
0	7.0	9.0
1	7.0	12.6
2	8.0	17.0
3	8.6	18.5
4	8.9	19.4
5	9.4	20.9
6	11.0	25.5
7	31.6	79.6

6

7 4.5.1.2.2 SO 68

8 The functions $k1(\bullet)$ and $k2(\bullet)$ depend on the anchor operating point, and are defined in **Table 4-7**, and $B_{f(i)}(m-1)$
 9 and $S_{f(i)}(m-1)$ are defined in Sections 4.5.2.2 and 4.5.2.3, respectively.

10

Table 4-7 Threshold scale factors as a function of SNR

$SNR_{f(i)}(m-1)$	$k1(SNR_{f(i)}(m-1))$	$k2(SNR_{f(i)}(m-1))$
0	7.0	9.0
1	7.0	12.6
2	8.0	17.0
3	8.6	18.5
4	8.9	19.4
5	9.4	20.9
6	22.0	51.0
7	73.2	158.2

11

12

Table 4-8 Threshold scale factors as a function of SNR

SNRf(i)(m-1)	k1(SNRf(i)(m-1))	k2(SNRf(i)(m-1))
0	7.0	9.0
1	7.0	12.6
2	8.0	17.0
3	8.6	18.5
4	8.9	19.4
5	11.3	25.1
6	33.0	76.5
7	126.4	318.4

Table 4-9 Threshold scale factors as a function of SNR

SNRf(i)(m-1)	k1(SNRf(i)(m-1))	k2(SNRf(i)(m-1))
0	7.0	9.0
1	8.7	15.8
2	9.0	18.5
3	10.0	20.0
4	10.6	22.8
5	13.8	31.6
6	50.2	158.5
7	200.0	631.0

The threshold scale factors are identical for the low- and high-frequency bands.

4.5.1.3 Comparing Thresholds

Band energy, $BE_{f(i)}$, is compared with two thresholds: $T_1(B_{f(i)}(m-1), SNR_{f(i)}(m-1))$ and $T_2(B_{f(i)}(m-1), SNR_{f(i)}(m-1))$. If $BE_{f(i)}$ is greater than both thresholds, Rate 1 is selected. If $BE_{f(i)}$ is greater than only one threshold, Rate 1/2 is selected. If $BE_{f(i)}$ is at or below both thresholds, Rate 1/8 is selected. This procedure is performed for both frequency bands and the higher of the two encoding rates selected from the individual bands is chosen as the preliminary data rate, $Rate(m)$, of the current frame m .

4.5.1.4 Performing Hangover

If the preliminary data rate decision (from 4.5.1) transitions from at least two consecutive Rate 1 frames to a lower rate frame, then the next M frames are encoded as Rate 1 before allowing the encoding rate to drop to Rate 1/2 and finally to Rate 1/8. The number of hangover frames, M , is a function of the $SNR_{f(1)}(m-1)$ (the

SNR in the lower frequency band) and is denoted as $Hangover(SNR_{f(1)}(m-1))$ in Table 4-10. $SNR_{f(1)}(m-1)$ is calculated as defined in Equation 4.5.1-5. The hangover algorithm is defined by the following pseudocode:

```

{
  if ( Rate(m) == Rate 1 )
    count = 0
  if ( Rate(m-1) == Rate 1 and Rate(m-2) == Rate 1 and Rate(m) != Rate 1 ) {
    if ( count == 0 )
      M = Hangover(SNRf(1)(m-1))
    if ( count < M ) {
      Rate(m) = Rate 1
      count = count + 1
    }
  }
}

```

where $Rate(m)$ is the rate of the current frame and $Rate(m-1)$ and $Rate(m-2)$ are the rates of the previous two frames, respectively. Also, the rates for the previous frames, as used here, are those generated by the RDA prior to override logic, and are, therefore, not subject to modification by external rate control as described in 4.5.1.5.

4.5.1.4.1 Hangover Table for SO 3

Table 4-10. Hangover Frames as a Function of SNR

SNR _{f(1)} (m-1)	Hangover (SNR _{f(1)} (m-1))
0	7
1	7
2	7
3	3
4	0
5	0
6	0
7	0

4.5.1.4.2 Hangover Table for SO 68

For SO 68, the hangover table is chosen to be one of the three tables **Table 4-11** to **Table 4-13** depending on the Anchor operating point (viz, required aggressiveness of the VAD to meet the capacity operating point).

Table 4-11 Hangover frames as a function of SNR

SNR _{f(1)} (m-1)	Hangover (SNR _{f(1)} (m-1))
0	5
1	5

SNRf(1)(m-1)	Hangover (SNRf(1)(m-1))
2	4
3	3
4	0
5	0
6	0
7	0

1

2

Table 4-12 Hangover frames as a function of SNR

SNRf(1)(m-1)	Hangover (SNRf(1)(m-1))
0	4
1	4
2	2
3	2
4	0
5	0
6	0
7	0

3

4

Table 4-13 Hangover frames as a function of SNR

SNRf(1)(m-1)	Hangover (SNRf(1)(m-1))
0	4
1	3
2	2
3	1
4	0
5	0
6	0
7	0

5

4.5.1.5 Constraining Rate Selection

The rate selected by the procedures described in 4.5.1.3 and 4.5.1.4 are used for the current frame except where it is modified by the following constraints.

If the previous frame was selected as Rate 1 and the current frame is selected as Rate 1/8, then the encoding rate of the current frame should be modified to Rate 1/2. There are no other restrictions on encoding rate transitions.

If the speech codec has been commanded to generate a Rate 1/2 maximum packet and the rate determined is Rate 1, it generates a Rate 1/2 packet. If the speech codec has been requested to generate a Blank packet, it generates a packet based on the rate determined by the rate determination algorithm (RDA).

4.5.2 Updating RDA Parameters

After the RDA is complete, RDA parameters shall be updated as described in 4.5.2.1 through 4.5.2.3.

4.5.2.1 Updating the Smoothed Band Energy

The band energy, $BE_{f(i)}$, calculated in Equation 4.5.1-1 is smoothed and used to estimate both the background noise energy (see 4.5.2.2) and signal energy (see 4.5.2.3) in each band. The smoothed band energy, $E_{f(i)}^{sm}(m)$, is computed as:

$$E_{f(i)}^{sm}(m) = \alpha_E(m)E_{f(i)}^{sm}(m-1) + (1 - \alpha_E(m))BE_{f(i)} \quad ; \quad 1 \leq i \leq 2 \quad (4.5.2-1)$$

where m refers to the current frame, and

$$\alpha_E(m) = \begin{cases} 0 & ; m \leq 1, \\ 0.6 & ; m > 1. \end{cases} \quad (4.5.2-2)$$

This allows the smoothed band energy to be initialized to the band energy of the first frame ($m = 1$).

4.5.2.2 Updating the Background Noise Estimate

An estimate of the background noise level, $B_{f(i)}(m)$, is computed for the current, or m th, frame using $B_{f(i)}(m-1)$, $E_{f(i)}^{sm}(m)$ (see 4.5.2.1) and $SNR_{f(i)}(m-1)$ (see 4.5.1.2). Pseudocode describing the background noise update for band $f(i)$ is given as

```

{
  if (  $\beta < 0.30$  for 8 or more consecutive frames )
     $B_{f(i)}(m) = \min \{ E_{f(i)}^{sm}(m), 80954304, \max \{ 1.03B_{f(i)}(m-1), B_{f(i)}(m-1) + 1 \} \}$ 
  else {
    if (  $SNR_{f(i)}(m-1) > 3$  )
       $B_{f(i)}(m) = \min \{ E_{f(i)}^{sm}(m), 80954304, \max \{ 1.00547B_{f(i)}(m-1), B_{f(i)}(m-1) + 1 \} \}$ 
    else
       $B_{f(i)}(m) = \min \{ E_{smf(i)}(m), 80954304, B_{f(i)}(m-1) \}$ 
  }
  if (  $B_{f(i)}(m) < \text{lownoise}(i)$  )
     $B_{f(i)}(m) = \text{lownoise}(i)$ 
}

```

1 where β , $E^{sm}f(i)(m)$, and $SNRf(i)(m-1)$ are defined in 4.4.3 and Equations 4.5.2-1 and 4.5.1-5, respectively.
 2 $lownoise(1)$ equals 160.0 and $lownoise(2)$ equals 80.0.
 3 At initialization, the background noise estimate for the first frame, $Bf(i)(0)$, is set to 80,954,304 for both
 4 frequency bands, and the consecutive frame counter for β is set to zero. Initialization also occurs if the audio
 5 input to the encoder is disabled and then enabled.†

6 4.5.2.3 Updating the Signal Energy Estimate

7 The signal energy, $Sf(i)(m)$, is computed as

$$\begin{aligned}
 & \{ \\
 & \text{If } (\beta > 0.5 \text{ for 5 or more consecutive frames}) \\
 & \quad Sf(i)(m) = \max \{ E^{sm}f(i)(m), \min \{ 0.97Sf(i)(m-1), Sf(i)(m-1) - 1 \} \} \\
 & \text{else} \\
 & \quad Sf(i)(m) = \max \{ E^{sm}f(i)(m), Sf(i)(m-1) \} \\
 & \}
 \end{aligned}$$

14 where β and $E_{f(i)}^{sm}(m)$ are defined in Section 4.4.3 and Equation 4.5.2-1, respectively.

15 At initialization, the signal energy estimates for the first frame, $Sf(1)(0)$ and $Sf(2)(0)$, are set to 51,200,000 and
 16 5,120,000, respectively, and the consecutive frame counter for β is set to zero. Initialization also occurs if the
 17 audio input to the encoder is disabled and then enabled.

18 4.6 Mode decision and Rate decision for SO 68

19 While the RDA block mentioned above aims to classify the speech broadly into speech, and background noise,
 20 the Mode-Decision block further classifies the non-silence part of the input is further classified using a multi-
 21 level decision logic into transition, voiced, unvoiced and end-of-word, based on a variety of features and the
 22 desired operating point.

23 4.6.1 Pitch-based NACF

24 An important feature that is used in the mode-decision is the pitch-based autocorrelation similar to the β that
 25 was computed in the Open-loop pitch section. The procedure for computing the pitch based NACF is shown in
 26 the flowcharts below.

27 Inputs

28 residual – formant residual of current frame and look-ahead frame computed with unquantized LPC

29 D_0, D_1 – delay estimates for the first and second subframe of the current frame

† This prevents the silence before the audio is connected from being mistaken as unusually low background noise.

Outputs

nacf[4] – NACF from 4-subframe NACF track searching, returned value

nacf_at_pitch – Maximum NACF around pitch estimates for 3 subframes




Figure 4.6-1 Pitch-based NACF computation

1 4.6.2 Pitch based NACF computation

2 The Open Loop Pitch Search provides the NACF, a key ingredient for mode.

3 4.6.2.1 Decimation of formant residual (current frames and look-ahead frames)

4 The formant residual of the current frame, and the look-ahead frame is first filtered through a 3rd order High-
5 pass, with 3dB cut-off frequency at about 100 HZ.

6 It is then low-pass filtered with a FIR filter of length 13 and then decimated by a factor of 2. This decimated
7 residual signal is denoted by $r_d(n)$.

8 4.6.2.2 NACF Computation for the two subframes of current frame

9 The normalized autocorrelation functions (NACFs) for two subframes of the current frame are computed as

$$10 \quad nacf(k) = MAX \left(\frac{\text{sign} \left(\sum_{n=0}^{40-1} (r_d(40k+n)r_d(40k+n-lag(k)+i)) \right) \left(\sum_{n=0}^{40-1} (r_d(40k+n)r_d(40k+n-lag(k)+i)) \right)^2}{\left(\sum_{n=0}^{40-1} (r_d(40k+n)r_d(40k+n)) \right) \left(\sum_{n=0}^{40-1} (r_d(40k+n-lag(k)+i)r_d(40k+n-lag(k)+i)) \right)} \right) \quad (4.6.2-1)$$

11 for $k=1,2$, and the maximization done over all integer i such that,

$$12 \quad - \frac{1 + MAX(6, MIN(0.2 \cdot pitchlag(k), 16))}{2} \leq i \leq \frac{1 + MAX(6, MIN(0.2 \cdot pitchlag(k), 16))}{2}$$

13 14 4.6.2.3 NACF computation for the look-ahead frame

15 The normalized autocorrelation functions (NACFs) for the lookahead subframe is computed as

$$16 \quad nacf(2) = MAX \left(\frac{\text{sign} \left(\sum_{n=0}^{80-1} (r_d(80+n)r_d(80+n-i)) \right) \left(\sum_{n=0}^{80-1} (r_d(80+n)r_d(80+n-i)) \right)^2}{\left(\sum_{n=0}^{80-1} (r_d(80+n)r_d(80+n)) \right) \left(\sum_{n=0}^{80-1} (r_d(80+n-i)r_d(80+n-i)) \right)} \right) \quad (4.6.2-2)$$

17 the maximization done over all integer i such that,

$$18 \quad \frac{20}{2} \leq i < \frac{120}{2}$$

1 4.6.3 Speech Coding Mode decision algorithm

2 **Definitions**

- 3 Transient – voiced but less periodic speech, encoded with full rate CELP
- 4 Up-transient – first voiced frame in active speech, encoded the same way as transient
- 5 Down-transient – low energy voiced speech typically at end of word, encoded with half rate CELP
- 6 Voiced – highly periodic voiced speech, mainly vowels. Will be further classified as full rate or
- 7 quarter rate according to different patterns to meet ADR requirements
- 8 Unvoiced – unvoiced speech, mainly consonants. Encoded with quarter rate NELP
- 9 Silence – inactive speech. Encoded with eighth-rate same as EVRC

10 **Inputs**

- 11 curr_va – current frame VAD, which comes from EVRC RDA
- 12 prev_voiced – indicates the presence of stationary voiced speech in previous frame
- 13 prev_mode – previous frame mode decision
- 14 nacf_at_pitch – subframe NACFs based on pitch estimates
- 15 curr_ns_snr – low and high band instantaneous SNRs from the noise suppressor
- 16 curr_snr – low and high band instantaneous SNRs from the EVRC RDA (VAD)
- 17 t_in – speech buffer, which has both the current frame and the look ahead frame speech

18 **Outputs**

- 19 Current frame mode decision

4.6.3.1 Energy and zero crossing rate

Energies in the 0 to 2 kHz band and 2 to 4 kHz band are computed as $EL = \sum_{n=0}^{159} s_L^2(n)$, and $EH = \sum_{n=0}^{159} s_H^2(n)$ respectively, where $s_L(n)$, and $s_H(n)$ are the low-pass filtered (using a 12th order pole-zero LPF), and the high-pass filtered (using a 12th order pole-zero HPF) versions of the input speech respectively. The speech signal energy itself is $E = \sum_{n=0}^{159} s^2(n)$.

The zero crossing rate ZCR is computed as


If $(s(n)s(n+1)<0)$ ZCR=ZCR+1, $0 \leq n < 159$

Table 4-14 describes the features used in the mode decision.

Table 4-14 Features used in mode decision

Feature name	Description
curr_ns_snr	This feature is extracted from the noise suppressor. It's the band SNRs derived from the FFT. Low band is from 0 to 2 kHz, high band is from 2 to 4 kHz.
curr_snr	This is the band SNRs derived from VAD, after noise suppression.
curr_snr_diff	Band SNR difference, defined as curr_snr[0]-curr_snr[1]
zcr	This is the zero crossing rate of the current frame, defined as the number of sign changes in speech.
E	Current frame energy
Enext	Look ahead frame energy
bER	Band energy ratio, defined as $\log_2(EL/EH)$, where EL is the low band current frame energy from 0 to 2k, and EH is the high band current frame energy from 2k to 4k.
vEav	3-frame average voiced energy, updated only if current frame is voiced, or reset to 0.1 at unvoiced or inactive speech.
vEprev	Previous valid 3-frame average voiced energy
vER	Current energy to previous 3-frame average voiced energy ratio, defined as $10 \cdot \log_{10}(E/vEprev)$.
vER2	Defined as $\text{MIN}(20, 10 \cdot \log_{10}(E/vEav))$
maxsfe_idx	Current frame is evenly divided into 10 subframes, r.m.s value is computed on each subframe. This is the index to the subframe that has the largest r.m.s value in the second half of the current frame.

1 The flow chart in Figure 4.6-2 illustrates the high level mode-decision scheme.



2

3

Figure 4.6-2 High level diagram of mode decision

4

The various features are used in a multilevel decision logic to make the mode-decision. The following diagrams outline how the mode decision is made. Current mode decision is a transition between states based on the previous mode decision and features such as NACFs. The states are the different modes that correspond to different coding schemes.


5

6

7

8

nacf_at_pitch[2]>VOICEDTH – second subframe NACF of the current frame is high



9

10

11

Figure 4.6-3 nacf_at_pitch[2]>VOICEDTH – second subframe NACF of the current frame is high

The following pseudo-code shows the decision making process using the features mentioned above, and detailing the above state transition diagram.

```

1
2
3
4     if ( nacf_ap[2]>=VOICEDTH ) { // 2nd subframe NACF high
5         switch (prev_mode) {
6
7             case SILENCE:
8                 m.speech_type=UP_TRANSIENT;
9                 if (nacf_ap[3]<UNVOICEDTH && zcr>70 && bER<0)
10                    m.speech_type=UNVOICED;
11                 if (nacf_ap[3]<UNVOICEDTH && zcr>100 && vER<-20)
12                    m.speech_type=UNVOICED;
13                 if (vER<-25)
14                    m.speech_type=UNVOICED;
15
16                 break;
17
18             case UNVOICED:
19                 m.speech_type=UP_TRANSIENT;
20                 if (nacf_ap[3]<UNVOICEDTH && nacf_ap[4]<UNVOICEDTH &&
21 nacf<UNVOICEDTH && zcr>70 && bER<0)
22                    m.speech_type=UNVOICED;
23                 if (nacf_ap[3]<UNVOICEDTH && zcr>100 && vER<-20 && E<Eprev)
24                    m.speech_type=UNVOICED;
25                 if (vER<-25)
26                    m.speech_type=UNVOICED;
27
28                 break;
29
30             case VOICED:
31                 m.speech_type=VOICED;
32                 /*
33                 if ((nacf_ap[2]-nacf_ap[3]>0.3) && nacf_ap[3]<LOWVOICEDTH &&
34 E>=2*Eavg)
35                    m.speech_type=TRANSIENT;
36                 */
37                 if ((nacf_ap[2]-nacf_ap[1]>0.3) && nacf_ap[1]<LOWVOICEDTH &&
38 E>0.5*Eprev)
39                    m.speech_type=TRANSIENT;
40                 if (vER<-18 && nacf_ap[3]<VOICEDTH)
41                    m.speech_type=DOWN_TRANSIENT;
42                 if (vER<-30 && E<Eprev)
43                    m.speech_type=UNVOICED;
44                 break;
45


```

```

1      case DOWN_TRANSIENT:
2          m.speech_type=DOWN_TRANSIENT;
3          //      if (E>0.2*vEav) m.speech_type=TRANSIENT;
4          if (vER<-30)
5              m.speech_type=UNVOICED;
6          if (E>Eprev) m.speech_type=TRANSIENT;
7          break;
8
9      default: // previous is transient
10         m.speech_type=VOICED;
11         if ((nacf_ap[2]-nacf_ap[1]>0.45) || nacf_ap[1]<UNVOICEDTH )
12             m.speech_type=TRANSIENT;
13         if (nacf_ap[1]-nacf_ap[0]>0.3 && nacf_ap[1]<VOICEDTH &&
14 prev_mode !=TRANSIENT)
15             m.speech_type=TRANSIENT;
16
17         if (((nacf_ap[1]-nacf_ap[0]>0.3) || (nacf_ap[2]-nacf_ap[1]>0.3))
18 && nacf_ap[1]<LOWVOICEDTH && nacf_ap[0]<UNVOICEDTH)
19             m.speech_type=TRANSIENT;
20
21         if (E<0.05*vEav && nacf_ap[3]<VOICEDTH)
22             m.speech_type=DOWN_TRANSIENT;
23         if (vER<-30 && E<Eprev)
24             m.speech_type=UNVOICED;
25         break;
26     }
27 }

```

29 nacf_at_pitch[2]<UNVOICEDTH – second subframe NACF of the current frame is low



30
31 **Figure 4.6-4 nacf_at_pitch[2]<UNVOICEDTH – second subframe NACF of the current**
32 **frame is low**

The following pseudo-code shows the decision making process using the features mentioned above, and detailing the above state transition diagram.

```

1      if ( nacf_ap[2]<=UNVOICEDTH ) {
2
3          switch (prev_mode) {
4
5              case SILENCE:
6
7                  m.speech_type=UNVOICED;
8
9                  if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] &&
10 nacf_ap[4]>LOWVOICEDTH && zcr<110 && vER>-21 && (nacf_ap[3]>UNVOICEDTH ||
11 bER>-2))
12
13                     m.speech_type=UP_TRANSIENT;
14
15                     if (zcr<60 && bER>6 && vER>-13 && curr_snr_diff>13.5463)
16
17                         m.speech_type=UP_TRANSIENT;
18
19                         if ((nacf_ap[3]>LOWVOICEDTH || nacf_ap[4]>LOWVOICEDTH) && bER>3 &&
20 zcr<60 && vER>0)
21
22                             m.speech_type=UP_TRANSIENT;
23
24                             if (nacf_ap[3]>LOWVOICEDTH && nacf_ap[4]>LOWVOICEDTH && bER>3 &&
25 zcr<40 && vER>-15)
26
27                                 m.speech_type=UP_TRANSIENT;
28
29                                 break;
30
31             case UNVOICED:
32
33                 m.speech_type=UNVOICED;
34
35                 if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] &&
36 nacf_ap[4]>LOWVOICEDTH && zcr<110 && vER>-21 && (nacf_ap[3]>UNVOICEDTH ||
37 bER>-2))
38
39                     m.speech_type=UP_TRANSIENT;
40
41                     if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] && E>5*Eprev &&
42 bER>3 && vER>-16)
43
44                         m.speech_type=UP_TRANSIENT;
45
46                         if (nacf_ap[4]>VOICEDTH && bER>3 && zcr<80 && E>2*Eprev && vER>-
47 20)
48
49                             m.speech_type=UP_TRANSIENT;
50
51                             if (nacf_ap[3]>VOICEDTH && bER>0 && zcr<80 && E>2*Eprev && vER>-
52 16)
53
54                                 m.speech_type=UP_TRANSIENT;
55
56                                 if ((nacf_ap[3]>LOWVOICEDTH || nacf_ap[4]>LOWVOICEDTH) && bER>0 &&
57 zcr<80 && maxsfe_idx==SFNUM && vER>-16)
58
59                                     m.speech_type=UP_TRANSIENT;
60
61                                     if (nacf_ap[3]>UNVOICEDTH && nacf_ap[4]>UNVOICEDTH && zcr<80 &&
62 bER>4 && vER>-20 && curr_snr_diff>0 && curr_ns_snr[0]>=SNR_THLD) // Clean
63 condition
64
65                                         m.speech_type=UP_TRANSIENT;
66
67                                         if (nacf_ap[3]>LOWVOICEDTH && nacf_ap[4]>LOWVOICEDTH && zcr<80 &&
68 E>Eprev && vER>-20)

```

3GPP2 C.S0014-B ver 1.0


```
1         m.speech_type=UP_TRANSIENT;
2         if (nacf_ap[3]>VOICEDTH && nacf_ap[4]>VOICEDTH && vER>-20)
3             m.speech_type=UP_TRANSIENT;
4         if (bER>0 && zcr<80 && E>10*Eprev && vER>-10)
5             m.speech_type=UP_TRANSIENT;
6
7         if (((bER>5 && vER>-10) || (bER>3 && vER>-6) || (bER>0 && vER>-3))
8             && zcr<80 && curr_snr_diff>0 && curr_ns_snr[0]>=SNR_THLD) // Clean condition
9             m.speech_type=UP_TRANSIENT;
10
11         if (bER>-3 && vER>-14 && zcr<80 && curr_ns_snr[0]<SNR_THLD)
12 //Noisy condition
13         m.speech_type=UP_TRANSIENT;
14         if (nacf>UNVOICEDTH && zcr<60 && bER>2 && vER>-5 &&
15 curr_ns_snr[0]<SNR_THLD) //Noisy condition
16         m.speech_type=UP_TRANSIENT;
17         if (bER>-5 && vER>-4 && nacf_ap[3]>UNVOICEDTH &&
18 nacf_ap[4]>nacf_ap[3] && zcr<100 && curr_ns_snr[0]<SNR_THLD) // Noisy
19 condition
20         m.speech_type=UP_TRANSIENT;
21
22         break;
23
24     case DOWN_TRANSIENT: // following down_transient
25         m.speech_type=UNVOICED;
26         if (bER>0) {
27             if (vER>-20 && zcr<70)
28                 m.speech_type=DOWN_TRANSIENT;
29             if ((nacf_ap[3]>LOWVOICEDTH || nacf_ap[4]>LOWVOICEDTH) &&
30 E>=2*Eprev && vER>-15)
31                 m.speech_type=TRANSIENT;
32             if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] &&
33 nacf_ap[4]>VOICEDTH && vER>-15 && E>Eprev)
34                 m.speech_type=TRANSIENT;
35         }
36         else {
37             if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] &&
38 nacf_ap[4]>VOICEDTH && vER>-15 && E>2*Eprev)
39                 m.speech_type=TRANSIENT;
40         }
41         break;
42     case VOICED:
43     default:
44         if (bER>0) {
45             m.speech_type=TRANSIENT;
46             if (vER2<-15 && zcr<90 && E<Eprev && nacf_ap[3]<VOICEDTH)
47                 m.speech_type=DOWN_TRANSIENT;
```

```

1         if (vER<-25 && E<Eprev)
2             m.speech_type=UNVOICED;
3         }
4         else {
5             m.speech_type=UNVOICED;
6             if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] &&
7                 nacf_ap[4]>UNVOICEDTH && zcr<100 && vER>-20 && curr_ns_snr[0]<SNR_THLD) //
8                 Noisy condition
9                 m.speech_type=TRANSIENT;
10            if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] &&
11                nacf_ap[4]>LOWVOICEDTH && zcr<100 && vER>-20 && curr_ns_snr[0]>=SNR_THLD) //
12                Clean condition
13                m.speech_type=TRANSIENT;
14
15            if (((bER>-1 && vER>-12 && zcr<80) || (bER>-3 && vER>-10 &&
16                zcr<90) || (bER>-7 && vER>-3 && zcr<105)) && curr_ns_snr[0]<SNR_THLD) //
17                Noisy condition
18                m.speech_type=TRANSIENT;
19            if (bER>-3 && vER>-10 && zcr<90 && curr_ns_snr[0]>=SNR_THLD) //
20                Clean condition
21                m.speech_type=TRANSIENT;
22        }
23        break;
24
25    }
26 }

```

27 nacf_at_pitch[2]>=UNVOICEDTH && nacf_at_pitch[2]<=VOICEDTH – major gray area



28
29 **Figure 4.6-5 nacf_at_pitch[2]>=UNVOICEDTH && nacf_at_pitch[2]<=VOICEDTH**

30 The following pseudo-code shows the decision making process using the features mentioned above, and
31 detailing the above state transition diagram.

```

32
33     switch (prev_mode) {
34

```

3GPP2 C.S0014-B ver 1.0

```
1         case SILENCE:
2             m.speech_type=UNVOICED;
3             if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] &&
4 nacf_ap[4]>LOWVOICEDTH && zcr<110 && vER>-22)
5                 m.speech_type=UP_TRANSIENT;
6
7             if (nacf_ap[2]>LOWVOICEDTH && curr_snr_diff>0 && E>2*Eprev &&
8 zcr<70 && vER>-20)
9                 m.speech_type=UP_TRANSIENT;
10            if (nacf_ap[2]>LOWVOICEDTH && nacf_ap[3]>LOWVOICEDTH && zcr<70 &&
11 vER>-20)
12                m.speech_type=UP_TRANSIENT;
13            if ((nacf_ap[4]>VOICEDTH || nacf_ap[3]>VOICEDTH) &&
14 nacf_ap[3]>UNVOICEDTH && zcr<70 && vER>-20)
15                m.speech_type=UP_TRANSIENT;
16            if ((nacf_ap[3]-nacf_ap[2]>0.3) && E>2*Eprev && zcr<70 && bER>0 &&
17 vER>-20)
18                m.speech_type=UP_TRANSIENT;
19            if (nacf_ap[4]>VOICEDTH && (nacf_ap[2]>LOWVOICEDTH ||
20 nacf_ap[3]>LOWVOICEDTH) && E>2*Eprev && curr_snr_diff>0 && vER>-20)
21                m.speech_type=UP_TRANSIENT;
22            if (nacf_ap[3]>LOWVOICEDTH && nacf_ap[4]>LOWVOICEDTH && bER>3 &&
23 zcr<40 && vER>-15)
24                m.speech_type=UP_TRANSIENT;
25            break;
26
27        case UNVOICED:
28            m.speech_type=UNVOICED;
29            if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] &&
30 nacf_ap[4]>LOWVOICEDTH && zcr<110 && vER>-22)
31                m.speech_type=UP_TRANSIENT;
32            if ((nacf_ap[4]>LOWVOICEDTH || nacf_ap[3]>LOWVOICEDTH) && zcr<100
33 && E>Eprev && bER>0 && vER>-20)
34                m.speech_type=UP_TRANSIENT;
35            if (nacf_ap[4]>VOICEDTH && nacf>UNVOICEDTH && zcr<100 && E>Eprev
36 && bER>1 && vER>-16)
37                m.speech_type=UP_TRANSIENT;
38            if (zcr<60 && bER>3 && E>5*Eprev && curr_snr_diff>9.0309 && vER>-
39 20)
40                m.speech_type=UP_TRANSIENT;
41            if ((nacf_ap[3]>UNVOICEDTH || nacf_ap[4]>UNVOICEDTH) && bER>1 &&
42 vER>-16 && zcr<80 && curr_snr_diff>-6.0206)
43                m.speech_type=UP_TRANSIENT;
44
45            if (nacf_ap[2]>LOWVOICEDTH && curr_snr_diff>0 && E>2*Eprev &&
46 zcr<70 && vER>-20)
47                m.speech_type=UP_TRANSIENT;
```

```

1         if (nacf_ap[2]>LOWVOICEDTH && nacf_ap[3]>LOWVOICEDTH && zcr<100 &&
2         vER>-20)
3             m.speech_type=UP_TRANSIENT;
4             if ((nacf_ap[4]>VOICEDTH || nacf_ap[3]>VOICEDTH) &&
5         nacf_ap[3]>UNVOICEDTH && zcr<80 && vER>-20)
6                 m.speech_type=UP_TRANSIENT;
7                 if ((nacf_ap[3]>LOWVOICEDTH || nacf_ap[4]>LOWVOICEDTH) && bER>0 &&
8         zcr<100 && maxsfe_idx==SFNUM && vER>-20)
9                     m.speech_type=UP_TRANSIENT;
10                    if (nacf_ap[3]>UNVOICEDTH && nacf_ap[4]>UNVOICEDTH && zcr<100 &&
11         vER>-3 && bER>-5 && curr_ns_snr[0]<SNR_THLD) // Noisy condition
12                        m.speech_type=UP_TRANSIENT;
13
14                    if (bER>4 && zcr<100 && maxsfe_idx==SFNUM && vER>-20)
15                        m.speech_type=UP_TRANSIENT;
16
17                    if ((nacf_ap[3]-nacf_ap[2]>0.3) && E>2*Eprev && zcr<70 && bER>0 &&
18         vER>-20)
19                        m.speech_type=UP_TRANSIENT;
20                        if (nacf_ap[4]>VOICEDTH && (nacf_ap[2]>LOWVOICEDTH ||
21         nacf_ap[3]>LOWVOICEDTH) && E>2*Eprev && curr_snr_diff>0 && vER>-20)
22                            m.speech_type=UP_TRANSIENT;
23
24                            if (((bER>5 && vER>-10) || (bER>3 && vER>-6) || (bER>0 && vER>-3))
25         && zcr<80 && curr_ns_snr[0]>=SNR_THLD) // Clean condition
26                                m.speech_type=UP_TRANSIENT;
27
28                                if (bER>-3 && vER>-14 && zcr<80 && curr_ns_snr[0]<SNR_THLD) //
29         Noisy condition
30                                    m.speech_type=UP_TRANSIENT;
31                                    break;
32                                case DOWN_TRANSIENT:
33                                    m.speech_type=UNVOICED;
34                                    if (bER>0) {
35                                        if (vER>-20 && zcr<70)
36                                            m.speech_type=DOWN_TRANSIENT;
37                                        if ((nacf_ap[3]>LOWVOICEDTH || nacf_ap[4]>LOWVOICEDTH) &&
38         E>=2*Eprev && vER>-15)
39                                            m.speech_type=TRANSIENT;
40                                        if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] &&
41         nacf_ap[4]>VOICEDTH && vER>-15)
42                                            m.speech_type=TRANSIENT;
43
44                                    }
45                                    else {
46                                        if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] &&
47         nacf_ap[4]>VOICEDTH && vER>-15 && E>2*Eprev)

```

```

1         m.speech_type=TRANSIENT;
2     }
3     break;
4     case VOICED:
5     default:
6         if (nacf_ap[2]>=LOWVOICEDTH) {
7             m.speech_type=VOICED;
8             if (nacf_ap[1]<LOWVOICEDTH || (nacf_ap[1]<VOICEDTH &&
9 nacf_ap[1]-nacf_ap[0]>0.3) || bER<0)
10                m.speech_type=TRANSIENT;
11                if (vER<-15 && nacf_ap[3]<LOWVOICEDTH && E<Eprev)
12                    m.speech_type=DOWN_TRANSIENT;
13                    if (bER<0 && vER<-20 && Enext<E && nacf_ap[3]<UNVOICEDTH &&
14 nacf_ap[4]<UNVOICEDTH)
15                        m.speech_type=UNVOICED;
16                        if (bER<-30 && E<Eprev)
17                            m.speech_type=UNVOICED;
18
19                            if ((nacf_ap[2]-nacf_ap[3]>0.3) && nacf_ap[3]<0.3 &&
20 nacf_ap[4]<0.25)
21                                m.speech_type=TRANSIENT;
22                            }
23                            else {
24                                if (bER>0) {
25                                    m.speech_type=TRANSIENT;
26                                    if (vER2<-15 && zcr<90 && E<Eprev && nacf_ap[3]<VOICEDTH)
27                                        m.speech_type=DOWN_TRANSIENT;
28                                        if (vER<-25 && E<Eprev)
29                                            m.speech_type=UNVOICED;
30                                }
31                                else {
32                                    m.speech_type=UNVOICED;
33                                    if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] && zcr<100
34 && vER>-20 && curr_ns_snr[0]>=SNR_THLD) // Clean condition
35                                        m.speech_type=TRANSIENT;
36                                        if (nacf_ap[3]>nacf_ap[2] && nacf_ap[4]>nacf_ap[3] && zcr<110
37 && vER>-15 && curr_ns_snr[0]<SNR_THLD) // Noisy condition
38                                            m.speech_type=TRANSIENT;
39                                            if (bER>-1 && vER>-12 && zcr<80)
40                                                m.speech_type=TRANSIENT;
41                                                if (bER>-3 && vER>-10 && nacf>UNVOICEDTH && zcr<90)
42                                                    m.speech_type=TRANSIENT;
43                                                    if (bER>-7 && vER>-3 && zcr<105 && curr_ns_snr[0]<SNR_THLD) //
44 Noisy condition
45                                                        m.speech_type=TRANSIENT;
46                    }

```

```

1
2     }
3
4     break;
5     }
6 }
7

```

8 4.6.4 Rate-decision for SO 68

9 Depending on Input Operating Point, the mode-decision is first mapped to the different modes of the
10 encoder at different rates as following according to the general rules shown in the following table.

11 **Table 4-15 Mapping of speech mode decision to encoding rate and mode**

Open Loop Mode decision	Mode and Rate used to encode the frame
Transient	Full-rate CELP
Down Transient	Half-rate CELP or Full-rate CELP
Uptransient	Full-rate CELP
Voiced	FPPP, or QPPP, or FCELP processing Depending on the Operating Point, and a pre-determined pattern of interleaving QPPP with either FCELP or FPPP. A closed loop decision is later used in QPPP processing to achieve the input capacity operating point of EVRC-B.
Unvoiced	Quarter-rate NELP processing
Silence	Eighth-rate processing

12

13

14 4.6.4.1 Constraining Rate Selection

15 If the speech codec has been commanded to generate a Rate 1/2 maximum packet and the rate determined
16 is Rate 1, it generates a Rate 1/2 CELP packet. If the speech codec has been requested to generate a Blank
17 packet, it generates a packet based on the rate determined by the rate selection algorithm.

18 4.7 Quantization of LSP Parameters for SO 3

19 **Inputs:** The inputs to the LSP quantizer are:

- 20 • The unquantized LSPs for the current frame, $\Omega(m)$
- 21 • The rate of the current frame, $Rate(m)$

22 **Outputs:** The outputs from the LSP quantizer are:

- 23 • The quantized LSPs for the current frame, $\Omega_q(m)$

24 **Processing:** The quantizer takes the form of a weighted split vector LSP quantizer. The splits for the quantizer
25 for a given $Rate$ are given in parameterTable 4-16. All of the sub-matrices are coded using the number of bits

1 found in this table. The codebooks $q_{rate}(k)$, that are used to quantize each set of LSPs can be found in Table 9-1
 2 through Table 9-9. Each LSP set has one codebook with dimensions $n_{sub}(k)$ by $n_{size}(k)$. $n_{sub}(k)$ is the number of
 3 LSP parameters in the set and $n_{size}(k)$ is the codebook size.

4
 5 **Table 4-16. LSP Parameter Splits**

Codebook Number k	LSP Parameters in set $\Omega(m)$	LSP Split Starting Parameter Index $B(k)$	Number of LSP Parameters $n_{sub}(k)$	Code book Size $n_{size}(k)$	Number of bits allocated
Rate 1					
1	$\Omega(m, i); i \in (1, 2)$	1	2	64	6
2	$\Omega(m, i); i \in (3, 4)$	3	2	64	6
3	$\Omega(m, i); i \in (5, 6, 7)$	5	3	512	9
4	$\Omega(m, i); i \in (8, 9, 10)$	8	3	128	7
Rate 1/2					
1	$\Omega(m, i); i \in (1, 2, 3)$	1	3	128	7
2	$\Omega(m, i); i \in (4, 5, 6)$	4	3	128	7
3	$\Omega(m, i); i \in (7, \dots, 10)$	7	4	256	8
Rate 1/8					
1	$\Omega(m, i); i \in (1, \dots, 5)$	1	5	16	4
2	$\Omega(m, i); i \in (6, \dots, 10)$	6	5	16	4

6
 7 The number of codebooks, k_{num} , for each rate is shown in Table 4.4-2.

8
 9 **Table 4-17. Number of LSP Codebooks**

Rate	Number of Codebooks k_{num}
1	4
1/2	3
1/8	2

10 **4.7.1 Computation of Weights**

11 The weights, $w(i)$, for the LSP frequencies are defined as follows:

$$\omega(i) = \begin{cases} \frac{50}{2\pi} + 1 & ; \Delta_{\Omega}(m, i) = 0, \\ \frac{0.5}{2\pi\Delta_{\Omega}(m, i)} + 1 & ; \text{otherwise,} \end{cases} \quad 1 \leq i \leq 10, \quad (4.7.1-1)$$

2 where:

$$\Delta_{\Omega}(m, i) = \begin{cases} \Omega(m, i+1) - \Omega(m, i) & ; i=1, \\ \min((\Omega(m, i) - \Omega(m, i-1)), (\Omega(m, i+1) - \Omega(m, i))) & ; 2 \leq i \leq 9, \\ \Omega(m, i) - \Omega(m, i-1) & ; i=10. \end{cases} \quad (4.7.1-2)$$

4 4.7.2 Error Matrix Computation

5 Compute the error matrix, $e(k)$, for each set of LSP frequencies k :

$$e(k, j) = \sum_{i=1}^{n_{sub}(k)} \omega(B(k) + i - 1) (\Omega(m, B(k) + i - 1) - q_{rate}(k, i, j))^2 ; 1 \leq j \leq n_{size}(k), 1 \leq k \leq k_{num}, \quad (4.7.2-1)$$

7 where i is the sub-index of each LSP parameter set, and j is the index of the codebook entries. All the other
8 parameters are defined in Tables 4.4-1 and 4.4-2.

9 4.7.3 Adjustment of Quantization Error

10 The error associated between codebooks is adjusted to prevent excessively small (or negative) gaps between
11 LSPs at codebook seams. If the difference between a particular $q(k, l, j)$ and $\Omega_q(m, B(k)-1)$ is less than δ , $e(k, j)$
12 is assigned a value that will make it invalid for the search. The error matrix is adjusted by:

$$e(k, j) = \begin{cases} MAXFLOAT & ; (q_{rate}(k, l, j) - \Omega_q(m, B(k)-1)) \leq \delta, \\ e(k, j) & ; \text{otherwise,} \end{cases} \quad 1 \leq j \leq n_{size}(k), 1 \leq k \leq k_{num} \quad (4.7.3-1)$$

14 where $\delta = 0.05 / 2\pi$

15 4.7.4 Quantization Search

16 Each error matrix, $e(k, i)$, is searched for the minimum error, $e_{min}(k)$, as defined by:

$$e_{min}(k) = \min \{ e(k, j) MAXFLOAT \} ; 1 \leq j \leq n_{size}(k), 1 \leq k \leq k_{num}. \quad (4.7.4-1)$$

18 The codebook index to be transmitted, $LSPIDX(k)$, is defined as the index, j , where $e_{min}(k)$ was found above for
19 all k .

20 4.7.5 Generation of Quantized LSP Parameters

21 The codebook indices, $LSPIDX(k)$, are used to generate a quantized set of LSP parameters:

$$\Omega_q(m, B(k) + i - 1) = q_{rate}(k, i, LSPIDX(k)) ; 1 \leq i \leq n_{sub}(k), 1 \leq k \leq k_{num}. \quad (4.7.5-1)$$

1 **4.8 Quantization of LSP Parameters for SO 68**

2 **Inputs**

3 The inputs to the LSP quantizer are:

4 The unquantized LSPs for the current frame, $\Omega(m)$ (also referred to in this section as l)

5 The rate of the current frame, $Rate(m)$

6 **Outputs**

7 The outputs from the LSP quantizer are:

8 The quantized LSPs for the current frame, $\Omega_q(m)$

9 4.8.1 Full-rate, half-rate, and quarter-rate unvoiced: delta LSP VQ

10 For full-rate, half-rate, and quarter-rate unvoiced frames, a delta split LSPVQ scheme is used. The weights
11 used in the error calculation in the LSPVQ are computed as:

$$w(i) = \begin{cases} \frac{0.5}{2\pi\sqrt{(l(i)-l(i-1))(l(i+1)-l(i))}}; & 1 \leq i \leq 8 \\ \frac{0.5}{2\pi\sqrt{l(i)(l(i+1)-l(i))}}; & i = 0 \\ \frac{0.5}{2\pi\sqrt{(l(i)-l(i-1))(0.5)}}; & i = 9 \end{cases} \quad (4.8.1-1)$$

13 The delta split LSPVQ is in general represented by the following equation

$$k^* = \arg \max_k \sum_{i=i_l}^{i_u} \left[\left(\frac{l(i)-ll}{lu-ll} - cb[k][i-i_l] \right)^2 w(i) \right]; \quad 0 \leq k < CBSIZE \quad (4.8.1-2)$$

16 with the following conditions

$$cb[k][0] = \max \left(cb[k][0], \frac{0.05}{2\pi(lu-ll)} \right) \quad (4.8.1-3)$$

$$cb[k][i_u - i_l - 1] = \min \left(cb[k][i_u - i_l - 1], 1 - \frac{0.05}{2\pi(lu-ll)} \right) \quad (4.8.1-4)$$

19 where,

20 i_u , and i_l are the upper, and lower indices of the input LSP vector corresponding to a segment,

1 lu , and ll are the lower and upper limit of the segment delta vector quantization.

2 $cb[x][y]$ is the code-vector corresponding to the x th entry in the code-book, and y is index of the element in the
 3 current split i.e $il \leq y \leq lu$

4 CBSIZE is the size of the codebook for the current split

5 The dequantized LSP vector corresponding to the chosen index, k^* , for the split segment is given by

6
$$\hat{l}(i) = ll + (lu - ll)cb[k^*][i - i_l]; \quad i_l \leq i \leq i_u \quad (4.8.1-5)$$

7 with the following two conditioning on the end points of the split segment,

8
$$\hat{l}(i_l) = ll + \frac{0.05}{2\pi}; \quad \text{if } cb[k^*][0] < \frac{0.05}{2\pi(lu - ll)} \quad (4.8.1-6)$$

9
$$\hat{l}(i_u) = lu - \frac{0.05}{2\pi}; \quad \text{if } cb[k^*][i_u - i_l - 1] > 1 - \frac{0.05}{2\pi(lu - ll)}$$

10
 11
$$(4.8.1-7)$$

12 4.8.2 Full rate LSP VQ

13 Number of bits = 28.

14 The following table shows the parameters of the LSP VQ for full-rate frames.

15 **Table 4-18 LSPVQ parameters for full-rate**

Segment	i_l	i_u	ll	lu	# of elements in split	Elements	# of bits for the split	# of entries in quantization table
0	0	1	0	0.5	2	$l(0), l(1)$	6	64
1	2	3	$\hat{l}(1)$	$\hat{l}(4)$	2	$l(2), l(3)$	6	64
2	4	6	0	0.5	3	$l(4), l(5), l(6)$	9	512
3	7	9	$\hat{l}(6)$	0.5	3	$l(7), l(8), l(9)$	7	128

16
 17 Segments 0, and 2 are quantized absolutely using $ll = 0$, and $lu = 0.5$ first.

18 The quantization of segments 1 and 3 is performed using a multiple path approach where 4 best candidates (say
 19 $S0_C0, S0_C1, S0_C2, S0_C3$ in decreasing order of optimality) are independently picked for segment 0, and 6
 20 best candidates candidates (say $S2_C0, S2_C1, S2_C2, S2_C3, S2_C4, S2_C5$) are independently picked for
 21 segment 2. The quantization of the split segments 1 and 3 depend on the candidates picked for segments 0 and

3GPP2 C.S0014-B ver 1.0

- 1 2. The search for the best candidates of segments 1 and 3 are performed for the pairs of candidates of segments
- 2 0 and 1 as shown in Table 4-19.

Table 4-19 Multiple candidate search in full-rate LSPVQ

Segment 0 candidates in decreasing order of optimality	Number of top candidates of segment 2 used in search	Segment 2 candidates to be used in pair with segment 0 candidate
S0_C0	6	S2_C0, S2_C1, S2_C2, S2_C3, S2_C4, S2_C5
S0_C1	5	S2_C0, S2_C1, S2_C2, S2_C3, S2_C4
S0_C2	4	S2_C0, S2_C1, S2_C2, S2_C3
S0_C3	3	S2_C0, S2_C1, S2_C2

The basic idea is that the best candidate in Segment 0 are paired with all of the candidates of Segment 2, the next best candidate of Segment 0 are paired with one less number of candidates of Segment 2 and so on.

For each pair of candidates of Segment 0, and Segment 2, the best candidate for Segments 1, and 3 are chosen according to the above equation above.

The final set of candidates (and their codebook indices) for all these segments is chosen as the one that minimizes the following joint (10 dimensional going across segment split boundaries) error between the unquantized LSP and the quantized LSP (obtained from independently selecting the best quantized vector for the split segments).

$$e = \sum_{i=0}^9 w(i) (l(i) - \hat{l}(i))^2 \tag{4.8.2-1}$$

4.8.3 Half Rate LSPVQ

Number of bits = 22.

The following table shows the parameters of the LSP VQ for half-rate frames.

Table 4-20 LSPVQ parameters for half-rate

Segment	i_l	i_u	ll	lu	# of elements in split	Elements	# of bits for the split	# of entries in quantization table
0	0	2	0	0.5	3	$l(0), l(1), l(2)$	7	128
1	3	5	$\hat{l}(2)$	$\hat{l}(6)$	3	$l(3), l(4), l(5)$	7	128
2	6	9	0	0.5	4	$l(6), l(7), l(8), l(9)$	8	256

Segments 0, and 2 are quantized absolutely using $ll = 0$, and $lu = 0.5$ first.

1 The quantization of segment 1 is performed using a multiple path approach where 4 best candidates (say
 2 S0_C0, S0_C1, S0_C2, S0_C3 in decreasing order of optimality) are independently picked for segment 0, and 6
 3 best candidates candidates (say S2_C0, S2_C1, S2_C2, S2_C3, S2_C4, S2_C5) are independently picked for
 4 segment 2. The quantization of the split segment 1 depends on the candidates picked for segments 0 and 2. The
 5 search for the best candidates of segments 1 is performed for the pairs of candidates of segments 0 and 1 as
 6 shown below in the table

7 **Table 4-21 Multiple candidate search in half-rate LSPVQ**

Segment 0 candidates in Decreasing order of optimality	Number of top candidates of Segment 2 used in search	Segment 2 candidates to be used in pair with Segment 0 candidate
S0_C0	6	S2_C0, S2_C1, S2_C2, S2_C3, S2_C4, S2_C5
S0_C1	5	S2_C0, S2_C1, S2_C2, S2_C3, S2_C4
S0_C2	4	S2_C0, S2_C1, S2_C2, S2_C3
S0_C3	3	S2_C0, S2_C1, S2_C2

8
 9 The basic idea is that the best candidate in Segment 0 are paired with all of the candidates of Segment 2, the
 10 next best candidate of Segment 0 are paired with one less number of candidates of Segment 2 and so on.

11 For each pair of candidates of Segment 0, and Segment 2, the best candidate for Segments 1 is chosen
 12 according the above equation.

13 The final set of candidates (and their codebook indices) for all these segments is chosen as the one that
 14 minimizes the following joint (10 dimensional going across segment split boundaries) error between the
 15 unquantized LSP and the quantized LSP (obtained from independently selecting the best quantized vector for
 16 the split segments).

$$e = \sum_{i=0}^9 w(i) (l(i) - \hat{l}(i))^2 \quad (4.8.3-1)$$

18 4.8.4 Quarter rate unvoiced LSPVQ

19 Number of bits = 16.

20 The following table shows the parameters of the LSP VQ for quarter-rate unvoiced frames

Table 4-22 LSPVQ parameters for quarter-rate unvoiced

Segment	i_l	i_u	ll	lu	# of elements in split	Elements	# of bits for the split	# of entries in quantization table
0	0	4	0	$\hat{l}(5)$	5	$l(0), l(1), l(2), l(3), l(4)$	8	256
1	5	9	0	0.5	5	$l(5), l(6), l(7), l(8), l(9)$	8	256

Segment 1 is quantized absolutely using $ll = 0$, and $lu = 0.5$ first.

The quantization of segment 0 is performed using a multiple path approach where 6 best candidates (say S1_C0, S1_C1, S1_C2, S1_C3, S1_C4, S1_C5) are independently picked for segment 1. The quantization of the split segment 0 depends on the candidates picked for segment 1. The search for the best candidates of segment 0 is performed for each of the 6 candidates of segment 1 using the above equation.

The final set of candidates (and their codebook indices) for all these segments is chosen as the one that minimizes the following joint (10 dimensional going across segment split boundaries) error between the unquantized LSP and the quantized LSP (obtained from independently selecting the best quantized vector for the split segments).

$$e = \sum_{i=0}^9 w(i) (l(i) - \hat{l}(i))^2 \quad (4.8.4-1)$$

4.8.5 Quarter-rate Voiced LSPVQ

A second order moving average (MA) predictor is used for quantizing the LSPs in quarter-rate voiced frame processing.

4.8.5.1 QPPP LSP quantization Weight Computation

The weights described in Section 4.8.1 are used to compute the weighted square error distortion metrics needed to search the LSP VQ codebooks in the QPPP LSP VQ procedure described in this section.

The MA predictive quantizer ensures that the effect of frame errors discontinues after 2 frames. The quantized LSP vector at the m th frame is given as

$$\hat{\mathbf{L}}_{im} = 0.4\mathbf{C}_m + 0.4\mathbf{C}_{m-1} + 0.2\mathbf{C}_{m-2} \quad (4.8.5-1)$$

where \mathbf{C}_m is the codebook vector for the m th frame, and $\hat{\mathbf{L}}_{im}$ is the vector representation of the quantized LSP vector denoted by \hat{l}_i . The target vector \mathbf{U}_m to the quantizer is constructed using the input unquantized LSP vector \mathbf{L}_{im} , and the past codebook vectors as

$$\mathbf{U}_m = \frac{\mathbf{L}_{im} - 0.4\mathbf{C}_{m-1} - 0.2\mathbf{C}_{m-2}}{0.4} \quad (4.8.5-2)$$

A regular 16-bit split VQ structure (with weighted MSE as the selection criterion) is used to encode the first 6 elements of the target vector \mathbf{U}_m with a 10-bit codebook and the last 4 elements using 6 bits. Let i_1^* and i_2^* be the chosen best indices out of the split VQ for the two splits. The quantizer output \mathbf{C}_m is constructed as follows:

$$\mathbf{C}_m(i) = \begin{cases} \text{CB1}[i_1^*][i]; & 0 \leq i < 6 \\ \text{CB2}[i_2^*][i-6]; & 6 \leq i < 10 \end{cases} \quad (4.8.5-3)$$

4.8.5.2 Constructing the MAVQ memory during frames that are not QPPP

During frames that are not QPPP, a MAVQ scheme is not used. Therefore, it is essential to construct the MAVQ memory elements, \mathbf{C}_{m-1} and \mathbf{C}_{m-2} , as follows:

$$\mathbf{C}_{m-1} = \mathbf{C}_{m-1} = \hat{\mathbf{L}}_{im}$$

where the vector $\hat{\mathbf{L}}_{im}$ is the the quantized LSPs, \hat{l} .

1 4.8.6 Eighth-rate LSPVQ

2 The eighth-rate LSPVQ for SO 68 is the same as that for SO 3 and described in Section 4.7.

3 **4.9 Encoding at Rates 1/2 and 1 for SO 3 and SO 68**

4 The algorithm for encoding at Rate 1 is similar to that used for encoding at Rate 1/2 except for the quantization
5 tables used and the fact that certain quantities (e.g., the spectral transition indicator, *LPCFLAG*, and the delay
6 difference, *DDELAY*) are transmitted only at Rate 1. Encoding is accomplished as follows:

7 **Inputs:** The inputs to encoding are:

- 8 • The quantized LSPs from the previous frame, $\Omega_q(m-1)$
- 9 • The unquantized LSPs from the current and previous frames, $\Omega(m)$ and $\Omega(m-1)$
- 10 • The short-term prediction residual, $\varepsilon(n)$
- 11 • The pitch delay estimate for the previous frame, $\tau(m-1)$
- 12 • The pitch delay estimate for the current frame, $\tau(m)$
- 13 • The long term prediction gain, β
- 14 • The rate of the current frame, $Rate(m)$

15 **Outputs:** The outputs of encoding are:

- 16 • The quantized LSPs for the current frame, $\Omega_q(m)$
- 17 • The LSP indices corresponding to the quantized LSPs, $LSPIDX(k)$
- 18 • The adaptive codebook gain index, $ACBGIDX(m')$, for each subframe, m'
- 19 • The fixed codebook shape indices, $FCBSIDX(m')$, for each subframe, m'
- 20 • The fixed codebook gain indices, $FCBGIDX(m',k)$, for each subframe, m'
- 21 • The delay transmission code, $DELAY$
- 22 • The spectral transition indicator, *LPCFLAG*, Rate 1 only
- 23 • The delay difference, *DDELAY*, Rate 1 only

24 **State Variables Affected:**

- 25 • The adaptive codebook excitation signal, $E(n)$
- 26 • The accumulated shift counter, τ_{acc}
- 27 • The pointer to the last sample in the shifted residual, n_m
- 28 • The state of the shifted residual buffer, *shiftstate*
- 29 • The filter memories in $H_{wq}(z)$ and $H_w(z)$
- 30 • The modified residual buffer, $\hat{\varepsilon}(n)$

31 **Initialization:**

- 32 • The state of the shifted residual buffer, *shiftstate* = CENTER

- The quantized LSPs, $\Omega_q(m,k) = 0.048k$; $m = 0, 1 \leq k \leq 10$

Processing:

EVRC encoding shall comprise the procedures described in 4.9.1 through 4.9.4. A block diagram of the RCELP encoding process is shown in Figure 4.9-1.




Figure 4.9-1. RCELP Encoding Block Diagram

4.9.1 LSP Quantization

The encoder shall vector quantize the unquantized LSPs, $\Omega(m)$, using the procedure found in 4.7 for Rates 1 or 1/2.

4.9.2 RCELP Shift State Update

The encoder shall update the shift state with hysteresis and control the accumulated shift. This step prevents the asynchrony between the original signals and the modified signals from increasing over time. It shall be implemented as a state machine, given by:

```

/* if signal is not at all periodic, reset */
if (  $\beta < 0.1$  ) {
     $\tau_{acc} = 0$ 
     $n_m = 0$ 
     $shiftstate = CENTER$ 
}

```

```

1      /* update shift state with hysteresis */
2      if (  $\tau_{acc} > 20$  ) {
3          shiftstate = RIGHT
4      }
5      if (  $\tau_{acc} < -20$  ) {
6          shiftstate = LEFT
7      }
8      if (  $\tau_{acc} \leq 10$  && shiftstate = RIGHT ) {
9          shiftstate = CENTER
10     }
11     if (  $\tau_{acc} \geq -10$  && shiftstate = LEFT ) {
12         shiftstate = CENTER
13     }
14     /* control accumulated shift by adjusting the delay */
15     if ( shiftstate == LEFT &&  $\beta < 0.4$  ) {
16          $\tau(m) = \tau(m) + 1$ 
17     }
18     else if ( shiftstate == RIGHT &&  $\beta < 0.4$  ) {
19          $\tau(m) = \tau(m) - 1$ 
20     }
21     /* check to keep delay within bounds */
22      $\tau(m) = \min\{ \tau(m), 120 \}$ 
23      $\tau(m) = \max\{ \tau(m), 20 \}$ 

```

24 4.9.3 Delay Encoding

25 The delay parameter, $\tau(m)$, determined in 4.4.3, shall be encoded for transmission by:

$$26 \quad DELAY = \tau(m) - \tau_{min}, \quad (4.9.3-1)$$

27 where $\tau_{min} = 20$.

28 In Rate 1 processing only, a differential delay parameter shall be transmitted for use in reconstructing the delay
 29 contour in the decoder after frame erasures. The transmission code, $DDELAY$, is defined as:

$$30 \quad DDELAY = \begin{cases} 0 & ; |\Delta_{\tau}| > 15, \\ \Delta_{\tau} + 16 & ; \text{otherwise} \end{cases} \quad (4.9.3-2)$$

31 where

$$32 \quad \Delta_{\tau} = \tau(m) - \tau(m-1). \quad (4.9.3-3)$$

33 4.9.4 Rates 1/2 and 1 Subframe Processing

34 The procedures described in 4.9.4.1 through 4.9.4.14 shall be carried out for three subframes, $0 \leq m' < 3$.
 35 The subframe size, L , is 53 for subframes 0 and 1, and 54 for subframe 2.

4.9.4.1 Interpolation of LSP Parameters

Interpolate the unquantized and quantized LSPs over the three subframes, m' , in the current frame, m . The form of the unquantized, interpolated LSP vector for subframe m' is given by:

$$\dot{\Omega}(m') = (1 - \mu_{m'})\dot{\Omega}(m-1) + \mu_{m'}\dot{\Omega}(m), \quad (4.9.4-1)$$

and form of the quantized, interpolated LSP vector is given by:

$$\dot{\Omega}_q(m') = (1 - \mu_{m'})\dot{\Omega}_q(m-1) + \mu_{m'}\dot{\Omega}_q(m), \quad (4.9.4-2)$$

where the subframe interpolator constants are defined as $\mu = \{ 0.1667, 0.5, 0.8333 \}$.

4.9.4.2 LSP to LPC Conversion

Convert the unquantized, interpolated LSPs, $\dot{\Omega}(m')$, to unquantized, interpolated LPC parameters, $\left\{ \dot{a} \right\}$, as described in 4.4.2.2 for each subframe. Convert the quantized, interpolated LSPs, $\dot{\Omega}_q(m')$, to quantized, interpolated LPC parameters, $\left\{ \dot{a}_q \right\}$, as described in 4.4.2.2, using the quantized LSPs at the end-points instead of the unquantized LSPs.

4.9.4.3 Zero Input Response Calculation

Calculate the zero-input response, $a_{zir}(n)$, of the weighted synthesis filter, $H_{wg}(z)$. The weighted synthesis filter is defined as:

$$H_{wg}(z) = \frac{1}{A_q(z)} \left[\frac{\dot{A}(\gamma_1^{-1}z)}{\dot{A}(\gamma_2^{-1}z)} \right] \quad (4.9.4-3)$$

where

$$\dot{A}_q(z) = 1 - \sum_{k=1}^{10} \dot{a}_q(k)z^{-k}, \quad (4.9.4-4)$$

and

$$\dot{A}(\gamma_l^{-1}z) = 1 - \sum_{k=1}^{10} \dot{a}(k)\gamma_l^k z^{-k} \quad ; l=1,2, \quad (4.9.4-5)$$

where $\gamma_1 = 0.9, \gamma_2 = 0.5$.

4.9.4.4 Impulse Response Calculation

Calculate the impulse response, $h_{wg}(n)$, of the weighted synthesis filter, $H_{wg}(z)$, to 54 terms.

1 4.9.4.5 Interpolated Delay Estimate Calculation

2 Calculate a set of three interpolated delay estimates, $\hat{d}(m', j)$, for each subframe m' as follows:

3
$$\hat{d}(m', j) = \begin{cases} \tau(m) & ; |\tau(m) - \tau(m-1)| > 15, \\ (1-f(m'+j))\tau(m-1) + f(m'+j)\tau(m) & ; \text{otherwise,} \end{cases} \quad 0 \leq m' < 3, 0 \leq j < 3, \quad (4.9.4-6)$$

4 where m is the current frame, m' is the subframe index, and $m'+j$ is an index into an array of interpolator
5 coefficients, f , defined by:

6
$$f = \{ 0.0, 0.3313, 0.6625, 1.0, 1.0 \}. \quad (4.9.4-7)$$

7 4.9.4.6 Calculation of the Adaptive Codebook Contribution

8 Compute the adaptive codebook contribution, $E(n)$, described in 4.9.5.

9 4.9.4.7 Modification of the Original Residual

10 Generate a modified residual signal, $\tilde{\varepsilon}(n)$, by shifting the current residual signal, $\varepsilon(n)$, to match the delay
11 contour for the current subframe. See 4.9.6 for details on this operation.

12 4.9.4.8 Generation of the Weighted Modified Original Speech Vector

13 Generate the weighted modified original speech vector, $\hat{s}_w(n)$, by filtering the modified residual, $\tilde{\varepsilon}(n)$, through
14 the weighted synthesis filter, $H_w(z)$, given by:

15
$$H_w(z) = \frac{1}{A(z)} \begin{bmatrix} A(\gamma_1^{-1}z) \\ A(\gamma_2^{-1}z) \end{bmatrix}, \quad (4.9.4-8)$$

16 where

17
$$A(z) = 1 - \sum_{k=1}^{10} a(k)z^{-k}, \quad (4.9.4-9)$$

18 and all other terms are defined in 4.9.4.3.

19 4.9.4.9 Closed-Loop Gain Calculation

20 Subtract the zero-input response, $a_{zir}(n)$, of the weighted synthesis filter, $H_w(z)$, from the weighted modified
21 original speech vector, $\hat{s}_w(n)$:

22
$$\hat{s}_w(n) = \hat{s}_w(n) - a_{zir}(n) \quad ; 0 \leq n < L. \quad (4.9.4-10)$$

23 Convolve the impulse response, $h_w(n)$, with the adaptive codebook excitation, $E(n)$, generating the filtered
24 adaptive codebook excitation, $\lambda(n)$:

$$\lambda(n) = \sum_{j=0}^n h_{wq}(j)E(n-j) \quad ; 0 \leq n < L. \quad (4.9.4-11)$$

The closed-loop quantized gain, g_p , is calculated by first determining the cross-correlation, $R_{s\lambda}(0)$, of $\hat{s}_w(n)$ and $\lambda(n)$:

$$R_{s\lambda}(0) = \sum_{n=0}^{L-1} \hat{s}_w(n)\lambda(n), \quad (4.9.4-12)$$

the auto-correlation of $\lambda(n)$ is then calculated by:

$$R_{\lambda\lambda}(0) = \sum_{n=0}^{L-1} \lambda^2(n). \quad (4.9.4-13)$$

The quantized closed loop gain, g_p , is defined by:

$$g_p = \begin{cases} g_{pcb}(0) & ; R_{s\lambda}(0) \leq 0, \\ g_{pcb}(ACBGIDX(m')) & ; R_{s\lambda}(0) > 0, \end{cases} \quad (4.9.4-14)$$

where $g_{pcb}(k)$ is an entry in the adaptive codebook gain quantization Table 4-23, and $ACBGIDX(m')$ is the optimal index into $g_{pcb}(k)$ calculated by:

$$\begin{aligned} & ACBGIDX(m') = 0 \\ & \text{for } (k = 1; k < g_{pcb_size}; k = k + 1) \{ \\ & \quad \text{if } \left(R_{s\lambda}(0) > \left(\frac{g_{pcb}(k) + g_{pcb}(k-1)}{2} R_{\lambda\lambda}(0) \right) \right) \{ \\ & \quad \quad ACBGIDX(m') = k \\ & \quad \} \\ & \} \end{aligned}$$

where $g_{pcb_size} = 8$.

Table 4-23. Adaptive Codebook Gain Quantization Table

k	$g_{\text{pcb}}(k)$
0	0.00
1	0.30
2	0.55
3	0.70
4	0.80
5	0.90
6	1.00
7	1.20

1

2 4.9.4.10 Fixed Codebook Search Target Vector Generation

3 4.9.4.10.1 Perceptual Domain Target Vector

4 Calculate the target vector in the perceptual domain, $x_w(n)$, defined by:

5
$$x_w(n) = \hat{s}_w(n) - g_p \lambda(n) \quad ; 0 \leq n < L, \quad (4.9.4-15)$$

6 where $\hat{s}_w(n)$ and $\lambda(n)$ are defined in 4.5.4.9.

7 4.9.4.10.2 Conversion of the Target Vector to the Residual Domain

8 Convert the target vector from the perceptual domain to the residual domain by filtering $x_w(n)$ through the zero-
9 state inverse of the weighting filter, $H_{wq}(z)$:

10
$$H_{wq}^{-1}(z) = A_q(z) \frac{A(\gamma_2^{-1}z)}{A(\gamma_1^{-1}z)}, \quad (4.9.4-16)$$

11 and all other terms are defined in 4.9.4.3.

12 The resulting target vector in the residual domain is defined as $x(n)$.

13 4.9.4.10.3 Delay Calculation for Current Subframe

14 The fixed codebook search requires an estimate of the delay, $\hat{\tau}$, for the current subframe, defined by:

15
$$\hat{\tau} = \text{round} \left\{ \frac{\hat{d}(m',0) + \hat{d}(m',1)}{2} \right\}, \quad (4.9.4-17)$$

16 where $\hat{d}(m',j)$ is defined in 4.9.4.5.

1 4.9.4.11 Fixed Codebook Search

2 Perform the fixed codebook search as described in 4.9.7.

3 4.9.4.12 Fixed codebook gain quantization

4 The fixed codebook gain, g_c , computed in 4.9.4.11, is constrained by:

$$5 \quad g_c = \begin{cases} (1.0 - 0.15g_p)g_c & ; \text{Rate}(m) == \text{Rate}1, \\ (0.9 - 0.1g_p)g_c & ; \text{Rate}(m) == \text{Rate}1/2, \end{cases} \quad (4.9.4-18)$$

6 which is then quantized by the following process:

$$7 \quad \begin{aligned} &FCBGIDX(m') = 0 \\ &\text{for } (k = 1; k < g_{ccb_size}; k = k + 1) \\ &\quad \text{if } \left(g_c > \left(\frac{g_{ccb}(k) + g_{ccb}(k-1)}{2} \right) \right) \{ \\ &\quad \quad FCBGIDX(m') = k \\ &\quad \quad \} \\ &g_c = g_{ccb}(FCBGIDX(m')) \end{aligned}$$

14 where $g_{ccb}(k)$ is a fixed codebook gain quantization entry defined in Table 9-12 and Table 9-13 for Rate 1 and
15 Rate 1/2, respectively, and $FCBGIDX(m')$ is the optimal index into the appropriate table for each subframe m' .

16 4.9.4.13 Combined Excitation Vector Computation

17 The combined excitation vector, $E_T(n)$, for the current subframe, m' is defined as the sum of the adaptive
18 codebook contribution, $E(n)$, and the fixed codebook contribution, $c(n)$:

$$19 \quad E_T(n) = g_p E(n) + g_c c(n) \quad ; 0 \leq n < L. \quad (4.9.4-19)$$

20 4.9.4.14 Encoder State Variable Update

21 Update the weighted synthesis filter memory by filtering the combined excitation vector, $E_T(n)$, through the

$$22 \quad \text{weighted synthesis filter, } H_{wq}(z), \text{ which is given in Equation } H_{wq}(z) = \frac{1}{A_q(z)} \left[\frac{A(\gamma_1^{-1}z)}{A(\gamma_2^{-1}z)} \right] \quad (4.9.4-3).$$

23 Update the modified residual memory by copying n_m elements of the current modified residual to the beginning
24 of the modified residual buffer:

$$25 \quad \hat{e}(n) = \hat{e}(n+L); \quad 0 \leq n < n_m. \quad (4.9.4-20)$$

26 Update the excitation memory for the adaptive codebook with the combined excitation for the current
27 subframe:

$$28 \quad E(n) = \begin{cases} E(n+L) & ; -128 \leq n < -L \\ E_T(n+L) & ; -L \leq n < 0 \end{cases} \quad (4.9.4-21)$$

1 Conditionally reset the accumulated shift counter, τ_{acc} , and the pointer to the last sample in the shifted residual,
2 n_m , according to the following:

$$3 \quad \text{if } \left(\left(\sum_{i=0}^2 ACBGIDX(i) \leq 1 \right) \text{ and } (ACBGIDX(2) \neq 1) \right) \{$$

$$4 \quad \quad \tau_{acc} = 0$$

$$5 \quad \quad n_m = 0$$

$$6 \quad \quad \}$$

7 4.9.5 Computation of the Adaptive Codebook Contribution

8 **Inputs:** The inputs to the adaptive codebook computation are:

- 9 • The vector of interpolated delays, $\dot{d}(m', j)$, calculated in 4.9.4.5
- 10 • The current subframe number, m'
- 11 • The current subframe size, L

12 **Outputs:**

- 13 • The adaptive codebook excitation, $E(n)$, where $-128 \leq n \leq 64$

14 **Initialization:** The variables used in the computation of the adaptive codebook contribution are initialized as
15 follows:

- 16 • The adaptive codebook excitation memory, $E(n) = 0$; $-128 \leq n \leq 64$

17 **Processing:**

18 Computation of the adaptive codebook contribution shall be performed according to the procedures described
19 in 4.9.5.1 and 4.9.5.2.

20 4.9.5.1 Delay Contour Computation

21 Compute the 8-times oversampled delay contour vector, $\tau_c(n)$, defined by:

$$22 \quad \tau_c(n) = \begin{cases} d(m', 0) + \frac{n \left[\dot{d}(m', 1) - \dot{d}(m', 0) \right]}{L} & ; 0 \leq n < L, \\ d(m', 1) + \frac{(n-L) \left[\dot{d}(m', 2) - \dot{d}(m', 1) \right]}{L} & ; L \leq n < (L+10) \end{cases} \quad (4.9.5-1)$$

23 where m' is the current subframe, L is the current subframe size, $\dot{d}(m', j)$ is a set of interpolated delays
24 calculated in 4.9.4.5.

25 4.9.5.2 Mapping of the Adaptive Codebook to the Delay Contour

26 The new adaptive codebook contribution, $E(n)$, is calculated by:

$$27 \quad E(n) = \sum_{i=0}^{2f_i} E(i+n-T_E(n)-f_i) I_E \left(i + (2f_i+1) T_{IE}(n) \right) \quad ; 0 \leq n < (L+10), \quad (4.9.5-2)$$

where $T_E(n)$ and $T_{IE}(n)$ are calculated for every n by:

$$T_E(n) = \begin{cases} \text{round}\{\tau_c(n)\} & ; \tau_c(n) > 0, \\ -\text{round}\{-\tau_c(n)\} & ; \tau_c(n) \leq 0, \end{cases}$$

$$T_{IE}(n) = \text{trunc}\{(T_E(n) - \tau_c(n) + 0.5)R + 0.5\},$$

$$\text{if } (T_{IE}(n) == R) \{$$

$$T_{IE}(n) = 0$$

$$T_E(n) = T_E(n) - 1$$

$$\}$$

and L is the current subframe size, $f_l = 8$, $R = 8$, and $\{I_E(n)\}$ is a set of interpolation coefficients found in Table 9-11.

4.9.6 Modification of the Residual

Inputs: The inputs to the residual modification are:

- The vector of interpolated delays, $d(m', j)$, calculated in 4.9.4.5
- The short-term prediction residual, $e(n)$
- The pitch prediction gain, β
- The current subframe number, m'
- The current subframe size, L

Outputs: The outputs from the residual modification are:

- The modified residual signal, $\hat{e}(n)$

State Variables Affected:

- The modified target residual buffer, $\hat{e}_t(n)$, where $-128 \leq n \leq 64$
- The pointer to the end of the last residual frame modified, n_m
- The accumulated shift, τ_{acc}

Initialization: The variables used in the residual modification are initialized as follows:

- The modified target residual buffer, $\hat{e}_t(n) = 0$; $-128 \leq n \leq 64$
- The pointer to the end of the last residual frame modified, $n_m = 0$
- The accumulated shift, $\tau_{acc} = 0$

Processing: The modification of the residual signal to generate a target residual for the fixed codebook search shall be computed according to 4.9.6.1 through 4.9.6.4. A shifted target residual, $\hat{e}_t(n)$, is generated in 4.9.6.1 using the past modified residual buffer and the delay contour of the current frame. This shifted residual is used as a target for shifting the residual of the current subframe. All the pitch pulses in the original residual, $e(n)$, must be shifted individually to match the delay contour of the modified target residual, $\hat{e}_t(n)$. The modification is performed by finding a shift frame containing each pulse in the original residual by the process described in 4.9.6.2. Once the shift frame is found, the accumulated shift, τ_{acc} , must be adjusted as described in 4.9.6.3 to determine the proper shift needed to match the pulse to the delay contour. The shift frame containing

1 the pulse is then shifted by τ_{acc} as described in 4.9.6.4. The procedures described in 4.9.6.2 through 4.9.6.4 must
2 be carried out for all pulses found in the residual of the current subframe.

3 4.9.6.1 Mapping of the Past Modified Residual to the Delay Contour

4 Calculate the target for the residual modification process by warping the past modified residual buffer, $\hat{\varepsilon}_t(n)$,
5 by the delay contour, $\tau_c(n)$, calculated in 4.9.5.1.

6 The new target residual buffer, $\hat{\varepsilon}_t(n)$, is calculated by:

$$7 \quad \hat{\varepsilon}_t(n) = \sum_{i=0}^{2f_l} \hat{\varepsilon}_t(i+n-T_\varepsilon(n)-f_l) I_\varepsilon(i+(2f_l+1)T_{I_\varepsilon}(n)) \quad ; 0 \leq n < (L+10), \quad (4.9.6-1)$$

8 where $T_\varepsilon(n)$ and $T_{I_\varepsilon}(n)$ are calculated for every n by:

$$9 \quad T_\varepsilon(n) = \begin{cases} \text{round}\{\tau_c(n)\} & ; \tau_c(n) > 0, \\ -\text{round}\{-\tau_c(n)\} & ; \tau_c(n) \leq 0, \end{cases}$$

$$10 \quad T_{I_\varepsilon}(n) = \text{trunc}\{(T_\varepsilon(n) - \tau_c(n) + 0.5)R + 0.5\},$$

$$11 \quad \text{if } ((T_{I_\varepsilon}n) == R)$$

$$12 \quad \{$$

$$13 \quad \quad T_{I_\varepsilon}(n) = 0$$

$$14 \quad \quad T_\varepsilon(n) = T_\varepsilon(n) - 1$$

$$15 \quad \}$$

16 and L is the current subframe size, $f_l = 3$, $R = 8$, $\{I_\varepsilon(n)\}$ is a set of interpolation coefficients found in Table

$$17 \quad 9-10, \text{ and } \tau_c(n) \text{ is computed in Equation } \tau_c(n) = \begin{cases} d(m',0) + \frac{n[d(m',1) - d(m',0)]}{L} & ; 0 \leq n < L, \\ d(m',1) + \frac{(n-L)[d(m',2) - d(m',1)]}{L} & ; L \leq n < (L+10) \end{cases}$$

18 (4.9.5-1).

19 4.9.6.2 Calculation of the Residual Shift Frame Parameters

20 First define the current subframe residual as:

$$21 \quad \varepsilon_s(n) = \varepsilon(n+80+53m') \quad ; 0 \leq n < 240-53m', \quad (4.9.6-2)$$

22 and proceed with the following sections.

23 4.9.6.2.1 Search for Pulses in the Subframe Residual

24 Calculate the location, n_{emax} , that contains the pulse having maximum energy in the subframe residual. The
25 search window is centered at 1/2 the pitch lag, $d(m',1)$, after the last modified residual sample, and is 1.5 times
26 the pitch lag in length. This location, n_{emax} , is defined as the location, n , that maximizes:

$$27 \quad E_\varepsilon(n) = \sum_{i=-2}^2 \varepsilon_s^2(T+n+i) \quad ; 0 \leq n < 1, \quad (4.9.6-3)$$

1 where the index of the start of the energy search, T , is defined by:

$$2 \quad T = \max \left\{ \left(n_m + \text{trunc} \{ -\tau_{acc} + 0.5 \} - \text{trunc} \left\{ \frac{1}{4} d(m', 1) \right\} \right), (-78 - 53m') \right\}, \quad (4.9.6-4)$$

3 where n_m is an index to the last residual sample modified, and τ_{acc} is the accumulated shift; the size of the
4 window to be searched, l , is defined by:

$$5 \quad l = \min \left\{ \text{trunc} \left\{ 1.5 d(m', 1) \right\}, 238 - 53m' - T \right\}. \quad (4.9.6-5)$$

6 Adjust n_{emax} by τ_{acc} :

$$7 \quad n_{emax} = n_{emax} + T - \text{trunc} \{ -\tau_{acc} + 0.5 \}. \quad (4.9.6-6)$$

8 4.9.6.2.2 Location of the First Pulse in the Residual

9 The location of maximum pulse energy, n_{emax} , is checked to insure it is the first pitch pulse in the residual. If
10 ($n_{emax} < n_m$), the pulse located is in a region that already has been modified, so the residual must be searched
11 again using a smaller window size. The new search window is centered one pitch lag, $d(m', 1)$, after the pulse
12 location found in 4.9.6.2.1, and is one half of a pitch lag in length. The new location, n_{emax} , is defined as the
13 location, n , that maximizes:

$$14 \quad E_c(n) = \sum_{i=-2}^2 \varepsilon_s^2(T + n + i) \quad ; 0 \leq n < l, \quad (4.9.6-7)$$

15 where the index of the start of the energy search, T , is defined by:

$$16 \quad T = \max \left\{ \left(n_{emax} + \text{trunc} \{ -\tau_{acc} + 0.5 \} + \text{trunc} \left\{ \frac{3}{4} d(m', 1) + 0.5 \right\} \right), (-78 - 53m') \right\}, \quad (4.9.6-8)$$

17 where n_{emax} is the index of the pulse located in 4.9.6.2.1, τ_{acc} is the accumulated shift; the size of the window to
18 be searched, l , is defined by:

$$19 \quad l = \min \left\{ \text{trunc} \left\{ 1.5 d(m', 1) \right\}, 238 - 53m' - T \right\}. \quad (4.9.6-9)$$

20 The location of the maximum pulse, n_{emax} , is then re-defined and adjusted by:

$$21 \quad n_{emax} = n_{emax} + T - \text{trunc} \{ -\tau_{acc} + 0.5 \}. \quad (4.9.6-10)$$

4.9.6.2.3 Location of a Pulse Inside of the Lag Window

If $n_{emax} > \left(n_m + d(m',1) \right)$, where n_{emax} was determined in 4.9.6.2.1 or 4.9.6.2.2, the pulse found has a larger lag than expected. A final pulse energy search of the lag window must be made to insure that the pulse found at n_{emax} is the desired pulse to be shifted. The new search window is centered one pitch lag, $d(m',1)$, before the pulse location found in 4.9.6.2.1 or 4.9.6.2.2, and is one half of a pitch lag in length. The location, n''_{emax} , of the pulse with maximum energy in the current lag window is defined as the location, n , that maximizes:

$$E_g(n) = \sum_{i=-2}^2 \varepsilon_s^2(T+n+i) \quad ; 0 \leq n < 1, \quad (4.9.6-11)$$

where the index of the start of the energy search, T , is defined by:

$$T = \max \left\{ \left(n_{emax} + \text{trunc} \{ -\tau_{acc} + 0.5 \} - \text{trunc} \left\{ \frac{5}{4} d(m',1) + 0.5 \right\} \right), (-78 - 53m') \right\}, \quad (4.9.6-12)$$

where n_{emax} is the index of the pulse determined in 4.9.6.2.1 or 4.9.6.2.2, τ_{acc} is the accumulated shift; the size of the window to be searched, l , is defined by:

$$l = \min \left\{ \text{trunc} \left\{ 0.5 d(m',1) \right\}, 238 - 53m' - T \right\} \quad (4.9.6-13)$$

The location, n''_{emax} , of the maximum pulse in the lag window, is adjusted by τ_{acc} :

$$n''_{emax} = n_{emax} + T - \text{trunc} \{ -\tau_{acc} + 0.5 \}, \quad (4.9.6-14)$$

The location of the pulse to be shifted, n_{emax} , is then re-defined by:

$$n_{emax} = \begin{cases} n''_{emax} & ; n''_{emax} \geq n_m, \\ n_{emax} & ; \text{otherwise.} \end{cases} \quad (4.9.6-15)$$

4.9.6.2.4 Shift Frame Boundary Calculation

The boundaries, T_{start} and T_{end} , for the frame in the residual to be shifted are calculated by:

$$T_{start} = n_m, \quad (4.9.6-16)$$

$$T_{end} = \begin{cases} L & ; L-10 < n_{emax} < L-5, \\ L+10 & ; L < n_{emax} < L+5, \\ L & ; n_{emax} \geq L+5, \\ n_{emax} + 10 & ; \text{otherwise.} \end{cases} \quad (4.9.6-17)$$

1 4.9.6.2.5 Shift Decision

2 Calculate a shift decision flag, ε_{shift} , by:

$$3 \quad \varepsilon_{shift} = \begin{cases} FALSE & ;(n_{emax} \geq T_{end}) \text{ or } (n_{emax} < T_{start}), \\ TRUE & ;\text{otherwise.} \end{cases} \quad (4.9.6-18)$$

4 4.9.6.2.6 Peak to Average Ratio Calculation

5 If the shift decision flag is true ($\varepsilon_{shift} == TRUE$) as evaluated in 4.9.6.2.5, the ratio of the peak energy to the
6 average energy in the residual frame to be shifted must be calculated to insure that the frame contains a valid
7 pulse. The residual frame to be shifted is defined as $\varepsilon_s(n)$, where $T_{start} \leq n \leq T_{end}$ (see 4.5.6.2 through 4.5.6.4).

8 Calculate a vector of smoothed residual energies, $E_{win}(n)$, by:

$$9 \quad E_{win}(n) = \sum_{i=0}^4 \varepsilon_s^2(T_{adj} + i + n), \quad 0 \leq n \leq l, \quad (4.9.6-19)$$

10 where the window size is calculated by:

$$11 \quad l = T_{end} - T_{start} - 5, \quad (4.9.6-20)$$

12 and T_{adj} is calculated as:

$$13 \quad T_{adj} = T_{start} - \text{trunc}\{\tau_{acc}\}. \quad (4.9.6-21)$$

14 The peak energy, E_{peak} , is then calculated as:

$$15 \quad E_{peak} = \max\{E_{win}(n)\} \quad ;0 \leq n \leq l, \quad (4.9.6-22)$$

16 and the average energy, $E_{avg}(n)$, is calculated as:

$$17 \quad E_{avg}(n) = \begin{cases} \alpha E_{avg}(n-1) + (1-\alpha)\varepsilon_s^2(T_{adj} + n + 4); & \varepsilon_s^2(T_{adj} + n + 4) < 4E_{avg}(n-1), \\ E_{avg}(n-1) & ;\text{otherwise} \end{cases} \quad 0 < n \leq l, \quad (4.9.6-23)$$

18 where $\alpha=0.875$, and $E_{avg}(0) = E_{win}(0)$.

19 The ratio of the peak to average energy is then calculated by:

$$20 \quad E_{ratio} = \begin{cases} 0 & ;E_{avg}(l) = 0, \\ \left(\frac{E_{peak}}{E_{avg}(l)} \right) \left(\frac{54}{T_{end} - T_{start}} \right) & ;\text{otherwise,} \end{cases} \quad (4.9.6-24)$$

21 The shift decision flag, ε_{shift} , is then re-defined depending on the peak-to-average ratio by:

$$\varepsilon_{shift} = \begin{cases} FALSE & ;(E_{ratio} < 16.0), \\ TRUE & ;\text{otherwise.} \end{cases} \quad (4.9.6-25)$$

4.9.6.3 Matching the Residual to the Delay Contour

If the shift decision flag is true ($\varepsilon_{shift} == TRUE$) for the current shift frame, update the accumulated shift, τ_{acc} . The accumulated shift is adjusted by the shift required to match the residual shift frame determined in 4.5.6.2 to the modified residual target, $\hat{\varepsilon}_t(n)$. This operation is detailed in 4.5.6.3.1 through 4.5.6.3.4.

4.9.6.3.1 Computation of the Shift Range

The size of the residual frame to be shifted, l , is calculated by:

$$l = T_{end} - T_{start}, \quad (4.9.6-26)$$

The residual frame is shifted between T_{srl} and T_{srr} , calculated by:

$$T_{srl} = \begin{cases} S_r + 1 & ;\tau_{acc} < 0, \\ S_r & ;\text{otherwise,} \end{cases} \quad (4.9.6-27)$$

$$T_{srr} = \begin{cases} S_r + 1 & ;\tau_{acc} > 0, \\ S_r & ;\text{otherwise,} \end{cases} \quad (4.9.6-28)$$

where $S_r = 3$.

For non-periodic signals, T_{srl} and T_{srr} are limited as defined by:

$$\begin{aligned} & \text{if } [(\beta < 0.2) \text{ and } (|\tau_{acc}| > 15)] \text{ or } [(\beta < 0.3) \text{ and } (|\tau_{acc}| > 30)] \\ & \quad \text{if } (\tau_{acc} < 0) \\ & \quad \quad T_{srr} = 1 \\ & \quad \text{else} \\ & \quad \quad T_{srl} = 1 \end{aligned}$$

For both periodic and non-periodic signals, limit the shift bounds, T_{srl} and T_{srr} , as defined by:

$$T_{srl} = \min \{ 72 - \text{trunc} \{ \tau_{acc} \}, T_{srl} \}, \quad (4.9.6-29)$$

$$T_{srr} = \min \{ 72 + \text{trunc} \{ \tau_{acc} \}, T_{srr} \}. \quad (4.9.6-30)$$

4.9.6.3.2 Generation of a Temporary Modified Residual Signal for Matching

Generate a temporary modified residual, $\hat{\varepsilon}_{tmp}(n)$, by shifting the current residual shift frame, $\varepsilon_s(n)$, by $\tau_{acc} + T_{srl}$:

$$\hat{\varepsilon}_{tmp}(n) = \sum_{\hat{i}=0}^{2f_l} \hat{\varepsilon}_s(i + T_{start} - T - f_l + n) I_{\varepsilon}(i + (2f_l + 1)T_l) \quad ; 0 \leq n \leq (l + T_{srl} + T_{srr}), \quad (4.9.6-31)$$

1 where T and T_I are defined by:

$$\begin{aligned}
 & T_E(n) = \begin{cases} \text{round}\{\tau_{acc} + T_{srl}\} & ; \tau_{acc} + T_{srl} > 0, \\ -\text{round}\{-(\tau_{acc} + T_{srl})\} & ; \tau_{acc} + T_{srl} \leq 0, \end{cases} \\
 & T_I = \text{trunc}\{(T - (\tau_{acc} + T_{srl}) + 0.5)R + 0.5\}, \\
 & \text{if } (T_I = R) \{ \\
 & \quad T_I = 0 \\
 & \quad T = T - 1 \\
 & \}
 \end{aligned}$$

8 and l is the shift frame size, $f_l = 3$, $R = 8$, and $\{I_{\mathcal{E}}(k)\}$ is a set of interpolation coefficients found in Table 9-10.

9 4.9.6.3.3 Matching the Temporary Modified Residual to the Target Residual

10 Generate an integer energy correlation vector, $E_I(n)$:

$$E_I = \sum_{i=0}^{l-1} \hat{\epsilon}_{imp}(n+i) \hat{\epsilon}_I(T_{start} + i) \quad ; 0 \leq n \leq T_{srl} + T_{srr}, \quad (4.9.6-32)$$

12 where $\{\hat{\epsilon}_I\}$ was obtained in 4.5.6.1.

13 Interpolate $E_I(n)$ to obtain the fractional energy correlation vector, $E_f(n)$:

$$E_f(8(k-1) + j) = \sum_{i=-1}^1 I_f(i, j) E_I(i + K) \quad ; 0 \leq j \leq 7, 0 < T_{srl} + T_{srr}, \quad (4.9.6-33)$$

15 where $\{I_f(i, j)\}$ is a set of interpolation coefficients found in Table 9-14.

16 The optimal shift, τ_{opt} , that will match the temporary modified residual to the target residual is then defined as
 17 the index, n , that maximizes $E_f(n)$.

18 4.9.6.3.4 Adjustment of the Accumulated Shift

19 The accumulated shift is then adjusted by:

$$\tau_{acc} = \begin{cases} \tau_{acc} - \left[\frac{\tau_{acc} - RT_{srl} + R/2}{R} \right] & ; \alpha > 0.7, \\ \tau_{acc} & ; \text{otherwise,} \end{cases} \quad (4.9.6-34)$$

21 where $R = 8$, and the gain, α , of the new shift, τ_{opt} , is calculated by:

$$\alpha = \begin{cases} 0 & ; E_{\epsilon} E_T = 0, \\ \frac{E_f(\tau_{opt})}{\sqrt{E_{\epsilon} E_T}} & ; \text{otherwise.} \end{cases} \quad (4.9.6-35)$$

23 where the energy of the temporary modified residual is calculated by:

$$E_E = \sum_{i=T_{start}}^{L+T_{end}-1} \hat{\varepsilon}_{imp}^2(i+T_{start}), \quad (4.9.6-36)$$

and the energy of the target modified residual is defined by:

$$E_T = \sum_{i=0}^{L-1} \hat{\varepsilon}_t^2(i+T_{start}). \quad (4.9.6-37)$$

4.9.6.4 Modification of the Residual

The current subframe residual, $\varepsilon_s(n)$, is shifted by τ_{acc} , to create the modified residual, $\hat{\varepsilon}(n)$, for the fixed codebook search:

$$\hat{\varepsilon}(n+n_m) = \sum_{i=0}^{2f_i} \varepsilon_s(i+n+n_m-T-f_i)I_E(i+T_i(2f_i+1)) \quad ; 0 \leq n \leq T_{end}-T_{start}, \quad (4.9.6-38)$$

where T and T_i are calculated by:

$$T = \begin{cases} \text{round}\{\tau_{acc}\} & ; \tau_{acc} > 0, \\ -\text{round}\{-\tau_{acc}\} & ; \tau_{acc} \leq 0, \end{cases}$$

$$T_i = \text{trunc}\{(T - \tau_{acc} + 0.5)R + 0.5\},$$

$$\text{if } (T_i = R) \{$$

$$T_i = 0$$

$$T = T - 1$$

$$\}$$

and $f_i = 8$, $R = 8$, and $\{I_{\square}(n)\}$ is a set of interpolation coefficients found in Table 9-11.

Next, use the following pseudo-code to update n_m and determine whether the pulse searching procedure is complete:

```

if ( $T_{end} < L$ ) {
   $n_m = T_{end}$ 
  Go to 4.5.6.2
} else {
   $n_m = T_{end} - L$ 
  Go to 4.5.6.5
}

```

4.9.6.5 Modified Target Residual Update

After having completed the modification of the residual, $\hat{\varepsilon}(n)$, for the entire subframe, the modified target residual buffer, $\hat{\varepsilon}_t(n)$, is updated as follows:

$$\hat{\varepsilon}_t(n) = \begin{cases} \hat{\varepsilon}_t(n+L) & ; -128 \leq n < -L \\ \hat{\varepsilon}(n+L) & ; -L \leq n < 0 \end{cases}, \quad (4.9.6-39)$$

4.9.7 Computation of the ACELP Fixed Codebook Contribution for SO 3

The fixed codebook is based on an algebraic codebook structure, which has advantages in terms of storage, search complexity, and robustness. The codebook structure is based on an interleaved single-pulse permutation (ISPP) design. The codebook is searched on a subframe basis for the best index and gain to minimize the mean-squared weighted error between the original and synthesis speech.

Inputs: The inputs to the algebraic codebook coding routine are:

- The length L impulse response of the weighted synthesis filter, $h_{wq}(k)$, zero extended to length 55
- The length L residual domain target vector, $x(k)$, zero extended to length 55
- The length L perceptual domain target vector, $x_v(k)$, zero extended to length 55
- The average pitch delay for the current subframe, τ
- The quantized pitch prediction gain, g_p

Outputs: The outputs of the algebraic codebook coding routine are:

- The codeword of the algebraic codebook, $FCBSIDX(m',i)$; $0 \leq i \leq 3$
- The fixed codebook excitation vector, c_k
- The fixed codebook gain, g_c

Processing: The algebraic codebook shall be implemented using the procedures described in 4.9.7.1 through 4.9.7.4.

4.9.7.1 Algebraic Codebook Structure, Rate 1

The Rate 1 fixed codebook is a 35-bit algebraic codebook. In this codebook, every codebook vector of length 55 contains at most 8 non-zero pulses. All pulses can have the amplitudes +1 or -1. The 55 positions in a subframe are divided into 5 tracks, as shown in Table 4-24. The algebraic codebook search always examines all the 55 positions as shown, regardless of subframe size. Based on the possible subframe size of 53, 53, and 54, the extra positions are ignored.

Table 4-24 Positions of Individual Pulses in the Rate 1 Algebraic Codebook

Track	Positions
T0	0, 5, 10, 15, 20, 25, 30, 35,40,45,50
T1	1, 6, 11, 16, 21, 26, 31, 36,41,46,51
T2	2, 7, 12, 17, 22, 27, 32, 37,42,47,52
T3	3, 8, 13, 18, 23, 28, 33, 38,43,48,53
T4	4, 9, 14, 19, 24, 29, 34, 39,44,49,54

Of the 5 tracks, 3 are allocated two pulses each and 2 are allocated one pulse each. This accounts for a total of 8 pulses. The single-pulse tracks can be either T3-T4, T4-T0, T0-T1, or T1-T2. The choice of single-pulse tracks is encoded with 2 bits. The positions of the pulses in the 2 single-pulse tracks are encoded with 7 bits

1 (11x11=121<128) and their signs are encoded with 2 bits. For each double-pulse track, both positions and
 2 signs of the two pulses are encoded with 8 bits, which will be explained in more detail in 4.9.7.3. This gives a
 3 total of 35 bits (2+7+2+8x3).

4 The codebook vector, \mathbf{c}_k , is constructed according to:

$$5 \quad c_k(j) = \sum_{i=0}^{N_p-1} s_i \delta(j - p_i) \quad ; 0 \leq j \leq 54, \quad (4.9.7-1)$$

6 where $\delta(j - p_i)$ is a unit pulse at the i -th pulse position p_i of the k -th codevector, s_i is the sign of the i -th pulse,
 7 and N_p is the number of pulses, and k is the range of all possible code vectors.

8 A special feature incorporated in the algebraic codebook is that the selected codebook vector is dynamically
 9 shaped by filtering it through an adaptive pre-filter. In this implementation, the prefilter:

$$10 \quad F(z) = \begin{cases} 1 & ; \tau \geq L, \\ \frac{1}{1 - g_p z^{-\tau}} & ; \text{otherwise,} \end{cases} \quad (4.9.7-2)$$

11 shall be used, where τ is the average subframe pitch delay and g_p is the pitch gain. The pitch gain is the
 12 quantized pitch gain in the current subframe bounded by [0.2, 0.9]. For delays less than 55, the codebook
 13 vector, \mathbf{c}_k , is modified according to:

$$14 \quad c_k(j) = \begin{cases} c_k(j) & ; 0 \leq j < \tau, \\ c_k(j) + g_p c_k(j - \tau) & ; \tau \leq j \leq 54. \end{cases} \quad (4.9.7-3)$$

15 This modification is incorporated in the fixed codebook search by including the prefilter in the impulse
 16 response $h_{wq}(j)$. That is, prior to codebook search, the impulse response $h_{wq}(j)$ shall be modified according
 17 to:

$$18 \quad h_{wq}(j) = \begin{cases} h_{wq}(j) & ; 0 \leq j < \tau, \\ h_{wq}(j) + g_p h_{wq}(j - \tau) & ; \tau \leq j \leq 54. \end{cases} \quad (4.9.7-4)$$

19 4.9.7.2 Algebraic Codebook Search

20 The algebraic codebook is searched by minimizing the mean-squared error between the weighted input speech
 21 and the weighted synthesis speech. The perceptual domain target signal $x_w(n)$ is used in the closed-loop
 22 fixed-codebook search and is given by Equation 4.9.4-15.

23 Let \mathbf{c}_k be the algebraic codebook vector at index k . The algebraic codebook is searched by maximizing the
 24 term:

$$T_k = \frac{C_k}{E_k} = \frac{(\mathbf{d}^t \mathbf{c}_k)^2}{\mathbf{c}_k^t \Phi \mathbf{c}_k}, \quad (4.9.7-5)$$

where $\mathbf{d} = \mathbf{H}^t \mathbf{x}_w$ is the cross-correlation between the perceptual domain target signal $x_w(n)$ and the impulse response $h_{wq}(n)$, $\Phi = \mathbf{H}^t \mathbf{H}$ is the correlation matrix of the impulse response $h_{wq}(n)$, and \mathbf{H} is a lower triangular Toeplitz matrix with diagonal $h_{wq}(0)$ and lower diagonals $h_{wq}(1), \dots, h_{wq}(54)$, i.e.:

$$\mathbf{H} = \begin{bmatrix} h_{wq}(0) & 0 & 0 & \dots & 0 \\ h_{wq}(1) & h_{wq}(0) & 0 & \dots & 0 \\ h_{wq}(2) & h_{wq}(1) & h_{wq}(0) & \dots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ h_{wq}(54) & h_{wq}(53) & h_{wq}(52) & \dots & h_{wq}(0) \end{bmatrix}. \quad (4.9.7-6)$$

The cross-correlation vector \mathbf{d} and the matrix Φ are computed prior to the codebook search. The elements of the vector \mathbf{d} are computed by:

$$d(n) = \sum_{j=n}^{54} x_w(j) h_{wq}(j-n) \quad ; 0 \leq n \leq 54, \quad (4.9.7-7)$$

and the (i, j) -th element of the symmetric matrix Φ is computed by:

$$\phi(i, j) = \begin{cases} \sum_{n=\max\{i, j\}}^{L-1} h_{wq}(n-i) h_{wq}(n-j) & ; (0 \leq j < L) \text{ and } (0 \leq i < L) \\ 0 & ; (L \leq j < 55) \text{ and } (L \leq i < 55) \end{cases}. \quad (4.9.7-8)$$

The algebraic structure of the codebook allows for very fast search procedures since the innovation vector, \mathbf{c}_k , contains only a few non-zero pulses. The correlation in the numerator of Equation 4.9.7-5 is given by:

$$c_k = \left(\sum_{i=0}^{N_p-1} s_i d(p_i) \right)^2. \quad (4.9.7-9)$$

The energy in the denominator of Equation 4.9.7-5 is given by:

$$E_k = \sum_{i=0}^{N_p-1} \phi(p_i, p_i) + 2 \sum_{i=0}^{N_p-2} \sum_{j=i+1}^{N_p-1} s_i s_j \phi(p_i, p_j). \quad (4.9.7-10)$$

In order to determine the optimal algebraic codebook vector which maximizes the term in Equation 4.9.7-5, the correlation and energy terms in Equation 4.9.7-9 and Equation 4.9.7-10 should be computed for all possible combinations of pulse positions and signs. This, however, is a prohibitive task. In order to simplify the search, two strategies for searching the pulse signs and positions as explained below shall be used.

4.9.7.2.1 Pre-setting of Pulse Signs

In order to simplify the search procedure, the pulse signs are preset (outside the closed loop search) by considering the sign of an appropriate reference signal. In this case, the signal $e(i)$, given by:

$$e_i = \sqrt{\frac{\sum_{j=0}^{54} d^2(j)}{\sum_{j=0}^{54} x^2(j)}} x(i) + 2d(i); \quad 0 \leq i \leq 54, \quad (4.9.7-11)$$

shall be used, where $x(i)$ is the residual domain target vector which is described in 4.9.4.10.

Amplitude pre-setting shall be done by setting the amplitude of a pulse at position i equal to the sign of $e(i)$. Hence, once the sign signal $s_i = \text{sign}\{e(i)\}$ and the signal $d'(i) = d(i)s_i$ are computed, then the matrix Φ shall be modified by including the sign information, that is, $\phi'(i, j) = s_i s_j \phi(i, j)$. The correlation in Equation 4.9.7-9 is now given by:

$$c_k = \left(\sum_{i=0}^{N_p-1} d'(p_i) \right)^2, \quad (4.9.7-12)$$

and the energy in Equation 4.5.7.2-6 is given by:

$$E_k = \sum_{i=0}^{N_p-1} \phi'(p_i, p_i) + 2 \sum_{i=0}^{N_p-2} \sum_{j=i+1}^{N_p-1} \phi'(p_i, p_j). \quad (4.9.7-13)$$

4.9.7.2.2 Non-Exhaustive Pulse Position Search

Having preset the pulse amplitudes, as explained in 4.9.7.2.1, the optimal pulse positions shall be determined using an efficient non-exhaustive analysis-by-synthesis search technique. In this technique, the term in Equation 4.9.7-5 is tested for a small percentage of position combinations, using an iterative “depth-first” tree search strategy. In this approach, the 8 pulses are grouped into 4 pairs of pulses. The pulse positions shall be determined sequentially one pair at a time. In the first iteration, the single-pulse tracks are T3 and T4. The search process shall be repeated for other 3 iterations, by assigning the single-pulse tracks to T4-T0, T0-T1, and T1-T2 respectively. The codeword, q , used to represent the various chosen tracks are given in Table 4-25.

Table 4-25. Codeword for the Track Orders

Double-pulse Track Order (p₀, p₁), (p₂, p₃), (p₄, p₅)	Single-pulse Track Order (p₆, p₇)	Codeword (q)
T0-T1-T2	T3-T4	00
T1-T2-T3	T4-T0	01
T2-T3-T4	T0-T1	10
T3-T4-T0	T1-T2	11

1 Once the positions and signs of the excitation pulses are determined, the codebook vector, \mathbf{c}_k , shall be built as in
 2 Equation 4.9.7-1 and shall be modified according to Equation 4.9.7-3.

3 4.9.7.3 Codeword Computation of the Algebraic Codebook

4 Upon completion of algebraic codebook search, the positions and signs of the pulses are encoded into 35 bits.
 5 The algebraic codebook routine outputs 4 indices: the first 3 indices (8 bits each) represent the positions and
 6 signs of each double-pulse track and the 4th index (11 bits) represents the positions and signs of pulses in the
 7 two single-pulse tracks (9 bits) along with the codeword for the two single-pulse tracks (2 bits). For the
 8 codeword computations, the following variables are defined for each of the single and double pulse tracks:

9
$$\lambda_0 = \lfloor p_i / 5 \rfloor; \quad i \in \{0,2,4,6\}, \quad (4.9.7-14)$$

10
$$\lambda_1 = \lfloor p_j / 5 \rfloor; \quad j \in \{1,3,5,7\}. \quad (4.9.7-15)$$

11 These are the decimated pulse positions and s_{λ_0} and s_{λ_1} are the signs of the respective decimated positions, and
 12 b_{λ_0} and b_{λ_1} are defined as:

13
$$b_{\lambda_i} = \begin{cases} 0 & ;s_{\lambda_i} > 0, \\ 1 & ;s_{\lambda_i} < 0 \end{cases} \quad 0 \leq i \leq 1. \quad (4.9.7-16)$$

14 In the case of coding the 3 double-pulse tracks, each 8 bit codeword $FCBSIDX(m',i)$, is ($0 \leq i \leq 2$) calculated
 15 according to:

16
$$FCBSIDX(m',i) = \begin{cases} b_{\lambda_k} \times 128 + \min\{\lambda_0, \lambda_1\} \times 11 + \max\{\lambda_0, \lambda_1\}; & \text{if } s_{\lambda_0} = s_{\lambda_1}, \\ b_{\lambda_k} \times 128 + \max\{\lambda_0, \lambda_1\} \times 11 + \min\{\lambda_0, \lambda_1\}; & \text{if } s_{\lambda_0} = -s_{\lambda_1}, \end{cases} \quad (4.9.7-17)$$

17 where b_{λ_k} follows the sign of the pulse located at the larger decimated position, i.e., $\max\{\lambda_0, \lambda_1\}$. The three
 18 double-pulse codewords $FCBSIDX(m',i)$, $0 \leq i \leq 2$, are packed according to the order specified in the Table
 19 4-25, which depends on the positions of the single-pulse tracks.

20 In the case of coding the two single-pulse tracks, the 11 bit codeword $FCBSIDX(m',3)$ is calculated according
 21 to:

22
$$FCBSIDX(m',3) = q \times 512 + b_{\lambda_0} \times 256 + b_{\lambda_1} \times 128 + \lambda_0 \times 11 + \lambda_1, \quad (4.9.7-18)$$

23 where $0 \leq q \leq 3$ is the single-pulse track codeword in Table 4-25.

24 4.9.7.4 Algebraic Codebook Structure, Rate 1/2

25 A 10 bit algebraic codebook is used for Rate 1/2 packets. The innovation vector contains 3 non-zero pulses.
 26 Each pulse has 8 possible positions, which are coded by 3 bits. The pulse positions and corresponding
 27 codewords are given in Table 4-26. All pulses have a fixed signs (+1 for T_0 and T_2 and -1 for T_1). An
 28 additional bit, however, is used to change the signs of all three pulses simultaneously, i.e., $s = 1$ indicates
 29 polarity inversion, $s = 0$ otherwise. Therefore, the total bits per subframe for Rate 1/2 is $3 \times 3 + 1 = 10$.

1 The codebook is searched using techniques similar to that for Rate 1. However, in the Rate 1/2 case, all the
 2 pulse position combinations are exhaustively searched by maximizing Equation 4.9.7-5. Upon completion of
 3 the search, the sign information is processed as follows:

```

4         if ( sign{ d'ck } < 0 ) {
5             ck = -ck
6             s = 1
7         } else {
8             s = 0
9         }
    
```

10 By referencing Table 4-26, the 10-bit codeword can then be calculated by:

11
$$FCBSIDX(m', 0) = s \times 512 + q_{T_0} \times 64 + q_{T_1} \times 8 + q_{T_2} \text{ ,} \tag{4.9.7-19}$$

12 **Table 4-26. Positions of Individual Pulses in the Rate 1/2 Algebraic Codebook**

Pulse	Positions							
T ₀	0	7	14	21	28	35	42	49
T ₁	2	9	16	23	30	37	44	51
T ₂	4	11	18	25	32	39	46	53
Codewords <i>q_{T_i} ; 0 ≤ i ≤ 2</i>	000	001	010	011	100	101	110	111

13

1 4.9.8 Computation of the Factorial fixed codebook contribution

2 The fixed codebook is based on a factorial codebook structure, which has advantages in terms of storage,
3 search complexity, and robustness. The codebook is searched on a subframe basis for the best index and gain to
4 minimize the mean-squared weighted error between the original and synthesis speech.

5 **Inputs**

6 The inputs to the factorial codebook coding routine are:

7 The length L impulse response of the weighted synthesis filter, $h_{wq}(k)$, zero extended to length 55

8 The length L residual domain target vector, $x(k)$, zero extended to length 55

9 The length L perceptual domain target vector, $x_w(k)$, zero extended to length 55

10 The average pitch delay for the current subframe, τ

11 The quantized pitch prediction gain, g_p

12 **Outputs**

13 The outputs of the factorial codebook coding routine are:

14 The codeword of the factorial codebook, $FCBSIDX(m',i)$; $0 \leq i \leq 3$

15 The fixed codebook excitation vector, \mathbf{c}_k

16 The fixed codebook gain, g_c

17 **Processing**

18 The factorial codebook shall be implemented using the procedures described in Sections 4.9.8.1 through
19 4.9.8.4.

4.9.8.1 Fixed codebook structure, Rate 1

The Rate 1 fixed codebook is a 35-bit sparse pulse codebook. In this codebook, every codebook vector of length 55 contains at most 7 nonzero pulses. All pulses can have the amplitudes of 1 with a sign of +1 or -1. The 7 pulses can take any position in the subframe. Further, up to 7 of these pulses can be stacked onto the same position. Stacking reduces the number of nonzero pulses, but gives greater flexibility in controlling the shape for the fixed code vector. The factorial codebook search always examines all the 55 positions as shown, regardless of subframe size. Based on the possible subframe size of 53, 53, and 54, the extra positions are ignored.

The maximum number of code-vectors is given by

$$N = \sum_{p=1}^7 {}^{54}C_p {}^{(7-1)}C_{(p-1)} 2^p \quad (4.9.8-1)$$

It can be easily seen that $\lceil \log_2(N) \rceil = 35$ bits. The code-vector spans the range $0 \leq c < N$. The position of the pulses is searched as described in Section 4.9.4.11, where the notation

$${}^n C_r = \frac{n!}{r!(n-r)!} = \text{Number of ways to choose } r \text{ items out of a total of } n \text{ items} \quad (4.9.8-2)$$

The codebook vector, c_k , is constructed according to:

$$c_k(j) = \sum_{i=0}^{N_p-1} s_i \delta(j - p_i) \quad ; 0 \leq j \leq 54 \quad (4.9.8-3)$$

where $\delta(j - p_i)$ is a unit pulse at the i -th pulse position p_i of the k -th code vector, s_i is the sign of the i -th pulse, and N_p is the number of pulses, and k is the range of all possible code vectors.

A special feature incorporated in the factorial codebook is that the selected codebook vector is dynamically shaped by filtering it through an adaptive pre-filter. In this implementation, the prefilter:

$$F(z) = \begin{cases} 1 & ; \tau \geq L, \\ \frac{1}{1 - g_p z^{-\tau}} & ; \text{otherwise,} \end{cases} \quad (4.9.8-4)$$

shall be used, where τ is the average subframe pitch delay and g_p is the pitch gain. The pitch gain is the quantized pitch gain in the current subframe bounded by [0.2, 0.9]. For delays less than 55, the codebook vector, c_k , is modified according to:

$$c_k(j) = \begin{cases} c_k(j) & ; 0 \leq j < \tau, \\ c_k(j) + g_p c_k(j - \tau) & ; \tau \leq j \leq 54. \end{cases} \quad (4.9.8-5)$$

This modification is incorporated in the fixed codebook search by including the prefilter in the impulse response $h_{wq}(j)$. That is, prior to codebook search, the impulse response $h_{wq}(j)$ shall be modified according

to:

$$h_{wq}(j) = \begin{cases} h_{wq}(j) & ; 0 \leq j < \tau, \\ h_{wq}(j) + g_p h_{wq}(j - \tau) & ; \tau \leq j \leq 54. \end{cases} \quad (4.9.8-6)$$

4.9.8.2 Codebook search

The factorial codebook is searched by minimizing the mean-squared error between the weighted input speech and the weighted synthesis speech. The perceptual domain target signal $x_w(n)$ is used in the closed-loop fixed-codebook search and is given by Equation 4.9.4-15.

Let c_k be the factorial codebook vector at index k . The factorial codebook is searched by maximizing the term:

$$T_k = \frac{C_k}{E_k} = \frac{(\mathbf{d}^t \mathbf{c}_k)^2}{\mathbf{c}_k^t \Phi \mathbf{c}_k}, \quad (4.9.8-7)$$

where $\mathbf{d} = \mathbf{H}^t \mathbf{x}_w$ is the cross-correlation between the perceptual domain target signal $x_w(n)$ and the impulse response $h_{wq}(n)$, $\Phi = \mathbf{H}^t \mathbf{H}$ is the correlation matrix of the impulse response $h_{wq}(n)$, and \mathbf{H} is a lower triangular Toeplitz matrix with diagonal $h_{wq}(0)$ and lower diagonals $h_{wq}(1), \dots, h_{wq}(54)$, i.e.:

$$\mathbf{H} = \begin{bmatrix} h_{wq}(0) & 0 & 0 & \dots & 0 \\ h_{wq}(1) & h_{wq}(0) & 0 & \dots & 0 \\ h_{wq}(2) & h_{wq}(1) & h_{wq}(0) & \dots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ h_{wq}(54) & h_{wq}(53) & h_{wq}(52) & \dots & h_{wq}(0) \end{bmatrix} \quad (4.9.8-8)$$

The cross-correlation vector \mathbf{d} and the matrix Φ are computed prior to the codebook search. The elements of the vector \mathbf{d} are computed by:

$$d(n) = \sum_{j=n}^{54} x_w(j) h_{wq}(j-n) \quad ; 0 \leq n \leq 54, \quad (4.9.8-9)$$

and the (i, j) -th element of the symmetric matrix Φ is computed by:

$$\phi(i, j) = \begin{cases} \sum_{n=\max\{i, j\}}^{L-1} h_{wq}(n-i) h_{wq}(n-j) & ; (0 \leq j < L) \text{ and } (0 \leq i < L) \\ 0 & ; (L \leq j < 55) \text{ and } (L \leq i < 55) \end{cases} \quad (4.9.8-10)$$

The sparse structure of the codebook allows for very fast search procedures since the innovation vector, c_k , contains only a few nonzero pulses. The correlation in the numerator of Equation 4.9.8-7 is given by:

$$c_k = \left(\sum_{i=0}^{N_p-1} s_i d(p_i) \right)^2 \quad (4.9.8-11)$$

The energy in the denominator of Equation 4.9.8-7 is given by:

$$E_k = \sum_{i=0}^{N_p-1} \phi(p_i, p_i) + 2 \sum_{i=0}^{N_p-2} \sum_{j=i+1}^{N_p-1} s_i s_j \phi(p_i, p_j) \quad (4.9.8-12)$$

In order to determine the optimal factorial codebook vector which maximizes the term in Equation 4.9.8.2-1, the correlation and energy terms in Equation 4.9.8.2-5 and Equation 4.9.8.2-6 should be computed for all possible combinations of pulse positions and signs. This, however, is a prohibitive task. In order to simplify the search, two strategies for searching the pulse signs and positions as explained below shall be used.

4.9.8.2.1 Pre-setting of pulse signs

In order to simplify the search procedure, the pulse signs are preset (outside the closed loop search) by considering the sign of an appropriate reference signal. In this case, the signal $e(i)$, given by:

$$e_i = \sqrt{\frac{\sum_{j=0}^{54} d^2(j)}{\sum_{j=0}^{54} x^2(j)}} x(i) + 2d(i) \quad ; \quad 0 \leq i \leq 54, \quad (4.9.8-13)$$

shall be used, where $x(i)$ is the residual domain target vector which is described in Section 4.9.4.10.

Amplitude pre-setting shall be done by setting the amplitude of a pulse at position i equal to the sign of $e(i)$. Hence, once the sign signal $s_i = \text{sign}\{e(i)\}$ and the signal $d'(i) = d(i)s_i$ are computed, then the matrix Φ shall be modified by including the sign information, that is, $\phi'(i, j) = s_i s_j \phi(i, j)$. The correlation in Equation

4.9.8.2-5 is now given by:

$$c_k = \left(\sum_{i=0}^{N_p-1} d'(p_i) \right)^2 \quad (4.9.8-14)$$

and the energy in Equation 4.9.8.2-6 is given by:

$$E_k = \sum_{i=0}^{N_p-1} \phi'(p_i, p_i) + 2 \sum_{i=0}^{N_p-2} \sum_{j=i+1}^{N_p-1} \phi'(p_i, p_j) \quad (4.9.8-15)$$

4.9.8.2.2 Non-exhaustive pulse position search

Having preset the pulse amplitudes, as explained in Section 4.9.8.2.1, the optimal pulse positions shall be determined using an efficient non-exhaustive analysis-by-synthesis search technique. Once the positions and signs of the excitation pulses are determined, the codebook vector, c_k , shall be built as in Equation 4.9.8-3 and shall be modified according to Equation 4.9.8-5.

4.9.8.3 Codeword computation of the factorial codebook

Upon completion of factorial codebook search, the positions and signs of the pulses are encoded into 35 bits based on the chosen codebook vector, c_k .

Table 4-27 Definitions for full-rate CELP factorial codebook

Code	Definition
L	Subframe size
T	Total number of unit amplitude pulses
\tilde{T}	Number of nonzero pulses (or locations) in the best code vector; $1 \leq \tilde{T} \leq T$
$P_i; 0 \leq i \leq \tilde{T} - 1$	Positions in the code vector that contain the \tilde{T} nonzero pulses; $0 \leq P_i \leq L - 1$
$S_i; 0 \leq i \leq \tilde{T} - 1$	Sign information of the \tilde{T} nonzero pulses; $S_i = \begin{cases} 0; & \text{if sign of pulse at } P_i \text{ is zero or positive} \\ 1; & \text{if sign of pulse at } P_i \text{ is negative} \end{cases}$
$A_i; 0 \leq i \leq \tilde{T} - 1$	Number of unit amplitude pulses in each of the \tilde{T} nonzero pulse locations; $\sum_{i=0}^{\tilde{T}-1} A_i = T$
$T_d^k; 1 \leq k \leq T$	Number of pulse locations with at least k stacked unit amplitude pulses. Note: $T_d^1 = \tilde{T}, T_d^{k-1} \geq T_d^k$
$T_m^k;$	Total number of unit amplitude pulse (T) - number of pulse locations with at most k stacked unit amplitude pulses.
$P_d^k; 1 \leq k \leq T$	Set of positions in the code vector that contain at least k stacked unit amplitude pulses; $0 \leq P_d^k \leq L - 1$

Code	Definition
$I_{off_s}(\tilde{T}, T, L)$	<p>Total number of ways of putting T pulses into greater than \tilde{T} nonzero locations. That is,</p> $I_{off_s}(\tilde{T}, T, L) = \sum_{p=\tilde{T}+1}^T {}^{54}C_p {}^{(7-1)}C_{(p-1)} 2^p$ <p>This is the minimum offset in the code-vector space corresponding to a vector that has exactly \tilde{T} nonzero pulses</p>
$I_{off}(T_d^k, T_m^k, T_d^{k-1})$	<p>Total number of ways of putting T_m^k pulses into greater than T_d^k nonzero locations out of a maximum possible T_d^{k-1} locations.</p> <p>That is,</p> $I_{off}(T_d^k, T_m^k, T_d^{k-1}) = \sum_{p=T_d^k+1}^{T_m^k} {}^{T_m^k}C_p {}^{(T_m^k-1)}C_{(p-1)}$
$I_{pos}(P_d^k, T_d^k)$	<p>Sum of the number of ways of putting p pulses in $P_d^k(p)$, for all p such that</p> $\sum_{p=0}^{T_d^k} (P_d^k(p)) C_p$

1
2
3
4

The code-word is given by

$$C = \sum_{i=0}^{\tilde{T}-1} (S_i 2^{\tilde{T}-i}) + I_{off_s}(\tilde{T}, T, L) + \left(\sum_{k=1}^T (I_{off}(T_d^k, T_m^k, T_d^{k-1}) + I_{pos}(P_d^k, T_d^k)) D(T_m^k, T_d^k) \right) 2^{\tilde{T}} \tag{4.9.8-16}$$

5
6

Basically, given the number of locations of nonzero pulses, their signs, and the number of stacked pulses at each of the nonzero locations, the code-word in the above formula is built progressively using offsets.

1 4.9.8.4 Converting a code-word to a code-vector

2 Given a code-word, C , the code-vector, ck , is reconstructed using the following iterative procedure,
 3 where the notation $D(x,y) = {}^{(x-1)}C_{(y-1)}$.

```

4
5     Tlen = L;
6
7     for (indx=0; indx<Tlen; indx++) {
8         retvector[indx]=0;
9         signvector[indx]=1;
10    }
11
12    Nd=0;
13    do {
14        Tcode = Ioff_S(Nd, Np, Tlen);
15        Nd++;
16    } while(Tcode>code);
17    Nd--;
18    Spos = code & ((0x0001<<Nd) - 1);
19
20    Tcode = (code-Ioff_S(Nd, Np, Tlen))>>Nd;
21    pos = Tcode/ D(Np,Nd);
22    for(indx=0; indx<Nd; indx++) {
23        TNd=Nd-indx-1;
24        while(F(TNd, Nd-indx)<=pos) {
25            TNd++;
26        }
27        TNd--;
28        posvect [Nd-indx-1]=TNd;
29        retvector[TNd]++;
30        signvector[TNd]=(Spos & (0x0001<<(indx)))?-1:1;
31        pos=pos-F(TNd, Nd-indx);
32    }
33    Tcode = (code-Ioff_S(Nd, Np, Tlen))>>Nd;
34    pos = Tcode/D(Np,Nd);
35    code = Tcode - pos*D(Np,Nd);
36    Np = Np - Nd;
37    Tlen = Nd;
38    pv_offset=Tlen;
39    while(Np>0) {
40        Nd=0;
41        while(Ioff(Nd, Np, Tlen)>code) {
42            Nd++;
43        }
44

```

```

1      Tcode = (code-Ioff(Nd, Np, Tlen));
2      pos = Tcode/D(Np,Nd);
3      for(indx=0; indx<Nd; indx++) {
4          TNd=Nd-indx-1;
5          while(F(TNd, Nd-indx) <= pos) {
6              TNd++;
7          }
8          TNd--;
9          retvector[posvect[TNd+pv_offset-Tlen]]++;
10         posvect[pv_offset-indx-1]=posvect[TNd+pv_offset-Tlen];
11         pos=pos-F(TNd, Nd-indx);
12     }
13     Tcode = (code-Ioff(Nd, Np, Tlen));
14     pos = Tcode/D(Np,Nd);
15     code = Tcode - pos*D(Np,Nd);
16     Np = Np - Nd;
17     Tlen = Nd;
18 }
19 for(indx=0; indx<len; indx++) {
20     ck [indx]=retvector[indx]*signvector[indx];
21 }
22

```

23 4.9.8.5 Codebook structure, Rate 1/2

24 A 10 bit sparse codebook is used for Rate 1/2 packets. The innovation vector contains 3 nonzero pulses.
25 The 3-pulse codebook takes different structures, i.e., allows different pulse positions, depending on the nature
26 of the input signal, pitch lag, periodicity, etc. The bit-usage is reduced by allowing only certain combinations of
27 pulse-positions for the 3-pulses, based on the nature of the input signal.

28 The codebook is searched using techniques similar to that for Rate 1.

29 Case 1 ($lag \geq 95$ or ($lag > 66$, and adaptive codebook gain, $g_p > 0.3$))

30 $lag \geq 95$

31 $sign = 1$

32 $ratio = \min(\max(0.9 * (lag - 95), 0.1), 0.8)$

33 $offset = \begin{cases} 1; & lag < 100 \\ 2; & otherwise \end{cases}$

34 $lag > 66$, and adaptive codebook gain, $g_p > 0.3$

35 $sign = -1$

36 $ratio = 0.0$

37 $offset = 0$

Table 4-28 Pulse positions for half-rate CELP codebook

Pulse	Positions
Possible positions for pulse 0, p_0	1, 3, 6, 8, 10, 13, 15, 18, 20, 22, 25, 27, 30, 32, 34, 37, 39, 42, 44, 46, 49, 51
Possible positions for pulse 1, p_1	$p_0 + offset$
Possible positions for pulse 2, p_2	0, 2, 4, 7, 9, 12, 14, 16, 19, 21, 24, 26, 28, 31, 33, 36, 38, 40, 43, 45, 48, 50, 52

Numerator correlation is

$$c_k = d(p_0) + r \cdot d(p_r) + sign \cdot d(p_1) \quad (4.9.8-17)$$

$$E_k = \phi(p_0, p_0) + r \cdot (r \cdot \phi(p_1) + 2 \cdot \phi(p_0, p_1)) + \phi(p_2, p_2) + 2 \cdot sign \cdot (\phi(p_0, p_2) + r \cdot \phi(p_2, p_1)) \quad (4.9.8-18)$$

Once the best set of p_0 , p_1 , and p_2 are chosen, the best code vector is given by

$$cb(n) = \begin{cases} s(p_0); & n = p_0 \\ r \cdot s(p_1); & n = p_1 \\ s(p_2); & n = p_2 \end{cases} \quad (4.9.8-19)$$

Case 0 ($lag \leq 66$, or ($lag < 95$, and adaptive codebook gain, $g_p \leq 0.3$))

$$span = \begin{cases} 24; & g_p > 0.3 \& (lag < SFSIZE) \& (lag < 24) \\ lag; & g_p > 0.3 \& (lag < SFSIZE) \& (lag \geq 24) \\ SFSIZE & otherwise \end{cases} \quad (4.9.8-20)$$

$span$ is divided into three parts t_0 , t_1 , t_2 such that

$$t_0 = \begin{cases} \lfloor span/3 \rfloor & span \% 3 = 0 \\ \lfloor span/3 \rfloor + 1 & otherwise \end{cases} \quad (4.9.8-21)$$

$$t_1 = \begin{cases} \lfloor span/3 \rfloor + 1 & span \% 3 = 2 \\ \lfloor span/3 \rfloor & otherwise \end{cases} \quad (4.9.8-22)$$

4.9.8.5.1 Converting a Rate $\frac{1}{2}$ code-word to a code-vector

The following pseudo-code illustrates how to convert the code-vector to a code-word:

```

1   for (i=0; i<55; i++) cod[i] = 0.0;
2
3
4   if((*gain_code = Exy / Eyy) < 0) {
5       *gain_code = -(*gain_code);
6       s = -1.0;
7       index = 1;
8   } else {
9       s = 1.0;
10      index = 0;
11  }
12
13  if (flag > 0) {
14      for(i=0; i<3; i++) {
15          pos = pos_table[ix][i];
16          cod[pos] += s;
17          s = -s;
18      }
19      index <<= 9;
20      index += ix;
21  } else {
22      pos = codvec[0];
23      cod[pos] += s;
24      cod[pos+offset[1]] += s * r;
25      i0 = (pos - pos/6)/2;
26
27      pos = codvec[1];
28      cod[pos] += s*sign;
29      i1 = (pos - pos/6)/2;
30
31      index = (index <<9) + i0*23 + i1;
32  }
33
34  *indices = index;
35
36  if(flag == 2)
37      for (i = pit_lag; i < l_subfr; i++) cod[i] += cod[i -
38  pit_lag];
39
40
41

```

1 If $\text{lag} < 54$, and $\text{gp} > 0.3$, the impulse response is pitch sharpened as according to:

$$c_k(j) = \begin{cases} c_k(j) & ; 0 \leq j < \tau, \\ c_k(j) + g_p c_k(j - \tau) & ; \tau \leq j \leq 54. \end{cases}$$

5 4.9.8.6 Fixed Codebook Gain Calculation

6 The fixed codebook gain for both Rate 1 and Rate 1/2 shall be found by:

$$7 \quad g_c = \frac{\mathbf{d}^t \mathbf{c}_k}{\mathbf{c}_k^t \Phi \mathbf{c}_k}, \quad (4.9.8-26)$$

8 where all variables are previously defined.

9 4.10 Voiced encoding (full-rate PPP and quarter-rate PPP)

10 Stationary voiced frames are coded using the Prototype Pitch Period (PPP) synthesis model. In the PPP
 11 synthesis model, only one prototype pitch period waveform is extracted from approximately the end of a frame
 12 of the modified residual is quantized and sent to the decoder. The whole frame of the excitation is reconstructed
 13 at the decoder by pitch synchronous interpolation between the quantized prototype pitch period of the current
 14 frame, and the prototype pitch period of the previous frame.

15 4.10.1 Modification of the original residual

16 Generate a modified residual signal, $r(n)$, by shifting the current residual signal, $\varepsilon(n)$, to match the delay
 17 contour for the current subframe. See Section 4.9.4.7 for details on this operation.

18 4.10.2 Prototype pitch period processing

19 The Discrete Fourier Series (DFS) representation of the prototype pitch period is used in various aspects of the
 20 voiced encoder. The DFS representation for a signal $x(n)$ of length L is defined as

$$21 \quad X(k) = \frac{1}{L} \sum_{n=0}^{L-1} x(n) e^{j \frac{2\pi}{L} kn}; \quad 0 \leq k < L \quad (4.10.2-1)$$

22 As X is a complex vector, it is equivalently maintained in the speech coder as two vectors – $X.a$, the real
 23 vector, and $X.b$, the imaginary vector. Further, note that x is a real vector in the time domain. Therefore, the
 24 DFS components $X.a$, and $X.a$ are symmetric about the frequency π . Therefore, $X.a$, and $X.a$ are
 25 defined by

$$X.a(k) = \begin{cases} \frac{2}{L} \sum_{n=0}^{L-1} x(n) \cos\left(\frac{2\pi}{L} kn\right); & 1 \leq k < \left\lfloor \frac{L-1}{2} \right\rfloor \\ 0; & k = 0 \\ \frac{1}{L} \sum_{n=0}^{L-1} x(n) \cos\left(\frac{2\pi}{L} \frac{L}{2} n\right); & k = \frac{L}{2}; \text{ if } L \text{ is even} \end{cases} \quad (4.10.2-2)$$

$$X.b(k) = \begin{cases} \frac{2}{L} \sum_{n=0}^{L-1} x(n) \sin\left(\frac{2\pi}{L} kn\right); & 1 \leq k < \left\lfloor \frac{L-1}{2} \right\rfloor \\ 0; & k = 0 \\ 0; & k = \frac{L}{2}; \text{ if } L \text{ is even} \end{cases} \quad (4.10.2-3)$$

The inverse DFS of X is defined as

$$x(n) = X.a(0) + \sum_{k=1}^{\left\lfloor \frac{L}{2} \right\rfloor} X.a(k) \cos\left(\frac{2\pi}{L} nk\right) + X.b(k) \sin\left(\frac{2\pi}{L} nk\right); \quad 0 \leq n < L \quad (4.10.2-4)$$

For simplicity of notation, we will henceforth simply use the unsubscripted notations like lower-case x , and the upper-case X to refer to the time domain vectors, and the DFS representation respectively.

4.10.3 Alignment extraction between two DFS, X_1 , and X_2

We refer to the alignment between X_1 , and X_2 as the circular shift to X_2 that would maximize the correlation between the two DFS' in the perceptual weighted domain. Let X_{1p} , and X_{2p} be the pole-filtered version of X_1 , and X_2 through the LPC filter as described in Section 4.10.4.

4.10.4 Pole-filtering a DFS

Pole-filtering is represented in a generic case for a DFS X , LPC coefficients A , and output X_p by the following equation:

$$X_p.a(k) = \frac{X.a(k) \cdot \left(1 + \sum_{v=0}^9 A(v) \cos\left(\frac{2\pi}{L} kv\right)\right) + X.b(k) \cdot \left(\sum_{v=0}^9 A(v) \sin\left(\frac{2\pi}{L} kv\right)\right)}{\left(1 + \sum_{v=0}^9 A(v) \cos\left(\frac{2\pi}{L} kv\right)\right)^2 + \left(\sum_{v=0}^9 A(v) \sin\left(\frac{2\pi}{L} kv\right)\right)^2}; \quad 0 \leq k \leq \left\lfloor \frac{L}{2} \right\rfloor \quad (4.10.4-1)$$

$$Xp.b(k) = \frac{-X.a(k) \cdot \left(\sum_{v=0}^9 A(v) \sin\left(\frac{2\pi}{L} kv\right) \right) + X.b(k) \cdot \left(1 + \sum_{v=0}^9 A(v) \cos\left(\frac{2\pi}{L} kv\right) \right)}{\left(1 + \sum_{v=0}^9 A(v) \cos\left(\frac{2\pi}{L} kv\right) \right)^2 + \left(\sum_{v=0}^9 A(v) \sin\left(\frac{2\pi}{L} kv\right) \right)^2}; \quad 0 \leq k \leq \left\lfloor \frac{L}{2} \right\rfloor$$

(4.10.4-2)

Let $X1pz$, and $X2pz$ be the pole-zero filtered version of $X1$, and $X2$ obtained by zero-filtering $X1p$, and $X2p$ through A_w , the weighted LPC filter, $A_w(k) = A(k)(0.7^k)$; $0 \leq k < 9$

4.10.5 Zero-filtering a DFS

$$Xp.a(k) = X.a(k) \cdot \left(1 + \sum_{v=0}^9 A(v) \cos\left(\frac{2\pi}{L} kv\right) \right) - X.b(k) \cdot \left(\sum_{v=0}^9 A(v) \sin\left(\frac{2\pi}{L} kv\right) \right); \quad 0 \leq k \leq \left\lfloor \frac{L}{2} \right\rfloor$$

(4.10.5-1)

$$Xp.b(k) = X.a(k) \cdot \left(\sum_{v=0}^9 A(v) \sin\left(\frac{2\pi}{L} kv\right) \right) + X.b(k) \cdot \left(1 + \sum_{v=0}^9 A(v) \cos\left(\frac{2\pi}{L} kv\right) \right); \quad 0 \leq k \leq \left\lfloor \frac{L}{2} \right\rfloor$$

(4.10.5-2)

The alignment between $X1$, and $X2$ is given by

$$alignment = \arg \max_n \left(\sum_{k=0}^{\left\lfloor \frac{L}{2} \right\rfloor} \left((X1.a(k)X2.a(k) + X1.b(k)X2.b(k)) \cos\left(\frac{2\pi}{L} nk\right) + (X1.b(k)X2.a(k) - X1.a(k)X2.b(k)) \sin\left(\frac{2\pi}{L} nk\right) \right) \right) (1 - 0.01|n|);$$

$$-\max(4, L/8) \leq n \leq \max(4, L/8)$$

(4.10.5-3)

4.10.6 Applying a phase shift to a DFS

A phase shift ϕ is applied to a DFS, X , according to the following equations

$$\begin{cases} Xs.a(k) = X.a(k) \cos(k\phi) - X.b(k) \sin(k\phi) \\ Xs.b(k) = X.a(k) \sin(k\phi) + X.b(k) \cos(k\phi) \end{cases}; \quad 0 \leq k \leq \left\lfloor \frac{L}{2} \right\rfloor$$

(4.10.6-1)

1 4.10.7 Energy of a DFS, X

$$2 \quad \text{energy} = \begin{cases} (X.a(0))^2 + 0.5 \sum_{k=1}^{\lfloor \frac{L-1}{2} \rfloor + 1} ((X.a(k))^2 + (X.b(k))^2), & \text{if } L \text{ is even} \\ (X.a(0))^2 + 0.5 \sum_{k=1}^{\lfloor \frac{L-1}{2} \rfloor} ((X.a(k))^2 + (X.b(k))^2), & \text{otherwise} \end{cases}$$

3 (4.10.7-1)

4 4.10.8 Converting a DFS from Cartesian to polar representation

5 Let X_c , and X_p be the Cartesian and polar respectively.

$$6 \quad X_p.a(k) = \begin{cases} \frac{\sqrt{(X_c.a(k))^2 + (X_c.b(k))^2}}{2}; & 1 \leq k \leq \left\lfloor \frac{L-1}{2} \right\rfloor; \\ \sqrt{(X_c.a(k))^2 + (X_c.b(k))^2}; & k = \frac{L}{2}; \text{ if } L \text{ is even} \end{cases} \quad (4.10.8-1)$$

$$7 \quad X_p.b(k) = \tan^{-1} \left(\frac{X_c.b(k)}{\sqrt{(X_c.a(k))^2 + (X_c.b(k))^2}} \right); \quad \begin{cases} 1 \leq k \leq \left\lfloor \frac{L-1}{2} \right\rfloor; \text{ if } L \text{ is odd} \\ 1 \leq k \leq \frac{L}{2}; \text{ if } L \text{ is even} \end{cases}$$

8 (4.10.8-2)

9 4.10.9 Converting a DFS from polar to Cartesian representation

$$10 \quad X_c.a(k) = \begin{cases} 2X_p.a(k)\cos(X_p.b(k)); & 1 \leq k \leq \left\lfloor \frac{L-1}{2} \right\rfloor; \\ X_p.a(k)\cos(X_p.b(k)); & k = \frac{L}{2}; \text{ if } L \text{ is even} \end{cases} \quad (4.10.9-1)$$

$$11 \quad X_c.b(k) = \begin{cases} 2X_p.a(k)\sin(X_p.b(k)); & 1 \leq k \leq \left\lfloor \frac{L-1}{2} \right\rfloor; \\ X_p.a(k)\sin(X_p.b(k)); & k = \frac{L}{2}; \text{ if } L \text{ is even} \end{cases} \quad (4.10.9-2)$$

12 4.10.10 Normalizing the band energy of a DFS in polar representation

13 The average energy in a DFS between the frequencies f_1 , and f_2 is

$$en = \frac{1}{k_2 - k_1 + 1} \sum_{k=k_1}^{k_2} (X_p \cdot a(k))^2; \quad f_1 < k_1 \frac{8000}{L} \leq k \frac{8000}{L} \leq k_2 \frac{8000}{L} \leq f_2$$

(4.10.10-1)

This is used to scale the DFS between a wider frequency range, $g_1 \leq f_1$, and $g_2 \geq f_2$, such that the average energy between f_1 , and f_2 is normalized to a value en_o as shown below

$$X_{1p} \cdot a(k) = \sqrt{\frac{en_o}{en}} X_p \cdot a(k); \quad g_1 < k \frac{8000}{L} \leq g_2 \quad (4.10.10-2)$$

4.10.11 Converting the DFS amplitudes to equivalent rectangular bandwidth (ERB) amplitudes

The ERB amplitudes of a DFS (in the polar form) are obtained as

$$ERB_x(i) = \frac{\sum_k X_p \cdot a(k)}{N_i}; \quad \text{for all } k \text{ such that } erbfreq[i] \leq k \frac{8000}{L} < erbfreq[i+1]$$

(4.10.11-1)

where $erbfreq[22] = \{0.0, 92.8061, 185.6121, 278.4182, 371.2243, 464.0304, 556.8364, 649.6425, 746.4, 853.6, 972.5, 1104.0, 1251.8, 1415.8, 1599.2, 1804.6, 2035.2, 2294.9, 2588.4, 2921.2, 3300.1, 3733.7, 4001.0\}$ contains the list of 22 frequency edges of the ERB bands.

$N_j = \left\lceil \frac{erbfreq[j+1]}{8000/L} \right\rceil - \left\lceil \frac{erbfreq[j]}{8000/L} \right\rceil$ is the number of harmonics in the frequency range between $erbfreq[i]$, and $erbfreq[i+1]$

4.10.12 LPC power-spectrum

The power-spectrum of a set of LPC coefficients, A , at a set of NUMFREQ frequencies represented by $F[NUMFREQ]$ is given by

$$PowSpect[i] = \frac{1}{\left(1 + \sum_{v=0}^9 A(v) \cos\left(\frac{2\pi F[i]}{8000}\right)\right)^2 + \left(\sum_{v=0}^9 -A(v) \sin\left(\frac{2\pi F[i]}{8000}\right)\right)^2}; \quad 0 \leq i < NUMFREQ$$

(4.10.12-1)

4.10.13 Current to previous PPP energy ratio

$$res_en_ratio = \frac{currp_nq_en}{prev_ppp_en} \quad (4.10.13-1)$$

$$weighted_alignment = \arg \max_n \left(\sum_{k=0}^{\lfloor \frac{L}{2} \rfloor} \left((X1.a(k)X2.a(k) + X1.b(k)X2.b(k)) \cos\left(\frac{2\pi}{L}nk\right) + (X1.b(k)X2.a(k) - X1.a(k)X2.b(k)) \sin\left(\frac{2\pi}{L}nk\right) \right) (1 - 0.01|n|) \right);$$

$E - \max(6, 0.15 \cdot L) \leq n \leq E + \max(6, 0.15 \cdot L)$
n increases in steps of 0.25 if $L < 60$
n increases in steps of 0.5 if $L \geq 60$

(4.10.16-1)

4.10.17 Zero padding a DFS to have the same lag as another DFS

$$X1_2.a(k) = \begin{cases} X1.a(k); & 0 \leq k < \frac{L1}{2} \\ 0; & \frac{L1}{2} \leq k \leq \frac{L2}{2} \end{cases}$$

(4.10.17-1)

$$X1_2.b(k) = \begin{cases} X1.b(k); & 0 \leq k < \frac{L1}{2} \\ 0; & \frac{L1}{2} \leq k \leq \frac{L2}{2} \end{cases}$$

(4.10.17-2)

4.10.18 Band-limited correlation between two DFS

The correlation between two DFS' focused in between frequencies $f1 < f < f2$ is given by

$$corr = \sum_k \left((X1_2.a(k)X2.a(k) + X1_2.b(k)X2.b(k)) + (X1_2.b(k)X2.a(k) - X1_2.a(k)X2.b(k)) \right); \quad \text{for all } k \text{ such that } f1 \leq k \frac{8000}{L} < f2$$

(4.10.18-1)

4.10.19 Speech domain energy of a DFS

The speech domain energy in between frequencies $f1 \leq f < f2$ corresponding to a residual domain DFS, X_p , and LPC parameters A of order M, is given by

$$sp_energy = \begin{cases} \sum_k \frac{(X_p \cdot a(k))^2}{\left(\left(1 + \sum_{v=0}^{M-1} \left(A(v) \cos\left(\frac{2\pi vk}{L}\right) \right) \right)^2 + \left(\sum_{v=0}^{M-1} \left(-A(v) \sin\left(\frac{2\pi vk}{L}\right) \right) \right)^2 \right)}; & k = 0, \text{ or } (k = \lfloor L/2 \rfloor \text{ and } L \text{ is even}) \\ \sum_k \frac{2 \cdot (X_p \cdot a(k))^2}{\left(\left(1 + \sum_{v=0}^{M-1} \left(A(v) \cos\left(\frac{2\pi vk}{L}\right) \right) \right)^2 + \left(\sum_{v=0}^{M-1} \left(-A(v) \sin\left(\frac{2\pi vk}{L}\right) \right) \right)^2 \right)}; & \text{other } k \end{cases}$$

for all k such that $f1 \leq k \frac{8000}{L} < f2$

(4.10.19-1)

4.10.20 Grouping DFS harmonics into ERB slots

The representative (central) frequency of the ERB in terms of the harmonics of a DFS is the arithmetic mean of the harmonic frequencies in the ERB band given by, for $0 \leq j < 22$.

$$erbfreq(j) = \begin{cases} \frac{k \frac{8000}{L}}{N_j}; & N_j \neq 0, \text{ for all } k \text{ such that } erbfreq[j] \leq k \frac{8000}{L} < erbfreq[j+1] \\ 0; & N_j = 0 \end{cases}$$

(4.10.20-1)

where as earlier

$$N_j = \left\lfloor \frac{erbfreq[j+1]}{8000/L} \right\rfloor - \left\lfloor \frac{erbfreq[j]}{8000/L} \right\rfloor$$

is the number of harmonics in the frequency range between $erbfreq[j]$, and $erbfreq[j+1]$. Clearly, N_j can be zero for some j depending on the lag, L .

4.10.21 Zero inserting into a DFS

Interleaving the DFS coefficients with zeros is equivalent to periodically extending the time domain waveform corresponding to the DFS. This zero insertion is described below.

$$X_o \cdot a(k) = \begin{cases} X_i \cdot a\left(\frac{k}{I}\right); & k \% I = 0 \\ 0; & \text{otherwise} \end{cases}; \quad 0 \leq k \leq \left\lfloor \frac{I \cdot L}{2} \right\rfloor$$

where the lag of the input DFS is L_i , and the lag of the output DFS is $I \cdot L_i$.

4.10.22 Peak to average ratio of PPP from its DFS

The DFS X , is first converted to the time-domain signal. We compute the positive and negative peak-to-average of x as follows:

$$\max_positive = \max((x(j))^2) \quad \text{for all } j \text{ in } [0, L) \text{ such that } x(j) \geq 0 \quad (4.10.22-1)$$

$$\max_negative = \max((x(j))^2) \quad \text{for all } j \text{ in } [0, L) \text{ such that } x(j) < 0 \quad (4.10.22-2)$$

$$peaktoaverage_pos = \sqrt{\frac{\max_positive \cdot L}{\sum_{j=0}^{L-1} (x(j))^2}} \quad (4.10.22-3)$$

4.10.23 Converting ERB amplitudes to DFS amplitudes

The DFS amplitudes are reconstructed from the ERB amplitudes by linear interpolation.

$$X.a(k) = \frac{currerbQ(j) \left(k \frac{8000}{L} - erbhfreq(m-1) \right) + currerbQ(j-1) \left(erbhfreq(m) - k \frac{8000}{L} \right)}{erbhfreq(m) - erbhfreq(m-1)} \quad (4.10.23-1)$$

Using the procedure mentioned in Section 4.10.10, the lower (0 to 1104.5 Hz) and higher frequency bands (1104.5 to 4000 Hz) of the polar form of $PREV_PPP_E$ are first independently normalized using the energies $last_en_l$ (the energy between 92.0 and 1104.5), and $last_en_u$ (the energy between 1004.5 to 3300) respectively.

4.10.24 Prototype pitch period extraction

While the goal is to extract a prototype pitch period from the end of the current frame of the formant residual, it is not always as direct as to extract the last L values of the current frame. This is because if the high energy pitch spike regions happen to be very close to the ends of the final pitch period, i.e., either close to the end of the frame, or beginning of the final L samples, the last L values may not contain the main pitch spike completely. This would lead to artifacts during the synthesis. In such cases, the solution is to extract the prototype pitch period is from slightly ahead in the frame such that the main pitch spike is obtained not from the end of the frame but from the last but one pitch period of the frame.

Let $spike$ ($0 \leq spike < L$) be the location of the maximum absolute value in the last L samples of the current frame of modified residual, $r(n)$. That is,

$$spike = \arg \max_{k=0}^{L-1} (abs(r(160 - L + k))) \quad (4.10.24-1)$$

Let *range* be the number of samples that is considered too close to the end points of the last pitch period, such that,

Case 1: Spike too close to beginning of last *L* samples i.e., $spike < range$.

$$currp_nq_extracted(n) = \begin{cases} r(160 - L + n); & 0 \leq n < L + spike - range \\ r(160 - 2L + n); & L + spike - range \leq spike < L \end{cases} \quad (4.10.24-2)$$

Case 2: Spike too close to end of last *L* samples i.e., $spike \geq L - range$.

$$currp_nq_extracted(n) = \begin{cases} r(160 - L + n); & 0 \leq n < spike - range \\ \begin{cases} r(160 - 2L + n); & 160 - 2L + spike - range \geq 0 \\ r(160 - L + n); & otherwise \end{cases} & ; \quad spike - range \leq n < L \end{cases} \quad (4.10.24-3)$$

Case 3: Spike not near boundary.

$$currp_nq_extracted(n) = r(160 - L + n); \quad 0 \leq n < L \quad (4.10.24-4)$$

Since the extracted pitch period doesn't always belong to the last *L* samples of the frame, the energy of the extracted period is matched with the energy of the last *L* samples of the frame as follows:

$$currp_nq_extracted(n) = \sqrt{\frac{\sum_{m=0}^{L-1} (r(160 - L + nm))^2}{\sum_{nm=0}^{L-1} (currp_nq_extracted(nm))^2}} currp_nq_extracted(n); \quad 0 \leq n < L \quad (4.10.24-5)$$

Let *CURRP_NQ_EXTRACTED* be the Discrete Fourier Series (DFS) of the above extracted prototype pitch period.

Further, since the extracted pitch period doesn't always belong to the last *L* samples of the frame, the extracted period is circularly rotated so that it is aligned with the last *L* samples of the frame. This alignment is performed through correlation search followed by phase shifting. Let $tmp(n) = r(160 - L + n); \quad 0 \leq n < L$ be a temporary signal containing the last *L* samples of the frame, and *TMP* be the DFS of *tmp*. The alignment, α , required between *CURRP_NQ_EXTRACTED*, and *TMP* is obtained using the following generic method, and this is phase shift, α , is applied (using the method mentioned below) to *CURRP_NQ_EXTRACTED* to yield *CURRP_NQ*.

1 4.10.25 Restoring PPP memories if last frame is non-PPP or full-rate PPP

2 If the previous frame was not a PPP frame, then the previous prototype pitch period's DFS, $PREV_PPP$, is
3 computed from the last PL values of the pitch memory (excitation memory).

4 The phase offset, ph_offset_E used in the PPP synthesis is set to 0.

5 The previous prototype pitch period's energy, $prev_ppp_en$ is computed from $PREV_PPP$ using the
6 procedure in Section 4.10.7.

7 Using the procedure mentioned in Section 4.10.10, the lower (0 to 1104.5 Hz) and higher frequency bands
8 (1104.5 to 4000 Hz) of the polar form of $PREV_PPP$ are first independently normalized using the energies
9 $last_en_l$ (the energy between 92.0 and 1104.5), and $last_en_u$ (the energy between 1004.5 to 3300)
10 respectively.

11 Further, the previous frame's lower and higher band energy gains are computed as

$$12 \quad lastLgainE = \log_{10}(L \cdot last_en_l) \quad (4.10.25-1)$$

$$13 \quad lastHgainE = \log_{10}(L \cdot last_en_u) \quad (4.10.25-2)$$

14 The normalized previous PPP's DFS in the polar form is used to obtain the last frame's ERB amplitudes,
15 $lasterbE$, as described in Section 4.10.11.

16 4.10.26 Correlation between current and previous PPP

17 To determine the correlation between the current and previous PPP, $PREV_PPP$ is first aligned using a full-
18 search w.r.t $CURRP_NQ$ as described in Section 4.10.14, and rotated as mentioned in Section 4.10.6
19 (equivalently, $CURRP_NQ$ can be rotated in the opposite direction to yield $CURRP_NQ_rotated$). The
20 residual correlation, res_corr , is then calculated between 100 and 3700 Hz, as mentioned in Section 4.10.18.

21 In addition, the pole-filtered (as in Section 4.10.4) version of $PREV_PPP_E$, and
22 $CURRP_NQ_rotated$ are used to compute the speech domain energy ratio, sp_en_ratio , using a
23 procedure same as the one used to calculate res_en_ratio as in Section 4.10.13.

24 4.10.27 Open-loop coding scheme change

25 Depending on some features of the current frame that detect the suitability of PPP processing, PPP processing
26 is discontinued (we use the notation $PPP_MODE_E = 'B'$, where PPP_MODE_E represents the PPP
27 processing mode, and can take on three values 'F', 'Q', 'B' representing full-rate PPP, Quarter-rate PPP
28 processing, and Full-rate CELP processing respectively) and CELP processing is applied to code the current
29 frame. These rules/features satisfying discontinue of PPP processing are described below.

30 If $(\Delta L = L - PL) < -7$, or $(\Delta L = L - PL) > 8$

31 If the anchor operating point, $OP = 1$, or, $OP = 2$

32 If $NS_SNR < 25$, $res_en_ratio > 5$, AND $res_corr < 0.65$

33 Else if $NS_SNR \geq 25$, $res_en_ratio > 3$, AND $res_corr < 1.2$

1 Rapid ramp-down frame:

2 If the anchor operating point, $OP = 1$

3 If $NS_SNR < 25$, AND $res_en_ratio < 0.025$

4 Else if $NS_SNR \geq 25$, AND $res_en_ratio < 0.075$

5 If the anchor operating point, $OP = 2$

6 If $NS_SNR < 25$, AND $res_en_ratio < 0.025$

7 Else if $NS_SNR \geq 25$, AND $res_en_ratio < 0.075$

8 Else if $NS_SNR \geq 25$, AND $MIN(res_en_ratio, sp_en_ratio) < 0.075$,

9 AND $res_corr < 0.5$

10 Rapid ramp-up frame:

11 If the anchor operating points, $OP = 1$, or $OP = 2$

12 If $NS_SNR < 25$, AND $res_en_ratio > 14.5$

13 Else if $NS_SNR \geq 25$, AND $res_en_ratio > 7$

14 If the anchor operating point, $OP = 2$

15 If $NS_SNR \geq 25$, AND $res_corr \leq 0.0$

16 If the previous frame was quarter-rate NELP, or silence

17 4.10.28 Quarter-rate PPP quantization

18 The Excitation memory from the previous frame is extended into the current frame as described in the Section
 19 4.9.4.6. We call this signal $acb(n)$. A prototype pitch period of length L is extracted from $acb(n)$ as described
 20 in Section 4.10.24, and let ACB be the DFS of the extracted PPP from the extended excitation memory.

21 4.10.28.1 Delta delay quantization

22 The pitch lag for the PPP in QPPP processing is quantized differentially as

$$23 \quad DELTADelay = L - PL + 7 .$$

24 4.10.28.2 ERB differential amplitude quantization

25 Let $CURRP_NQ_p$ be the polar representation of the DFS of $CURRP_NQ$.

26 The speech domain energy of $CURRP_NQ_p$ is computed in two frequency bands $[0,1104.5)$, and
 27 $[1104.5,4000)$ is computed as shown in Section 4.10.19. Let these be denoted by sp_en1 , and sp_en2
 28 respectively. We obtain two speech domain log ratios corresponding to the two frequency bands as,

$$29 \quad sp_en_log_ratio1 = \frac{\log_{10}(sp_en1)}{\log_{10}(sp_en1) + \log_{10}(sp_en2)} \quad (4.10.28-1)$$

$$sp_en_log_ratio2 = \frac{\log_{10}(sp_en2)}{\log_{10}(sp_en1) + \log_{10}(sp_en2)} \quad (4.10.28-2)$$

Using the procedure mentioned in Section 4.10.10, the lower (0 to 1104.5 Hz) and higher frequency bands (1104.5 to 4000 Hz) $CURRP_NQ_p$ are first independently normalized using the energies $curr_en_l$ (the energy between 92.0 and 1104.5), and $curr_en_h$ (the energy between 1004.5 to 3300) respectively. Let the normalized DFS be $CURRP_NQ_p_norm$.

Further, the current frame's lower and higher band energy gains are computed as

$$currLgainE = \log_{10}(L \cdot curr_en_l) \quad (4.10.28-3)$$

$$currHgainE = \log_{10}(L \cdot curr_en_h) \quad (4.10.28-4)$$

The change in the lower and higher band energy gains between the current and the previous frames are given by,

$$\Delta LgainE = currLgainE - prevLgainE \quad (4.10.28-5)$$

$$\Delta HgainE = currHgainE - prevHgainE$$

$$(4.10.28-6)$$

These delta lower and higher band energy gains are vector quantized using the speech domain log ratios as weights in the MSE calculation.

$$error(j) = \begin{pmatrix} sp_en_log_ratio1 \cdot (\Delta LgainE - PowerCB[j][0]) \\ sp_en_log_ratio2 \cdot (\Delta HgainE - PowerCB[j][1]) \end{pmatrix} \quad (4.10.28-7)$$

Where $PowerCB[64][2]$ is the codebook for the delta-band-energy VQ.

The error is further conditioned as

$$error(j) = 0.8 \cdot error(j) \text{ if } \Delta LgainE > PowerCB[j][0] \text{ and } \Delta HgainE > PowerCB[j][1] \quad (4.10.28-8)$$

The best VQ codebook index is given by

$$POWER_IDX = \arg \min_j (error(j)); \quad 0 \leq j < 64 \quad (4.10.28-9)$$

1 The normalized current PPP's DFS in the polar form, $CURRP_NQ_p_norm$, is used to obtain the current
 2 frame's ERB amplitudes, $currerb$, as described in Section 4.10.11.

3 The current and previous lags are used as mentioned in Section 4.10.20 to give two sets of ERB slot
 4 representative frequencies $erbfreq_c$, and $erbfreq_p$ respectively, and $N_{j,c}$, and $N_{j,p}$ being the number
 5 of harmonics in the different ERB bands.

6 Before using it in the amplitude quantization, the empty slots in the previous frame's ERB, $lasterbE$ are
 7 populated based on whether $PL > L$, or $L > PL$ as follows

$$lasterbE(j) = \begin{cases} \left\{ \begin{array}{l} \text{lasterbE}(k); \text{ if } N_{j,p} = 0, k \text{ is the largest integer } < j, \text{ AND } N_{j,p} \neq 0 \\ \text{lasterbE}(j); \text{ if } N_{j,p} \neq 0 \end{array} \right\}; PL > L \\ \left\{ \begin{array}{l} \text{lasterbE}(k); \text{ if } N_{j,p} = 0, k \text{ is the smallest integer } > j, \text{ AND } N_{j,p} \neq 0 \\ \text{lasterbE}(j); \text{ if } N_{j,p} \neq 0 \end{array} \right\}; PL < L \end{cases}$$

$$0 \leq j < 22$$

8
 9

(4.10.28-10)

11 Next, the delta between the current and previous ERB amplitudes is computed as

$$\Delta erb(j) = currerb(j) - lasterbE(j); \quad 0 \leq j < 22 \quad (4.10.28-11)$$

13 The weighted LPC power-spectrum, $PowSpectW$, is computed using A_w , the weighted LPC
 14 filter, $A_w(k) = A(k)(0.78^k)$, $0 \leq k < 9$, using the method described in Section 4.10.12.

15 The Δerb is Vector Quantized in two splits, the first split corresponding to the ERB indices 1 to 10, and the
 16 second split corresponding to the ERB indices 11 to 19. The best indice for the first split is selected as

$$errordist1(i) = \begin{cases} (\Delta erb(i))^2; & AmpCBI[k][i-1] < -lasterbE(i) \\ (currerb(i) - AmpCBI[k][i-1])^2; & otherwise \end{cases}$$

$$AmpIDX1 = \left\{ \arg \min_k \left(\sum_{i=1}^{10} w1_i (PowSpectW(i) \cdot errordist1(i)) \right) \right.$$

where

$$w1_i = \begin{cases} 0.9; & \text{if } AmpCBI[k][i-1] < \Delta erb(i) \\ 1.0; & otherwise \end{cases}$$

i such that $N_i \neq 0$
 $0 \leq k < 64$ (4.10.28-12)

17

18 The best indices for the second split is selected as

$$\begin{aligned}
errorDist2(i) &= \begin{cases} (\Delta erb(i))^2; & AmpCB2[k][i-1] < -lasterbE(i) \\ (currerb(i) - AmpCB2[k][i-1])^2; & otherwise \end{cases} \\
AmpIDX2 &= \left\{ \arg \min_k \left(\sum_{i=1}^{19} w1_i (PowSpectW(i) \cdot errorDist2(i)) \right) \right\} \\
&\text{where} \\
w1_i &= \begin{cases} 0.9; & \text{if } AmpCBI[k][i-1] < \Delta erb(i) \\ 1.0; & otherwise \end{cases} \\
&\quad i \text{ such that } N_i \neq 0 \\
&\quad 0 \leq k < 64
\end{aligned} \tag{4.10.28-13}$$

where $AmpCBI[10][64]$, and $A_AmpCB2[9][64]$ are the codebook for the VQ for the two splits.

4.10.28.3 ERB differential amplitude dequantization

The current and previous lags are used as mentioned in Section 4.10.20 to give two sets of ERB slot representative frequencies $erbhfreq_c$, and $erbhfreq_p$ respectively, and $N_{j,c}$, and $N_{j,p}$ being the number of harmonics in the different ERB bands. Before using it in the amplitude quantization, the empty slots in the previous frame's ERB, $lasterbE$ are populated based on whether $PL > L$, or $L > PL$ as follows:

$$lasterbE(j) = \begin{cases} \left\{ \begin{array}{l} \text{lasterbE}(k); \text{ if } N_{j,p} = 0, k \text{ is the largest integer } < j, \text{ AND } N_{j,p} \neq 0 \\ \text{lasterbE}(j); \text{ if } N_{j,p} \neq 0 \end{array} \right\}; PL > L \\ \left\{ \begin{array}{l} \text{lasterbE}(k); \text{ if } N_{j,p} = 0, k \text{ is the smallest integer } > j, \text{ AND } N_{j,p} \neq 0 \\ \text{lasterbE}(j); \text{ if } N_{j,p} \neq 0 \end{array} \right\}; PL < L \end{cases} \\
0 \leq j < 22$$

(4.10.28-14)

The quantized ERB amplitudes are dequantized according to the following equation:

$$currerbQ(i) = \begin{cases} MAX(0, \text{lasterbE}(i) + AmpCB1[AmpIDX1][i-1]); & i \text{ such that } N_i \neq 0, \text{ and } 0 \leq i < 10 \\ MAX(0, \text{lasterbE}(i) + AmpCB2[AmpIDX1][i-11]); & i \text{ such that } N_i \neq 0, \text{ and } 10 \leq i < 19 \\ 0; & N_i = 0 \end{cases}$$

$$currerbQ(0) = 0.3 \cdot currerbQ(1)$$

$$currerbQ(20) = 0.3 \cdot currerbQ(19)$$

$$currerbQ(21) = 0$$

(4.10.28-15)

4.10.28.4 Evaluating the quality of quantization

The quarter-rate PPP amplitude quantization is evaluated for its performance to detect outliers of large errors, and these would be bumped up to full-rate. The following distance metric is computed after the quantization:

$$amerror = \frac{\sum_{i=1}^{10} |currerb(i) - currerbQ(i)|}{N_i}; \quad i \text{ such that } N_i \neq 0$$

(4.10.28-16)

If $amerror > 0.47$ AND $\Delta LgainE > -0.4$, quarter-rate PPP processing is abandoned and the processing is bumped up to full-rate processing.

4.10.28.5 Obtaining the dequantized current PPP DFS

The procedure in Section 4.10.23 is used to convert the quantized $currerbQ$ to quantized current frame PPP DFS, $CURRP_Q_pA$.

Using the procedure mentioned in Section 4.10.10, the lower (0 to 1104.5 Hz) and higher frequency bands (1104.5 to 4000 Hz) $CURRP_Q_pA$ are first independently normalized using the energies $currq_en_l$ (the energy of $CURRP_Q_pA$ between 92.0 and 1104.5 calculated as in Section 4.10.7), and $currq_en_u$ (the energy of $CURRP_Q_pA$ between 1004.5 to 3300 calculated as in Section 4.10.7) respectively. Let the normalized DFS be $CURRP_Q_pB$.

This normalized DFS $CURRP_Q_pB$ is converted back to ERB amplitudes as in Section 4.10.11, and backed up into $lasterbE$.

The lower and upper quantized band energy gains are given by

$$currLgainE = PowerCB[POWER_IDX][0] + prevLgainE \quad (4.10.28-17)$$

$$currHgainE = PowerCB[POWER_IDX][1] + prevHgainE \quad (4.10.28-18)$$

These are backed into $prevLgainE$, and $prevHgainE$.

Using the procedure mentioned in Section 4.10.10, the lower (0 to 1104.5 Hz) and higher frequency bands (1104.5 to 4000 Hz) of $CURRP_Q_pA$ are first independently normalized using the energies $currq_en_l$ (the energy of $CURRP_Q_pA$ between 92.0 and 1104.5 calculated as in Section 4.10.7) to $\left(10^{currLgainE}\right)/L$, and $currq_en_u$ (the energy of $CURRP_Q_pA$ between 1004.5 to 3300 calculated as in Section 4.10.7) to $\left(10^{currHgainE}\right)/L$ respectively. This gives the amplitudes of the quantized current PPP DFS $CURRP_Q_p$

4.10.28.6 Copying the phase spectrum of previous PPP DFS

In quarter-rate PPP, the phase of the current DFS is set to be equal to the phase of the previous DFS after it is extended into the current frame. That is, the phase of $CURRP_Q_p$ (which is in polar form) is obtained as follows:

$$CURRP_Q_p.b(k) = ACB_p.b(k); \quad 0 \leq k \leq \lfloor L/2 \rfloor \quad (4.10.28-19)$$

where ACB_p is the polar representation of ACB .

In addition a target DFS, $TARGET_Q_p$, whose amplitude is quantized, but which has the unquantized prototype's phases is computed as follows:

$$TARGET_Q_p.a(k) = CURRP_Q_p.a(k); \quad 0 \leq k \leq \lfloor L/2 \rfloor \quad (4.10.28-20)$$

$$TARGET_Q_p.b(k) = CURRP_NQ_p.b(k); \quad 0 \leq k \leq \lfloor L/2 \rfloor \quad (4.10.28-21)$$

The Cartesian representations of $CURRP_Q_p$, and $TARGET_Q_p$ (lets call these $CURRP_Q$, and $TARGET_Q$ respectively) are used in the fine alignment method mentioned in Section 4.10.15 to shift $TARGET_Q$ to be aligned with $CURRP_Q$.

4.10.28.7 Closed loop bump-up from QPPP to full-rate CELP coding scheme

After the above quarter-rate PPP quantization, the following features are used to determine whether the QPPP scheme is sufficient for the current frame. If not, full-rate CELP coding scheme is pursued.

- Operating point average rate
- Signal-to-noise ratio of the current frame from noise suppression
- Positive and negative peak to average of $CURRP_Q$ (quantized amplitudes, phase copy from previous PPP)
- Positive and Negative peak to average of $TARGET_Q$ (true amplitudes, true current phase)
- Energy of the unquantized current PPP
- Energy of the previous quantized PPP
- Positive and negative peak to average of $CURRP_NQ$ (quantized amplitudes, true current phase)
- LPC prediction gain
- SNR between $TARGET_Q$, and $CURRP_Q$
- $CURRP_NQ$ residual energy ratio
- $CURRP_NQ$ speech energy ratio

The basic idea is to make sure that some features of the $CURRP_NQ$, the true PPP, should not deviate too much upon amplitude quantization, and/or, the phase quantization, i.e., copying of the phase from the past PPP extended into the current frame. The tolerances for the deviation are dependent on the Operating Point Average, noise suppression SNR, and LPC prediction gain.

4.10.29 FPPP DFS amplitude vector quantization

Let $CURRP_NQ_p$ be the polar representation of the DFS of $CURRP_NQ$.

The speech domain energy of $CURRP_NQ_p$ is computed in two frequency bands $[0,1104.5)$, and $[1104.5,4000)$ is computed as shown in Section 4.10.19. Let these be denoted by sp_en1 , and sp_en2 respectively. We obtain two speech domain log ratios corresponding to the two frequency bands as,

$$sp_en_log_ratio1 = \frac{\log_{10}(sp_en1)}{\log_{10}(sp_en1) + \log_{10}(sp_en2)} \quad (4.10.29-1)$$

$$sp_en_log_ratio2 = \frac{\log_{10}(sp_en2)}{\log_{10}(sp_en1) + \log_{10}(sp_en2)} \quad (4.10.29-2)$$

Using the procedure mentioned in Section 4.10.10, the lower (0 to 1104.5 Hz) and higher frequency bands (1104.5 to 4000 Hz) $CURRP_NQ_p$ are first independently normalized using the energies $curr_en_l$ (the energy between 92.0 and 1104.5), and $curr_en_h$ (the energy between 1004.5 to 3300) respectively. Let the normalized DFS be $CURRP_NQ_p_norm$.

Further, the current frame's lower and higher band energy gains are computed as

$$currLgainE = \log_{10}(L \cdot curr_en_l) \quad (4.10.29-3)$$

$$currHgainE = \log_{10}(L \cdot curr_en_h) \quad (4.10.29-4)$$

These lower and higher band energy gains are vector quantized using the speech domain log ratios as weights in the MSE calculation.

$$error(j) = \left(\begin{array}{l} sp_en_log_ratio1 \cdot (currLgainE - A_PowerCB[j][0]) + \\ sp_en_log_ratio2 \cdot (currHgainE - A_PowerCB[j][1]) \end{array} \right) \quad (4.10.29-5)$$

Where $A_PowerCB[256][2]$ is the codebook for the delta-band-energy VQ.

The error is further conditioned as

$$error(j) = 0.8 \cdot error(j) \text{ if } currLgainE > A_PowerCB[j][0] \text{ and } currHgainE > A_PowerCB[j][1] \quad (4.10.29-6)$$

The best VQ codebook index is given by

$$POWER_IDX = \arg \min_j (error(j)); \quad 0 \leq j < 256 \quad (4.10.29-7)$$

1 The normalized current PPP's DFS in the polar form, $CURRP_NQ_p_norm$, is used to obtain the current
 2 frame's ERB amplitudes, $currerb$, as described in Section 4.10.11.

3 The current lag are used as mentioned in Section 4.10.20 to give a set of ERB slot representative
 4 frequencies $erbfreq_c$, and $N_{j,c}$, being the number of harmonics in the different ERB bands.

5 The weighted LPC power-spectrum, $PowSpectW$, is computed using A_w , the weighted LPC filter,
 6 $A_w(k) = A(k)(0.78^k)$, $0 \leq k < 9$, using the method described in Section 4.10.12.

7 The $currerb$ is Vector Quantized in three splits, the first split corresponding to the ERB indices 0 to 4, the
 8 second split corresponding to the ERB indices 5 to 9, and the third split corresponding to the ERB indices 10 to
 9 18.

10 The best indices for the first split is selected as

$$A_AmpIDX1 = \arg \min_k \left(\sum_{i=0}^4 w1_i (PowSpectW(i) \cdot (currerb(i) - A_AmpCB1[k][i])^2) \right);$$

where

$$w1_i = \begin{cases} 0.9; & \text{if } A_AmpCB1[k][i] < currerb(i) \\ 1.0; & \text{otherwise} \end{cases}$$

i such that $N_i \neq 0$

$$0 \leq k < 64$$

(4.10.29-8)

13 The best indices for the second split is selected as

$$A_AmpIDX2 = \arg \min_k \left(\sum_{i=5}^9 w2_i (PowSpectW(i) \cdot (currerb(i) - A_AmpCB2[k][i-6])^2) \right);$$

where

$$w2_i = \begin{cases} 0.9; & \text{if } A_AmpCB2[k][i] < currerb(i) \\ 1.0; & \text{otherwise} \end{cases}$$

i such that $N_i \neq 0$

$$0 \leq k < 64$$

(4.10.29-9)

16 The best indices for the 3rd split is selected as

$$A_AmpIDX3 = \arg \min_k \left(\sum_{i=10}^{18} w3_i \left(PowSpectW(i) \cdot (currerb(i) - A_AmpCB3[k][i-10])^2 \right) \right);$$

where

$$w3_i = \begin{cases} 0.9; & \text{if } A_AmpCB3[k][i] < currerb(i) \\ 1.0; & \text{otherwise} \end{cases}$$

i such that $N_i \neq 0$

$$0 \leq k < 256$$

(4.10.29-10)

where $A_AmpCB1[5][64]$, $A_AmpCB2[5][64]$ and $A_AmpCB3[9][256]$ are the codebook for the VQ for the two splits.

4.10.29.1 ERB amplitude dequantization

The quantized ERB amplitudes are dequantized according to the following equation

$$currerbQ(i) = \begin{cases} A_AmpCB1[AmpIDX1][i]; & i \text{ such that } N_i \neq 0, \text{ and } 0 \leq i < 5 \\ A_AmpCB2[AmpIDX2][i-5]; & i \text{ such that } N_i \neq 0, \text{ and } 5 \leq i < 9 \\ A_AmpCB3[AmpIDX3][i-10]; & i \text{ such that } N_i \neq 0, \text{ and } 10 \leq i < 1 \\ 0; & N_i = 0 \end{cases}$$

$$currerbQ(0) = 0.3 \cdot currerbQ(1)$$

$$currerbQ(20) = 0.3 \cdot currerbQ(19)$$

$$currerbQ(21) = 0$$

(4.10.29-11)

The procedure in Section 4.10.23 is used to convert the quantized $currerbQ$ to quantized current frame PPP DFS, $CURRP_Q_pA$.

Using the procedure mentioned in Section 4.10.10, the lower (0 to 1104.5 Hz) and higher frequency bands (1104.5 to 4000 Hz) of $CURRP_Q_pA$ are first independently normalized using the energies $currq_en_l$ (the energy of $CURRP_Q_pA$ between 92.0 and 1104.5 calculated as in Section 4.10.7) to $\left(10^{currLgainE}\right)/L$, and $currq_en_u$ (the energy of $CURRP_Q_pA$ between 1004.5 to 3300 calculated as in Section 4.10.7) to $\left(10^{currHgainE}\right)/L$ respectively. This gives the amplitudes of the quantized current PPP DFS $CURRP_Q_p$.

4.10.29.2 Phase quantization

The phases of DFS, $CURRP_Q_p$, is set to zero as follows:

$$CURRP_Q_p.b(k) = 0; \quad 0 \leq k \leq \lfloor L/2 \rfloor \quad (4.10.29-12)$$

1 A target DFS, $TARGET_Q_p$, whose amplitude is quantized, but which has the unquantized prototype's phases
 2 is computed as follows:

$$3 \quad TARGET_Q_p.a(k) = CURRP_Q_p.a(k); \quad 0 \leq k \leq \lfloor L/2 \rfloor \quad (4.10.29-13)$$

$$4 \quad TARGET_Q_p.b(k) = CURRP_NQ_p.b(k); \quad 0 \leq k \leq \lfloor L/2 \rfloor \quad (4.10.29-14)$$

5 $CURRP_Q_p$, and $TARGET_Q_p$ are converted to Cartesian representation as shown in Section 4.10.9,
 6 and then converted to the perceptually weighted domain by pole-filtering using A_w , the weighted LPC filter,
 7 $A_w(k) = A(k)(0.8^k)$, $0 \leq k < 9$. Let's identify the resulting DFS' by $CURRP_Q_s$, and $TARGET_Q_s$
 8 respectively.

9 4.10.29.2.1 Global alignment

10 The alignment between $CURRP_Q_s$, and $TARGET_Q_s$, is searched in the full-range of 0 to $[0, L)$, as shown
 11 below.

$$alignment = \arg \max_n \left(\sum_{k=0}^{\lfloor L/2 \rfloor} \left(\begin{array}{l} \left(CURRP_Q_s.a(k)TARGET_Q_s.a(k) \right) \cos\left(\frac{2\pi}{128}nk\right) \\ + CURRP_Q_s.b(k)TARGET_Q_s.b(k) \end{array} \right) \right);$$

$$12 \quad \left(\begin{array}{l} \left(CURRP_Q_s.b(k)TARGET_Q_s.a(k) \right) \sin\left(\frac{2\pi}{128}nk\right) \\ + \left(-CURRP_Q_s.a(k)TARGET_Q_s.b(k) \right) \sin\left(\frac{2\pi}{128}nk\right) \end{array} \right) \right);$$

$$13 \quad 0 \leq n < 128$$

(4.10.29-15)

14 $CURRP_Q_s$ is then shifted by the negative of this alignment as described in Section 4.10.6. This corresponds
 15 to applying an expected linear phase shift to the PPP represented by $CURRP_Q_s$ to maximally align with the
 16 target (quantized amplitude but true phase) PPP. $TARGET_Q_s$.

17 4.10.29.2.2 Band alignment

18 Since the linear phase shift is insufficient to capture the true phase of all harmonics, we compute band-focused
 19 alignments, in addition to the global alignment, in multiple bands (whose band-edges are given below).

20 F_BAND[18]={0,200,300,400,500,600,850,1000,1200,1400,1600,1850,2100,2375,2650,2950,3250,4000}
 21 ;

22 The band alignment between $CURRP_Q_s$, and $TARGET_Q_s$, is searched in the range of $[-16,16)$, for a
 23 band of frequencies $[lband, hband)$ as shown below:

$$band_alignment(j) = \frac{16}{\eta} + \arg \max_n \left(\sum_k \left(\begin{array}{l} \left(\begin{array}{l} CURRP_Q_s.a(k)TARGET_Q_s.a(k) \\ + CURRP_Q_s.b(k)TARGET_Q_s.b(k) \end{array} \right) \cos\left(\frac{2\pi}{L}n\eta k\right) \\ + \left(\begin{array}{l} CURRP_Q_s.b(k)TARGET_Q_s.a(k) \\ - CURRP_Q_s.a(k)TARGET_Q_s.b(k) \end{array} \right) \sin\left(\frac{2\pi}{L}n\eta k\right) \end{array} \right) \right);$$

$$0 \leq j < 17$$

$$-\frac{16}{\eta} \leq n < \frac{16}{\eta}; n \text{ increasing in steps of } 1$$

$$\text{all } k \in \left[0, \left\lfloor \frac{L}{2} \right\rfloor\right] \text{ such that } lband(j) \leq k \frac{8000}{L} < hband(j)$$

where, $\eta = \begin{cases} 1; & j < 3 \\ 0.5; & 3 \leq j < 17 \end{cases}$

and, $lband(j) = F_BAND[j]$

$hband(j) = F_BAND[j + 1]$

If for a given $lband$, $hband$, and L , there is no k such that $lband \leq k \frac{8000}{L} < hband$,

$band_alignment(j) = INVALID_ID;$

1
2

3 Such band alignments with INVALID_ID are not packed.

4 The band phase shift ϕ is applied to a DFS, $CURRP_Q_s$, according to the following equations

$$\begin{aligned}
CURRP_Q_s.a(k) &= \left[\begin{array}{c} CURRP_Q_s.a(k) \cos \left(-k \frac{2\pi}{L} \eta \left(-\frac{16}{\eta} + band_alignment(j) \right) \right) \\ CURRP_Q_s.b(k) \sin \left(-k \frac{2\pi}{L} \eta \left(-\frac{16}{\eta} + band_alignment(j) \right) \right) \end{array} \right] \\
CURRP_Q_s.b(k) &= \left[\begin{array}{c} CURRP_Q_s.a(k) \sin \left(-k \frac{2\pi}{L} \eta \left(-\frac{16}{\eta} + band_alignment(j) \right) \right) \\ CURRP_Q_s.b(k) \cos \left(-k \frac{2\pi}{L} \eta \left(-\frac{16}{\eta} + band_alignment(j) \right) \right) \end{array} \right] \\
0 \leq k &\leq \left\lfloor \frac{L}{2} \right\rfloor \\
0 \leq j &< 17 \\
-\frac{16}{\eta} \leq n &< \frac{16}{\eta}; n \text{ increasing in steps of } 1 \\
&\text{for every } j, \\
k \in \left[0, \left\lfloor \frac{L}{2} \right\rfloor \right] &\text{ such that } lband(j) \leq k \frac{8000}{L} < hband(j)
\end{aligned}$$

$$\text{where, } \eta = \begin{cases} 1; & j < 3 \\ 0.5; & 3 \leq j < 17 \end{cases}$$

$$\text{and, } lband(j) = F_BAND[j]$$

$$hband(j) = F_BAND[j+1]$$

1
2
3 $CURRP_Q_s$ is then zero filtered using the procedure in Section 4.10.5, and A_w , the weighted LPC filter,
4 $A_w(k) = A(k)(0.8^k)$, $0 \leq k < 9$ to obtain the quantized full-rate PPP DFS, $CURRP_Q$.

5 4.10.30 PPP synthesis

6 Now that we have the quantized current PPP DFS, $CURRP_Q$, and the previous DFS, $PREV_PPP$, we
7 generate the 160 samples of the current frame as below, adjusting the previous and current PPP for synthesis if
8 pitch double or halving.

9 The running phase-offset of the previous the previous frame's PPP is first updated if the current pitch is more
10 than the two times the previous frame's pitch lag. That is

$$11 \quad phase_offset = phase_offset / I; \quad \text{if } L / PL > 2.$$

12 Further, if $L > 2PL$, the previous frame DFS, $PREV_PPP$, is zero-inserted as described in Section 4.10.21,
13 and a flag signal, $synthesis_flag$ is set to 1. This corresponds to interpolating the time-domain signal.

14 If $PL > L$, the current frame DFS, $CURRP_Q$, is zero-inserted as described in Section 4.10.21, and the flag
15 signal, $synthesis_flag$ is set to 2.

4.10.30.1 Calculating the expected alignment shift

The expected alignment shift between the previous PPP and the current PPP is computed as

$$E_{rot} = rem\left(\left(\left[rem\left(160, \left\lfloor \frac{L+PL}{2} \right\rfloor\right)\right] + alignment_offset\right), L\right)$$

where

$$alignment_offset = \begin{cases} 2\pi \cdot PL \cdot phase_offset \cdot round\left(\frac{L}{PL}\right); & \text{if } synthesis_flag = 1 \\ 2\pi \cdot PL \cdot phase_offset; & \text{otherwise} \end{cases}$$

4.10.30.2 Computing the actual alignment shift and shifting the current PPP

The actual alignment between the previous PPP, and the current PPP is computed around E_{rot} using the weighted alignment method described in Section 4.10.16. Let the result of this alignment be $alignment_synthesis$. The current PPP, $CURRP_Q$, is then phase shifted by

$$phaseshift_synthesis = \frac{2\pi \cdot alignment_synthesis}{L} \text{ as described in Section 4.10.6.}$$

4.10.30.3 Computation of the cubic phase track for the synthesis of one frame of residual

The phase track used to synthesis the whole frame of residual from the previous and current PPP is modeled using a cubic polynomial as below

$$phase_out(n) = \begin{cases} rem(phase_offset, 2\pi) & ; n = 0 \\ ((coef[0] \cdot n + coef[1]) \cdot n + coef[2]) \cdot n + coef[3] & ; 1 \leq n < 160 - L \\ phase_out(n-1) + \frac{2\pi}{L} & ; 1 \leq n < 160 - L \end{cases}$$

where the coefficients of the cubic polynomial, $coef[4]$, are computed as below

$$coef[3] = rem(phase_offset, 2\pi)$$

$$coef[2] = \frac{2\pi}{PL}$$

$$coef[0] = \left(N_{rem} \left(2\pi \left(\frac{1}{L} - \frac{1}{PL} \right) \right) \right) - \left(2 \cdot \left(phaseshift_synthesis - phase_offset - N_{rem} \cdot \frac{2\pi}{PL} + 2\pi\zeta \right) \right)$$

where, $N_{rem} = (160 - L)$, represents the initial region of the current frame not containing the current PPP (which represents the end of the frame), and

$$\zeta = \text{round} \left(\frac{\text{phase_offset} - \text{phaseshift_synthesis} + 0.5N_{rem} 2\pi \left(\frac{1}{L} + \frac{1}{PL} \right)}{2\pi} \right)$$

$$\text{coef}[1] = \frac{2\pi \left(\frac{1}{L} + \frac{1}{PL} \right) - 3N_{rem}^2 \text{coef}[0]}{2N_{rem}}$$

4.10.30.4 Generating the whole frame of residual

Using the current, and previous PPP, and the above described cubic phase track, the whole frame of residual is synthesized as described below.

The number of intermediate Pitch periods to be synthesized is given by

$$N_{synth} = \text{round} \left(\frac{N}{\lfloor 0.5(L + PL) \rfloor} \right)$$

The PPP DFS with the shorter lag between the current and the previous PPP is first zero-padded to the larger lag as described in Section 4.10.17. Thus, $CURRP_Q$, and, $PREV_PPP$, are made to be of the same pitch lag.

$r_q(n)$, the residual of the frame is generated for $0 \leq n < 160$, inverse discrete Fourier series inverse transform calculated at n , of a phase-shifted (given by the phase-track) time varying DFS, $PPP_SYNTH(n)$ that is the interpolated version of $CURRP_Q$, and, $PREV_PPP_E$, and the phase track, computed as below.

$$PPP_SYNTH(n)a(k) = (1 - w(n))(PREV_PPP.a(k)) + w(n)(CURRP_Q.a(k)); \quad 0 \leq k \leq \lfloor L/2 \rfloor$$

$$PPP_SYNTH(n)b(k) = (1 - w(n))(PREV_PPP.b(k)) + w(n)(CURRP_Q.b(k)); \quad 0 \leq k \leq \lfloor L/2 \rfloor$$

where the time varying interpolation weight is given by

$$w(n) = \begin{cases} 1 - e^{-\left((n+1) \log \left(\frac{0.2}{L-160} \right) \right)}, & \text{if } L < 140 \\ \frac{n+1}{160}, & \text{otherwise} \end{cases}$$

4.10.31 Perceptual weighting filter update

Although there is no closed-loop search at Rate 1 and Rate $\frac{1}{4}$ PPP coding, it is still necessary to update the memory of the perceptual weighting filter with the new excitation determined in 4.6.7 for each subframe. Update the weighted synthesis filter memory by filtering the excitation vector, $rq(n)$, through the weighted

$$H_{wq}(z) = \frac{1}{A_q(z)} \left[\frac{A(\gamma_1^{-1}z)}{A(\gamma_2^{-1}z)} \right] \quad (4.9.4-3).$$

synthesis filter, $Hwq(z)$, which is given in Equation

4.11 Encoding at Rate 1/4 unvoiced for SO 68

NELP is used for Rate 1/4 unvoiced frames. A pseudo-random noise is colored using a set of filters, and scaled appropriately by gains in 10 subframes of 16 samples each to model the excitation.




Figure 4.11-1: Excitation coding for Rate 1/4 frames

4.11.1 Computation and quantization of gains

Input

Residual, $r(n)$

Quantized LSFs, $lsf_1^q(i)$

Output

Quantized excitation, $r_q(n)$

The energy E_i of the residual signal is computed for each of the 10 subframes ($0 \leq i < 10$) as

$$E_i = \frac{1}{16} \sum_{n=16i}^{16i+15} r^2(n) \tag{4.11.1-1}$$

The 10 subframe gains G_i are computed from the above energies as

$$G_i = \sqrt{E_i} \tag{4.11.1-2}$$

Two normalization factors for two splits ($0 \leq j < 2$) of the above 10 gains are determined by

$$G'[j] = \sqrt{\frac{1}{5} \sum_{i=0}^4 G_{j*5+i}^2} \quad (4.11.1-3)$$

The above two normalization factors are vector quantized using a two dimensional codebook $UVG1CB[32][2]$ to provide an index $i\hat{G}'$ as

$$i\hat{G}' = \arg \min_k \left(\sum_{j=0}^1 (\log_{10}(G'[j]) - UVG1CB[k][j])^2 \right), \quad 0 \leq k < 32 \quad (4.11.1-4)$$

The quantized normalization factors are then computed for $(0 \leq j < 2)$ using

$$\hat{G}'[j] = 10^{UVG1CB[i\hat{G}'][j]} \quad (4.11.1-5)$$

The 10 subframe gains are then normalized using the quantized normalization factors according to

$$G''[2j+i] = \frac{G[2j+i]}{\hat{G}'[j]}, \quad 0 \leq i < 5, 0 \leq j < 2 \quad (4.11.1-6)$$

The 10 normalized gains are then vector quantized using a 3-dimensional codebook $UVG2CB[2][64][5]$ to provide two indices $iG''[0]$, and $iG''[1]$ such that

$$i\hat{G}''[j] = \arg \min_k \left(\sum_{i=0}^4 (G''[2j+i] - UVG2CB[j][k][i])^2 \right); \quad 0 \leq k < 64; 0 \leq j < 2 \quad (4.11.1-7)$$

The quantized, normalized gains are then given by

$$\hat{G}''[2j+i] = UVG2CB[j][i\hat{G}''][i], \quad 0 \leq i < 5, 0 \leq j < 2 \quad (4.11.1-8)$$

The quantized gains used to scale the NELP excitation then are

$$\hat{G}[2j+i] = \hat{G}'[j] \hat{G}''[2j+i], \quad 0 \leq i < 5, 0 \leq j < 2 \quad (4.11.1-9)$$

4.11.2 Random number generation

A pseudo-random vector e_{rand} of 160 samples is generated as follows,

$$e_{rand}(n) = \begin{cases} NELPseed, & \text{where} \\ NELPseed = (521 \times NELPseed + 259) / 32768; \end{cases} \quad 0 \leq n < 160 \quad (4.11.2-1)$$

1 For Rate 1/4, the seed, $NELP_{seed}$, is initialized at the beginning of each frame to a signed 16-bit number that is
 2 derived from the bits representing the LSF.

3 4.11.3 Creation of sparse nonzero excitation

4 The above pseudo-random vector $e_{rand}(n)$ is divided into 10 subframes, and each subframe is made sparse by
 5 retaining the 4 largest absolute magnitude samples, and zeroing out the remaining 12. Each of these 10
 6 subframes of the sparse vectors is denoted by $e_{sparse}(i, n)$, $0 \leq i < 10$; $0 \leq n < 16$. These sparse vectors are then
 7 scaled by their appropriate gains to create 160 samples of a sparse, excitation signal

$$r_1(16i + n) = \sqrt{3}\hat{G}(i)e_{sparse}(i, n), \quad 0 \leq i < 10; 0 \leq n < 16 \quad (4.11.3-1)$$

9 4.11.4 Shaping the excitation

10 The above excitation $r_1(n)$ is filtered by a 12th order bandpass filter, in order to remove the low band and high
 11 components to yield the signal $r_2(n)$. This bandpass filter is given by the following transfer function

$$BP(z) = \frac{BP_{n0} + BP_{n1}z^{-1} + \dots + BP_{n12}z^{-12}}{1 + BP_{d1}z^{-1} + \dots + BP_{d12}z^{-12}} \quad (4.11.4-1)$$

13 where the coefficients BP_{ni} , and BP_{di} are given in the tables `bp1_num_coef`, and `bp1_den_coef` respectively in
 14 the C-code.

15 $r_2(n)$ is then filtered by the 10th order shaping filter $SF1(z)$ to give the signal $r_3(n)$. This shaping filter is
 16 given by the following transfer function

$$SF1(z) = \frac{SF1_{n0} + SF1_{n1}z^{-1} + \dots + SF1_{n12}z^{-10}}{1 + SF1_{d1}z^{-1} + \dots + SF1_{d12}z^{-10}} \quad (4.11.4-2)$$

18 where the coefficients $SF1_{ni}$, and $SF1_{di}$ are given in the tables `shap1_num_coef`, and `shap1_den_coef`
 19 respectively in the C-code.

20 $r_3(n)$ is then scaled according to the following equation to yield

$$r_4(n) = \left(\frac{\sqrt{\sum_{n=0}^{159} [r(n)]^2}}{\sqrt{\sum_{n=0}^{159} [r_3(n)]^2}} \right) r_3(n) \quad (4.11.4-3)$$

22 $r(n)$ and $r_4(n)$ are filtered by the 10th order lowpass filter $LP(z)$ to give $r_L(n)$ and $r_{4L}(n)$. Similarly, $r(n)$
 23 and $r_4(n)$ are filtered by the 10th order highpass filter $HP(z)$ to give $r_H(n)$ and $r_{4H}(n)$.

$$LP(z) = \frac{LP_{n0} + LP_{n1}z^{-1} + \dots + LP_{n12}z^{-10}}{1 + LP_{d1}z^{-1} + \dots + LP_{d12}z^{-10}} \quad (4.11.4-4)$$

$$HP(z) = \frac{HP_{n0} + HP_{n1}z^{-1} + \dots + HP_{n12}z^{-10}}{1 + HP_{d1}z^{-1} + \dots + HP_{d12}z^{-10}} \quad (4.11.4-5)$$

where the coefficients LP_{ni} , and LP_{di} are given in the tables `txlpf1_num_coef`, and `txlpf1_den_coef` respectively in the C-code, and the coefficients HP_{ni} , and HP_{di} are given in the tables `txhpf1_num_coef`, and `txhpf1_den_coef` respectively in the C-code.

Two factors R_L , and R_H are computed as follows

$$R_L = 10 \log 10 \left(\frac{\sum_{n=0}^{n=159} [r_L(n)]^2}{\sum_{n=0}^{n=159} [r_{4L}(n)]^2} \right) \quad (4.11.4-6)$$

and

$$R_H = 10 \log 10 \left(\frac{\sum_{n=0}^{n=159} [r_H(n)]^2}{\sum_{n=0}^{n=159} [r_{4H}(n)]^2} \right) \quad (4.11.4-7)$$

A filter index F_{idx} is computed as follows from R_L , and R_H , and sent to the decoder.

$$F_{idx} = \begin{cases} 1 & ; \quad R_L < -3 \\ 2 & ; \quad R_L \geq -3 \text{ and } R_H < -3 \\ 0 & ; \quad \textit{otherwise} \end{cases} \quad (4.11.4-8)$$

The shaping filter $SF(z)$ is determined from F_{idx} as follows

$$SF(z) = \begin{cases} SF1(z) & ; \quad F_{idx} = 0 \\ SF1(z)SF2(z) & ; \quad F_{idx} = 1 \\ SF1(z)SF3(z) & ; \quad F_{idx} = 2 \end{cases} \quad (4.11.4-9)$$

where, $SF2(z)$, $SF3(z)$ are

$$SF2(z) = \frac{SF2_{n0} + SF2_{n1}z^{-1} + \dots + SF2_{n12}z^{-10}}{1 + SF2_{d1}z^{-1} + \dots + SF2_{d12}z^{-10}} \quad (4.11.4-10)$$

$$SF3(z) = \frac{SF3_{n0} + SF3_{n1}z^{-1} + \dots + SF3_{n12}z^{-10}}{1 + SF3_{d1}z^{-1} + \dots + SF3_{d12}z^{-10}} \quad (4.11.4-11)$$

3GPP2 C.S0014-B ver 1.0

1 where the coefficients $SF2_{ni}$, $SF2_{di}$, $SF3_{ni}$, and $SF3_{di}$ are given in the tables `shape2_num_coef`,
2 `shape2_den_coef`, `shape3_num_coef`, and `shape3_den_coef` respectively in the C-code.
3 Finally, $r_3(n)$ is filtered by $SF(z)$ to provide the quantized formant residual $r_q(n)$ for the Rate 1/4 frame.

4 4.11.5 Perceptual weighting filter update

5 Although there is no closed-loop search at Rate 1/4 unvoiced coding, it is still necessary to update the memory of
6 the perceptual weighting filter with the new excitation determined in 4.6.7 for each subframe. Update the
7 weighted synthesis filter memory by filtering the excitation vector, $E(n)$, through the weighted synthesis filter,

$$H_{wq}(z) = \frac{1}{A_q(z)} \left[\frac{A(\gamma_1^{-1}z)}{A(\gamma_2^{-1}z)} \right] \quad (4.9.4-3).$$

8 $H_{wq}(z)$, which is given in Equation

10 4.12 Encoding at Rate 1/8

11 **Inputs:** The inputs to Rate 1/8 encoding are:

- 12 • The unquantized LSPs from the current and previous frames, $\Omega(m)$ and $\Omega(m-1)$
- 13 • The quantized LSPs from the previous frame, $\Omega_q(m-1)$
- 14 • The short-term prediction residual, $\varepsilon(n)$

15 **Outputs:** The outputs of Rate 1/8 encoding are:

- 16 • The quantized LSPs for the current frame, $\Omega_q(m)$
- 17 • The quantization index corresponding to these LSPs, $LSPIDX(k)$
- 18 • The vector quantized frame energy index, $FGIDX$

19 **State Variables Affected:**

- 20 • The accumulated shift counter, τ_{acc} , is set to 0
- 21 • The pointer to the last element in shifted residual, n_m , is set to 0

22 **Processing:** Rate 1/8 encoding shall comprise 4.12.1 to 4.12.10.

23 4.12.1 LSP Quantization

24 Vector quantize the unquantized LSPs, $\Omega(m)$, using the procedure found in 4.7 for Rate 1/8.

25 4.12.2 Interpolation of LSP Parameters

26 Interpolate the quantized LSPs over the three subframes, m' , in the current frame, m , as defined in 4.4.2.1.

27 4.12.3 LSP to LPC Conversion

28 Convert the quantized, interpolated LSPs, $\Omega_q(m)$, to quantized, interpolated LPC parameters, $\{a_q\}$, as
29 described in Section 4.4.2.2 for each subframe.

4.12.4 Impulse Response Computation

Calculate the unweighted impulse response, $h(n)$, of $1/A_q(z)$ to 54 terms for each subframe, where $A_q(z)$ is defined as:

$$A_q(z) = 1 - \sum_{i=1}^{10} a_q(i)z^{-i} \quad (4.12.4-1)$$

4.12.5 Calculation of the Frame Energy Gain for SO 3

The frame energy gain is defined as the ratio of the energy of the impulse response to the mean of the residual for each subframe m' :

$$\gamma(m') = \frac{E_\varepsilon(m')}{E_h(m')}, \quad (4.12.5-1)$$

where the energy of the impulse response is given by:

$$E_h(m') = \sqrt{\sum_{i=0}^{L-1} h^2(n)}, \quad (4.12.5-2)$$

and the mean $E_\varepsilon(m')$ of the residual signal $\varepsilon(n)$ is defined as:

$$E_\varepsilon(m') = \max \left\{ 1, \frac{1}{L} \sum_{i=0}^{L-1} |\varepsilon(n)| \right\}, \quad (4.12.5-3)$$

where L is the subframe size (53 for subframes 0 and 1, 54 for subframe 2), $n = 0$ is defined as the index of the first sample in the current subframe, and $\varepsilon(n)$ is the residual at the current subframe.

4.12.6 Gain Quantization for SO 3

The gain vector, $\gamma(m')$, shall be quantized to 8 bits using a vector quantizer. The quantizer will assign one index for the best three-element gain vector corresponding to $\gamma(m')$. The best vector is found by calculating the error vector, $e_g(k)$, as defined by:

$$e_g(k) = \sum_{m'=0}^2 \left(\log_{10}(\gamma(m')) - q_{\log}(m',k) \right)^2, \quad (4.12.6-1)$$

where $q_{\log}(m',k)$ is an entry in the gain quantization codebook found in Table 9-15. The best codebook index, $FGIDX$, is defined as the index, k , at which $e_g(k)$ is minimized. This codebook index, $FGIDX$, shall be used to determine a set of quantized gains $\gamma_q(m')$:

$$\gamma_q(m') = 10^{q \log(m', FGIDX)}; \quad 0 \leq m' < 3 \quad (4.12.6-2)$$

1 4.12.7 Calculation of the frame energy gain

2 The mean $E_\varepsilon(m')$ of the residual signal $\varepsilon(n)$ is defined as:

$$E_\varepsilon(m') = \max \left\{ 1, \frac{1}{L} \sum_{i=0}^{L-1} |\varepsilon(n)| \right\}, \quad (4.12.7-1)$$

3
4 where L is the subframe size (53 for subframes 0 and 1, 54 for subframe 2), n = 0 is defined as the index of the
5 first sample in the current subframe, and $\varepsilon(n)$ is the residual at the current subframe.

4.12.8 Gain quantization

The gain shall be quantized to 6 bits using a scalar quantizer. The best gain index is found by minimizing the error, eg, as defined by:

$$FGIDX = \arg \min_i \left(\log \left(\max_{m'} (E_t(m')) \right) - \left(MINLOGE + i \cdot \left(\frac{MAXLOGE - MINLOGE}{NUMQLEVELS} \right) \right) \right)$$

, (4.12.8-1)

where $0 \leq i < NUMQLEVELS$, the indices of gain quantization, and MINLOGE is 0.2, MAXLOGE is 2.6, and NUMQLEVELS is 64;

This codebook index, FGIDX, shall be used to determine a frame gain γ_q :

$$\gamma_q(m') = 10^{q \log(m', FGIDX)}; \quad 0 \leq m' < 3 \quad (4.12.8-2)$$

$$\gamma_q = 10^{MINLOGE + FGIDX \cdot \left(\frac{MAXLOGE - MINLOGE}{NUMQLEVELS} \right)} \quad (4.12.8-3)$$

And the set of 3 subframe gains are given by

$$\gamma_q(m') = \begin{cases} \frac{2}{3} \gamma_q^{last} + \frac{1}{3} \gamma_q; & m' = 0 \\ \frac{1}{3} \gamma_q^{last} + \frac{2}{3} \gamma_q; & m' = 1 \\ \gamma_q; & m' = 2 \end{cases} \quad (4.12.8-4)$$

4.12.9 Generation of Rate 1/8 Excitation

The excitation for each subframe at Rate 1/8 is generated by using a zero-mean, unit variance pseudo-Gaussian white noise sequence which is scaled by the quantized frame energy gain $\gamma_q(m')$ for each subframe m' :

$$E(n) = \gamma_q \text{ran_g}\{seed\}; \quad 0 \leq n < L, \quad (4.12.9-1)$$

where $\text{ran_g}\{seed\}$ is the unit variance pseudo-random Gaussian white noise generator (see 4.13.2) and $seed$ is a unique seed value defined at reset of the system.

4.12.10 Perceptual Weighting Filter Update

Although there is no closed-loop search at Rate 1/8, it is still necessary to update the memory of the perceptual weighting filter with the new excitation determined in 4.12.9 for each subframe. Update the weighted synthesis filter memory by filtering the excitation vector, $E(n)$, through the weighted synthesis filter, $H_{wg}(z)$, which is

$$H_{wg}(z) = \frac{1}{A_q(z)} \left[\frac{A(\gamma_1^{-1}z)}{A(\gamma_2^{-1}z)} \right] \quad (4.9.4-3).$$

given in Equation

4.13 Random Number Generation

Zero mean, unit variance gaussian pseudo-random numbers are obtained by generating uniform pseudo-random numbers and appropriately transforming them. The following two sub-sections describe the uniform pseudo-random number generator and the algorithm for effecting the uniform to gaussian transformation.

4.13.1 Uniform Pseudo-Random Number Generation Algorithm

The algorithm for generating the uniform pseudo-random numbers is initialized with a seed value, and produces a new seed value with each successive invocation, as well as producing the desired pseudo-random number. The state of the uniform random number generator is captured by the current value of the seed. Different modules making use of the random number generator should maintain their own seeds. Uniform pseudo-random numbers are generated as follows:

Inputs: The input to the uniform number generator is:

- The seed value, *seed0*

Outputs: The outputs of the uniform pseudo-random number generator are:

- The uniform pseudo-random number, *ran0*
- The modified seed value, *newseed0*

Processing: Uniform pseudo-random number generation is accomplished as described in the following pseudo-code:

```

newseed0 = seed0 ⊕ 23148373
temp = trunc(newseed0 / 127773)
newseed0 = 16807 * (newseed0 - temp * 127773) - 2836 * temp
if(newseed0 < 0)
    newseed0 = newseed0 + 2147483647
ran0 = newseed0 / 2147483647
newseed0 = seed0 ⊕ 23148373

```

4.13.2 Gaussian Pseudo-Random Number Generator

The gaussian pseudo-random number generator makes use of the uniform pseudo-random number generator described in 4.13.1. Gaussian pseudo-random numbers are generated in pairs. While the algorithm that performs the transformation from uniform to gaussian does not itself have any memory, the values produced by it are a function of the seed value, which is used in invocations of the uniform pseudo-random number generator described in 4.13.1. Consequently, it is important for each module that makes use of the random

1 number generator to maintain its own seed value. The transformation from uniform to gaussian is described as
 2 follows:

3 **Inputs:** The input to the gaussian pseudo-random number generator is

- 4 • The seed value, *seed*

5 **Outputs:** The outputs of the gaussian pseudo-random number generator are:

- 6 • The pair of gaussian pseudo-random numbers generated, *ran_g0* and *ran_g1*
- 7 • The new value of the seed, *newseed*.

8 **Processing:** Generation of gaussian pseudo-random numbers is described in the following pseudocode. Note
 9 that *ran_u0* and *ran_u1* are the uniform pseudo-random numbers produced by two different invocations of the
 10 algorithm of 4.13.1, and *newseed0* and *newseed1* are the new seed values produced by each of these respective
 11 invocations. Each invocation of the uniform pseudo-random number generator uses the current value of *seed* as
 12 its input.

```

13     do {
14         v1 = 2.0 * ran_u0 - 1.0
15         seed = newseed0
16         v2 = 2.0 * ran_u1 - 1.0
17         seed = newseed1
18         rsq = v1 * v1 + v2 * v2
19     } while (rsq >= 1.0 OR rsq == 0.0)
20     fac = (-2.0 * log(rsq) / rsq)1/2
21     ran_g0 = v1 * fac
22     ran_g1 = v2 * fac
23

```

24 4.14 Discontinuous Transmission

25 DTX implementation of EVRC-A follow the requirements in [N2]. EVRC-B has a native Discontinuous
 26 Transmission or DTX scheme. When DTX is enabled, the EVRC-B encoder doesn't transmit Rate 1/8 frame
 27 every 20 ms during VAD = 0, but only sends eighth-rate frame infrequently. At the end of a talk spurt (defined
 28 by the use of a Rate 1 or Rate 1/2 or Rate 1/4 frame), the first Rate 1/8 frame is transmitted. Subsequently, all
 29 following Rate 1/8 frames are blanked and not transmitted. If there is an appreciable change in the Rate 1/8
 30 frame indicating a significant change in the background noise characteristic, another Rate 1/8 frame is sent.
 31 This change is calculated by comparing gain of the eighth-rate frame with a running average of eighth-rate
 32 frame energies. If the change is larger than a threshold, then an eighth-rate frame is transmitted. Similarly, the
 33 LSPs of the eighth-rate frame is compared with the LSPs of the last transmitted eighth-rate frame. If the change
 34 is greater than a threshold an eighth-rate frame is transmitted, otherwise an eighth-rate frame is transmitted
 35 according to the "DTX max" parameter in [N2]. In addition to the above mentioned adaptive decision to
 36 transmit an eighth-rate frame, the DTX implementation of EVRC-B also follows the requirements in [N2]
 37 including the default values.

38 When a decision is made to transmit an eighth-rate frame, a smoothed prototype of the eighth-rate frame is
 39 transmitted rather than the Rate 1/8 frame computed according to Section 4.12. The gains and the LSPs are
 40 statistically smoothed in that, the smoothed prototype contains the gain and LSPs that have been most often
 41 chosen in the recent past.

4.15 Packet Formatting for SO 3

After encoding, the encoded speech packets shall be formatted as described in Table 4-31. For each parameter, bit index 0 corresponds to the most significant bit. The packet buffer bit index 1 indicates the bit position corresponding to the beginning of the packet buffer. Parameter notations are defined as follows:

- *LPCFLAG*: spectral change indicator,
- *LSPIDX(k)[j]*: the *j*-th bit of the *k*-th LSP codebook for the entire frame, (4 codebooks for Rate 1, 3 for Rate 1/2, and 2 for Rate 1/8).
- *DELAY[j]*: the *j*-th bit of the pitch delay estimate for the entire frame,
- *DDELAY[j]*: the *j*-th bit of the delay difference for the entire frame,
- *ACBGIDX(m')[j]*: the *j*-th bit of the adaptive codebook gain index for the *m'*-th subframe,
- *FCBSIDX(m',k)[j]*: the *j*-th bit of the *k*-th fixed codebook shape index for the *m'*-th subframe, (4 codebooks for Rate 1, 1 for Rate 1/2),
- *FCBGIDX(m')[j]*: the *j*-th bit of the fixed codebook gain index for the *m'*-th subframe,
- *FGIDX[j]*: the *j*-th bit of the frame energy gain

In the case where a Rate 1/8 packet with all bits set to '1' (null Traffic Channel data) is generated, *FGIDX*[0] is set to zero.

Table 4-31. Packet Formats

Bit Index	Rate 1 Packet Bits	Rate 1/2 Packet Bits	Rate 1/8 Packet Bits
1	<i>LPCFLAG</i>	<i>LSPIDX</i> (1)[0]	<i>LSPIDX</i> (1)[0]
2	<i>LSPIDX</i> (1)[0]	<i>LSPIDX</i> (1)[1]	<i>LSPIDX</i> (1)[1]
3	<i>LSPIDX</i> (1)[1]	<i>LSPIDX</i> (1)[2]	<i>LSPIDX</i> (1)[2]
4	<i>LSPIDX</i> (1)[2]	<i>LSPIDX</i> (1)[3]	<i>LSPIDX</i> (1)[3]
5	<i>LSPIDX</i> (1)[3]	<i>LSPIDX</i> (1)[4]	<i>LSPIDX</i> (2)[0]
6	<i>LSPIDX</i> (1)[4]	<i>LSPIDX</i> (1)[5]	<i>LSPIDX</i> (2)[1]
7	<i>LSPIDX</i> (1)[5]	<i>LSPIDX</i> (1)[6]	<i>LSPIDX</i> (2)[2]
8	<i>LSPIDX</i> (2)[0]	<i>LSPIDX</i> (2)[0]	<i>LSPIDX</i> (2)[3]
9	<i>LSPIDX</i> (2)[1]	<i>LSPIDX</i> (2)[1]	<i>FGIDX</i> [0]
10	<i>LSPIDX</i> (2)[2]	<i>LSPIDX</i> (2)[2]	<i>FGIDX</i> [1]
11	<i>LSPIDX</i> (2)[3]	<i>LSPIDX</i> (2)[3]	<i>FGIDX</i> [2]
12	<i>LSPIDX</i> (2)[4]	<i>LSPIDX</i> (2)[4]	<i>FGIDX</i> [3]
13	<i>LSPIDX</i> (2)[5]	<i>LSPIDX</i> (2)[5]	<i>FGIDX</i> [4]
14	<i>LSPIDX</i> (3)[0]	<i>LSPIDX</i> (2)[6]	<i>FGIDX</i> [5]
15	<i>LSPIDX</i> (3)[1]	<i>LSPIDX</i> (3)[0]	<i>FGIDX</i> [6]
16	<i>LSPIDX</i> (3)[2]	<i>LSPIDX</i> (3)[1]	<i>FGIDX</i> [7]
17	<i>LSPIDX</i> (3)[3]	<i>LSPIDX</i> (3)[2]	
18	<i>LSPIDX</i> (3)[4]	<i>LSPIDX</i> (3)[3]	
19	<i>LSPIDX</i> (3)[5]	<i>LSPIDX</i> (3)[4]	
20	<i>LSPIDX</i> (3)[6]	<i>LSPIDX</i> (3)[5]	
21	<i>LSPIDX</i> (3)[7]	<i>LSPIDX</i> (3)[6]	
22	<i>LSPIDX</i> (3)[8]	<i>LSPIDX</i> (3)[7]	
23	<i>LSPIDX</i> (4)[0]	<i>DELAY</i> [0]	
24	<i>LSPIDX</i> (4)[1]	<i>DELAY</i> [1]	
25	<i>LSPIDX</i> (4)[2]	<i>DELAY</i> [2]	
26	<i>LSPIDX</i> (4)[3]	<i>DELAY</i> [3]	
27	<i>LSPIDX</i> (4)[4]	<i>DELAY</i> [4]	

28	<i>LSPIDX(4)[5]</i>	<i>DELAY[5]</i>	
29	<i>LSPIDX(4)[6]</i>	<i>DELAY[6]</i>	
30	<i>DELAY[0]</i>	<i>ACBGIDX(0)[0]</i>	
31	<i>DELAY[1]</i>	<i>ACBGIDX(0)[1]</i>	
32	<i>DELAY[2]</i>	<i>ACBGIDX(0)[2]</i>	
33	<i>DELAY[3]</i>	<i>FCBSIDX(0,0)[0]</i>	
34	<i>DELAY[4]</i>	<i>FCBSIDX(0,0)[1]</i>	
35	<i>DELAY[5]</i>	<i>FCBSIDX(0,0)[2]</i>	
36	<i>DELAY[6]</i>	<i>FCBSIDX(0,0)[3]</i>	
37	<i>DDELAY[0]</i>	<i>FCBSIDX(0,0)[4]</i>	
38	<i>DDELAY[1]</i>	<i>FCBSIDX(0,0)[5]</i>	
39	<i>DDELAY[2]</i>	<i>FCBSIDX(0,0)[6]</i>	
40	<i>DDELAY[3]</i>	<i>FCBSIDX(0,0)[7]</i>	
41	<i>DDELAY[4]</i>	<i>FCBSIDX(0,0)[8]</i>	
42	<i>ACBGIDX(0)[0]</i>	<i>FCBSIDX(0,0)[9]</i>	
43	<i>ACBGIDX(0)[1]</i>	<i>FCBGIDX(0)[0]</i>	
44	<i>ACBGIDX(0)[2]</i>	<i>FCBGIDX(0)[1]</i>	
45	<i>FCBSIDX(0,0)[0]</i>	<i>FCBGIDX(0)[2]</i>	
46	<i>FCBSIDX(0,0)[1]</i>	<i>FCBGIDX(0)[3]</i>	
47	<i>FCBSIDX(0,0)[2]</i>	<i>ACBGIDX(1)[0]</i>	
48	<i>FCBSIDX(0,0)[3]</i>	<i>ACBGIDX(1)[1]</i>	
49	<i>FCBSIDX(0,0)[4]</i>	<i>ACBGIDX(1)[2]</i>	
50	<i>FCBSIDX(0,0)[5]</i>	<i>FCBSIDX(1,0)[0]</i>	
51	<i>FCBSIDX(0,0)[6]</i>	<i>FCBSIDX(1,0)[1]</i>	
52	<i>FCBSIDX(0,0)[7]</i>	<i>FCBSIDX(1,0)[2]</i>	
53	<i>FCBSIDX(0,1)[0]</i>	<i>FCBSIDX(1,0)[3]</i>	
54	<i>FCBSIDX(0,1)[1]</i>	<i>FCBSIDX(1,0)[4]</i>	
55	<i>FCBSIDX(0,1)[2]</i>	<i>FCBSIDX(1,0)[5]</i>	
56	<i>FCBSIDX(0,1)[3]</i>	<i>FCBSIDX(1,0)[6]</i>	
57	<i>FCBSIDX(0,1)[4]</i>	<i>FCBSIDX(1,0)[7]</i>	
58	<i>FCBSIDX(0,1)[5]</i>	<i>FCBSIDX(1,0)[8]</i>	
59	<i>FCBSIDX(0,1)[6]</i>	<i>FCBSIDX(1,0)[9]</i>	
60	<i>FCBSIDX(0,1)[7]</i>	<i>FCBGIDX(1)[0]</i>	
61	<i>FCBSIDX(0,2)[0]</i>	<i>FCBGIDX(1)[1]</i>	
62	<i>FCBSIDX(0,2)[1]</i>	<i>FCBGIDX(1)[2]</i>	
63	<i>FCBSIDX(0,2)[2]</i>	<i>FCBGIDX(1)[3]</i>	
64	<i>FCBSIDX(0,2)[3]</i>	<i>ACBGIDX(2)[0]</i>	
65	<i>FCBSIDX(0,2)[4]</i>	<i>ACBGIDX(2)[1]</i>	
66	<i>FCBSIDX(0,2)[5]</i>	<i>ACBGIDX(2)[2]</i>	
67	<i>FCBSIDX(0,2)[6]</i>	<i>FCBSIDX(2,0)[0]</i>	
68	<i>FCBSIDX(0,2)[7]</i>	<i>FCBSIDX(2,0)[1]</i>	
69	<i>FCBSIDX(0,3)[0]</i>	<i>FCBSIDX(2,0)[2]</i>	
70	<i>FCBSIDX(0,3)[1]</i>	<i>FCBSIDX(2,0)[3]</i>	
71	<i>FCBSIDX(0,3)[2]</i>	<i>FCBSIDX(2,0)[4]</i>	
72	<i>FCBSIDX(0,3)[3]</i>	<i>FCBSIDX(2,0)[5]</i>	
73	<i>FCBSIDX(0,3)[4]</i>	<i>FCBSIDX(2,0)[6]</i>	
74	<i>FCBSIDX(0,3)[5]</i>	<i>FCBSIDX(2,0)[7]</i>	
75	<i>FCBSIDX(0,3)[6]</i>	<i>FCBSIDX(2,0)[8]</i>	
76	<i>FCBSIDX(0,3)[7]</i>	<i>FCBSIDX(2,0)[9]</i>	
77	<i>FCBSIDX(0,3)[8]</i>	<i>FCBGIDX(2)[0]</i>	
78	<i>FCBSIDX(0,3)[9]</i>	<i>FCBGIDX(2)[1]</i>	
79	<i>FCBSIDX(0,3)[10]</i>	<i>FCBGIDX(2)[2]</i>	
80	<i>FCBGIDX(0)[0]</i>	<i>FCBGIDX(2)[3]</i>	
81	<i>FCBGIDX(0)[1]</i>		

82	<i>FCBGIDX(0)[2]</i>		
83	<i>FCBGIDX(0)[3]</i>		
84	<i>FCBGIDX(0)[4]</i>		
85	<i>ACBGIDX(1)[0]</i>		
86	<i>ACBGIDX(1)[1]</i>		
87	<i>ACBGIDX(1)[2]</i>		
88	<i>FCBSIDX(1,0)[0]</i>		
89	<i>FCBSIDX(1,0)[1]</i>		
90	<i>FCBSIDX(1,0)[2]</i>		
91	<i>FCBSIDX(1,0)[3]</i>		
92	<i>FCBSIDX(1,0)[4]</i>		
93	<i>FCBSIDX(1,0)[5]</i>		
94	<i>FCBSIDX(1,0)[6]</i>		
95	<i>FCBSIDX(1,0)[7]</i>		
96	<i>FCBSIDX(1,1)[0]</i>		
97	<i>FCBSIDX(1,1)[1]</i>		
98	<i>FCBSIDX(1,1)[2]</i>		
99	<i>FCBSIDX(1,1)[3]</i>		
100	<i>FCBSIDX(1,1)[4]</i>		
101	<i>FCBSIDX(1,1)[5]</i>		
102	<i>FCBSIDX(1,1)[6]</i>		
103	<i>FCBSIDX(1,1)[7]</i>		
104	<i>FCBSIDX(1,2)[0]</i>		
105	<i>FCBSIDX(1,2)[1]</i>		
106	<i>FCBSIDX(1,2)[2]</i>		
107	<i>FCBSIDX(1,2)[3]</i>		
108	<i>FCBSIDX(1,2)[4]</i>		
109	<i>FCBSIDX(1,2)[5]</i>		
110	<i>FCBSIDX(1,2)[6]</i>		
111	<i>FCBSIDX(1,2)[7]</i>		
112	<i>FCBSIDX(1,3)[0]</i>		
113	<i>FCBSIDX(1,3)[1]</i>		
114	<i>FCBSIDX(1,3)[2]</i>		
115	<i>FCBSIDX(1,3)[3]</i>		
116	<i>FCBSIDX(1,3)[4]</i>		
117	<i>FCBSIDX(1,3)[5]</i>		
118	<i>FCBSIDX(1,3)[6]</i>		
119	<i>FCBSIDX(1,3)[7]</i>		
120	<i>FCBSIDX(1,3)[8]</i>		
121	<i>FCBSIDX(1,3)[9]</i>		
122	<i>FCBSIDX(1,3)[10]</i>		
123	<i>FCBGIDX(1)[0]</i>		
124	<i>FCBGIDX(1)[1]</i>		
125	<i>FCBGIDX(1)[2]</i>		
126	<i>FCBGIDX(1)[3]</i>		
127	<i>FCBGIDX(1)[4]</i>		
128	<i>ACBGIDX(2)[0]</i>		
129	<i>ACBGIDX(2)[1]</i>		
130	<i>ACBGIDX(2)[2]</i>		
131	<i>FCBSIDX(2,0)[0]</i>		
132	<i>FCBSIDX(2,0)[1]</i>		
133	<i>FCBSIDX(2,0)[2]</i>		
134	<i>FCBSIDX(2,0)[3]</i>		
135	<i>FCBSIDX(2,0)[4]</i>		

136	FCBSIDX(2,0)[5]		
137	FCBSIDX(2,0)[6]		
138	FCBSIDX(2,0)[7]		
139	FCBSIDX(2,1)[0]		
140	FCBSIDX(2,1)[1]		
141	FCBSIDX(2,1)[2]		
142	FCBSIDX(2,1)[3]		
143	FCBSIDX(2,1)[4]		
144	FCBSIDX(2,1)[5]		
145	FCBSIDX(2,1)[6]		
146	FCBSIDX(2,1)[7]		
147	FCBSIDX(2,2)[0]		
148	FCBSIDX(2,2)[1]		
149	FCBSIDX(2,2)[2]		
150	FCBSIDX(2,2)[3]		
151	FCBSIDX(2,2)[4]		
152	FCBSIDX(2,2)[5]		
153	FCBSIDX(2,2)[6]		
154	FCBSIDX(2,2)[7]		
155	FCBSIDX(2,3)[0]		
156	FCBSIDX(2,3)[1]		
157	FCBSIDX(2,3)[2]		
158	FCBSIDX(2,3)[3]		
159	FCBSIDX(2,3)[4]		
160	FCBSIDX(2,3)[5]		
161	FCBSIDX(2,3)[6]		
162	FCBSIDX(2,3)[7]		
163	FCBSIDX(2,3)[8]		
164	FCBSIDX(2,3)[9]		
165	FCBSIDX(2,3)[10]		
166	FCBGIDX(2)[0]		
167	FCBGIDX(2)[1]		
168	FCBGIDX(2)[2]		
169	FCBGIDX(2)[3]		
170	FCBGIDX(2)[4]		
171	TTY Baud Rate Bit		

1 4.16 Packet Formatting for SO 68

2 **Table 4-32: Packet formatting for Full-rate CELP**

Parameter (Value)	Number of Bits	Bit index in Packet
ModeBit (0)	1	P0-P0
DelayIndex	7	P1-P7
LSP_IDX0	6	P8-P13
LSP_IDX1	6	P14-P19
LSP_IDX2	9	P20-P28
LSP_IDX3	7	P29-P35
DDELAY_IDX	5	P36-P40

ACBG_IDX_SF0	3	P41-P43
ACBG_IDX_SF1	3	P44-P46
ACBG_IDX_SF2	3	P47-P49
FCB_PULSE_IDX0_SF0	16	P50-P65
FCB_PULSE_IDX1_SF0	16	P66-P81
FCB_PULSE_IDX2_SF0	3	P82-P84
FCB_PULSE_IDX0_SF1	16	P85-P100
FCB_PULSE_IDX1_SF1	16	P101-P116
FCB_PULSE_IDX2_SF1	3	P117-P119
FCB_PULSE_IDX0_SF2	16	P120-P135
FCB_PULSE_IDX1_SF2	16	P136-P151
FCB_PULSE_IDX2_SF2	3	P152-P154
FCBG_IDX_SF0	5	P155-P159
FCBG_IDX_SF1	5	P160-P164
FCBG_IDX_SF2	5	P165-P169
RESERVED (0)	1	P170

1

2

Table 4-33: Packet formatting for Full-rate PPP

Parameter (Value)	Number of Bits	Bit index in Packet
ModeBit (1)	1	P0-P0
DelayIndex	7	P1-P7
LSP_IDX0	6	P8-P13
LSP_IDX1	6	P14-P19
LSP_IDX2	9	P20-P28
LSP_IDX3	7	P29-P35

ROTATION_IDX	7	P36-P42
AMP_IDX0	6	P43-P48
AMP_IDX1	6	P49-P54
AMP_IDX2	8	P55-62
POWER_IDX	8	P63-70
ALIGN_IDX0	5	P71-P75
ALIGN_IDX1	5	P76-P80
ALIGN_IDX2	5	P81-P85
ALIGN_IDX3	6	P86-P91
ALIGN_IDX4	6	P92-P97
ALIGN_IDX5	6	P98-P103
ALIGN_IDX6	6	P104-P109
ALIGN_IDX7	6	P110-P115
ALIGN_IDX8	6	P116-P121
ALIGN_IDX9	6	P122-P127
ALIGN_IDX10	6	P128-P133
ALIGN_IDX11	6	P134-P139
ALIGN_IDX12	6	P140-P145
ALIGN_IDX13	6	P146-P151
ALIGN_IDX14	6	P152-P157
ALIGN_IDX15	6	P158-P163
ALIGN_IDX16	6	P164-P169
RESERVED (0)	1	P170

1

2

Table 4-34: Packet formatting for Half-rate CELP

Parameter (Value)	Number of Bits	Bit index in Packet
DelayIndex	7	P0-P6
LSP_IDX0	7	P7-P13
LSP_IDX1	7	P14-P20
LSP_IDX2	8	P21-P28
ACBG_IDX_SF0	3	P29-P31

ACBG_IDX_SF1	3	P32-P34
ACBG_IDX_SF2	3	P35-P37
FCB_PULSE_IDX0_SF0	10	P38-P47
FCB_PULSE_IDX0_SF1	10	P48-P57
FCB_PULSE_IDX0_SF2	10	P58-P67
FCBG_IDX_SF0	4	P68-P71
FCBG_IDX_SF1	4	P72-P75
FCBG_IDX_SF2	4	P76-P79

1

2

Table 4-35: Packet formatting for Special Half-rate CELP

Parameter (Value)	Number of Bits	Bit index in Packet
SpecialHalfCelpFlag0(0x6E)	7	P0-P6
SpecialHalfCelpFlag1(0x00)	2	P7-P8
ModeBit (0)	1	P9-P9
LSP_IDX0	6	P10-P15
LSP_IDX1	6	P16-P21
LSP_IDX2	9	P22-P30
LSP_IDX3	7	P31-P37
ACBG_IDX_SF0	3	P38-P40
ACBG_IDX_SF1	3	P41-P43
ACBG_IDX_SF2	3	P44-P46
DelayIndex	7	P47-P53
RESERVED (all 0s)	26	P54-P79

3

4

Table 4-36: Packet formatting for Special Half-rate PPP

Parameter (Value)	Number of Bits	Bit index in Packet
SpecialHalfPPPFlag0(0x6E)	7	P0-P6
SpecialHalfPPPFlag1(0x00)	2	P7-P8

ModeBit (1)	1	P9-P9
LSP_IDX0	6	P10-P15
LSP_IDX1	6	P16-P21
LSP_IDX2	9	P22-P30
LSP_IDX3	7	P31-P37
ROTATION_IDX	7	P38-P44
AMP_IDX0	6	P45-P50
AMP_IDX1	6	P51-P56
AMP_IDX2	8	P57-64
POWER_IDX	8	P65-72
DelayIndex	7	P73-P79

1

Table 4-37: Packet formatting for Special Half-rate NELP

2

Parameter (Value)	Number of Bits	Bit index in Packet
SpecialHalfNelpFlag0(0x6E)	7	P0-P6
SpecialHalfNelpFlag1(0x01)	2	P7-P8
LSP_IDX0	8	P9-P16
LSP_IDX1	8	P17-P24
NELP_GAIN_IDX0	5	P25-P29
NELP_GAIN_IDX1	6	P30-P35
NELP_GAIN_IDX2	6	P36-P41
NELP_FILTER_ID	2	P42-P43
RESERVED (all 0s)	36	P44-P79

3

Table 4-38: Packet formatting for Quarter-rate NELP

4

Parameter (Value)	Number of Bits	Bit index in Packet
ModeBit (0)	1	P0-P0
LSP_IDX0	8	P1-P8
LSP_IDX1	8	P9-P16
NELP_GAIN_IDX0	5	P17-P21

NELP_GAIN_IDX1	6	P22-P27
NELP_GAIN_IDX2	6	P28-P33
NELP_FILTER_ID	2	P34-P35
RESERVED (0)	4	P36-P39

1

Table 4-39: Packet formatting for Quarter-rate PPP

2

Parameter (Value)	Number of Bits	Bit index in Packet
ModeBit (1)	1	P0-P0
LSP_IDX0	10	P1-P10
LSP_IDX1	6	P11-P16
DELTA_LAG_IDX	4	P17-P20
AMP_IDX0	6	P21-P26
AMP_IDX1	6	P27-P32
POWER_IDX	6	P33-P38
RESERVED (0)	1	P39-P39

3

Table 4-40: Packet formatting for Eighth-Rate

4

Parameter (Value)	Number of Bits	Bit index in Packet
LSP_IDX0	4	P1-P4
LSP_IDX1	4	P5-P8
GAIN_IDX	6	P9-P14
RESERVED0 (0)	1	P15-P15
RESERVED1 (0)	1	P16-P16
POWER_IDX	6	P33-P38
RESERVED (0)	1	P39-P39

5

4.16.1 Special Half NELP frame

6

This frame format carries the NELP frame in a half-rate packet. This packet is used in half-rate max mode.

7


4.16.2 Packet Level Signaling Interworking Function

8

Table 4-35 and Table 4-36 show special half-rate CELP and special half-rate PPP frames formats.

- 1 A packet level signaling interworking function that needs to dim a full-rate packet CELP packet to a special
- 2 half-rate CELP packet should receive a packet in the frame in the format described in Table 4-32 and convert it
- 3 to the format described in Table 4-35 by relocating some of the parameters (those that are common between
- 4 Table 4-32 and Table 4-35) and setting the SpecialHalfRateCELP flag.

- 5 A packet level signaling interworking function that needs to dim a full-rate packet PPP packet to a special half-
- 6 rate PPP packet should receive a packet in the frame in the format described in Table 4-33 and convert it to the
- 7 format described in Table 4-36 by relocating some of the parameters (those that are common between Table
- 8 4-33 and Table 4-36) and setting the SpecialHalfRateCELP flag.

1 **5 SPEECH DECODER**2
3 **Figure 4.16-1. Speech Decoder Top-Level Diagram**

4 Figure 5-1 presents a top-level view of the EVRC speech decoder for SO 3. Figure 4.2-2 presents a top-level
 5 view of the EVRC-B speech decoder for SO 68. The inputs to the decoder are the received speech packet, and
 6 a packet type indicator from the multiplex sub-layer. The frame error detection module uses the packet type
 7 indicator to determine the data rate and whether or not there was a frame error detected by the multiplex sub-layer.
 8 The decoder also applies rules to detect some channel errors not detected by the multiplex sub-layer.

9 The decoder uses the parameters contained in the received packet to re-synthesize the speech frame based on
 10 the rate decision. It uses the frame erasure flag to trigger frame error recovery logic. The raw synthesized
 11 speech is then post-filtered and output.

12 **5.1 Frame Error Detection**

13 **Inputs:** The inputs to frame error detection are:

14 The packet type supplied by the multiplex sublayer

- 15 • The delay transmission code, *DELAY*

16 **Outputs:** The outputs of frame error detection are:

- 17 • The frame erasure flag, *FER_FLAG(m)*
- 18 • The rate of operation for the decoder, *Rate*

19 **Processing:** The frame error detector shall comprise 5.1.1 and 5.1.2.

20 **Initialization:**

- 21 • The last valid rate of operation, *last_valid_rate*, is initialized to Rate 1/8
- 22 • The frame erasure flag, *FER_FLAG(m) = FALSE ; m = 0*

1 5.1.1 Received Packet Type Processing for SO 3

2 The received packet type from the multiplex sublayer (see 2.1.2) is used to generate the decoder rate of
 3 operation, *Rate*, as well as the frame erasure flag, *FER_FLAG(m)*. *FER_FLAG(m)*, is defined for each received
 4 packet type in Table 5.1.1-1.

5 **Table 5-1 Received Packet Type Decoding**

Packet Type	<i>FER_FLAG(m)</i>
Rate 1	FALSE
Rate 1/2	FALSE
Rate 1/4	TRUE
Rate 1/8	FALSE
Blank	TRUE
Insufficient frame quality (erasure)	TRUE
Rate 1/8 with all bits set to '1'	TRUE
Rate 1 with all bits set to '0'	TRUE
Rate 1/2 with all bits set to '0'	TRUE
Rate 1/4 with all bits set to '0'	TRUE
Rate 1/8 with all bits set to '0'	TRUE

6
 7 The decoder rate of operation for the current frame, *Rate*, is then defined by the pseudo-code:

```

8     if ( FER_FLAG(m) == TRUE ) {
9         if ( last_valid_rate == Rate 1/8 ) {
10            Rate = Rate 1/8
11        }
12        else {
13            Rate = Rate 1
14        }
15    }
16    if ( ( Rate == Rate 1/8 ) and ( last_valid_rate == Rate 1 ) and
17        ( FER_FLAG(m-1) == FALSE ) ) {
18        FER_FLAG(m) = TRUE
19        Rate = Rate 1
20    }
21    if ( FER_FLAG(m) == FALSE ) {
22        Rate = Rate from received packet type
23        last_valid_rate = Rate
24    }
    
```

5.1.2 Received Packet Type Processing for SO 68

The received packet type from the multiplex sublayer (see 2.1.2) is used to generate the decoder rate of operation, *Rate*, as well as the frame erasure flag, *FER_FLAG(m)*. *FER_FLAG(m)*, is defined for each received packet type in Table 5.1.1-1.

Table 5-2 Received Packet Type Decoding

Packet Type	<i>FER_FLAG(m)</i>
Rate 1	FALSE
Rate 1/2	FALSE
Rate 1/4	FALSE
Rate 1/8	FALSE
Blank with last valid received rate not equal to Rate 1/8	TRUE
Blank with last valid received rate Rate 1/8	FALSE
Insufficient frame quality (erasure)	TRUE
Rate 1/8 with all bits set to '1'	TRUE
Rate 1 with all bits set to '0'	TRUE
Rate 1/2 with all bits set to '0'	TRUE
Rate 1/4 with all bits set to '0'	TRUE
Rate 1/8 with all bits set to '0'	TRUE

The decoder rate of operation for the current frame, *Rate*, is then defined by the pseudo-code:

```

if ( FER_FLAG(m) == TRUE ) {
    if ( last_valid_rate == Rate 1/8 ) {
        Rate = Rate 1/8
    }
    else {
        Rate = Rate 1
    }
}

if ( ( Rate == Rate 1/8 ) and ( last_valid_rate == Rate 1 ) and
    ( FER_FLAG(m-1) == FALSE ) ) {
    FER_FLAG(m) = TRUE
    Rate = Rate 1
}

if ( FER_FLAG(m) == FALSE ) {
    if ( Rate == Blank ) {

```

```

1
2           Rate = last_valid_rate (also same as Rate 1/8)
3       }
4       else {
5           Rate = Rate from received packet type
6           last_valid_rate = Rate
7       }
8   }

```

9 5.1.3 Packet Sanitycheck for Badrate Detection for SO 3

10 5.1.3.1 Delay Parameter Checking

11 If *Rate* is determined to be Rate 1/2 or 1, and the delay transmission code, *DELAY*, is greater than 100, the
12 *FER_FLAG(m)* flag shall be set to TRUE.

13 5.1.3.2 Delta Delay Parameter Checking

14 If *Rate* is determined to be Rate 1, the delta delay transmission code, *DDELAY*, shall be sanity checked. The
15 last frame's delay shall be computed according to Eq. 5.2.2.-5. If the computed delay is less than *DMIN* or
16 greater than *DMAX*, then the *FER_FLAG(m)* flag shall be set to TRUE.

17 5.1.4 Packet Sanitycheck for Badrate Detection for SO 68

18 5.1.4.1 Delay parameter checking

19 If *Rate* is determined to be Rate 1/2 or 1, and the delay transmission code, *DELAY*, is greater than 100, and not
20 equal to 120 or 115, the *FER_FLAG(m)* flag shall be set to TRUE.

21 5.1.4.2 Delta delay parameter checking

22 If *Rate* is determined to be Rate 1, the delta delay transmission code, *DDELAY*, shall be sanity checked. The
23 last frame's delay shall be computed according to Equation 5.2.2-5. If the computed delay is less than *DMIN* or
24 greater than *DMAX*, then the *FER_FLAG(m)* flag shall be set to TRUE.

25 5.1.4.3 LSP checking

26 If *Rate* is determined to be Rate 1/2, decode the LSP parameters, $\Omega_q(m)$, as defined in Section 4.8, using the
27 decoded LSP indices, *LSPIDX(k)*. If $\text{MAX}(\Omega_q(0), \Omega_q(1), \Omega_q(2)) \geq \text{MIN}(\Omega_q(6), \Omega_q(7), \Omega_q(8), \Omega_q(9))$, the
28 *FER_FLAG(m)* flag shall be set to TRUE.

29 If *Rate* is determined to be Rate 1, decode the LSP parameters, $\Omega_q(m)$, as defined in Section 4.8, using the
30 decoded LSP indices, *LSPIDX(k)*. If $\text{MAX}(\Omega_q(0), \Omega_q(1)) > \text{MIN}(\Omega_q(4), \Omega_q(5), \Omega_q(6))$, the *FER_FLAG(m)*
31 flag shall be set to TRUE.

32 5.1.4.4 Unused bit checking

33 If *Rate* is determined to be Rate 1/8, and bit 15 of the received packet is 1, the *FER_FLAG(m)* flag shall be set
34 to TRUE.

1 If Rate is determined to be Rate 1/4 and frame is a NELP frame, and if any of the bits 36, 37, 38, 39 of the
2 received packet is 1, the FER_FLAG (m) flag shall be set to TRUE.

3 If Rate is determined to be Rate 1/4 and frame is a PPP frame, and if bit 39 of the received packet is 1, the
4 FER_FLAG (m) flag shall be set to TRUE.

5 5.1.4.5 Invalid filter ID

6 If Rate is determined to be Rate 1/4 and frame is a NELP frame, and the shaping filter ID is equal to 3, the
7 FER_FLAG (m) flag shall be set to TRUE.

8 5.1.4.6 Invalid transition

9 If Rate is determined to be Rate 1/4 and the frame is a PPP frame, and if the previous frame is a Rate 1/8, or a
10 Rate 1/4 NELP frame, the FER_FLAG (m) flag shall be set to TRUE.

11 If Rate is determined to be Rate 1 and the frame is a PPP frame, and if the previous frame is a Rate 1/8, or a
12 Rate 1/4 NELP frame, the FER_FLAG (m) flag shall be set to TRUE.

13

14

15 5.2 Rate 1/2 and 1 CELP Decoding for SO 3 and SO 68

16 **Inputs:** The inputs to Rate 1/2 and 1 CELP decoding are:

- 17 • The quantized LSP indices from the current frame, $LSPIDX(k)$
- 18 • The quantized LSPs from the previous frame, $\Omega_q(m-1)$
- 19 • The adaptive codebook gain index, $ACBGIDX(m')$, for each subframe, m' ,
- 20 • The fixed codebook shape indices, $FCBSIDX(m', k)$, for each subframe, m' ,
- 21 • The fixed codebook gain indices, $FCBGIDX(m', k)$, for each subframe, m' ,
- 22 • The delay transmission code, $DELAY$
- 23 • The spectral transition indicator, $LPCFLAG$, Rate 1 only
- 24 • The delay difference, $DDELAY$, Rate 1 only
- 25 • The frame erasure flag, $FER_FLAG(m)$, for the current frame, m

26 **Outputs:** The outputs from Rate 1/2 and 1 CELP decoding are:

- 27 • The post-filtered synthesized speech signal, $\hat{s}_{pf}(n)$

28 **State Variables:**

- 29 • The adaptive codebook excitation, $E(n)$

30 **Initialization:**

- 31 • The adaptive codebook excitation memory, $E(n) = 0$; $-128 \leq n < 64$
- 32 • The memory for the last valid adaptive codebook buffer, $\{E_b(n)\} = 0$; $0 \leq n < 128$
- 33 • The delay, $\tau(m) = 40$; $m = 0$

3GPP2 C.S0014-B ver 1.0

- 1 • The quantized LSPs, $\Omega_q(m,k) = 0.048k$; $1 \leq k \leq 10, m = 0$
 2 • The codebook and pitch gains for the last valid frame (see 5.2.3.5 and 5.2.3.6)
 3 $g_c(m') = g_p(m') = 0$; $0 \leq m' \leq 2$
 4 • The fader scaler variable, $\alpha_f = 1$

5 **Processing:**

6 Rate 1/2 and 1 decoding shall comprise 5.2.1 to 5.2.3

7 5.2.1 Decoding of the LSP Parameters

8 If ($FER_FLAG(m) = TRUE$), use the LSP parameters from the last frame to generate bandwidth expanded LSPs
 9 for the current frame as follows: $\Omega_q(m) = 0.875 \Omega_q(m-1) + 0.125 \Omega_{spread}$ where Ω_{spread} are the initial values of
 10 the LSPs, as defined in Section 5.2.

11 Otherwise, decode the LSP parameters, $\Omega_q(m)$, as defined in 4.7.5, using the decoded LSP indices, $LSPIDX(k)$.
 12 In the event that the decoded LSPs are not strictly ascending, $FER_FLAG(m)$ shall be set to $TRUE$, where
 13 “strictly ascending” is defined as $\Omega_q(m, i) < \Omega_q(m, i+1)$; $1 \leq i \leq 9$.

14 5.2.2 Delay Decoding and Frame Erasure Delay Contour Reconstruction

15 5.2.2.1 Delay Decoding

16 The delay parameter, $\tau(m)$, for the current frame is defined as:

$$17 \quad \tau(m) = \begin{cases} \tau(m-1) & ; FER_FLAG(m) = TRUE, \\ DELAY + 20 & ; otherwise, \end{cases} \quad (5.2.2-1)$$

18 where $DELAY$ is the pitch delay transmission code.

19 5.2.2.2 Frame Erasure Delay Contour Reconstruction for Rate 1 for SO 3

20 If ($FER_FLAG(m) = FALSE$) and ($FER_FLAG(m-1) = TRUE$) and ($Rate = Rate 1$), the delay contour shall be
 21 reconstructed (for Rate 1 operation only) by warping the last valid adaptive codebook memory buffer, $E_h(n)$,
 22 using a recovered delay contour. $E_h(n)$ is first copied to the current adaptive codebook excitation memory,
 23 $E(n)$:

$$24 \quad E(n-128) = E_h(n); \quad 0 \leq n < 128 \quad (5.2.2-2)$$

25 where $E_h(n)$ was determined in 5.2.3.9 for the last valid frame, and $E(n)$ is the adaptive codebook excitation
 26 memory.

27 5.2.2.3 Frame erasure delay contour reconstruction for Rate 1 good frame following an Erased Frame for SO
 28 68

29 If ($FER_FLAG(m) = FALSE$) and ($FER_FLAG(m-1) = TRUE$) and ($Rate = Rate 1$) and if the previous frame
 30 was neither Silence nor Rate 1/4 NELP, the delay contour shall be reconstructed (for Rate 1 operation only) by
 31 warping the last valid adaptive codebook memory buffer, $E_h(n)$, using a recovered delay contour. $E_h(n)$ is first
 32 copied to the current adaptive codebook excitation memory, $E(n)$:

$$E(n-128) = E_{iv}(n); \quad 0 \leq n < 128 \quad (5.2.2-3)$$

where $E_{iv}(n)$ was determined in Section 5.2.3.10 for the last valid frame, and $E(n)$ is the adaptive codebook excitation memory.

5.2.2.3.1 Delay Reconstruction

Calculate a delay, τ' , which corresponds to the delay of the last valid frame:

$$\tau' = \tau(m-1), \quad (5.2.2-4)$$

and recover the last frame's delay as computed in the encoder by using the delay difference:

$$\tau(m-1) = \tau(m) - DDELAY - 16, \quad (5.2.2-5)$$

where $DDELAY$ is the received delay difference transmission code, and $\tau(m)$ is the current frame delay parameter.

Limit τ' by:

$$\tau' = \begin{cases} \tau(m-1) & ; |\tau(m-1) - \tau'| > 15, \\ \tau' & ; otherwise, \end{cases} \quad (5.2.2-6)$$

$E(n)$ is then warped using τ' and $\tau(m-1)$ in 5.2.2.3.2 and 5.2.2.3.3 for each subframe $0 \leq m' < 3$.

5.2.2.3.2 Reconstruction of the Delay Contour

The reconstructed delay contour, $\tau_c(n)$, is generated as defined in 4.9.5.1 of the encoder, using a set of delay interpolations computed by:

$$\dot{d}(m', j) = \begin{cases} \tau(m-1) & ; |\tau(m-1) - \tau'| > 15, \\ \left[(1 - f(m' + j)) \tau(m-1) + f(m' + j) \tau' \right] & ; otherwise, \end{cases} \quad 0 \leq j < 3, \quad (5.2.2-7)$$

where m is the current frame, m' is the subframe index, and $m' + j$ is an index into an array of interpolator coefficients, f , defined by:

$$f = \{ 0.0, 0.3313, 0.6625, 1.0, 1.0 \}. \quad (5.2.2-8)$$

5.2.2.3.3 Warping of the Adaptive Codebook Memory

The adaptive codebook memory, $E(n)$, is then mapped to the delay contour, $\tau_c(n)$, as described in 4.9.5.2 of the encoder.

1 5.2.2.4 Frame erasure delay contour reconstruction for Rate 1 good frame following a QPPP frame which
 2 follows an Erased Frame in SO 68
 3

4 If (FER_FLAG(m) = FALSE) and (FER_FLAG(m-1) = FALSE) and (FER_FLAG(m-2) = TRUE) and (Rate =
 5 Rate 1) and if the previous frame was QPPP, the delay contour shall be reconstructed (for Rate 1 operation
 6 only) by warping the valid prior to the last valid adaptive codebook memory buffer, Elvlv(n), using a recovered
 7 delay contour. Elvlv(n) is first copied to the current adaptive codebook excitation memory, E(n):

$$E(n-128) = E_{nlv}(n); \quad 0 \leq n < 128 \quad (5.2.2-9)$$

9 where Elvlv(n) was determined in Section 5.2.3.10 for the last valid frame, and E(n) is the adaptive codebook
 10 excitation memory.

11 5.2.2.4.1 Delay reconstruction

12 Recover the prior to the last frame's delay as computed in the encoder by using the delay difference:

$$\tau'' = \tau(m-2), \quad (5.2.2-10)$$

14 and recover the prior to the last frame's delay as computed in the encoder by using the delay difference:

$$\tau(m-2) = \tau(m) - \text{DELAY} - 16 - \text{DELTADELAY}, \quad (5.2.2-11)$$

16 where DELTADDELAY is the received delay difference transmission code, and $\tau(m)$ is the current frame
 17 delay parameter.

18 E(n) is then warped using τ'' and $\tau(m-2)$ in 5.2.2.3.2 and 5.2.2.3.3 for each subframe $0 \leq m' < 3$.

19 E(n) is then further warped using $\tau(m-2)$ and $\tau(m-1)$ in 5.2.2.3.2 and 5.2.2.3.3 for each subframe $0 \leq m' < 3$
 20 to obtain an adaptive codebook buffer using a recovered delay contour.

21 5.2.2.4.2 Reconstruction of the delay contour

22 The reconstructed delay contour, $\tau_c(n)$, is generated as defined in Section 4.9.5.1 of the encoder, using a set of
 23 delay interpolations computed by:

$$\dot{d}(m', j) = \begin{cases} \tau(m-1) & ; | \tau(m-1) - \tau' | > 15, \\ (1-f(m'+j))\tau(m-1) + f(m'+j)\tau' & ; \text{otherwise}, \end{cases} \quad 0 \leq j < 3, \quad (5.2.2-12)$$

26 where m is the current frame, m' is the subframe index, and m'+j is an index into an array of interpolator
 27 coefficients, f, defined by:

$$f = \{ 0.0, 0.3313, 0.6625, 1.0, 1.0 \}. \quad (5.2.2-13)$$

1 5.2.2.4.3 Warping of the adaptive codebook memory

2 The adaptive codebook memory, $E(n)$, is then mapped to the delay contour, $\tau(n)$, as described in 4.9.5.2 of the
3 encoder. For the first subframe, m' , the mapped adaptive codebook memory is scaled by a value g given by:

$$4 \quad g = \begin{cases} \text{MIN}(g_{avg}, 0.95); & \text{for } m' = 0 \\ 0.95; & \text{otherwise} \end{cases}$$

5 where g_{avg} is the average adaptive codebook gain value.

7 5.2.2.5 Smoothing of the Decoded Delay

8 The delay of the previous frame, $\tau(m-1)$, shall be smoothed for delay interpolation in 5.2.3.4 by:

$$9 \quad \tau(m-1) = \begin{cases} \tau(m) & ; | \tau(m) - \tau(m-1) - \tau' | > 15, \\ \tau(m-1) & ; \text{otherwise,} \end{cases} \quad (5.2.2-14)$$

10 5.2.3 Rates 1/2 and 1 Subframe Decoding

11 Compute the decoded synthesized speech signal for each subframe, $0 \leq m' < 3$, as described in 5.2.3.1
12 through 5.2.3.10. The subframe size, L , is 53 for subframes 0 and 1, and 54 for subframe 2.

13 5.2.3.1 Interpolation of LSP Parameters

14 Interpolate the quantized LSPs over the three subframes, m' , in the current frame, m . The form of the
15 quantized, interpolated LSP vector is:

$$16 \quad \dot{\Omega}_q(m') = (1 - \mu_{m'})\dot{\Omega}_q(m-1) + \mu_{m'}\dot{\Omega}_q(m), \quad (5.2.3-1)$$

17 where the subframe interpolator constants are defined as $\mu = \{ 0.1667, 0.5, 0.8333 \}$.

18 5.2.3.2 LSP to LPC Conversion

19 Convert the quantized, interpolated LSPs, $\dot{\Omega}_q(m)$, to quantized, interpolated LPC parameters, $\left\{ \dot{a}_q \right\}$, as
20 described in 4.4.2.2 for each subframe.

21 5.2.3.3 Bandwidth Expansion

22 If the decoded $LPCFLAG$ transmission code = $TRUE$, and $(FER_FLAG(m-1) = TRUE)$, the interpolated LPC
23 parameters, $\left\{ \dot{a}_q \right\}$, shall be bandwidth expanded using:

$$24 \quad \dot{a}_q(k) = (0.75)^K \dot{a}_q(k); \quad 1 \leq k < 10. \quad (5.2.3-2)$$

1 5.2.3.4 Interpolated Delay Estimate Calculation.

2 Calculate the set of interpolated delay estimates, $d(m', j)$, as in 4.9.4.5 of the encoder. If ($FER_FLAG(m) =$
 3 $TRUE$), and the average adaptive codebook gain (see 5.2.3.5) for the last valid frame, ($g_{pavg} < 0.3$), the
 4 interpolated delay estimates are defined as:

$$5 \quad d(m', j) = d_{md}(m' + j); \quad 0 \leq j < 3 \quad (5.2.3-3)$$

6 where $d_{md}(k)$ is the k^{th} element of:

$$7 \quad d_{md} = \{55.0, 80.0, 39.0, 71.0, 33.0\}, \quad (5.2.3-4)$$

8 5.2.3.5 Calculation of the Adaptive Codebook Contribution

9 The average adaptive codebook gain, g_{pavg} is computed by:

10 5.2.3.5.1 SO 3

$$11 \quad g_{pavg} = \begin{cases} g_{pavg}(m-1) & ; FER_FLAG(m) = TRUE \text{ and } FER_FLAG(m-1) = FALSE, \\ 0.75g_{pavg}(m-1) & ; FER_FLAG(m) = TRUE \text{ and } FER_FLAG(m-1) = TRUE, \\ \frac{1}{3} \sum_{i=0}^2 g_p(i) & ; FER_FLAG(m) = FALSE, \end{cases} \quad (5.2.3-5)$$

12 5.2.3.5.2 SO 68

$$13 \quad g_{pavg} = \begin{cases} g_{pavg}(m-1) & ; FER_FLAG(m) = TRUE \text{ and } FER_FLAG(m-1) = FALSE \\ 0.75g_{pavg}(m-1) & ; FER_FLAG(m) = TRUE \text{ and } FER_FLAG(m-1) = TRUE \\ \frac{g_p(0) + 2g_p(1) + 3g_p(2)}{6} & ; FER_FLAG(m) = FALSE \end{cases}$$

14 where $g_{pcb}(k)$ is an entry in the adaptive codebook gain quantization Table 4-23, and $ACBGIDX(m')$ is the
 15 decoded adaptive codebook gain index.

16 The adaptive codebook gain, $g_p(m')$, shall be defined as:

$$17 \quad g_p(m') = \begin{cases} g_{pavg}(m) & ; FER_FLAG(m) = TRUE, \\ g_{pcb}(ACBGIDX(m')) & ; FER_FLAG(m) = FALSE, \end{cases} \quad (5.2.3-6)$$

18 For SO 68, if the previous frame was erased, and was processed as a silence or a NELP frame, then the current
 19 frame adaptive codebook gain, $g_p(m')$ is set to zero.

20 Calculate the adaptive codebook excitation, $E(n)$, as described in 4.9.5 of the encoder.

1 5.2.3.6 Calculation of the Fixed Codebook Gain

2 The fixed codebook gain, $g_c(m')$, is defined as:

$$3 \quad g_c(m') = \begin{cases} g_{cavg} & ; FER_FLAG(m) = TRUE , \\ g_{ccb}(FCBGIDX(m')) & ; otherwise , \end{cases} \quad (5.2.3-7)$$

4 where the average fixed codebook gain, g_{cavg} , is defined by:

$$5 \quad g_{cavg} = \frac{1}{3} \sum_{i=0}^2 g_c(i) , \quad (5.2.3-8)$$

6 calculated over $g_c(i)$ for the last valid frame; $g_{ccb}(k)$ is an entry in the fixed codebook gain quantization Table
7 9-12, and $FCBGIDX(m')$ is the fixed codebook gain index.

8 5.2.3.7 Computing of the Reconstructed ACELP Fixed Codebook Excitation for SO 3

9 If $(FER_FLAG(m) = TRUE)$, the ACELP contribution is $c(n) = 0$; $0 \leq n \leq 54$, otherwise generate the fixed
10 codebook contribution as follows:

11 For Rate 1 frames, the position of the two-single-pulse tracks, q , is determined by using $FCBSIDX(m',3)[9,10]$
12 as given in Table 4-25. The remaining three tracks correspond to double-pulse tracks.

13 The single and double-pulse track positions in the decimated domain, for $0 \leq i \leq 3$, are determined by:

$$14 \quad \lambda_0 = \left\lfloor \frac{FCBSIDX(m',i)[0,\dots,6]}{11} \right\rfloor , \quad (5.2.3-9)$$

$$15 \quad \lambda_1 = FCBSIDX(m',i)[0,\dots,6] - 11\lambda_0 . \quad (5.2.3-10)$$

16 The sign of the three double-pulse tracks is determined by using the relationship between λ_0 and λ_1 as well as
17 $FCBSIDX(m', i) [7]$ for $i = 0, 1, 2$. If $\lambda_0 < \lambda_1$, then the two pulses have the same sign, as specified by
18 $FCBSIDX(m', i) [7]$. If $\lambda_0 > \lambda_1$, then the two pulses have different signs, and $FCBSIDX(m', i) [7]$ specifies the
19 sign of the pulse at position λ_0 as described in 4.9.7.3. The sign of the two single-pulse tracks is given by the
20 codeword $FCBSIDX(m', 3) [7]$ and $FCBSIDX(m', 3) [8]$, accordingly.

21 Next, referring to Equations 4.9.7.3-1 and 4.9.7.3-2 and Table 4-24 and Table 4-25, the pulse positions in the
22 decimated domain shall be converted to the undecimated domain.

23 For Rate 1/2, $FCBSIDX(m', 0) [9]$ indicates the sign of the first and the third pulse track, and the opposite sign
24 of the 2nd pulse track, and $FCBSIDX(m', 0) [0,\dots,8]$ indicates the positions of three pulses in the three tracks
25 accordingly, as given in the Table 4-26.

26 The received algebraic codebook index is used to extract the positions and amplitudes (signs) of the excitation
27 pulses and to construct the algebraic codevector, c , according to Equation 4.9.7.1-1. If the pitch delay, τ , is less
28 than the subframe size 55, the pitch sharpening processing shall be applied which modifies $c(n)$ by
29 $c(n) = c(n) + g_p c(n-\tau)$, where g_p is the decoded pitch gain bounded by [0.2, 0.9].

1 5.2.3.8 Computing of the reconstructed fixed codebook excitation in SO 68

2 If ($FER_FLAG(m) = TRUE$), the FACTORIAL CODEBOOK contribution is $c(n) = 0$; $0 \leq n \leq 54$, otherwise
 3 generate the fixed codebook contribution as follows:

4 For Rate 1 frames, the Fixed codebook codeword is converted to the fixed codebook vector, $c(n)$ as described
 5 in Section 4.9.4.11.

6 For Rate 1/2, the Fixed codebook codeword is converted to the fixed codebook vector, $c(n)$ as described in
 7 Section 4.9.4.11.

8 If the pitch delay, τ , is less than the subframe size 55, the pitch sharpening processing shall be applied which
 9 modifies $c(n)$ by $c(n)=c(n)+gPc(n-\tau)$, where gP is the decoded pitch gain bounded by $[0.2, 0.9]$.

10

11 5.2.3.9 Decoder Total Excitation Generation

12 Add the fixed and adaptive codebook contributions to obtain the total excitation, $E_T(n)$, for the current frame as
 13 defined by:

$$14 \quad E_T(n) = \begin{cases} g_p E(n); & FER_FLAG(m) = TRUE, \\ g_p E(n) + g_c c(n); & otherwise, \end{cases} ; 0 \leq n < L. \quad (5.2.3-11)$$

15 5.2.3.10 Adaptive Codebook Memory Update

16 Update the adaptive codebook excitation memory with the combined excitation for the current subframe, $E_T(n)$,
 17 excluding any random excitations added in 5.2.3.10:

$$18 \quad E_T(n) = \begin{cases} E(n+L); & -128 \leq n < -L, \\ E_T(n+L); & -L \leq n < 0. \end{cases} \quad (5.2.3-12)$$

19 If ($FER_FLAG(m) = FALSE$), and the current subframe, $m' = 2$, update the last valid excitation memory buffer,
 20 $E_{iv}(n)$ with the adaptive codebook memory:

$$21 \quad E_{iv}(n) = E(n-128); \quad 0 \leq n < 128. \quad (5.2.3-13)$$

22 5.2.3.11 Additional Excitation Frame Processing

23 A fade scaling variable, α_f , shall be calculated every subframe as defined by:

$$24 \quad \alpha_f = \begin{cases} \alpha_f - 0.05; & FER_FLAG(m) = TRUE, \\ \alpha_f + 0.2; & otherwise, \end{cases} \quad (5.2.3-14)$$

25 where α_f is bounded by $0 \leq \alpha_f \leq 1$, and is used to scale the combined excitation:

$$26 \quad E_T(n) = \alpha_f E_T(n); \quad 0 \leq n < L. \quad (5.2.3-15)$$

1 If ($FER_FLAG(m) = TRUE$), or if the frame is a special packet-level signaling half-rate CELP frame for SO 68,
 2 and the average adaptive codebook gain, ($g_{avg} < 0.4$), a random fixed codebook excitation is added to the
 3 combined excitation:

$$4 \quad E_T(n) = E_T(n) + 0.1g_{avg} \text{ran_g}\{seed\}; \quad 0 \leq n < L, \quad (5.2.3-16)$$

5 where g_{avg} is calculated in 5.2.3.6 for the last valid frame, and $\text{ran_g}\{seed\}$ is a unit variance pseudo-random
 6 Gaussian white noise sequence (see 4.7.2).

7 5.2.3.12 Frame expansion or compression in CELP frames in SO 68

8 To interface to dynamic jitter buffer mechanisms used in Packet Switched networks, CELP decoder In SO 68
 9 can output more than or less than 160 samples. When it is needed to output less than 160 samples, CELP
 10 decoder generates 160-DELAY samples of total excitation as described below.

$$11 \quad E_T(n) = \begin{cases} \frac{(merge_stop - n)}{merge_stop} E_T(n) + \frac{n}{merge_stop} E_T(n + merge_end); & 0 \leq n < merge_stop \\ E_T(n + merge_end); & merge_stop \leq n < 160 - merge_end \end{cases}$$

12 where,

13 $merge_end = DELAY$, and

$$14 \quad merge_stop = \begin{cases} merge_end; & merge_end \leq 80 \\ 160 - merge_end; & merge_end > 80 \end{cases}$$

15 When more than 160 samples are needed, CELP generates 160+DELAY samples of total excitation as
 16 described below.

$$17 \quad E_T(n) = \begin{cases} E_T(n); & 0 \leq n < merge_end \\ \frac{(merge_stop - n)}{merge_stop} E_T(n) + \frac{n}{merge_stop} E_T(n - merge_end); & merge_end \leq n < merge_end + merge_ \\ E_T(n - merge_end); & merge_end + merge_stop \leq n < 160 + merge_end \end{cases}$$

18 where,

19 $merge_end = DELAY$, and

$$20 \quad merge_stop = \begin{cases} merge_end; & merge_end \leq 80 \\ 160 - merge_end; & merge_end > 80 \end{cases}$$

21

22 5.2.3.13 PPP smoothing of CELP frame after erasure in SO 68

23

24 In order to smooth some phase discontinuities between a past erasure frame and a good CELP frame, PPP
 25 synthesis is employed to smooth such a transition.

26 Using a PPP DFS, $CURRP_Q$, obtained from the last L (pitch lag of current frame) values of the current
 27 constructed total excitation, and the previous DFS, $PREV_PPP$, obtained from the last pitch lag (of previous

1 frame) of samples from excitation of the previous frame we generate the 160 samples of the current frame
 2 excitation, ET(m), similar to the method described in Section 4.10.30.4.

3 The above mentioned PPP smoothing is disabled if there is a significant change (either increase or decrease)
 4 between the energies of CURRP_Q, and PREV_PPP referred to in this section.

5 5.2.3.14 Synthesis of the decoder output signal

6 Filter the combined excitation, ET(m), through the synthesis filter using the interpolated LPCs generated in
 7 Section 5.2.3.2, creating the synthesized speech signal, $\hat{s}(n)$. The synthesis filter for the decoder, Hq(z), is
 8 defined by:

$$H_q(z) = \frac{1}{A_q(z)} = \frac{1}{1 - \sum_{k=1}^{10} a_q(k)z^{-k}} \quad (5.2.3-17)$$

10 The signal, $\hat{s}(n)$, shall be post-filtered according to Section 5.7, producing the post-filtered synthesized speech
 11 signal, $\hat{s}_{pf}(n)$.

13 5.2.3.15 Synthesis of the Decoder Output Signal

14 Filter the combined excitation, E7(m), through the synthesis filter using the interpolated LPCs generated in
 15 5.2.3.2, creating the synthesized speech signal, $\hat{s}(n)$. The synthesis filter for the decoder, Hq(z), is defined by:

$$H_q(z) = \frac{1}{A_q(z)} = \frac{1}{1 - \sum_{k=1}^{10} a_q(k)z^{-k}} \quad (5.2.3-18)$$

17 The signal, $\hat{s}(n)$, shall be post-filtered according to 5.4, producing the post-filtered synthesized speech
 18 signal, $\hat{s}_{pf}(n)$.

19 **5.3 Rate 1 and Rate 1/4 PPP decoding (FPPP and QPPP) for SO 68**

20 5.3.1 Decoding of the LSP parameters in FPPP

21 If (FER_FLAG(m) = TRUE), use the LSP parameters from the last frame to generate bandwidth expanded
 22 LSPs for the current frame as follows: $\Omega_q(m) = 0.875 \Omega_q(m-1) + 0.125 \Omega_{spread}$ where Ω_{spread} are the initial
 23 values of the LSPs, as defined in Section 5.2.

24 Otherwise, decode the LSP parameters, $\Omega_q(m)$ using the decoded LSP indices, LSPIDX(k). In the event that
 25 the decoded LSPs are not strictly ascending, FER_FLAG(m) shall be set to TRUE, where "strictly ascending"
 26 is defined as $\Omega_q(m, i) < \Omega_q(m, i+1)$; $1 \leq i \leq 9$.

27 5.3.2 Decoding of the LSP parameters in QPPP

28 A second order moving average (MA) predictor is used for quantizing the LSPs in quarter-rate voiced frame
 29 processing.

30 The MA predictive quantizer ensures that the effect of frame errors discontinues after 2 frames. The quantized
 31 LSP vector at the mth frame is given as

$$\hat{\mathbf{L}}_m = 0.4\mathbf{C}_m + 0.4\mathbf{C}_{m-1} + 0.2\mathbf{C}_{m-2} \quad (5.3.2-1)$$

where \mathbf{C}_m is the codebook vector for the mth frame is constructed as follows:

$$C_m(i) = \begin{cases} CB1[i_1^*][i]; & 0 \leq i < 6 \\ CB2[i_2^*][i-6]; & 6 \leq i < 10 \end{cases}$$

where i_1^* , and i_2^* be the LSP codebook indices obtained from the QPPP packet for the two splits.

The LSP parameters, $\Omega_q(m)$, are elements of the vector L.

5.3.3 Delay decoding in FPPP

The delay parameter, L, for the current frame is defined as:

$$L(m) = DELAY + 20 \quad (5.3.3-1)$$

where DELAY is the pitch delay transmission code.

5.3.4 Delay decoding in QPPP

The delay parameter, L, for the current frame is defined as:

$$L(m) = DELTADelay - 7 + PREV_DELAY \quad (5.3.4-1)$$

where DELTADelay is the pitch delay transmission code, and PREV_DELAY is the decoded delay parameter of the previous frame (same as L(m-1)).

5.3.5 Previous frame delay PPP (QPPP and FPPP)

The delay value, PL, of the previous frame is defined as:

$$PL = \begin{cases} L(m) & ; \text{if previous frame was Rate 1/4 unvoiced or Rate 1/8} \\ L(m-1) & ; \text{otherwise} \end{cases}$$

PL is further conditioned as follows

$$PL = \begin{cases} PL / 2; & \text{if } PL > 1.85L \\ PL \cdot 2; & \text{if } PL \leq 0.54L \text{ AND } PL < 127 / 2 \\ PL; & \text{otherwise} \end{cases}$$

5.3.6 Interpolation of LSP parameters and LSP to LPC conversion

Interpolate the quantized LSPs over the three subframes, m' , in the current frame, m. The form of the quantized, interpolated LSP vector is:

$$\hat{\Omega}_q(m') = (1 - \mu_{m'})\Omega_q(m-1) + \mu_{m'}\Omega_q(m), \quad (5.3.6-1)$$

1 where the subframe interpolator constants are defined as $\mu = \{ 0.1667, 0.5, 0.8333 \}$.
 2 Convert the quantized, interpolated LSPs, $\Omega_q(m)$, to quantized, interpolated LPC parameters, $\{a_q\}$, as
 3 described in Section 4.4.2.1, and Section 4.4.2.2 for each subframe.
 4 The quantized interpolated LPC parameters at the end of the previous frame, and the current frames are used in
 5 the synthesis of the current frame of residual.

6 5.3.7 Restoring PPP memories if last frame is non-PPP or full-rate PPP

7 The past-frame memory required for PPP processing is restored as was done in the encoder described in Section
 8 4.10.25.

9 5.3.8 ERB amplitude dequantization of full-rate PPP

10 The ERB amplitudes are created from the Amplitude Quantization Indices as described in Section 4.10.29 to
 11 obtain the current PPP DFS $CURRP_Q_p$ in the polar form.

12 5.3.9 Phase dequantization of full-rate PPP or Special Half-rate PPP (packet level signaling) frame

13 The phases of DFS, $CURRP_Q_p$, is set to zero as follows:

14
$$CURRP_Q_p \cdot b(k) = 0; \quad 0 \leq k \leq \lfloor L/2 \rfloor \quad (5.3.9-1)$$

15 $CURRP_Q_p$, is converted to Cartesian representation as shown in Section 4.10.9, and then converted to the
 16 perceptually weighted domain by pole-filtering using A_w , the weighted LPC filter,
 17 $A_w(k) = A(k)(0.8^k)$, $0 \leq k < 9$. Lets identify the resulting DFS' by $CURRP_Q_S$.

18 $CURRP_Q_S$ is then shifted by the negative of the global alignment, *alignment*, obtained from the received
 19 packet as described in Section 4.10.6.

20 The band alignments from the received packets are then applied to $CURRP_Q_S$, according to the following
 21 equations:

$$\begin{aligned}
 CURRP_Q_S.a(k) &= \left(\begin{array}{c} CURRP_Q_S.a(k) \cos \left(-k \frac{2\pi}{L} \eta \left(-\frac{16}{\eta} + band_alignment(j) \right) \right) \\ CURRP_Q_S.b(k) \sin \left(-k \frac{2\pi}{L} \eta \left(-\frac{16}{\eta} + band_alignment(j) \right) \right) \end{array} \right) - \\
 CURRP_Q_S.b(k) &= \left(\begin{array}{c} CURRP_Q_S.a(k) \sin \left(-k \frac{2\pi}{L} \eta \left(-\frac{16}{\eta} + band_alignment(j) \right) \right) \\ CURRP_Q_S.b(k) \cos \left(-k \frac{2\pi}{L} \eta \left(-\frac{16}{\eta} + band_alignment(j) \right) \right) \end{array} \right) + \\
 0 \leq k &\leq \left\lfloor \frac{L}{2} \right\rfloor
 \end{aligned}$$

$$0 \leq j < 17$$

$$-\frac{16}{\eta} \leq n < \frac{16}{\eta}; n \text{ increasing in steps of } 1$$

for every j ,

$$k \in \left[0, \left\lfloor \frac{L}{2} \right\rfloor \right] \text{ such that } lband(j) \leq k \frac{8000}{L} < hband(j)$$

$$\text{where, } \eta = \begin{cases} 1; & j < 3 \\ 0.5; & 3 \leq j < 17 \end{cases}$$

$$\text{and, } lband(j) = F_BAND[j]$$

$$hband(j) = F_BAND[j+1]$$

If the frame is a special HPPP frame, the band alignments used in the above equation are not present in the input packet but instead are given by:

$$band_alignment(j) = \begin{cases} 16; & j < 3 \\ 32; & \text{otherwise} \end{cases}$$

$CURRP_Q_S$ is then zero filtered using the procedure in Section 4.10.5, and A_w , the weighted LPC filter,

$$A_w(k) = A(k) (0.8^k); \quad 0 \leq k < 9$$

5.3.10 Obtaining the dequantized current DFS in QPPP

The ERB amplitudes of the QPPP frames are decoded as described in Section 4.10.28.3. The amplitude dequantized current PPP DFS, $CURRP_Q_p$, is then obtained as described in Section 4.10.28.5 $CURRP_Q_p$.

5.3.11 Copying the phase spectrum of previous PPP DFS

In quarter-rate PPP, the phase of the current DFS is set to be equal to the phase of the previous DFS after it is extended into the current frame. That is, the phase of $CURRP_Q_p$ (which is in polar form) is obtained as follows:

$$CURRP_Q_p.b(k) = ACB_p.b(k); \quad 0 \leq k \leq \left\lfloor L/2 \right\rfloor \quad (5.3.11-1)$$

where ACB_p is the polar representation of ACB .

The Cartesian representation of yields the DFS of the current PPP, $CURRP_Q$, that is to be used in the synthesis of the whole frame of excitation.

5.3.12 PPP synthesis

Now that we have the quantized current PPP DFS, $CURRP_Q$, and the previous DFS, $PREV_PPP$, we generate the 160 samples of the current frame excitation, $ET(m)$, similar to the method described in Section 4.10.30.4.

5.3.12.1 Frame expansion or compression in PPP synthesis

To interface to dynamic jitter buffer mechanisms used in Packet Switched networks, Rate 1/4 PPP and Rate 1/2 PPP synthesis can output more than or less than 160 samples. When it is needed to output less than 160 samples, PPP generates 160-L samples. When more than 160 samples are needed, PPP generates 160+L samples.

5.3.13 Synthesis of the decoder output signal in PPP

Filter the excitation, $ET(m)$, through the synthesis filter using the interpolated LPCs generated in 5.2.3.2, creating the synthesized speech signal, $\hat{s}(n)$. The synthesis filter for the decoder, $H_q(z)$, is defined by:

$$H_q(z) = \frac{1}{A_q(z)} = \frac{1}{1 - \sum_{k=1}^{10} a_q(k)z^{-k}} \quad (5.3.13-1)$$

The signal, $\hat{s}(n)$, shall be post-filtered according to Section 5.7, producing the post-filtered synthesized speech signal, $\hat{s}_{pf}(n)$.

5.4 Decoding of rate 1/4 unvoiced decoding or special rate-1/2 NELP decoding

The decoding of Rate 1/4 unvoiced or the Special Rate 1/2 NELP frame is depicted in Figure 5.4-1.




Figure 5.4-1 Excitation decoding for rate 1/4 NELP or rate 1/2 special NELP

The gain indices $i\hat{G}'$, and $i\hat{G}''[j], 0 \leq j < 2$, and the shaping filter index F_{idx} are decoded from the bitstream input to the decoder. The gains are dequantized using Equations (4.11.1-5) and (4.11.1-8). A pseudo-random vector, $e_{rand}(n)$, is generated as described in Section 4.11.2. As described in Section 4.11.3, this pseudo-random vector is used to generate a gain scaled sparse signal, $r_1(n)$, which is then shaped by the bandpass filter $BP(z)$, and the shaping filter $SF(z)$ to yield the Rate 1/4 frame LPC excitation. As shown in Equation (4.11.4-9), the index of the filter, F_{idx} , is used to establish $SF(z)$. The Rate 1/4 unvoiced frame excitation is then filtered by the LP synthesis filter and the post-processing filter to generate speech.

5.4.1 Frame expansion or compression in Rate 1/4 NELP decoding

To interface to dynamic jitter buffer mechanisms used in Packet Switched networks, Rate 1/4 NELP frames can output more than or less than 160 samples. When it is needed to output less than 160 samples, Rate 1/4 NELP puts out 128 samples. When more than 160 samples are needed, Rate 1/4 NELP puts out 192. samples.

For compression, the number of subframes of Rate 1/4 NELP used are 8. Specifically, only first 8 gain values are used in the excitation generation.

For expansion, the number of subframes of Rate 1/4 NELP used are 12. Specifically, the two extra gain values used in the excitation generation are set to the last subframe's gain value in the decoded packet. That is, $\hat{G}(10) = \hat{G}(11) = \hat{G}(9)$.

5.5 Rate 1/8 Decoding

Inputs: The inputs to Rate 1/8 decoding are:

- The quantized LSP indices from the current frame, $LSPIDX(k)$
- The quantized LSPs from the previous frame, $\Omega_q(m-1)$
- The vector quantized frame energy index, $FGIDX(m)$
- The vector quantized frame energy index from the last frame, $FGIDX(m - 1)$
- The frame erasure flag, $FER_FLAG(m)$, for the current frame m

Outputs: The outputs from Rate 1/8 decoding are:

- The post-filtered synthesized speech signal, $\hat{s}_{pf}(n)$

State Variables:

None.

Processing:

Rate 1/8 decoding shall comprise 5.5.1 to 5.5.3.

5.5.1 Decoding of the LSP parameters

If $(FER_FLAG(m) = TRUE)$, use the LSP parameters from the last frame, $\Omega_q(m) = \Omega_q(m-1)$. Otherwise, decode the LSP parameters, $\Omega_q(m)$, as defined in 4.7.5, using the decoded $LSPIDX(k)$. In the event that the decoded LSPs are not strictly ascending, $FER_FLAG(m)$ shall be set to $TRUE$, where “strictly ascending” is defined as $\Omega_q(m, i) < \Omega_q(m, i+1) ; 1 \leq i \leq 9$.

5.5.2 Decoding of the Frame Energy Vector for SO 3

If $(FER_FLAG(m) = FALSE)$, the frame energy vector, $\gamma_q(m')$, shall be defined as:

$$\gamma_q(m') = 10^{q_{\log}(m', FGIDX(m))}; \quad 0 \leq m' < 3, \tag{5.5.2-1}$$

where $q_{\log}(m', FGIDX)$ is an entry in the gain quantization codebook found in Table 9-15.

If $(FER_FLAG(m) = TRUE)$, the frame energy vector, $\gamma_q(m')$, is calculated by:

$$\gamma_q(m') = \frac{1}{3} \sum_{i=0}^2 10^{q \log(i, FGIDX(m-1))}; \quad 0 \leq m' < 3, \quad (5.5.2-2)$$

where $FGIDX(m-1)$ is the codebook index from the last Rate 1/8 packet in which FER_FLAG was $FALSE$.

5.5.3 Decoding of the Frame Energy Gain for SO 68

If ($FER_FLAG(m) = FALSE$), the frame energy vector, $\gamma_q(m')$, is defined as in Section 4.12.6.

If ($FER_FLAG(m) = TRUE$), the frame energy vector, $\gamma_q(m')$, is calculated by:

$$\gamma_q(m') = 10^{\left(\frac{LG0+LG1+LG2}{3}\right)} \quad (5.5.3-1)$$

where,

$$LG2 = \sqrt{\frac{\sum_{j=-128}^{-2 \times 54} (E_T(j))^2}{128 - 2 \times 54}}$$

$$LG1 = \sqrt{\frac{\sum_{j=-54 \times 2 - 1}^{-54} (E_T(j))^2}{54}}$$

$$LG0 = \sqrt{\frac{\sum_{j=-53}^0 (E_T(j))^2}{54}}$$

where E_T is the adaptive codebook vector mentioned in Section 5.2.3.10.

5.5.4 Rate 1/8 Subframe Decoding

Compute the decoded synthesized speech signal for each subframe, $0 \leq m' < 3$, as described in 5.3.3.1 to 5.3.3.4. The subframe size, L , is 53 for subframes 0 and 1, and 54 for subframe 2.

5.5.4.1 Rate 1/8 Excitation Generation

Obtain the Rate 1/8 excitation by generating a zero-mean, unit variance pseudo-random Gaussian white noise process (see 4.7.2) scaled by $\gamma_q(m')$:

$$E(n) = \gamma_q(m') \text{ran_g}\{seed\}; \quad 0 \leq n < L, \quad (5.5.4-1)$$

1 No attempt is made to synchronize the random time series generated at the receiver with that generated at the
2 transmitter.

3 5.5.4.2 Interpolation of LSP Parameters

4 Interpolate the quantized LSPs as in 5.2.3.1.

5 5.5.4.3 LSP to LPC conversion

6 Perform the LSP to LPC conversion as defined in 5.2.3.2.

7 5.5.4.4 Synthesis of Decoder Output Signal

8 Filter the Rate 1/8 excitation, $E(n)$, through the synthesis filter as in 5.2.3.11. The signal, $\hat{s}(n)$, shall be post-
9 filtered according to 5.4, producing the post-filtered synthesized speech signal, $\hat{s}_{pf}(n)$.

10 5.6 Suppressed/Blanked Rate 1/8 decoding

11 Inputs

12 The frame erasure flag, FER_FLAG(m), for the current frame m

13 Outputs

14 The post-filtered synthesized speech signal, $\hat{s}_{pf}(n)$.

15 State Variables

16 The background noise estimate, $E_{bgn}(n)$

17 Processing

18 Suppressed Rate 1/8 decoding shall comprise Sections 5.6.1 and 5.6.2. The basic structure of the decoder is
19 modified as shown in Figure 5-2 to incorporate decoding of suppressed rate 1/8 frames. The received packet is
20 decoded as defined in the previous sections when the rate is not of type 0 (blank or suppressed rate 1/8). When
21 the received rate is a suppressed rate 1/8 frame, the switch connects the output of the comfort noise synthesizer
22 and encoder to the decoder to produce the output signal.

23




Figure 5.6-1 Comfort Noise Synthesizer Block Diagram

5.6.1 Synthesizing comfort noise

The comfort noise is synthesized from the background noise estimate $E_{bgn}(n)$, generated in 5.9.3. The frequency domain representation of the noise is computed from the background noise estimate. First, the background noise estimate is smoothed to produce

$$E_{bgnSm}(m,i) = \begin{cases} \beta_2 E_{bgnSm}(m-1,i) + (1-\beta_2) E_{bgn}(m,i) & ; m \geq 10 \\ \beta_{2r} E_{bgnSm}(m-1,i) + (1-\beta_{2r}) E_{bgn}(m,i) & ; m < 10 \end{cases} \quad (5.6.1-1)$$

Next, the magnitude of noise is computed according to:

$$X_{decmag}(k) = 10^{E_{bgn}(m,i)/20} ; f_L(i) \leq k \leq f_H(i), 0 \leq i < N_c \quad (5.6.1-2)$$

where $\beta_2 = 0.9925$, and $\beta_{2r} = 0.794$.

with $f_L(i)$, $f_H(i)$, and N_c defined in section 4.3.2.2. The phase is randomized to produce X_{dec} , according to:

$$\phi(k) = \cos(2\pi \cdot \text{ran } 0\{\text{seed}\}) + j \sin(2\pi \cdot \text{ran } 0\{\text{seed}\}) \quad (5.6.1-3)$$

$$X_{dec}(k) = X_{decmag}(k) \cdot \phi(k) \quad (5.6.1-4)$$

where $\text{ran}0$ is a uniform pseudo-random number generator as described in 4.13.1. The noise is converted to the time domain using the inverse DFT:

$$x_{dec}(m, n) = \begin{cases} x_{dec}(m-1, n+L-D) + w_g(n) \cdot \frac{1}{2} \sum_{k=0}^{M-1} X_{dec}(k) e^{j2\pi nk/M} & ; 0 \leq n < D \\ w_g(n) \cdot \frac{1}{2} \sum_{k=0}^{M-1} X_{dec}(k) e^{j2\pi nk/M} & ; D \leq n < M. \end{cases} \quad (5.6.1-5)$$

with $w_g(n)$ defined as:

$$w_g(n) = \begin{cases} \sin^2(\pi(n+0.5)/2D) & ; 0 \leq n < D \\ 1 & ; D \leq n < L \\ \sin^2(\pi(n-L+D+0.5)/2D) & ; L \leq n < L+D \end{cases} \quad (5.6.2-1) \text{ Generating encoded}$$

packet from synthesized noise

To better match the spectral characteristics of Rate 1/8 frames, the synthesized comfort noise $x_{dec}(m, n)$ is encoded as a Rate 1/8 frame. The encoding process is a simplified version of the one described in chapter 4. First, the synthesized noise from (5.5.1-4) is used to compute the LPC coefficients according to (4.4.1.1) by redefining $s'(k)$ as:

$$s'(k) = \begin{cases} x_{dec}(m-1, k) & ; 0 \leq k < 160 \\ x_{dec}(m, k-160) & ; 160 \leq k < 320 \end{cases} \quad (5.6.2-2)$$

Then, the LPC coefficients are converted to LSPs according to (4.4.1.3). The LSPs are interpolated for each subframe and converted back to LPCs according to (4.4.2.1) and (4.4.2.2).

To compute the LPC gain, a short-term residual $\varepsilon(n)$ is generated according to equation (4.4.2.3-1). Then, the impulse response h_{noise} of the inverse LPC filter for the current subframe m' , is calculated to the subframe length L_{sf} . The frame energy gain is determined by:

$$\gamma(m') = \log_{10} \left(\frac{\frac{2}{L_{sf}} \cdot \sum_{n=0}^{L_{sf}-1} |\varepsilon(n)|}{\sqrt{\sum_{n=0}^{L_{sf}-1} h_{noise}^2(n)}} \right) \quad (5.6.2-3)$$

1 The LSPs are vector quantized according to 4.12.1, and the frame energy gain according to 4.12.6. The
 2 encoded parameters are processed by 5.5.1 through 5.5.4.4 assuming FER_FLAG(m) is not set to produce the
 3 decoded output $\hat{s}(n)$.

5 **5.7 Adaptive Postfilter for SO 3**

6 The Adaptive Postfilter function improves the perceived speech quality of the decoder output. Refer to 1.1 for
 7 guidelines concerning potential variations of the Adaptive Postfilter.

8 **Inputs:**

- 9 • The decoder synthesis output signal, $\hat{s}(n)$
- 10 • The quantized, interpolated LPC coefficients, $A_q(n)$
- 11 • The interpolated pitch delays, $d(m')$

12 **Output:**

13 The post-filtered synthesis signal, $\hat{s}_{pf}(n)$

14 **Initialization:** All filter memories shall be initialized to zero at start-up.

15 **Processing:** The decoded speech signal, $\hat{s}(n)$, shall be post-filtered by applying the following operations in the
 16 sequence specified:

- 17 • A tilt-compensation filter $H_t(z)$
- 18 • A short term residual filter, $H_E(z)$
- 19 • A long term filter, $H_p(z)$
- 20 • Gain normalization, g_s
- 21 • A short term filter, $H_s(z)$

22 The postfilter shall be applied once for each of the three subframes and shall take the form:

$$23 \quad PF(z) = H_s(z)g_sH_p(z)H_E(z)H_t(z). \quad (5.7-1)$$

24 The postfilter residual memory buffer is then updated with the current subframe's residual signal. Each of
 25 these steps shall be carried out as specified in Sections 5.7.1 to 574.5.

26 **5.7.1 Tilt Compensation Filter**

27 Generate the tilt-compensated speech signal, $\hat{s}_t(n)$, by filtering the decoded speech signal, $\hat{s}(n)$, through the
 28 tilt compensation filter given by:

$$29 \quad H_t(z) = 1 - \mu z^{-1}, \quad (5.7.1-1)$$

30 where μ is the tilt coefficient calculated by determining if $\hat{s}(n)$ is voiced or un-voiced. The signal, $\hat{s}(n)$, is
 31 defined as being voiced if:

$$R = \left(\sum_{i=0}^{L-2} \hat{s}(i)\hat{s}(i+1) \right) \geq 0. \quad (5.7.1-2)$$

Using the above result, the tilt coefficient, μ , is defined as:

$$\mu = \begin{cases} 0 & ; R < 0, \\ \text{tilt}(\text{Rate}) & ; R \geq 0, \end{cases} \quad (5.7.1-3)$$

where $\text{tilt}(\text{Rate})$ is defined in Table Table 5-35.4.1-1.

Table 5-3. Postfilter Coefficients

<i>Rate</i>	<i>tilt(Rate)</i>	γ_{p1}	γ_{p2}
1	0.20	0.57	0.75
1/2	0.35	0.50	0.75
1/8	0	0.57	0.57

5.7.2 The Short Term Residual Filter

Compute the postfilter residual, $\varepsilon_p(n)$, by filtering the tilted speech signal, $\hat{s}_t(n)$, through $H_{\mathcal{E}}(z)$, given by:

$$H_{\mathcal{E}}(z) = A_q(\gamma_{p1}^{-1}z) = 1 - \sum_{k=1}^{10} a_q(k)\gamma_{p1}^k z^{-k}, \quad (5.7.2-1)$$

where γ_{p1} is given for each *Rate* in Table 5-3, and $\{a_q\}$ are the interpolated LPC parameters for the current subframe.

5.7.3 The Long-term Postfilter

Generate the long-term post-filtered signal, $\hat{s}_p(n)$, by filtering the residual signal, $\varepsilon_p(n)$, through the long term post filter given by:

$$H_p(z) = \begin{cases} 1.0 + g_p g_{lt} z^{-d_{opt}} & ; 0.5 \leq g_p < 1.0, \\ 1.0 + g_{lt} z^{-d_{opt}} & ; 1.0 \leq g_p, \\ 1.0 & ; \text{otherwise,} \end{cases} \quad (5.7.3-1)$$

where $g_{lt} = 0.5$ and where the long term predication gain, g_p , is calculated by:

$$g_p = \frac{\sum_{n=0}^{L-1} \varepsilon_{pf}(n) \varepsilon_{pf}(n-d_{opt})}{\sum_{n=0}^{L-1} \varepsilon_{pf}(n-d_{opt}) \varepsilon_{pf}(n-d_{opt})}, \quad (5.7.3-2)$$

and where the long-term delay, d_{opt} , is calculated from $\varepsilon_{pf}(n)$ by finding the best integer delay around $d_I = \left\lfloor \frac{d(m',0) + d(m',1)}{2} \right\rfloor$. The decoded interpolated integer delay d_I is searched from $(d_I - 3)$ to $(d_I + 3)$ to find the best integer delay for the long-term postfilter. The best integer delay d_{opt} is computed by maximizing the correlation:

$$R(d_{opt}) = \sum_{n=0}^{L-1} \varepsilon_{pf}(n) \varepsilon_{pf}(n-d_{opt}); \quad (d_I - 3) \leq d_{opt} \leq (d_I + 3). \quad (5.7.3-3)$$

5.7.4 Gain Normalization and Short-Term Postfilter

Compute the temporary signal, $\hat{s}_s(n)$, by filtering the long-term postfilter output signal, $\hat{s}_p(n)$, through the short-term postfilter, $H_s(z)$, given by:

$$H_s(z) = \frac{1}{A_q(\gamma_{p2}^{-1}z)}, \quad (5.7.4-1)$$

where γ_{p2} is found in Table Table 5-3.

Then compute the short-term postfilter gain, g_s , by using the temporary signal, $\hat{s}_s(n)$:

$$g_s = \sqrt{\frac{\sum_{n=0}^{L-1} \hat{s}_s^2(n)}{\sum_{n=0}^{L-1} \hat{s}_s^2(n)}}, \quad (5.7.4-2)$$

where g_s is upper bound limited at 1.0. The signal $g_s \hat{s}_p(n)$ is then filtered through the short-term postfilter in Equation 5.7.4-1 to produce the final post-filtered speech signal, $\hat{s}_{pf}(n)$.

5.8 Adaptive post filter for SO 68

The adaptive post filter function improves the perceived speech quality of the decoder output.

Inputs

The decoder synthesis output signal, $\hat{s}(n)$

The quantized, interpolated LPC coefficients, $A_q(n)$

1 The quantized, interpolated LSPs, $\Omega_q(m,k)$; $1 \leq k \leq 10$

2 The interpolated pitch delays, $d(m')$

3 Output

4 The post-filtered synthesis signal, $\hat{s}_{pf}(n)$.

5 Initialization

6 All filter memories shall be initialized to zero at start-up.

7 Processing

8 The decoded speech signal, $\hat{s}(n)$, shall be post-filtered by applying the following operations.

9 A reference set of LPCs is first obtained from the decoded speech signal as follows:

$$A_{ref}(k) = \begin{cases} -\frac{\sum_{n=0}^{L-2} \hat{s}(n)\hat{s}(n+1)}{\sum_{n=0}^{L-1} \hat{s}(n)\hat{s}(n)}; & k = 0 \\ 0; & otherwise \end{cases}$$

10 A_{ref} is then converted to a reference LSPs, Ω_{ref} as described in Section 4.4.1.3.

12 Two sets of interpolated LSPs, Ω_3 , and Ω_4 , are derived from Ω_{ref} , and the input interpolated quantized
13 LSPs, Ω_m as follows:

$$\Omega_3(i) = \begin{cases} (0.3 + 0.04i)\Omega_{ref}(i) + (0.7 - 0.04i)\Omega_m(i); & 0 \leq i < 5 \\ (0.5)\Omega_{ref}(i) + (0.5)\Omega_m(i); & 5 \leq i < 10 \end{cases}$$

$$\Omega_4(i) = (0.3)\Omega_{ref}(i) + (0.7)\Omega_m(i); \quad 0 \leq i < 10$$

16 These interpolated LSPs are then converted to interpolated LPCs A_3 and A_4 as described in Section 4.4.2.2.

17 The decoded speech signal, $\hat{s}(n)$, shall be post-filtered by applying the following operations in the sequence
18 specified:

19 A short term residual filter, $H_\epsilon(z)$

20 A long term filter, $H_p(z)$

21 Gain normalization, g_s

22 A short term filter, $H_s(z)$

23 The post filter shall be applied once for each of the three subframes and shall take the form:

$$PF(z) = H_s(z)g_sH_p(z)H_\epsilon(z) \quad (5.8-1)$$

1 The post filter residual memory buffer is then updated with the current subframe's residual signal. Each of
 2 these steps shall be carried out as specified in Sections 5.8.1 to 5.8.5.

3 5.8.1 The short-term residual filter

4 Compute the postfilter residual, $\epsilon_{pf}(n)$, by filtering the tilted speech signal, $\hat{s}_t(n)$, through $H_\epsilon(z)$ which is
 5 equal to $A_3(z)$.

6 5.8.2 The long-term post filter

7 Generate the long-term post-filtered signal, $\hat{s}_p(n)$, by filtering the residual signal, $\epsilon_{pf}(n)$, through the long term
 8 post filter given by:

$$H_p(z) = \begin{cases} 1.0 + g_p g_{lt} z^{-d_{opt}} & ; 0.5 \leq g_p < 1.0, \\ 1.0 + g_{lt} z^{-d_{opt}} & ; 1.0 \leq g_p, \\ 1.0 & ; \text{otherwise,} \end{cases} \quad (5.8.2-1)$$

10 where $g_{lt} = 0.4$ and where the long term predication gain, g_p , is calculated by:

$$g_p = \frac{\sum_{n=0}^{L-1} \epsilon_{pf}(n) \epsilon_{pf}(n - d_{opt})}{\sum_{n=0}^{L-1} \epsilon_{pf}(n - d_{opt}) \epsilon_{pf}(n - d_{opt})}, \quad (5.8.2-2)$$

12 and where the long-term delay, d_{opt} , is calculated from $\epsilon_{pf}(n)$ by finding the best integer delay
 13 around $d_I = \left\lfloor \frac{d(m',0) + d(m',1)}{2} \right\rfloor$. The decoded interpolated integer delay d_I is searched from
 14 $(d_I - 3)$ to $(d_I + 3)$ to find the best integer delay for the long-term postfilter. The best integer delay d_{opt}
 15 is computed by maximizing the correlation:

$$R(d_{opt}) = \sum_{n=0}^{L-1} \epsilon_{pf}(n) \epsilon_{pf}(n - d_{opt}); \quad (d_I - 3) \leq d_{opt} \leq (d_I + 3). \quad (5.8.2-3)$$

17 5.8.3 Gain normalization and short-term post filter

18 Compute the temporary signal, $\hat{s}_s(n)$, by filtering the long-term postfilter output signal, $\hat{s}_p(n)$, through the
 19 short-term postfilter, $H_s(z)$, which is same as $A_4(z)$.

20 Then compute the short-term postfilter gain, g_s , by using the temporary signal, $\hat{s}_s(n)$:

$$g_s = \sqrt{\frac{\sum_{n=0}^{L-1} \hat{s}_s^2(n)}{\sum_{n=0}^{L-1} \hat{s}_s^2(n)}}, \quad (5.8.3-1)$$

1 where g_s is upper bound limited at 1.0. The signal $g_s \hat{s}_s(n)$ is then filtered through the short-term postfilter in
 2 Equation 7.4.4-1 to produce the final post-filtered speech signal, $\hat{s}_{pf}(n)$.

3

4 **5.9 Background Noise Estimation**

5 To allow suppressed Rate 1/8 frames, the output of the adaptive postfilter is used to determine an estimated
 6 background noise spectrum.

7 **Inputs**

8 The post-filtered synthesis signal, $\hat{s}_{pf}(n)$

9 The current frame rate, Rate

10 Background noise estimate adaptation factor, W_α

11 **Outputs**

12 None. Only state variables affected.

13 **State Variables**

14 The background noise envelope estimate, E_{bgn} .

15

16 **Initialization**

17 The following variables shall be set to zero at initialization (frame $m=0$):

18 The overlapped portion of the input buffer (output of the postfilter), {}

19 The following shall be initialized to a startup value other than zero:

20 The channel noise estimate, $E_{bgn}(0)$

21 The channel energy leaky integrator's memory, $E_{Nch}(0)$

22

23 **Processing**

24 The background noise spectral estimate is only computed on frames where FER_FLAG(m) is not set and Rate
 25 is not equal to Suppressed Rate 1/8. The post-filtered speech signal, $\hat{s}_{pf}(n)$, is used to determine the
 26 background noise spectral estimate at the decoder. Although the frame size of the decoder is 20 ms, the
 27 background noise spectral estimator uses procedures from the noise suppressor and therefore operates in blocks
 28 of 10 ms. The following procedures shall be executed two times per 20 ms of decoded speech frame, and the
 29 current 10ms frame for the background noise estimator shall be denoted m . Figure 5.9-1 depicts the
 30 Background Noise Estimator that is described in the following sections.

31




Figure 5.9-1 Background Noise Estimator Block Diagram

5.9.1 Frequency Domain Conversion

The post-filtered signal $\hat{s}_{pf}(m, n)$ is windowed using a smoothed trapezoid window, in which the first D samples of the noise estimator's input frame buffer $s_m(n)$ are obtained by windowing the last D samples of the previous frame ($\hat{s}_{pf}(m-1, n)$). $s_m(n)$ is obtained by:

$$s_m(n) = \begin{cases} \hat{s}_{pf}(m-1, L-D+n) \cdot \sin^2(\pi(n+0.5)/2D) & ; 0 \leq n < D, \\ \hat{s}_{pf}(m, n-D) & ; D \leq n < L, \\ \hat{s}_{pf}(m, n-D) \cdot \sin^2(\pi(n-L+D+0.5)/2D) & ; L \leq n < D+L, \\ 0 & ; D+L \leq n < M. \end{cases} \quad (5.9.1-1)$$

where m is the current frame, n is the sample index to the buffer $s_m(n)$, $L = 80$ is the frame length, $D = 24$ is the overlap (or delay) in samples, and $M = 128$ is the DFT sequence length. This results in the input buffer containing $L + D = 104$ samples, and being zero-padded to M samples.

The transformation of $s_m(n)$ to the frequency domain is performed using the Discrete Fourier Transform (DFT) to produce $S_m(k)$ as follows:

$$S_m(k) = \frac{2}{M} \sum_{n=0}^{M-1} s_m(n) e^{-j2\pi nk/M} \quad ; 0 \leq k < M \quad (5.9.1-2)$$

5.9.2 Channel Energy Estimator

Calculate the channel energy estimate $E_{Nch}(m, i)$ in decibels (dB) for the current frame, m , as:

$$E_{Nch}(m, i) = \max \left\{ E_{Nmin}, \alpha_w(m) E_{Nch}(m-1, i) + (1 - \alpha_w(m)) \cdot \left(\frac{10}{f_H(i) - f_L(i) + 1} \sum_{k=f_L(i)}^{f_H(i)} \log_{10}(|S_m(k)|^2) + c_m \right) \right\} \quad (5.9.2-1)$$

1 where $E_{N\min} = -15dB$ is the minimum allowable channel energy, $\alpha_w(m)$ is the channel energy smoothing
 2 factor (defined below), $N_c = 16$ is the number of combined channels, and $f_l(i)$ and $f_h(i)$ are the i -th elements of
 3 the respective low and high channel combining tables, which are defined in the noise suppressor (section
 4 4.3.2.2).

5 The channel energy smoothing factor, $\alpha_w(m)$, is defined as:

$$6 \quad \alpha_w(m) = \begin{cases} 0 & ; m < 3 \\ 0.6 \cdot w_\alpha & ; m \geq 3, rate(m) = 1/8 \\ w_\alpha & ; otherwise \end{cases} \quad (5.9.2-2)$$

7 and

$$8 \quad c_m = \begin{cases} 3.52 & ; rate(m) \neq 1/8 \\ 0 & ; otherwise \end{cases} \quad (5.9.2-3)$$

9
 10 This means that $\alpha_w(m)$ assumes a value of zero for the first two frames ($m < 3$) and a value of 0.6 times the
 11 weight coefficient w_α for all subsequent frames. This allows the channel energy estimate to be initialized to
 12 the unfiltered channel energy of the first frame, and some control over the adaptation via the weight coefficient.
 13 The weight coefficient is varied according to:

$$14 \quad w_\alpha = \begin{cases} 1.0 & ; FER_FLAG(m) = 1 \\ 1.1 & ; FER_FLAG(m) \neq 1 \end{cases} \quad (5.9.2-4)$$

16 5.9.3 Background Noise Estimate

17 The background noise energy estimate \mathbf{E}_{bgn} is updated according to the following:

18 If the current frame is a rate 1/8 frame,

$$19 \quad E_{bgn}(m, i) = \beta_1 \cdot E_{Nch}(m-1, i) + (1 - \beta_1) \cdot E_{Nch}(m, i) \quad (5.9.3-1)$$

20 For all other frame rates:

$$21 \quad E_{bgn}(m, i) = \begin{cases} E_{Nch}(m, i) & ; E_{Nch}(m, i) < E_{bgn}(m-1, i) \\ E_{bgn}(m-1, i) + \Delta_1 & ; (E_{Nch}(m, i) - E_{bgn}(m-1, i)) > E_{voice} \\ E_{bgn}(m-1, i) + \Delta_2 & ; otherwise \end{cases} \quad (5.9.3-2)$$

3GPP2 C.S0014-B ver 1.0

1 where $\Delta_1 = 0.005$, $\Delta_2 = 0.010$ $E_{voice} = 12dB$..

2 NOTE: The background update routines are only called when FER_FLAG(m) is not set and Rate is not set to
3 Suppressed Rate 1/8.

4

6 TTY/TDD EXTENSION FOR SO 3

6.1 Introduction

This section provides an option to reliably transport the TTY/TDD 45.45 bps and 50 bps Baudot code, making digital wireless technology accessible to TTY/TDD users. This section is separated into two major components. Section 6.3 describes the new interface between the encoder and the decoder for transporting the TTY information. Section 6.3.4 is a description of the TTY/TDD software simulation of this section, and is offered only as a recommendation for implementation. However, in the event of ambiguous or contradictory information, the software simulation shall be used to resolve any conflicts.

This section is an extension of the previous version of the TTY/TDD extension for EVRC, C.S0014-0 v3.0. It extends the previous version by adding the 50 bps Baudot functionality, but is capable with interoperating with C.S0014-0 V3.0 when used at 45.45 bps. See Section 6.3.3.2 for details regarding interoperability with C.S0014-0 V3.0.

This section uses the following verbal forms: “Shall” and “shall not” identify requirements to be followed strictly to conform to the standard and from which no deviation is permitted. “Should” and “should not” indicate that one of several possibilities is recommended as particularly suitable, without mentioning or excluding others; that a certain course of action is preferred but not necessarily required; or that (in the negative form) a certain possibility or course of action is discouraged but not prohibited. “May” and “need not” indicate a course of action permissible within the limits of the standard. “Can” and “cannot” are used for statements of possibility and capability, whether material, physical, or causal.

6.2 Overview

The following sections provide a method for reliably transporting the 45.45 bps and 50 bps Baudot code in the audio path, making digital wireless telephony accessible to TTY/TDD users. The following extension is robust to frame and bit errors and is completely interoperable with the pre-existing 3GPP2 C.S0014-0 V1.0 speech-coding standard. The solution supports voice carryover/hearing carryover (VCO/HCO). VCO allows a TTY/TDD user to switch between receiving TTY and talking into the phone. Similarly, HCO allows a user to switch between transmitting TTY characters and picking up the phone to listen. When Baudot tones are not present, the vocoder operates as usual, there is no modification or added delay to the voice path when speech is present.

The TTY/TDD audio solution transports Baudot signals through the vocoder by detecting the characters, and their baud rate, that are being transmitted by the TTY/TDD in the encoder and conveying those characters to the decoder. Because one Baudot character spans at least 7 speech processing frames, the character being transmitted shall be sent a minimum of 6 times to the decoder, allowing the decoder to correctly regenerate the character despite frame errors and random bit errors in the speech packet.

The TTY characters are concealed in the speech packet in a way that interoperates with legacy vocoders that have not been modified for TTY. This is made possible because, when Baudot tones are present, the TTY information replaces the pitch lag bits for the adaptive codebook (ACB) and the ACB gain is set to zero so that an unmodified decoder ignores the TTY information. The rest of the bits in the speech packet contain information for an unmodified decoder to reconstruct the Baudot signal with the fixed codebook and the linear prediction (LPC) filter at least as well as if the encoder was not modified. Furthermore, the encoder shall disable noise suppression, and the rate shall be set to full rate when the Baudot tones are present. This further enhances the system’s performance when a modified encoder is interoperating with an unmodified decoder.

1 A decoder modified with this extension maintains a history buffer to monitor the ACB gain and pitch lag in the
2 speech packets. When the decoder detects that the ACB gain has been set to zero, and the pitch lag contains
3 information consistent with TTY, the decoder stops decoding speech and begins regenerating the Baudot tones.
4 When the decoder stops detecting TTY information, it resumes processing speech.

5 When Baudot tones are not present, the modified vocoder operates on speech in exactly the same way as the
6 unmodified vocoder. The TTY processing does not add any additional delay to the speech path.

7 **6.3 TTY/TDD Extension**

8 The TTY processing in the encoder shall process the received PCM one frame at a time and label each frame as
9 NON_TTY, or as TTY_SILENCE, or as a TTY character. The vocoder will be in one of two states:
10 TTY_MODE or NON_TTY_MODE. In the absence of Baudot tones, the encoder and decoder shall be in the
11 NON_TTY_MODE, and the encoder and decoder shall process the frame as speech. When Baudot tones are
12 present, the encoder and decoder shall enter TTY_MODE and process the TTY information as described
13 below.

14 There shall exist a mechanism to disable the TTY/TDD extension in the vocoder, reverting the vocoder to its
15 unmodified state.

16 **6.3.1 TTY Onset Procedure**

17 The TTY Onset Procedure describes the process by which the vocoder shall transition from the speech mode to
18 the TTY mode.

19 **6.3.1.1 Encoder TTY Onset Procedure**

20 When the TTY encoder processing initially detects that Baudot tones are present, the encoder shall label each
21 frame as TTY_SILENCE until it buffers enough frames to detect the character being sent. The TTY_SILENCE
22 message shall be sent to the decoder according to the method described below. Because of the delay caused by
23 the buffering in the encoder and decoder to detect TTY characters, it is necessary to alert the decoder to mute
24 its output when Baudot tones are first detected. This prevents the Baudot tones from getting through the speech
25 path before the TTY decoder processing is able to detect the TTY characters and regenerate the tones. The
26 TTY_SILENCE message shall be sent to the decoder within 2 frames after the PCM containing the Baudot
27 tones initially enters the encoder. However, in order to reduce the risk of false alarms, the TTY encoder may
28 delay sending the TTY_SILENCE message for the very first character in a call. The TTY_SILENCE message
29 shall be sent for a minimum of 4 frames and shall continue to be sent until a TTY character is detected, or until
30 a NON_TTY frame is detected.

31 **6.3.1.2 Decoder TTY Onset Procedure**

32 When the decoder is in NON_TTY_MODE, the packet shall be decoded in the usual manner for speech.
33 Because there are no bits in the packet to switch the decoder's state, the decoder shall infer the presence of TTY
34 information from the ACB gain and pitch information. The decoder shall recognize when TTY_SILENCE
35 messages are being sent in the packets and transition from NON_TTY_MODE to TTY_MODE before the
36 decoder's speech path reconstructs a TTY character from the audio information in the speech packets. When
37 the decoder makes the transition to TTY_MODE, it shall mute its output until it detects TTY characters or until
38 it transitions back to NON_TTY_MODE. Refer to the implementation recommendation in Section 6.3.4 for an
39 example of the TTY decoder processing.

6.3.1.3 TTY_MODE PROCESSING

The format of the Baudot code can be found in ITU-T Recommendation V.18. The Baudot code is a carrierless, binary FSK signaling scheme. A 1400 Hz. tone is used to signal a logical “1” and an 1800 Hz. tone is used to signal a logical “0”. A TTY bit has a duration of 22 ± 0.4 ms for 45.45 baud and 20 ± 0.4 ms for 50 baud. A character consists of 1 start bit, 5 data bits, and 1.5 – 2 stop bits. When a character is not being transmitted, silence, or a noisy equivalent, is transmitted. Hence, a TTY character spans a minimum of 7 speech processing frames. When the TTY encoder processing detects a character, it shall send the character, its baud rate, and its header (see Section 6.3.2) for a description of the header) to the decoder over a minimum of 6 consecutive frames and a maximum of 16 frames. Because channel impairments cause frame errors and bit errors, the decoder may not receive all of the packets sent by the encoder. The decoder shall use the redundancy to correct any corrupted TTY information. Once the decoder recognizes the TTY character being sent, the decoder’s TTY repeater shall regenerate the Baudot tones corresponding to that character.

At call startup, the encoder processing may initialize its baud rate to either 45.45 baud or 50 baud. It is recommended that the default baud rate be set to the predominant baud rate of the region. Because the encoder may require several characters to determine the correct baud rate, it should be expected that the baud rate may change 3-7 characters into the TTY call.

6.3.1.4 TTY_SILENCE Processing

In order to reduce the average data rate of a TTY call, the TTY processing shall be capable of transmitting 1/8 rate packets to the decoder when the encoder is processing the silence periods between characters. Since no TTY information is in the 1/8 packet, the decoder shall infer TTY_SILENCE from an 1/8 rate packet when it is in TTY_MODE. The TTY_SILENCE message may also be sent to the decoder using a full rate frame, as described in Section 6.3.2. When setting the rate to accommodate the TTY information, care shall be taken so that a full rate frame is not immediately followed by an 1/8 rate frame. This is an illegal rate transition according to C.S0014-0 V1.0, and will force an unmodified decoder to declare a frame erasure.

6.3.2 TTY Header, Baud Rate, and Character Format

The TTY information put into the speech packet contains header character, and baud rate information. When the encoder is transmitting a TTY character, the header shall contain a sequence number to distinguish that character from its preceding and following neighbors. The same header, character, and baud rate information shall be transmitted for each instance of a character for a minimum of 6 frames and a maximum of 16 frames. The header shall cycle through its range of valid values, one value for each instance of a character. The header and character field shall be assigned a value to correspond to the TTY_SILENCE message. TTY_SILENCE may also be conveyed by 1/8 rate packets (see Section 6.3.1.4).

The rate bit shall specify the baud rate to be regenerated by the decoder. The rate bit shall be set to ‘0’ to denote 45.45 baud and ‘1’ to denote 50 baud. During the TTY_SILENCE message, the baud rate bit shall be set to its last transmitted value. In the case where the baud rate has not yet been determined, the default startup baud rate shall be used. The encoder processing may initialize its baud rate to either 45.45 baud or 50 baud.

1

2

Table 6.3.2-1: TTY Header and Character Fields

Description	Range		
	Header (2 bits)	Character (5 bits)	Baud Rate (1 bit)
Reserved	0	0 – 31	0-1
TTY Character	1 – 2	0 – 31	0-1
TTY SILENCE	3	4	0-1
Reserved	3	0 – 3, 5 – 31	0-1

3

4 The combinations of valid values for the TTY header, character, and baud rate fields are specified in Table
5 6.3.2-1. Note that the value for TTY_SILENCE corresponds to the index for the maximum pitch value allowed
6 by the vocoder. All unused values are reserved for future use and shall be considered as invalid values for the
7 purposes of this annex.

8 6.3.3 Transporting the TTY Information in the Speech Packet.

9 In full rate and half rate, there are 7 bits per frame assigned to the pitch lag. In full rate, the last bit of the
10 speech packet, Bit 171, is reserved by the speech coder. This bit plus the 7 bits assigned to the pitch lag shall
11 be used to convey TTY information from the encoder to the decoder using full rate frames. Half rate packets
12 may also be used for conveying TTY information. Because half rate packets have only 7 bits available, i.e., the
13 7 pitch lag bits, half rate frames shall contain the TTY header and TTY character information only and the
14 decoder shall use its last valid baud rate to regenerate TTY characters. In order to improve interoperability
15 between a modified encoder and an unmodified decoder, it is recommended to transport the TTY information in
16 a full rate packet; however, a modified decoder shall be capable of detecting TTY information in both full rate
17 and half rate packets.

18 The TTY information replaces the pitch lag bits and the reserved Bit 171. The ACB gain shall be set to zero for
19 each subframe in packets containing TTY information. Bit 171 shall be used to convey the baud rate
20 information and the 7 pitch lag bits shall be used to convey the TTY header and character information. The 5
21 least significant bits of the pitch bits shall be used for the 5-bit Baudot code. Two remaining pitch bits shall be
22 used for the TTY header information. The TTY information is assigned to the pitch lag bits according to Table
23 6.3.3-1.

Table 6.3.3-1: TTY Header and Character Bit Assignment

PITCH LAG BIT ASSIGNMENT						
MSB						LSB
6	5	4	3	2	1	0
TTY HEADER		5 BIT BAUDOT CODE				
MSB	LSB	MSB				LSB
1	0	4	3	2	1	0

6.3.3.1 Half Rate TTY Mode

In the case where the encoder and decoder are both modified for TTY, it is possible to

reduce the average data rate by using half rate packets to transport TTY information. Half rate packets should only be used to transport TTY information during Dim & Burst signaling, or when it is determined that both the near-end and far-end vocoders are TTY capable. When the near-end (far-end) decoder recognizes that the far-end (near-end) encoder is sending TTY information, the near-end (far-end) encoder may be notified by the near-end (far-end) decoder to send TTY information in half rate packets. When the near-end (far-end) decoder receives a NON_TTY packet, the near-end (far-end) encoder should exit half rate TTY mode. This preserves interoperability in the event of a hard handoff from a modified vocoder to an unmodified vocoder. Because half rate packets do not convey the baud rate, the vocoder should return to full rate for at least 4 characters after a change in baud rate before returning to half rate TTY mode, whenever possible. In Dim & Burst signaling, for example, it may be more desirable to stay in half rate TTY mode to complete the signaling message rather than go to full rate to convey a baud rate change.

6.3.3.2 Interoperability with 45.45 Baud-Only TTY Extensions

Previous TTY extensions support 45.45 bps Baudot code only. This extension supports both 45.45 baud and 50 baud by using an additional bit to convey the baud rate. Note, the other 7 bits used for the character information and header are the same as the 45.45 baud-only TTY extensions.

Because the baud rate uses a bit in the encoded speech packet that was not previously used for TTY, some level of interoperability is achieved (See Table 6.3.3.2-1). When a 45.45 baud decoder is receiving 50 baud TTY packets, it will regenerate the characters at 45.45 baud. In this case, the regenerator may fall behind and drop characters because it is regenerating characters at a slower rate than the encoder is sending them.

Table 6.3.3.2-1: Baud Rate Interoperability Matrix

	45.45 baud-only decoder	45.45 and 50 baud decoder
45.45 baud-only encoder	Compatible	EITHER 45.45 OR 50 BAUD WILL BE REGENERATED BY THE DECODER, DEPENDING ON THE VALUE OF THE BAUD RATE BIT SET BY THE ENCODER.
45.45 and 50 baud encoder	BAUD RATE IS IGNORED AND DECODER ALWAYS REGENERATES 45.45 BAUD.	Compatible

In the case where the encoder is 45.45 baud-only and the decoder is capable of regenerating either 45.45 or 50 baud, the 2 header bits and the 5 TTY character bits are the same, so the decoder is able to decode these bits correctly. The baud rate bit, however, has no meaning to the 45.45 baud-only encoder, so it will be set randomly, depending on the implementation, and the baud rate used by the decoder will depend on the value of the baud rate bit.

In order for 45.45 baud-only implementations to interoperate with this extension, it is recommended that the 45.45 baud-only encoder implementations set the reserved Bit 171 to zero so that the baud rate bit is set to 45.45 baud.

6.3.3.3 Reflected Baudot Tones

It is possible for the signal generated by the TTY solution to reflect back to the near-end TTY detector, either on the network side or the mobile side. Possible sources of the reflected signal are crosstalk, impedance mismatch, or hybrid echo. To prevent the detector from detecting Baudot tones, that are not intentionally originated by the TTY device, the input PCM shall be muted, before being processed by the near-end encoder, whenever Baudot tones are being regenerated. This requirement applies to both the network and mobiles. Note, the sample solution described in Section 6.3.4 does not contain a mechanism for blocking reflected Baudot tones.

6.3.4 TTY/TDD Processing Recommendation

The following describes the software simulation of this annex. It is intended as a recommendation for implementation only and is not required to satisfy compliance with this annex. However, the software shall be used to resolve ambiguous or incomplete statements that may exist in the sections above. The TTY/TDD processing is divided into 2 major components, encoder processing and decoder processing. The TTY encoder process detects the presence of Baudot tones and decodes the TTY character being transmitted. It then conveys that information to the decoder. The TTY decoder processing shall detect the presence of TTY information and regenerate the Baudot tones corresponding to that character. Refer to Figure 6.3.4-1 for a block diagram of the TTY processing.




Figure 6.3.4-1. TTY/TDD Processing Block Diagram

6.3.5 TTY Encoder Processing

The TTY encoder processing takes the larger task of detecting TTY characters and divides it into a series of smaller tasks, creating different levels of detection. It is through this divide and conquer approach that the `ty_enc()` routine has low complexity in the absence of Baudot tones.

The first level of detection is to divide the 160 samples in the speech frame into 10 blocks of 16 samples. These blocks are called detection intervals, or dits. Each dit is classified as `NON_TTY`, `LOGIC_0`, or `LOGIC_1`.

The next level of detection is to determine if there are enough `LOGIC_0` or `LOGIC_1` dits in a row to form a TTY bit. The transition from a “0” bit to a “1” bit or the detection of two consecutive “0” bits signals the onset of a character and the `TTY_SILENCE` message is sent to the decoder. The `TTY_SILENCE` message shall continue to be sent until a TTY character is detected, or until a `NON_TTY` frame is detected. When enough bits are detected to form a character, the rate of the character is determined and the TTY character information is sent to the decoder.

6.3.5.1 TTY Encoder Inputs

- TTY character information from the previous frame (header, TTY character, and baud rate).
- 160 PCM samples from the output of the high pass filter.

6.3.5.2 Dit Classification

The 160 samples from the high pass filter's output are converted into 10 dits. For every block of 16 samples, it computes the spectral energy at the mark and space frequencies using a 16-point DFT at 1400 Hz and 1800 Hz with a rectangular window. The ratio of the maximum energy between the mark and space energy and the total energy is compared to a threshold; i.e.,

$$\frac{\max(\text{mark_energy}, \text{space_energy})}{\text{total_energy}} > \text{THRESH}$$

If that threshold is exceeded, the dit is labeled as either a mark or a space, whichever one has the greater energy. If the threshold is not met, the dit is labeled as NON_TTY.

6.3.5.3 Dits to Bits

The dits are used to form a TTY bit. Dits are classified as LOGIC_0, LOGIC_1, or UNKNOWN. A nominal bit consists of 11 dits for 45.45 baud and 10 dits for 50 baud. A bit is not required to have a continuous run of LOGIC_0's or LOGIC_1's in order to be detected. Spurious UNKNOWN detections are permitted, up to a threshold.

A TTY bit is searched by looking at the dits within a variable-length sliding window. The window varies in length from 8 dits to 13 dits. The number of LOGIC_0's, LOGIC_1's, and UNKNOWN dit detections are counted in the window. The dits in the search window must meet the following criteria in order to detect a TTY bit:

- Minimum of 6 LOGIC_0 (LOGIC_1) dits
- Maximum of 2 LOGIC_1 (LOGIC_0) dits
- Maximum of 5 UNKNOWN dits

Heuristics are also applied so that the sliding window is centered over the TTY bit being detected. If all of the thresholds are met, a "0" ("1") TTY bit is declared, and the overall length of the bit and the number of bad dits within the window are recorded. If the dits in the search window do not meet the criteria for a TTY bit, a gap between TTY bits is declared and the gap is recorded. The window is slid by one dit and the search is repeated.

The length of the search window is allowed to vary. The length is adjusted depending on the previous character's baud rate, and where the mark/space transitions occur.

Two history buffers are maintained to record the detected TTY bits and gaps. The array `tty_bit_hist[]` maintains a history of the bits that are detected and `tty_bit_len_hist[]` stores the lengths, in dits, of the gaps and TTY bits that are detected. Both arrays are 9 elements long, there is one element for the start bit, five for the data bits, one for the stop bit, and one for the memory bit, the bit before the start bit, as depicted in Figure 6.3.5.3-1. The last element in the array is used to record partially detected TTY bits.

Figure 6.3.5.3-1 TTY Bit History Buffer

0	1	2	3	4	5	6	7	8
Memory Bit	Start Bit	LSB Data 0	Data 1	Data 2	Data 3	MSB Data 4	Stop Bit	Next Bit

When a TTY bit or a gap is detected, its value is recorded in `tty_bit_hist[]` and its length is stored in `tty_bit_len_hist[]`. The length is used by `get_tty_char()` to threshold the length of a candidate character, and by `tty_rate()` to determine if a detected character is 45.45 baud or 50 baud. Since the length of the memory bit is irrelevant, `tty_bit_len_hist[0]` is used to count the number of NON_TTY and TTY_SILENCE dits that were detected within the TTY bits.

Because the speech frames may not coincide with the boundaries of the TTY bits, it is possible that a bit may straddle two speech frames. It is possible, therefore, that the sliding window may contain only a partial bit within a frame. These partial detections are recorded in element 8 of the TTY bit history buffers, labeled “Next Bit” in Figure 6.3.5.3-1.

6.3.5.4 TTY Character Classification

The routine `get_tty_char()` checks if the detected bits form a TTY character. The following conditions must be met in order for a character to be declared.

- The bit preceding the start bit must not be a “0”.
- The start bit must be a “0”
- The stop bit must be a “1”
- The length of the candidate character, in dits, must be within a maximum and minimum threshold.
- The number of bad dit detections within the character must be within a threshold.

If all of the conditions are met, a character is declared.

Once a character is found, the character information and its header are sent to the decoder a minimum of 6 frames and a maximum of 16 frames. The constant `FRAMING_HANGOVER` dictates the maximum number of times the information for the same character is sent. If a new character is framed before `FRAMING_HANGOVER` is reached, the information for the old character is terminated and the new information is sent to the decoder.

6.3.5.5 TTY Baud Rate Determination

After a character has been detected, `tty_rate()` determines the baud rate of the character by counting the length, in dits, of the start bit and the five data bits. The length of the stop bit is not used because its length is too variable.

A character with a length of 63 dits or greater is declared 45.45 baud, otherwise it is declared 50 baud. A hangover of three characters is maintained before `tty_rate()` will switch from one baud rate to the other. That is to say, if the baud rate changes in the middle of a call, three consecutive characters must be detected at the new baud rate in order for `tty_rate()` to declare the new baud rate.

6.3.5.6 TTY State Machine

The routine `get_tty_state()` is responsible for changing the state of the TTY encoder processing. There are 3 states, `NON_TTY_MODE`, `TTY_ONSET`, and `TTY_MODE`. `Get_tty_state()` is responsible for determining `NON_TTY_MODE` and `TTY_ONSET`.

1 Changing TTY state from NON_TTY_MODE to TTY_ONSET requires that a “0” bit is followed by a “1” bit.
 2 This rule requires the presence of both the space tone and the mark tone and for the tones to be the correct
 3 duration. This test must be met in order to declare TTY_ONSET for the first time.

4 NON_TTY_MODE is declared by get_tty_state() whenever a non-TTY bit is detected or when a “0” bit
 5 occupies the bit preceding the start bit.

6 6.3.6 TTY/TDD Decoder Processing

7 The TTY decoder processing must recognize when TTY/TDD information is in the packet, recover from
 8 channel impairments to decode the TTY character being sent, and regenerate the Baudot tones corresponding to
 9 that character.

10 When the decoder is in NON_TTY_MODE, the packet is decoded in the usual manner for speech. When the
 11 decoder makes the transition to TTY_MODE, it mutes its output until it receives TTY character information or
 12 until it transitions back to NON_TTY_MODE.

13 6.3.6.1 TTY Decoder Inputs

- 14 • TTY Information (header, TTY character, baud rate).
- 15 • Bad frame indicator

16 6.3.6.2 Decoding the TTY/TDD Information

17 The task of detecting the presence of TTY information, recovering from frame and bit errors, and decoding the
 18 TTY character is performed in tty_dec(). If the routine detects that TTY information is being sent, the tty_dec(
 19) flag is set to non-zero and the PCM buffer is filled with the appropriate Baudot tones. If TTY is not detected,
 20 the flag is set to zero and the PCM buffer is returned unmodified.

21 **Table 6.3.6.2-1: tty_dec() History Buffer**

Frame:	0	1	2	3	4	5	6	7	8	9	10
Description:	Lookahead									Current Frame	Lookback

22 The routine labels each frame as NON_TTY, TTY_SILENCE, FER, or a TTY character, and maintains a
 23 history buffer of these classifications for 11 frames: 9 frames of lookahead, 1 current frame, and 1 frame of
 24 lookback (see Table 6.3.6.2-1). The most recent packet enters the buffer at location 0, but the decision for the
 25 current frame is based on the contents of element 9. The buffer is updated at the end of each frame, shifting its
 26 contents to the right by one. The buffer is initialized to NON_TTY.

27 At the start of each frame, the most recent information is sanity checked to see if it is consistent with TTY
 28 information. If the frame erasure flag is set, the frame is labeled FER, otherwise the TTY/TDD information is
 29 checked to see if the header and TTY character fields fall within the allowed range of values. If all of the tests
 30 pass, Frame 0 is labeled with the TTY character in the history buffer.

31 The TTY decoder processing can reliably regenerate the TTY characters despite channel impairments because
 32 the character information is transmitted a minimum of 6 times from the encoder. Errors are corrected by a
 33 voting process. The current frame and nine frames of lookahead are used to determine the correct TTY header,
 34 character, and baud rate. Errors are replaced with the winner of the voting process.

35 Voting is conducted under the following conditions:

- 36 • Any time the current frame is labeled as FER.

- 1 • Every time the current frame contains information for the start of a new character. Because a new
2 character must contain a minimum of 6 frames of the same information, a vote is taken to verify that
3 the information is present before it will generate the tones for that character. Once a character wins
4 the vote, any frame errors, bit errors, or other inconsistencies are corrected in the frame window where
5 the character information is expected, i.e. the current frame and the adjacent frames of lookahead will
6 contain the same header and character information.
- 7 • Any time the current frame contains TTY_SILENCE or a TTY character, and the frame of lookback
8 contains NON_TTY. This makes it harder for the decoder to erroneously go into TTY_MODE, thus
9 preventing false alarms when speech is present.

10 In the normal course of TTY transmissions, TTY_SILENCE messages are sent first, followed by the TTY
11 character information. When 3 TTY_SILENCE messages are received in a window of 5 frames, the decoder's
12 output is muted until a NON_TTY frame is received or until the voting results in a TTY character to be
13 regenerated. If a new character is detected, it will only be regenerated if it was preceded by TTY_SILENCE.
14 If it is not, the character information is ignored and the decoder returns to NON_TTY mode. This is done to
15 prevent false alarms from packets that look like TTY packets but are really speech packets with the ACB gain
16 coincidentally set to zero.

17 Once `tty_dec()` makes its decision on the current frame, `tty_dec()` calls `tty_gen()` to generate the appropriate
18 PCM samples.

19 6.3.6.3 Baudot Generator

20 Once the current frame is labeled by `tty_dec()`, `tty_gen()` is called to fill the PCM buffer with the appropriate
21 Baudot tones. In the case of NON_TTY, the PCM buffer is returned unmodified. In the case of
22 TTY_SILENCE, the PCM is muted.

23 Generating TTY characters is more involved because one character spans many frames, so `tty_gen()` must
24 generate the Baudot tones one subframe at a time. When a TTY character needs to be regenerated, `tty_gen()`
25 puts a subframe's worth of samples in the PCM buffer. It keeps track of which bit it is in the middle of
26 generating and the number of samples left to generate for that bit, so that the next time it is called, it can pick up
27 where it left off. Once `tty_gen()` begins to generate a character, it will generate the entire character before it
28 will generate the next character. This is done so that the repeater will only generate valid TTY characters.

29 There exists logic in `tty_gen()` to detect when the next character arrives before the current one is finished. If
30 the next character arrives before the current one can be regenerated, a minimum of 1 stop bit is generated.

31 There exists a provision in the ITU-T Recommendation V.18 for the TTY/TDD device to extend its stop bit in
32 order to prevent a TTY/TDD device from detecting its own echo. This routine will extend the stop bit a
33 maximum of 300 ms if a TTY character is followed by silence. If a new character arrives before 300 ms has
34 elapsed, the extended stop bit is terminated and the new character is generated immediately.

35 The tones themselves are generated by `tone_gen()`. Before `tty_gen()` returns, it updates the decoder's
36 lookback field in the TTY history buffer with the information corresponding to the last samples generated. For
37 example, if `tty_gen()` finished generating a character in the middle of the subframe and started generating
38 silence, the lookback field is updated with TTY_SILENCE.

39 6.3.6.4 Tone Generator

40 The routine `tone_gen()` is a sine wave generator. Given a frequency and the number of samples, it will
41 generate the PCM samples by using a 2 tap marginally stable IIR filter. The filter implements the trigonometric
42 identity:

1
$$\cos(k\omega) = 2 \cdot \cos(\omega) \cdot \cos((k-1)\omega) - \cos((k-2)\omega)$$

- 2 It is a zero excitation filter, using only its past 2 samples and the cosine of the frequency to be generated, to
3 produce the next sample.

1

2 **7 EVRC-B DATA CAPABILITIES**3 **7.1 EVRC-B data capabilities**

4 EVRC-B provides the capability for passing data by replacing the speech allocated bits by general user data
 5 bits. This capability is called in-band or in-bitstream data. In this document, TTY/TDD Baudot Code (45.45
 6 baud and 50 baud) and DTMF are the only data payloads that are defined and supported by EVRC-B.

7 In-band TTY/TDD Baudot Code is mandatory. All EVRC-B implementations shall include in-band TTY/TDD
 8 capability. However, in-band DTMF is not always mandatory. Depending upon applications such as wireless
 9 local loop (fixed wireless) or mobility, in-band DTMF can be optional. In any case, in-band and out-of-band
 10 DTMF shall not be transmitted simultaneously.

11 For mobility applications, in-band DTMF signaling shall not be used.

12 For fixed wireless (also known as wireless local loop) applications, sending DTMF in the forward link is
 13 common (e.g., answering machine access). In order to guarantee that in-band DTMF can be decoded correctly
 14 in both forward and reverse links, implementing the in-band DTMF decoder is mandatory in both directions
 15 (forward and reverse), whereas implementing the in-band DTMF encoder is optional.

16 In-band data is transported with Rate 1/2 packet with data.

17 The TTY/TDD and DTMF features define their own error recovery schemes. The decoder, however, is capable
 18 of automatically detecting the in-band data by decoding the packet. No out-of-band signaling is required to
 19 send in-band data from the encoder to the decoder.

20 When the encoder sends in-band data to the decoder, the data is packed in Rate 1/2 frames and they contain a
 21 unique bit pattern that can be identified by the decoder to indicate that the packet contains data. The decoder
 22 then reads the header bits to determine which type of data is in the frame and calls the appropriate algorithm to
 23 regenerate the signal at the decoder's output, or to send the data to an appropriate application.

24 The bit allocation for Rate 1/2 data frames is summarized in Table 7-1.

25

Table 7-1 Bit allocation for rate 1/2 data frames

# of bits	Rate 1/2 data frame
3	Data Header
70	Data Block
7	Illegal Lag Codeword

26

27 For in-band data formats, a codeword is put in the packet that is considered illegal for speech frames. A packet
 28 is identified as containing data if these fields are set to the values below. The illegal codeword for each of the
 29 in-band data formats are in Table 7-2.

30

Table 7-2 Illegal codeword value

Codeword	Rate 1/2 data
Illegal Lag Codeword	0x78

1

2 Whereas the illegal codeword identifies the packet as containing data, the Data Header is a 3-bit field, which
 3 identifies the data format and payload. Table 7-3 contains a description of the Data Header field for Rate 1/2
 4 packets.

5

Table 7-3 Data header description

Data Header value	Rate 1/2 (bits 2 to 4)
0	Reserved
1	Data
2	TTY/TDD
3	DTMF
4	Reserved
5 to 7	Reserved

6

7 **7.2 TTY/TDD payload format**

8 The TTY/TDD payload shall be transported using the Rate 1/2 packet data format only. Rate 1 data formats
 9 shall not be used for this application. For TTY/TDD payloads, the Data Header field shall be set to 2 (see Table
 10 7-3) and the first 8 bits of the data field shall correspond to the TTY Type field. The Baudot code is currently
 11 the only TTY Type supported by this standard. Table 7-4 summarizes the valid values for the TTY Type field.

12

Table 7-4 TTY Type field

TTY Type	Description
0	Reserved
1	Baudot Code
2 to 255	Reserved

13

14 **7.3 Baudot code payload**

15 Payloads for TTY/TDD Baudot codes at 45.45 baud and 50 baud are defined for EVRC-B. For transmitting the
 16 Baudot code, the Data Field shall be set to 2 and TTY Type shall be set to 1. For Baudot, the bits in the Rate
 17 1/2 packet are defined as in Table 7-5.

1

Table 7-5 Rate 1/2 packet for TTY/TDD baudot code payload

# of bits	Field	Value
3	Data Header	2
8	TTY Type	1
8	TTY Header	See Table 7-8
16	TTY Character	See Table 7-9
16	TTY Rate	See Table 7-10
22	Reserved	N/A
7	Illegal Codeword	0x78

2

7.4 DTMF payload format

The DTMF payload shall be transported using the Rate 1/2 packet data format only. Rate 1 data formats shall not be used for this application. Table 7-6 shows a Rate 1/2 packet with the format for a DTMF payload. The Data Header field shall be set to 3 (see Table 7-3) and the first 16 bits of the data field shall correspond to a 16-bit signed value DTMF digit, as specified in Table 7-7.

Table 7-6 Rate 1/2 packet with DTMF payload

# of bits	Field	Value
3	Data Header	3
16	DTMF Digit	See Table 7-7
54	Reserved	N/A
7	Illegal Codeword	0x78

Table 7-7 DTMF data values

Data field	DTMF signal
1	1
2	2
3	4
5	5
6	6
7	7
8	8
9	9
10	0
11	*
12	#
13	A
14	B
15	C
16	D
-1	No signal detected

7.5 TTY/TDD operation

The following feature provides a method for reliably transporting the 45.45 bps and 50 bps Baudot code in the EVRC-B, making digital wireless telephony accessible to TTY/TDD users. The feature supports voice

1 carryover/hearing carryover (VCO/HCO). VCO allows a TTY/TDD user to switch between receiving TTY and
2 talking into the phone. Similarly, HCO allows a user to switch between transmitting TTY characters and
3 picking up the phone to listen. When Baudot tones are not present, the vocoder operates as usual; there is no
4 modification or added delay to the voice path when speech is present.

5 The Baudot code is specified in ITU-T Recommendation V.18. The Baudot code is a carrierless, binary FSK
6 signaling scheme. A 1400 Hz tone is used to signal a logical “1” and a 1800 Hz tone is used to signal a logical
7 “0”. A 45.45 bps TTY bit has a duration of $22 \text{ ms} \pm 0.4$ and a 50 bps bit has a duration of $20 \text{ ms} \pm 0.4$, and a
8 character consists of 1 start bit, 5 data bits, and 1.5 to 2 stop bits. When a character is not being transmitted,
9 silence, or a noisy equivalent, is transmitted. Hence, a TTY character spans a minimum of 6 speech processing
10 frames. When the TTY encoder processing detects a character, it sends the character and its header (see
11 Section 7.5.1 for a description of the header) to the decoder over a minimum of 6 consecutive frames and a
12 maximum of 16 frames. Because of channel impairments, the decoder may not receive all of the packets sent by
13 the encoder because of frame erasures and random bit errors. The decoder uses the redundancy to correct any
14 corrupted TTY information. Once the decoder recognizes the TTY character being sent, the decoder’s TTY
15 repeater regenerates the Baudot tones corresponding to that character. The TTY processing in the encoder
16 processes the received PCM input one frame at a time and labels each frame as either NON_TTY,
17 TTY_ONSET, or as a TTY character. The vocoder is in one of two states, TTY_MODE or
18 NON_TTY_MODE. In the absence of Baudot tones, the encoder and decoder are in the NON_TTY_MODE
19 and the encoder and decoder process the frame as speech. When Baudot tones are present, the encoder and
20 decoder enter TTY_MODE and process the TTY information as described in the following subsections. When
21 the vocoder stops detecting TTY information, it resumes processing speech.

22 It is recommended that a mechanism exist to disable the TTY/TDD feature in the vocoder.

23 Figure 7.5-1 depicts the TTY/TDD processing block diagram.




Figure 7.5-1 TTY/TDD processing block diagram

7.5.1 TTY header and character format

The TTY information passed from the encoder to the decoder contains a header, character information, and the baud rate. When the encoder is transmitting a TTY character, the header contains a sequence number to distinguish that character from the characters immediately before and after. The same TTY information is transmitted for each instance of a character for a minimum of 6 frames and a maximum of 16 frames. The header cycles through its range of valid values, one value for each instance of a character. During the TTY_ONSET state, the encoder sends the decoder a TTY_SILENCE message in the header and character field. The TTY header uses 2 bits in an 8-bit field (see Table 7-8). The TTY character uses 5 bits in a 16-bit field (see Table 7-9). The TTY baud rate uses 1 bit in a 16-bit field (see Table 7-10).

Table 7-8 Range of values for TTY/TDD Baudot header field

Range	Description
0	TTY_SILENCE
1 to 3	TTY Counter
4 to 255	Reserved

Table 7-9 Range of values for TTY/TDD Baudot character field

Range	Description
4	TTY_SILENCE (when TTY Header = 0)
0 to 31	TTY Character
32 to 65535	Reserved

Table 7-10 Range of values for TTY/TDD baud rate field

Range	Description
0	45.45 baud
1	50 baud
2 to 65535	Reserved

7.5.2 TTY encoder processing

The TTY encoder processing takes the larger task of detecting TTY characters and divides it into a series of smaller tasks, creating different levels of detection. It is through this divide and conquer approach that the `tty_enc()` routine has low complexity in the absence of Baudot tones.

The first level of detection is to divide the 160 samples in the speech frame into 10 blocks of 16 samples. These blocks are called detection intervals, or dits. Each dit is classified as NON_TTY, LOGIC_0, or LOGIC_1.

The next level of detection is to determine if there are enough LOGIC_0 or LOGIC_1 dits in a row to form a TTY bit. The transition from a "0" bit to a "1" bit is used to determine the onset of a TTY character and the TTY_SILENCE message is sent to the decoder. The TTY_SILENCE message shall continue to be sent until a TTY character is detected, or until a NON_TTY frame is detected. When enough bits are detected to form a character, the rate of the character is determined and the TTY character information is sent to the decoder.

7.5.2.1 TTY encoder inputs

TTY character information from the previous frame (header, TTY character, and baud rate)

160 PCM samples from the output of the high pass filter

7.5.2.2 Dit classification

The 160 samples from the high pass filter's output are converted into 10 dits. For every block of 16 samples, it computes the spectral energy at the mark and space frequencies using a 16-point DFT at 1400 Hz and 1800 Hz with a rectangular window. The ratio of the maximum energy between the mark and space energy and the total energy is compared to a threshold; i.e.:

$$\frac{\max(\text{mark_energy}, \text{space_energy})}{\text{total_energy}} > \text{THRESH}$$

If that threshold is exceeded, the dit is labeled as either a mark or a space, whichever one has the greater energy. If the threshold is not met, the dit is labeled as NON_TTY.

A second threshold is applied to the total energy of the dit. If the total energy is less than the threshold, the dit is classified as NON_TTY. This minimum energy threshold prevents the TTY detector from being overly sensitive to low level tones that may have been unintentionally reflected back into the TTY detector. The threshold is set at approximately -50 dBm.

7.5.2.3 Dits to bits

The dits are used to form a TTY bit. Dits are classified as LOGIC_0, LOGIC_1, or UNKNOWN. A nominal bit consists of 11 dits for 45.45 baud and 10 dits for 50 baud. A bit is not required to have a continuous run of LOGIC_0's or LOGIC_1's in order to be detected. Spurious UNKNOWN detections are permitted, up to a threshold.

A TTY bit is searched by looking at the dits within a variable length sliding window. The window varies in length from 8 dits to 13 dits. The number of LOGIC_0's, LOGIC_1's, and UNKNOWN dit detections are counted in the window. The dits in the search window must meet the following criteria in order to detect a TTY bit:

Minimum of 6 LOGIC_0 (LOGIC_1) dits

Maximum of 2 LOGIC_1 (LOGIC_0) dits

Maximum of 5 UNKNOWN dits

Heuristics are also applied so that the sliding window is centered over the TTY bit being detected. If all of the thresholds are met, a "0" ("1") TTY bit is declared, and the overall length of the bit and the number of bad dits within the window are recorded. If the dits in the search window do not meet the criteria for a TTY bit, a gap between TTY bits is declared and the gap is recorded. The window is slid by one dit and the search is repeated.

The length of the search window is allowed to vary. The length is adjusted depending on the previous character's baud rate, and where the mark/space transitions occur.

Two history buffers are maintained to record the detected TTY bits and gaps. The array tty_bit_hist[] maintains a history of the bits that are detected and tty_bit_len_hist[] stores the lengths, in dits, of the gaps and TTY bits that are detected. Both arrays are 9 elements long; there is one element for the start bit, five for the data bits, one for the stop bit, and one for the memory bit, the bit before the start bit, as depicted in Figure 7.5-2. The last element in the array is used to record partially detected TTY bits.

0	1	2	3	4	5	6	7	8
Memory Bit	Start Bit	LSB Data 0	Data 1	Data 2	Data 3	MSB Data 4	Stop Bit	Next Bit

Figure 7.5-2 TTY bit history buffer

When a TTY bit or a gap is detected, its value is recorded in `tty_bit_hist[]` and its length is stored in `tty_bit_len_hist[]`. The length is used by `get_tty_char()` to threshold the length of a candidate character, and by `tty_rate()` to determine if a detected character is 45.45 baud or 50 baud. Since the length of the memory bit is irrelevant, `tty_bit_len_hist[0]` is used to count the number of NON_TTY and TTY_SILENCE dits that were detected within the TTY bits.

Because the speech frames may not coincide with the boundaries of the TTY bits, it is possible that a bit may straddle two speech frames. It is possible, therefore, that the sliding window may contain only a partial bit within a frame. These partial detections are recorded in element 8 of the TTY bit history buffers, labeled “Next Bit” in Figure 7.5-2.

7.5.2.4 TTY character classification

The routine `get_tty_char()` checks if the detected bits form a TTY character. The following conditions must be met in order for a character to be declared:

The bit preceding the start bit must not be a “0”.

The start bit must be a “0”.

The stop bit must be a “1”.

The length of the candidate character, in dits, must be within a maximum and minimum threshold.

The number of bad dit detections within the character must be within a threshold.

If all of the conditions are met, a character is declared.

Once a character is found, the character information and its header are sent to the decoder a minimum of 6 frames and a maximum of 16 frames. The constant `FRAMING_HANGOVER` dictates the maximum number of times the information for the same character is sent. If a new character is framed before `FRAMING_HANGOVER` is reached, the information for the old character is terminated and the new information is sent to the decoder.

7.5.2.5 TTY baud rate determination

After a character has been detected, `tty_rate()` determines the baud rate of the character by counting the length, in dits, of the start bit and the five data bits. The length of the stop bit is not used because its length is too variable.

A character with a length of 63 dits or greater is declared 45.45 baud, otherwise, it is declared 50 baud. A hangover of three characters is maintained before `tty_rate()` will switch from one baud rate to the other. That is to say, if the baud rate changes in the middle of a call, three consecutive characters must be detected at the new baud rate in order for `tty_rate()` to declare the new baud rate.

7.5.2.6 TTY state machine

The routine `get_tty_state()` is responsible for changing the state of the TTY encoder processing. There are 3 states, `NON_TTY_MODE`, `TTY_ONSET`, and `TTY_MODE`. `Get_tty_state()` is responsible for determining `NON_TTY_MODE` and `TTY_ONSET`.

Changing TTY state from `NON_TTY_MODE` to `TTY_ONSET` requires that a “0” bit is followed by a “1” bit. This rule requires the presence of both the space tone and the mark tone and for the tones to be the correct duration. This test must be met in order to declare `TTY_ONSET` for the first time.

`NON_TTY_MODE` is declared by `get_tty_state()` whenever a non-TTY bit is detected or when a “0” bit occupies the bit preceding the start bit.

7.5.3 TTY/TDD decoder processing

The TTY decoder processing must recognize when TTY/TDD information is in the packet, recover from channel impairments to decode the TTY character being sent, and regenerate the Baudot tones corresponding to that character.

When the decoder is in `NON_TTY_MODE`, the packet is decoded in the usual manner for speech. When the decoder makes the transition to `TTY_MODE`, it mutes its output until it receives TTY character information or until it transitions back to `NON_TTY_MODE`.

7.5.3.1 TTY decoder inputs

TTY information (header, TTY character, baud rate)

Bad frame indicator

7.5.3.2 Decoding the TTY/TDD information

The task of detecting the presence of TTY information, recovering from frame and bit errors, and decoding the TTY character is performed in `tty_dec()`. If the routine detects that TTY information is being sent, the `tty_dec()` flag is set to nonzero and the PCM buffer is filled with the appropriate Baudot tones. If TTY is not detected, the flag is set to zero and the PCM buffer is returned unmodified.

The routine labels each frame as `NON_TTY`, `TTY_SILENCE`, `FER`, or a TTY character, and maintains a history buffer of these classifications for 11 frames: 9 frames of lookahead, 1 current frame, and 1 frame of lookback (see Figure 7.5-3). The most recent packet enters the buffer at location 0, but the decision for the current frame is based on the contents of element 9. The buffer is updated at the end of each frame, shifting its contents to the right by one. The buffer is initialized to `NON_TTY`.

Frame	0	1	2	3	4	5	6	7	8	9	10
Description	Lookahead									Current Frame	Lookback

Figure 7.5-3 `tty_dec()` history buffer

At the start of each frame, the most recent information is sanity checked to see if it is consistent with TTY information. If the frame erasure flag is set, the frame is labeled `FER`, otherwise, the TTY/TDD information is

1 checked to see if the header and TTY character fields fall within the allowed range of values. If all of the tests
2 pass, Frame 0 is labeled with the TTY character in the history buffer.

3 The TTY decoder processing can reliably regenerate the TTY characters despite channel impairments because
4 the character information is transmitted a minimum of 6 times from the encoder. Errors are corrected by a
5 voting process. The current frame and 9 frames of lookahead are used to determine the correct TTY header,
6 character, and baud rate. Errors are replaced with the winner of the voting process.

7 Voting is conducted under the following conditions:

8 Any time the current frame is labeled as FER.

9 Every time the current frame contains information for the start of a new character. Because a new
10 character must contain a minimum of 6 frames of the same information, a vote is taken to verify
11 that the information is present before it will generate the tones for that character. Once a character
12 wins the vote, any frame errors, bit errors, or other inconsistencies are corrected in the frame
13 window where the character information is expected, i.e., the current frame and the adjacent
14 frames of lookahead will contain the same header and character information.

15 Any time the current frame contains TTY_SILENCE or a TTY character, and the frame of lookback
16 contains NON_TTY. This makes it harder for the decoder to erroneously go into TTY_MODE,
17 thus preventing false alarms when speech is present.

18 Once `tty_dec()` makes its decision on the current frame, `tty_dec()` calls `tty_gen()` to generate the
19 appropriate PCM samples.

20 7.5.3.3 Baudot generator

21 Once the current frame is labeled by `tty_dec()`, `tty_gen()` is called to fill the PCM buffer with the appropriate
22 Baudot tones. In the case of NON_TTY, the PCM buffer is returned unmodified. In the case of
23 TTY_SILENCE, the PCM is muted.

24 Generating TTY characters is more involved because one character spans many frames, so `tty_gen()` must
25 generate the Baudot tones one subframe at a time. When a TTY character needs to be regenerated, `tty_gen()`
26 puts a subframe's worth of samples in the PCM buffer. It keeps track of which bit it is in the middle of
27 generating and the number of samples left to generate for that bit, so that the next time it is called, it can pick up
28 where it left off. Once `tty_gen()` begins to generate a character, it will generate the entire character before it will
29 generate the next character. This is done so that the repeater will only generate valid TTY characters.

30 There exists logic in `tty_gen()` to detect when the next character arrives before the current one is finished. If the
31 next character arrives before the current one can be regenerated, the bit duration is reduced by 4 samples and a
32 minimum of 1 stop bit is generated. Otherwise, nominal bit lengths are generated, i.e., 22 ms bits for 45.45
33 baud and 20 ms bits for 50 baud, and a minimum of 1.5 stop bits is generated for 45.45 baud, and a minimum
34 of 1.75 stop bits is generated for 50 baud.

35 There exists a provision in the ITU-T Recommendation V.18 for the TTY/TDD device to extend its stop bit in
36 order to prevent a TTY/TDD device from detecting its own echo. This routine will extend the stop bit a
37 maximum of 300 ms if a TTY character is followed by silence. If a new character arrives before 300 ms has
38 elapsed, the extended stop bit is terminated and the new character is generated immediately.

39 The tones themselves are generated by `tone_gen()`. Before `tty_gen()` returns, it updates the decoder's lookback
40 field in the TTY history buffer with the information corresponding to the last samples generated. For example,
41 if `tty_gen()` finished generating a character in the middle of the subframe and started generating silence, the
42 lookback field is updated with TTY_SILENCE.

1 7.5.3.4 Tone generator

2 The routine tone_gen() is a sine wave generator. Given a frequency and the number of samples, it will generate
 3 the PCM samples by using a 2 tap marginally stable IIR filter. The filter implements the trigonometric identity:

4
$$\cos(k\omega) = 2 \cdot \cos(\omega) \cdot \cos((k-1)\omega) - \cos((k-2)\omega)$$

5 It is a zero excitation filter, using only its past 2 samples and the cosine of the frequency to be generated, to
 6 produce the next sample.

7 **7.6 DTMF**

8 7.6.1 DTMF detector

9 The DTMF (Dual Tone Multiple Frequency) detector detects the presence and the information content of
 10 incoming DTMF tone signals. Its row and its column frequency, listed in Table 7-11, uniquely identify each
 11 key on the keypad. It outputs a 16-bit value associated with each of the 16 possible DTMF tone combinations.

12
 13 **NOTE** A row and a column tone is associated with each digit.

14 **Table 7-11 Touch-tone telephone keypad**

		Column frequency group			
		1209 Hz	1336 Hz	1477 Hz	1633 Hz
Row frequency group	697 Hz	1	2	3	A
	770 Hz	4	5	6	B
	852 Hz	7	8	9	C
	941 Hz	*	0	#	D

15
 16 7.6.1.1 Description of the DTMF detector

17 The DTMF detector consists of three main functions:

18 AGC – Normalizes the input frame.

19 Goertzel – Performs spectral analysis at the 8 frequencies and at the second harmonic of the column
 20 frequencies using an 80 point Goertzel algorithm. The Goertzel algorithm provides an efficient
 21 means of calculating the DFT energy at a specific frequency (see Oppenheim and Schafer, *Digital
 22 Signal Processing*, Prentice-Hall). In addition, a 160 point Goertzel algorithm is used at the first
 23 and fourth row frequency in order to satisfy the requirements found in Bellcore document *GR-
 24 506-CORE LSSGR: Signaling and Analog Interfaces*, Issue 1, June 1996.

25 Check – Checks the spectral energies to determine if a valid DTMF tone is detected.

26 7.6.1.2 Input

27 Pointer to 16-bit linear time series for current 20 msec. frame and 10 msec. look-ahead.

1 7.6.1.3 Output

2 16-bit valid DTMF tone digit if a tone is detected or 0xffff to indicate no DTMF present.

3 **8 SUMMARY OF NOTATION**

4 **Table 8-1. Summary of Noise Suppression Notation**

Parameter	Section	Name/Description
$\alpha(m)$	4.1.2.5	Exponential windowing factor.
$\alpha_{ch}(m)$	4.1.2.2	Channel energy smoothing factor.
$\Delta_E(m)$	4.1.2.5	Spectral deviation for the current frame.
$\{\gamma_{ch}\}$	4.1.2.8	Linear channel gains.
$\{\gamma_{dB}\}$	4.1.2.8	Channel gains (in dB).
γ_n	4.1.2.8	Overall gain factor.
μ_g	4.1.2.8	Gain slope.
$\{\sigma_q\}$	4.1.2.3	Quantized channel SNR indices, in 0.375 dB increments.
$\{\sigma'_q\}$	4.1.2.7	Modified, quantized channel SNR indices.
$\{\sigma''_q\}$	4.1.2.7	Limited, modified, quantized channel SNR indices.
ζ_d	4.1.2.11	Deemphasis factor.
ζ_p	4.1.2.1	Preemphasis factor.
D	4.1.2.1	Input overlap (delay).
$\{d(m)\}$	4.1.2.1	Input overlap buffer.
$E_{ch}(m)$	4.1.2.2	Channel energy estimate vector.
$E_{dB}(m)$	4.1.2.4	Estimated log power spectra for the current frame.
$\overline{E}_{dB}(m)$	4.1.2.4	Estimated long-term log power spectra for the current frame.
E_{init}	4.1.2.2	Minimum allowable channel noise initialization energy.
E_{min}	4.1.2.2	Minimum allowable channel energy.
$E_n(m)$	4.1.2.10	Channel noise energy estimate vector.
$E_{tot}(m)$	4.1.2.4	Total channel energy for the current frame.
f_H	4.1.2.2	Frequency combining table, high limit.
f_L	4.1.2.2	Frequency combining table, low limit.
$\{G(k)\}$	4.1.2.1	Frequency domain input DFT buffer.
$\{g(n)\}$	4.1.2.1	Time domain input DFT buffer.
$\{h'(n)\}$	4.1.2.11	Overlap-and-add output buffer.
$\{H(k)\}$	4.1.2.9	Frequency domain output DFT buffer.
$\{h(m)\}$	4.1.2.11	Time domain output DFT buffer.
L	4.1.2.1	Frame length = 80.
M	4.1.2.1	DFT sequence length = 128.
m	4.1.2.1	The current 10 ms frame.
N_c	4.1.2.2	Number of channels = 16.
$\{s'(n)\}$	4.1.2	Noise suppressor output signal.

$\{s_{hp}(n)\}$	4.1.2	High pass filter output/noise suppressor input signal.
V	4.1.2.3	Voice metric table.
$v(m)$	4.1.2.3	Voice metric sum.

1

2

Table 8-2. Summary of Model Parameter Estimation Notation

Parameter	Section	Name/Description
$\{s'(n)\}$	4.2	Noise suppressor output signal.
$\Omega(m)$	4.2	Vector of unquantized line spectral pairs for frame m .
$\gamma_{lpc}(m)$	4.2	LPC prediction gain for frame m .
$a(m)$	4.2	Vector of unquantized linear predictive coefficients for frame m .
$\{e(n)\}$	4.2	Prediction residual.
τ	4.2	Long-term predictor (pitch) delay.
β	4.2	Long-term prediction gain.
<i>LPCFLAG</i>	4.2	Spectral transition indicator.
$\{h(n)\}$	4.2.1	Impulse response of the formant filter.

3

Table 8-3. Summary of Rate Determination Algorithm Notation

Parameter	Section	Name/Description
β	4.2.3	Long-term prediction gain
$BE_{f(i)}$	4.3.1.1	Energy in the i th frequency band.
$B_{f(i)}(m)$	4.3.1.2	Background noise estimate for the i th frequency band in the m th frame.
$E_{sm_{f(i)}(m)}$	4.3.2.1	Smoothed energy estimate for the i th frequency band in the m th frame.
$f(i)$	4.3.1	Frequency span of band-pass filter i .
$h_i(n)$	4.3.1.1	Impulse response of the i th frequency band filter.
<i>Hangover</i>	4.3.1.4	Number of frames after a Rate 1 frame required before a non-Rate 1 frame can be encoded.
L_h	4.3.1.1	The length of the impulse response of the band-pass filters.
$lownoise(i)$	4.3.2.2	Lower bound on the background noise estimate in the i th frequency band.
$R_{ii}(k)$	4.3.1.1	k th value of the bandwidth expanded autocorrelation function for the current frame.
$R_{f(i)}(k)$	4.3.1.1	Autocorrelation function of the i th frequency band impulse response.
$Rate(m)$	4.3.1.3	Encoding rate for the m th frame
$S_{f(i)}(m)$	4.3.1.2	Signal energy estimate in the i th frequency band for the m th frame.
$SNR_{f(i)}(m)$	4.3.1.2	Quantized Signal-to-Noise Ratio in the i th frequency band for the m th frame.
$T_i(B,SNR)$	4.3.1.2	Thresholds used to determine the data rate as a function of the background noise and the quantized SNR in each frequency band i .

1

Table 7-4. Summary of Encoder/Decoder Notation

Parameter	Section	Name/Description
q_{rate}	4.4	Quantized LSP codebooks for each rate.
$\Omega_q(m)$	4.5, 5.2, 5.3	Vector of quantized LSPs for frame m .
$\Omega_{nq}(m)$	4.5	Vector of unquantized LSPs for frame m .
m	4.5, 5.2	Current frame number.
M'	4.5, 5.2	Current subframe number.
L	4.5, 5.2	Subframe size.
$LSPIDX$	4.5	Vector of LSP indices corresponding to the quantized LSPs.
$ACBGIDX(m')$	4.5	Adaptive codebook index.
$FCBSIDX(m')$	4.5	Fixed codebook shape index.
$FCBGIDX(m')$	4.5	Fixed codebook gain index
$\tau(m)$	4.5, 5.2	Pitch delay estimate for frame m .
$DELAY$	4.5	Delay transmission code.
$DDELAY$	4.5	Delay difference.
β	4.5, 5.2	Long-term prediction gain
$\{\epsilon(n)\}$	4.5, 5.2	Short-term prediction residual signal.
$\{\alpha_{zir}(n)\}$	4.5	Zero-input response of weighted filter.
$E(n)$	4.5, 5.2	Adaptive codebook excitation signal.
$E_T(n)$	4.5, 5.2	Adaptive codebook excitation signal.
τ_{acc}	4.5	Accumulated shift counter.
$shiftstate$	4.5	State of the shifted residual buffer.
$\hat{d}(m', j)$	4.5, 5.2	Interpolated delay estimates for each subframe, m' .
$g_c(m')$	4.5, 5.2	Fixed codebook gain for each subframe, m' .
$g_p(m')$	4.5, 5.2	Adaptive codebook gain for each subframe, m' .
$\{\hat{S}_w(n)\}$	4.5.4.9	Weighted modified original speech vector.
$\{x_w(n)\}$	4.5.4.10.1	Target vector in the perceptual domain.
n_m	4.5.6	Pointer to the last sample in the shifted residual.
$\{\hat{\epsilon}(n)\}$	4.5.6	Modified residual signal.
$\{\hat{\epsilon}_t(n)\}$	4.5.6	Modified residual target.
$FER_FLAG(m)$	5.1, 5.2, 5.3	Frame erasure flag for frame m .
$Rate$	5.1	Decoder rate of operation.

$last_valid_rate$	5.1	Last valid decoder rate of operation.
$E_{lv}(n)$	5.2.2.2	Last valid codebook memory.
$\{\hat{s}(n)\}$	5.2, 5.3	Decoder synthesized speech signal.
$\{\hat{s}_{pf}(n)\}$	5.2, 5.3	Decoder post-filtered synthesized speech signal.
$g_{avg}(m')$	5.2.3	Decoder average fixed codebook gain.
$g_{avg}(m')$	5.2.3	Decoder average adaptive codebook gain.

9 CODEBOOK MEMORIES AND CONSTANTS

Table 9-1. LSP Quantization Table, Rate 1, Codebook 1

j	$q_{rate}(1, 1, j)$	$q_{rate}(1, 2, j)$	j	$q_{rate}(1, 1, j)$	$q_{rate}(1, 2, j)$	j	$q_{rate}(1, 1, j)$	$q_{rate}(1, 2, j)$
1	1.420163E-2	1.938816E-2	23	3.891726E-2	5.657889E-2	45	3.185912E-2	4.621231E-2
2	2.916675E-2	6.517492E-2	24	6.048006E-2	1.045370E-1	46	6.189098E-2	7.332318E-2
3	2.066932E-2	4.975649E-2	25	2.691566E-2	3.571689E-2	47	4.417184E-2	5.792409E-2
4	3.947198E-2	9.558509E-2	26	4.111172E-2	7.333230E-2	48	7.935962E-2	1.411774E-1
5	2.270125E-2	3.966258E-2	27	4.126607E-2	4.851652E-2	49	2.474123E-2	3.236294E-2
6	5.387895E-2	6.283478E-2	28	7.180496E-2	1.062024E-1	50	3.365639E-2	8.046506E-2
7	2.905255E-2	5.734358E-2	29	3.380379E-2	4.243004E-2	51	3.379437E-2	5.449772E-2
8	4.482806E-2	1.153646E-1	30	5.918182E-2	7.974680E-2	52	6.536490E-2	9.527759E-2
9	1.941107E-2	3.468897E-2	31	4.701079E-2	6.285638E-2	53	2.933642E-2	4.284110E-2
10	4.375030E-2	6.752285E-2	32	9.420119E-2	1.300532E-1	54	5.278705E-2	8.161594E-2
11	3.554973E-2	4.940868E-2	33	1.942443E-2	2.727323E-2	55	4.007249E-2	6.181447E-2
12	6.992199E-2	8.672798E-2	34	3.708317E-2	6.648982E-2	56	6.758486E-2	1.171961E-1
13	2.778802E-2	4.657485E-2	35	2.801364E-2	5.159849E-2	57	3.030650E-2	3.869141E-2
14	5.791110E-2	6.745425E-2	36	5.344610E-2	9.259042E-2	58	4.831063E-2	7.423830E-2
15	4.746644E-2	5.502715E-2	37	2.549592E-2	4.328448E-2	59	4.375483E-2	5.228423E-2
16	7.888989E-2	1.224430E-1	38	5.518607E-2	7.361823E-2	60	8.323100E-2	1.098820E-1
17	2.217159E-2	3.026288E-2	39	3.398511E-2	6.053291E-2	61	3.756006E-2	4.532172E-2
18	3.391345E-2	7.177040E-2	40	6.181821E-2	1.345813E-1	62	6.601132E-2	7.975802E-2
19	3.179891E-2	4.989961E-2	41	2.356692E-2	3.552420E-2	63	5.032251E-2	5.901763E-2
20	6.115560E-2	8.733612E-2	42	5.108042E-2	6.795625E-2	64	8.771333E-2	1.631874E-1
21	2.675065E-2	3.967359E-2	43	3.834650E-2	5.234694E-2			
22	4.441010E-2	8.267313E-2	44	7.442758E-2	9.661083E-2			

Table 9-2. LSP Quantization Table, Rate 1, Codebook 2

j	$q_{rate}(2, 1, j)$	$q_{rate}(2, 2, j)$	j	$q_{rate}(2, 1, j)$	$q_{rate}(2, 2, j)$	j	$q_{rate}(2, 1, j)$	$q_{rate}(2, 2, j)$
1	5.219596E-2	8.384457E-2	23	9.266608E-2	1.467255E-1	45	7.772978E-2	1.202872E-1
2	1.058741E-1	1.286942E-1	24	1.792855E-1	2.197060E-1	46	1.306480E-1	1.843318E-1
3	5.483239E-2	1.338429E-1	25	7.064585E-2	9.999245E-2	47	6.919396E-2	1.842180E-1
4	1.177685E-1	1.940373E-1	26	1.065005E-1	1.794434E-1	48	2.039041E-1	2.497152E-1
5	5.360865E-2	1.113987E-1	27	8.792497E-2	1.252877E-1	49	7.076717E-2	9.031861E-2
6	1.199897E-1	1.474747E-1	28	1.536402E-1	1.978527E-1	50	1.084716E-1	1.619665E-1
7	8.003736E-2	1.429997E-1	29	8.884301E-2	1.124657E-1	51	7.168864E-2	1.510932E-1
8	1.640866E-1	2.098218E-1	30	1.482867E-1	1.675170E-1	52	1.387795E-1	2.188018E-1
9	5.210592E-2	9.952294E-2	31	8.165681E-2	1.692740E-1	53	6.759071E-2	1.267403E-1
10	8.675680E-2	1.859665E-1	32	2.078105E-1	2.310336E-1	54	1.334124E-1	1.688389E-1
11	7.773411E-2	1.315069E-1	33	6.149280E-2	8.362632E-2	55	9.618226E-2	1.587287E-1
12	1.605455E-1	1.819303E-1	34	1.144733E-1	1.367800E-1	56	1.864856E-1	2.365609E-1
13	7.422437E-2	1.104371E-1	35	6.871299E-2	1.380991E-1	57	8.234471E-2	1.021260E-1
14	1.186351E-1	1.753068E-1	36	1.105114E-1	2.153529E-1	58	1.003366E-1	1.949185E-1
15	6.615578E-2	1.644419E-1	37	5.556523E-2	1.222428E-1	59	9.959820E-2	1.364251E-1
16	1.968109E-1	2.166820E-1	38	1.205576E-1	1.610725E-1	60	1.824485E-1	2.036552E-1
17	6.053178E-2	9.454086E-2	39	8.322497E-2	1.554755E-1	61	9.788907E-2	1.211455E-1

18	1.062714E-1	1.480139E-1	40	1.616385E-1	2.282689E-1	62	1.454531E-1	1.836045E-1
19	5.874866E-2	1.477246E-1	41	6.291523E-2	1.062296E-1	63	9.583955E-2	1.721949E-1
20	1.348165E-1	2.015180E-1	42	8.291869E-2	2.067745E-1	64	2.232959E-1	2.464186E-1
21	6.596983E-2	1.164474E-1	43	8.847569E-2	1.358000E-1			
22	1.322972E-1	1.532673E-1	44	1.697722E-1	1.937739E-1			

Table 9-3. LSP Quantization Table, Rate 1, Codebook 3

j	$q_{rate}(3, 1, j)$	$q_{rate}(3, 2, j)$	$q_{rate}(3, 3, j)$	j	$q_{rate}(3, 1, j)$	$q_{rate}(3, 2, j)$	$q_{rate}(3, 3, j)$
1	1.364258E-1	1.686519E-1	2.046882E-1	257	1.476240E-1	1.812728E-1	2.047079E-1
2	1.857176E-1	2.287562E-1	2.519580E-1	258	1.937514E-1	2.209740E-1	2.617752E-1
3	1.227602E-1	1.859507E-1	2.794467E-1	259	1.320898E-1	1.948516E-1	2.835476E-1
4	1.964685E-1	2.644844E-1	2.893189E-1	260	2.077394E-1	2.705968E-1	2.922648E-1
5	1.256537E-1	1.505293E-1	2.761443E-1	261	1.277334E-1	1.668960E-1	2.838914E-1
6	1.963016E-1	2.417000E-1	2.882307E-1	262	2.053094E-1	2.478075E-1	2.836328E-1
7	1.400994E-1	2.223656E-1	2.746666E-1	263	1.542119E-1	2.250141E-1	2.700820E-1
8	2.599523E-1	2.753950E-1	3.109759E-1	264	2.675741E-1	2.844269E-1	3.093348E-1
9	1.584522E-1	1.885910E-1	2.073392E-1	265	1.688469E-1	1.870045E-1	2.024332E-1
10	1.956162E-1	2.213795E-1	2.870229E-1	266	2.024411E-1	2.167331E-1	2.930792E-1
11	1.694246E-1	2.016147E-1	2.756692E-1	267	1.636213E-1	2.156165E-1	2.827929E-1
12	2.123938E-1	2.642507E-1	3.179675E-1	268	2.255093E-1	2.662830E-1	3.178866E-1
13	1.829651E-1	1.995476E-1	2.295388E-1	269	1.891103E-1	2.056094E-1	2.221136E-1
14	2.152007E-1	2.624094E-1	2.824327E-1	270	2.212402E-1	2.602889E-1	2.925411E-1
15	1.464046E-1	2.369667E-1	2.900671E-1	271	1.555634E-1	2.468508E-1	2.896488E-1
16	2.453386E-1	3.033581E-1	3.422602E-1	272	2.484062E-1	3.052919E-1	3.553167E-1
17	1.374790E-1	1.582766E-1	2.392172E-1	273	1.271222E-1	1.580537E-1	2.541644E-1
18	2.019990E-1	2.201026E-1	2.695469E-1	274	2.049988E-1	2.194769E-1	2.783420E-1
19	1.183500E-1	2.302064E-1	2.835548E-1	275	1.333023E-1	2.296140E-1	2.869472E-1
20	2.255193E-1	2.722721E-1	3.060730E-1	276	2.367771E-1	2.679182E-1	3.082309E-1
21	1.356614E-1	1.916340E-1	2.659120E-1	277	1.408536E-1	2.034147E-1	2.732571E-1
22	1.957331E-1	2.319262E-1	3.143761E-1	278	2.076843E-1	2.345200E-1	3.245833E-1
23	1.679990E-1	2.277063E-1	2.769478E-1	279	1.771817E-1	2.295954E-1	2.835392E-1
24	2.501706E-1	3.016271E-1	3.210842E-1	280	2.613784E-1	3.011602E-1	3.217071E-1
25	1.334923E-1	2.012231E-1	2.338940E-1	281	1.485957E-1	2.077720E-1	2.469461E-1
26	2.064421E-1	2.387042E-1	2.775601E-1	282	2.143348E-1	2.480613E-1	2.722592E-1
27	1.790488E-1	1.957766E-1	2.806566E-1	283	1.763803E-1	1.968979E-1	2.922869E-1
28	2.061936E-1	2.640554E-1	3.330984E-1	284	1.981935E-1	2.754833E-1	3.490376E-1
29	1.751853E-1	1.911663E-1	2.575403E-1	285	1.761532E-1	1.932490E-1	2.695485E-1
30	2.283986E-1	2.452967E-1	3.089808E-1	286	2.369686E-1	2.500658E-1	3.068208E-1
31	1.808598E-1	2.435791E-1	2.966311E-1	287	1.760607E-1	2.540376E-1	3.035668E-1
32	2.761530E-1	3.082561E-1	3.468226E-1	288	2.829529E-1	3.017651E-1	3.539563E-1
33	1.371157E-1	1.800578E-1	2.209535E-1	289	1.453537E-1	1.836788E-1	2.347501E-1
34	1.813701E-1	2.267701E-1	2.703927E-1	290	1.938426E-1	2.306356E-1	2.678178E-1
35	1.252465E-1	1.796069E-1	3.103764E-1	291	1.389590E-1	1.867608E-1	3.131132E-1
36	1.907084E-1	2.877342E-1	3.134762E-1	292	1.999445E-1	2.776248E-1	3.250463E-1
37	1.304861E-1	1.604353E-1	3.002437E-1	293	1.429661E-1	1.713108E-1	3.030134E-1
38	1.973186E-1	2.563785E-1	2.784743E-1	294	2.077417E-1	2.586918E-1	2.887670E-1
39	1.585971E-1	2.373814E-1	2.629103E-1	295	1.717769E-1	2.402461E-1	2.732845E-1
40	2.618259E-1	2.777172E-1	3.313822E-1	296	2.710466E-1	2.851709E-1	3.274011E-1
41	1.641607E-1	1.858415E-1	2.356159E-1	297	1.698546E-1	1.875458E-1	2.244847E-1

42	2.094861E-1	2.214528E-1	2.921539E-1	298	2.152220E-1	2.273397E-1	2.950088E-1
43	1.668079E-1	2.136418E-1	2.706759E-1	299	1.755966E-1	2.179366E-1	2.748796E-1
44	2.298343E-1	2.883746E-1	3.062383E-1	300	2.346654E-1	2.895309E-1	3.164944E-1
45	1.821543E-1	2.008225E-1	2.401694E-1	301	1.899470E-1	2.049538E-1	2.469552E-1
46	2.249447E-1	2.698139E-1	2.914012E-1	302	2.372978E-1	2.683167E-1	2.906843E-1
47	1.639406E-1	2.503412E-1	2.783078E-1	303	1.699632E-1	2.533675E-1	2.925330E-1
48	2.567280E-1	2.951038E-1	3.532971E-1	304	2.706599E-1	2.971461E-1	3.561840E-1
49	1.402188E-1	1.766877E-1	2.467733E-1	305	1.525397E-1	1.701390E-1	2.527039E-1
50	2.152913E-1	2.292160E-1	2.642836E-1	306	2.191192E-1	2.359007E-1	2.697391E-1
51	1.210027E-1	2.183338E-1	3.223413E-1	307	1.422457E-1	2.181846E-1	3.282181E-1
52	2.542432E-1	2.739862E-1	2.962625E-1	308	2.614728E-1	2.780257E-1	3.023759E-1
53	1.603854E-1	1.837629E-1	2.815987E-1	309	1.535260E-1	1.907277E-1	2.928208E-1
54	1.878322E-1	2.374204E-1	3.297775E-1	310	2.092410E-1	2.498087E-1	3.247091E-1
55	1.777884E-1	2.267035E-1	3.023225E-1	311	1.751764E-1	2.386468E-1	3.063927E-1
56	2.751082E-1	2.937306E-1	3.123738E-1	312	2.732189E-1	3.039550E-1	3.205139E-1
57	1.701164E-1	1.852321E-1	2.461250E-1	313	1.639116E-1	1.896116E-1	2.562725E-1
58	2.217548E-1	2.399122E-1	2.868919E-1	314	2.269538E-1	2.401202E-1	2.927285E-1
59	1.950837E-1	2.083379E-1	2.883497E-1	315	1.955657E-1	2.119562E-1	2.973747E-1
60	2.375365E-1	2.750045E-1	3.397860E-1	316	2.410456E-1	2.884970E-1	3.363523E-1
61	1.883693E-1	2.043718E-1	2.573750E-1	317	1.949483E-1	2.094753E-1	2.563097E-1
62	2.472502E-1	2.605518E-1	3.021375E-1	318	2.478846E-1	2.633564E-1	3.112709E-1
63	1.669442E-1	2.469124E-1	3.188944E-1	319	1.691897E-1	2.358646E-1	3.362494E-1
64	2.781186E-1	3.130111E-1	3.653293E-1	320	2.860016E-1	3.254238E-1	3.596074E-1
65	1.452135E-1	1.630515E-1	2.249126E-1	321	1.562586E-1	1.767049E-1	2.143934E-1
66	2.056925E-1	2.208315E-1	2.528178E-1	322	2.089969E-1	2.239687E-1	2.608868E-1
67	1.211257E-1	1.963741E-1	3.001227E-1	323	1.357654E-1	2.035801E-1	3.055032E-1
68	2.155668E-1	2.656573E-1	2.992029E-1	324	2.189614E-1	2.794635E-1	2.994508E-1
69	1.091342E-1	1.784721E-1	2.883232E-1	325	1.340648E-1	1.783321E-1	2.901696E-1
70	2.035085E-1	2.403479E-1	2.963097E-1	326	2.132984E-1	2.400315E-1	3.003459E-1
71	1.531018E-1	2.254153E-1	2.848437E-1	327	1.643734E-1	2.264387E-1	2.871712E-1
72	2.502334E-1	2.777369E-1	3.248407E-1	328	2.507396E-1	2.808125E-1	3.353494E-1
73	1.663089E-1	1.941734E-1	2.116354E-1	329	1.636495E-1	1.971080E-1	2.211652E-1
74	2.012895E-1	2.260622E-1	2.932465E-1	330	2.081396E-1	2.308698E-1	2.961371E-1
75	1.495188E-1	2.142017E-1	2.838948E-1	331	1.591131E-1	2.181892E-1	2.955320E-1
76	2.218361E-1	2.852315E-1	3.200826E-1	332	2.398835E-1	2.818312E-1	3.260456E-1
77	1.895732E-1	2.065776E-1	2.303323E-1	333	1.893947E-1	2.081271E-1	2.384464E-1
78	2.312477E-1	2.468643E-1	2.898466E-1	334	2.329957E-1	2.596035E-1	2.934280E-1
79	1.391169E-1	2.591899E-1	2.980196E-1	335	1.605588E-1	2.551648E-1	3.028729E-1
80	2.445126E-1	2.826714E-1	3.612583E-1	336	2.535093E-1	2.960285E-1	3.677216E-1
81	1.225310E-1	1.685148E-1	2.708793E-1	337	1.301244E-1	1.748390E-1	2.604860E-1
82	2.043728E-1	2.303984E-1	2.717929E-1	338	2.102040E-1	2.335708E-1	2.830619E-1
83	1.426439E-1	2.224056E-1	2.920572E-1	339	1.523655E-1	2.253388E-1	3.037210E-1
84	2.426437E-1	2.774294E-1	2.971355E-1	340	2.405586E-1	2.771922E-1	3.058919E-1
85	1.520486E-1	1.969211E-1	2.610132E-1	341	1.637288E-1	1.947794E-1	2.692536E-1
86	2.178750E-1	2.458404E-1	3.081386E-1	342	2.257094E-1	2.409027E-1	3.180606E-1
87	1.901093E-1	2.310991E-1	2.801782E-1	343	1.920551E-1	2.298578E-1	2.898267E-1
88	2.543142E-1	2.940798E-1	3.396492E-1	344	2.627597E-1	3.042922E-1	3.356806E-1
89	1.566986E-1	2.085975E-1	2.280108E-1	345	1.660712E-1	2.068192E-1	2.397125E-1
90	2.250887E-1	2.500145E-1	2.762502E-1	346	2.239156E-1	2.501069E-1	2.852962E-1

3GPP2 C.S0014-B ver 1.0

91	1.782190E-1	1.982282E-1	3.041989E-1	347	1.884023E-1	2.037937E-1	3.030411E-1
92	2.085672E-1	2.923954E-1	3.467869E-1	348	2.306990E-1	2.870441E-1	3.498028E-1
93	1.710521E-1	2.034388E-1	2.626443E-1	349	1.820254E-1	2.140735E-1	2.634700E-1
94	2.302755E-1	2.588175E-1	3.119865E-1	350	2.372978E-1	2.650254E-1	3.178155E-1
95	1.853336E-1	2.457602E-1	3.105540E-1	351	1.892787E-1	2.588022E-1	3.048662E-1
96	2.894139E-1	3.110956E-1	3.464762E-1	352	2.972431E-1	3.171531E-1	3.565839E-1
97	1.503324E-1	1.675382E-1	2.401829E-1	353	1.586075E-1	1.786598E-1	2.419194E-1
98	1.799717E-1	2.371686E-1	2.608997E-1	354	1.948874E-1	2.416959E-1	2.621767E-1
99	1.498662E-1	1.978901E-1	3.079166E-1	355	1.581244E-1	2.117531E-1	3.113522E-1
100	2.107997E-1	2.881801E-1	3.297472E-1	356	2.169027E-1	2.987968E-1	3.209941E-1
101	1.317111E-1	1.659065E-1	3.228980E-1	357	1.492728E-1	1.749641E-1	3.153344E-1
102	2.148320E-1	2.528221E-1	2.975471E-1	358	2.216223E-1	2.561791E-1	3.039030E-1
103	1.837604E-1	2.375236E-1	2.746100E-1	359	1.759796E-1	2.435055E-1	2.858017E-1
104	2.555752E-1	2.754392E-1	3.460219E-1	360	2.645904E-1	2.855416E-1	3.451078E-1
105	1.826622E-1	1.994709E-1	2.160517E-1	361	1.801371E-1	2.052794E-1	2.222560E-1
106	2.092403E-1	2.224067E-1	3.023829E-1	362	2.107962E-1	2.263154E-1	3.144269E-1
107	1.840883E-1	2.113278E-1	2.825381E-1	363	1.791512E-1	2.094397E-1	2.932809E-1
108	2.411711E-1	2.970360E-1	3.159793E-1	364	2.497190E-1	2.912577E-1	3.271623E-1
109	1.968047E-1	2.118159E-1	2.416477E-1	365	1.987002E-1	2.158968E-1	2.499602E-1
110	2.427620E-1	2.585866E-1	2.932044E-1	366	2.407264E-1	2.648577E-1	2.996396E-1
111	1.589055E-1	2.650770E-1	2.898813E-1	367	1.712497E-1	2.681662E-1	3.035727E-1
112	2.580606E-1	3.189032E-1	3.478468E-1	368	2.695556E-1	3.161006E-1	3.565707E-1
113	1.487664E-1	1.668539E-1	2.668274E-1	369	1.505648E-1	1.841909E-1	2.686748E-1
114	2.159423E-1	2.299383E-1	2.760416E-1	370	2.169412E-1	2.408140E-1	2.789422E-1
115	1.384105E-1	2.392834E-1	3.279724E-1	371	1.353995E-1	2.605865E-1	3.326049E-1
116	2.437653E-1	2.884085E-1	3.060487E-1	372	2.561510E-1	2.878229E-1	3.061564E-1
117	1.701571E-1	1.899863E-1	2.812192E-1	373	1.663988E-1	1.887218E-1	2.930237E-1
118	2.191170E-1	2.580053E-1	3.265720E-1	374	2.292141E-1	2.615654E-1	3.274941E-1
119	1.921636E-1	2.236142E-1	2.986831E-1	375	1.982666E-1	2.329705E-1	2.991343E-1
120	2.735454E-1	3.120781E-1	3.307666E-1	376	2.870463E-1	3.071038E-1	3.272981E-1
121	1.624521E-1	2.049309E-1	2.533377E-1	377	1.758987E-1	2.118986E-1	2.513329E-1
122	2.238553E-1	2.376711E-1	3.032020E-1	378	2.320674E-1	2.446222E-1	2.994437E-1
123	1.939553E-1	2.123356E-1	3.075669E-1	379	1.907801E-1	2.120900E-1	3.250593E-1
124	2.299127E-1	2.975811E-1	3.374992E-1	380	2.315312E-1	3.141661E-1	3.427359E-1
125	1.893354E-1	2.041481E-1	2.786098E-1	381	1.950999E-1	2.095543E-1	2.794835E-1
126	2.423036E-1	2.731631E-1	3.153617E-1	382	2.404161E-1	2.696048E-1	3.280155E-1
127	1.550097E-1	2.880952E-1	3.359964E-1	383	1.718009E-1	2.822331E-1	3.147493E-1
128	2.737162E-1	3.312155E-1	3.625391E-1	384	2.692438E-1	3.384625E-1	3.799357E-1
129	1.523894E-1	1.726191E-1	1.905857E-1	385	1.599346E-1	1.779668E-1	2.008186E-1
130	1.969883E-1	2.263098E-1	2.461975E-1	386	2.019797E-1	2.306685E-1	2.567733E-1
131	1.205552E-1	2.063698E-1	2.811998E-1	387	1.340243E-1	2.109616E-1	2.846877E-1
132	1.937094E-1	2.719005E-1	3.013329E-1	388	2.037129E-1	2.830531E-1	3.033094E-1
133	1.367012E-1	1.540932E-1	2.822584E-1	389	1.445289E-1	1.647281E-1	2.850794E-1
134	1.972992E-1	2.536563E-1	2.903151E-1	390	2.062856E-1	2.486490E-1	2.963831E-1
135	1.434638E-1	2.438729E-1	2.755337E-1	391	1.581382E-1	2.343177E-1	2.796500E-1
136	2.584773E-1	2.732799E-1	3.211191E-1	392	2.649956E-1	2.799007E-1	3.186194E-1
137	1.544062E-1	1.937935E-1	2.158842E-1	393	1.665375E-1	1.842794E-1	2.145475E-1
138	2.059795E-1	2.242770E-1	2.857324E-1	394	2.030519E-1	2.351105E-1	2.887560E-1
139	1.745353E-1	2.084824E-1	2.796685E-1	395	1.684227E-1	2.039462E-1	2.874789E-1

140	2.188446E-1	2.724863E-1	3.270956E-1	396	2.317270E-1	2.740864E-1	3.247552E-1
141	1.776097E-1	2.129902E-1	2.391197E-1	397	1.853562E-1	2.141131E-1	2.290304E-1
142	2.291638E-1	2.591659E-1	2.835147E-1	398	2.424826E-1	2.606555E-1	2.830303E-1
143	1.573532E-1	2.399613E-1	3.042631E-1	399	1.675623E-1	2.420275E-1	2.994620E-1
144	2.456138E-1	3.168245E-1	3.429094E-1	400	2.388099E-1	3.190039E-1	3.584159E-1
145	1.429532E-1	1.619054E-1	2.537102E-1	401	1.379083E-1	1.547878E-1	2.656112E-1
146	2.101928E-1	2.228477E-1	2.711038E-1	402	2.110193E-1	2.246073E-1	2.799547E-1
147	1.268439E-1	2.167091E-1	2.977347E-1	403	1.375699E-1	2.251285E-1	3.093129E-1
148	2.310001E-1	2.801091E-1	2.997074E-1	404	2.292399E-1	2.761510E-1	3.152418E-1
149	1.529805E-1	1.939969E-1	2.728957E-1	405	1.604875E-1	1.954612E-1	2.831695E-1
150	2.128607E-1	2.415454E-1	3.165188E-1	406	2.185057E-1	2.381972E-1	3.303401E-1
151	1.711547E-1	2.224697E-1	2.937865E-1	407	1.819913E-1	2.330270E-1	2.932760E-1
152	2.519882E-1	3.042550E-1	3.312700E-1	408	2.545523E-1	3.143942E-1	3.363923E-1
153	1.331889E-1	2.079250E-1	2.553621E-1	409	1.440958E-1	2.266402E-1	2.505951E-1
154	2.120449E-1	2.421897E-1	2.889037E-1	410	2.151880E-1	2.514173E-1	2.850440E-1
155	1.846125E-1	2.011436E-1	2.863608E-1	411	1.876744E-1	2.044589E-1	2.941690E-1
156	2.182867E-1	2.767524E-1	3.445815E-1	412	2.304948E-1	2.684524E-1	3.523701E-1
157	1.835622E-1	1.994785E-1	2.621566E-1	413	1.850221E-1	1.990753E-1	2.719306E-1
158	2.331305E-1	2.495969E-1	3.158428E-1	414	2.425694E-1	2.553892E-1	3.113993E-1
159	1.898990E-1	2.468749E-1	2.971325E-1	415	1.951661E-1	2.491021E-1	2.989985E-1
160	2.750225E-1	3.224903E-1	3.469777E-1	416	2.836542E-1	3.146003E-1	3.556194E-1
161	1.423053E-1	1.926892E-1	2.161559E-1	417	1.514900E-1	1.977298E-1	2.324675E-1
162	1.956762E-1	2.222686E-1	2.765874E-1	418	2.000299E-1	2.301013E-1	2.819339E-1
163	1.332415E-1	1.977918E-1	3.228979E-1	419	1.387113E-1	1.918166E-1	3.457804E-1
164	1.848651E-1	2.971062E-1	3.261052E-1	420	1.965804E-1	3.047148E-1	3.405534E-1
165	1.502037E-1	1.767813E-1	2.915362E-1	421	1.381543E-1	1.885431E-1	2.994612E-1
166	2.031445E-1	2.596162E-1	2.991560E-1	422	2.056665E-1	2.689049E-1	3.055372E-1
167	1.654890E-1	2.383421E-1	2.874939E-1	423	1.724479E-1	2.335584E-1	2.936252E-1
168	2.710713E-1	2.895445E-1	3.195210E-1	424	2.701454E-1	2.986548E-1	3.285564E-1
169	1.685984E-1	1.988256E-1	2.303476E-1	425	1.754894E-1	1.913616E-1	2.355853E-1
170	2.138117E-1	2.344718E-1	2.909596E-1	426	2.205488E-1	2.347740E-1	2.953977E-1
171	1.746054E-1	2.172560E-1	2.856881E-1	427	1.856524E-1	2.223491E-1	2.798839E-1
172	2.285035E-1	2.961903E-1	3.165347E-1	428	2.294570E-1	3.045463E-1	3.246843E-1
173	1.871726E-1	2.205474E-1	2.396887E-1	429	1.869008E-1	2.154694E-1	2.518568E-1
174	2.288848E-1	2.635832E-1	3.013295E-1	430	2.349105E-1	2.712174E-1	2.998947E-1
175	1.778971E-1	2.581315E-1	2.814877E-1	431	1.851424E-1	2.560710E-1	2.932913E-1
176	2.595136E-1	3.072044E-1	3.487936E-1	432	2.638837E-1	3.071275E-1	3.625467E-1
177	1.452244E-1	1.787160E-1	2.591870E-1	433	1.609976E-1	1.789379E-1	2.558083E-1
178	2.190623E-1	2.382235E-1	2.604615E-1	434	2.256711E-1	2.437351E-1	2.686250E-1
179	1.436509E-1	2.097608E-1	3.158302E-1	435	1.550762E-1	2.303962E-1	3.210056E-1
180	2.501275E-1	2.791823E-1	3.051536E-1	436	2.517605E-1	2.796534E-1	3.142022E-1
181	1.489864E-1	2.012268E-1	2.825437E-1	437	1.569888E-1	2.074669E-1	2.899340E-1
182	2.083878E-1	2.356039E-1	3.453639E-1	438	2.174795E-1	2.596264E-1	3.406591E-1
183	1.858303E-1	2.216073E-1	3.107736E-1	439	1.768115E-1	2.310871E-1	3.175625E-1
184	2.809047E-1	2.954698E-1	3.254995E-1	440	2.829526E-1	2.998444E-1	3.368229E-1
185	1.729673E-1	1.970781E-1	2.458011E-1	441	1.820603E-1	1.987347E-1	2.519803E-1
186	2.194957E-1	2.447671E-1	2.935878E-1	442	2.258742E-1	2.524692E-1	2.933564E-1
187	1.839096E-1	2.150043E-1	3.003345E-1	443	2.008000E-1	2.177869E-1	3.022101E-1
188	2.453386E-1	2.685953E-1	3.483304E-1	444	2.474238E-1	2.868829E-1	3.478206E-1

3GPP2 C.S0014-B ver 1.0

189	1.929574E-1	2.066251E-1	2.673364E-1	445	2.011281E-1	2.147469E-1	2.622697E-1
190	2.548456E-1	2.686423E-1	3.035479E-1	446	2.539634E-1	2.694780E-1	3.121338E-1
191	1.768531E-1	2.593310E-1	3.162008E-1	447	1.910349E-1	2.557382E-1	3.325596E-1
192	2.909291E-1	3.156348E-1	3.687235E-1	448	2.910537E-1	3.314584E-1	3.685885E-1
193	1.571170E-1	1.735529E-1	2.287365E-1	449	1.572299E-1	1.853741E-1	2.253613E-1
194	2.125093E-1	2.305012E-1	2.522180E-1	450	2.080513E-1	2.383509E-1	2.642129E-1
195	1.425218E-1	2.019799E-1	2.930122E-1	451	1.468483E-1	2.130001E-1	3.001926E-1
196	2.149197E-1	2.780651E-1	3.141761E-1	452	2.186306E-1	2.902638E-1	3.090458E-1
197	1.359473E-1	1.810559E-1	2.754754E-1	453	1.436992E-1	1.878152E-1	2.837699E-1
198	1.984167E-1	2.416738E-1	3.051734E-1	454	2.073280E-1	2.450887E-1	3.089564E-1
199	1.595173E-1	2.315801E-1	2.954125E-1	455	1.642281E-1	2.278267E-1	3.089079E-1
200	2.582036E-1	2.873481E-1	3.203520E-1	456	2.619197E-1	2.913337E-1	3.315280E-1
201	1.748407E-1	1.928833E-1	2.112500E-1	457	1.706489E-1	2.021575E-1	2.178278E-1
202	2.021685E-1	2.270257E-1	3.048841E-1	458	2.077961E-1	2.347048E-1	3.067838E-1
203	1.695321E-1	2.118262E-1	2.973554E-1	459	1.721188E-1	2.140574E-1	3.101518E-1
204	2.300337E-1	2.915044E-1	3.265894E-1	460	2.291162E-1	2.809499E-1	3.337743E-1
205	1.950461E-1	2.117092E-1	2.277058E-1	461	1.966222E-1	2.166531E-1	2.332797E-1
206	2.379269E-1	2.524116E-1	2.977522E-1	462	2.377892E-1	2.589713E-1	3.046092E-1
207	1.537629E-1	2.465416E-1	3.147689E-1	463	1.551820E-1	2.630326E-1	3.189431E-1
208	2.360757E-1	3.035689E-1	3.706245E-1	464	2.493888E-1	3.169709E-1	3.777625E-1
209	1.386603E-1	1.679500E-1	2.735153E-1	465	1.513636E-1	1.750107E-1	2.782458E-1
210	2.138062E-1	2.272672E-1	2.862763E-1	466	2.198102E-1	2.323602E-1	2.850349E-1
211	1.250806E-1	2.440984E-1	3.025488E-1	467	1.426306E-1	2.406029E-1	3.041251E-1
212	2.357149E-1	2.812088E-1	3.089037E-1	468	2.427649E-1	2.837621E-1	3.154812E-1
213	1.516914E-1	2.108778E-1	2.638130E-1	469	1.574675E-1	2.075241E-1	2.756749E-1
214	2.207304E-1	2.527779E-1	3.164137E-1	470	2.287586E-1	2.490922E-1	3.281394E-1
215	1.849247E-1	2.394248E-1	2.851208E-1	471	1.908727E-1	2.381252E-1	2.948946E-1
216	2.595485E-1	3.098099E-1	3.264237E-1	472	2.663893E-1	3.143214E-1	3.386695E-1
217	1.629307E-1	2.199009E-1	2.361486E-1	473	1.706442E-1	2.259800E-1	2.473724E-1
218	2.341942E-1	2.499443E-1	2.775491E-1	474	2.364428E-1	2.530035E-1	2.882204E-1
219	1.708702E-1	1.982916E-1	3.214126E-1	475	1.854238E-1	2.048889E-1	3.146088E-1
220	2.315669E-1	2.750151E-1	3.697104E-1	476	2.173790E-1	2.945536E-1	3.678310E-1
221	1.800024E-1	2.067010E-1	2.712049E-1	477	1.885640E-1	2.151743E-1	2.729997E-1
222	2.380753E-1	2.540062E-1	3.238276E-1	478	2.451021E-1	2.597704E-1	3.218856E-1
223	1.991483E-1	2.542739E-1	3.074797E-1	479	1.984442E-1	2.611607E-1	3.170979E-1
224	2.874286E-1	3.250451E-1	3.486346E-1	480	2.990139E-1	3.289653E-1	3.566812E-1
225	1.452850E-1	1.913592E-1	2.496914E-1	481	1.582488E-1	1.922057E-1	2.460591E-1
226	1.946593E-1	2.408212E-1	2.773027E-1	482	2.023854E-1	2.479658E-1	2.717497E-1
227	1.531510E-1	1.943757E-1	3.275504E-1	483	1.617108E-1	2.137081E-1	3.273847E-1
228	2.040858E-1	2.985957E-1	3.214801E-1	484	2.144197E-1	3.055525E-1	3.337216E-1
229	1.560097E-1	1.810127E-1	3.009317E-1	485	1.618200E-1	1.898973E-1	3.105016E-1
230	2.109624E-1	2.557703E-1	3.080861E-1	486	2.194363E-1	2.650296E-1	3.092888E-1
231	1.854441E-1	2.490213E-1	2.740298E-1	487	1.883039E-1	2.496332E-1	2.854995E-1
232	2.744935E-1	2.894420E-1	3.387949E-1	488	2.693254E-1	2.998070E-1	3.417225E-1
233	1.769419E-1	1.944769E-1	2.220773E-1	489	1.724060E-1	2.109773E-1	2.277732E-1
234	2.163775E-1	2.307358E-1	3.036893E-1	490	2.202815E-1	2.340158E-1	3.128461E-1
235	1.896835E-1	2.146608E-1	2.884454E-1	491	1.832573E-1	2.220620E-1	2.910524E-1
236	2.408273E-1	2.981418E-1	3.273784E-1	492	2.425312E-1	3.095276E-1	3.303897E-1
237	2.017878E-1	2.194418E-1	2.393275E-1	493	2.075467E-1	2.246626E-1	2.444201E-1

238	2.488125E-1	2.658659E-1	2.933824E-1	494	2.458582E-1	2.702860E-1	3.051321E-1
239	1.820278E-1	2.682791E-1	2.939914E-1	495	1.848406E-1	2.720968E-1	3.125311E-1
240	2.564986E-1	3.199845E-1	3.626632E-1	496	2.742526E-1	3.212524E-1	3.746582E-1
241	1.587993E-1	1.754337E-1	2.673899E-1	497	1.664258E-1	1.844916E-1	2.682781E-1
242	2.242593E-1	2.366683E-1	2.776391E-1	498	2.284237E-1	2.430254E-1	2.811849E-1
243	1.492034E-1	2.265853E-1	3.452556E-1	499	1.600913E-1	2.529533E-1	3.358223E-1
244	2.506558E-1	2.922649E-1	3.135743E-1	500	2.621100E-1	2.955819E-1	3.133541E-1
245	1.580963E-1	2.021932E-1	2.987117E-1	501	1.677028E-1	2.015369E-1	3.018016E-1
246	2.288209E-1	2.485573E-1	3.447265E-1	502	2.378230E-1	2.598948E-1	3.382311E-1
247	1.879721E-1	2.341094E-1	3.042356E-1	503	1.972062E-1	2.454909E-1	3.178954E-1
248	2.856571E-1	3.148781E-1	3.369315E-1	504	2.984553E-1	3.192098E-1	3.409717E-1
249	1.626800E-1	2.178201E-1	2.574368E-1	505	1.711953E-1	2.243278E-1	2.627361E-1
250	2.240498E-1	2.467398E-1	3.007959E-1	506	2.306269E-1	2.533102E-1	3.012068E-1
251	2.013546E-1	2.182867E-1	3.130363E-1	507	2.048142E-1	2.218816E-1	3.259666E-1
252	2.380285E-1	2.981035E-1	3.535038E-1	508	2.229875E-1	3.063391E-1	3.507172E-1
253	1.988300E-1	2.128771E-1	2.729808E-1	509	2.008554E-1	2.153599E-1	2.841435E-1
254	2.506165E-1	2.676600E-1	3.206119E-1	510	2.509517E-1	2.661893E-1	3.333606E-1
255	1.709018E-1	2.693304E-1	3.344282E-1	511	1.756103E-1	2.937913E-1	3.403269E-1
256	3.049889E-1	3.361967E-1	3.652354E-1	512	2.917451E-1	3.406025E-1	3.813972E-1

Table 9-4. LSP Quantization Table, Rate 1, Codebook 4

j	$q_{rate}(4, 1, j)$	$q_{rate}(4, 2, j)$	$q_{rate}(4, 3, j)$	j	$q_{rate}(4, 1, j)$	$q_{rate}(4, 2, j)$	$q_{rate}(4, 3, j)$
1	2.774615E-1	3.169721E-1	3.954983E-1	65	2.491101E-1	3.256969E-1	4.117283E-1
2	3.365604E-1	3.601570E-1	3.814730E-1	66	3.459292E-1	3.685775E-1	3.884733E-1
3	3.105093E-1	3.317324E-1	3.668644E-1	67	3.132197E-1	3.392295E-1	3.875979E-1
4	3.374710E-1	3.967953E-1	4.123563E-1	68	3.514540E-1	3.987303E-1	4.126562E-1
5	2.796604E-1	3.665201E-1	3.853135E-1	69	2.934871E-1	3.757631E-1	3.944881E-1
6	3.160390E-1	3.856093E-1	4.013048E-1	70	3.244708E-1	3.942029E-1	4.088827E-1
7	3.099604E-1	3.434107E-1	4.247455E-1	71	3.127108E-1	3.577203E-1	4.140612E-1
8	3.542436E-1	4.086993E-1	4.221680E-1	72	3.665072E-1	4.081713E-1	4.238914E-1
9	2.955872E-1	3.337411E-1	3.874217E-1	73	2.999657E-1	3.319934E-1	4.078602E-1
10	3.334464E-1	3.869748E-1	4.013531E-1	74	3.349252E-1	3.861430E-1	4.115381E-1
11	3.234128E-1	3.652697E-1	3.851933E-1	75	3.347880E-1	3.661962E-1	3.933471E-1
12	3.427320E-1	4.031925E-1	4.199204E-1	76	3.478479E-1	4.059265E-1	4.305073E-1
13	2.776818E-1	3.824950E-1	4.042742E-1	77	2.859529E-1	3.952833E-1	4.161193E-1
14	3.182480E-1	3.959853E-1	4.313532E-1	78	3.238674E-1	4.064767E-1	4.424828E-1
15	3.037114E-1	3.803197E-1	4.371736E-1	79	3.167167E-1	3.844516E-1	4.394110E-1
16	3.782888E-1	4.070773E-1	4.226791E-1	80	3.867729E-1	4.118246E-1	4.278315E-1
17	2.381165E-1	3.424543E-1	4.246247E-1	81	2.380724E-1	3.623424E-1	4.309317E-1
18	3.456157E-1	3.686811E-1	4.008173E-1	82	3.464500E-1	3.790829E-1	4.065678E-1
19	3.176881E-1	3.419027E-1	4.056018E-1	83	3.165766E-1	3.564686E-1	3.962183E-1
20	3.663690E-1	3.890399E-1	4.061545E-1	84	3.665392E-1	3.895909E-1	4.210556E-1
21	2.993980E-1	3.520217E-1	3.999557E-1	85	3.082914E-1	3.713243E-1	4.078674E-1
22	3.249919E-1	3.900288E-1	4.194787E-1	86	3.364352E-1	3.915144E-1	4.229771E-1
23	3.230258E-1	3.681143E-1	4.020878E-1	87	3.230355E-1	3.804473E-1	4.095502E-1
24	3.623263E-1	4.169280E-1	4.327737E-1	88	3.652281E-1	4.279104E-1	4.436913E-1
25	2.726964E-1	3.592050E-1	4.268807E-1	89	2.720380E-1	3.765968E-1	4.336859E-1
26	3.465399E-1	3.696166E-1	4.156212E-1	90	3.576658E-1	3.777616E-1	4.091790E-1
27	3.341091E-1	3.557363E-1	3.967496E-1	91	3.364986E-1	3.642159E-1	4.092555E-1

28	3.374690E-1	4.103927E-1	4.259868E-1	92	3.480824E-1	4.176318E-1	4.332845E-1
29	2.994690E-1	3.806483E-1	4.182841E-1	93	3.027545E-1	3.959748E-1	4.337173E-1
30	3.213782E-1	4.111980E-1	4.287925E-1	94	3.316763E-1	4.175872E-1	4.362398E-1
31	3.278412E-1	3.693451E-1	4.343956E-1	95	3.332876E-1	3.807991E-1	4.396207E-1
32	3.806691E-1	4.260864E-1	4.427546E-1	96	3.881120E-1	4.369336E-1	4.508293E-1
33	2.689437E-1	3.429430E-1	3.986815E-1	97	2.560266E-1	3.480152E-1	4.229226E-1
34	3.381029E-1	3.763388E-1	3.920432E-1	98	3.457740E-1	3.817258E-1	3.967941E-1
35	3.235935E-1	3.487421E-1	3.725520E-1	99	3.256238E-1	3.503919E-1	3.873307E-1
36	3.475508E-1	3.928854E-1	4.211699E-1	100	3.568681E-1	3.985748E-1	4.231772E-1
37	3.041828E-1	3.598167E-1	3.816333E-1	101	3.012262E-1	3.869070E-1	4.033356E-1
38	3.142214E-1	4.021086E-1	4.200853E-1	102	3.281784E-1	4.020902E-1	4.193893E-1
39	3.013066E-1	3.626627E-1	4.292628E-1	103	3.143854E-1	3.690439E-1	4.343753E-1
40	3.717703E-1	3.986964E-1	4.314390E-1	104	3.723211E-1	4.116724E-1	4.405187E-1
41	2.745913E-1	3.355955E-1	4.200797E-1	105	2.904797E-1	3.481219E-1	4.262165E-1
42	3.445408E-1	3.904518E-1	4.064121E-1	106	3.444388E-1	3.826664E-1	4.173211E-1
43	3.252398E-1	3.783445E-1	3.946733E-1	107	3.348668E-1	3.762357E-1	4.044752E-1
44	3.566835E-1	3.905742E-1	4.338511E-1	108	3.590254E-1	4.047219E-1	4.348384E-1
45	2.635013E-1	3.952601E-1	4.231164E-1	109	2.791280E-1	4.111066E-1	4.353606E-1
46	3.375207E-1	3.925635E-1	4.434158E-1	110	3.481255E-1	3.987321E-1	4.469274E-1
47	3.145223E-1	3.809686E-1	4.226764E-1	111	3.270189E-1	3.901073E-1	4.417075E-1
48	3.762351E-1	4.172987E-1	4.314513E-1	112	3.908584E-1	4.198139E-1	4.351535E-1
49	2.618550E-1	3.686461E-1	4.042606E-1	113	2.553193E-1	3.704060E-1	4.321886E-1
50	3.555802E-1	3.779945E-1	3.958682E-1	114	3.546520E-1	3.883327E-1	4.029561E-1
51	3.277428E-1	3.538728E-1	4.110406E-1	115	3.216082E-1	3.544898E-1	4.282998E-1
52	3.629606E-1	3.994670E-1	4.146902E-1	116	3.751635E-1	3.988340E-1	4.141774E-1
53	3.094109E-1	3.737961E-1	3.926725E-1	117	3.119536E-1	3.914307E-1	4.125525E-1
54	3.310163E-1	4.008016E-1	4.317593E-1	118	3.425288E-1	3.963653E-1	4.324974E-1
55	3.325731E-1	3.686196E-1	4.174551E-1	119	3.337444E-1	3.764224E-1	4.205370E-1
56	3.491159E-1	4.268401E-1	4.439140E-1	120	3.535291E-1	4.292311E-1	4.596993E-1
57	2.897386E-1	3.637593E-1	4.105118E-1	121	2.880179E-1	3.780000E-1	4.340117E-1
58	3.552865E-1	3.893313E-1	4.134324E-1	122	3.556835E-1	3.807800E-1	4.231455E-1
59	3.365659E-1	3.602225E-1	4.241790E-1	123	3.443583E-1	3.721849E-1	4.312654E-1
60	3.399327E-1	4.092288E-1	4.401849E-1	124	3.539661E-1	4.141667E-1	4.429413E-1
61	3.008897E-1	4.000811E-1	4.179557E-1	125	3.047702E-1	4.125175E-1	4.341831E-1
62	3.170521E-1	4.222881E-1	4.422296E-1	126	3.359134E-1	4.245908E-1	4.463785E-1
63	3.273368E-1	3.843117E-1	4.302886E-1	127	3.437382E-1	3.847662E-1	4.352714E-1
64	3.989909E-1	4.294984E-1	4.434752E-1	128	4.109413E-1	4.406630E-1	4.521134E-1

Table 9-5. LSP Quantization Table, Rate 1/2, Codebook 1

j	$q_{rate}(1, 1, j)$	$q_{rate}(1, 2, j)$	$q_{rate}(1, 3, j)$	j	$q_{rate}(1, 1, j)$	$q_{rate}(1, 2, j)$	$q_{rate}(1, 3, j)$
1	1.352263E-2	1.820813E-2	3.939407E-2	65	2.104905E-2	2.918910E-2	4.600358E-2
2	2.293929E-2	3.578312E-2	1.053529E-1	66	3.648633E-2	4.623870E-2	1.070442E-1
3	2.091065E-2	3.041591E-2	8.939411E-2	67	2.686521E-2	3.929376E-2	8.411799E-2
4	1.889090E-2	3.827222E-2	1.378204E-1	68	2.729040E-2	5.538051E-2	1.415862E-1
5	2.051438E-2	2.854812E-2	7.397622E-2	69	2.484767E-2	3.632777E-2	7.624309E-2
6	4.695103E-2	6.840319E-2	1.091238E-1	70	5.254308E-2	7.757787E-2	1.145680E-1
7	3.155572E-2	5.691400E-2	8.570576E-2	71	4.077414E-2	5.399238E-2	9.076405E-2
8	3.811819E-2	7.777847E-2	1.925329E-1	72	5.730433E-2	7.658031E-2	1.795790E-1
9	2.162972E-2	2.929089E-2	6.250420E-2	73	2.460324E-2	3.414084E-2	6.789908E-2

10	3.114140E-2	5.990793E-2	1.028607E-1	74	4.082201E-2	6.297838E-2	9.951913E-2
11	3.027993E-2	5.350124E-2	7.809258E-2	75	3.830250E-2	5.528575E-2	7.900193E-2
12	6.508462E-2	9.066247E-2	1.428510E-1	76	7.241113E-2	1.019039E-1	1.469796E-1
13	3.273404E-2	5.040278E-2	6.264923E-2	77	3.739022E-2	4.704639E-2	6.546845E-2
14	5.274399E-2	6.225743E-2	1.221983E-1	78	5.273975E-2	6.727704E-2	1.396804E-1
15	3.488404E-2	6.422224E-2	9.160246E-2	79	4.053654E-2	7.050813E-2	9.256686E-2
16	4.889844E-2	1.050580E-1	1.688135E-1	80	4.434253E-2	1.103672E-1	1.996363E-1
17	2.357911E-2	3.210347E-2	5.608996E-2	81	2.549207E-2	3.476040E-2	6.059020E-2
18	2.772528E-2	4.872818E-2	1.012242E-1	82	4.354655E-2	5.323695E-2	1.083260E-1
19	2.743480E-2	4.049659E-2	9.349261E-2	83	2.795998E-2	4.913248E-2	8.842845E-2
20	4.383601E-2	6.032613E-2	1.524009E-1	84	4.980519E-2	8.817289E-2	1.525973E-1
21	2.689949E-2	4.529064E-2	6.498004E-2	85	3.193463E-2	4.621693E-2	6.852064E-2
22	5.160590E-2	6.083122E-2	1.087996E-1	86	5.802463E-2	6.842687E-2	1.150853E-1
23	4.200649E-2	6.118451E-2	8.544740E-2	87	4.339047E-2	6.905756E-2	8.449844E-2
24	7.135027E-2	1.019721E-1	1.746410E-1	88	7.396916E-2	1.192405E-1	1.773402E-1
25	2.889067E-2	4.139644E-2	5.259280E-2	89	3.187675E-2	4.596974E-2	5.723726E-2
26	3.163645E-2	6.635321E-2	1.249503E-1	90	4.508738E-2	5.665094E-2	1.320058E-1
27	4.302895E-2	5.140233E-2	7.968777E-2	91	4.590970E-2	5.455804E-2	8.614233E-2
28	5.709708E-2	1.084445E-1	1.440756E-1	92	7.446858E-2	1.138154E-1	1.615706E-1
29	3.388403E-2	5.047469E-2	7.297654E-2	93	3.975096E-2	4.953595E-2	7.225423E-2
30	6.542657E-2	7.909877E-2	1.155706E-1	94	6.762578E-2	8.310290E-2	1.279901E-1
31	3.854235E-2	7.331254E-2	1.023075E-1	95	5.762581E-2	6.953264E-2	1.050130E-1
32	6.578245E-2	1.029098E-1	2.118744E-1	96	6.853135E-2	1.217588E-1	2.206266E-1
33	1.547279E-2	2.045597E-2	5.461213E-2	97	2.184805E-2	2.991309E-2	5.162080E-2
34	2.279502E-2	3.909542E-2	1.194438E-1	98	3.643432E-2	4.917951E-2	1.232772E-1
35	3.068892E-2	4.545402E-2	8.204189E-2	99	3.896113E-2	4.766350E-2	8.617166E-2
36	2.259572E-2	4.791017E-2	1.718444E-1	100	4.146352E-2	6.880070E-2	1.693562E-1
37	2.710880E-2	4.017396E-2	7.019229E-2	101	3.355146E-2	4.178152E-2	7.371594E-2
38	4.957894E-2	7.929633E-2	1.048625E-1	102	5.802247E-2	8.703142E-2	1.129175E-1
39	3.060959E-2	5.640594E-2	9.495841E-2	103	4.802431E-2	5.694865E-2	1.007557E-1
40	6.342246E-2	9.116555E-2	1.847244E-1	104	5.988731E-2	8.579423E-2	2.013889E-1
41	2.433424E-2	3.919983E-2	6.314062E-2	105	2.993100E-2	3.948284E-2	6.463761E-2
42	3.380120E-2	6.608465E-2	1.110315E-1	106	3.886266E-2	8.074436E-2	1.155198E-1
43	3.517841E-2	5.793973E-2	7.207029E-2	107	3.494440E-2	6.289110E-2	8.049820E-2
44	6.490541E-2	8.658319E-2	1.546487E-1	108	6.888179E-2	9.924311E-2	1.603933E-1
45	2.919347E-2	5.162046E-2	6.944373E-2	109	3.642377E-2	5.340165E-2	6.701520E-2
46	5.945228E-2	7.198293E-2	1.274345E-1	110	5.834927E-2	7.852858E-2	1.417467E-1
47	5.318885E-2	6.381821E-2	9.882185E-2	111	4.864696E-2	7.267369E-2	9.483159E-2
48	8.682910E-2	1.411354E-1	1.917285E-1	112	5.855336E-2	1.362898E-1	1.986397E-1
49	2.499911E-2	3.625560E-2	5.037240E-2	113	2.608885E-2	3.734068E-2	5.578532E-2
50	2.822464E-2	5.445723E-2	1.126635E-1	114	4.585044E-2	5.605125E-2	1.179279E-1
51	3.626181E-2	4.590732E-2	9.433436E-2	115	4.288013E-2	5.147391E-2	9.753090E-2
52	5.704553E-2	7.463004E-2	1.591572E-1	116	6.376116E-2	8.735529E-2	1.683349E-1
53	2.729875E-2	4.566259E-2	7.525297E-2	117	3.767099E-2	4.582160E-2	7.865281E-2
54	5.128602E-2	8.511270E-2	1.235880E-1	118	6.751946E-2	8.986979E-2	1.194181E-1
55	4.914520E-2	5.934831E-2	9.226860E-2	119	5.463743E-2	6.668059E-2	8.938138E-2
56	7.069619E-2	1.054520E-1	1.926021E-1	120	7.730866E-2	1.217544E-1	1.995792E-1
57	2.807338E-2	4.185092E-2	5.871598E-2	121	3.156213E-2	4.517022E-2	6.257685E-2
58	4.644490E-2	7.066988E-2	1.260384E-1	122	3.787827E-2	8.034865E-2	1.389617E-1

59	4.184537E-2	6.304453E-2	7.661699E-2	123	5.083033E-2	6.187406E-2	8.311538E-2
60	8.424164E-2	1.132829E-1	1.436871E-1	124	8.963114E-2	1.287538E-1	1.648916E-1
61	4.176156E-2	5.594729E-2	7.098728E-2	125	4.735035E-2	5.757244E-2	7.652646E-2
62	5.551614E-2	9.501267E-2	1.277272E-1	126	7.168986E-2	9.898957E-2	1.300784E-1
63	5.909355E-2	7.367300E-2	9.659359E-2	127	6.290826E-2	7.907788E-2	1.051111E-1
64	7.841367E-2	1.414324E-1	2.174286E-1	128	8.806498E-2	1.652062E-1	2.132142E-1

Table 9-6. LSP Quantization Table, Rate 1/2, Codebook 2

j	$q_{rate}(2, 1, j)$	$q_{rate}(2, 2, j)$	$q_{rate}(2, 3, j)$	j	$q_{rate}(2, 1, j)$	$q_{rate}(2, 2, j)$	$q_{rate}(2, 3, j)$
1	9.759153E-2	1.237015E-1	1.694380E-1	65	1.140764E-1	1.330714E-1	1.731815E-1
2	9.495363E-2	2.010818E-1	2.268553E-1	66	1.135758E-1	1.903073E-1	2.416812E-1
3	9.004966E-2	1.491649E-1	2.265328E-1	67	8.591653E-2	1.639202E-1	2.379345E-1
4	1.703027E-1	1.972229E-1	2.499748E-1	68	1.929169E-1	2.150824E-1	2.391281E-1
5	1.087736E-1	1.519724E-1	1.751234E-1	69	1.372918E-1	1.594233E-1	1.797222E-1
6	1.302789E-1	2.132292E-1	2.296464E-1	70	1.404354E-1	2.220923E-1	2.409608E-1
7	1.249180E-1	1.873478E-1	2.047120E-1	71	1.403872E-1	1.896012E-1	2.056357E-1
8	2.006702E-1	2.289636E-1	2.694208E-1	72	2.116955E-1	2.365784E-1	2.812489E-1
9	8.983756E-2	1.253328E-1	2.105394E-1	73	9.030106E-2	1.271574E-1	2.335679E-1
10	9.623767E-2	2.071859E-1	2.541745E-1	74	1.101181E-1	2.093284E-1	2.728363E-1
11	1.056946E-1	1.788564E-1	2.001210E-1	75	1.167104E-1	1.778540E-1	2.228088E-1
12	1.560490E-1	2.195737E-1	2.910794E-1	76	1.816915E-1	2.322652E-1	2.749912E-1
13	1.373923E-1	1.599933E-1	1.946985E-1	77	1.465535E-1	1.694747E-1	1.902460E-1
14	1.072625E-1	2.377910E-1	2.707408E-1	78	1.092138E-1	2.632920E-1	2.884908E-1
15	1.429765E-1	2.015505E-1	2.184689E-1	79	1.498151E-1	2.113427E-1	2.288995E-1
16	2.142705E-1	2.718814E-1	3.012002E-1	80	1.976455E-1	2.832300E-1	3.148823E-1
17	1.107292E-1	1.336882E-1	1.548772E-1	81	1.244956E-1	1.460980E-1	1.661252E-1
18	1.066677E-1	1.766788E-1	2.627989E-1	82	1.348786E-1	1.830301E-1	2.892883E-1
19	9.163529E-2	1.745928E-1	2.193293E-1	83	9.330321E-2	1.839622E-1	2.385430E-1
20	1.840386E-1	2.279641E-1	2.477622E-1	84	1.928443E-1	2.395883E-1	2.584215E-1
21	1.105724E-1	1.582072E-1	1.960131E-1	85	1.237968E-1	1.655566E-1	2.084084E-1
22	1.335434E-1	2.322697E-1	2.518282E-1	86	1.511443E-1	2.358011E-1	2.592806E-1
23	1.559223E-1	1.779413E-1	2.180966E-1	87	1.506577E-1	1.900525E-1	2.283626E-1
24	1.922601E-1	2.495125E-1	2.899115E-1	88	1.981810E-1	2.567942E-1	3.089756E-1
25	1.137089E-1	1.378724E-1	2.029299E-1	89	1.284900E-1	1.490840E-1	1.983765E-1
26	1.025575E-1	1.848201E-1	2.921646E-1	90	9.205958E-2	2.122313E-1	2.929488E-1
27	1.365956E-1	1.586874E-1	2.413996E-1	91	1.416981E-1	1.723567E-1	2.584541E-1
28	1.728138E-1	2.493034E-1	3.004586E-1	92	1.967335E-1	2.297097E-1	2.957802E-1
29	1.368712E-1	1.572498E-1	2.109132E-1	93	1.470622E-1	1.689181E-1	2.073636E-1
30	1.289748E-1	2.451679E-1	2.676536E-1	94	1.363099E-1	2.603731E-1	2.826074E-1
31	1.668123E-1	1.889980E-1	2.313459E-1	95	1.810411E-1	2.018261E-1	2.388676E-1
32	2.322485E-1	2.631961E-1	3.167549E-1	96	2.453263E-1	2.801831E-1	3.119543E-1
33	9.245610E-2	1.199775E-1	1.912623E-1	97	1.041318E-1	1.330407E-1	1.898347E-1
34	1.130853E-1	2.084615E-1	2.293681E-1	98	1.232982E-1	2.096211E-1	2.478132E-1
35	1.007164E-1	1.406701E-1	2.580630E-1	99	1.240408E-1	1.598274E-1	2.588561E-1
36	1.670104E-1	2.181055E-1	2.625925E-1	100	1.870489E-1	2.124881E-1	2.596291E-1
37	1.254872E-1	1.626870E-1	1.844092E-1	101	1.242553E-1	1.737690E-1	1.928500E-1
38	1.524066E-1	2.071317E-1	2.475824E-1	102	1.589178E-1	2.253898E-1	2.432848E-1
39	1.374412E-1	1.802624E-1	2.176988E-1	103	1.534212E-1	1.918073E-1	2.092495E-1
40	2.078535E-1	2.492095E-1	2.698301E-1	104	2.271545E-1	2.511812E-1	2.726004E-1

41	9.352573E-2	1.491974E-1	2.046520E-1	105	1.099221E-1	1.571003E-1	2.200250E-1
42	1.119972E-1	2.252331E-1	2.470031E-1	106	1.327824E-1	2.194855E-1	2.670289E-1
43	1.093150E-1	1.938119E-1	2.138022E-1	107	1.268575E-1	1.988363E-1	2.179285E-1
44	1.751186E-1	2.525203E-1	2.750828E-1	108	1.914150E-1	2.524242E-1	2.726528E-1
45	1.369187E-1	1.774406E-1	1.979311E-1	109	1.552776E-1	1.795735E-1	2.007736E-1
46	1.368112E-1	2.374262E-1	2.847378E-1	110	1.175477E-1	2.478699E-1	3.082793E-1
47	1.607598E-1	2.008332E-1	2.180845E-1	111	1.657070E-1	2.103395E-1	2.291993E-1
48	2.337102E-1	2.663726E-1	2.918021E-1	112	2.256949E-1	2.844382E-1	3.121061E-1
49	1.191711E-1	1.397032E-1	1.877233E-1	113	1.295032E-1	1.484201E-1	1.801804E-1
50	1.310500E-1	1.936967E-1	2.604270E-1	114	1.547525E-1	1.977485E-1	2.672750E-1
51	1.082671E-1	1.651948E-1	2.395230E-1	115	1.285902E-1	1.761784E-1	2.399059E-1
52	2.031950E-1	2.259422E-1	2.494032E-1	116	2.149268E-1	2.376344E-1	2.587940E-1
53	1.238429E-1	1.457946E-1	2.156356E-1	117	1.283223E-1	1.593385E-1	2.266266E-1
54	1.712263E-1	2.380545E-1	2.579756E-1	118	1.557476E-1	2.477405E-1	2.737268E-1
55	1.669238E-1	1.886047E-1	2.111242E-1	119	1.757417E-1	1.979524E-1	2.191159E-1
56	2.106208E-1	2.624427E-1	2.831280E-1	120	2.186264E-1	2.458092E-1	3.004797E-1
57	1.057488E-1	1.362865E-1	2.200502E-1	121	1.177090E-1	1.455129E-1	2.380445E-1
58	9.729458E-2	2.334715E-1	2.961140E-1	122	1.180069E-1	2.237755E-1	2.941751E-1
59	1.342984E-1	1.939554E-1	2.391488E-1	123	1.513492E-1	1.881578E-1	2.487433E-1
60	1.642293E-1	2.700678E-1	2.941425E-1	124	1.893122E-1	2.695805E-1	2.937860E-1
61	1.427603E-1	1.650334E-1	2.241004E-1	125	1.498956E-1	1.745373E-1	2.374300E-1
62	1.464145E-1	2.479423E-1	3.007081E-1	126	1.397755E-1	2.717094E-1	3.078395E-1
63	1.747788E-1	2.193493E-1	2.381630E-1	127	1.839457E-1	2.077172E-1	2.267222E-1
64	2.363111E-1	2.906697E-1	3.280110E-1	128	2.545522E-1	2.966409E-1	3.248015E-1

Table 9-7. LSP Quantization Table, Rate 1/2, Codebook 3

j	$q_{rate}(3, 1, j)$	$q_{rate}(3, 2, j)$	$q_{rate}(3, 3, j)$	$q_{rate}(3, 4, j)$
1	2.369047E-1	2.561044E-1	3.169558E-1	4.075205E-1
2	2.975969E-1	3.234825E-1	3.476675E-1	3.745512E-1
3	2.737212E-1	2.982975E-1	3.299239E-1	3.835991E-1
4	3.078496E-1	3.328363E-1	3.893403E-1	4.055760E-1
5	2.338036E-1	2.602965E-1	3.673520E-1	4.043883E-1
6	2.975137E-1	3.153566E-1	3.851352E-1	4.021971E-1
7	2.856188E-1	3.108728E-1	3.650224E-1	3.848168E-1
8	3.352716E-1	3.552222E-1	3.819211E-1	3.986858E-1
9	2.002656E-1	2.505023E-1	3.703982E-1	4.320127E-1
10	3.079821E-1	3.337677E-1	3.581991E-1	3.783868E-1
11	2.600861E-1	3.255203E-1	3.568733E-1	3.847378E-1
12	3.013564E-1	3.413694E-1	4.002968E-1	4.173372E-1
13	2.670810E-1	2.976744E-1	3.697020E-1	3.891392E-1
14	2.726699E-1	3.497041E-1	3.919253E-1	4.063833E-1
15	2.528259E-1	3.496366E-1	3.845510E-1	4.059310E-1
16	3.429271E-1	3.742740E-1	4.054682E-1	4.203519E-1
17	2.524087E-1	2.803758E-1	3.214366E-1	3.884369E-1
18	2.969702E-1	3.171736E-1	3.653426E-1	4.027368E-1
19	2.819052E-1	3.014792E-1	3.343356E-1	4.076335E-1
20	3.268729E-1	3.471777E-1	3.750177E-1	4.053724E-1
21	2.363711E-1	3.164411E-1	3.487070E-1	3.820304E-1
22	2.878176E-1	3.136270E-1	4.051297E-1	4.233797E-1

23	2.775025E-1	3.018438E-1	3.722509E-1	4.192128E-1
24	3.289889E-1	3.619011E-1	4.020155E-1	4.192298E-1
25	2.249605E-1	2.746364E-1	3.770161E-1	3.947265E-1
26	3.010455E-1	3.404862E-1	3.748881E-1	4.025322E-1
27	2.598980E-1	3.303350E-1	3.574938E-1	4.086580E-1
28	3.009619E-1	3.564491E-1	4.047795E-1	4.225090E-1
29	2.209796E-1	3.164777E-1	4.017441E-1	4.207358E-1
30	2.797550E-1	3.307761E-1	4.111529E-1	4.326870E-1
31	2.642469E-1	3.166106E-1	3.838767E-1	4.366838E-1
32	3.443812E-1	3.853657E-1	4.249495E-1	4.415602E-1
33	2.194883E-1	2.364599E-1	3.424660E-1	4.249900E-1
34	2.914651E-1	3.222820E-1	3.728528E-1	3.916359E-1
35	2.747924E-1	3.165363E-1	3.453926E-1	3.745552E-1
36	3.105835E-1	3.352649E-1	3.875272E-1	4.230762E-1
37	2.232115E-1	2.984976E-1	3.684262E-1	3.902137E-1
38	2.890788E-1	3.265128E-1	3.763087E-1	4.095537E-1
39	2.638301E-1	3.089773E-1	3.814530E-1	4.046608E-1
40	3.470736E-1	3.647978E-1	3.867635E-1	4.045117E-1
41	2.184527E-1	2.756141E-1	3.627111E-1	4.182790E-1
42	3.150428E-1	3.408132E-1	3.786272E-1	3.963168E-1
43	2.797277E-1	3.312597E-1	3.600613E-1	3.811755E-1
44	3.186024E-1	3.380443E-1	4.090108E-1	4.303004E-1
45	2.641969E-1	2.906725E-1	3.685950E-1	4.318568E-1
46	2.726456E-1	3.635148E-1	3.965188E-1	4.200912E-1
47	2.265410E-1	3.500551E-1	3.938515E-1	4.125970E-1
48	3.530539E-1	3.699296E-1	4.096561E-1	4.263873E-1
49	2.607884E-1	2.851725E-1	3.459433E-1	3.975007E-1
50	3.011131E-1	3.282019E-1	3.560680E-1	4.108038E-1
51	2.881016E-1	3.095596E-1	3.437568E-1	4.248729E-1
52	3.104894E-1	3.514219E-1	3.937174E-1	4.155505E-1
53	2.223083E-1	3.267982E-1	3.779817E-1	3.986350E-1
54	3.029155E-1	3.227819E-1	3.985589E-1	4.254896E-1
55	2.771368E-1	3.199926E-1	3.774909E-1	4.291775E-1
56	3.387318E-1	3.581644E-1	4.083864E-1	4.254954E-1
57	2.187262E-1	2.843850E-1	3.940537E-1	4.163470E-1
58	3.010060E-1	3.440937E-1	3.690137E-1	4.150913E-1
59	2.807837E-1	3.330537E-1	3.767262E-1	3.975269E-1
60	3.143941E-1	3.626788E-1	4.236690E-1	4.418992E-1
61	2.664536E-1	3.085138E-1	3.974072E-1	4.174502E-1
62	2.942227E-1	3.419044E-1	4.127269E-1	4.348889E-1
63	2.873007E-1	3.324346E-1	3.788567E-1	4.382340E-1
64	3.571466E-1	3.981471E-1	4.298757E-1	4.442439E-1
65	2.296713E-1	2.510186E-1	3.410466E-1	4.043763E-1
66	2.944726E-1	3.349446E-1	3.604097E-1	3.836829E-1
67	2.882510E-1	3.117227E-1	3.316801E-1	3.651047E-1
68	3.248816E-1	3.456567E-1	3.883064E-1	4.059549E-1
69	2.508292E-1	2.776235E-1	3.707995E-1	3.904792E-1
70	2.935234E-1	3.283192E-1	3.921123E-1	4.094641E-1
71	2.836088E-1	3.038856E-1	3.785044E-1	3.973106E-1

72	3.340398E-1	3.528374E-1	3.972729E-1	4.143220E-1
73	2.218919E-1	2.518775E-1	3.717235E-1	4.317910E-1
74	3.132014E-1	3.411754E-1	3.655036E-1	3.885672E-1
75	2.713305E-1	3.391637E-1	3.626164E-1	3.957360E-1
76	3.075501E-1	3.477777E-1	4.010496E-1	4.327675E-1
77	2.593874E-1	2.872438E-1	3.868173E-1	4.060427E-1
78	2.854852E-1	3.440950E-1	4.020505E-1	4.194138E-1
79	2.657814E-1	3.400844E-1	3.694077E-1	4.270317E-1
80	3.537409E-1	3.844633E-1	4.117478E-1	4.261818E-1
81	2.438665E-1	2.683502E-1	3.422020E-1	3.984572E-1
82	2.931452E-1	3.347542E-1	3.617028E-1	3.984166E-1
83	2.913430E-1	3.131552E-1	3.365259E-1	3.877486E-1
84	3.056568E-1	3.629046E-1	3.881534E-1	4.055432E-1
85	2.174923E-1	3.117235E-1	3.759848E-1	4.289978E-1
86	2.911493E-1	3.293809E-1	4.039004E-1	4.223332E-1
87	2.903621E-1	3.095310E-1	3.789942E-1	4.136884E-1
88	3.295649E-1	3.774047E-1	4.065849E-1	4.247397E-1
89	2.464616E-1	2.715933E-1	3.663383E-1	4.307538E-1
90	3.141077E-1	3.370119E-1	3.804097E-1	4.110994E-1
91	2.765684E-1	3.273207E-1	3.588443E-1	4.289495E-1
92	3.171791E-1	3.589724E-1	4.047658E-1	4.403763E-1
93	2.427778E-1	3.349548E-1	3.969435E-1	4.133184E-1
94	2.888955E-1	3.256912E-1	4.228596E-1	4.437587E-1
95	2.775833E-1	3.254790E-1	3.891447E-1	4.410759E-1
96	3.591257E-1	3.906941E-1	4.210095E-1	4.357085E-1
97	2.201724E-1	2.477193E-1	3.543819E-1	4.253981E-1
98	3.060468E-1	3.279247E-1	3.669928E-1	3.931926E-1
99	2.708056E-1	3.168266E-1	3.456487E-1	4.117176E-1
100	3.231889E-1	3.454631E-1	3.897788E-1	4.215708E-1
101	2.461361E-1	3.123920E-1	3.721886E-1	3.958427E-1
102	3.038567E-1	3.243548E-1	3.857473E-1	4.141550E-1
103	2.810754E-1	3.186085E-1	3.856469E-1	4.027036E-1
104	3.535171E-1	3.727025E-1	3.962646E-1	4.130749E-1
105	2.092211E-1	2.952622E-1	3.803143E-1	4.312782E-1
106	3.253136E-1	3.467355E-1	3.707240E-1	3.910456E-1
107	2.863965E-1	3.435600E-1	3.697136E-1	3.898678E-1
108	3.277947E-1	3.473678E-1	4.054651E-1	4.245662E-1
109	2.530550E-1	3.026563E-1	3.821651E-1	4.298983E-1
110	2.944185E-1	3.707454E-1	3.954433E-1	4.195148E-1
111	2.628731E-1	3.450692E-1	4.041409E-1	4.219021E-1
112	3.650635E-1	3.824351E-1	4.134248E-1	4.312417E-1
113	2.487885E-1	2.823728E-1	3.657723E-1	4.109811E-1
114	3.072888E-1	3.278289E-1	3.776650E-1	4.362209E-1
115	2.985423E-1	3.206273E-1	3.505697E-1	4.276202E-1
116	3.162580E-1	3.629038E-1	3.882251E-1	4.256089E-1
117	2.390779E-1	3.313105E-1	3.703179E-1	4.159959E-1
118	3.037358E-1	3.328061E-1	4.102328E-1	4.277511E-1
119	2.960025E-1	3.190148E-1	3.810625E-1	4.269550E-1
120	3.325089E-1	3.625170E-1	4.233151E-1	4.409952E-1

121	2.351287E-1	2.747311E-1	4.120706E-1	4.354788E-1
122	2.980738E-1	3.553388E-1	3.790878E-1	4.153188E-1
123	2.834298E-1	3.452649E-1	3.703763E-1	4.099008E-1
124	3.235931E-1	3.654128E-1	4.128131E-1	4.310235E-1
125	2.766264E-1	3.005084E-1	4.022369E-1	4.266388E-1
126	2.945129E-1	3.614432E-1	4.196352E-1	4.369992E-1
127	2.908073E-1	3.416894E-1	3.927793E-1	4.434903E-1
128	3.593915E-1	4.039851E-1	4.408438E-1	4.530286E-1
129	2.232955E-1	2.391925E-1	3.237680E-1	4.216895E-1
130	2.947781E-1	3.187987E-1	3.532178E-1	3.919064E-1
131	2.590321E-1	3.102405E-1	3.435690E-1	3.950642E-1
132	3.164747E-1	3.385444E-1	3.933290E-1	4.122356E-1
133	2.401082E-1	2.846312E-1	3.602810E-1	3.799738E-1
134	2.969091E-1	3.157983E-1	3.949643E-1	4.151276E-1
135	2.854341E-1	3.049215E-1	3.619747E-1	4.057673E-1
136	3.374071E-1	3.566722E-1	3.851551E-1	4.111867E-1
137	2.240149E-1	2.601162E-1	3.947725E-1	4.195859E-1
138	3.006479E-1	3.416407E-1	3.702235E-1	3.895201E-1
139	2.659460E-1	3.250392E-1	3.743399E-1	3.923461E-1
140	3.160293E-1	3.404913E-1	4.023553E-1	4.204842E-1
141	2.698415E-1	2.945624E-1	3.623418E-1	4.064155E-1
142	2.788973E-1	3.598310E-1	3.820258E-1	4.105775E-1
143	2.607608E-1	3.310885E-1	3.888263E-1	4.054866E-1
144	3.433723E-1	3.826470E-1	4.147166E-1	4.315929E-1
145	2.479981E-1	2.733932E-1	3.311604E-1	4.189432E-1
146	3.035796E-1	3.252025E-1	3.709844E-1	4.144205E-1
147	2.768969E-1	3.004995E-1	3.541782E-1	4.288070E-1
148	3.236556E-1	3.598170E-1	3.895254E-1	4.092887E-1
149	2.389278E-1	3.099192E-1	3.539156E-1	4.166343E-1
150	2.811717E-1	3.075203E-1	4.162649E-1	4.385238E-1
151	2.888587E-1	3.098108E-1	3.678452E-1	4.360356E-1
152	3.384235E-1	3.706344E-1	4.154500E-1	4.315345E-1
153	2.412604E-1	2.736179E-1	3.895546E-1	4.125395E-1
154	2.980467E-1	3.401221E-1	3.861837E-1	4.138264E-1
155	2.824364E-1	3.315975E-1	3.579414E-1	4.121152E-1
156	3.038202E-1	3.705886E-1	4.057750E-1	4.315171E-1
157	2.390777E-1	3.116385E-1	4.139358E-1	4.353041E-1
158	2.671168E-1	3.419379E-1	4.174094E-1	4.391848E-1
159	2.679468E-1	3.333439E-1	3.864814E-1	4.374625E-1
160	3.405110E-1	3.908780E-1	4.354851E-1	4.491019E-1
161	2.100699E-1	2.325245E-1	3.617814E-1	4.313579E-1
162	2.945099E-1	3.337098E-1	3.822786E-1	3.986389E-1
163	2.805252E-1	3.259052E-1	3.506470E-1	3.928739E-1
164	3.199996E-1	3.436747E-1	3.910705E-1	4.375011E-1
165	2.205810E-1	3.031519E-1	3.817655E-1	4.044882E-1
166	2.861227E-1	3.297465E-1	3.881028E-1	4.242477E-1
167	2.698071E-1	3.253323E-1	3.791545E-1	4.151382E-1
168	3.348589E-1	3.692584E-1	3.947431E-1	4.119222E-1
169	2.071098E-1	2.727795E-1	3.785664E-1	4.345800E-1

170	3.064662E-1	3.466957E-1	3.871383E-1	4.035583E-1
171	2.701486E-1	3.466545E-1	3.776967E-1	3.964345E-1
172	3.187459E-1	3.402257E-1	4.149916E-1	4.415788E-1
173	2.585928E-1	3.143701E-1	3.650838E-1	4.216152E-1
174	2.827130E-1	3.541371E-1	4.067460E-1	4.292679E-1
175	2.520218E-1	3.591051E-1	3.951029E-1	4.181484E-1
176	3.549062E-1	3.749529E-1	4.189660E-1	4.361444E-1
177	2.648411E-1	2.929418E-1	3.277515E-1	4.087905E-1
178	3.077743E-1	3.355862E-1	3.622096E-1	4.253942E-1
179	2.884663E-1	3.160757E-1	3.609896E-1	4.195514E-1
180	3.171284E-1	3.557722E-1	4.058088E-1	4.239730E-1
181	2.470897E-1	3.381846E-1	3.718596E-1	3.959715E-1
182	3.079817E-1	3.326918E-1	4.005342E-1	4.382737E-1
183	2.794848E-1	3.161835E-1	3.972377E-1	4.347466E-1
184	3.444905E-1	3.661532E-1	4.109594E-1	4.417271E-1
185	2.357418E-1	2.945873E-1	3.980725E-1	4.168334E-1
186	3.140385E-1	3.522720E-1	3.791389E-1	4.109691E-1
187	2.830025E-1	3.381363E-1	3.886419E-1	4.061933E-1
188	3.236253E-1	3.502434E-1	4.280896E-1	4.466304E-1
189	2.612521E-1	3.249710E-1	4.002145E-1	4.253218E-1
190	3.052845E-1	3.421642E-1	4.244751E-1	4.438310E-1
191	2.873748E-1	3.325006E-1	3.943083E-1	4.425385E-1
192	3.740754E-1	4.020264E-1	4.309335E-1	4.441600E-1
193	2.345040E-1	2.562186E-1	3.412388E-1	4.230453E-1
194	3.054926E-1	3.291570E-1	3.527098E-1	3.924391E-1
195	2.813236E-1	3.032923E-1	3.489254E-1	3.931639E-1
196	3.218935E-1	3.504199E-1	3.973175E-1	4.145603E-1
197	2.396846E-1	2.924515E-1	3.789374E-1	3.965355E-1
198	3.073072E-1	3.291279E-1	3.984556E-1	4.161433E-1
199	2.852746E-1	3.087745E-1	3.929165E-1	4.144377E-1
200	3.444464E-1	3.622019E-1	3.976198E-1	4.177436E-1
201	2.320831E-1	2.678080E-1	3.780757E-1	4.345609E-1
202	3.047387E-1	3.518653E-1	3.759732E-1	3.952937E-1
203	2.619909E-1	3.462073E-1	3.712969E-1	4.124389E-1
204	3.110809E-1	3.510409E-1	4.160828E-1	4.343401E-1
205	2.749804E-1	2.966315E-1	3.875205E-1	4.092438E-1
206	2.909391E-1	3.544556E-1	3.934270E-1	4.082203E-1
207	2.718719E-1	3.455108E-1	3.871253E-1	4.225906E-1
208	3.632459E-1	3.819322E-1	4.041149E-1	4.183707E-1
209	2.457707E-1	2.729093E-1	3.483179E-1	4.251618E-1
210	3.141390E-1	3.378723E-1	3.651952E-1	4.044234E-1
211	2.940758E-1	3.169355E-1	3.430472E-1	4.061304E-1
212	3.146275E-1	3.724134E-1	4.006607E-1	4.179308E-1
213	2.340142E-1	3.140072E-1	3.830035E-1	4.348292E-1
214	2.936357E-1	3.205300E-1	4.108374E-1	4.363931E-1
215	2.895058E-1	3.118289E-1	3.863115E-1	4.387713E-1
216	3.263174E-1	3.808582E-1	4.197214E-1	4.387955E-1
217	2.508095E-1	2.830181E-1	3.822474E-1	4.342444E-1
218	3.189941E-1	3.448551E-1	3.726901E-1	4.230670E-1

219	2.883801E-1	3.366222E-1	3.697423E-1	4.250576E-1
220	3.061077E-1	3.818569E-1	4.182062E-1	4.328684E-1
221	2.338983E-1	3.448618E-1	4.121766E-1	4.292162E-1
222	2.859809E-1	3.429038E-1	4.251129E-1	4.442997E-1
223	2.798588E-1	3.387893E-1	3.920854E-1	4.405410E-1
224	3.645093E-1	3.822027E-1	4.298306E-1	4.458184E-1
225	2.343923E-1	2.573774E-1	3.595671E-1	4.300886E-1
226	3.050319E-1	3.275894E-1	3.783056E-1	4.010261E-1
227	2.775226E-1	3.181303E-1	3.677943E-1	4.015430E-1
228	3.330358E-1	3.558210E-1	3.875489E-1	4.246287E-1
229	2.450210E-1	3.125607E-1	3.911476E-1	4.087628E-1
230	2.970591E-1	3.402469E-1	3.929193E-1	4.288997E-1
231	2.778393E-1	3.250198E-1	3.974364E-1	4.159209E-1
232	3.494653E-1	3.703625E-1	3.954825E-1	4.319234E-1
233	2.314856E-1	2.910234E-1	3.779095E-1	4.322597E-1
234	3.192835E-1	3.536711E-1	3.809829E-1	3.978434E-1
235	2.896892E-1	3.502657E-1	3.807297E-1	3.979694E-1
236	3.289873E-1	3.520054E-1	4.125572E-1	4.375979E-1
237	2.762733E-1	3.022672E-1	3.817234E-1	4.349891E-1
238	2.796273E-1	3.737273E-1	4.123746E-1	4.306263E-1
239	2.534428E-1	3.659400E-1	4.149370E-1	4.327436E-1
240	3.761072E-1	3.951420E-1	4.167877E-1	4.330236E-1
241	2.628158E-1	2.882705E-1	3.473972E-1	4.241826E-1
242	3.019313E-1	3.436526E-1	3.770313E-1	4.342045E-1
243	2.978343E-1	3.234954E-1	3.644924E-1	4.335508E-1
244	3.317745E-1	3.643249E-1	3.982436E-1	4.350783E-1
245	2.490497E-1	3.278708E-1	3.835870E-1	4.355581E-1
246	3.046534E-1	3.276712E-1	4.184847E-1	4.413788E-1
247	2.969609E-1	3.238989E-1	3.904637E-1	4.399160E-1
248	3.439238E-1	3.671005E-1	4.295232E-1	4.452150E-1
249	2.593997E-1	2.916027E-1	4.043725E-1	4.314132E-1
250	2.975375E-1	3.575738E-1	3.889918E-1	4.300070E-1
251	2.840689E-1	3.495746E-1	3.810428E-1	4.297128E-1
252	3.257163E-1	3.748759E-1	4.319593E-1	4.472908E-1
253	2.653030E-1	3.147460E-1	4.167035E-1	4.372947E-1
254	3.003986E-1	3.541473E-1	4.285381E-1	4.603364E-1
255	2.980772E-1	3.493049E-1	4.004293E-1	4.482135E-1
256	3.755762E-1	4.166573E-1	4.421368E-1	4.527286E-1

Table 9-8. LSP Quantization Table, Rate 1/8, Codebook 1

j	$q_{rate}(1, 1, j)$	$q_{rate}(1, 2, j)$	$q_{rate}(1, 3, j)$	$q_{rate}(1, 4, j)$	$q_{rate}(1, 5, j)$
1	4.209106E-2	6.947497E-2	1.116895E-1	1.457197E-1	2.089358E-1
2	5.494466E-2	9.824226E-2	1.100788E-1	1.589078E-1	2.054824E-1
3	4.518857E-2	7.519943E-2	1.142339E-1	1.546973E-1	1.974671E-1
4	4.947500E-2	7.966750E-2	1.257135E-1	1.694478E-1	2.077532E-1
5	4.178938E-2	6.345956E-2	1.206803E-1	1.585077E-1	2.040682E-1
6	4.715924E-2	7.912955E-2	1.218311E-1	1.565005E-1	2.230923E-1
7	5.453992E-2	8.034305E-2	1.294776E-1	1.518615E-1	2.017172E-1
8	5.585208E-2	9.411485E-2	1.401603E-1	1.780708E-1	2.295549E-1

9	4.544353E-2	7.354141E-2	1.193766E-1	1.544203E-1	2.101075E-1
10	6.317801E-2	9.523149E-2	1.236498E-1	1.767254E-1	2.174373E-1
11	5.276537E-2	8.435144E-2	1.158909E-1	1.579092E-1	2.073235E-1
12	5.186575E-2	8.132854E-2	1.375623E-1	1.832288E-1	2.164007E-1
13	4.441953E-2	6.887446E-2	1.311525E-1	1.626358E-1	2.165910E-1
14	4.937844E-2	8.188255E-2	1.306717E-1	1.682190E-1	2.313608E-1
15	5.590978E-2	9.078330E-2	1.334885E-1	1.629847E-1	2.096152E-1
16	6.137821E-2	9.860277E-2	1.479333E-1	1.928319E-1	2.315651E-1

Table 9-9. LSP Quantization Table, Rate 1/8, Codebook 2

<i>j</i>	$q_{rate}(2, 1, j)$	$q_{rate}(2, 2, j)$	$q_{rate}(2, 3, j)$	$q_{rate}(2, 4, j)$	$q_{rate}(2, 5, j)$
1	2.682296E-1	3.058530E-1	3.111035E-1	3.682334E-1	4.077447E-1
2	2.441801E-1	2.897017E-1	3.257376E-1	3.902148E-1	4.134584E-1
3	2.334183E-1	3.007829E-1	3.289390E-1	3.855733E-1	4.106846E-1
4	2.590587E-1	2.975686E-1	3.419662E-1	3.853117E-1	4.129523E-1
5	2.429045E-1	2.922362E-1	3.271855E-1	3.778814E-1	4.033293E-1
6	2.467419E-1	2.974937E-1	3.363123E-1	3.942606E-1	4.225895E-1
7	2.137760E-1	3.314042E-1	3.406769E-1	3.822208E-1	4.093902E-1
8	2.667348E-1	3.079165E-1	3.441972E-1	3.961151E-1	4.238752E-1
9	2.612143E-1	3.049254E-1	3.299724E-1	3.848680E-1	4.202374E-1
10	2.495487E-1	2.937286E-1	3.338274E-1	3.785067E-1	4.171406E-1
11	2.415889E-1	3.017342E-1	3.412825E-1	3.842858E-1	4.161965E-1
12	2.581891E-1	3.173641E-1	3.490434E-1	3.876993E-1	4.155136E-1
13	2.445059E-1	3.067345E-1	3.357932E-1	3.784443E-1	4.055705E-1
14	2.516403E-1	3.122508E-1	3.384779E-1	3.955419E-1	4.239680E-1
15	2.278799E-1	3.177920E-1	3.383191E-1	4.004411E-1	4.118556E-1
16	2.789686E-1	3.226197E-1	3.565811E-1	4.020676E-1	4.237045E-1

Table 9-10a. Interpolation Filter Coefficients, Cutoff=0.5 (1/2)

<i>n</i>	$I_{\mathbf{g}}(7n)$	$I_{\mathbf{g}}(1 + 7n)$	$I_{\mathbf{g}}(2 + 7n)$	$I_{\mathbf{g}}(3 + 7n)$
0	-2.279553E-2	9.638780E-2	4.296515E-1	4.296515E-1
1	-2.165019E-2	6.437141E-2	3.936069E-1	4.594094E-1
2	-1.928710E-2	3.758768E-2	3.527558E-1	4.816282E-1
3	-1.634340E-2	1.617878E-2	3.087218E-1	4.953565E-1
4	-1.332172E-2	0.000000E+0	2.631803E-1	5.000000E-1
5	-1.057099E-2	-1.134067E-2	2.177682E-1	4.953565E-1
6	-8.282481E-3	-1.842952E-2	1.739981E-1	4.816282E-1
7	-6.500361E-3	-2.198557E-2	1.331849E-1	4.594094E-1

Table 9-10b. Interpolation Filter Coefficients, Cutoff=0.5 (2/2)

<i>n</i>	$I_{\mathbf{g}}(4 + 7n)$	$I_{\mathbf{g}}(5 + 7n)$	$I_{\mathbf{g}}(6 + 7n)$
0	9.638780E-2	-2.279553E-2	-5.144665E-3
1	1.331849E-1	-2.198557E-2	-6.500361E-3
2	1.739981E-1	-1.842952E-2	-8.282481E-3
3	2.177682E-1	-1.134067E-2	-1.057099E-2
4	2.631803E-1	0.000000E+0	-1.332172E-2
5	3.087218E-1	1.617878E-2	-1.634340E-2
6	3.527558E-1	3.758768E-2	-1.928710E-2
7	3.936069E-1	6.437141E-2	-2.165019E-2

1

Table 9-11a. Interpolation Filter Coefficients, Cutoff=0.9 (1/3)

n	$I_E(17n)$	$I_E(1 + 17n)$	$I_E(2 + 17n)$	$I_E(3 + 17n)$	$I_E(4 + 17n)$
0	3.333057E-3	-4.447694E-3	3.032594E-3	5.505681E-3	-2.749339E-2
1	1.814939E-3	-1.051010E-3	-3.490370E-3	1.602235E-2	-4.161043E-2
2	3.143855E-4	1.903512E-3	-8.614938E-3	2.320955E-2	-4.897606E-2
3	-1.011791E-3	4.128520E-3	-1.191523E-2	2.662804E-2	-4.954024E-2
4	-2.054155E-3	5.477784E-3	-1.325900E-2	2.636338E-2	-4.408088E-2
5	-2.749624E-3	5.939437E-3	-1.278129E-2	2.294780E-2	-3.401131E-2
6	-3.074976E-3	5.612335E-3	-1.082686E-2	1.723493E-2	-2.113197E-2
7	-3.038022E-3	4.671966E-3	-7.873206E-3	1.024916E-2	-7.363276E-3

2

Table 9-11b. Interpolation Filter Coefficients, Cutoff=0.9 (2/3)

n	$I_E(5 + 17n)$	$I_E(6 + 17n)$	$I_E(7 + 17n)$	$I_E(8 + 17n)$	$I_E(9 + 17n)$	$I_E(10 + 17n)$
0	7.357492E-2	-1.760500E-1	6.238571E-1	6.238571E-1	-1.760500E-1	7.357492E-2
1	8.809371E-2	-1.788657E-1	4.934066E-1	7.373307E-1	-1.480059E-1	4.678921E-2
2	9.025505E-2	-1.604327E-1	3.555172E-1	8.252803E-1	-9.275004E-2	9.433596E-3
3	8.139432E-2	-1.261773E-1	2.198452E-1	8.809472E-1	-1.067283E-2	-3.518170E-2
4	6.395375E-2	-8.231784E-2	9.530775E-2	9.000000E-1	9.530775E-2	-8.231784E-2
5	4.107321E-2	-3.518170E-2	-1.067283E-2	8.809472E-1	2.198452E-1	-1.261773E-1
6	1.614589E-2	9.433596E-3	-9.275004E-2	8.252803E-1	3.555172E-1	-1.604327E-1
7	-7.606618E-3	4.678921E-2	-1.480059E-1	7.373307E-1	4.934066E-1	-1.788657E-1

3

Table 9-11c. Interpolation Filter Coefficients, Cutoff=0.9 (3/3)

n	$I_E(11 + 17n)$	$I_E(12 + 17n)$	$I_E(13 + 17n)$	$I_E(14 + 17n)$	$I_E(15 + 17n)$	$I_E(16 + 17n)$
0	-2.749339E-2	5.505681E-3	3.032594E-3	-4.447694E-3	3.333057E-3	-2.669328E-3
1	-7.606618E-3	-7.363276E-3	1.024916E-2	-7.873206E-3	4.671966E-3	-3.038022E-3
2	1.614589E-2	-2.113197E-2	1.723493E-2	-1.082686E-2	5.612335E-3	-3.074976E-3
3	4.107321E-2	-3.401131E-2	2.294780E-2	-1.278129E-2	5.939437E-3	-2.749624E-3
4	6.395375E-2	-4.408088E-2	2.636338E-2	-1.325900E-2	5.477784E-3	-2.054155E-3
5	8.139432E-2	-4.954024E-2	2.662804E-2	-1.191523E-2	4.128520E-3	-1.011791E-3
6	9.025505E-2	-4.897606E-2	2.320955E-2	-8.614938E-3	1.903512E-3	3.143855E-4
7	8.809371E-2	-4.161043E-2	1.602235E-2	-3.490370E-3	-1.051010E-3	1.814939E-3

4

Table 9-12. Fixed Codebook Gain Quantization, Rate 1

k	$g_{ccb}(k)$	k	$g_{ccb}(k)$
0	1.2840254E+0	16	7.0105412E+1
1	1.6487213E+0	17	9.0017131E+1
2	2.1170000E+0	18	1.1558429E+2
3	2.7182818E+0	19	1.4841316E+2
4	3.4903430E+0	20	1.9056627E+2
5	4.4816891E+0	21	2.4469193E+2
6	5.7546027E+0	22	3.1419066E+2
7	7.3890561E+0	23	4.0342879E+2
8	9.4877358E+0	24	5.1801283E+2
9	1.2182494E+1	25	6.6514163E+2
10	1.5642632E+1	26	8.5405876E+2
11	2.0085537E+1	27	1.0966332E+3
12	2.5790340E+1	28	1.4081049E+3
13	3.3115452E+1	29	1.8080424E+3

14	4.2521082E+1	30	2.3215724E+3
15	5.4598150E+1	31	2.9809580E+3

Table 9-13. Fixed Codebook Gain Quantization, Rate 1/2

k	$G_{ccb}(k)$	k	$G_{ccb}(k)$
0	1.6487213E+0	8	9.0017131E+1
1	2.7182818E+0	9	1.4841316E+2
2	4.4816891E+0	10	2.4469193E+2
3	7.3890561E+0	11	4.0342879E+2
4	1.2182494E+1	12	6.6514163E+2
5	2.0085537E+1	13	1.0966332E+3
6	3.3115452E+1	14	1.8080424E+3
7	5.4598150E+1	15	2.9809580E+3

Table 9-14. Residual Shift Interpolation Filter Coefficients

j	$I_f(-1, j)$	$I_f(0, j)$	$I_f(1, j)$
0	3.750000E-01	7.500000E-01	-1.250000E-01
1	2.578125E-01	8.593750E-01	-1.171875E-01
2	1.562500E-01	9.375000E-01	-9.375000E-02
3	7.031250E-02	9.843750E-01	-5.468750E-02
4	0.000000E+00	1.000000E+00	0.000000E+00
5	-5.468750E-02	9.843750E-01	7.031250E-02
6	-9.375000E-02	9.375000E-01	1.562500E-01
7	-1.171875E-01	8.593750E-01	2.578125E-01

Table 9-15. Rate 1/8 Frame Energy Quantization

k	$q_{log}(0, k)$	$q_{log}(1, k)$	$q_{log}(2, k)$	k	$q_{log}(0, k)$	$q_{log}(1, k)$	$q_{log}(2, k)$
0	-2.464E-02	-4.005E-03	-1.107E-01	128	-4.208E-02	-1.491E-01	-7.639E-02
1	8.734E-01	1.004E+00	9.930E-01	129	1.046E+00	9.598E-01	9.176E-01
2	4.222E-01	3.894E-01	5.020E-01	130	4.478E-01	4.605E-01	5.111E-01
3	1.450E+00	1.328E+00	1.278E+00	131	1.521E+00	1.292E+00	1.342E+00
4	1.957E-01	2.169E-01	2.735E-01	132	2.220E-01	2.549E-01	2.510E-01
5	1.142E+00	1.240E+00	1.157E+00	133	1.186E+00	1.254E+00	1.171E+00
6	7.881E-01	6.778E-01	4.185E-01	134	8.999E-01	4.960E-01	4.943E-01
7	1.504E+00	1.468E+00	1.534E+00	135	1.423E+00	1.484E+00	1.620E+00
8	3.173E-01	2.693E-01	-9.526E-02	136	2.796E-01	2.778E-01	-2.820E-01
9	1.141E+00	1.154E+00	1.044E+00	137	1.170E+00	1.181E+00	1.076E+00
10	5.147E-01	5.784E-01	8.802E-01	138	4.068E-01	8.541E-01	9.352E-01
11	1.502E+00	1.407E+00	1.409E+00	139	1.584E+00	1.416E+00	1.387E+00
12	3.163E-01	3.592E-01	2.830E-01	140	3.325E-01	3.655E-01	3.340E-01
13	1.217E+00	1.213E+00	1.216E+00	141	1.224E+00	1.257E+00	1.245E+00
14	1.023E+00	1.139E+00	-9.526E-02	142	1.061E+00	1.138E+00	-9.526E-02
15	1.619E+00	1.655E+00	1.642E+00	143	1.681E+00	1.704E+00	1.673E+00
16	1.437E-01	1.505E-01	6.838E-02	144	1.932E-01	1.489E-01	1.258E-01
17	9.794E-01	1.021E+00	1.117E+00	145	1.023E+00	1.088E+00	1.145E+00
18	4.701E-01	6.426E-01	5.519E-01	146	5.190E-01	6.873E-01	5.172E-01
19	1.366E+00	1.397E+00	1.406E+00	147	1.380E+00	1.405E+00	1.474E+00
20	2.918E-01	3.022E-01	2.420E-01	148	3.393E-01	3.100E-01	2.231E-01
21	1.309E+00	1.241E+00	1.220E+00	149	1.354E+00	1.249E+00	1.270E+00

3GPP2 C.S0014-B ver 1.0

22	7.989E-01	7.654E-01	7.391E-01	150	7.363E-01	8.508E-01	8.247E-01
23	1.612E+00	1.502E+00	1.447E+00	151	1.612E+00	1.537E+00	1.509E+00
24	2.594E-01	1.948E-01	2.555E-01	152	2.952E-01	2.053E-01	2.590E-01
25	1.091E+00	1.150E+00	1.272E+00	153	1.138E+00	1.219E+00	1.262E+00
26	3.423E-01	4.150E-01	1.294E+00	154	1.345E+00	1.289E+00	1.338E+00
27	1.729E+00	1.377E+00	1.065E+00	155	1.437E+00	1.360E+00	1.442E+00
28	4.103E-01	3.287E-01	3.228E-01	156	4.826E-01	3.298E-01	3.842E-01
29	1.144E+00	1.281E+00	1.416E+00	157	1.219E+00	1.311E+00	1.413E+00
30	1.047E+00	1.117E+00	6.188E-01	158	1.212E+00	1.186E+00	6.357E-01
31	1.914E+00	1.777E+00	1.516E+00	159	1.873E+00	1.939E+00	1.674E+00
32	-2.117E-02	2.159E-01	2.351E-01	160	1.260E+00	1.306E+00	1.368E+00
33	1.093E+00	1.088E+00	1.026E+00	161	1.146E+00	1.077E+00	1.025E+00
34	5.567E-01	5.092E-01	4.654E-01	162	6.029E-01	5.039E-01	5.781E-01
35	1.510E+00	1.449E+00	1.201E+00	163	1.514E+00	1.420E+00	1.324E+00
36	2.362E-01	3.426E-01	2.549E-01	164	2.652E-01	3.192E-01	3.042E-01
37	1.340E+00	1.225E+00	1.117E+00	165	1.368E+00	1.198E+00	1.200E+00
38	1.203E+00	3.819E-01	2.269E-01	166	1.234E+00	4.910E-01	3.464E-02
39	1.373E+00	1.404E+00	1.830E+00	167	1.347E+00	1.560E+00	1.861E+00
40	2.570E-01	2.668E-01	1.636E-01	168	2.766E-01	2.887E-01	2.029E-01
41	1.219E+00	1.098E+00	1.122E+00	169	1.257E+00	1.105E+00	1.145E+00
42	6.985E-01	8.456E-01	1.069E+00	170	1.351E+00	1.353E+00	1.406E+00
43	1.550E+00	1.501E+00	1.388E+00	171	1.506E+00	1.580E+00	1.362E+00
44	2.870E-01	3.060E-01	3.599E-01	172	2.794E-01	3.868E-01	4.277E-01
45	1.178E+00	1.345E+00	1.302E+00	173	1.234E+00	1.334E+00	1.336E+00
46	1.270E+00	1.215E+00	1.812E-01	174	1.280E+00	1.252E+00	1.805E-01
47	1.725E+00	1.777E+00	1.693E+00	175	1.387E+00	1.396E+00	1.434E+00
48	2.074E-01	2.104E-01	1.539E-01	176	2.902E-01	1.170E-01	1.698E-01
49	1.105E+00	1.034E+00	1.104E+00	177	1.134E+00	1.077E+00	1.117E+00
50	6.683E-01	6.646E-01	6.639E-01	178	6.986E-01	7.177E-01	7.366E-01
51	1.403E+00	1.462E+00	1.435E+00	179	1.370E+00	1.491E+00	1.495E+00
52	3.389E-01	3.754E-01	2.150E-01	180	4.031E-01	5.144E-01	1.751E-01
53	1.288E+00	1.325E+00	1.257E+00	181	1.333E+00	1.377E+00	1.257E+00
54	8.933E-01	8.253E-01	8.133E-01	182	9.212E-01	8.934E-01	8.897E-01
55	1.555E+00	1.579E+00	1.565E+00	183	1.589E+00	1.614E+00	1.523E+00
56	3.264E-01	2.434E-01	2.852E-01	184	3.152E-01	2.164E-01	3.230E-01
57	1.242E+00	1.180E+00	1.202E+00	185	1.300E+00	1.145E+00	1.212E+00
58	1.314E-01	1.698E-01	1.646E+00	186	1.269E+00	1.245E+00	1.497E+00
59	1.797E+00	1.597E+00	1.241E+00	187	1.763E+00	1.716E+00	1.311E+00
60	4.721E-01	5.346E-01	3.066E-01	188	4.702E-01	5.422E-01	4.306E-01
61	1.274E+00	1.401E+00	1.351E+00	189	1.342E+00	1.433E+00	1.423E+00
62	1.455E+00	1.386E+00	6.430E-01	190	1.472E+00	1.404E+00	8.371E-01
63	1.828E+00	1.867E+00	1.825E+00	191	1.936E+00	1.883E+00	1.838E+00
64	-3.265E-01	-2.956E-01	-2.462E-01	192	1.266E+00	1.295E+00	1.302E+00
65	1.035E+00	1.020E+00	1.003E+00	193	1.074E+00	1.002E+00	1.023E+00
66	3.702E-01	4.307E-01	7.072E-01	194	5.206E-01	4.045E-01	6.549E-01
67	1.424E+00	1.345E+00	1.352E+00	195	1.457E+00	1.378E+00	1.363E+00
68	2.267E-01	2.680E-01	3.037E-01	196	2.715E-01	2.629E-01	2.841E-01
69	1.235E+00	1.249E+00	1.146E+00	197	1.264E+00	1.271E+00	1.175E+00
70	9.944E-01	6.485E-01	5.248E-01	198	1.337E+00	1.305E+00	1.306E+00

71	1.539E+00	1.492E+00	1.612E+00	199	1.555E+00	1.571E+00	1.657E+00
72	3.815E-01	3.360E-01	-9.526E-02	200	3.341E-01	4.147E-01	-3.648E-01
73	1.163E+00	1.144E+00	1.117E+00	201	1.188E+00	1.185E+00	1.161E+00
74	6.734E-01	7.656E-01	1.014E+00	202	6.198E-01	7.208E-01	1.157E+00
75	1.568E+00	1.438E+00	1.455E+00	203	1.582E+00	1.465E+00	1.513E+00
76	3.409E-01	3.317E-01	3.856E-01	204	3.839E-01	3.651E-01	3.814E-01
77	1.180E+00	1.284E+00	1.284E+00	205	1.214E+00	1.256E+00	1.292E+00
78	1.244E+00	1.214E+00	-9.526E-02	206	1.361E+00	1.363E+00	1.312E+00
79	1.753E+00	1.598E+00	1.744E+00	207	1.793E+00	1.693E+00	1.669E+00
80	1.548E-01	1.388E-01	2.020E-01	208	1.889E-01	1.275E-01	2.534E-01
81	1.027E+00	1.133E+00	1.093E+00	209	1.066E+00	1.174E+00	1.133E+00
82	3.906E-01	7.505E-01	5.705E-01	210	4.999E-01	8.207E-01	5.813E-01
83	1.420E+00	1.357E+00	1.543E+00	211	1.478E+00	1.416E+00	1.497E+00
84	3.252E-01	3.136E-01	2.804E-01	212	3.814E-01	3.138E-01	2.889E-01
85	1.351E+00	1.309E+00	1.224E+00	213	1.396E+00	1.265E+00	1.233E+00
86	8.781E-01	8.095E-01	7.109E-01	214	9.458E-01	9.161E-01	5.875E-01
87	1.614E+00	1.580E+00	1.433E+00	215	1.672E+00	1.632E+00	1.553E+00
88	3.222E-01	2.298E-01	2.157E-01	216	3.505E-01	2.525E-01	2.364E-01
89	1.216E+00	1.077E+00	1.247E+00	217	1.211E+00	1.138E+00	1.235E+00
90	1.363E+00	1.280E+00	1.317E+00	218	1.391E+00	1.231E+00	1.355E+00
91	1.751E+00	1.457E+00	1.182E+00	219	1.783E+00	1.510E+00	1.199E+00
92	4.428E-01	4.082E-01	3.181E-01	220	4.227E-01	4.548E-01	3.671E-01
93	1.157E+00	1.227E+00	1.604E+00	221	1.281E+00	1.254E+00	1.661E+00
94	1.286E+00	1.268E+00	8.167E-01	222	1.338E+00	1.379E+00	9.531E-01
95	1.994E+00	2.018E+00	1.307E+00	223	2.148E+00	1.965E+00	1.584E+00
96	2.671E-02	2.594E-01	3.397E-01	224	9.324E-02	3.575E-01	3.522E-01
97	1.164E+00	1.080E+00	9.321E-01	225	1.212E+00	1.086E+00	1.044E+00
98	5.998E-01	6.076E-01	5.081E-01	226	6.128E-01	6.136E-01	6.060E-01
99	1.442E+00	1.442E+00	1.375E+00	227	1.484E+00	1.507E+00	1.396E+00
100	2.390E-01	3.554E-01	3.426E-01	228	2.820E-01	3.848E-01	3.156E-01
101	1.287E+00	1.307E+00	1.144E+00	229	1.368E+00	1.287E+00	1.128E+00
102	1.200E+00	7.495E-01	3.967E-01	230	1.369E+00	1.352E+00	1.358E+00
103	1.561E+00	1.517E+00	1.898E+00	231	1.381E+00	1.765E+00	2.113E+00
104	3.598E-01	3.463E-01	1.200E-01	232	1.314E+00	1.345E+00	1.334E+00
105	1.298E+00	1.125E+00	1.062E+00	233	1.290E+00	1.172E+00	1.119E+00
106	7.577E-01	1.013E+00	1.194E+00	234	1.304E+00	1.377E+00	1.427E+00
107	1.537E+00	1.513E+00	1.464E+00	235	1.490E+00	1.540E+00	1.536E+00
108	4.041E-01	4.038E-01	3.897E-01	236	3.994E-01	4.402E-01	4.173E-01
109	1.293E+00	1.219E+00	1.378E+00	237	1.323E+00	1.307E+00	1.392E+00
110	1.250E+00	1.391E+00	2.451E-01	238	1.400E+00	1.388E+00	1.369E+00
111	1.558E+00	1.764E+00	1.728E+00	239	1.669E+00	1.818E+00	1.834E+00
112	2.700E-01	1.894E-01	1.924E-01	240	2.742E-01	2.235E-01	1.986E-01
113	1.111E+00	1.112E+00	1.173E+00	241	1.137E+00	1.139E+00	1.201E+00
114	7.579E-01	8.342E-01	4.781E-01	242	1.324E+00	1.385E+00	1.349E+00
115	1.464E+00	1.477E+00	1.469E+00	243	1.455E+00	1.574E+00	1.454E+00
116	4.001E-01	3.104E-01	2.217E-01	244	5.019E-01	3.255E-01	2.555E-01
117	1.346E+00	1.421E+00	1.312E+00	245	1.388E+00	1.438E+00	1.300E+00
118	1.071E+00	8.967E-01	7.511E-01	246	1.394E+00	1.349E+00	1.411E+00
119	1.616E+00	1.551E+00	1.574E+00	247	1.639E+00	1.580E+00	1.681E+00

3GPP2 C.S0014-B ver 1.0

120	3.329E-01	2.785E-01	3.140E-01	248	3.920E-01	2.498E-01	3.523E-01
121	1.281E+00	1.209E+00	1.239E+00	249	1.301E+00	1.221E+00	1.285E+00
122	2.805E-01	2.687E-01	1.646E+00	250	1.318E+00	1.342E+00	1.494E+00
123	1.814E+00	1.514E+00	1.510E+00	251	1.910E+00	1.680E+00	1.470E+00
124	6.231E-01	4.200E-01	3.701E-01	252	6.082E-01	5.270E-01	4.173E-01
125	1.255E+00	1.429E+00	1.454E+00	253	1.255E+00	1.477E+00	1.503E+00
126	1.642E+00	1.581E+00	7.112E-01	254	1.807E+00	1.742E+00	6.553E-01
127	1.844E+00	1.963E+00	1.895E+00	255	2.000E+00	2.072E+00	2.051E+00

1
2

1 **10 CHANGE HISTORY FOR C.S0014-0 V1.0 EVRC**

2 **Introduction**

3 The following is catalog of changes that have been adopted for the EVRC ANSI standard.

5 **Bug Fixes and Sanity Checks**

6 Bottom Guard for Offset

- 7 • Text Changes: Modify Sections 4.5.6.2.1-3
- 8 • Floating Point C Sim: cshift.c
- 9 • Fixed Point C Sim: cshift.c
- 10 • Test Vector: ansi_offset.pcm

11 The offset computed in cshiftframe() is used in maxeloc() to index elements in the array residual[]. Under
12 certain circumstances, offset value causes maxeloc() to access elements below residual[0]. A fix constrains the
13 offset so that maxeloc() does not attempt to access residual[] below &residual[0].

14 All-Zeros Packet

- 15 • Text: Create Section 1.4.3
- 16 • Floating Point C Sim: fer.c
- 17 • Fixed Point C Sim: fer.c
- 18 • Test Vector: ansi_zeros.pkt

19 Detect of all-zeros full rate and half rate packets. If such a packet is detected, the frame is erased. This avoids
20 clicks and pops in the decoded speech.

21 All-Ones Packet

- 22 • Text: Modify Section 1.4.2
- 23 • Floating Point C Sim: d_globs.c, d_globs.h, decode.c, fer.c
- 24 • Fixed Point C Sim: d_globs.c, d_rate_1.c, fer.c
- 25 • Test Vector: ansi_ones.pkt

26 Mute after more than 2 all-ones Rate 1/8 packets are received. This fixed an end-of-call buzz problem.

27 Gaussian Noise Fix

- 28 • Text: No change
- 29 • Floating Point C Sim: decode.c
- 30 • Fixed Point C Sim: d_fer.c
- 31 • Test Vector: ansi_fer.pkt

32 This fix has the seed value of the erasure noise random number generator initialized only once at the beginning
33 of a set of consecutive erasure frames. Otherwise, the seed is reloaded for each sub frame generating a "noise

1 envelope" that repeats with the period of a subframe length. It sounds vaguely like the noise from a bug's
2 wings, hence, it has been referred to as the "wing" sound.

3 Delta Delay Check

- 4 • Text: New Section 5.1.3
- 5 • Floating Point C Sim: decode.c
- 6 • Fixed Point C Sim: d_no_fer.c
- 7 • Test Vector: ansi_ddelay.pkt

8 This change increases the integrity checks on the incoming frame to make sure the DDELAY value would yield
9 a valid pitch value. In some cases, out of range pitch values would drive the adaptive post filter berserk.

10 Bandwidth Expansion of Erasure LSPs

- 11 • Text: Modify Section 5.2.1
- 12 • Floating Point C Sim: fer.c
- 13 • Fixed Point C Sim: d_fer.c , d_rate_1.c
- 14 • Test Vector: ansi_fer.pkt

15 This improvement addresses the "buzz" sound. In some cases, valid frames may generate LSP/LPC values that
16 cause the synthesis filter to go unstable. Typically, these values are used for only one frame, but if these frames
17 are followed by a series of erasure frames, the old LSP/LPC values are "reused" causing "rail-to-rail"
18 oscillations of the synthesis filter. This fix interpolates the old LSP values, eventually causing the LSP to go
19 "full spread", which yields LPC coefficients that make the synthesis filter to go to unity gain, passing the
20 erasure noise only.

21 **TTY Changes**

22 This section is to serve as a reminder that the TTY library for C.S0014-0 V1.0 EVRC and 3GPP2 C.S0020-A
23 V1.0 13K have been changed to support both 45.45 baud and 50 baud Baudot code. The library is based on the
24 TTY library, which uses the 40-bit DSP math library. The major differences are:

- 25 1. Supports both 45.45 baud and 50 baud Baudot code.
- 26 2. Makes the half-duplex solution mandatory for mitigating the effects of echo, on both the mobile and the
27 infrastructure.
- 28 3. Applies a minimum input energy threshold to the input signal so that very low level tones (below -50
29 dBm) are not detected and regenerated.
- 30 4. Uses the 40-bit DSP math library.

31
32
33
34
35
36