3GPP TSG CN Plenary
Meeting #10, Bangkok, Thailand
6th – 8th December 2000

Tdoc NP-000635

Source: **TSG_CN WG 4**

Title: **CRs to R97 Work Item Camel Phase 2**

Agenda item: **7.1**

Document for: **APPROVAL**

Introduction:

This document contains 2 CRs on R97 Work Item Camel Phase 2, that have been agreed by TSG_CN WG4, and is forwarded to TSG_N Plenary meeting #10 for approval.

SMG#	TDoc	SPEC	CR	RE	PHAS	VERS	SUBJECT	CAT
CN10	N4-001060	09.02	A313		R97	6.9.0	Clarification in SupportedCamelPhases	F
CN10	N4-001061	09.02	A314		R98	7.6.0	Clarification in SupportedCamelPhases	A

CHANGE REQUEST

GSM 09.02 CR **A313**   rev **-**   Current version: **6.9.0**

Proposed change affects: (U)SIM ☐   ME/UE ☐   Radio Access Network ☐   Core Network ☒

Title:	Clarification in SupportedCamelPhases
Source:	CN4
Work item code:	CAMEL2
Date:	13ᵗʰ November 2000
Category:	**F** Critical correction
Release:	R97

Use one of the following categories:	*Use one of the following releases:*
F *(essential correction)*	*2* *(GSM Phase 2)*
A *(corresponds to a correction in an earlier release)*	*R96* *(Release 1996)*
B *(Addition of feature),*	*R97* *(Release 1997)*
C *(Functional modification of feature)*	*R98* *(Release 1998)*
D *(Editorial modification)*	*R99* *(Release 1999)*
Detailed explanations of the above categories can	*REL-4* *(Release 4)*
be found in 3GPP TR 21.900.	*REL-5* *(Release 5)*

Reason for change:	Currently, it is not clear whether an entity should indicate all CAMEL phases supported or only the highest phase supported.
Summary of change:	Addition of note stating that an entity shall indicate all phases it supports.
Consequences if not approved:	Mis-operation between networks: One network could indicate support of CAMEL Phase 2 only, the receiving network could interpret that to mean the sending entity supports both CAMEL Phase 1 and 2. (There is already evidence of different interpretations of the standard.)

Clauses affected:	17.7.1
Other specs affected:	☒ Other core specifications GSM 09.02-A314 (Tdoc N4-001061)
	☐ Test specifications
	☐ O&M Specifications
Other comments:	The equivalent CRs are not required for the 3G specifications, as the note is already included in 3G TS 29.002.

**** Modified Section ****

17.7.1   Mobile Service data types

.
.
.

```
SupportedCamelPhases ::= BIT STRING {
    phase1 (0),
    phase2 (1) } (SIZE (1..16))
-- A node shall mark in the BIT STRING all CAMEL Phases which it supports.
-- Other values than those listed above shall be discarded.
```

.
.
.

**** End of Document ****

CHANGE REQUEST

GSM 09.02 CR **A314**   rev **-**   Current version: **7.6.0**

Proposed change affects: (U)SIM ☐   ME/UE ☐   Radio Access Network ☐   Core Network ☒

Title:	Clarification in SupportedCamelPhases
Source:	CN4
Work item code:	CAMEL2 ***Date:*** 13th November 2000
Category:	**A** ***Release:*** R98

Use one of the following categories:
   F (essential correction)
   A (corresponds to a correction in an earlier release)
   B (Addition of feature),
   C (Functional modification of feature)
   D (Editorial modification)
Detailed explanations of the above categories can
be found in 3GPP TR 21.900.

Use one of the following releases:
   2   (GSM Phase 2)
   R96   (Release 1996)
   R97   (Release 1997)
   R98   (Release 1998)
   R99   (Release 1999)
   REL-4 (Release 4)
   REL-5 (Release 5)

Reason for change:	Currently, it is not clear whether an entity should indicate all CAMEL phases supported or only the highest phase supported.
Summary of change:	Addition of note stating that an entity shall indicate all phases it supports.
Consequences if not approved:	Mis-operation between networks: One network could indicate support of CAMEL Phase 2 only, the receiving network could interpret that to mean the sending entity supports both CAMEL Phase 1 and 2. (There is already evidence of different interpretations of the standard.)

Clauses affected:	17.7.1
Other specs affected:	☒ Other core specifications GSM 09.02-A313 (Tdoc N4-001060) ☐ Test specifications ☐ O&M Specifications
Other comments:	The equivalent CRs are not required for the 3G specifications, as the note is already included in 3G TS 29.002.

**** Modified Section ****

17.7.1　Mobile Service data types

.
.
.

```
SupportedCamelPhases ::= BIT STRING {
     phase1 (0),
     phase2 (1) } (SIZE (1..16))
-- A node shall mark in the BIT STRING all CAMEL Phases which it supports.
-- Other values than those listed above shall be discarded.
```

.
.
.

**** End of Document ****