

3GPP TSG CN Plenary Meeting #16
5th - 7th June 2002. Marco Island, USA.

NP-020182

Source: CN5 (OSA)
Title: Rel-5 CRs 29.198-xy (OSA API) Addition of support for WSDL realisation
Agenda item: 8.2
Document for: APPROVAL

Doc-1 st -Level	Spec	CR	R v	Pha	Subject	Cat	Ver Curr	Ver New	Doc-2 nd -Level	Work item
NP-020182	29.198-01	006	-	Rel-5	Addition of support for WSDL realisation	B	4.3.1	5.0.0	N5-020440	OSA2
NP-020182	29.198-02	015	-	Rel-5	Addition of support for WSDL realisation	B	4.4.0	5.0.0	N5-020388	OSA2
NP-020182	29.198-03	035	-	Rel-5	Addition of support for WSDL realisation	B	4.5.0	5.0.0	N5-020389	OSA2
NP-020182	29.198-04	038	-	Rel-5	Addition of support for WSDL realisation	B	4.4.0	5.0.0	N5-020390	OSA2
NP-020182	29.198-05	011	-	Rel-5	Addition of support for WSDL realisation	B	4.4.0	5.0.0	N5-020391	OSA2
NP-020182	29.198-06	010	-	Rel-5	Addition of support for WSDL realisation	B	4.4.0	5.0.0	N5-020392	OSA2
NP-020182	29.198-07	006	-	Rel-5	Addition of support for WSDL realisation	B	5.0.0	5.1.0	N5-020393	OSA2
NP-020182	29.198-08	006	-	Rel-5	Addition of support for WSDL realisation	B	4.4.0	5.0.0	N5-020394	OSA2
NP-020182	29.198-11	009	-	Rel-5	Addition of support for WSDL realisation	B	4.3.0	5.0.0	N5-020395	OSA2
NP-020182	29.198-12	017	-	Rel-5	Addition of support for WSDL realisation	B	4.3.0	5.0.0	N5-020396	OSA2

CHANGE REQUEST

⌘ **29.198-01 CR 006** ⌘ rev **-** ⌘ Current version: **4.3.1** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ Addition of support for WSDL realisation		
Source:	⌘ CN5		
Work item code:	⌘ OSA2	Date:	⌘ 17/05/2002
Category:	⌘ B	Release:	⌘ REL-5
	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) REL-4 (Release 4) REL-5 (Release 5)

Reason for change:	⌘ It has been acknowledged that OSA can be realised using different distribution technologies. One of these proposed distribution technologies is SOAP/HTTP. In order to realise OSA using SOAP, a definition of the OSA SCFs for SOAP is required. The chosen definition for SOAP/HTTP in OSA is WSDL. In order to acknowledge WSDL, it is proposed that the following changes be made to the OSA Overview (29.198-01).
Summary of change:	⌘ These changes include: <ul style="list-style-type: none"> • Indicating that OSA is realised though both IDL and WSDL. • Providing an Informative Annex which specifies how the WSDL is created based on provided mapping from UML.
Consequences if not approved:	⌘ Lack of interoperability between OSA gateways which include SOAP as a transportation mechanism.

Clauses affected:	⌘ 2, 3.2, 5
Other specs affected:	⌘ <input type="checkbox"/> Other core specifications ⌘ <input type="checkbox"/> <input type="checkbox"/> Test specifications ⌘ <input type="checkbox"/> <input type="checkbox"/> O&M Specifications ⌘ <input type="checkbox"/>
Other comments:	⌘ <input type="text"/>

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: http://www.3gpp.org/3G_Specs/CRs.htm. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be

downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "3G Vocabulary".
- [2] 3GPP TS 22.127: "Stage 1 Service Requirement for the Open Service Access (OSA) (Release 4)".
- [3] 3GPP TS 23.127: "Virtual Home Environment (Release 4)".
- [4] 3GPP TS 23.078: "CAMEL Phase 3, stage 2".
- [5] 3GPP TS 22.101: "Universal Mobile Telecommunications System (UMTS): Service Aspects; Service Principles".
- [6] World Wide Web Consortium Composite Capability/Preference Profiles (CC/PP): A user side framework for content negotiation (www.w3.org).
- [7] 3GPP TS 29.002: "Mobile Application Part (MAP)".
- [8] 3GPP TS 29.078: "CAMEL Phase 3, , CAMEL Application Part (CAP) Specification".
- [9] Wireless Application Protocol (WAP), Version 1.2, UAPProf Specification (www.wapforum.org).
- [10] Wireless Application Protocol (WAP), version 1.2, WAP Service Indication specification, (www.wapforum.org).
- [11] Wireless Application Protocol (WAP), version 1.2, WAP Push Architecture Overview (www.wapforum.org).
- [12] Wireless Application Protocol (WAP), version 1.2, WAP Architecture (www.wapforum.org).
- [13] SUN IDL Compiler (www.javasoft.com/products/jdk/idl/index.html).
- [14] UML Unified Modelling Language (www.rational.com/uml).
- [15] Object Management Group (www.omg.org).
- [16] 3GPP TS 22.002: "Circuit Bearer Services supported by a PLMN".
- [17] 3GPP TS 22.003: "Circuit Teleservices supported by a PLMN".
- [18] 3GPP TS 24.002: "Public Land Mobile Network (PLMN) Access Reference Configuration".
- [19] ITU-T Q.763: "Signalling System No. 7 – ISDN user part formats and codes".
- [20] ITU-T Q.931: "ISDN user-network interface layer 3 specification for basic call control".
- [21] ISO 8601: "Data elements and interchange formats -- Information interchange -- Representation of dates and times".
- [22] ISO 4217: "Codes for the representation of currencies and funds".

- [23] 3GPP TS 22.121: "Service aspects; The Virtual Home Environment (Release 4)".
- [24] <http://www.parlay.org>
- [25] <http://www.java.sun.com/products/jain>
- [26] 3GPP TS 23.057: "Mobile Station Application Execution Environment (MExE)".
- [27] <http://www.w3c.org>

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 22.101 [5] and the following apply.

Applications: Services, which are designed using Service Capability Features (SCFs).

Gateway: Synonym for Service Capability Server (SCS). From the viewpoint of applications, an SCS can be seen as a gateway to the core network.

HE-VASP: Home Environment Value Added Service Provider. This is a VASP that has an agreement with the Home Environment to provide services.

Home Environment: responsible for overall provision of services to users.

Local Service: A service, which can be exclusively provided in the current serving network by a Value Added Service Provider.

OSA Interface: Standardised Interface used by application to access service capability features.

Personal Service Environment (PSE): contains personalised information defining how subscribed services are provided and presented towards the user. The Personal Service Environment is defined in terms of one or more User Profiles.

Service Capabilities: Bearers defined by parameters, and/or mechanisms needed to realise services. These are within networks and under network control.

Service Capability Feature (SCF): Functionality offered by service capabilities that are accessible via the standardised OSA interface.

Service Capability Server (SCS): Functional Entity providing OSA interfaces towards an application.

Service: term used as an alternative for Service Capability Feature in this specification.

User Interface Profile: Contains information to present the personalised user interface within the capabilities of the terminal and serving network.

User Profile: This is a label identifying a combination of one user interface profile, and one user services profile.

User Services Profile: Contains identification of subscriber services, their status and reference to service preferences.

Value Added Service Provider: provides services other than basic telecommunications service for which additional charges may be incurred.

Virtual Home Environment: A concept for personal service environment portability across network boundaries and between terminals.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply.

API	Application Programming Interface
CAMEL	Customised Application for Mobile network Enhanced Logic
CAP	CAMEL Application Part
CSE	CAMEL Service Environment
FW	Framework
HE	Home Environment
HE-VASP	Home Environment - Value Added Service Provider
HLR	Home Location Register
INAP	Intelligent Networks Application Part
IDL	Interface Description Language
MAP	Mobile Application Part
ME	Mobile Equipment
ME _x E	Mobile Station (Application) Execution Environment
MS	Mobile Station
MSC	Mobile Switching Centre
OSA	Open Service Access
PLMN	Public Land Mobile Network
PSE	Personal Service Environment
SAT	SIM Application Tool-Kit
SCF	Service Capability Feature
SCP	Service Control Point
SCS	Service Capability Server
SIM	Subscriber Identity Module
SMS	Short Message Service
SMTP	Simple Mail Transfer Protocol
UE	User Equipment
USIM	Universal Subscriber Identity Module
VLR	Visited Location Register
VASP	Value Added Service Provider
VHE	Virtual Home Environment
WAP	Wireless Application Protocol
WGP	Wireless Gateway Proxy
WPP	Wireless Push Proxy
<u>WSDL</u>	<u>Web Services Definition Language</u>

4 Open Service Access APIs

The OSA-specifications define an architecture that enables service application developers to make use of network functionality through an open standardised interface, i.e. the OSA APIs. The network functionality is describes as Service Capability Features (SCFs) or Services. The OSA Framework is a general component in support of Services (Service Capabilities) and Applications. The concepts and the functional architecture for the OSA are contained in 3GPP TS 23.127 [3]. The requirements for OSA are contained in 3GPP TS 22.127 [2].

The OSA API is split into three types of interface classes, Service and Framework (FW).

- Interface classes between the Applications and the Framework (FW), that provide applications with basic mechanisms (e.g. Authentication) that enable them to make use of the service capabilities in the network.
- Interface classes between Applications and SCFs, which are individual services that may be required by the client to enable the running of third party applications over the interface e.g. Messaging type service.
- Interface classes between the Framework (FW) and the SCFs, that provide the mechanisms necessary for a multi-vendor environment.

These interfaces represent interfaces 1, 2 and 3 in Figure 1 below. The other interfaces are not yet part of the scope of the work.




Figure 1:

Within the OSA concept a set of Service Capability Features (SCFs) has been specified. The OSA documentation is structured in parts. The first Part (the present document) contains an overview, the second Part contains common data definitions, the third Part the Framework interfaces and the following Parts contain the description of the SCFs.

NOTE: The terms 'Service' and 'Service Capability Feature' are used as alternatives for the same concept in the present document. In the OSA API itself the SCFs as identified in the 3GPP requirements and architecture are reflected as 'service', in terms like serviceFactory, serviceDiscovery.

5 Structure of the OSA API (29.198) and Mapping (29.998) documents

The Open Service Access (OSA) Application Programming Interface (API) specifications consist of two sets of documents:

API specification (3GPP TS 29.198)

The Parts of 29.198 - apart from Part 1 (the present document) and Part 2 - define the interfaces, parameters and state models that belong to the API specification. UML (Unified Modelling Language) is used to specify the interface classes.

As such it provides a UML interface class description of the methods (API calls) supported by that interface and the relevant parameters and types. The interfaces are specified both in IDL (Interface Description Language) and WSDL (Web Services Definition Language).

Mapping specification of the OSA APIs and network protocols (3GPP TR 29.998)

The Parts of 29.998 contain a possible mapping from the APIs defined in 29.198 to various network protocols (i.e. MAP [7], CAP [8], etc.). It is an informative document, since this mapping is considered as implementation- / vendor-dependent. On the other hand this mapping will provide potential service designers with a better understanding of the relationship of the OSA API interface classes and the behaviour of the network associated to these interface classes.

The purpose of the OSA API is to shield the complexity of the network, its protocols and specific implementation from the applications. This means that applications do not have to be aware of the network nodes, a Service Capability Server interacts with, in order to provide the SCFs to the application. The specific underlying network and its protocols are transparent to the application.

The **API specification** (3GPP TS 29.198) is structured in the following Parts:

29.198-1	Part 1:	Overview
29.198-2	Part 2:	Common Data Definitions
29.198-3	Part 3:	Framework
29.198-4	Part 4:	Call Control SCF
29.198-5	Part 5:	User Interaction SCF
29.198-6	Part 6:	Mobility SCF
29.198-7	Part 7:	Terminal Capabilities SCF
29.198-8	Part 8:	Data Session Control SCF
29.198-9	Part 9:	Generic Messaging SCF
29.198-10	Part 10:	Connectivity Manager SCF
29.198-11	Part 11:	Account Management SCF
29.198-12	Part 12:	Charging SCF

The **Mapping specification of the OSA APIs and network protocols** (3GPP TR 29.998) is also structured as above. A mapping to network protocols is however not applicable for all Parts, but the numbering of Parts is kept. Also in case a Part is not supported in a Release, the numbering of the parts is maintained.

Structure of the Parts of 29.198

The Parts with API specification themselves are structured as follows:

- The Sequence diagrams give the reader a practical idea of how each of the SCF is implemented.
- The Class relationships clause shows how each of the interfaces applicable to the SCF, relate to one another.
- The Interface specification clause describes in detail each of the interfaces shown within the Class diagram part.
- The State Transition Diagrams (STD) show the progression of internal processes either in the application, or Gateway.
- The Data definitions clauses show a detailed expansion of each of the data types associated with the methods within the classes. It is to be noted that some data types are used in other methods and classes and are therefore defined within the Common Data types part of this specification.
- IDL description of the interface (normative Annex).
- [WSDL description of the interfaces \(informative Annex\).](#)

6 Methodology

Following is a description of the methodology used for the establishment of API specification for OSA.

6.1 Tools and Languages

The Unified Modelling Language (UML) [14] is used as the means to specify class and state transition diagrams.

6.2 Packaging

A hierarchical packaging scheme is used to avoid polluting the global name space. The root is defined as:

org.csapi

6.3 Colours

For clarity, class diagrams follow a certain colour scheme. Blue for application interface packages and yellow for all the others.

6.4 Naming scheme

The following naming scheme is used for documentation.

packages

lowercase.

Using the domain-based naming (For example, org.csapi)

classes, structures and types. Start with T

TpCapitalizedWithInternalWordsAlsoCapitalized

Exception class:

TpClassNameEndsWithException

Interface. Start with Ip:

IpThisIsAnInterface

constants:

P_UPPER_CASE_WITH_UNDERSCORES_AND_START_WITH_P

methods:

firstWordLowerCaseButInternalWordsCapitalized()

method's parameters

firstWordLowerCaseButInternalWordsCapitalized

collections (set, array or list types)

TpCollectionEndsWithSet

class/structure members

FirstWordAndInternalWordsCapitalized

Spaces in-between words are not allowed.

6.5 State Transition Diagram text and text symbols

The descriptions of the State Transitions in the State Transition Diagrams follow the convention:

when_this_event_is_received [guard condition is true] /do_this_action ^send_this_message

Furthermore, text underneath a line through the middle of a State indicates an exit or entry event (normally specified which one).

6.6 Exception handling and passing results

OSA methods communicate errors in the form of exceptions. OSA methods themselves always use the return parameter to pass results. If no results are to be returned a void is used instead of the return parameter. In order to support mapping to as many languages as possible, no method *out* parameters are allowed.

6.7 References

In the interface specification whenever Interface parameters are to be passed as an *in* parameter, they are done so by reference, and the "Ref" suffix is appended to their corresponding type (e.g. IpAnInterfaceRef anInterface), a reference can also be viewed as a logical indirection.

Original type	IN parameter declaration	
IpInterface	parm : IN IpInterfaceRef	

6.8 Strings and Collections

For character strings, the *String* data type is used without regard to the maximum length of the string.

For homogeneous collections of instances of a particular data type the following naming scheme is used: <datatype>Set

6.9 Prefixes

OSA constants and data types are defined in the global name space: *org.csapi*.

Annex A (normative): OMG IDL

A.1 Tools and Languages

The Object Management Group's (OMG) [15] Interface Definition Language (IDL) is used as a means to programmatically define the interfaces. IDL files are either generated manually from class diagrams or by using a UML tool. In the case IDLs are manually written and/or being corrected manually, correctness has been verified using a CORBA2 (orbos/97-02-25) compliant IDL compiler, e.g. [13].

A.2 Strings and Collections

In IDL, the data type *String* is typedefed (see Note below) from the CORBA primitive *string*. This CORBA primitive is made up of a length and a variable array of byte.

NOTE: A *typedef* is a type definition declaration in IDL.

In OMG IDL, this maps to a sequence of the data type. A CORBA sequence is implicitly made of a length and a variable array of elements of the same type.

Example 1: `typedef sequence<TpSessionID> TpSessionIDSet;`

Collection types can be implemented (for example, in C++) as a structure containing an integer for the *number* part, and an array for the *data* part.

Example 2: The `TpAddressSet` data type may be defined in C++ as:

```
typedef struct {
    short    number;
    TpAddress address [];
} TpAddressSet;
```

The array "address" is allocated dynamically with the exact number of required `TpAddress` elements based on "number".

A.3 Naming space across CORBA modules

The following shows the naming space used in this specification.

```
module org {
  module csapi {
    /* The fully qualified name of the following constant is
    org::csapi::P_THIS_IS_AN_OSA_GLOBAL_CONST */
    const long P_THIS_IS_AN_OSA_GLOBAL_CONST= 1999;
    // Add other OSA global constants and types here
    module fw {
      /* no scoping required to access P_THIS_IS_AN_OSA_GLOBAL_CONST */
      const long P_FW_CONST= P_THIS_IS_AN_OSA_GLOBAL_CONST;
    };
    module mm {
      // scoping required to access P_FW_CONST
      const long P_M_CONST= fw::P_FW_CONST;
    };
  };
};
```

Annex B (informative):

W3C WSDL

B.1 Tools and Languages

The W3C [27] WSDL (Web Services Definition Language) is an XML format for describing network services as a set of endpoints operating on messages containing either document-oriented or procedure-oriented information. WSDL files are generated from the UML model using scripts. The generated WSDL files are verified using WSDL compilers, such as ~~CapeClear's CapeStudio or IBM's WSTK~~. The WSDL is based on W3C WSDL 1.1

B.2 Proposed Namespaces for the OSA WSDL

Namespaces are an important part of an XML Schema. They are used to qualify the source of a particular XML element.

There are several XML/SOAP/WSDL related Namespaces which are used within each of the WSDL documents. The Namespace Prefix and the Namespace are noted below.

`xmlns:wSDL = 'http://http://schemas.xmlsoap.org/wSDL/'`

`xmlns:soap='http://schemas.xmlsoap.org/wSDL/soap/'`

`xmlns:SOAP-ENC='http://schemas.xmlsoap.org/soap/encoding/'`

`xmlns:xsd='http://www.w3c.org/2001/XMLSchema'`

There are also OSA specific namespaces which are used within the OSA WSDL documents. The OSA related namespaces present within each WSDL document depends on the WSDL document and which WSDL documents it imports. The guidelines used to derive these namespaces are:

- The root namespace for the OSA WSDL and XML schemas is <http://www.csapi.org/>
- There is one document generated for each component (Module) within the Analysis UML model. The document will have the name of the UML component with the extension '.wSDL' For each wSDL document generated the following additional namespaces will be included:
 - `xmlns:<component name>='http://www.csapi.org/<component name>/wSDL'`
 - `xmlns:<component name>xsd='http://www.csapi.org/<component name>/schema'`
 - For each OSA wSDL document which is referenced by an import statement within the current wSDL document then the following additional namespaces will be included.
 - `xmlns:<imported component name>='http://www.csapi.org/<imported component name>/wSDL'`
 - `xmlns:<imported component name>xsd='http://www.csapi.org/<imported component name>/schema'`
- Attributes which require a QName value shall use the appropriate Namespace Prefix (as defined in the definitions element of the wSDL file) to qualify the element being referenced.

The namespaces are defined within the 'definitions' element of a wsdl document. For example, the definitions element of the am.wsdl document would look like:

```
<definitions
  name='am'
  targetNamespace='http://www.csapi.org/am/wsdl'
  xmlns='http://schemas.xmlsoap.org/wsdl/'
  xmlns:wsdl='http://schemas.xmlsoap.org/wsdl/'
  xmlns:soap='http://schemas.xmlsoap.org/wsdl/soap/'
  xmlns:SOAP-ENC='http://schemas.xmlsoap.org/soap/encoding/'
  xmlns:xsd='http://www.w3.org/2001/XMLSchema'
  xmlns:am='http://www.csapi.org/am/wsdl'
  xmlns:amxsd='http://www.csapi.org/am/schema'
  xmlns:osa='http://www.csapi.org/osa/wsdl'
  xmlns:osaxsd='http://www.csapi.org/osa/schema'>

<import namespace='http://www.csapi.org/osa/wsdl'
  location='osa.wsdl' />
```

B.3 Object References

Object references are used to identify a particular remote object instance. Object references are used in two ways:

1. Passed as a parameter within a method to a remote object.
2. Included within a message to identify the object for which the message is intended.

Within the context of SOAP, an object reference can be represented as a URL appended with a String. The String suffix identifies the particular remote object instance in the context of the URL.

An object reference will be represented by the new type ObjectRef. The ObjectRef type is defined within osa.wsdl as:

```
<xsd:simpleType name='Objectref'>
  <xsd:restriction base='xsd:anyURI' />
</xsd:simpleType>
```

When an object reference is passed as a parameter, the parameter type is defined as a reference to an interface. Each interface will have a corresponding reference type associated with it. The interface reference will be defined as:

```
<xsd:simpleType name='InterfaceNameRef'>
  <xsd:restriction base='osaxsd:ObjectRef' />
</xsd:simpleType>
where InterfaceName is the name of the particular interface.
```

When an object reference is used to identify the intended recipient of a message, then the object reference is included in the SOAP Header element as an ObjectRefHeader. The ObjectRefHeader is defined in the osa.wsdl document as follows:

```
<message name='ObjectRefHeader'>
  <part name='header' element='osaxsd:ObjectRef' />
</message>
```

Within each method, the ObjectRefHeader is bound to the message within the wsdl soap:header element of the input message of the binding element. For example:

```
<binding name='IpAccountManagerBinding' type='am:IpAccountManager'>
  <soap:binding style='rpc' transport='http://schemas.xmlsoap.org/soap/http' />
  <operation name='createNotification'>
    <soap:operation
      soapAction='http://www.csapi.org/am/IpAccountManager#createNotification' />
    <input>
      <soap:body
        encodingStyle='http://schemas.xmlsoap.org/soap/encoding/'
        namespace='http://www.csapi.org/am.wsdl' />
      />
    />
  />
```

```

      use='encoded' />
    <soap:header
      message='osaxsd:ObjectRefHeader' part='header' />
  </input>

```

B.4 Mapping UML Data Types → XML Schema

Data Types

<<Constant>>

The UML Constant data type contains the following attributes:

- Name
- Constant Value

This type would then map to the following XML Schema construct:

This mapping assumes that all constants are of type TpInt32

```

<xsd:simpleType name="Name">
  <xsd:restriction base="osaxsd:TpInt32">
    <xsd:minInclusive value="Constant Value" />
    <xsd:maxInclusive value="Constant Value" />
  </xsd:restriction>
</xs:simpleType>

```

<<NameValuePair>>

The UML NameValuePair data type contains the following attributes:

- Name
- Attributes
 - Name

This type would then map to the following XML Schema construct:

```

<xsd:simpleType base="xsd:string" name="Name">
  <xsd:restriction base="xsd:String">
    <xsd:enumeration value="Attribute-Name" />
    <xsd:enumeration value="Attribute-Name" />
    ...
    <xsd:enumeration value="Attribute-Name" />
  </xsd:restriction>
</xsd:simpleType>

```

<<SequenceOfDataElements>>

The UML SequenceOfDataElements data type contains the following attributes:

- Name

- [Roles](#)
 - [Name](#)
 - [Type](#)

[This type would then map to the following XML Schema construct:](#)

```
<xsd:complexType name="Name"
  <xsd:sequence>
    <xsd:element
      Name="Role-Name"
      type="Role-Type" />
    <xsd:element
      Name="Role-Name"
      type="Role-Type" />
    ...
    <xsd:element
      Name="Role-Name"
      type="Role-Type" />
  </xsd:sequence>
</xsd:complexType>
```

<<TypeDef>>

[The UML TypeDef data type contains the following attributes:](#)

- [Name](#)
- [ImplementationType](#)

[If the Implementation type is a technology specific type, then the following mappings have been made:](#)

[TpBoolean – xsd:boolean](#)

[TpInt32 – xsd:float](#)

[TpFloat – xsd:float](#)

[TpLongString – xsd:string](#)

[TpString – xsd:string](#)

[TpOctet – xsd:hexBinary](#)

[This type would then map to the following XML Schema construct:](#)

```
<complexType name="Name" base="ImplementationType" />
```

<<NumberedSetOfDataElements>>

[The UML NumberedSetOfDataElements data type for sequences types contains the following attributes:](#)

- [Name](#)
- [ImplementationType](#)

[This type would then map to the following XML Schema construct:](#)

```

<xsd:complexType name="Name">
  <xsd:sequence>
    <xsd:element
      name="Name"
      type="ImplementationType"
      minOccurs="0"
      maxOccurs="unbounded" />
  </xsd:sequence>
</xsd:complexType>

```

<<TaggedChoiceOfDataElements>>

The UML TaggedChoiceOfDataElements data type contains the following attributes:

- Name
- SwitchType
- Roles
 - Name
 - Type

This type would then map to the following XML Schema construct:

```

<xsd:complexType name="Name">
  <xsd:element name="SwitchName" type="SwitchType" />
  <xsd:choice>
    <xsd:element name="Role-Name" type="Role-Type" />
    <xsd:element name="Role-Name" type="Role-Type" />
    ...
    <xsd:element name="Role-Name" type="Role-Type" />
  </xsd:choice>
</complexType>

```


B.5 Mapping of UML SCF to WSDL

Mapping of Operations to WSDL *message* element

A UML Operation contains the following attributes:

- Name
- Module Name
- Return Type
- Parameter
 - Name
 - Type

This type would then map to the following XML Schema construct:

```
<message name= "Name">
  <part
    name= "Parameter-Name"
    type= "Parameter-Type" />
  ...
  <part
    name= "Parameter-Name"
    type= "Parameter-Type" />
</message>

<message name= "NameResponse">
  <part name= "return" type= "ReturnType" />
</message>
```

Note: If the ReturnType is void, then no 'type' attribute would be included in the Response message.

Mapping of Exception to WSDL *message* element

A UML Exception has the following attributes:

- Name

All exceptions (except for CommonException), contain a parameter called ExtraInformation which is of type TpString.

This type would then map to the following XML Schema Construct:

```
<message name= "Name">
  <part
    name= "ExtraInformation"
    type= "osaxsd:TpString" />
</message>
```

Mapping of CommonExceptions to WSDL message element

The UML CommonExceptions type has the following attributes:

- Name ("CommonExceptions")

The UML CommonException contains two parameters: ExceptionType which is of type osaxsd:TpInt32 and ExtraInformation which is of type osaxsd:TpString.

This type would then map to the following XML Schema Construct:

```
<message name="CommonExceptions">
  <part
    name="ExceptionType"
    type="osaxsd:TpInt32" />
  <part
    name="ExtraInformation"
    type="osaxsd:TpString" />
</message>
```

Mapping of Interface Class to WSDL portType and binding elements

A UML Interface Class contains the following attributes:

- Name
- Associated module (i.e. component)
- Operations
 - Name
 - Parameters
 - Name
 - Exceptions
 - Name

This type would then map to the following WSDL portType element:

```
<portType name="Name">
  <operation
    name="Operation-Name"
    <input message="Operation-Name"/>
    <output message="Operation-NameResponse"/>
    <fault message="Operation-Exception-Name" />
  ...
  <fault message="Operation-Exception-Name" />
</operation>
...
<operation
  name="Operation-Name"
  <input message="Operation-Name"/>
  <output message="Operation-NameResponse"/>
  <fault name="Operation-Exception-Name" message="Operation-Exception-Name"
/>
...
<fault message="Operation-Exception-Name" />
```

```

</operation>
</portType>

```

This type would also then map into the following WSDL binding element:

```

<binding
  name="Interface-NameBinding"
  type="Interface-Name">
  <soap:binding style="rpc" transport="http://schemas.xmlsoap.org/soap/http"/>
  <operation name="Operation-Name">
    <soap:operation soapAction="http://www.csapi.org/am/Name#Operation-Name"/>
    <input>
      <soap:body
        encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
        namespace="http://www.csapi.org/Module-Name.wsdl"
        use="encoded"/>
      <soap:header message="osaxsd:ObjRefHeader" part="header" />
    </input>
    <output>
      <soap:body
        encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
        namespace=" http://www.csapi.org/Module-Name.wsdl "
        use="encoded"/>
    </output>
    <fault>
      <soap:fault name="Operation-Exception-Name"
        encodingStyle="http://schemas.xmlsoap.org/soap/encoding/"
        namespace="http://www.csapi.org/Module-Name.wsdl"
        use="encoded"/>
    </fault>
    ... additional fault elements
  </operation>
  ... additional operation elements
</binding>

```

Mapping of UML SCF to WSDL service element

A UML Module contains the following attributes:

- Name
- Interfaces
 - Name

This type would then map to the following WSDL service element:

```

<service name="Name">
  <port binding="Interface-NameBinding" name="Interface-Name">
    <soap:address location="http://{Service Address}"/>
  </port>

```

```
... additional port elements  
</service>  
</definitions>
```

Annex C (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Mar 2001	CN_11	NP-010134	047	--	CR 29.198: for moving TS 29.198 from R99 to Rel 4 (N5-010158)	3.2.0	4.0.0
Jun 2001	CN_12	NP-010330	001	--	Corrections to OSA API Rel4 (Correction to IDL namespace to align with that of ETSI and Parlay equivalent APIs: Change org.open_service_access root namespace to org.csapi) (N5-010267)	4.0.0	4.1.0
Sep 2001	CN_13	NP-010464	002	--	Changing references to JAIN	4.1.0	4.2.0
Dec 2001	CN_14	NP-010594	003	--	Replace Out Parameters with Return Types	4.2.0	4.3.0
Dec 2001	CN_14	NP-010594	004	--	Remove the perception that the OSA API only uses CORBA for its transport mechanism	4.2.0	4.3.0
Mar 2002	--	--	--	--	Editorial update (no CR) following Hong Kong CN5#16	4.3.0	4.3.1

CHANGE REQUEST

⌘ **29.198-02 CR 015** ⌘ rev **-** ⌘ Current version: **4.4.0** ⌘

For [HELP](#) on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘	Addition of support for WSDL realisation		
Source:	⌘	CN5		
Work item code:	⌘	OSA2	Date:	⌘ 17/05/2002
Category:	⌘	B	Release:	⌘ REL-5
		<i>Use <u>one</u> of the following categories:</i> F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		<i>Use <u>one</u> of the following releases:</i> 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) REL-4 (Release 4) REL-5 (Release 5)

Reason for change:	⌘	It has been acknowledged that OSA can be realised using different distribution technologies. One of these proposed distribution technologies is SOAP/HTTP. In order to realise OSA using SOAP, a definition of the OSA SCFs for SOAP is required. The chosen definition for SOAP/HTTP in OSA is WSDL. In order to acknowledge WSDL, it is proposed that the following changes be made to this specification.
Summary of change:	⌘	In order to acknowledge WSDL as an alternative technology to realise OSA, it is proposed that an Annex B (informative) be inserted which is entitled "W3C WSDL Description of ..."
Consequences if not approved:	⌘	Lack of interoperability between OSA gateways which include SOAP as a transportation mechanism.

Clauses affected:	⌘	Annex B
Other specs affected:	⌘	<input type="checkbox"/> Other core specifications <input type="checkbox"/> Test specifications <input type="checkbox"/> O&M Specifications
Other comments:	⌘	

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: http://www.3gpp.org/3G_Specs/CRs.htm. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/>. For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

Annex B (informative):

W3C WSDL Description of the Common Data definitions

The W3C WSDL representation of this specification is contained in a text file (osa.wsdl contained in archive 2919802WSDL.ZIP) which accompanies the present document.

CHANGE REQUEST

⌘ **29.198-03 CR 035** ⌘ rev **-** ⌘ Current version: **4.5.0** ⌘

For [HELP](#) on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ Addition of support for WSDL realisation		
Source:	⌘ CN5		
Work item code:	⌘ OSA2	Date:	⌘ 17/05/2002
Category:	⌘ B	Release:	⌘ REL-5
	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) REL-4 (Release 4) REL-5 (Release 5)

Reason for change:	⌘ It has been acknowledged that OSA can be realised using different distribution technologies. One of these proposed distribution technologies is SOAP/HTTP. In order to realise OSA using SOAP, a definition of the OSA SCFs for SOAP is required. The chosen definition for SOAP/HTTP in OSA is WSDL. In order to acknowledge WSDL, it is proposed that the following changes be made to this specification.
Summary of change:	⌘ In order to acknowledge WSDL as an alternative technology to realise OSA, it is proposed that an Annex B (informative) be inserted which is entitled "W3C WSDL Description of ..."
Consequences if not approved:	⌘ Lack of interoperability between OSA gateways which include SOAP as a transportation mechanism.

Clauses affected:	⌘ Annex B		
Other specs affected:	<input type="checkbox"/> Other core specifications <input type="checkbox"/> Test specifications <input type="checkbox"/> O&M Specifications	⌘	
Other comments:	⌘		

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: http://www.3gpp.org/3G_Specs/CRs.htm. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/>. For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

Annex B (informative):

W3C WSDL Description of Framework

The W3C WSDL representation of this specification is contained in text files (fw_data.wsdl, fw_if_access.wsdl, fw_if_app.wsdl, and fw_if_service.wsdl contained in archive 2919803WSDL.ZIP) which accompanies the present document.

CHANGE REQUEST

⌘ **29.198-04 CR 038** ⌘ rev **-** ⌘ Current version: **4.4.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ Addition of support for WSDL realisation		
Source:	⌘ CN5		
Work item code:	⌘ OSA2	Date:	⌘ 17/05/2002
Category:	⌘ B	Release:	⌘ REL-5
	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) REL-4 (Release 4) REL-5 (Release 5)

Reason for change:	⌘ It has been acknowledged that OSA can be realised using different distribution technologies. One of these proposed distribution technologies is SOAP/HTTP. In order to realise OSA using SOAP, a definition of the OSA SCFs for SOAP is required. The chosen definition for SOAP/HTTP in OSA is WSDL. In order to acknowledge WSDL, it is proposed that the following changes be made to this specification.
Summary of change:	⌘ In order to acknowledge WSDL as an alternative technology to realise OSA, it is proposed that an Annex B (informative) be inserted which is entitled "W3C WSDL Description of ..."
Consequences if not approved:	⌘ Lack of interoperability between OSA gateways which include SOAP as a transportation mechanism.

Clauses affected:	⌘ Annex B		
Other specs affected:	<input type="checkbox"/> Other core specifications <input type="checkbox"/> Test specifications <input type="checkbox"/> O&M Specifications	⌘	
Other comments:	⌘		

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: http://www.3gpp.org/3G_Specs/CRs.htm. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under [ftp://ftp.3gpp.org/specs/](http://ftp.3gpp.org/specs/). For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

Annex B (informative):

W3C WSDL Description of Call Control SCF

The W3C WSDL representation of this specification is contained in text files ([common_cc_data.wsdl](#), [gcc_data.wsdl](#), [gcc_interfaces.wsdl](#), [mpcc_interfaces.wsdl](#), and [mpcc_data.wsdl](#) contained in archive 2919804WSDL.ZIP) which accompanies the present document.

CHANGE REQUEST

⌘ **29.198-05 CR 011** ⌘ rev **-** ⌘ Current version: **4.4.0** ⌘

For [HELP](#) on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ Addition of support for WSDL realisation		
Source:	⌘ CN5		
Work item code:	⌘ OSA2	Date:	⌘ 17/05/2002
Category:	⌘ B	Release:	⌘ REL-5
	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) REL-4 (Release 4) REL-5 (Release 5)

Reason for change:	⌘ It has been acknowledged that OSA can be realised using different distribution technologies. One of these proposed distribution technologies is SOAP/HTTP. In order to realise OSA using SOAP, a definition of the OSA SCFs for SOAP is required. The chosen definition for SOAP/HTTP in OSA is WSDL. In order to acknowledge WSDL, it is proposed that the following changes be made to this specification.
Summary of change:	⌘ In order to acknowledge WSDL as an alternative technology to realise OSA, it is proposed that an Annex B (informative) be inserted which is entitled "W3C WSDL Description of ..."
Consequences if not approved:	⌘ Lack of interoperability between OSA gateways which include SOAP as a transportation mechanism.

Clauses affected:	⌘ Annex B		
Other specs affected:	<input type="checkbox"/> Other core specifications <input type="checkbox"/> Test specifications <input type="checkbox"/> O&M Specifications	⌘	
Other comments:	⌘		

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: http://www.3gpp.org/3G_Specs/CRs.htm. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/>. For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

Annex B (informative):

W3C WSDL Description of User Interaction SCF

The W3C WSDL representation of this specification is contained in text files (ui_interfaces.wsdl and ui_data.wsdl contained in archive 2919805WSDL.ZIP) which accompanies the present document.

CHANGE REQUEST

⌘ **29.198-06 CR 010** ⌘ rev **-** ⌘ Current version: **4.4.0** ⌘

For [HELP](#) on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ Addition of support for WSDL realisation		
Source:	⌘ CN5		
Work item code:	⌘ OSA2	Date:	⌘ 17/05/2002
Category:	⌘ B Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .	Release:	⌘ REL-5 Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) REL-4 (Release 4) REL-5 (Release 5)

Reason for change:	⌘ It has been acknowledged that OSA can be realised using different distribution technologies. One of these proposed distribution technologies is SOAP/HTTP. In order to realise OSA using SOAP, a definition of the OSA SCFs for SOAP is required. The chosen definition for SOAP/HTTP in OSA is WSDL. In order to acknowledge WSDL, it is proposed that the following changes be made to this specification.
Summary of change:	⌘ In order to acknowledge WSDL as an alternative technology to realise OSA, it is proposed that an Annex B (informative) be inserted which is entitled "W3C WSDL Description of ..."
Consequences if not approved:	⌘ Lack of interoperability between OSA gateways which include SOAP as a transportation mechanism.

Clauses affected:	⌘ Annex B		
Other specs affected:	⌘ <input type="checkbox"/> Other core specifications	⌘	
	<input type="checkbox"/> Test specifications		
	<input type="checkbox"/> O&M Specifications		
Other comments:	⌘		

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: http://www.3gpp.org/3G_Specs/CRs.htm. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/>. For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

Annex B (informative):

W3C WSDL Description of Mobility SCF

The W3C WSDL representation of this specification is contained in a text file (mm.wsdl contained in archive 2919806WSDL.ZIP) which accompanies the present document.

CHANGE REQUEST

⌘ **29.198-07 CR 006** ⌘ rev **-** ⌘ Current version: **5.0.0** ⌘

For [HELP](#) on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ Addition of support for WSDL realisation		
Source:	⌘ CN5		
Work item code:	⌘ OSA2	Date:	⌘ 17/05/2002
Category:	⌘ B	Release:	⌘ REL-5
	<p>Use <u>one</u> of the following categories:</p> <p>F (correction)</p> <p>A (corresponds to a correction in an earlier release)</p> <p>B (addition of feature),</p> <p>C (functional modification of feature)</p> <p>D (editorial modification)</p> <p>Detailed explanations of the above categories can be found in 3GPP TR 21.900.</p>		<p>Use <u>one</u> of the following releases:</p> <p>2 (GSM Phase 2)</p> <p>R96 (Release 1996)</p> <p>R97 (Release 1997)</p> <p>R98 (Release 1998)</p> <p>R99 (Release 1999)</p> <p>REL-4 (Release 4)</p> <p>REL-5 (Release 5)</p>

Reason for change:	⌘ It has been acknowledged that OSA can be realised using different distribution technologies. One of these proposed distribution technologies is SOAP/HTTP. In order to realise OSA using SOAP, a definition of the OSA SCFs for SOAP is required. The chosen definition for SOAP/HTTP in OSA is WSDL. In order to acknowledge WSDL, it is proposed that the following changes be made to this specification.
Summary of change:	⌘ In order to acknowledge WSDL as an alternative technology to realise OSA, it is proposed that an Annex B (informative) be inserted which is entitled "W3C WSDL Description of ..."
Consequences if not approved:	⌘ Lack of interoperability between OSA gateways which include SOAP as a transportation mechanism.

Clauses affected:	⌘ Annex B		
Other specs affected:	<input type="checkbox"/> Other core specifications <input type="checkbox"/> Test specifications <input type="checkbox"/> O&M Specifications	⌘	
Other comments:	⌘		

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: http://www.3gpp.org/3G_Specs/CRs.htm. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/>. For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

Annex B (informative):

W3C WSDL Description of Terminal Capabilities SCF

The W3C WSDL representation of this specification is contained in a text file (termcap.wsdl contained in archive 2919807WSDL.ZIP) which accompanies the present document.

CHANGE REQUEST

⌘ **29.198-08 CR 006** ⌘ rev **-** ⌘ Current version: **4.4.0** ⌘

For [HELP](#) on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ Addition of support for WSDL realisation		
Source:	⌘ CN5		
Work item code:	⌘ OSA2	Date:	⌘ 17/05/2002
Category:	⌘ B	Release:	⌘ REL-5
	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) REL-4 (Release 4) REL-5 (Release 5)

Reason for change:	⌘ It has been acknowledged that OSA can be realised using different distribution technologies. One of these proposed distribution technologies is SOAP/HTTP. In order to realise OSA using SOAP, a definition of the OSA SCFs for SOAP is required. The chosen definition for SOAP/HTTP in OSA is WSDL. In order to acknowledge WSDL, it is proposed that the following changes be made to this specification.
Summary of change:	⌘ In order to acknowledge WSDL as an alternative technology to realise OSA, it is proposed that an Annex B (informative) be inserted which is entitled "W3C WSDL Description of ..."
Consequences if not approved:	⌘ Lack of interoperability between OSA gateways which include SOAP as a transportation mechanism.

Clauses affected:	⌘ Annex B		
Other specs affected:	<input type="checkbox"/> Other core specifications <input type="checkbox"/> Test specifications <input type="checkbox"/> O&M Specifications	⌘	
Other comments:	⌘		

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: http://www.3gpp.org/3G_Specs/CRs.htm. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/>. For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

[Annex B \(informative\):](#)

[W3C WSDL Description of Data Session Control SCF](#)

[The W3C WSDL representation of this specification is contained in a text file \(dsc.wsdl contained in archive 2919808WSDL.ZIP\) which accompanies the present document.](#)

CHANGE REQUEST

⌘ **29.198-11 CR 009** ⌘ rev **-** ⌘ Current version: **4.3.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ Addition of support for WSDL realisation	
Source:	⌘ CN5	
Work item code:	⌘ OSA2	Date: ⌘ 17/05/2002
Category:	⌘ B Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .	Release: ⌘ REL-5 Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) REL-4 (Release 4) REL-5 (Release 5)

Reason for change:	⌘ It has been acknowledged that OSA can be realised using different distribution technologies. One of these proposed distribution technologies is SOAP/HTTP. In order to realise OSA using SOAP, a definition of the OSA SCFs for SOAP is required. The chosen definition for SOAP/HTTP in OSA is WSDL. In order to acknowledge WSDL, it is proposed that the following changes be made to this specification.
Summary of change:	⌘ In order to acknowledge WSDL as an alternative technology to realise OSA, it is proposed that an Annex B (informative) be inserted which is entitled "W3C WSDL Description of ..."
Consequences if not approved:	⌘ Lack of interoperability between OSA gateways which include SOAP as a transportation mechanism.

Clauses affected:	⌘ Annex B	
Other specs affected:	⌘ <input type="checkbox"/> Other core specifications	⌘ <input type="checkbox"/>
	<input type="checkbox"/> Test specifications	
	<input type="checkbox"/> O&M Specifications	
Other comments:	⌘	

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: http://www.3gpp.org/3G_Specs/CRs.htm. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under [ftp://ftp.3gpp.org/specs/](http://ftp.3gpp.org/specs/). For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

[Annex B \(informative\):](#)

[W3C WSDL Description of Account Management SCF](#)

[The W3C WSDL representation of this specification is contained in a text file \(am.wsdl contained in archive 2919811WSDL.ZIP\) which accompanies the present document.](#)

CHANGE REQUEST

⌘ **29.198-12 CR 017** ⌘ rev **-** ⌘ Current version: **4.3.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ Addition of support for WSDL realisation		
Source:	⌘ CN5		
Work item code:	⌘ OSA2	Date:	⌘ 17/05/2002
Category:	⌘ B	Release:	⌘ REL-5
	Use <u>one</u> of the following categories:		Use <u>one</u> of the following releases:
	F (correction)	2 (GSM Phase 2)	
	A (corresponds to a correction in an earlier release)	R96 (Release 1996)	
	B (addition of feature),	R97 (Release 1997)	
	C (functional modification of feature)	R98 (Release 1998)	
	D (editorial modification)	R99 (Release 1999)	
	Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		REL-4 (Release 4)
			REL-5 (Release 5)

Reason for change:	⌘ It has been acknowledged that OSA can be realised using different distribution technologies. One of these proposed distribution technologies is SOAP/HTTP. In order to realise OSA using SOAP, a definition of the OSA SCFs for SOAP is required. The chosen definition for SOAP/HTTP in OSA is WSDL. In order to acknowledge WSDL, it is proposed that the following changes be made to this specification.
Summary of change:	⌘ In order to acknowledge WSDL as an alternative technology to realise OSA, it is proposed that an Annex B (informative) be inserted which is entitled "W3C WSDL Description of ..."
Consequences if not approved:	⌘ Lack of interoperability between OSA gateways which include SOAP as a transportation mechanism.

Clauses affected:	⌘ Annex B		
Other specs affected:	⌘ <input type="checkbox"/> Other core specifications	⌘	
	<input type="checkbox"/> Test specifications		
	<input type="checkbox"/> O&M Specifications		
Other comments:	⌘		

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: http://www.3gpp.org/3G_Specs/CRs.htm. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under [ftp://ftp.3gpp.org/specs/](http://ftp.3gpp.org/specs/). For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.

- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

[Annex B \(informative\):](#)

[W3C WSDL Description of Charging SCF](#)

[The W3C WSDL representation of this specification is contained in a text file \(cs.wsdl contained in archive 2919812WSDL.ZIP\) which accompanies the present document.](#)