

**TSG-RAN Meeting #14**  
**Kyoto, Japan, 11 - 15 December 2001**

**RP-010808**

**(R2-012772, copy TSG-RAN) Response to LS (R4-011664) on UE Rx-Tx Time Difference measurement**

**Title:** Response to LS (R4-011664) on UE Rx-Tx Time Difference measurement  
**Source:** RAN2  
**To:** RAN4  
**Cc:** RAN  
**Response to:** LS (R4-011664) on UE Rx-Tx Time Difference measurement.  
**Release:** R'99

**Contact Person:**

**Name:** Claudiu Mihailescu  
**Tel. Number:** + 33 1 39 44 31 93  
**E-mail Address:** [cmihaile@nortelnetworks.com](mailto:cmihaile@nortelnetworks.com)

**Attachments:** suggested draft CR on 25.133

---

**1. Overall Description:**

RAN WG2 would like to thank RAN WG4 for their LS on UE Rx-Tx Time Difference Measurement (Tdoc R4-011664). RAN2 would like to inform RAN4 about the outcome of the discussion on UE Rx-Tx Time measurement for R'99 at the RAN2 #25 meeting.

Regarding the UE Rx-Tx Time Difference Type 1, the conclusion of the discussion in RAN2 was that RAN2 would prefer to keep unchanged the current R'99 ASN.1 signalling in RRC. Therefore RAN2 would kindly request RAN4 to consider the granularity of 1 chip used in RRC and update 25.133 accordingly. An example of possible mapping is suggested in the attached draft CR to 25.133.

Regarding the UE Rx-Tx Time Difference Type 2, RAN2 confirms that the changes proposed by RAN4 seem acceptable from RAN2's point of view.

**2. Actions:**

**To RAN4 group.**

**ACTION:** RAN2 asks RAN4 group to consider the attached suggested draft CR on 25.133 and to update the 25.133 by aligning the granularity and the mapping to the ones signalled in 25.331.

**3. Date of Next RAN2 Meetings:**

RAN2_26	7 – 11 January 2002	Sophia Antipolis, France.
RAN2_27	18 – 22 February 2002	Orlando, FL, USA.

## CHANGE REQUEST

⌘ **25.133 CR** ⌘ ev **-** ⌘ Current version: **3.7.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

**Proposed change affects:** ⌘ (U)SIM  ME/UE  Radio Access Network  Core Network

**Title:** ⌘ Correction to the mapping of UE Rx-Tx Time Difference Type 1 and Type 2 SFN-SFN observed time difference type 2

**Source:** ⌘ Nortel Networks

**Work item code:** ⌘ **Date:** ⌘ 12 November 2001

<p><b>Category:</b> ⌘ <b>F</b></p> <p>Use <u>one</u> of the following categories:</p> <p><b>F</b> (correction)  <b>A</b> (corresponds to a correction in an earlier release)  <b>B</b> (addition of feature),  <b>C</b> (functional modification of feature)  <b>D</b> (editorial modification)</p> <p>Detailed explanations of the above categories can be found in 3GPP TR 21.900.</p>	<p><b>Release:</b> ⌘ <b>R99</b></p> <p>Use <u>one</u> of the following releases:</p> <p><b>2</b> (GSM Phase 2)  <b>R96</b> (Release 1996)  <b>R97</b> (Release 1997)  <b>R98</b> (Release 1998)  <b>R99</b> (Release 1999)  <b>REL-4</b> (Release 4)  <b>REL-5</b> (Release 5)</p>
--	--

**Reason for change:** ⌘ There currently is a misalignment between the mapping defined in 25.133 for the UE Rx-Tx time difference type 1 and type 2 measurement and the expectation of the signalling in 25.331.

For Type 1, 25.331 defines 512 values using 9 bits for the return value, while 25.133 defines 8194 values requiring 14 bits

For Type 2 – in particular, 25.331 defines 13 bits (8192 values) for the return value of the measurement while 25.133 defines a mapping with 8194 values (two more than allowed).

**Summary of change:** ⌘ The mapping of the UE Rx-Tx time difference type 1 is corrected to align 25.133 on 25.331 to contain 512 levels.  
 The mapping of the UE Rx-Tx time difference type 2 is corrected to contain only 8192 levels to align with the signalling in 25.331. This is done by removing the last two levels in the current mapping.

**Consequences if not approved:** ⌘ The number of levels in the mapping will exceed the number of 8192 values or 13 bits defined in 25.331 for the signalling message causing a possible misalignment in the number of bits expected for the reporting of the measurement quantity.

Isolated Impact analysis:  
 Correction to a function where the specification was:

- Contradictory between 25.133 and 25.331

Would not affect implementations behaving like indicated in the CR, would affect implementations supporting the corrected functionality otherwise.

The corrected functionality is the UE Rx-Tx time difference type 1 and type 2 measurement.

- If the network implements the change but not the UE, there will be a mismatch in the number of bits expected for the reporting of the

measurement quantity

- If the UE implements the change but not the network, there will be a mismatch in the number of bits expected for the reporting of the measurement quantity

**Clauses affected:** ⌘ 9.1.9-2.2

**Other specs affected:** ⌘  Other core specifications ⌘  Test specifications  
 O&M Specifications

**Other comments:** ⌘

### How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at: [http://www.3gpp.org/3G\\_Specs/CRs.htm](http://www.3gpp.org/3G_Specs/CRs.htm). Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

**Table 9.24**

Reported value	Measured quantity value	Unit
T2_SFN-SFN_TIME_00000	SFN-SFN observed time difference type 2 < -1280.0000	chip
T2_SFN-SFN_TIME_00001	-1280.0000 ≤ SFN-SFN observed time difference type 2 < -1279.9375	chip
T2_SFN-SFN_TIME_00002	-1279.9375 ≤ SFN-SFN observed time difference type 2 < -1279.8750	chip
...	...	...
T2_SFN-SFN_TIME_40959	1279.8750 ≤ SFN-SFN observed time difference type 2 < 1279.9375	chip
T2_SFN-SFN_TIME_40960	1279.9375 ≤ SFN-SFN observed time difference type 2 < 1280.0000	chip
T2_SFN-SFN_TIME_40961	1280.0000 ≤ SFN-SFN observed time difference type 2	chip

9.1.9 UE Rx-Tx time difference

9.1.9.1 UE Rx-Tx time difference type 1

NOTE: This measurement is used for call set up purposes to compensate propagation delay of DL and UL.

The measurement period in CELL\_DCH state is [100 ms]

9.1.9.1.1 Measurement requirement

**Table 9.25**

Parameter	Unit	Accuracy [chip]	Conditions
			Io [dBm]
UE RX-TX time difference	chip	± 1.5	-94...-50

9.1.9.1.2 UE Rx-Tx time difference type 1 measurement report mapping

The reporting range is for UE Rx-Tx time difference type 1 is from 768 ... 1280 chip.

In table 9.26 the mapping of measured quantity is defined. The range in the signalling may be larger than the guaranteed accuracy range.

**Table 9.26**

Reported value	Measured quantity value	Unit
RX-TX_TIME_0000	UE Rx-Tx Time difference type 1 < 768.000	chip
RX-TX_TIME_0001	768.000 ≤ UE Rx-Tx Time difference type 1 < 768.0625	chip
RX-TX_TIME_0002	768.0625 ≤ UE Rx-Tx Time difference type 1 < 768.1250	chip
RX-TX_TIME_0003	768.1250 ≤ UE Rx-Tx Time difference type 1 < 768.1875	chip
...	...	...
RX-TX_TIME_8190	1279.8125 ≤ UE Rx-Tx Time difference type 1 < 1279.8750	chip
RX-TX_TIME_8191	1279.8750 ≤ UE Rx-Tx Time difference type 1 < 1279.9375	chip
RX-TX_TIME_8192	1279.9375 ≤ UE Rx-Tx Time difference type 1 < 1280.0000	chip
RX-TX_TIME_8193	1280.0000 ≤ UE Rx-Tx Time difference type 1	chip

Reported value	Measured quantity value	Unit
RX-TX_TIME_000	UE Rx-Tx Time difference type 1 < 769.0	chip
RX-TX_TIME_001	769.0 ≤ UE Rx-Tx Time difference type 1 < 770.0	chip
RX-TX_TIME_002	770.0 ≤ UE Rx-Tx Time difference type 1 < 771.0	chip
RX-TX_TIME_003	771.0 ≤ UE Rx-Tx Time difference type 1 < 772.0	chip
...	...	...
RX-TX_TIME_509	1278.0 ≤ UE Rx-Tx Time difference type 1 < 1279.0	chip
RX-TX_TIME_510	1279.0 ≤ UE Rx-Tx Time difference type 1 < 1280.0	chip
RX-TX_TIME_511	1280.0 ≤ UE Rx-Tx Time difference type 1	chip

### 9.1.9.2 UE Rx-Tx time difference type 2

NOTE: This measurement is used for UE positioning purposes.

It is optional for a terminal to support a subset of UE positioning methods. This measurement represents an instantaneous value that is time stamped as defined in the IE description in TS 25.331 [16].

#### 9.1.9.2.1 Measurement requirement

**Table 9.27**

Parameter	Unit	Accuracy [chip]	Conditions
			Io [dBm]
UE RX-TX time difference	chip	± TBD	-94...-50

#### 9.1.9.2.2 UE Rx-Tx time difference type 2 measurement report mapping

The reporting range is for *UE Rx-Tx time difference type2* is from 768 ... 1280 chip.

In table 9.28 the mapping of measured quantity is defined. The range in the signalling may be larger than the guaranteed accuracy range.

**Table 9.28**

Reported value	Measured quantity value	Unit
RX-TX_TIME_0000	UE Rx-Tx Time difference type 2 < 768.000	chip
RX-TX_TIME_0001	768.000 ≤ UE Rx-Tx Time difference type 2 < 768.0625	chip
RX-TX_TIME_0002	768.0625 ≤ UE Rx-Tx Time difference type 2 < 768.1250	chip
RX-TX_TIME_0003	768.1250 ≤ UE Rx-Tx Time difference type 2 < 768.1875	chip
...	...	...
RX-TX_TIME_8189	1279.7500 ≤ UE Rx-Tx Time difference type 2 < 1279.8125	chip
RX-TX_TIME_8190	1279.8125 ≤ UE Rx-Tx Time difference type 2 < 1279.8750	chip
RX-TX_TIME_8191	1279.8750 ≤ UE Rx-Tx Time difference type 2 < 1279.9375	chip
RX-TX_TIME_8192	1279.9375 ≤ UE Rx-Tx Time difference type 2 < 1280.0000	chip
RX-TX_TIME_8193	1280.0000 ≤ UE Rx-Tx Time difference type 2	chip

### 9.1.10 Observed time difference to GSM cell

NOTE: This measurement is used to determine the system time difference between UTRAN and GSM cells.

The requirements in this section are valid for terminals supporting UTRA and GSM.

#### 9.1.10.1 Measurement requirement

The measurement period for CELL\_DCH state is equal to the maximum time between two successive BSIC re-confirmations for one particular GSM cell according to sub clause 8.1.2.5.2. The measurement period for CELL\_FACH state is equal to the maximum time between two successive BSIC re-confirmations according to sub clause 8.4.2.5.2.

NOTE: The conditions for which the accuracy requirement in table 9.29 is valid are FFS.

**Table 9.29**

Parameter	Unit	Accuracy [chip]	Conditions
Observed time difference to GSM cell	ms	± 20	

### 9.1.10.2 Observed time difference to GSM cell measurement report mapping

The reporting range is for *Observed time difference to GSM cell* is from 0 ... 3060/13 ms.

In table 9.30 the mapping of measured quantity is defined. The range in the signalling may be larger than the guaranteed accuracy range.