

CR-Form-v7.1

## CHANGE REQUEST

25.306 **CR 106** rev - Current version: 6.3.0

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ☞ symbols.

**Proposed change affects:** | UICC apps  ME  Radio Access Network  Core Network

<b>Title:</b>	<span style="border: 1px solid black; padding: 2px;">☞</span> Definition of Six UE categories for Enhanced Uplink		
<b>Source:</b>	<span style="border: 1px solid black; padding: 2px;">☞</span> Fujitsu, Motorola, NEC, Nokia, Nortel Networks, NTTDocomo, Orange, Philips, Vodafone Group		
<b>Work item code:</b>	<span style="border: 1px solid black; padding: 2px;">☞</span> EDCH-L23	<b>Date:</b>	<span style="border: 1px solid black; padding: 2px;">☞</span> 08/03/2005
<b>Category:</b>	<span style="border: 1px solid black; padding: 2px;">☞</span> <b>B</b> Use <u>one</u> of the following categories: <b>F</b> (correction) <b>A</b> (corresponds to a correction in an earlier release) <b>B</b> (addition of feature), <b>C</b> (functional modification of feature) <b>D</b> (editorial modification) Detailed explanations of the above categories can be found in 3GPP <a href="#">TR 21.900</a> .		<b>Release:</b> <span style="border: 1px solid black; padding: 2px;">☞</span> Rel-6 Use <u>one</u> of the following releases: <b>Ph2</b> (GSM Phase 2) <b>R96</b> (Release 1996) <b>R97</b> (Release 1997) <b>R98</b> (Release 1998) <b>R99</b> (Release 1999) <b>Rel-4</b> (Release 4) <b>Rel-5</b> (Release 5) <b>Rel-6</b> (Release 6) <b>Rel-7</b> (Release 7)

<b>Reason for change:</b>	<span style="border: 1px solid black; padding: 2px;">☞</span> UE categories were discussed at RAN1#40 meeting. The proposed categories classify the UEs in terms of 1) maximum number of E-DCH codes transmitted, 2) support of the 2ms TTI and 3) maximum transport block size (i.e. maximum bit rate). It was agreed that a total of 6 categories would span a reasonable range of configurations. Among the 8 categories that were initially proposed, 5 were agreed in RAN1. Two were felt as close enough to the agreed 5 to be potentially removed. But there was no agreement whether the following category should be included or not: 2xSF2, 10ms TTI <i>only</i> , 20000 bits. This category allows high bit rate for 10ms TTI only configurations. Regardless of the gains a 2ms TTI may bring, undoubtedly there is a benefit in making the 10ms TTI as efficient as possible, and as such there should not be any reasons not to allow a category aiming at doing so. Going even further, the maximum transport block size for 10ms TTI could be increased to 24000 bits. Therefore it is proposed to standardize the 5 categories agreed in RAN1 with a maximum transport size of 24000 bits for the 10ms TTI + the 6 <sup>th</sup> category that maximises the performance of 10ms TTI only configurations.
<b>Summary of change:</b>	<span style="border: 1px solid black; padding: 2px;">☞</span> Table 5.1g added with 6 UE categories
<b>Consequences if not approved:</b>	<span style="border: 1px solid black; padding: 2px;">☞</span> No UE categories defined for E-DCH

<b>Clauses affected:</b>	<span style="border: 1px solid black; padding: 2px;">☞</span> 5.1		
	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="padding: 2px 5px;">Y</td> <td style="padding: 2px 5px;">N</td> </tr> </table>	Y	N
Y	N		

<b>Other specs affected:</b>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Other core specifications	<input type="checkbox"/>
	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Test specifications	
	<input type="checkbox"/>	<input checked="" type="checkbox"/>	O&M Specifications	
<b>Other comments:</b>	<input type="checkbox"/>			

**How to create CRs using this form:**

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>.

Below is a brief summary:

- 1) Fill out the above form. The symbols above marked  contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

## 5.1 Value ranges

**Table 5.1: UE radio access capability parameter value ranges**

		UE radio access capability parameter	Value range
PDCP parameters		Support for RFC 2507	Yes/No
		Support for RFC 3095	Yes/No
		Support for RFC 3095 context relocation	Yes/No
		Support for loss-less SRNS relocation	Yes/No
		Maximum header compression context space	1024, 2048, 4096, 8192, 16384, 32768, 65536, 131072 bytes
		Maximum number of ROHC context sessions	2, 4, 8, 12, 16, 24, 32, 48, 64, 128, 256, 512, 1024, 16384
		Support for Reverse Decompression	Not supported, 1..65535
RLC and MAC-hs parameters		Total RLC AM and MAC-hs buffer size	2, 10, 50, 100, 150, 200, 300, 400, 500, 750, 1000 kBytes
		Maximum number of AM entities	3, 4, 5, 6, 8, 16, 30
		Maximum RLC AM window size	2047, 4095
PHY parameters	Transport channel parameters in downlink	Maximum sum of number of bits of all transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all convolutionally coded transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all turbo coded transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum number of simultaneous transport channels	4, 8, 16, 32
		Maximum number of simultaneous CCTrCH	1, 2, 3, 4, 5, 6, 7, 8
		Maximum total number of transport blocks received within TTIs that end within the same 10 ms interval	4, 8, 16, 32, 48, 64, 96, 128, 256, 512
		Maximum number of TFC	16, 32, 48, 64, 96, 128, 256, 512, 1024
		Maximum number of TF	32, 64, 128, 256, 512, 1024
		Support for turbo decoding	Yes/No
		Transport channel parameters in uplink	Maximum sum of number of bits of all transport blocks being transmitted at an arbitrary time instant
	Maximum sum of number of bits of all convolutionally coded transport blocks being transmitted at an arbitrary time instant		640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
	Maximum sum of number of bits of all turbo coded transport blocks being transmitted at an arbitrary time instant		640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
	Maximum number of simultaneous transport channels		2, 4, 8, 16, 32
	Maximum number of simultaneous CCTrCH of DCH type (TDD only)		1, 2, 3, 4, 5, 6, 7, 8
	Maximum total number of transport blocks transmitted within TTIs that start at the same time		2, 4, 8, 16, 32, 48, 64, 96, 128, 256, 512
	Maximum number of TFC		4, 8, 16, 32, 48, 64, 96, 128, 256, 512, 1024
	Maximum number of TF		32, 64, 128, 256, 512, 1024
	Support for turbo encoding		Yes/No

		UE radio access capability parameter	Value range
	FDD Physical channel parameters in downlink	Maximum number of DPCH/PDSCH codes to be simultaneously received	1, 2, 3, 4, 5, 6, 7, 8
		Maximum number of physical channel bits received in any 10 ms interval (DPCH, PDSCH, S-CCPCH)	600, 1200, 2400, 3600, 4800, 7200, 9600, 14400, 19200, 28800, 38400, 48000, 57600, 67200, 76800
		Support for SF 512	Yes/No
		Support of PDSCH	Yes/No
		Support of HS-PDSCH	Yes/No
		Simultaneous reception of SCCPCH and DPCH	Yes/No
		Simultaneous reception of SCCPCH, DPCH and PDSCH	Yes/No
		Simultaneous reception of SCCPCH, DPCH and HS-PDSCH	Yes/No
		Maximum number of simultaneous S-CCPCH radio links	1 NOTE: Only the value 1 is part of this release of the specification
		Support of dedicated pilots for channel estimation	Yes
	Support of dedicated pilots for channel estimation of HS-DSCH	Yes/No	
	FDD Physical channel parameters in uplink	Maximum number of DPDCH bits transmitted per 10 ms	600, 1200, 2400, 4800, 9600, 19200, 28800, 38400, 48000, 57600
		Support of PCPCH	Yes/No
	TDD 3.84 Mcps physical channel parameters in downlink	Maximum number of timeslots per frame	1..14
Maximum number of physical channels per frame		1, 2, 3..224	
Minimum SF		16, 1	
Support of PDSCH		Yes/No	
Support of HS-PDSCH		Yes/No	
TDD 3.84 Mcps physical channel parameters in uplink	Maximum number of physical channels per timeslot	1..16	
	Maximum Number of timeslots per frame	1..14	
	Maximum number of physical channels per timeslot	1, 2	
	Minimum SF	16, 8, 4, 2, 1	
TDD 1.28 Mcps physical channel parameters in downlink	Support of PUSCH	Yes/No	
	Maximum number of timeslots per subframe	1..6	
	Maximum number of physical channels per subframe	1, 2, 3, ..., 96	
	Minimum SF	16, 1	
	Support of PDSCH	Yes/No	
	Support of HS-PDSCH	Yes/No	
TDD 1.28 Mcps physical channel parameters in uplink	Maximum number of physical channels per timeslot	1..16	
	Support 8PSK	Yes/No	
	Maximum number of timeslots per subframe	1..6	
	Maximum number of physical channels per timeslot	1, 2	
	Minimum SF	16, 8, 4, 2, 1	
RF parameters	FDD RF parameters	UE power class	3, 4 NOTE: Only power classes 3 and 4 are part of this release of the specification
		Tx/Rx frequency separation	190 Mhz 174.8 MHz to 205.2 MHz 134.8 MHz to 245.2 MHz

		UE radio access capability parameter	Value range
RF parameters	TDD 3.84 Mcps RF parameters	UE power class	2, 3 NOTE: Only power classes 2 and 3 are part of this release of the specification
		Radio frequency bands	a), b), c), a+b), a+c), b+c), a+b+c)
	TDD 1.28 Mcps RF parameters	UE power class	2, 3
		Radio frequency bands	a), b), c), a+b), a+c), b+c), a+b+c)
Multi-mode related parameters		Support of UTRA FDD	Yes/No
		Support of UTRA TDD 3.84 Mcps	Yes/No
		Support of UTRA TDD 1.28 Mcps	Yes/No
Multi-RAT related parameters		Support of GSM	Yes/No (per GSM frequency band)
		Support of multi-carrier	Yes/No
		Support of UTRAN to GERAN Network Assisted Cell Change	Yes/No
		Support of ciphering algorithm UEA0	Yes
Security parameters		Support of ciphering algorithm UEA1	Yes
		Support of integrity protection algorithm UIA1	Yes
		Standalone location method(s) supported	Yes/No
UE positioning related parameters		Network assisted GPS support	Network based / UE based / Both / None
		GPS reference time capable	Yes/No
		Support for IPDL	Yes/No
		Support for OTDOA UE based method	Yes/No
		Support for Rx-Tx time difference type 2 measurement	Yes/No
		Support for UE Positioning assisted GPS measurement validity in CELL_PCH and URA_PCH RRC states	Yes
		Support for SFN-SFN observed time difference type 2 measurement	Yes/No
		Need for downlink compressed mode	Yes/No (per frequency band, UTRA mode and RAT)
Measurement related capabilities		Need for uplink compressed mode	Yes/No (per frequency band, UTRA mode and RAT)
		Access Stratum release indicator	R99, REL-4, REL-5
General capabilities		DL capability with simultaneous HS-DSCH configuration	32 kbps, 64 kbps, 128 kbps, 384 kbps

Table 5.1a: FDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes received	Minimum inter-TTI interval	Maximum number of bits of an HS-DSCH transport block received within an HS-DSCH TTI	Total number of soft channel bits
Category 1	5	3	7298	19200
Category 2	5	3	7298	28800
Category 3	5	2	7298	28800
Category 4	5	2	7298	38400
Category 5	5	1	7298	57600
Category 6	5	1	7298	67200
Category 7	10	1	14411	115200
Category 8	10	1	14411	134400
Category 9	15	1	20251	172800
Category 10	15	1	27952	172800
Category 11	5	2	3630	14400
Category 12	5	1	3630	28800

UEs of Categories 11 and 12 support QPSK only.

**Table 5.1b: RLC and MAC-hs parameters for FDD HS-DSCH physical layer categories**

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size [kBytes]
Category 1	6	50
Category 2	6	50
Category 3	6	50
Category 4	6	50
Category 5	6	50
Category 6	6	50
Category 7	8	100
Category 8	8	100
Category 9	8	150
Category 10	8	150
Category 11	6	50
Category 12	6	50

**Table 5.1c: 1.28 Mcps TDD HS-DSCH physical layer categories**

HS-DSCH category	Maximum number of HS-DSCH codes per timeslot	Maximum number of HS-DSCH timeslots per TTI	Maximum number of HS-DSCH transport channel bits that can be received within an HS-DSCH TTI	Total number of soft channel bits
Category 1	12	5	7016	28160
Category 2	12	5	7016	56320
Category 3	12	5	7016	84480
Category 4	16	5	7016	28160
Category 5	16	5	7016	56320
Category 6	16	5	7016	84480
Category 7	12	5	10204	40912
Category 8	12	5	10204	81824
Category 9	12	5	10204	122736
Category 10	16	5	10204	40912
Category 11	16	5	10204	81824
Category 12	16	5	10204	122736
Category 13	16	5	14056	56320
Category 14	16	5	14056	112640
Category 15	16	5	14056	168960

**Table 5.1d: RLC and MAC-hs parameters for 1.28 Mcps TDD HS-DSCH physical layer categories**

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size [kBytes]
Category 1	6	50
Category 2	6	50
Category 3	6	50
Category 4	6	50
Category 5	6	50
Category 6	6	50
Category 7	6	50
Category 8	6	50
Category 9	6	50
Category 10	6	50
Category 11	6	50

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size [kBytes]
Category 12	6	50
Category 13	6	100
Category 14	6	100
Category 15	6	100

**Table 5.1e: 3.84 Mcps TDD HS-DSCH physical layer categories**

HS-DSCH category	Maximum number of HS-DSCH codes per timeslot	Maximum number of HS-DSCH timeslots per TTI	Maximum number of HS-DSCH transport channel bits that can be received within an HS-DSCH TTI	Total number of soft channel bits
Category 1	16	2	12000	52992
Category 2	16	12	12000	52992
Category 3	16	4	24000	105984
Category 4	16	12	24000	105984
Category 5	16	6	36000	158976
Category 6	16	12	36000	158976
Category 7	16	12	53000	211968
Category 8	16	12	73000	264960
Category 9	16	12	102000	317952

**Table 5.1f: RLC and MAC-hs parameters for 3.84 Mcps TDD HS-DSCH physical layer categories**

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size [kBytes]
Category 1	6	50
Category 2	6	50
Category 3	6	50
Category 4	6	50
Category 5	6	100
Category 6	6	100
Category 7	6	150
Category 8	8	150
Category 9	8	200

**Table 5.1g: FDD E-DCH physical layer categories**

<u>E-DCH category</u>	<u>Maximum number of E-DCH codes transmitted</u>	<u>Minimum spreading factor</u>	<u>Support for 10 and 2 ms TTI EDCH</u>	<u>Maximum number of bits of an E-DCH transport block transmitted within a 10 ms E-DCH TTI</u>	<u>Maximum number of bits of an E-DCH transport block transmitted within a 2 ms E-DCH TTI</u>
<u>Category 1</u>	<u>1</u>	<u>SF4</u>	<u>10 ms TTI only</u>	<u>7296</u>	<u>-</u>
<u>Category 2</u>	<u>2</u>	<u>SF4</u>	<u>10 ms and 2 ms TTI</u>	<u>14592</u>	<u>2919</u>
<u>Category 3</u>	<u>2</u>	<u>SF4</u>	<u>10 ms TTI only</u>	<u>14592</u>	<u>-</u>
<u>Category 4</u>	<u>2</u>	<u>SF2</u>	<u>10 ms and 2 ms TTI</u>	<u>24000</u>	<u>5837</u>
<u>Category 5</u>	<u>2</u>	<u>SF2</u>	<u>10 ms TTI only</u>	<u>24000</u>	<u>-</u>
<u>Category 6</u>	<u>4</u>	<u>SF2</u>	<u>10 ms and 2 ms TTI</u>	<u>24000</u>	<u>11520</u>

NOTE: When 4 codes are transmitted in parallel, two codes shall be transmitted with SF2 and two with SF4

