

MIMO Enhancements for Rel-18

RAN Rel-18 Workshop

28th June – 2nd July 2021

RWS-210075

Nokia, Nokia Shanghai Bell

MIMO Enhancements: Motivation

Release 16 added important steps to make Type II codebook and MU-MIMO operation reality with low overhead feedback

Release 17 to finalize especially multi-TRP operation beyond PDSCH to cover PUSCH and also PDCCH/PUCCH

In Release 18 important to focus on clear improvements, not just extending existing functionality

- Keep concise structure in the WID, with minimum number of Feature Leads

In particular the following areas are relevant for Rel-18 enhancements:

- **CSI acquisition enhancements:** performance drops significantly at moderate-to-high speeds already (see slides 5&6)
- **UL MIMO enhancements:** in Rel-16 and Rel-17 the focus has been on DL MIMO enhancements, reducing the gap between DL and UL performance, motivated by the desire to equalize the UL and DL capabilities/performance given the emergence of UL-heavy applications and advanced UEs/CPEs/IAB nodes/Industrial devices
- **Multi-TRP operation:** only DL is supported with mTRP in Rel-16 and Rel-17, UL performance can be enhanced by mTRP operation in UL, e.g. taking into account UEs with multiple panels
- **Multi-beam enhancements:** some topics are not expected to fully conclude in Rel-17 due to lack of time, in particular related to beam enhancements, e.g. L1/L2 mobility

MIMO Enhancements: Objectives

- **CSI acquisition enhancements (FR1 & FR2)**

- CSI acquisition enhancements for higher mobility UEs / High Speed Trains
- Lower the latency of initial acquisition and improve the CSI processing timeline

- **UL enhancements (FR1 & FR2)**

- Support higher rank on UL, frequency selective precoding for >4TX precoders (FR1)
- Support multi layer PUSCH transmission with DFT-S-OFDM

- **Other topics pending on Rel-17 WI progress**

- MPE leftovers (if any) (FR2)
- MPUE with different panel capabilities (FR2)

- **Multi-TRP operation (FR1 & FR2)**

- Support more realistic assumptions (e.g., different TA, beam switching gap) for Multi-TRP operation
- Support UL transmission from a multi-panel UE to two TRPs (simultaneous transmission from two UE panels)
- Multi-codeword encoding for Multi-TRP transmission with single-DCI


- **Multi-beam enhancements (FR1 & FR2)**

- Enhanced TCI framework: enablers for dynamic configuration of separate TCIs
- Improvements to L1/L2-centric mobility (RAN1/RAN2) (FR1&FR2)
- Latency and overhead reduction, including
 - Support of P3 narrow beam alignment procedures
 - Enhanced UE-assisted UL beam switching
- Enhanced interference indication

CSI acquisition enhancements: Background

- **Enhancing CSI reporting for medium and high mobility (FR1 & FR2)**

- Current CSI framework does not consider time variations; each report is an independent snapshot of the channel
 - Introduce mechanisms to track CSI variations in time for higher mobility UEs
 - In fast varying channels, achieve higher CSI accuracy and lower overhead compared to reducing the CSI reporting period



- **Potential means for improving the CSI processing timeline**

- Faster initial CSI acquisition after (re)configuration
- Currently, 'low latency' is possible only with Type-I SP, only 'high latency' is available for Type-II/eType-II
 - Study the use of DMRS for CSI acquisition, to reduce the measurement delay, CSI calculation delay (e.g., fewer ports to measure)
 - Improve timeline for certain CSI quantities
- Currently, outdated CSI measurements may be reported, e.g., when DRX is configured or in case of CPU overbooking
 - Reduce maximum latency between a CSI-RS measurement and CSI reporting

CSI acquisition enhancements: Background

Impact of speed on CSI reporting

- **Both Type I and Type II/eType II suffer significant degradation already at 15 km/h, with Type II/eType II degrading more rapidly**
 - 30% SE loss at 15 km/h for Type II/eType II relative to 3 km/h; 40% loss at 60 km/h
 - 20% SE loss at 15 km/h for Type I relative to 3km/h; 30% loss at 60 km/h
- **Subband CSI impacted more than wideband CSI in SU-MIMO operation**
 - WB Type I performance overtakes SB already at 15 km/h
 - SB reporting degrades more at cell edge



Parameters:

- 3.7GHz US C-Band, ISD=500m, NR-Uma
- All UEs are outdoors and at the same speed
- 10MHz BW, 15kHz SCS,
- Minimum feedback delay = 5msec
- CSI feedback periodicity = 40msec

SU2 = SU-MIMO with max rank 2

MUS1 = MU with SU-MIMO weights (i.e., no ZF) with max rank 1 per UE

MUZ1 = MU with regularized ZF and max rank of 1 per UE





CSI acquisition enhancements: Background

Impact of speed on CSI reporting

- **All feedback schemes suffer significant degradation at 30 km/h, with eType II and fePS Rel17 degrading more rapidly**
 - Relative UE thput gain of fePS Rel17 ,eType II over Type 1 vanishes at 30kmph
 - Relative UE thput gain of fePS Rel17 over eType II is significantly reduced at higher speeds
 - Up to 20% loss in UE thput at MR2 for fePS Rel17 at 30kmph relative to fePS Rel17 at 3kmph
 - In a high LOS scenario, weaker beams/weaker FD components age more quickly, i.e. results in a worse performance.

Parameters:

- 32 APs, 2GHz, ISD=200m, NR-Duma
- Bursty traffic, RU ~65%, MU-MIMO
- All UEs are outdoors and at the same speed
- 20MHz BW, 15kHz SCS,
- Minimum feedback delay = 5msec
- CSI feedback periodicity = 5msec
- Rel.16 regular (configs 1-6)/ Rel.17 fePS ($K_1 = 16, P = 32, \beta = 0.25, 0.5, 0.75, 1$)
- UE thput normalized w.r.t Type I @3kmph



Uplink enhancements: Background

- **Uplink enhancements (FR1 & FR2)**
 - **Support higher rank on UL, frequency selective precoding for >4TX precoders (FR1)**
 - Introduction of IAB and new vertical applications (video camera, robots, drone etc) are requiring for UL enhancement
 - Support for 8 TX codebook and SRS enhancement
 - 8TX with frequency selective precoding did show decent throughput gain.
 - **Support multi layer PUSCH transmission with DFT-S-OFDM**
 - DFT-s-OFDM has advantage of coverage gain over CP-OFDM, however it has a limitation of supporting rank-1 only. Especially for FR2, PAPR gain has more potential to improve UL coverage even when higher rank is supported.

Multi-beam enhancements: Background

- **Support further overhead and latency reduction enhancements**
 - Enable dynamic TCI state switching for periodic RSs
 - In Rel15/16/17 TCI state for periodic RS can be switched only with RRC
 - Reduce activation latency of TCI states
 - In general, MAC based activation used for beam switching assumes always UE's panel switch-on latency (3 ms) which is not needed in all cases (beams under the same panel or panels that are active simultaneously)
 - Support standalone A-TRS
 - Currently P-TRS needs to be configured, A-TRS can only be associated to P-TRS
 - Use cases: A-TRS upon P2 CSI-RS TX beam, NR-U
 - Support dynamic operation of joint and separate TCIs
 - Rel17 expected to configure already in RRC the TCI state being either joint between DL and UL or separate
 - Consider pool of TCI states in RRC and MAC to construct both joint and separate DL/UL TCI states (activation step)
- **Support interference handling enhancements**
 - In Rel-15/16 DCI based interference indication (DMRS CDM group and ports) supported but no explicit interference regarding to other interference
 - Assist dynamically UE to determine its RX according to indicated interference situation
- **UE-assisted UL beam switching**
 - In Rel15/16/17 the gNB explicitly configures/activates/indicates spatial source/TCI state for the UE in uplink, based on L1-RSRP reporting of best DL RS(s)
 - Facilitate UE-assisted UL TX beam selection while keeping control at gNB to account e.g. MPE and beam switching overhead
 - E.g. for dynamic grant and configured grant PUSCH

Multi-TRP enhancements: Background

- Support more realistic assumptions for Multi-TRP operation
 - In both Rel-16 and 17, multi-TRP framework assume unrealistic assumptions (e.g. same TA, no switching gaps)
 - E.g. : In realistic network deployment scenarios, multi-TRP transmissions may not be received within a CP duration.
 - RAN1 shall **identify the realistic assumptions** for supported M-TRP modes (including multi-DCI multi-TRP, PDCCH/PUCCH/PUSCH repetition, and inter-cell multi-TRP operation), and further **consider the required enhancements and changes** to support them.
- Support simultaneous UL transmission from two UE panels
 - All multi-TRP UL schemes (or operation) defined in Rel-16/17 are TDM schemes.
 - E.g. multi-DCI based multi-TRP operation has to guarantee non-overlapping PUSCH scheduling towards multiple TRPs, Rel-17 PUCCH/PUSCH schemes are only TDM.
 - RAN1 shall consider simultaneous UL transmission towards multiple TRPs, including,
 - PUSCH/PUCCH with **fully/partially overlapping in time and frequency** for multi-DCI multi-TRP.
 - **SDM and FDM repetition schemes** for Rel-17 PUCCH/PUSCH schemes
- Multi-codeword encoding for Multi-TRP transmission with single-DCI
 - In Rel-16, single-DCI multi-TRP operation was restricted to use legacy codeword layer mapping.
 - With a simple **extension on codeword layer mapping**, s-DCI based M-TRP operation can be extended to transmission of two codewords where link adaptation can be done per CW basis (optimized per TRP).
- Extending unified TCI framework to Multi-TRP operation.
 - Unified TCI framework is a redundant signalling framework, which is not necessary for multi-TRP operation.

NOKIA

Copyright and confidentiality

The contents of this document are proprietary and confidential property of Nokia. This document is provided subject to confidentiality obligations of the applicable agreement(s).

This document is intended for use of Nokia's customers and collaborators only for the purpose for which this document is submitted by Nokia. No part of this document may be reproduced or made available to the public or to any third party in any form or means without the prior written permission of Nokia. This document is to be used by properly trained professional personnel. Any use of the contents in this document is limited strictly to the use(s) specifically created in the applicable agreement(s) under which the document is submitted. The user of this document may voluntarily provide suggestions, comments or other feedback to Nokia in respect of the contents of this document ("Feedback").

Such Feedback may be used in Nokia products and related specifications or other documentation. Accordingly, if the user of this document gives Nokia Feedback on the contents of this document, Nokia may freely use, disclose, reproduce, license, distribute and otherwise commercialize the feedback in any Nokia product, technology, service, specification or other documentation.

Nokia operates a policy of ongoing development. Nokia reserves the right to make changes and improvements to any of the products and/or services described in this document or withdraw this document at any time without prior notice.

The contents of this document are provided "as is". Except as required by applicable law, no warranties of any kind, either express or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose,

are made in relation to the accuracy, reliability or contents of this document. NOKIA SHALL NOT BE RESPONSIBLE IN ANY EVENT FOR ERRORS IN THIS DOCUMENT or for any loss of data or income or any special, incidental, consequential, indirect or direct damages howsoever caused, that might arise from the use of this document or any contents of this document.

This document and the product(s) it describes are protected by copyright according to the applicable laws.

Nokia is a registered trademark of Nokia Corporation. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.