

RWS-210441

3GPP TSG RAN Rel-18 workshop
Electronic Meeting, June 28 – July 2, 2021
Agenda Item: 4.1

Rel-18 NR Multi-Band Serving Cell

Huawei, HiSilicon




Contents

- Motivations
- Multi-band Serving Cell
- Potential gains
- Potential Objectives



Non-contiguous FDD Spectrum: Large aggregated BW and excellent coverage

FDD Spectrum: Non-contiguous but large aggregated BW

BW of 95% contiguous FDD spectrum <=30MHz




90% operators own more than 1 FDD band




Note: based on statistic info over 1.4~2.6G spectrum of 63 operators.

Non-contiguous spectrum status not change in near future




Non-contiguous bandwidth with Excellent coverage

MB-SC: More efficient to aggregate non-contiguous spectrum



Idle/inactive State



Common signaling (SSB/OSI/paging) in one band


- All carriers are visible and accessible by UEs

Dynamical selection of UL carrier for Initial access

- Synchronized and access to all carriers without SCell procedure

Overhead reduction and offloading from initial access

Connected State



- No need SSB/RS for synch. and AGC settling
- No SCell (de-)activation procedure

BWP-based carrier switching and aggregation


- Instant wideband transmission, load balancing or power saving

L1/L2 overhead reduction

- Single PDCCH scheduling multi-carriers, sharing TRS etc.

Improved experience and capacity

Mobility Management



Simplified Mobility Management


- One RRM for all carriers instead of RRM per carrier
- One handover without SCell addition/releasing procedure
- O&M complexity reduction due to less serving cells

Simplified O&M and better experience

“One serving cell” UE Experience & compact management


MB-SC: Potential gains

Lowest signaling overhead




DL Capacity

Lowest latency of multi-band operation



DL UPT

Least interruption & delay of Mobility



Interruption reduction for Mobility

Optimized signaling overhead, latency & interruption

MB-SC: Potential Objectives

Specify mechanisms for configuring one serving cell over non-contiguous carriers from one or multiple bands [RAN1/2/4],

- Support multiple active DL&UL BWPs in the serving cell for a UE where each BWP is mapped within a carrier of contiguous bandwidth
- Support single PDCCH scheduling PDSCH/PUSCH over multiple BWPs within the serving cell
- Support the operation of initial access related channels/signals being transmitted only in one carrier of the serving cell
- Note: The frequency distance between the non-contiguous carriers in the serving cell may be within a limit such that simplified network and/or UE behavior can be exploited, e.g. the time-frequency synchronization, QCL, etc. from one carrier can be used for another carrier of the serving cell.

Thank you.

Bring digital to every person, home and organization for a fully connected, intelligent world.

**Copyright©2018 Huawei Technologies Co., Ltd.
All Rights Reserved.**

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.



Simulation assumptions: DL capacity (1/3)

Table 1: System level simulation assumptions for single PDCCH

Parameters	Assumption
Carrier frequency	700/800/900 MHz
Bandwidth	10 MHz
SCS	15kHz
Inter-site distance	500m
Antenna	4T2R
Channel model	SCM-UMA-3D
IBLER of PDSCH	10%
Device deployment	80% indoor, 20% outdoor
UE speeds of interest	Indoor users: 3km/h
	Outdoor users (in-car): 30 km/h
Traffic model	Full buffer
Scheduling algorithm	PF
NR UE number per cell	10/15/20
UE speed	3km/h
PDCCH symbols	3
DCI size (excluding CRC)	Legacy DCI scheduling one carrier: 60 bits
	DCI scheduling 3 carriers: 132 bits
Target BLER of PDCCH	1%

Table 2: Configuration assumptions for common signalling

Parameters	Assumption
SSB	4 symbols& 20 RBs @20ms
TRS	2 symbols&2 slots& wideband @20ms
SBI1	14symbols&48 RB @20ms
OSI	14symbols&16 RB @20ms
Paging	14symbols&16 RB @20ms
CORESET0	48RBs&2symbols @20ms

Simulation assumptions: DL UPT (2/3)

Table 3: Evaluation assumptions for UPT and power saving

Common parameters	Assumption
Number of carriers	3
Carrier bandwidth	10MHz
Traffic model	FTP3
Packet size	0.5Mbyte (36.872)
RU	20%
Legacy CA with SCell (de-)activation	Assumption
Deactivate SCell condition	No packet arrival within 100ms
R17 SCell activation delay	12ms
MB-SC	Assumption
Switch to one band condition	No packet arrival within 20ms
The delay of switching back to multi-bands	2ms

Simulation assumptions: Interruption of mobility (3/3)

Table 5. Duration without CA for the mobility between two sites with DAPS

Procedures	Delay
DAPS handover delay 1	46 ms (38.133) Including RRC procedure delay Excluding cell search time since the new PCell is known Including waiting for PRACH occasion
2-step RACH procedure	10 ms gNB sending RAR
DAPS handover delay 2	11 ms (38.133)
SCell addition	16 ms (38.331)
SCell activation	12 ms (R17 DSS discussion) Excluding cell search time since the SCells are known Using temporary RS for activation