

Title: **Agreed CR (Rel-5) to TS 25.306**Source: **TSG-RAN WG2**Agenda item: **7.2.5**

Doc-1st-	Status-	Spec	CR	Rev	Phase	Subject	Cat	Version-	Version
R2-023201	Agreed	25.306	049	3	Rel-5	HSDPA L2 buffer sizes	F	5.2.0	5.3.0
R2-023203	Agreed	25.306	056	-	Rel-5	Correction to Access Stratum release indicator	F	5.2.0	5.3.0
R2-023205	Agreed	25.306	057	-	Rel-5	Dedicated pilot bits for HS-DSCH	F	5.2.0	5.3.0

Sophia Antipolis, France, 12-15 November 2002

CR-Form-v7

CHANGE REQUEST⌘ **25.306 CR 049** ⌘ rev **3** ⌘ Current version: **5.2.0** ⌘For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.**Proposed change affects:** UICC apps ⌘ ME Radio Access Network Core Network

Title:	⌘ HSDPA L2 buffer sizes	
Source:	⌘ Nokia, Siemens and InterDigital	
Work item code:	⌘ HSDPA-L23	Date: ⌘ November 2002
Category:	⌘ F Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification)	Release: ⌘ Rel-5 Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)
Detailed explanations of the above categories can be found in 3GPP <u>TR 21.900</u> .		

Reason for change:	⌘ The minimum total RLC AM and MAC-hs buffer sizes for all UTRA TDD UE categories are still in square brackets. The parameter value ranges for Minimum total RLC AM and MAC-hs buffer size for TDD (3.84 Mcps) needs to be updated in order to reflect correct analysis aligned with FDD. The minimum L2 buffer sizes for some UE categories are still in square brackets.
Summary of change:	⌘ Square brackets are removed and the following minimum total RLC AM and MAC-hs buffer sizes are proposed for UTRA TDD (3.84 Mcps option) UE categories in section 5.1: Category 1 – Category 4: 50 kBytes Category 5 – Category 6: 100 kBytes Category 7 – Category 8: 150 kBytes Category 9: 200 kBytes Added possibility to signal 200, 300, 400, 750 kBytes into parameter value range for Minimum total UTRA TDD RLC AM and MAC-hs buffer size in section 5.1. 3.84 Mcps TDD reference DL combinations updated accordingly in section 5.2.2. Square brackets are removed.
Consequences if not approved:	⌘ Missing critical requirement on minimum L2 UE buffer sizes for HSDPA operation in UTRA TDD. Parameter value range for Minimum total UTRA TDD RLC AM and MAC-hs buffer size needs not suitable for UTRA TDD (3.84 Mcps option). Non-valid reference UE radio access capability combination for the DL of UTRA TDD (3.84 Mcps option). The HSDPA L2 Buffer size value for TDD will not be complete

Clauses affected:	⌘	Tables 5.1d and 5.1f. 5.1, 5.2.2								
Other specs affected:	⌘	<table border="1" style="display: inline-table; vertical-align: middle;"> <tr> <td style="text-align: center;">Y</td> <td style="text-align: center;">N</td> </tr> <tr> <td style="text-align: center;">X</td> <td></td> </tr> <tr> <td style="text-align: center;"></td> <td style="text-align: center;">X</td> </tr> <tr> <td style="text-align: center;"></td> <td style="text-align: center;">X</td> </tr> </table> Other core specifications Test specifications O&M Specifications	Y	N	X			X		X
Y	N									
X										
	X									
	X									
Other comments:	⌘									

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked ⌘ contain pop-up help information about the field that they are closest to.
- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

5.1 Value ranges

Table 5.1: UE radio access capability parameter value ranges

		UE radio access capability parameter	Value range
PDCP parameters		Support for RFC 2507	Yes/No
		Support for RFC 3095	Yes/No
		Support for RFC 3095 context relocation	Yes/No
		Support for loss-less SRNS relocation	Yes/No
		Maximum header compression context space	512, 1024, 2048, 4096, 8192 bytes
RLC and MAC-hs parameters		Total RLC AM and MAC-hs buffer size	2, 10, 50, 100, 200, 150, 200, 300, 400, 500, 750, 1000 kBytes
		Maximum number of AM entities	3, 4, 5, 6, 8, 16, 30
PHY parameters	Transport channel parameters in downlink	Maximum sum of number of bits of all transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all convolutionally coded transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all turbo coded transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum number of simultaneous transport channels	4, 8, 16, 32
		Maximum number of simultaneous CCTrCH	1, 2, 3, 4, 5, 6, 7, 8
		Maximum total number of transport blocks received within TTIs that end within the same 10 ms interval	4, 8, 16, 32, 48, 64, 96, 128, 256, 512
		Maximum number of TFC	16, 32, 48, 64, 96, 128, 256, 512, 1024
	Transport channel parameters in uplink	Maximum number of TF	32, 64, 128, 256, 512, 1024
		Support for turbo decoding	Yes/No
		Maximum sum of number of bits of all transport blocks being transmitted at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all convolutionally coded transport blocks being transmitted at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all turbo coded transport blocks being transmitted at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum number of simultaneous transport channels	2, 4, 8, 16, 32
		Maximum number of simultaneous CCTrCH of DCH type (TDD only)	1, 2, 3, 4, 5, 6, 7, 8
	FDD Physical channel parameters in downlink	Maximum total number of transport blocks transmitted within TTIs that start at the same time	2, 4, 8, 16, 32, 48, 64, 96, 128, 256, 512
		Maximum number of TFC	4, 8, 16, 32, 48, 64, 96, 128, 256, 512, 1024
		Maximum number of TF	32, 64, 128, 256, 512, 1024
		Support for turbo encoding	Yes/No
		Maximum number of DPCH/PDSCH codes to be simultaneously received	1, 2, 3, 4, 5, 6, 7, 8
		Maximum number of physical channel bits received in any 10 ms interval (DPCH, PDSCH, S-CCPCH)	600, 1200, 2400, 3600, 4800, 7200, 9600, 14400, 19200, 28800, 38400, 48000, 57600, 67200, 76800
		Support for SF 512	Yes/No
		Support of PDSCH	Yes/No
		Support of HS-PDSCH	Yes/No
		Simultaneous reception of SCCPCH and DPCH	Yes/No

		UE radio access capability parameter	Value range	
UE radio access capability parameter	FDD Physical channel parameters in uplink	Simultaneous reception of SCCPCH, DPCH and PDSCH	Yes/No	
		Maximum number of simultaneous S-CCPCH radio links	1 NOTE: Only the value 1 is part of this release of the specification	
		Support of dedicated pilots for channel estimation	Yes	
	TDD 3.84 Mcps physical channel parameters in downlink	Maximum number of DPDCH bits transmitted per 10 ms	600, 1200, 2400, 4800, 9600, 19200, 28800, 38400, 48000, 57600	
		Support of PCPCH	Yes/No	
	TDD 3.84 Mcps physical channel parameters in uplink	Maximum number of timeslots per frame	1..14	
		Maximum number of physical channels per frame	1, 2, 3..224	
		Minimum SF	16, 1	
		Support of PDSCH	Yes/No	
		Support of HS-PDSCH	Yes/No	
		Maximum number of physical channels per timeslot	1..16	
	TDD 1.28 Mcps physical channel parameters in downlink	Maximum Number of timeslots per frame	1..14	
		Maximum number of physical channels per timeslot	1, 2	
		Minimum SF	16, 8, 4, 2, 1	
		Support of PUSCH	Yes/No	
	TDD 1.28 Mcps physical channel parameters in uplink	Maximum number of timeslots per subframe	1..6	
		Maximum number of physical channels per subframe	1, 2, 3, ..., 96	
		Minimum SF	16, 1	
		Support of PDSCH	Yes/No	
		Support of HS-PDSCH	Yes/No	
		Maximum number of physical channels per timeslot	1..16	
RF parameters	FDD RF parameters	Support 8PSK	Yes/No	
		Maximum number of timeslots per subframe	1..6	
RF parameters	TDD 3.84 Mcps RF parameters	Maximum number of physical channels per timeslot	1, 2	
		Minimum SF	16, 8, 4, 2, 1	
		Support of 8PSK	Yes/No	
		Support of PUSCH	Yes/No	
		UE power class	3, 4 NOTE: Only power classes 3 and 4 are part of this release of the specification	
	TDD 1.28 Mcps RF parameters	Tx/Rx frequency separation	190 MHz 174.8 MHz to 205.2 MHz 134.8 MHz to 245.2 MHz	
		UE power class	2, 3 NOTE: Only power classes 2 and 3 are part of this release of the specification	
		Radio frequency bands	a), b), c), a+b), a+c), b+c), a+b+c)	
		UE power class	2, 3	
		Radio frequency bands	a), b), c), a+b), a+c), b+c), a+b+c)	
Multi-mode related parameters		Support of UTRA FDD	Yes/No	
		Support of UTRA TDD 3.84 Mcps	Yes/No	
		Support of UTRA TDD 1.28 Mcps	Yes/No	
Multi-RAT related parameters		Support of GSM	Yes/No (per GSM frequency band)	
		Support of multi-carrier	Yes/No	
Security parameters		Support of ciphering algorithm UEA0	Yes	
		Support of ciphering algorithm UEA1	Yes	
		Support of integrity protection algorithm UIA1	Yes	

	UE radio access capability parameter	Value range
UE positioning related parameters	Standalone location method(s) supported	Yes/No
	Network assisted GPS support	Network based / UE based / Both/ None
	GPS reference time capable	Yes/No
	Support for IPDL	Yes/No
	Support for OTDOA UE based method	Yes/No
	Support for Rx-Tx time difference type 2 measurement	Yes/No
	Support for UE Positioning measurement validity in CELL_PCH and URA_PCH RRC states	Yes/No
Measurement related capabilities	Need for downlink compressed mode	Yes/No (per frequency band, UTRA mode and RAT)
	Need for uplink compressed mode	Yes/No (per frequency band, UTRA mode and RAT)
General capabilities	Access Stratum release indicator	R99, REL-4
DL capabilities with simultaneous HS-DSCH	DL capability with simultaneous HS-DSCH configuration	32 kbps, 64 kbps, 128 kbps, 384 kbps

Table 5.1a: FDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes received	Minimum inter-TTI interval	Maximum number of bits of an HS-DSCH transport block received within an HS-DSCH TTI	Total number of soft channel bits
Category 1	5	3	7300	19200
Category 2	5	3	7300	28800
Category 3	5	2	7300	28800
Category 4	5	2	7300	38400
Category 5	5	1	7300	57600
Category 6	5	1	7300	67200
Category 7	10	1	14600	115200
Category 8	10	1	14600	134400
Category 9	15	1	20432	172800
Category 10	15	1	28776	172800
Category 11	5	2	3650	14400
Category 12	5	1	3650	28800

UEs of Categories 11 and 12 support QPSK only.

Table 5.1b: RLC and MAC-hs parameters for FDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size
Category 1	6	50
Category 2	6	50
Category 3	6	50
Category 4	6	50
Category 5	6	{50}
Category 6	6	{50}
Category 7	8	{100}
Category 8	8	{100}
Category 9	8	{150}
Category 10	8	{150}
Category 11	{6}	{50}
Category 12	{6}	{50}

Table 5.1c: 1.28 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes per timeslot	Maximum number of HS-DSCH timeslots per TTI	Maximum number of HS-DSCH transport channel bits that can be received within an HS-DSCH TTI	Total number of soft channel bits	Support of SF=1 for HS-PDSCH
Category 1	12	5	7016	28160	Yes
Category 2	12	5	7016	56320	Yes
Category 3	12	5	7016	84480	Yes
Category 4	16	5	7016	28160	Yes
Category 5	16	5	7016	56320	Yes
Category 6	16	5	7016	84480	Yes
Category 7	12	5	10204	40912	Yes
Category 8	12	5	10204	81824	Yes
Category 9	12	5	10204	122736	Yes
Category 10	16	5	10204	40912	Yes
Category 11	16	5	10204	81824	Yes
Category 12	16	5	10204	122736	Yes
Category 13	16	5	14056	56320	Yes
Category 14	16	5	14056	112640	Yes
Category 15	16	5	14056	168960	Yes

Table 5.1d: RLC and MAC-hs parameters for 1.28 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size
Category 1	6	[50]
Category 2	6	[50]
Category 3	6	[50]
Category 4	6	[50]
Category 5	6	[50]
Category 6	6	[50]
Category 7	6	[50]
Category 8	6	[50]
Category 9	6	[50]
Category 10	6	[50]
Category 11	6	[50]
Category 12	6	[50]
Category 13	6	[100]
Category 14	6	[100]
Category 15	6	[100]

Table 5.1e: 3.84 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes per timeslot	Maximum number of HS-DSCH timeslots per TTI	Maximum number of HS-DSCH transport channel bits that can be received within an HS-DSCH TTI	Total number of soft channel bits	Support of SF=1 for HS-PDSCH
Category 1	16	2	12000	70656	Yes
Category 2	16	12	12000	70656	Yes
Category 3	16	4	24000	141312	Yes
Category 4	16	12	24000	141312	Yes
Category 5	16	6	36000	211968	Yes
Category 6	16	12	36000	211968	Yes
Category 7	16	12	53000	282624	Yes
Category 8	16	12	73000	353280	Yes
Category 9	16	12	102000	423936	Yes

Table 5.1f: RLC and MAC-hs parameters for 3.84 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size
Category 1	6	[50]
Category 2	6	[50]
Category 3	6	[100]50
Category 4	6	[100]50
Category 5	6	[150]100
Category 6	6	[150]100
Category 7	6	[200]150
Category 8	8	[250]150
Category 9	8	[350]200

5.2.2 Combinations of UE Radio Access Parameters for DL

Table 5.2.2.1: UE radio access capability parameter combinations, DL parameters

Reference combination of UE Radio Access capability parameters in DL	32 kbps class	64 kbps class	128 kbps class	384 kbps class	768 kbps class	2048 kbps class
Transport channel parameters						
Maximum sum of number of bits of all transport blocks being received at an arbitrary time instant	640	3840	3840	6400	10240	20480
Maximum sum of number of bits of all convolutionally coded transport blocks being received at an arbitrary time instant	640	640	640	640	640	640
Maximum sum of number of bits of all turbo coded transport blocks being received at an arbitrary time instant	NA	3840	3840	6400	10240	20480(1) 10240(2) NOTE 5
Maximum number of simultaneous transport channels	8 NOTE 4	16 NOTE 4				
Maximum number of simultaneous CCTrCH (FDD)	1 NOTE 3	2/1 NOTE 2 NOTE 3	2/1 NOTE 2 NOTE 3	2 NOTE 3	2 NOTE 3	2 NOTE 3
Maximum number of simultaneous CCTrCH (TDD)	2 NOTE 3	3 NOTE 3	3 NOTE 3	3 NOTE 3	4 NOTE 3	4 NOTE 3
Maximum total number of transport blocks received within TTIs that end at the same time	8	8	16	32	64	96
Maximum number of TFC	32	48	96	128	256	1024
Maximum number of TF	32	64	64	64	128	256
Support for turbo decoding	No	Yes	Yes	Yes	Yes	Yes
Physical channel parameters (FDD)						
Maximum number of DPCH/PDSCH codes to be simultaneously received	1	2/1 NOTE 2	2/1 NOTE 2	3	3	3
Maximum number of physical channel bits received in any 10 ms interval (DPCH, PDSCH, S-CCPCH).	1200	3600/2400 NOTE2	7200/4800 NOTE2	19200	28800	57600
Support for SF 512 for DPCH NOTE 6	No	No	No	No	No	No
Support of PDSCH	No	Yes/No NOTE 1	Yes/No NOTE 1	Yes	Yes	Yes
Support of HS-PDSCH	No	Yes/No NOTE 1				
Maximum number of simultaneous S-CCPCH radio links	1	1	1	1	1	1
Support of dedicated pilots for channel estimation	Yes NOTE 1 NOTE 7					
Physical channel parameters (TDD 3.84 Mcps)						
Maximum number of timeslots per frame	1	2	4	5	10	12
Maximum number of physical channels per frame	8	9	14	28	64	136
Minimum SF	16	16	16	1/16 NOTE 1	1/16 NOTE 1	1/16 NOTE 1
Support of PDSCH	Yes/No NOTE 1	Yes	Yes	Yes	Yes	Yes
Support of HS-PDSCH	No	Yes/No NOTE 1				
Maximum number of physical channels per timeslot	8	9	9	9	9	13
Physical channel parameters (TDD 1.28 Mcps)						
Maximum number of timeslots per subframe	1	2	3	4	6	6
Maximum number of physical	8	12	18	43	77	77

Reference combination of UE Radio Access capability parameters in DL	32 kbps class	64 kbps class	128 kbps class	384 kbps class	768 kbps class	2048 kbps class
channels per subframe						
Minimum SF	16	16	16	1/16 NOTE 1	1/16 NOTE 1	1
Support of PDSCH	Yes/No NOTE 1	Yes	Yes	Yes	Yes	Yes
Support of HS-PDSCH	No	Yes/No NOTE 1	Yes/No NOTE 1	Yes/No NOTE 1	Yes/No NOTE 1	Yes/No NOTE 1
Maximum number of physical channels per timeslot	8	11	14	14	14	14
Support of 8PSK	No	No	No	No	No	Yes

NOTE 1: Options represent different combinations that should be supported with conformance tests.

NOTE 2: Options depend on the support of PDSCH. The highest value is required if PDSCH is supported.

NOTE 3: The given number does not contain the BCH CCTrCH of the current cell nor of the neighbour cells.

NOTE 4: The given number does not contain the BCH of the neighbour cell.

NOTE 5: (1) For FDD and 3.84 Mcps TDD (2) For 1.28 Mcps TDD.

NOTE 6: This UE capability does not relate to the support of CPCH in the uplink for which SF 512 is needed

NOTE 7: A UE conforming to this release of the specification shall set the support of channel estimation based on dedicated pilot bits to TRUE.

The reference combinations for HS-DSCH capabilities are shown in tables 5.2.2.2, 5.2.2.3 and 5.2.2.4. These tables are subject to further discussions in TSG-RAN WG1 and TSG-RAN WG2.

Table 5.2.2.2: FDD UE radio access capability parameter combinations, DL HS-DSCH parameters

Reference combination	1.2 Mbps class	3.6 Mbps class	7 Mbps class	10 Mbps class
RLC and MAC-hs parameters				
Minimum total RLC AM and MAC-hs buffer size (kbytes)	50	{50}	{100}	{150}
Maximum number of AM RLC entities	6	6	8	8
PHY parameters				
FDD HS-DSCH category	Category 1	Category 5	Category 7	Category 9

Table 5.2.2.3: 1.28 Mcps TDD UE radio access capability parameter combinations, DL HS-DSCH parameters

Reference combination	1.4 Mbps class	2.0 Mbps class	2.8 Mbps class
RLC and MAC-HS parameters			
Total RLC AM and MAC-hs buffer size (kbytes)	{50}	{50}	{100}
Maximum number of AM RLC entities	6	6	6
PHY parameters			
1.28 Mcps TDD HS-DSCH Category	Category 1	Category 7	Category 13

Table 5.2.2.4: 3.84 Mcps TDD UE radio access capability parameter combinations, DL HS-DSCH parameters

Reference combination	1.2 Mbps class	2.4 Mbps class	3.6 Mbps class	7.3 Mbps class	10.2 Mbps class
RLC and MAC-hs parameters					
Total minimal RLC AM and MAC-hs buffer size (kbytes)	{50}	{100}, {50}	{150}, {100}	{250}, {150}	{350}, {200}
Maximum number of AM RLC entities	6	6	6	8	8
PHY parameters					
3.84Mcps TDD HS-DSCH category	Category 1	Category 3	Category 5	Category 8	Category 9

CHANGE REQUEST

25.306 CR 056 # rev - # Current version: **5.2.0**

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the # symbols.

Proposed change affects: UICC apps # ME Radio Access Network Core Network

Title:	# Correction to Access Stratum release indicator	
Source:	# Siemens AG	
Work item code:	# TE15	Date: # 21/10/2002
Category:	# F <i>Use one of the following categories:</i> F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification)	Release: # Rel-5 <i>Use one of the following releases:</i> 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)
Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		

Reason for change:	# With current value range of UE radio access capability parameter "Access Stratum release indicator", only up to Rel-4 version of protocol could be indicated to UTRAN.
Summary of change:	# The value range of UE radio access capability parameter "Access Stratum release indicator" is extended for UE to also be able to signal Rel-5 version of protocol. This parameter corresponds to IE "Access stratum release indicator" defined in 25.331. An appropriate CR is provided for 25.331.
Consequences if not approved:	# UE will not be able to signal Rel-5 version of protocol.

Clauses affected:	# 5.1									
Other specs affected:	<table border="1" style="display: inline-table; vertical-align: middle;"> <tr> <td>Y</td> <td>N</td> </tr> <tr> <td>X</td> <td></td> </tr> <tr> <td></td> <td>X</td> </tr> <tr> <td></td> <td>X</td> </tr> </table> Other core specifications Test specifications O&M Specifications	Y	N	X			X		X	# 25.331, CR 1791.
Y	N									
X										
	X									
	X									
Other comments:	#									

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked # contain pop-up help information about the field that they are closest to.

- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

5.1 Value ranges

Table 5.1: UE radio access capability parameter value ranges

		UE radio access capability parameter	Value range
PDCP parameters		Support for RFC 2507	Yes/No
		Support for RFC 3095	Yes/No
		Support for RFC 3095 context relocation	Yes/No
		Support for loss-less SRNS relocation	Yes/No
		Maximum header compression context space	512, 1024, 2048, 4096, 8192 bytes
RLC and MAC-hs parameters		Total RLC AM and MAC-hs buffer size	2, 10, 50, 100, 150, 500, 1000 kBytes
		Maximum number of AM entities	3, 4, 5, 6, 8, 16, 30
PHY parameters	Transport channel parameters in downlink	Maximum sum of number of bits of all transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all convolutionally coded transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all turbo coded transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum number of simultaneous transport channels	4, 8, 16, 32
		Maximum number of simultaneous CCTrCH	1, 2, 3, 4, 5, 6, 7, 8
		Maximum total number of transport blocks received within TTIs that end within the same 10 ms interval	4, 8, 16, 32, 48, 64, 96, 128, 256, 512
		Maximum number of TFC	16, 32, 48, 64, 96, 128, 256, 512, 1024
		Maximum number of TF	32, 64, 128, 256, 512, 1024
		Support for turbo decoding	Yes/No
	Transport channel parameters in uplink	Maximum sum of number of bits of all transport blocks being transmitted at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all convolutionally coded transport blocks being transmitted at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all turbo coded transport blocks being transmitted at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum number of simultaneous transport channels	2, 4, 8, 16, 32
		Maximum number of simultaneous CCTrCH of DCH type (TDD only)	1, 2, 3, 4, 5, 6, 7, 8
		Maximum total number of transport blocks transmitted within TTIs that start at the same time	2, 4, 8, 16, 32, 48, 64, 96, 128, 256, 512
		Maximum number of TFC	4, 8, 16, 32, 48, 64, 96, 128, 256, 512, 1024
		Maximum number of TF	32, 64, 128, 256, 512, 1024
		Support for turbo encoding	Yes/No
	FDD Physical channel parameters in downlink	Maximum number of DPCH/PDSCH codes to be simultaneously received	1, 2, 3, 4, 5, 6, 7, 8
		Maximum number of physical channel bits received in any 10 ms interval (DPCH, PDSCH, S-CCPCH)	600, 1200, 2400, 3600, 4800, 7200, 9600, 14400, 19200, 28800, 38400, 48000, 57600, 67200, 76800
		Support for SF 512	Yes/No
		Support of PDSCH	Yes/No

		UE radio access capability parameter	Value range	
		Support of HS-PDSCH	Yes/No	
		Simultaneous reception of SCCPCH and DPCH	Yes/No	
		Simultaneous reception of SCCPCH, DPCH and PDSCH	Yes/No	
		Maximum number of simultaneous S-CCPCH radio links	1 NOTE: Only the value 1 is part of this release of the specification	
		Support of dedicated pilots for channel estimation	Yes	
	FDD Physical channel parameters in uplink	Maximum number of DPDCH bits transmitted per 10 ms	600, 1200, 2400, 4800, 9600, 19200, 28800, 38400, 48000, 57600	
		Support of PCPCH	Yes/No	
	TDD 3.84 Mcps physical channel parameters in downlink	Maximum number of timeslots per frame	1..14	
		Maximum number of physical channels per frame	1, 2, 3..224	
		Minimum SF	16, 1	
		Support of PDSCH	Yes/No	
		Support of HS-PDSCH	Yes/No	
		Maximum number of physical channels per timeslot	1..16	
	TDD 3.84 Mcps physical channel parameters in uplink	Maximum Number of timeslots per frame	1..14	
		Maximum number of physical channels per timeslot	1, 2	
		Minimum SF	16, 8, 4, 2, 1	
		Support of PUSCH	Yes/No	
	TDD 1.28 Mcps physical channel parameters in downlink	Maximum number of timeslots per subframe	1..6	
		Maximum number of physical channels per subframe	1, 2, 3, ..., 96	
		Minimum SF	16, 1	
		Support of PDSCH	Yes/No	
		Support of HS-PDSCH	Yes/No	
		Maximum number of physical channels per timeslot	1..16	
	TDD 1.28 Mcps physical channel parameters in uplink	Support 8PSK	Yes/No	
		Maximum number of timeslots per subframe	1..6	
		Maximum number of physical channels per timeslot	1, 2	
		Minimum SF	16, 8, 4, 2, 1	
		Support of 8PSK	Yes/No	
		Support of PUSCH	Yes/No	
RF parameters	FDD RF parameters	UE power class	3, 4 NOTE: Only power classes 3 and 4 are part of this release of the specification	
		Tx/Rx frequency separation	190 MHz 174.8 MHz to 205.2 MHz 134.8 MHz to 245.2 MHz	
RF parameters	TDD 3.84 Mcps RF parameters	UE power class	2, 3 NOTE: Only power classes 2 and 3 are part of this release of the specification	
		Radio frequency bands	a), b), c), a+b), a+c), b+c), a+b+c)	
	TDD 1.28 Mcps RF parameters	UE power class	2, 3	
		Radio frequency bands	a), b), c), a+b), a+c), b+c), a+b+c)	
Multi-mode related parameters		Support of UTRA FDD	Yes/No	
		Support of UTRA TDD 3.84 Mcps	Yes/No	
		Support of UTRA TDD 1.28 Mcps	Yes/No	

	UE radio access capability parameter	Value range
Multi-RAT related parameters	Support of GSM	Yes/No (per GSM frequency band)
	Support of multi-carrier	Yes/No
Security parameters	Support of ciphering algorithm UEA0	Yes
	Support of ciphering algorithm UEA1	Yes
	Support of integrity protection algorithm UIA1	Yes
UE positioning related parameters	Standalone location method(s) supported	Yes/No
	Network assisted GPS support	Network based / UE based / Both/ None
	GPS reference time capable	Yes/No
	Support for IPDL	Yes/No
	Support for OTDOA UE based method	Yes/No
	Support for Rx-Tx time difference type 2 measurement	Yes/No
	Support for UE Positioning measurement validity in CELL_PCH and URA_PCH RRC states	Yes/No
Measurement related capabilities	Need for downlink compressed mode	Yes/No (per frequency band, UTRA mode and RAT)
	Need for uplink compressed mode	Yes/No (per frequency band, UTRA mode and RAT)
General capabilities	Access Stratum release indicator	R99, REL-4, REL-5
DL capabilities with simultaneous HS-DSCH	DL capability with simultaneous HS-DSCH configuration	32 kbps, 64 kbps, 128 kbps, 384 kbps

Table 5.1a: FDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes received	Minimum inter-TTI interval	Maximum number of bits of an HS-DSCH transport block received within an HS-DSCH TTI	Total number of soft channel bits
Category 1	5	3	7300	19200
Category 2	5	3	7300	28800
Category 3	5	2	7300	28800
Category 4	5	2	7300	38400
Category 5	5	1	7300	57600
Category 6	5	1	7300	67200
Category 7	10	1	14600	115200
Category 8	10	1	14600	134400
Category 9	15	1	20432	172800
Category 10	15	1	28776	172800
Category 11	5	2	3650	14400
Category 12	5	1	3650	28800

UEs of Categories 11 and 12 support QPSK only.

Table 5.1b: RLC and MAC-hs parameters for FDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size
Category 1	6	50
Category 2	6	50
Category 3	6	50
Category 4	6	50
Category 5	6	[50]
Category 6	6	[50]
Category 7	8	[100]
Category 8	8	[100]
Category 9	8	[150]
Category 10	8	[150]

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size
Categorie 11	[6]	[50]
Categorie 12	[6]	[50]

Table 5.1c: 1.28 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes per timeslot	Maximum number of HS-DSCH timeslots per TTI	Maximum number of HS-DSCH transport channel bits that can be received within an HS-DSCH TTI	Total number of soft channel bits	Support of SF=1 for HS-PDSCH
Category 1	12	5	7016	28160	Yes
Category 2	12	5	7016	56320	Yes
Category 3	12	5	7016	84480	Yes
Category 4	16	5	7016	28160	Yes
Category 5	16	5	7016	56320	Yes
Category 6	16	5	7016	84480	Yes
Category 7	12	5	10204	40912	Yes
Category 8	12	5	10204	81824	Yes
Category 9	12	5	10204	122736	Yes
Category 10	16	5	10204	40912	Yes
Category 11	16	5	10204	81824	Yes
Category 12	16	5	10204	122736	Yes
Category 13	16	5	14056	56320	Yes
Category 14	16	5	14056	112640	Yes
Category 15	16	5	14056	168960	Yes

Table 5.1d: RLC and MAC-hs parameters for 1.28 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size
Category 1	6	[50]
Category 2	6	[50]
Category 3	6	[50]
Category 4	6	[50]
Category 5	6	[50]
Category 6	6	[50]
Category 7	6	[50]
Category 8	6	[50]
Category 9	6	[50]
Category 10	6	[50]
Category 11	6	[50]
Category 12	6	[50]
Category 13	6	[100]
Category 14	6	[100]
Category 15	6	[100]

Table 5.1e: 3.84 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes per timeslot	Maximum number of HS-DSCH timeslots per TTI	Maximum number of HS-DSCH transport channel bits that can be received within an HS-DSCH TTI	Total number of soft channel bits	Support of SF=1 for HS-PDSCH
Category 1	16	2	12000	70656	Yes
Category 2	16	12	12000	70656	Yes
Category 3	16	4	24000	141312	Yes

HS-DSCH category	Maximum number of HS-DSCH codes per timeslot	Maximum number of HS-DSCH timeslots per TTI	Maximum number of HS-DSCH transport channel bits that can be received within an HS-DSCH TTI	Total number of soft channel bits	Support of SF=1 for HS-PDSCH
Category 4	16	12	24000	141312	Yes
Category 5	16	6	36000	211968	Yes
Category 6	16	12	36000	211968	Yes
Category 7	16	12	53000	282624	Yes
Category 8	16	12	73000	353280	Yes
Category 9	16	12	102000	423936	Yes

Table 5.1f: RLC and MAC-hs parameters for 3.84 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size
Category 1	6	[50]
Category 2	6	[50]
Category 3	6	[100]
Category 4	6	[100]
Category 5	6	[150]
Category 6	6	[150]
Category 7	6	[200]
Category 8	8	[250]
Category 9	8	[350]

CHANGE REQUEST

25.306 CR 057 # rev - # Current version: 5.2.0

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the # symbols.

Proposed change affects: UICC apps # ME Radio Access Network Core Network

Title:	# Dedicated pilot bits for HS-DSCH	
Source:	# Ericsson	
Work item code:	# TEI-5	Date: # 14/11/2002
Category:	# F <i>Use one of the following categories:</i> F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) <i>Detailed explanations of the above categories can be found in 3GPP TR 21.900.</i>	Release: # Rel-5 <i>Use one of the following releases:</i> 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)

Reason for change:	# In LS R2-022528(R1-02-1192) from RAN1 to RAN2 it was indicated that RAN1 have agreed that the support of dedicated pilots for HS-PDSCH and HS-SCCH shall be optional for the UE in Rel-5. Therefor a new capability is included in Rel-5 to indicate if the UE supports dedicated pilots for HSDPA.
---------------------------	--

Summary of change:	# The capability "Support of dedicated pilots for channel estimation of HS-DSCH" is added in 4.5.3. This is then also reflected in table 5.1 and table 5.2.2.1.
---------------------------	--

Consequences if not approved:	# It is not possible for a UE to indicate support or non-support of dedicated pilots for channel estimation of HS-PDSCH and HS-SCCH.
--------------------------------------	--

Clauses affected:	# 4.5.3, 5.1, 5.2.2									
Other specs affected:	<table border="1" style="display: inline-table; vertical-align: middle;"> <tr> <td>Y</td> <td>N</td> </tr> <tr> <td>X</td> <td></td> </tr> <tr> <td></td> <td>X</td> </tr> <tr> <td></td> <td>X</td> </tr> </table> Other core specifications Test specifications O&M Specifications	Y	N	X			X		X	# 25.331 v5.2.0. CR 1794.
Y	N									
X										
	X									
	X									
Other comments:	#									

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at <http://www.3gpp.org/specs/CR.htm>. Below is a brief summary:

- 1) Fill out the above form. The symbols above marked # contain pop-up help information about the field that they are closest to.

- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under <ftp://ftp.3gpp.org/specs/> For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

4.5.3 FDD Physical channel parameters in downlink

Maximum number of DPCH/PDSCH codes to be simultaneously received

Defines the number of codes the UE is capable of receiving in parallel. For DPCH in soft/softer handover, each DPCH is only calculated once in this capability. The capability does not include codes used for S-CCPCH.

Maximum number of physical channel bits received in any 10 ms interval (DPCH, PDSCH, S-CCPCH)

Defines the number of physical channel bits the UE is capable of receiving. For DPCH in soft/softer handover, each DPCH is only calculated once in this capability.

The number of DPCH channel bits indicates the capability of the UE when operating in non-compressed mode.

The parameter also indicates the capability of the UE to support compressed mode by spreading factor reduction as follows. The UE shall:

- for parameter values up to and including 9600 bits:
 - support compressed mode by spreading factor reduction when operating at any value up to the reported capability.
- for parameter values greater than 9600 bits:
 - support compressed mode by spreading factor reduction when operating at any value up to the greater of:
 - half the reported capability; or
 - 9600bits.

NOTE: Compressed mode by spreading factor reduction is not applicable when operating at spreading factor 4.

Support for SF 512

Defines whether the UE supports spreading factor 512 in downlink or not.

Support of PDSCH

Defines whether the UE supports PDSCH or not.

Support of HS-PDSCH

Defines whether the UE supports HS-PDSCH or not.

Simultaneous reception of SCCPCH and DPCH

Defines whether the UE supports simultaneous reception of SCCPCH and DPCH or not.

NOTE: Simultaneous reception of SCCPCH and DPCH, i.e. simultaneous reception of FACH and DCH is required for e.g. DRAC procedure

Simultaneous reception of SCCPCH, DPCH and PDSCH

Defines whether the UE supports simultaneous reception of SCCPCH, DPCH and PDSCH or not. The PDSCH part of this capability is only relevant if the UE supports PDSCH, as covered by the capability "Support of PDSCH".

NOTE: Simultaneous reception of SCCPCH, DPCH and PDSCH, i.e. simultaneous reception of FACH, DCH and DSCH is required for e.g. simultaneous use of DSCH and the DRAC procedure.

Maximum number of simultaneous S-CCPCH radio links

Defines the maximum number of radio links on which the UE is capable of receiving S-CCPCH simultaneously.

Support of dedicated pilots for channel estimation

Defines whether the UE supports dedicated pilots for channel estimation or not.

Support of dedicated pilots for channel estimation of HS-DSCH

Defines whether the UE supports dedicated pilots for channel estimation of HS-PDSCH and HS-SCCH or not.

Maximum number of HS-DSCH codes received

Defines the maximum number of HS-DSCH codes the UE is capable of receiving.

Total number of soft channel bits in HS-DSCH

Defines the maximum number of soft channel bits over all HARQ processes.

Minimum inter-TTI interval in HS-DSCH

Defines the distance from the beginning of a TTI to the beginning of the next TTI that can be assigned to the UE.

Possible UE radio access capability parameter settings

5.1 Value ranges

Table 5.1: UE radio access capability parameter value ranges

		UE radio access capability parameter	Value range
PDCP parameters		Support for RFC 2507	Yes/No
		Support for RFC 3095	Yes/No
		Support for RFC 3095 context relocation	Yes/No
		Support for loss-less SRNS relocation	Yes/No
		Maximum header compression context space	512, 1024, 2048, 4096, 8192 bytes
RLC and MAC-hs parameters		Total RLC AM and MAC-hs buffer size	2, 10, 50, 100, 150, 500, 1000 kBytes
		Maximum number of AM entities	3, 4, 5, 6, 8, 16, 30
PHY parameters	Transport channel parameters in downlink	Maximum sum of number of bits of all transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all convolutionally coded transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum sum of number of bits of all turbo coded transport blocks being received at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840
		Maximum number of simultaneous transport channels	4, 8, 16, 32
		Maximum number of simultaneous CCTrCH	1, 2, 3, 4, 5, 6, 7, 8
		Maximum total number of transport blocks received within TTIs that end within the same 10 ms interval	4, 8, 16, 32, 48, 64, 96, 128, 256, 512
		Maximum number of TFC	16, 32, 48, 64, 96, 128, 256, 512, 1024
		Maximum number of TF	32, 64, 128, 256, 512, 1024
		Support for turbo decoding	Yes/No

		UE radio access capability parameter	Value range
Transport channel parameters in uplink	Maximum sum of number of bits of all transport blocks being transmitted at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840	
	Maximum sum of number of bits of all convolutionally coded transport blocks being transmitted at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840	
	Maximum sum of number of bits of all turbo coded transport blocks being transmitted at an arbitrary time instant	640, 1280, 2560, 3840, 5120, 6400, 7680, 8960, 10240, 20480, 40960, 81920, 163840	
	Maximum number of simultaneous transport channels	2, 4, 8, 16, 32	
	Maximum number of simultaneous CCTrCH of DCH type (TDD only)	1, 2, 3, 4, 5, 6, 7, 8	
	Maximum total number of transport blocks transmitted within TTIs that start at the same time	2, 4, 8, 16, 32, 48, 64, 96, 128, 256, 512	
	Maximum number of TFC	4, 8, 16, 32, 48, 64, 96, 128, 256, 512, 1024	
	Maximum number of TF	32, 64, 128, 256, 512, 1024	
FDD Physical channel parameters in downlink	Support for turbo encoding	Yes/No	
	Maximum number of DPCH/PDSCH codes to be simultaneously received	1, 2, 3, 4, 5, 6, 7, 8	
	Maximum number of physical channel bits received in any 10 ms interval (DPCH, PDSCH, S-CCPCH)	600, 1200, 2400, 3600, 4800, 7200, 9600, 14400, 19200, 28800, 38400, 48000, 57600, 67200, 76800	
	Support for SF 512	Yes/No	
	Support of PDSCH	Yes/No	
	Support of HS-PDSCH	Yes/No	
	Simultaneous reception of SCCPCH and DPCH	Yes/No	
	Simultaneous reception of SCCPCH, DPCH and PDSCH	Yes/No	
	Maximum number of simultaneous S-CCPCH radio links	1 NOTE: Only the value 1 is part of this release of the specification	
	Support of dedicated pilots for channel estimation	Yes	
FDD Physical channel parameters in uplink	Support of dedicated pilots for channel estimation of HS-DSCH	Yes/No	
	Maximum number of DPDCH bits transmitted per 10 ms	600, 1200, 2400, 4800, 9600, 19200, 28800, 38400, 48000, 57600	
TDD 3.84 Mcps physical channel parameters in downlink	Support of PCPCH	Yes/No	
	Maximum number of timeslots per frame	1..14	
	Maximum number of physical channels per frame	1, 2, 3..224	
	Minimum SF	16, 1	
	Support of PDSCH	Yes/No	
	Support of HS-PDSCH	Yes/No	
TDD 3.84 Mcps physical channel parameters in uplink	Maximum number of physical channels per timeslot	1..16	
	Maximum Number of timeslots per frame	1..14	
	Maximum number of physical channels per timeslot	1, 2	
	Minimum SF	16, 8, 4, 2, 1	
TDD 1.28 Mcps physical channel parameters in downlink	Support of PUSCH	Yes/No	
	Maximum number of timeslots per subframe	1..6	
	Maximum number of physical channels per subframe	1, 2, 3, ..., 96	
	Minimum SF	16, 1	

		UE radio access capability parameter	Value range
RF parameters	TDD 1.28 Mcps physical channel parameters in uplink	Support of PDSCH	Yes/No
		Support of HS-PDSCH	Yes/No
		Maximum number of physical channels per timeslot	1..16
		Support 8PSK	Yes/No
		Maximum number of timeslots per subframe	1..6
	FDD RF parameters	Maximum number of physical channels per timeslot	1, 2
		Minimum SF	16, 8, 4, 2, 1
		Support of 8PSK	Yes/No
		Support of PUSCH	Yes/No
		UE power class	3, 4 NOTE: Only power classes 3 and 4 are part of this release of the specification
RF parameters	TDD 3.84 Mcps RF parameters	Tx/Rx frequency separation	190 MHz 174.8 MHz to 205.2 MHz 134.8 MHz to 245.2 MHz
		UE power class	2, 3 NOTE: Only power classes 2 and 3 are part of this release of the specification
		Radio frequency bands	a), b), c), a+b), a+c), b+c), a+b+c)
	TDD 1.28 Mcps RF parameters	UE power class	2, 3
Multi-mode related parameters		Radio frequency bands	a), b), c), a+b), a+c), b+c), a+b+c)
Multi-RAT related parameters		Support of UTRA FDD	Yes/No
		Support of UTRA TDD 3.84 Mcps	Yes/No
		Support of UTRA TDD 1.28 Mcps	Yes/No
Security parameters		Support of GSM	Yes/No (per GSM frequency band)
		Support of multi-carrier	Yes/No
UE positioning related parameters		Support of ciphering algorithm UEA0	Yes
		Support of ciphering algorithm UEA1	Yes
		Support of integrity protection algorithm UIA1	Yes
Measurement related capabilities		Standalone location method(s) supported	Yes/No
		Network assisted GPS support	Network based / UE based / Both/ None
		GPS reference time capable	Yes/No
		Support for IPDL	Yes/No
		Support for OTDOA UE based method	Yes/No
		Support for Rx-Tx time difference type 2 measurement	Yes/No
		Support for UE Positioning measurement validity in CELL_PCH and URA_PCH RRC states	Yes/No
General capabilities		Access Stratum release indicator	R99, REL-4
DL capabilities with simultaneous HS-DSCH		DL capability with simultaneous HS-DSCH configuration	32 kbps, 64 kbps, 128 kbps, 384 kbps

Table 5.1a: FDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes received	Minimum inter-TTI interval	Maximum number of bits of an HS-DSCH transport block received within an HS-DSCH TTI	Total number of soft channel bits
Category 1	5	3	7300	19200
Category 2	5	3	7300	28800
Category 3	5	2	7300	28800
Category 4	5	2	7300	38400
Category 5	5	1	7300	57600
Category 6	5	1	7300	67200
Category 7	10	1	14600	115200
Category 8	10	1	14600	134400
Category 9	15	1	20432	172800
Category 10	15	1	28776	172800
Categorie 11	5	2	3650	14400
Categorie 12	5	1	3650	28800

UEs of Categories 11 and 12 support QPSK only.

Table 5.1b: RLC and MAC-hs parameters for FDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size
Category 1	6	50
Category 2	6	50
Category 3	6	50
Category 4	6	50
Category 5	6	[50]
Category 6	6	[50]
Category 7	8	[100]
Category 8	8	[100]
Category 9	8	[150]
Category 10	8	[150]
Categorie 11	[6]	[50]
Categorie 12	[6]	[50]

Table 5.1c: 1.28 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes per timeslot	Maximum number of HS-DSCH timeslots per TTI	Maximum number of HS-DSCH transport channel bits that can be received within an HS-DSCH TTI	Total number of soft channel bits	Support of SF=1 for HS-PDSCH
Category 1	12	5	7016	28160	Yes
Category 2	12	5	7016	56320	Yes
Category 3	12	5	7016	84480	Yes
Category 4	16	5	7016	28160	Yes
Category 5	16	5	7016	56320	Yes
Category 6	16	5	7016	84480	Yes
Category 7	12	5	10204	40912	Yes
Category 8	12	5	10204	81824	Yes
Category 9	12	5	10204	122736	Yes
Category 10	16	5	10204	40912	Yes
Category 11	16	5	10204	81824	Yes
Category 12	16	5	10204	122736	Yes
Category 13	16	5	14056	56320	Yes
Category 14	16	5	14056	112640	Yes
Category 15	16	5	14056	168960	Yes

Table 5.1d: RLC and MAC-hs parameters for 1.28 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size
Category 1	6	[50]
Category 2	6	[50]
Category 3	6	[50]
Category 4	6	[50]
Category 5	6	[50]
Category 6	6	[50]
Category 7	6	[50]
Category 8	6	[50]
Category 9	6	[50]
Category 10	6	[50]
Category 11	6	[50]
Category 12	6	[50]
Category 13	6	[100]
Category 14	6	[100]
Category 15	6	[100]

Table 5.1e: 3.84 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of HS-DSCH codes per timeslot	Maximum number of HS-DSCH timeslots per TTI	Maximum number of HS-DSCH transport channel bits that can be received within an HS-DSCH TTI	Total number of soft channel bits	Support of SF=1 for HS-PDSCH
Category 1	16	2	12000	70656	Yes
Category 2	16	12	12000	70656	Yes
Category 3	16	4	24000	141312	Yes
Category 4	16	12	24000	141312	Yes
Category 5	16	6	36000	211968	Yes
Category 6	16	12	36000	211968	Yes
Category 7	16	12	53000	282624	Yes
Category 8	16	12	73000	353280	Yes
Category 9	16	12	102000	423936	Yes

Table 5.1f: RLC and MAC-hs parameters for 3.84 Mcps TDD HS-DSCH physical layer categories

HS-DSCH category	Maximum number of AM RLC entities	Minimum total RLC AM and MAC-hs buffer size
Category 1	6	[50]
Category 2	6	[50]
Category 3	6	[100]
Category 4	6	[100]
Category 5	6	[150]
Category 6	6	[150]
Category 7	6	[200]
Category 8	8	[250]
Category 9	8	[350]

5.2.2 Combinations of UE Radio Access Parameters for DL

Table 5.2.2.1: UE radio access capability parameter combinations, DL parameters

Reference combination of UE Radio Access capability parameters in DL	32 kbps class	64 kbps class	128 kbps class	384 kbps class	768 kbps class	2048 kbps class
Transport channel parameters						
Maximum sum of number of bits of all transport blocks being received at an	640	3840	3840	6400	10240	20480

Reference combination of UE Radio Access capability parameters in DL	32 kbps class	64 kbps class	128 kbps class	384 kbps class	768 kbps class	2048 kbps class
arbitrary time instant						
Maximum sum of number of bits of all convolutionally coded transport blocks being received at an arbitrary time instant	640	640	640	640	640	640
Maximum sum of number of bits of all turbo coded transport blocks being received at an arbitrary time instant	NA	3840	3840	6400	10240	20480(1) 10240(2) NOTE 5
Maximum number of simultaneous transport channels	8 NOTE 4	16 NOTE 4				
Maximum number of simultaneous CCTrCH (FDD)	1 NOTE 3	2/1 NOTE 2 NOTE 3	2/1 NOTE 2 NOTE 3	2	2	2
Maximum number of simultaneous CCTrCH (TDD)	2 NOTE 3	3 NOTE 3	3 NOTE 3	3 NOTE 3	4 NOTE 3	4 NOTE 3
Maximum total number of transport blocks received within TTIs that end at the same time	8	8	16	32	64	96
Maximum number of TFC	32	48	96	128	256	1024
Maximum number of TF	32	64	64	64	128	256
Support for turbo decoding	No	Yes	Yes	Yes	Yes	Yes
Physical channel parameters (FDD)						
Maximum number of DPCH/PDSCH codes to be simultaneously received	1	2/1 NOTE 2	2/1 NOTE 2	3	3	3
Maximum number of physical channel bits received in any 10 ms interval (DPCH, PDSCH, S-CCPCH).	1200	3600/2400 NOTE2	7200/4800 NOTE2	19200	28800	57600
Support for SF 512 for DPCH NOTE 6	No	No	No	No	No	No
Support of PDSCH	No	Yes/No NOTE 1	Yes/No NOTE 1	Yes	Yes	Yes
Support of HS-PDSCH	No	Yes/No NOTE 1				
Maximum number of simultaneous S-CCPCH radio links	1	1	1	1	1	1
Support of dedicated pilots for channel estimation	Yes NOTE 1 NOTE 7					
Support of dedicated pilots for channel estimation of HS-DSCH	Yes/No NOTE 1					
Physical channel parameters (TDD 3.84 Mcps)						
Maximum number of timeslots per frame	1	2	4	5	10	12
Maximum number of physical channels per frame	8	9	14	28	64	136
Minimum SF	16	16	16	1/16 NOTE 1	1/16 NOTE 1	1/16 NOTE 1
Support of PDSCH	Yes/No NOTE 1	Yes	Yes	Yes	Yes	Yes
Support of HS-PDSCH	No	Yes/No NOTE 1				
Maximum number of physical channels per timeslot	8	9	9	9	9	13
Physical channel parameters (TDD 1.28 Mcps)						
Maximum number of timeslots per subframe	1	2	3	4	6	6
Maximum number of physical channels per subframe	8	12	18	43	77	77
Minimum SF	16	16	16	1/16 NOTE 1	1/16 NOTE 1	1

Reference combination of UE Radio Access capability parameters in DL	32 kbps class	64 kbps class	128 kbps class	384 kbps class	768 kbps class	2048 kbps class
Support of PDSCH	Yes/No NOTE 1	Yes	Yes	Yes	Yes	Yes
Support of HS-PDSCH	No	Yes/No NOTE 1				
Maximum number of physical channels per timeslot	8	11	14	14	14	14
Support of 8PSK	No	No	No	No	No	Yes

NOTE 1: Options represent different combinations that should be supported with conformance tests.

NOTE 2: Options depend on the support of PDSCH. The highest value is required if PDSCH is supported.

NOTE 3: The given number does not contain the BCH CCTrCH of the current cell nor of the neighbour cells.

NOTE 4: The given number does not contain the BCH of the neighbour cell.

NOTE 5: (1) For FDD and 3.84 Mcps TDD (2) For 1.28 Mcps TDD.

NOTE 6: This UE capability does not relate to the support of CPCH in the uplink for which SF 512 is needed

NOTE 7: A UE conforming to this release of the specification shall set the support of channel estimation based on dedicated pilot bits to TRUE.

The reference combinations for HS-DSCH capabilities are shown in tables 5.2.2.2, 5.2.2.3 and 5.2.2.4. These tables are subject to further discussions in TSG-RAN WG1 and TSG-RAN WG2.

Table 5.2.2.2: FDD UE radio access capability parameter combinations, DL HS-DSCH parameters

Reference combination	1.2 Mbps class	3.6 Mbps class	7 Mbps class	10 Mbps class
RLC and MAC-hs parameters				
Total RLC AM and MAC-hs buffer size (kbytes)	50	[50]	[100]	[150]
Maximum number of AM RLC entities	6	6	8	8
PHY parameters				
FDD HS-DSCH category	Category 1	Category 5	Category 7	Category 9

Table 5.2.2.3: 1.28 Mcps TDD UE radio access capability parameter combinations, DL HS-DSCH parameters

Reference combination	1.4 Mbps class	2.0 Mbps class	2.8 Mbps class
RLC and MAC-HS parameters			
Total RLC AM and MAC-hs buffer size (kbytes)	[50]	[50]	[100]
Maximum number of AM RLC entities	6	6	6
PHY parameters			
1.28 Mcps TDD HS-DSCH Category	Category 1	Category 7	Category 13

Table 5.2.2.4: 3.84 Mcps TDD UE radio access capability parameter combinations, DL HS-DSCH parameters

Reference combination	1.2 Mbps class	2.4 Mbps class	3.6 Mbps class	7.3 Mbps class	10.2 Mbps class
RLC and MAC-hs parameters					
Total RLC AM and MAC-hs buffer size (kbytes)	[50]	[100]	[150]	[250]	[350]
Maximum number of AM RLC entities	6	6	6	8	8
PHY parameters					
3.84Mcps TDD HS-DSCH category	Category 1	Category 3	Category 5	Category 8	Category 9

