

Tokyo, Japan, 9 - 11 March 2005

## Release 6 Submission form

<b>Feature / Item:</b>		<b>Improved minimum performance requirements for HSDPA UE categories 7 &amp; 8</b>				
<b>Affects:</b>	<b>UE/MS:</b> x	<b>CN:</b>	<b>UTRAN:</b> x	<b>GERAN:</b>	<b>Compatibility Issues:</b> Yes: No:x	
<b>Expected Completion Date:</b>		RAN#28				
<b>Services impacted:</b>		no				
<b>Specifications affected:</b>		TS 25.101				
<b>Tasks within work which are not complete:</b>			<p><b>-Further evaluation of need for enhanced performance requirements with single transmit antenna in Pedestrian A 3km/h and Vehicular A 120km/h</b></p> <p><b>Conditions for performance assessment for Closed loop transmit diversity</b></p> <p><b>Performance requirements</b></p>			
<b>Consequences if not included in Release 6:</b>			<b>Performance improvements and therefore potential capacity increase in the system delayed.</b>			
<b>Accepted by</b> TSG# 27		<b>for late inclusion in Release 6:</b>				

**Abstract of document:**

[Improving receiver performance for HSDPA reception in terminal](#)

**Contentious Issues:**

[None](#)