

3GPP TSG RAN Meeting #75
Dubrovnik, Croatia, March 6 - 9, 2017

Document for: Discussion
Agenda Item: 10.1.4

RP-170354



Motivation for new work item on LTE DL 8Rx antenna ports

Huawei, HiSilicon

Motivation

- Recently clear market needs are observed
 - Boost downlink peak data rate to 1.2Gbps and 1.6Gbps by using 8-layer transmission.
 - New UE DL category 18 and 19 were introduced correspondingly.
 - RAN4 should specify new RF, RRM and demodulation performance requirements.
- Benefits:
 - Higher peak data rate and higher spectrum efficiency are available.
 - Improve the downlink throughput.
 - Improve the coverage.
 - Make high order modulation like 256QAM and 1024QAM usable in more practical operating SINR range.
 - Be capable of canceling more inter-cell interferences.

Objectives

- Core requirements
 - Specify RF core requirement such as REFSENS.
 - Specify RRM core requirement such as RLM.
- Performance requirements
 - Specify the channel model including correlation matrices for 8Rx antennas
 - Specify corresponding RRM tests such as RLM and application rules
 - Specify demodulation performance, CSI reporting requirements, and application rules
 - Identify a minimum set of necessary requirements for PDSCH, PDCCH/PCFICH, PHICH, PBCH, EPDCCH to achieve a good trade-off between test coverage and test case number.
 - Assume MMSE and MMSE-IRC as baseline receivers
 - Specify methodology including antenna connection to reuse the existing demodulation performance requirements, which are not covered by the minimum set of requirements.
 - Use the methodology to specify 4Rx requirements as starting point.
- Both core and performance requirements will cover the single carrier and CA scenarios