Technical Specification Group Services and System Aspects Meeting #4, Miami, USA, 21-23 June 1999

ETSI SMG2#31 Tucson-AZ, USA May 31-June 4, 1999 Tdoc SMG2 765/99 Agenda Item: 7.2.7

Source: SMG2

Liaison To: TSG SA, TSG-CN/SMG3

cc: TSG-S1, S2, S3, N2, R2, T3, SMG9, SMG10

Title: Response to the TSG-SA LS on the usage of GSM-only SIM Cards

for 3G access

SMG2 has reviewed the Liaison received from TSG-SA on the usage of GSM-only SIM cards for 3G access.

SMG2 believes that in order to implement the proposed compromise, the Core Network must be able to selectively accept or reject to register a Terminal equipped with a GSM-only SIM Card in some part of the network (3G or GSM).

As a result, a dual mode Terminal equipped with a GSM-only SIM Card trying to register on a dual mode 3G/GSM network could either be accepted for both operating modes (3G and/or GSM) or only on the GSM part of the network. In the later case, SMG2 believes that the easiest way to handle this situation is for the Terminal to revert to a single operating mode (equivalent to a GSM only Terminal). Similarly, the network should then consider this Terminal as a single mode GSM Terminal. The Terminal should stay in this pseudo-single operating mode while registered on the GSM part of the network, until a new PLMN selection is required.