3GPP TSG-T WG1 meeting #9TSG T1#9(00)0265Redondo Beach, USA, 16 <sup>th</sup> -17 <sup>th</sup> November 2000		
Title:	LS on TR 21.905: Vocabulary for 3GPP Specifications	
Source:	TSG T1	
То:	TSG-SA	
Cc:	TSG-RAN, TSG-T	
Document for:	Approval	

## Introduction

TSG-T1 has gone through the definitions of vocabulary, which are used in T1 test specifications, and checked them with 3G Vocabulary document <sup>[1]</sup> TR 21.905. This document proposes modifications of 3G Vocabulary document <sup>[1]</sup> TR 21.905 according to the terms used in <sup>[5]</sup> TS 34.121 those are regarded as 3GPP global ones.

T1 would ask TSG-SA to take an appropriate action for modification.

# Proposal

The following abbreviations should be added or modified.

AFC	Automatic Frequency Control
BER	Bit Error <u>Ratio</u> Rate
BLER	Block Error <u>Ratio</u> -Rate
<u>BTFD</u>	Blind Transport Format Detection
FDR	False transmit format Detection Ratio
IM	Intermodulation
MER	Message Error <u>Ratio</u> -Rate
<u>OCNS</u>	Orthogonal Channel Noise Simulator, a mechanism used to simulate the users or control signals on
	the other orthogonal channels of a downlink
PAR	Peak to Average Ratio
P_CCPCH	Primary Common Control Physical Channel
P-CPICH	Primary Common Pilot Channel
PCDE	Peak Code Domain Error
RBW	Resolution Bandwidth
S_CCPCH	Secondary Common Control Physical Channel
<u>S-CPICH</u>	Secondary Common Pilot Channel
SS	System Simulator

## **3GPP TSG-T WG1 meeting #9 Redondo Beach, USA, 16<sup>th</sup>-17<sup>th</sup> November 2000**

#### *TSG T1#9(00)0265*

The following equations should be added or modified.

$\frac{CPICH\_E_c}{I_{or}}$	The ratio of the received energy per PN chip of the CPICH to the total transmit power spectral density at the Node B (SS) antenna connector.
$\frac{DPCH\_E_c}{I_{or}}$	The ratio of the received energy per PN chip of the DPCH to the total transmit power spectral density at the <u>Node B-BS (SS)</u> antenna connector.
$\frac{\underline{DPCCH\_E_c}}{I_{or}}$	The ratio of the transmit energy per PN chip of the DPCCH to the total transmit power spectral density at the Node B antenna connector.
$\frac{DPDCH\_E_c}{I_{or}}$	The ratio of the transmit energy per PN chip of the DPDCH to the total transmit power spectral density at the Node B antenna connector.
	The power spectral density of the adjacent frequency channel as measured at the UE antenna connector.
I <sub>oc</sub>	The power spectral density of a band limited white noise source (simulating interference from other cells, which are not defined in a test procedure) as measured at the UE antenna connector.
I <sub>or</sub>	The total transmit power spectral density of the <u>down</u> -Forward link at the <u>Node B</u> base station antenna connector.
Î <sub>or</sub>	The received power spectral density of the <u>down</u> -Forward link as measured at the UE antenna connector.
Iouw	Unwanted signal power level.
$\underline{P - CCPCH \_ E_c}$	Average* energy per PN chip for P-CCPCH.
$\frac{P - CCPCH \frac{E_c}{I_o}}{\frac{PCCPCH \frac{E_c}{I_o}}{I_o}}$	The ratio of the received P_CCPCH energy per chip to the total received power spectral density at the UE antenna connector.
$ \frac{P - CCPCH \_ E_c}{I_{or}} $ $ \frac{PCCPCH \_ E_c}{I_{or}} $	The ratio of the average <sup>*</sup> transmit energy per PN chip for the P_CCPCH to the total transmit power spectral density.
$P-CPICH \_E_c$	Average* energy per PN chip for P-CPICH.
PICH_E <sub>c</sub>	Average* energy per PN chip for PICH.
$\frac{PICH\_E_c}{I_{or}}$	The ratio of the received energy per PN chip of the PICH to the total transmit power spectral density at the Node B (SS) antenna connector.
$\frac{S - CCPCH \_ E_c}{SCCPCH \_ E_c}$	Average energy per PN chip for S_CCPCH.

### 3GPP TSG-T WG1 meeting #9 Redondo Beach, USA, 16<sup>th</sup>-17<sup>th</sup> November 2000

#### TSG T1#9(00)0265

Redondo Deach, OSI, 10 -17 Rovember 2000		
$\underline{SCH \_ E_c}$	Average* energy per PN chip for SCH.	
SCCPCH	Secondary Common Control Physical Channel.	
$S - CPICH \_ E_c$	Average* energy per PN chip for S-CPICH.	

\*Note: Averaging period for energy/power of discontinuously transmitted channels should be defined.

# References

- [1] TR 21.905 V3.2.0 (2000-10): Vocabulary for 3GPP Specifications
- [2] TR 25.990 V3.0.0 (1999-10): Vocabulary
- [3] TS 25.101 V3.4.0 (2000-10): UE Radio Transmission and Reception (FDD)
- [4] TS 25.133 V3.3.0 (2000-09): Requirements for Support of Radio Resource Management (FDD)
- [5] TS 34.121 V3.2.0 (2000-09): Terminal Conformance Specification; Radio transmission and reception (FDD)