

---

**Source:** SA WG3

**Title:** 2 CRs to 33.107: Source of PDP context initiation (Rel-4, Rel-5)

**Document for:** Approval

**Agenda Item:** 7.3.3

| Spec   | CR  | Rev | Phase | Cat | Subject                          | Version-Current | Version-New | Doc-2nd-Level |
|--------|-----|-----|-------|-----|----------------------------------|-----------------|-------------|---------------|
| 33.107 | 015 |     | Rel-4 | F   | Source of PDP context initiation | 4.1.0           | 4.2.0       | S3-010517     |
| 33.107 | 016 |     | Rel-5 | A   | Source of PDP context initiation | 5.0.0           | 5.1.0       | S3-010518     |

**3GPP TSG SA WG3 Security — S3#20**  
**16 - 19 October, 2001, Sydney, Australia**

**S3-010517**

3GPP LI  
 Saarbruecken August 21-23

Tdoc S3LI01\_102

|   |
|---|
| CR-Form-v3  |
| <h2 style="margin: 0;">CHANGE REQUEST</h2> <p style="margin: 10px 0;">                 ⌘ <b>33.107 CR 015</b> ⌘ rev <b>-</b> ⌘ Current version: <b>4.1.0</b> ⌘             </p> |

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

**Proposed change affects:** ⌘ (U)SIM  ME/UE  Radio Access Network  Core Network

|                        |   |                 |  |
|------------------------|---|-----------------|--|
| <b>Title:</b>          | ⌘ Source of PDP context initiation  |                 |  |
| <b>Source:</b>         | ⌘ SA WG3  |                 |  |
| <b>Work item code:</b> | ⌘ SEC1-LI   | <b>Date:</b>    | ⌘ Aug 13, 2001   |
| <b>Category:</b>       | ⌘ <b>F</b>  | <b>Release:</b> | ⌘ REL-4  |
|                        | Use <u>one</u> of the following categories:<br><b>F</b> (essential correction)<br><b>A</b> (corresponds to a correction in an earlier release)<br><b>B</b> (Addition of feature),<br><b>C</b> (Functional modification of feature)<br><b>D</b> (Editorial modification) |                 | Use <u>one</u> of the following releases:<br>2 (GSM Phase 2)<br>R96 (Release 1996)<br>R97 (Release 1997)<br>R98 (Release 1998)<br>R99 (Release 1999)<br>REL-4 (Release 4)<br>REL-5 (Release 5) |
|                        | Detailed explanations of the above categories can be found in 3GPP TR 21.900.   |                 |  |

|                                      |   |
|--------------------------------------|---|
| <b>Reason for change:</b>            | ⌘ The "PDP context activation" reports, provide no indication regarding the source of the PDP context initiation, i.e. whether the MS has initiated the PDP session it or whether it was done by the network. |
| <b>Summary of change:</b>            | ⌘ An optional session initiator field is being added to this specification in the PDP context activation report.  |
| <b>Consequences if not approved:</b> | ⌘ Missing capability and compatibility with 3GPP TS 23.060.   |

|                              |   |  |
|------------------------------|---|--|
| <b>Clauses affected:</b>     | ⌘ 7.3.2, 7.4.3  |  |
| <b>Other specs Affected:</b> | ⌘ <input type="checkbox"/> Other core specifications ⌘<br><input type="checkbox"/> Test specifications<br><input type="checkbox"/> O&M Specifications |  |
| <b>Other comments:</b>       | ⌘   |  |

## 7.3.2 Structure of the events

There are seven different events in which the information is sent to the DF2 if this is required. Details are described in the following section. The events for interception are configurable (if they are sent to DF2) in the 3G GSN and can be suppressed in the DF2.

**The following events are applicable to 3G SGSN:**

- Mobile Station Attach;
- Mobile Station Detach;
- PDP context activation;
- Start of intercept with PDP context active;
- PDP context deactivation;
- RA update;
- SMS.

NOTE: 3G GGSN interception is a national option. Location information may not be available in this case.

The following events are applicable to the 3G GGSN:

- PDP context activation ;
- PDP context deactivation ;
- Start of interception with PDP context active.

A set of fields as shown below is used to generate the events. The events transmit the information from 3G GSN to DF2. This set of fields as shown below can be extended in the 3G GSN, if this is necessary as a national option. DF2 can extend this information if this is necessary as a national option e.g. a unique number for each surveillance warrant.

**Table 2: Information Events for Packet Data Event Records**

|   |
|---|
| Observed MSISDN<br>MSISDN of the target subscriber (monitored subscriber)   |
| Observed IMSI<br>IMSI of the target subscriber (monitored subscriber)   |
| Observed IMEI<br>IMEI of the target subscriber (monitored subscriber),it shall be checked for each activation over the radio interface.   |
| Event type<br>Description which type of event is delivered: MS attach, MS detach, PDP context activation, Start of intercept with PDP context active, PDP context deactivation, SMS, Cell and/or RA update, |
| Event date<br>Date of the event generation in the 3G GSN  |
| Event time<br>Time of the event generation in the 3G GSN  |
| PDP address<br>The PDP address of the target subscriber. Note that this address might be dynamic.   |
| Access Point Name<br>The APN of the access point. (Typically the GGSN of the other party)   |
| Location Information<br>Location Information is the service area identity, RAI and/or location area identity that is present at the GSN at the time of event record production.                             |
| PDP Type<br>The used PDP type.  |
| Correlation Number<br>The correlation number is used to correlate CC and IRI.   |
| SMS<br>The SMS content with header which is sent with the SMS-service. The header also includes the SMS-Centre address.   |
| Network Element Identifier<br>Unique identifier for the element reporting the ICE.  |
| Failed attach reason<br>Reason for failed attach of the target subscriber.  |
| Failed context activation reason<br>Reason for failed context activation of the target subscriber.  |
| IAs<br>The observed Interception Areas  |
| Session Initiator<br>The initiator of the PDP context either the network or the 3G MS   |

### 7.4.3 Packet Data PDP context activation

For PDP context activation a PDP context activation-event is generated. When a PDP context activation is generated from the mobile to 3G GSN this event is generated. These fields will be delivered to the DF2 if available:

|                                  |
|----------------------------------|
| Observed MSISDN                  |
| Observed IMSI                    |
| Observed IMEI                    |
| PDP address of observed party    |
| Event Type                       |
| Event Time                       |
| Event Date                       |
| Correlation number               |
| Access Point Name                |
| PDP Type                         |
| Network Element Identifier       |
| Location Information             |
| Failed context activation reason |
| IAs (if applicable)              |
| Session Initiator (optional)     |

**3GPP TSG SA WG3 Security — S3#20**  
**16 - 19 October, 2001, Sydney, Australia**

**S3-010518**

3GPP LI  
 Saarbruecken August 21-23

Tdoc S3LI01\_103r2

|   |
|---|
| CR-Form-v3  |
| <h2 style="margin: 0;">CHANGE REQUEST</h2> <p style="margin: 10px 0;">⌘ <b>33.107 CR 016</b> ⌘ rev <b>-</b> ⌘ Current version: <b>5.0.0</b> ⌘</p> |

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

**Proposed change affects:** ⌘ (U)SIM  ME/UE  Radio Access Network  Core Network

|                        |  |                 |  |
|------------------------|--|-----------------|--|
| <b>Title:</b>          | ⌘ Source of PDP context initiation   |                 |  |
| <b>Source:</b>         | ⌘ SA WG3   |                 |  |
| <b>Work item code:</b> | ⌘ SEC1-LI  | <b>Date:</b>    | ⌘ Aug 13, 2001   |
| <b>Category:</b>       | ⌘ A  | <b>Release:</b> | ⌘ REL-5  |
|                        | Use <u>one</u> of the following categories:<br>F (essential correction)<br>A (corresponds to a correction in an earlier release)<br>B (Addition of feature),<br>C (Functional modification of feature)<br>D (Editorial modification) |                 | Use <u>one</u> of the following releases:<br>2 (GSM Phase 2)<br>R96 (Release 1996)<br>R97 (Release 1997)<br>R98 (Release 1998)<br>R99 (Release 1999)<br>REL-4 (Release 4)<br>REL-5 (Release 5) |
|                        | Detailed explanations of the above categories can be found in 3GPP TR 21.900.  |                 |  |

|                                      |   |
|--------------------------------------|---|
| <b>Reason for change:</b>            | ⌘ The "PDP context activation" reports, provide no indication regarding the source of the PDP context initiation, i.e. whether the MS has initiated the PDP session it or whether it was done by the network. |
| <b>Summary of change:</b>            | ⌘ An optional session initiator field is being added to this specification in the PDP context activation report.  |
| <b>Consequences if not approved:</b> | ⌘ Missing capability and compatibility with 3GPP TS 23.060.   |

|                              |   |   |
|------------------------------|---|---|
| <b>Clauses affected:</b>     | ⌘ 7.3.2, 7.4.3  |   |
| <b>Other specs Affected:</b> | <input type="checkbox"/> Other core specifications<br><input type="checkbox"/> Test specifications<br><input type="checkbox"/> O&M Specifications | ⌘ |
| <b>Other comments:</b>       | ⌘   |   |

## 7.3.2 Structure of the events

There are seven different events in which the information is sent to the DF2 if this is required. Details are described in the following section. The events for interception are configurable (if they are sent to DF2) in the 3G GSN and can be suppressed in the DF2.

**The following events are applicable to 3G SGSN:**

- Mobile Station Attach;
- Mobile Station Detach;
- PDP context activation;
- Start of intercept with PDP context active;
- PDP context deactivation;
- RA update;
- SMS.

NOTE: 3G GGSN interception is a national option. Location information may not be available in this case.

The following events are applicable to the 3G GGSN:

- PDP context activation ;
- PDP context deactivation ;
- Start of interception with PDP context active.

A set of fields as shown below is used to generate the events. The events transmit the information from 3G GSN to DF2. This set of fields as shown below can be extended in the 3G GSN, if this is necessary as a national option. DF2 can extend this information if this is necessary as a national option e.g. a unique number for each surveillance warrant.

**Table 2: Information Events for Packet Data Event Records**

|   |
|---|
| Observed MSISDN<br>MSISDN of the target subscriber (monitored subscriber)   |
| Observed IMSI<br>IMSI of the target subscriber (monitored subscriber)   |
| Observed IMEI<br>IMEI of the target subscriber (monitored subscriber),it shall be checked for each activation over the radio interface.   |
| Event type<br>Description which type of event is delivered: MS attach, MS detach, PDP context activation, Start of intercept with PDP context active, PDP context deactivation, SMS, Cell and/or RA update, |
| Event date<br>Date of the event generation in the 3G GSN  |
| Event time<br>Time of the event generation in the 3G GSN  |
| PDP address<br>The PDP address of the target subscriber. Note that this address might be dynamic.   |
| Access Point Name<br>The APN of the access point. (Typically the GGSN of the other party)   |
| Location Information<br>Location Information is the service area identity, RAI and/or location area identity that is present at the GSN at the time of event record production.                             |
| PDP Type<br>The used PDP type.  |
| Correlation Number<br>The correlation number is used to correlate CC and IRI.   |
| SMS<br>The SMS content with header which is sent with the SMS-service. The header also includes the SMS-Centre address.   |
| Network Element Identifier<br>Unique identifier for the element reporting the ICE.  |
| Failed attach reason<br>Reason for failed attach of the target subscriber.  |
| Failed context activation reason<br>Reason for failed context activation of the target subscriber.  |
| IAs<br>The observed Interception Areas  |
| <u>Session Initiator</u><br><u>The initiator of the PDP context either the network or the 3G MS</u>   |

### 7.4.3 Packet Data PDP context activation

For PDP context activation a PDP context activation-event is generated. When a PDP context activation is generated from the mobile to 3G GSN this event is generated. These fields will be delivered to the DF2 if available:

|                                     |
|-------------------------------------|
| Observed MSISDN                     |
| Observed IMSI                       |
| Observed IMEI                       |
| PDP address of observed party       |
| Event Type                          |
| Event Time                          |
| Event Date                          |
| Correlation number                  |
| Access Point Name                   |
| PDP Type                            |
| Network Element Identifier          |
| Location Information                |
| Failed context activation reason    |
| IAs (if applicable)                 |
| <u>Session Initiator (optional)</u> |