Technical Specification Group Services and System Aspects Meeting #15, Cheju Island, Korea, 11-14 March 2002

SA5 (Telecom Management)
Rel-4 CR 32.304 (Configuration Management; Notification Integration Reference Point: CMIP SS) Correction of invalid ASN.1 definitions
Decision
7.5.3

Doc-1st- Level	Spec	CR	l Phas e	Subject	t	Version - Current	-New	Doc-2nd- Level	Workite m
SP- 020018	32.304	005		Correction of invalid ASN.1 definitions	F	4.1.0	4.2.0	S5- 020066	OAM-CM

3GPP TSG-SA5 (Telecom Management)S5-02006Meeting #25, Sophia Antipolis, France 14 - 18 January 2002S5C020039							
CHANGE REQUEST							
ж	32.304 CR 005 * rev - [*] Current version: 4.1.0						
For HELP on using this form, see bottom of this page or look at the pop-up text over the # symbols.							
Proposed change a	ffects: 第 (U)SIM ME/UE Radio Access Network X Core Network						
Title: %	Correction of invalid ASN.1 definitions						
Source: ೫	SA5						
Work item code: %	OAM-CM Date: # 18/01/2002						
	FRelease: %REL-4Use one of the following categories:Use one of the following releases:F (correction)2A (corresponds to a correction in an earlier release)R96B (addition of feature),R97C (functional modification of feature)R98D (editorial modification)R99D (editorial modification)R99Detailed explanations of the above categories canREL-4Kelease 4)REL-5Kelease 5)						
Reason for change.	: # There is an invalid ASN.1 definition in the TS.						
Summary of change	e: # Explicit tags are added to subscriptionState, timeTick and status of GetSubscriptionStatusReply SEQUENCE.						
Consequences if not approved:	# Implementation of Notification IRP CMIP Solution Set would be impossible.						
Clauses affected:	<mark>ቻ 6</mark>						
Other specs affected:	% Other core specifications % Test specifications O&M Specifications						
Other comments:	ж						

6 ASN.1 definitions

•••

GetSubscriptionStatusReply ::= SEQUENCE

{	
notificationCategoryList	NotificationCategoryList,
filterInEffect	CMISFilter, ITU-T X.711
subscriptionState	[2] SubscriptionState OPTIONAL,
timeTick	[3] INTEGER OPTIONAL,
status	[4] ErrorCauses
}	
-	

