

---

**Source:** SA WG3  
**Title:** CR to 33.107: PDP context Deactivation cause (Rel-5)  
**Document for:** Approval  
**Agenda Item:** 7.3.3

---

SA doc#	Spec	CR	R	Phase	Subject	Cat	Current Version	SA WG3 doc#
SP-020109	33.107	017		Rel-5	PDP context Deactivation cause	B	5.1.0	S3-020069

3GPP TSG SA WG3 Security — S3#22

S3-020069

25 - 28 February 2002

Bristol, UK

3GPP LI  
Amsterdam January 29-31, 2001

Tdoc S3LI02\_001r1001r2

CR-Form-v3
<b>CHANGE REQUEST</b>
⌘ <b>33.107 CR 017</b> ⌘ rev <b>-</b> ⌘ Current version: <b>5.1.0</b> ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM  ME/UE  Radio Access Network  Core Network

<b>Title:</b>	⌘ PDP context Deactivation cause		
<b>Source:</b>	⌘ SA WG3		
<b>Work item code:</b>	⌘ SEC-LI	<b>Date:</b>	⌘ 20 February 2002
<b>Category:</b>	⌘ <b>B</b>	<b>Release:</b>	⌘ REL-5
Use <u>one</u> of the following categories: <b>F</b> (essential correction) <b>A</b> (corresponds to a correction in an earlier release) <b>B</b> (Addition of feature), <b>C</b> (Functional modification of feature) <b>D</b> (Editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900.		Use <u>one</u> of the following releases: <b>2</b> (GSM Phase 2) <b>R96</b> (Release 1996) <b>R97</b> (Release 1997) <b>R98</b> (Release 1998) <b>R99</b> (Release 1999) <b>REL-4</b> (Release 4) <b>REL-5</b> (Release 5)	

<b>Reason for change:</b>	⌘ The information reported to the DF2 for the "PDP context deactivation" event, provides no indication regarding the cause of the PDP context deactivation (e.g., regular deactivation, network failure, protocol error). In addition, currently the intercepting system does not deliver information to determine the initiator of the PDP Context Deactivation request.
<b>Summary of change:</b>	⌘ A Deactivation/termination cause field is being added to this specification in the PDP context deactivation report. An request initiator field is being added to this specification in the PDP context deactivation report.  See also S3LI01_102 / 103
<b>Consequences if not approved:</b>	⌘ Missing capability and compatibility with 3GPP TS 23.060. ??

<b>Clauses affected:</b>	⌘ 7.4.5		
<b>Other specs Affected:</b>	⌘ <input type="checkbox"/> Other core specifications	⌘ <input type="checkbox"/>	⌘ <input type="checkbox"/>
	<input type="checkbox"/> Test specifications		
	<input type="checkbox"/> O&M Specifications		
<b>Other comments:</b>	⌘		

## 7.3.2 Structure of the events

There are seven different events in which the information is sent to the DF2 if this is required. Details are described in the following section. The events for interception are configurable (if they are sent to DF2) in the 3G GSN and can be suppressed in the DF2.

**The following events are applicable to 3G SGSN:**

- Mobile Station Attach;
- Mobile Station Detach;
- PDP context activation;
- Start of intercept with PDP context active;
- PDP context deactivation;
- RA update;
- SMS.

NOTE: 3G GGSN interception is a national option. Location information may not be available in this case.

The following events are applicable to the 3G GGSN:

- PDP context activation;
- PDP context deactivation;
- Start of interception with PDP context active.

A set of fields as shown below is used to generate the events. The events transmit the information from 3G GSN to DF2. This set of fields as shown below can be extended in the 3G GSN, if this is necessary as a national option. DF2 can extend this information if this is necessary as a national option e.g. a unique number for each surveillance warrant.

**Table 2: Information Events for Packet Data Event Records**

Observed MSISDN MSISDN of the target subscriber (monitored subscriber)
Observed IMSI IMSI of the target subscriber (monitored subscriber)
Observed IMEI IMEI of the target subscriber (monitored subscriber), it shall be checked for each activation over the radio interface.
Event type Description which type of event is delivered: MS attach, MS detach, PDP context activation, Start of intercept with PDP context active, PDP context deactivation, SMS, Cell and/or RA update,
Event date Date of the event generation in the 3G GSN
Event time Time of the event generation in the 3G GSN
PDP address The PDP address of the target subscriber. Note that this address might be dynamic.
Access Point Name The APN of the access point. (Typically the GGSN of the other party)
Location Information Location Information is the Service Area Identity (SAI), RAI and/or location area identity that is present at the GSN at the time of event record production.
PDP Type The used PDP type.
Correlation Number The correlation number is used to correlate CC and IRI.
SMS The SMS content with header which is sent with the SMS-service. The header also includes the SMS-Centre address.
Network Element Identifier Unique identifier for the element reporting the ICE.
Failed attach reason Reason for failed attach of the target subscriber.
Failed context activation reason Reason for failed context activation of the target subscriber.
IAs The observed Interception Areas
Session Initiator The initiator of the PDP context either the network or the 3G MS
Initiator SMS indicator whether the SMS is MO or MT
<u>Deactivation / termination cause</u> The termination cause of the PDP context

\*\*\* NEXT MODIFICATION \*\*\*

### 7.4.5 Packet Data PDP context deactivation

At PDP context deactivation a PDP context deactivation-event is generated. These fields will be delivered to the DF2 if available:

Observed MSISDN
Observed IMSI
Observed IMEI
PDP address of observed party
Event Type
Event Time
Event Date
Correlation number
Access point name
Network Element Identifier
Location Information
IAs (if applicable)
<u>Deactivation cause</u>

