

---

**Source:** SA5 (Telecom Management)  
**Title:** Rel-5 TS 32.635-200 (Core Network Resources IRP: Bulk CM XML File Format Definition)  
**Document for:** Approval  
**Agenda Item:** 7.5.3

---

3GPP TSG-SA5 (Telecom Management)  
Meeting #30, Tampere, Finland, 19-23 August 2002

S5-026685

## **Presentation of Technical Specification to TSG SA**

---

**Presentation to:** TSG SA Meeting #17  
**Document for presentation:** TS 32.635, Version 2.0.0  
Core Network Resources IRP: Bulk CM XML File Format Definition  
**Presented for:** Approval

---

**Abstract of document:**

Work done against the WID contained in SP-010461 (Work Item ID: OAM-NIM).

Due to the number of TSs defining Network Resource Models (NRMs) for Configuration Management (CM) as well as their expected growth in size from Release 5 onwards, a new TS structure is needed in Release 5 for the definition of the eXtensible Markup Language (XML) file formats for the Bulk CM Integration Reference Point (IRP).

This Release 5 TS structure for Bulk CM XML file format definition sets out as follows:

- 32.615 provides the head part of it,
- The present TS provides the sub-part that is specific to the NRM of the Core Network Resources IRP (32.632), and
- 32.625, 32.645 and 32.655 provide the other NRM-specific sub-parts.

Note: Linked changes to 32.615 were covered through Release 5 CR 003 approved at TSG SA meeting #16 (TD SP-020298).

---

**Changes since last presentation to TSG SA Meeting #16:**

None

---

**Outstanding Issues:**

The present TS draft version does not take into account the impacts, if any, from Release 5 SWG C WT 12 "Extensions to the Core Network Resource Model".

---

**Contentious Issues:**

None

# 3GPP TS 32.635 V2.0.0 (2002-09)

---

*Technical Specification*

**3rd Generation Partnership Project;  
Technical Specification Group Services and System Aspects;  
Telecommunication management;  
Configuration Management (CM);  
Core network resources  
Integration Reference Point (IRP):  
Bulk CM eXtensible Markup Language (XML)  
file format definition  
(Release 5)**

---



The present document has been developed within the 3<sup>rd</sup> Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

---

Keywords

---

Configuration Management

**3GPP**

Postal address

---

3GPP support office address

---

650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE  
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

---

<http://www.3gpp.org>

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© 2002, 3GPP Organizational Partners (ARIB, CWTS, ETSI, T1, TTA, TTC).  
All rights reserved.

---

# Contents

Foreword .....	4
Introduction .....	4
1 Scope .....	6
2 References .....	6
3 Definitions and abbreviations .....	6
3.1 Definitions .....	6
3.2 Abbreviations .....	8
4 Structure and content of configuration data XML files .....	8
<b>Annex A (normative): Configuration data file NRM-specific XML schema coreNrm.xsd .....</b>	<b>9</b>
<b>Annex B (informative): Change history .....</b>	<b>16</b>

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

## Introduction

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as single actions on single NEs of the 3G network, or as part of a complex procedure involving actions on many resources/objects in one or several NEs.

Due to the number of specifications defining Network Resource Models (NRMs) for Configuration Management as well as their expected growth in size from Release 5 onwards, a new structure of specifications is already needed in Release 5 for the definition of the XML file formats for the Bulk CM IRP (in Release 4 solely defined in 3GPP TS 32.615). This structure is needed to enable independent development and release for CM NRMs and corresponding NRM-specific parts of the Bulk CM XML file format definition, from each other and from the non NRM-specific part of the Bulk CM XML file format definition.

**Table 1: New specification structure for Bulk CM IRP XML file format definition**

Rel-4 3GPP TS	Rel-5 3GPP TS	3GPP TS no.	3GPP TS title
New	Yes	32.615	Bulk CM Integration Reference Point (IRP); eXtensible Markup Language (XML) file format definition
	<b>New</b>	32.625	Generic network resources Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition
	<b>New</b>	32.635	Core network resources Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition
	<b>New</b>	32.645	UTRAN network resources Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition
	<b>New</b>	32.655	GERAN network resources Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition

The present document is 3GPP TS 32.635 " Telecommunication management; Configuration Management (CM); Core network resources Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition".

---

# 1 Scope

The present document provides the NRM-specific part related to the Core Network Resources IRP NRM [1] of the XML file format definition for the Bulk Configuration Management IRP IS [2].

The main part of this XML file format definition is provided by 3GPP TS 32.615 [3].

Bulk CM XML file formats are based on XML [4], XML Schema [5] [6] [7] and XML Namespace [8] standards.

This File Format Definition specification is related to 3GPP TS 32.632 (V5.0.X).

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.632: "Telecommunication management; Configuration Management (CM); Core network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [2] 3GPP TS 32.612: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); Information service".
- [3] 3GPP TS 32.615: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); eXtensible Markup Language (XML) file format definition".
- [4] W3C REC-xml-20001006: "Extensible Markup Language (XML) 1.0 (Second Edition)".
- [5] W3C REC-xmlschema-0-20010502: "XML Schema Part 0: Primer".
- [6] W3C REC-xmlschema-1-20010502: "XML Schema Part 1: Structures".
- [7] W3C REC-xmlschema-2-20010502: "XML Schema Part 2: Datatypes".
- [8] W3C REC-xml-names-19990114: "Namespaces in XML".

---

# 3 Definitions and abbreviations

## 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**XML file:** file containing an XML document

**XML document:** composed of the succession of an optional XML declaration followed by a root XML element

NOTE: See [4]; in the scope of the present document.

**XML declaration:** it specifies the version of XML being used

NOTE: See [4].

**XML element:** has a type, is identified by a name, may have a set of XML attribute specifications and is either composed of the succession of an XML start-tag followed by the XML content of the XML element followed by an XML end-tag, or composed simply of an XML empty-element tag; each XML element may contain other XML elements

NOTE: See [4].

**empty XML element:** having an empty XML content; an empty XML element still possibly has a set of XML attribute specifications; an empty XML element is either composed of the succession of an XML start-tag directly followed by an XML end-tag, or composed simply of an XML empty-element tag

NOTE: See [4].

**XML content (of an XML element):** empty if the XML element is simply composed of an XML empty-element tag; otherwise the part, possibly empty, of the XML element between its XML start-tag and its XML end-tag

**XML start-tag:** the beginning of a non-empty XML element is marked by an XML start-tag containing the name and the set of XML attribute specifications of the XML element

NOTE: See [4].

**XML end-tag:** the end of a non-empty XML element is marked by an XML end-tag containing the name of the XML element

NOTE: See [4].

**XML empty-element tag:** an empty XML element is composed simply of an empty-element tag containing the name and the set of XML attribute specifications of the XML element

NOTE: See [4].

**XML attribute specification:** has a name and a value

**DTD:** defines structure and content constraints to be respected by an XML document to be valid with regard to this DTD

NOTE: See [4].

**XML schema:** more powerful than a DTD, an XML schema defines structure and content constraints to be respected by an XML document to conform with this XML schema; through the use of XML namespaces several XML schemas can be used together by a single XML document; an XML schema is itself also an XML document that shall conform with the XML schema for XML schemas

NOTE: See [5], [6] and [7].

**XML namespace:** enables qualifying element and attribute names used in XML documents by associating them with namespaces identified by different XML schemas

NOTE: See [8], in the scope of the present document.

**XML complex type:** defined in an XML schema; cannot be directly used in an XML document; can be the concrete type or the derivation base type for an XML element type or for another XML complex type; ultimately defines constraints for an XML element on its XML attribute specifications and/or its XML content

NOTE: See [5], [6] and [7].

**XML element type:** declared by an XML schema; can be directly used in an XML document; as the concrete type of an XML element, directly or indirectly defines constraints on its XML attribute specifications and/or its XML content; can also be the concrete type or the derivation base type for another XML element type

NOTE: See [5], [6] and [7].



## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CM	Configuration Management
DTD	Document Type Definition
EDGE	Enhanced Data for GSM Evolution
GERAN	GSM/EDGE Radio Access Network
GSM	Global System for Mobile communication
IRP	Integration Reference Point
IS	Information Service
NRM	Network Resource Model
UMTS	Universal Mobile Telecommunications System
UTRAN	Universal Terrestrial Radio Access Network
XML	eXtensible Markup Language

---

## 4 Structure and content of configuration data XML files

The overall description of the file format of configuration data XML files is provided by 3GPP TS 32.615 [3].

Annex A of the present document defines the NRM-specific XML schema `coreNrm.xsd` for the Core Network Resources IRP NRM defined in 3GPP TS 32.632 [1].

XML schema `coreNrm.xsd` explicitly declares NRM-specific XML element types for the related NRM.

The definition of those NRM-specific XML element types complies with the generic mapping rules defined in 3GPP TS 32.615 [3].

## Annex A (normative): Configuration data file NRM-specific XML schema coreNrm.xsd

The following XML schema coreNrm.xsd is the NRM-specific schema for the Core Network Resources IRP NRM defined in 3GPP TS 32.632 [1]:

```
<?xml version="1.0" encoding="UTF-8"?>

<!--
  3GPP TS 32.635 Core Network Resources IRP
  Bulk CM Configuration data file NRM-specific XML schema
  coreNrm.xsd
-->

<schema
  targetNamespace=
"http://www.3gpp.org/ftp/specs/latest/rel-4/32_series/32635-500.zip#coreNrm"
  elementFormDefault="qualified"
  xmlns="http://www.w3.org/2001/XMLSchema"
  xmlns:xn=
"http://www.3gpp.org/ftp/specs/latest/rel-4/32_series/32625-500.zip#genericNrm"
>

  <import
    namespace=
"http://www.3gpp.org/ftp/specs/latest/rel-4/32_series/32625-500.zip#genericNrm"
  />

  <!-- Core Network Resources IRP NRM class associated XML elements -->

  <element name="MscFunction">
    <complexType>
      <complexContent>
        <extension base="xn:NrmClassXmlType">
          <sequence>
            <element name="attributes" minOccurs="0">
              <complexType>
                <all>
                  <element name="userLabel" minOccurs="0"/>
                </all>
              </complexType>
            </element>
          </sequence>
        </extension>
      </complexContent>
    </complexType>
  </element>

  <element name="HlrFunction">
    <complexType>
      <complexContent>
        <extension base="xn:NrmClassXmlType">
          <sequence>
            <element name="attributes" minOccurs="0">
              <complexType>
                <all>
                  <element name="userLabel" minOccurs="0"/>
                </all>
              </complexType>
            </element>
          </sequence>
        </extension>
      </complexContent>
    </complexType>
  </element>

  <element name="VlrFunction">
    <complexType>
      <complexContent>
        <extension base="xn:NrmClassXmlType">
          <sequence>
```

```

    <element name="attributes" minOccurs="0">
      <complexType>
        <all>
          <element name="userLabel" minOccurs="0"/>
        </all>
      </complexType>
    </element>
  </sequence>
</extension>
</complexContent>
</complexType>
</element>

<element name="AucFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="EirFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="SmsIwmscFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="SmsGmscFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

```

```

        </element>
      </sequence>
    </extension>
  </complexContent>
</complexType>
</element>

<element name="GmscFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="SgsnFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="GgsnFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="BgFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

```

```

<element name="SmlcFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="GmlcFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="ScfFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="SrfFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="CbcFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>

```

```

    <element name="attributes" minOccurs="0">
      <complexType>
        <all>
          <element name="userLabel" minOccurs="0"/>
        </all>
      </complexType>
    </element>
  </sequence>
</extension>
</complexContent>
</complexType>
</element>

<element name="CgfFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="MgwFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="GmscServerFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="IwfFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

```

```

        </element>
      </sequence>
    </extension>
  </complexContent>
</complexType>
</element>

<element name="MnpSrfFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="NpdbFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="SgwFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="SsfFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

```

```
<element name="BsFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClassXmlType">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
</schema>
```



---

## Annex B (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Jun 2002	S_16	SP-020298	--	--	Submitted to TSG SA #16 for Information	1.0.0	
Sep 2002	S_17	SP-020461	--	--	Submitted to TSG SA #17 for Approval	2.0.0	