
Source: SA5 (Telecom Management)
Title: Rel-5 TS 32.661-200 (Kernel Configuration Management IRP: Requirements)
Document for: Approval
Agenda Item: 7.5.3

3GPP TSG-SA5 (Telecom Management)
Meeting #30, Tampere, Finland, 19-23 August 2002

S5-026681

Presentation of Technical Specification to TSG SA

Presentation to: TSG SA Meeting #17
Document for presentation: TS 32.661, Version 2.0.0
Kernel Configuration Management IRP: Requirements
Presented for: Approval

Abstract of document:

This Specification defines the Requirements of the Kernel Configuration Management IRP.

Work done against the WID contained in SP-010461 (Work Item ID: OAM-NIM).

Purpose of These Specifications:

This Kernel CM IRP Requirements Specification is intended for Release 5 and is part of the Kernel Configuration Management IRP, which consists of the four specifications, a Requirements Specification (32.661), an Information Service Specification (32.662) and two Stage 3 Specifications; a CORBA Solution Set Specification (32.663) and CMIP Solution Set Specification (32.664).

The purpose of this set of specifications is to provide an IRP that contains the Configuration Management (CM) functionality that is basic and minimal. It is the functionality that is common to and required by both Basic CM and Bulk CM. While neither the Basic CM IRP nor Bulk CM IRP requires the other, they each require the Kernel CM IRP.

Status of these Specifications:

The Kernel CM IRP requirements (32.661) was sent to SA#15 (03/2002) for Information and is now ready for Rel-5 approval.

Outstanding Issues:

None.

Contentious Issues:

None.

3GPP TS 32.661 V2.0.0 (2002-09)

Technical Specification

**3rd Generation Partnership Project;
Technical Specification Group Services and System Aspects;
Telecommunication management;
Configuration Management (CM);
Kernel CM: Requirements
(Release 5)**



The present document has been developed within the 3rd Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

Keywords

Configuration management

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 2002, 3GPP Organizational Partners (ARIB, CWTS, ETSI, T1, TTA, TTC).
All rights reserved.

Contents

Foreword	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations	5
3.1 Definitions	5
3.3 Abbreviations	7
4 Requirements	7
4.1 General Requirements	7
4.2 Kernel CM Requirements	8
Annex A (informative): Change history	9

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The present document is 32.661 of the 32.66x-series covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Configuration Management (CM); Kernel CM, as identified below:

32.661: "Requirements";

32.662: "Information service";

32.663: "CORBA Solution set";

32.664: "CMIP Solution set".

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as single actions on single NEs of the 3G network, or as part of a complex procedure involving actions on many resources/objects in one or several NEs.

1 Scope

The present document defines, in addition to the requirements defined in [1], [2] and [3], the requirements for the present IRP: Kernel Configuration Management IRP. It is the intent of Kernel Configuration Management to provide an IRP that contains the configuration management functionality that is basic and minimal. It is the functionality that is common to and required by both Basic CM and Bulk CM. While neither the Basic CM IRP nor Bulk CM IRP requires the other, they each require the Kernel CM IRP.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "3G Telecom Management principles and high level requirements".
- [2] 3GPP TS 32.102: "3G Telecom Management Architecture".
- [3] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and main requirements".
- [4] 3GPP TS 32.622: "Telecommunication management; Configuration Management (CM); Generic network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [5] 3GPP TS 32.632: "Telecommunication management; Configuration Management (CM); Core Network Resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [6] 3GPP TS 32.642: "Telecommunication management; Configuration Management (CM); UTRAN network resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [7] 3GPP TS 32.652: "Telecommunication management; Configuration Management (CM); GERAN network resources Integration Reference Point (IRP): Network Resource Model (NRM)".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

data: any information or set of information required to give software or equipment or combinations thereof a specific state of functionality

Element Manager (EM): provides a package of end-user functions for management of a set of closely related types of Network Elements (NEs). These functions can be divided into two main categories:

Element Management Functions for management of NEs on an individual basis. These are basically the same functions as supported by the corresponding local terminals.

Sub-Network Management Functions that are related to a network model for a set of NEs constituting a clearly defined sub-network, which may include relations between the NEs. This model enables additional functions on the sub-network level (typically in the areas of network topology presentation, alarm correlation, service impact analysis and circuit provisioning).

IRP: See 3GPP TS 32.101 [1].

IRP Information Model: See 3GPP TS 32.101 [1].

IRP Information Service: See 3GPP TS 32.101 [1].

IRP Solution Set: See 3GPP TS 32.101 [1].

Managed Object (MO): abstract entity, which may be accessed through an open interface between two or more systems, and representing a Network Resource (NR) for the purpose of management. The Managed Object (MO) is an instance of a Managed Object Class (MOC) as defined in a Management Information Model (MIM). The MIM does not define how the MO or NR is implemented; only what can be seen in the interface.

Managed Object Class (MOC): description of all the common characteristics for a number of MOs, such as their attributes, operations, notifications and behaviour

Managed Object Instance (MOI): instance of a MOC, which is the same as a MO as described above

Management Information Base (MIB): set of existing managed objects in a management domain, together with their attributes, constitutes that management domain's MIB. The MIB may be distributed over several OS/NEs.

Management Information Model (MIM): also referred to as NRM – see the definition below. There is a slight difference between the meaning of MIM and NRM – the term MIM is generic and can be used to denote any type of management model, while NRM denotes the model of the actual managed telecommunications Network Resources (NRs).

Network Element (NE): discrete telecommunications entity, which can be, managed over a specific interface e.g. the RNC

Network Manager (NM): provides a package of end-user functions with the responsibility for the management of a network, mainly as supported by the EM(s) but it may also involve direct access to the NEs. All communication with the network is based on open and well-standardised interfaces supporting management of multi-vendor and multi-technology NEs.

Network Resource (NR): component of a NE, which can be identified as a discrete separate entity and is in an object oriented environment for the purpose of management represented by an abstract entity called Managed Object (MO)

Network Resource Model (NRM): model representing the actual managed telecommunications Network Resources (NRs) that a System is providing through the subject IRP. An NRM describes Managed Object Classes (MOC), their associations, attributes and operations. The NRM is also referred to as "MIM" (see above) which originates from the ITU-T TMN.

Object Management Group (OMG): See <http://www.omg.org>.

Operations System (OS): indicates a generic management system, independent of its location level within the management hierarchy

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CM	Configuration Management
CMIP	Common Management Information Protocol
CORBA	Common Object Request Broker Architecture
EM	Element Manager
FM	Fault Management
IRP	Integration Reference Point
IS	Information Service (see [1])
ITU-T	International Telecommunication Union, Telecommunication Standardisation Sector
MIB	Management Information Base
MIM	Management Information Model
MOC	Managed Object Class
MOI	Managed Object Instance
NE	Network Element
NM	Network Manager
NR	Network Resource
NRM	Network Resource Model
OMG	Object Management Group
OS	Operations System
PM	Performance Management
TM	Telecom Management
UML	Unified Modelling Language (OMG)
UMTS	Universal Mobile Telecommunications System

4 Requirements

4.1 General Requirements

This requirements specification defines requirements for the IS for this IRP. As such, capabilities specified here as being required in the IS are not necessarily required in the product implementation. That which is required in the product implementation will be specified in the IS itself.

The following general and high-level requirements apply for the present IRP:

- A. IRP-related requirements in 3GPP TS 32.101: "3G Telecom Management principles and high level requirements" [1].
- B. IRP-related requirements in 3GPP TS 32.102: "3G Telecom Management architecture" [2].
- C. IRP-related requirements in 3GPP TS 32.600: "3G Configuration Management: Concept and High-level Requirements" [3].

In addition to the above, the following more specific requirements apply:

1. The IS defined by this IRP shall enable an NM to operate on (access) any of the NRMs defined in [4], [5], [6] and [7].
2. The IS defined by this IRP shall as far as possible be independent of any specific definitions of MOCs, attributes etc. in the NRMs referred to in item 1.

4.2 Kernel CM Requirements

The IS defined by this IRP shall include the following operations that may be invoked by the IRP Manager to retrieve management information from the IRP Agent:

- An operation to retrieve the Network Resource IRP SS document versions (IRP Versions) of the NRM Solution Sets that are supported by each Network Resource IRP present in the subject implementation.

The IS defined by this IRP shall include a notification capability by which the IRP Agent sends management information to the IRP Manager whenever an event of a specific type occurs. Specifically, the following types of notifications shall be supported:

- A notification that identifies the instance of a managed object that was created.
- A notification that identifies one or more instances of a managed object that were deleted.
- A notification that identifies the values of one or more attributes of a managed object instance that were changed.

Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Mar 2002	S_15	SP-020034	--	--	Submitted to TSG SA #15 for Information	1.0.0	
Sep 2002	S_17	SP-020464	--	--	Submitted to TSG SA #17 for Approval	2.0.0	