Technical Specification Group Services and System Aspects **TSGS#19(03)0031** Meeting #19, Birmingham, UK, 17-20 March 2003**

Source: SA1

Title: CR to 22.243 on Correction of contradictory information (former:

'Removal of references') (Rel-6)

Document for: Approval

Agenda Item: 7.1.3

SA Doc	Spec	CR	Rev	Phase	Cat	Subject	Old Vers	New Vers	SA1 Doc
SP-030031	22.243	003	-	Rel-6	F	Correction of contradictory information (former: 'Removal of references')			S1-030151

CR-Form-v7 CHANGE REQUEST Current version: 6.1.0 \mathfrak{R} 22,243 CR 003 **#rev** For **HELP** on using this form, see bottom of this page or look at the pop-up text over the \mathbb{H} symbols. Proposed change affects: UICC apps₩ ME X Radio Access Network Core Network X Title: # Correction of contradictory information (former: "Removal of references") Source: 第 SA1 (NOKIA) Date: # 09/01/2003 ₩ F Release: # Rel-6 Category: Use one of the following releases: Use one of the following categories: **F** (correction) 2 (GSM Phase 2) **A** (corresponds to a correction in an earlier release) R96 (Release 1996) **B** (addition of feature), (Release 1997) R97 **C** (functional modification of feature) R98 (Release 1998) **D** (editorial modification) (Release 1999) R99 Detailed explanations of the above categories can Rel-4 (Release 4) be found in 3GPP TR 21.900. Rel-5 (Release 5) Rel-6 (Release 6) Reason for change: ₩ This statement is contradictory to information provided in Chapter 5 which mentions that either a conventional codec or DSR optimised codec will be the default uplink codec. Moreover, 3GPP SA4 is still debating the choice of codec for speech-enabled services. The current statement pre-supposes a particular kind of codec for these services. Summary of change: # Correction of sentence in section 4.1 "The terminal shall support a speech recognition optimized codec as a default uplink codec." to "The terminal shall support a codec suitable for speech recognition optimized codec as a default uplink codec." Consequences if Contradictory Information will be present in the document. not approved: Clauses affected: \mathfrak{H} Chapter 4 Other specs \mathfrak{R} X Other core specifications \mathfrak{R} affected: Test specifications **O&M** Specifications Other comments: \mathfrak{R}

S1-030151

Agenda Item: SES

How to create CRs using this form:

Comprehensive information and tips about how to create CRs can be found at http://www.3gpp.org/specs/CR.htm. Below is a brief summary:

- 2) Obtain the latest version for the release of the specification to which the change is proposed. Use the MS Word "revision marks" feature (also known as "track changes") when making the changes. All 3GPP specifications can be downloaded from the 3GPP server under ftp://ftp.3gpp.org/specs/ For the latest version, look for the directory name with the latest date e.g. 2001-03 contains the specifications resulting from the March 2001 TSG meetings.
- 3) With "track changes" disabled, paste the entire CR form (use CTRL-A to select it) into the specification just in front of the clause containing the first piece of changed text. Delete those parts of the specification which are not relevant to the change request.

4.1 Initiation

It shall be possible for a user to initiate a connection to the SRF-based automatic voice services by entering the identity of the service. Most commonly, when used as a voice service, this will be performed by entering a phone number. However, particular terminals may offer a user agent that accepts other addressing schemes to be entered by the user: IP address, URI, e-mail address possibly associated to a protocol identifier. This is particularly important for multi-modal usages.

In all cases, the terminal will convert the address entered by the user to initiate a session via the SIP IMS session initiation protocol and establish the different SRF protocols. During this initiation of the SRF session, it shall be possible to negotiate the uplink and downlink codecs. The terminal shall support a <u>codec suitable for</u> speech recognition optimized codec as a default uplink codec.