

14 - 17 May 2002, Victoria, Canada

CR-Form-v5

CHANGE REQUEST

⌘ **33.203 CR** ⌘ rev **-** ⌘ Current version: **5.1.0** ⌘

For **HELP** on using this form, see bottom of this page or look at the pop-up text over the ⌘ symbols.

Proposed change affects: ⌘ (U)SIM ME/UE Radio Access Network Core Network

Title:	⌘ UE and P-CSCF Behaviour on an Incomplete Authentication		
Source:	⌘ Hutchison 3G UK		
Work item code:	⌘	Date:	⌘
Category:	⌘ F	Release:	⌘ Rel-5
	Use <u>one</u> of the following categories: F (correction) A (corresponds to a correction in an earlier release) B (addition of feature), C (functional modification of feature) D (editorial modification) Detailed explanations of the above categories can be found in 3GPP TR 21.900 .		Use <u>one</u> of the following releases: 2 (GSM Phase 2) R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) REL-4 (Release 4) REL-5 (Release 5)

Reason for change:	⌘ The behaviour of the UE, P-CSCF and S-CSCF after an incomplete registration is not currently specified. This leaves an incomplete specification. The change also removes an Editor's note.
Summary of change:	⌘ Describes the behaviour of the UE, P-CSCF and S-CSCF after an incomplete authentication.
Consequences if not approved:	⌘ The specification will not be complete, which may lead to implementations that do not operate successfully together.

Clauses affected:	⌘ 6.1.2.3, 7.3, 7.3.1.4		
Other specs affected:	⌘ <input type="checkbox"/> Other core specifications <input type="checkbox"/> Test specifications <input type="checkbox"/> O&M Specifications	⌘	
Other comments:	⌘		

***** FIRST CHANGED SECTION *****

6.1.2.3 Incomplete authentication

If the S-CSCF does not receive a response to an authentication within an acceptable time, it considers the authentication to have failed. If the IMPU was not already registered, the S-CSCF shall send a Cx-Put to the HSS to set the registration-flag for that IMPU to *unregistered* (see message CM3 in clause 6.1.2.2). If the IMPU was already registered, the S-CSCF does not change the registration-flag.

***** NEXT CHANGED SECTION *****

7.3 Error cases in the set-up of security associations

~~Whenever an expected message is not received after a time-out the receiving entity considers the registration to have failed.~~

~~[Editor's note: Clarify, how SIP registration handles the inconsistent state that is created by a lost SM12 message]~~

***** NEXT CHANGED SECTION *****

7.3.1.4 Incomplete authentication

If the UE responds to an authentication challenge from a S-CSCF, but does not receive a reply before the request times out, the UE shall start a registration procedure if it still requires any IM services. The first message in this registration should be protected with an SA created by a previous successful authentication if one exists.

If the P-CSCF deletes a registration SA due to its lifetime being exceeded, the P-CSCF should delete any information relating to that registration procedure.