Povoa de varzim, Portugal, 6-10 October 2003

				CR-Form-v7
CHANGE REQUEST				
* SpecNun	nber CR CRNum	≭rev - ^ℋ	Current version: 0.3.0	ж
For HELP on using this form, see bottom of this page or look at the pop-up text over the # symbols.				
Proposed change affec	ets: UICC apps₩	ME Radio Ad	ccess Network Core Ne	etwork X
Title: % Requirements for A and C interface				
Source: % No	kia			
Work item code: # SE			Date: # 2003-09-25	
Deta	one of the following categories. F (correction) A (corresponds to a correction B (addition of feature), C (functional modification of the D (editorial modification) alied explanations of the above bund in 3GPP <u>TR 21.900</u> .	on in an earlier release feature)	Release: ¥ Rel-6 Use <u>one</u> of the following rele 2 (GSM Phase 2) 9 R96 (Release 1996) R97 (Release 1997) R98 (Release 1998) R99 (Release 1999) Rel-4 (Release 4) Rel-5 (Release 5) Rel-6 (Release 6)	ases:
Reason for change: # The TS contain requirements for B and D interfaces. The similar requirements for A and C interfaces are not in the Current TS.				
Summary of change: ℜ	This pseudo-CR adds a r interfaces A and C.	new subchapters inc	cluding the missing requirem	ents for
Consequences if # not approved:			that will be used for stage 3 CN4), are not documented	
Clauses affected: #	4.1.4			
Other specs % affected:	YN			
Other comments: ೫				

********* the addition**********

4.1.4 Requirements on protocol A (Ub)

The requirements for protocol A (Ub) are:

- The BSF shall be able to identify the UE.
- The BSF and the UE shall be able to authenticate each other based on AKA.
- The BSF shall be able to send a transaction identifer to UE.

4.1.5 Requirements on protocol C (Zh)

The requirements for protocol C (Zh) are:

- The BSF is able to communicate securely with the subscriber's HSS.
- The BSF is able to send bootstrapping information request concerning a subscriber.
- The HSS is able to send authentication vectors to the BSF.
- The HSS is able to send the subscriber's GAA profiles to the BSF.
- No state information concerning bootstrapping is required in the HSS.
- All procedures are initiated by the BSF.