

3G TS 26.915 V0.0.2 (2000-02)

Technical Specification

**3rd Generation Partnership Project;
TSG-SA Codec Working Group;
Echo Control For Speech and Multi-Media Services.
(3G TS 26.915 version 0.0.2)**



The present document has been developed within the 3rd Generation Partnership Project (3GPPTM) and may be further elaborated for the purposes of 3GPP.

The present document has not been subject to any approval process by the 3GPP Organisational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organisational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPPTM system should be obtained via the 3GPP Organisational Partners' Publications Offices.

Reference

DTS/TSG<name abbrev>-0<WG no><spec no> U

Keywords

<keyword[, keyword]>

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

<http://www.3gpp.org>

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© 1999, 3GPP Organizational Partners (ARIB, CWTS, ETSI, T1, TTA, TTC).
All rights reserved.

Contents

Foreword	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions, symbols and abbreviations	5
Abbreviations	5
4 Interfaces	6
5 Transmission Plan,	Error! Bookmark not defined.
5.1 Delay Budget.....	Error! Bookmark not defined.
5.1.1 General.....	Error! Bookmark not defined.
History	7

Foreword

This Technical Specification has been produced by the 3GPP.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of this TS, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 Indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the specification;

Introduction

The present document specifies minimum performance requirements for the transmission planning aspects of 3G speech and multi-media services.

The objective is to reach a quality as close as possible to ITU-T standards for PSTN circuits. However, due to technical and economic factors, there cannot be full compliance with the general characteristics of international telephone connections and circuits recommended by the ITU-T.

The performance requirements are specified the main body of the text; the test methods and considerations are described in [tbd].

1 Scope

The present document specifies minimum performance requirements for the gateway echo control of 3G speech and multi-media services. The present document is applicable to any narrow band speech telephony or multimedia service.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.

- [1] ITU-T Recommendation G.114 (1998): "Delay".
- [2] ITU-T Recommendation G.168 (1998): "Echo Cancellers".
- [3] ITU-T Recommendation G.131 (1998): "Echo".
-

3 Definitions, symbols and abbreviations

5.1 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ADC	Analogue to Digital Converter
DAC	Digital to Analogue Converter
DTX	Discontinuous Transmission
EC	Echo Cancellor
ERL	Echo Return Loss
ERLE	Echo Return Loss Enhancement
EEC	Electrical Echo Control
EL	Echo Loss
PCM	Pulse Code Modulation
POI	Point of Interconnection (with PSTN)
PSTN	Public Switched Telephone Network
TCL	Terminal Coupling Loss
TX	Transmission

4 Interfaces

The POI with the public switched telephone network (PSTN) will generally be at the 2 048 kbits/ level at an interface in accordance with ITU-T Recommendation G.703/G.704 or STM1 155Mbit/s. At this point, which is considered to have a relative level of 0 dBr, the analogue signals will be represented by 8-bit A-law, according to ITU-T Recommendation G.711. Analogue measurements may be made at this point using a standard send and receive side, as defined in ITU-T Recommendations.

5 Narrow Band Speech Telephony Network Echo Control

5.1 GSTN Network Echo Cancellation

Narrow band speech calls from the 3G mobile system to the public GSTN are terminated on local switch line cards where two to four wire conversion takes place. The hybrid used to carry out this function is never perfect and echo is generated which degrades the speech call quality for the 3G mobile user. To overcome this situation an echo cancellation device should be used at the gateway from the 3G mobile network to the GSTN. This echo control device shall conform to ITU-T G.168.

Note : Acoustic Echo Control : Narrow band speech calls from the 3G mobile network to the public GSTN involve a high delay. The only echo path that is audible to the GSTN user is the acoustic echo path in the UE. To overcome this echo, and acoustic echo loss or Terminal Coupling Loss (TCL) of 46dB should be achieved by the terminal. This provides adequate echo protection for calls up to a delay of 300ms as defined by ITU-T Recommendation G.131.

History

Document history		
0.0.2	February 2000	Second draft, change of scope to include echo control only.