

Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); IPTV Architecture; IPTV functions supported by the IMS subsystem

CAUTION: This **DRAFT document** is provided for information and is for future development work within the ETSI Technical Committee TISPAN only. ETSI and its Members accept no liability for any further use/implementation of this Specification.

Approved and published Specifications and reports for implementation of the TISPAN NGN system shall be obtained exclusively via the ETSI Documentation Service at <http://pda.etsi.org/pda/queryform.asp>



Reference

RTS/TISPAN-02070-NGN-R3

Keywords

architecture, IMS, IP, TV

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Draft

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2008.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™, TIPHON™, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Contents

Intellectual Property Rights	2
Foreword.....	2
1 Scope	2
2 References	2
2.1 Normative references	2
2.2 Informative references.....	2
3 Definitions and abbreviations.....	2
3.1 Definitions.....	2
3.2 Abbreviations	2
4 High-level overview	2
5 Overview of functional entities	2
5.1 Functional architecture for IPTV services.....	2
5.1.1 Functional architecture overview.....	2
5.1.2 IPTV services.....	2
5.1.2.1 General.....	2
5.1.3 Functional entities.....	2
5.1.3A Generic Capabilities.....	2
5.1.4 Elementary functions.....	2
5.1.4.1 Content security functions.....	2
5.1.5 Functional Entities.....	2
5.1.5.1 Service Discovery and Selection Functions (SDF and SSF).....	2
5.1.5.2 IPTV Service Control Functions (SCF).....	2
5.1.5.3 IPTV Media Control and Delivery Functions (MCF and MDF).....	2
5.1.5.4 UPSF.....	2
5.1.5.5 Transport processing functions	2
5.2 Interactions between Service Control function and Media Functions	2
5.3 Void.....	2
5.4 Inter-destination media synchronization	2
5.4.1 Functional entities MSAS and SC	2
5.4.2 Mapping onto the IPTV architecture	2
5.4.3 Modification and re-origination of media streams.....	2
6 Reference points.....	2
6.1 UE - SSF (Xa)	2
6.2 UE - IPTV Service Control Functions (Ut).....	2
6.3 UE - Core IMS (Gm).....	2
6.4 UE - Media Control Functions (Xc).....	2
6.5 UE - Media Delivery Functions (Xd).....	2
6.6 IPTV Service Control Functions (SCF) - UPSF (Sh).....	2
6.7 Core IMS - UPSF (Cx).....	2
6.8 Core IMS - IPTV Service Control Functions (ISC)	2
6.9 Core IMS - IPTV Media Functions (y2)	2
6.10 Core IMS - SDF (ISC).....	2
6.11 SDF - UPSF (Sh).....	2
6.12 Void.....	2
6.13 Application Functions - NASS (e2).....	2
6.14 Core IMS - RACS (Gq')	2
6.15 NASS - RACS (e4).....	2
6.16 IPTV Service Control Functions - SLF (Dh).....	2
6.17 Core IMS - SLF (Dx)	2
6.18 IPTV Media Control Function - IPTV Media Delivery Function (Xp).....	2
6.19 MSAS-SC reference point (Sync)	2
6.20 MSAS-SC' reference point (Sync').....	2

7	User data.....	2
7.1	Classification of information.....	2
7.2	Location and access to user data	2
7.2.1	Data management functions.....	2
7.2.2	Access from other application servers	2
7.2.3	Access from User Equipment (UE)	2
7.2.4	Access from the SSF.....	2
7.3	IPTV user profile structure.....	2
7.3.1	IPTV user profile structure	2
7.3.1.1	BC service package.....	2
7.3.1.2	BC service.....	2
7.3.1.3	UE.....	2
7.3.1.4	Global settings: language preference	2
7.3.1.5	Global settings: user action recordable	2
7.3.1.5A	Global settings: PC-CostLimit	2
7.3.1.5B	Global settings: PC-TotalCostLimit.....	2
7.3.1.5C	Global settings: PC-ClassificationRestriction.....	2
7.3.1.5D	Global settings: PC-TimePeriodRestriction	2
7.3.1.5E	Global settings: PC-TotalPlayTimeLimit.....	2
7.3.1.5F	Global settings: PC-AdminUser.....	2
7.3.1.5G	Global settings: dynamic PC-activation.....	2
7.3.1.5H	Global settings: PC-Contact.....	2
7.3.1.6	N-PVR storage-limit	2
7.3.1.6A	PVR: IPTVContentMarkerAuthorizedViewUser.....	2
7.3.1.6B	PVR: IPTVContentMarkerSourceUser	2
7.3.1.6C	PVR: AuthorizedControlUser	2
7.3.1.7	BC: ParentalControlLevel	2
7.3.1.10	PCh: PChId.....	2
7.3.1.11	PCh: PChExpiryTime.....	2
7.3.1.12	PCh: PChItemServiceType.....	2
7.3.1.13	PCh: PChItemContentId.....	2
7.3.1.14	PCh: PChItemStartTime.....	2
7.3.1.15	PCh: PChItemEndTime	2
7.3.1.16	PCh: PChItemOffset.....	2
7.3.1.17	CR Settings: CR notifications	2
7.3.2	Usage of IPTV user profile.....	2
7.3.3	Life cycle	2
7.4	IPTV service action data	2
7.4.1	Data model.....	2
7.4.2	Life cycle	2
7.5	IPTV information storing/sharing services.....	2
7.5.1	General.....	2
7.5.2	IPTV Content Marker	2
7.5.2.1	General.....	2
7.5.2.2	IPTVContentMarkerID	2
7.5.2.3	OwnerUserID	2
7.5.2.4	IPTVServiceType.....	2
7.5.2.5	ReferencedContentID.....	2
7.5.2.6	StartTimeOfIPTVContentMarker	2
7.5.2.8	UserComment	2
7.5.2.9	GenerationTime	2
7.5.2.10	ExpiryTime	2
7.5.3	IPTV Service Access History	2
7.5.3.1	Data model	2
7.5.3.2	UserID.....	2
7.5.3.3	AccessHistoryID	2
7.5.3.4	ServiceType	2
7.5.3.5	ReferencedContentID.....	2
7.5.3.6	Rating.....	2
7.5.3.7	AccessStartTime	2
7.5.3.8	AccessEndTime	2
7.5.3.9	HistoryExpiryTime	2

7.6	IPTV Content Recommendation profile.....	2
8	Procedures	2
8.1	IPTV addressing mechanisms	2
8.1.1	IPTV end-users identification and addressing mechanisms.....	2
8.1.2	Addressing of nodes.....	2
8.2	UE start-up procedure	2
8.3	Broadcast session	2
8.3.1	Signalling flows for broadcast session initiation	2
8.3.1.1	Overview of the signalling flows for session initiation.....	2
8.3.1.2	Signalling flows for the establishment of the delivery channel.....	2
8.3.2	Signalling flows for BC session modification	2
8.3.3	Signalling flows for broadcast session release.....	2
8.3.4	Signalling flow for Broadcast TV channel switching.....	2
8.3.5	Signalling flows for transition from Broadcast TV to Broadcast TV with trick play	2
8.3.6	Signalling flows for transition from Broadcast TV with trick play to Broadcast TV	2
8.3.7	Signalling flows for Broadcast TV with trick play session release.....	2
8.3.8	Signalling flows for Pay Per View service	2
8.4	CoD session.....	2
8.4.1	Signalling Flows for CoD session initiation	2
8.4.1.1	Overall signalling flows	2
8.4.1.2	Media Channel Negotiation	2
8.4.1.2.1	Signalling flows for the establishment of the content control and content delivery channels from MF	2
8.4.1.2.2	Signalling flows for the establishment of the content control and content delivery channels from UE.....	2
8.4.1.2.3	Signalling flows for the establishment of the content control channel from UE.....	2
8.4.2	Signalling Flows for CoD session modification	2
8.4.2.1	Signalling flows for the establishment/modification of the content delivery channel from UE.....	2
8.4.2.2	Signalling flows for the modification of the content delivery channels from MF	2
8.4.3	Signalling Flows for CoD session release.....	2
8.4.4	Signalling Flows for CoD session transfer	2
8.4.4.1	Terminal centric session transfer pushed from transferor UE to transferee UE	2
8.4.4.2	Network centric session Transfer pushed from transferor UE to transferee UE	2
8.4.4.3	Session Replication pushed from transferor UE to transferee UE	2
8.4.4.4	Session Transfer pulled by the transferee UE	2
8.4.4.5	Session Replication Between transferor to transferee in a pull mode transfer	2
8.4.5	Signalling flows for CoD service action data update.....	2
8.4.5.1	CoD service action data updated by UE.....	2
8.4.5.2	CoD service action data updated by MF.....	2
8.4.6	Signalling flows for generating playlist by SCF and sending playlist information from SCF to MF during CoD session initiation.....	2
8.4.7	Signalling flows for generating playlist by SCF and sending playlist information from SCF to MF during an existing CoD session.....	2
8.4.8	Content switch procedure within a CoD playlist	2
8.5	PVR service procedures	2
8.5.0A	Signalling Flows for PVR Using Impulsive Request.....	2
8.5.0B	Signalling flows for the PVR off-line capture request.....	2
8.5.1	Network PVR service procedures.....	2
8.5.1.1	Signalling Flows for Network-PVR Service Capture Request.....	2
8.5.1.1.1	Signalling Flows for Network-PVR Using Impulsive Request	2
8.5.1.1.2	Signalling flows for the Network-PVR off-line capture request	2
8.5.1.2	Signalling flows for Network-PVR content session.....	2
8.5.2	Client PVR service procedures	2
8.5.2.1	Signalling Flows for Client-PVR Service Capture Request.....	2
8.5.2.1.1	Signalling Flows for Client-PVR Using Impulsive Request	2
8.5.2.1.2	Signalling flows for the Client-PVR off-line capture request.....	2
8.5.2.2	Signalling flows for Client-PVR recording session	2
8.5.3	PVR content update procedures.....	2
8.6	Time Shift service procedures	2
8.7	Preview procedures	2
8.7.1	Preview procedures for BC service.....	2

8.7.1.1	Session initiation procedures for multi-screen BC preview	2
8.7.1.2	Procedures for transition between multi-screen BC preview and regular BC service.....	2
8.7.2	Preview procedures for COD service.....	2
8.7.2.1	CoD preview procedures for sharing identifier	2
8.8	Parental control procedures	2
8.9	UGC procedures	2
8.9.1	Overview	2
8.9.2	UGC creation procedure	2
8.9.3	UGC watching procedure	2
8.10	Personalized channel (PCh) service procedures	2
8.11	Interaction procedures with other IPTV Services.....	2
8.11.1	Notification procedures.....	2
8.11.1.1	Notification procedures using signalling path.....	2
8.11.1.2	Notification procedures using multicast media path	2
8.12	Procedures for IPTV User Profile Configuration	2
8.13	Content Recommendation service procedures.....	2
8.14	Advertising (Ad) service procedures	2
8.14.1	Generic Procedures for targeted ad insertion (TAI).....	2
8.14.2	Generic Signalling for Targeted Ad insertion	2
8.14.2.1	signalling flows for TAI at UE side	2
8.14.2.2	Signalling flows for TAI at MF side	2
8.15	Procedures for inter-destination media synchronization	2
8.15.1	MSAS – SC.....	2
8.15.1.1	SCF-based media synchronization	2
8.15.1.1.1	Mapping 1: SC in UE	2
8.15.1.1.2	Mapping 2: SC in Transport	2
8.15.2	MSAS – SC'	2
8.16	Signalling flows for network-controlled trick play	2
8.17	Push Procedures	2
8.17.1	Push CoD session	2
8.18	Unicast Content Upload/Download Procedures.....	2
8.18.1	Signalling Flows for UE-initiated Unicast Content Upload/Download	2
8.18.2	Signalling Flows for SCF-initiated Unicast Content Download	2
8.19	Multicast Content Download Procedures	2
8.19.1	Signalling Flows for UE-initiated Multicast Content Download.....	2
8.19.2	Signalling Flows for SCF-initiated Multicast Content Download	2
8.20	signalling flows for restricted trick play.....	2
8.21	Shared Service Control (SSC) procedures.....	2
8.21.1	Overview	2
8.21.2	Room creation procedure for SSC	2
8.21.3	Room selection procedure for SSC.....	2
8.21.4	Shared service control procedures	2
8.21.4.1	Shared BC channel changes	2
8.21.4.2	Shared CoD trick play commands.....	2
8.22	Personalized Service Composition (PSC) procedures	2
8.23	Signalling flows for IPTV Content Marker service procedures	2
8.23.1	IPTV Content Marker storing procedures.....	2
8.23.2	IPTV Content Marker retrieval procedures	2
8.24	Role of BGF in IPTV	2
8.25	Procedures for service initiation by remote UE.....	2
9	Interactions between IPTV services and other TISPAN services	2
9.1	Presence and IPTV	2
9.1.1	Presence architecture and functional description	2
9.1.2	Presence attributes for IPTV	2
9.1.3	SIP related procedure.....	2
9.2	Incoming call management.....	2
9.3	Message and IPTV	2
9.3.1	Messaging procedures.....	2
9.3.2	Procedures for deliver messages of BC service using media path	2
9.4	Event Handling involving the SCF.....	2

10	Security.....	2
10.1	Authentication	2
10.2	Content Security.....	2
11	Charging.....	2
12	Management.....	2
12.1	Management requirements	2
12.2	Content management.....	2
13	Support of Metadata.....	2
13.1	Introduction.....	2
13.2	SSF support.....	2
13.3	SCF/MF support.....	2
14	Support of Mobility Capabilities.....	2
Annex A (informative): Integration of non-SIP-AS Service Discovery Function in IMS based IPTV.....		2
A.1	Introduction.....	2
A.2	Architecture.....	2
A.2.1	Functional entities	2
A.2.2	Reference points.....	2
A.2.2.1	UE - SDF (Xa).....	2
A.2.3	Procedures.....	2
A.2.3.1	IPTV service attachment and selection.....	2
Annex B (informative): Policies for Shared Service Control.....		2
B.1	Types of Policies.....	2
B.1.1	Policy for floor control.....	2
B.1.2	Policy distribution towards UE.....	2
B.1.3	Policy for loose control.....	2
Annex C (informative): Architectures for Interactions between IPTV services and other TISPN services.....		2
C.1	Interaction based on an OSA/Parlay/Parlay X SCS.....	2
C.1.1	Service Capability Server (SCS).....	2
C.1.2	Architecture.....	2
C.2	Interaction based on a 3GPP SCIM.....	2
C.2.1	Service Capability Interaction Manager (SCIM).....	2
C.2.2	Architecture.....	2
Annex D (informative): Mapping of elementary functions.....		2
D.1	Mapping of elementary functions to generic capabilities.....	2
D.2	Mapping of elementary functions to functional entities.....	2
D.3	Mapping of elementary functions to IPTV services.....	2
Annex E (Note: it shall be decided if this annex is normative or informative): Architecture, reference points, Procedures for advertising.....		2
E.1	General Advertising Architecture.....	2
E.1.1	Definitions.....	2
E.2	Internal Advertising Architecture Option.....	2
E.2.2	Advertising architecture.....	2
E.2.3	Reference points.....	2
E.2.4	Procedures for targeted ad insertion (TAI).....	2
E.2.4.1	Signalling flows for TAI at UE side.....	2
E.2.4.2	Signalling flows for TAI at MF side.....	2
E.3	SCTE-130 Based External Advertising Architecture Option.....	2

E.3.1	Definitions	2
E.3.2	SCTE-130 based Advertising Architecture	2
E.3.3	Reference points	2
E.3.3.1	IPTV Service Control Functions (SCF) – SCTE-130 External Ad system (ADx)	2
E.3.3.2	IPTV Media Function (MF) – SCTE-130 External Ad system (ADy)	2
E.3.3.3	Procedures for targeted ad insertion (TAI)	2
E.3.3.3.1	Signalling flows for TAI	2
E.4	OMA MobAd Based External Architecture Option	2
E.4.1	Definitions	2
E.4.2	OMA MobAd based Advertising Architecture	2
E.4.3	Reference Points	2
E.4.3.1	IPTV SCF / MCF – MobAd External Ad system (MobAd-2)	2
E.4.3.2	IPTV UE – MobAd External Ad system (MobAd-3)	2
E.4.4	Procedures for Targeted Ad Insertion (TAI)	2
E.4.4.1	Signalling Flows for TAI	2
Annex F: Mapping between TISPAN entities and external architectures (Informative)		2
F.1	Mapping between TISPAN entities and SCTE-130 entities	2
F.1	Mapping between TISPAN Entities and OMA MobAd Entities	2
Annex G (informative): Ad placement options		2
G.1	IPTV Ad placement: SCTE-130 option	2
Annex H (informative): Interconnection Models to support of Mobility Capabilities		2
H.1	Interconnection model using IMS roaming to home IMS IPTV	2
H.2	Signalling flows	2
H.2.1	UE start-up procedures	2
H.2.2	CoD procedures	2
Annex ZZY (informative): Possible mappings with IMS based IPTV		2
ZZY.1	Possible conceptual mapping of 3GPP IMS based PSS and MBMS with TISPAN IMS based IPTV	2
ZZY.1.1	Mapping between TISPAN entities and 3GPP IMS based PSS and MBMS	2
ZZY.1.2	Mapping between 3GPP IMS based PSS and MBMS and TISPAN IMS based IPTV architecture	2
ZZY.1.3	Mapping to TISPAN reference points	2
Annex ZZZ(informative): Change history:		2
History	2

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN).

Draft

1 Scope

The present document specifies the architecture and functions of an IPTV system that makes use of the NGN IMS architecture and its features, implementing the requirements defined in TS 181 014 [13A] and TS 181 016 [13B].

The present document has taken IPTV solutions defined by other organizations (such as DVB, ATIS IIF etc) into account. It is based on an IMS based architecture and where appropriate the aforementioned solutions are referenced.

By relying on common components the resulting architecture can coexist with other TISPAN NGN services.

2 References

References are either specific (identified by date of publication and/or edition number or version number) or non-specific.

- For a specific reference, subsequent revisions do not apply.
- Non-specific reference may be made only to a complete document or a part thereof and only in the following cases:
 - if it is accepted that it will be possible to use all future changes of the referenced document for the purposes of the referring document;
 - for informative references.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

For online referenced documents, information sufficient to identify and locate the source shall be provided. Preferably, the primary source of the referenced document should be cited, in order to ensure traceability. Furthermore, the reference should, as far as possible, remain valid for the expected life of the document. The reference shall include the method of access to the referenced document and the full network address, with the same punctuation and use of upper case and lower case letters.

NOTE: While any hyperlinks included in this clause were valid at the time of publication ETSI cannot guarantee their long term validity.

2.1 Normative references

The following referenced documents are indispensable for the application of the present document. For dated references, only the edition cited applies. For non-specific references, the latest edition of the referenced document (including any amendments) applies.

- [1] ETSI ES 282 001: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Functional Architecture".
- [2] ETSI TS 123 506: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); IP Multimedia Subsystem (IMS); Stage 2 description [3GPP TS 23.228 Release 7, modified]".
- [3] ETSI ES 282 004: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Functional Architecture; Network Attachment Sub-System (NASS)".
- [4] ETSI TS 133 220: "Universal Mobile Telecommunications System (UMTS); Generic Authentication Architecture (GAA); Generic bootstrapping architecture (3GPP TS 33.220)".
- [5] ETSI TS 187 003: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); NGN Security; Security Architecture".

- [6] ETSI TS 102 034: "Digital Video Broadcasting (DVB); Transport of MPEG-2 TS Based DVB Services over IP Based Networks".
- [7] ITU-T Recommendation P.10/G.100 "Vocabulary for performance and quality of service " - New Appendix I - Definition of Quality of Experience (QoE).
- [8] ETSI ES 282 003: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Resource and Admission Control Sub-system (RACS); Functional Architecture".
- [9] ETSI TS 183 004: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); PSTN/ISDN simulation services: Communication Diversion (CDIV); Protocol specification".
- [10] ETSI TS 182 008: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Presence Service; Architecture and functional description (Endorsement of 3GPP TS 23.141 and OMA-AD-Presence-SIMPLE-V1-0)".
- [11] ETSI ES 282 007: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); IP Multimedia Subsystem (IMS); Functional architecture".
- [12] Void.
- [13] ETSI ES 283 030: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Presence Service Capability; Protocol Specification [3GPP TS 24.141 V7.0.0, modified and OMA-TS-Presence_SIMPLE-V1_0, modified]".
- [13A] ETSI TS 181 014: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Requirements for network transport capabilities to support IPTV services".
- [13B] ETSI TS 181 016: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Service Layer Requirements to integrate NGN services and IPTV".
- [13C] ETSI TS 122 340: "Universal Mobile Telecommunications System (UMTS); IP Multimedia Subsystem (IMS) messaging; Stage 1 (3GPP TS 22.340 version 7.0.0 Release 7)".

2.2 Informative references

- [14] DSL Forum Technical Report TR-126: "Triple-play Services Quality of Experience (QoE) Requirements".
- [15] Void.
- [16] ETSI ES 282 010: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Charging management Endorsement of 3GPP TS 32.240 Release 7, 3GPP TS 32.260 Release 7, 3GPP TS 32.297 Release 7, 3GPPTS 32.298 Release 7 and 3GPP TS 32.299 Release 7, modified".
- [17] ETSI TR 182 005: "Telecommunications and Internet converged Services and Protocols for Advanced Networking (TISPAN); Organization of user data".
- [18] ETSI ES 204 915: "Open Service Access (OSA); Application Programming Interface (API); (Parlay 6.0)".
- [19] ETSI ES 202 504: " Open Service Access (OSA); Parlay X Web Services; (Parlay X 3)".
- [20] 3GPP TS 29.198: "Technical Specification Group Core Network and Terminals; Open Service Access (OSA); Application Programming Interface (API); (Release 7)".
- [21] 3GPP TS 29.199: "Technical Specification Group Core Network and Terminals; Open Service Access (OSA); Parlay X Web Services; (Release 7)".

- [22] 3GPP TS 23.002: " Technical Specification Group Services and Systems Aspects; Network Architecture; (Release 8)".
- [23] 3GPP TS 23.218: " Technical Specification Group Core Network and Terminals; IP Multimedia (IM) session handling; IM call model; Stage 2 (Release 8)".
- [24] 3GPP TR 23.810: " Technical Specification Group Services and System Aspects; Study on Architecture Impacts of Service Brokering; (Release 8)".
- [25] Toshiro Nunome; Shuji Tasaka, "An Application–Level QoS Comparison of Inter–Destination Synchronization Schemes for Continuous Media Multicasting", IEICE transactions on communications, ISSN 0916-8516, Vol. 87 (2004), No. 10, pp. 3057-3067 (11).
- [26] SCTE-130 part 1: "Advertising Systems Overview".
- [27] SCTE-130 part 2: "Core Data Elements".
- [28] SCTE-130 part 3: "Ad Management Service interface".
- [29] OMA MobAd 1.0 RD: "Mobile Advertising Requirements"
- [30] OMA MobAd 1.0 AD: "Mobile Advertising Architecture"
- [31] 3GPP TS 26.237 V8.0.0 (2008-12) "3GPP IMS based PSS and MBMS User Service; Protocols (Release 8)"

Editor's Note: a liaison statement 20bTD338 will be sent to OMA to determine the status and availability of the OMA reference documents.

Draft

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

content control: procedure for controlling content delivery (e.g. starting content delivery, playback of content (such as pause, fast and slow playback, reverse playback, rewinding, jumping forwards or backwards), stopping content delivery), and content management (e.g. digital rights management, program scheduling management, delivery management).

content delivery: procedure for delivering multimedia contents.

IPTV content identifier: superclass of the identifiers that identify content in specific IPTV services.

Editor's note: An enumeration should be provided of identifiers that classify as IPTV content identifier. A first draft of this is provided in 20bTD239r1. It was noted during TISPAN 20bis that also the PCh id is an IPTV content identifier.

IPTV service type identifier: identifies type of IPTV services.

Editor's note: An enumeration should be provided of the service types that should be identified.

media stream identifier: identifier carried in a unicast or multicast media stream that identifies that specific media stream.

offset: value indicating the elapsed time between the beginning of content and the current reading position of the reading cursor in that same streamed content

park TV: feature that would enable a user (on a UE) make an impulsive request to record ongoing BC service/programme from a particular point in time

NOTE: This recording point is also referred to as a bookmark.

park and pickup TV: feature that would enable a user (on a UE) to Park TV and subsequently Pickup TV

pickup TV: feature that would enable a user (on a UE) retrieve or request BC service/programme that was recorded and bookmarked via an impulsive record request

NOTE: The IPTV content can be retrieved from the bookmarked location or recording point on same or different UE at a later point in time.

programme: entry in the Electronic Programme Guide

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BC	BroadCast
CoD	Content on Demand
CSF	Content Security Functions
ECF	Elementary Control Function
EF	Elementary Functions
EFF	Elementary Forwarding Function
EPG	Electronic Programme Guide
GAA	Generic Authentication Architecture
GBA	Generic Bootstrapping Architecture
HD	High Definition
IGMP	Internet Group Management Protocol
IMS	IP Multimedia Subsystem
MCF	Media Control Function
MCN	Media Channel Negotiation
MDF	Media Delivery Function
MF	Media Function
MSAS	Media Synchronization Application Server
NASS	Network Attachment SubSystem
NGN	Next Generation Network
N-PVR	Network-Personal Video Recorder
PSC	Personalized Stream Composition
PVR	Personal Video Recorder
QoE	Quality of Experience
QoS	Quality Of Service
RACS	Resource and Admission Control Subsystem
SC	Synchronization Client
SCF	Service Control Function
SD	Standard Definition
SDF	Service Discovery Function
SIP	Session Initiation Protocol
SLF	Subscription Locator Function
SSF	Service Selection Function
TPF	Transport Processing Functions
UE	User Equipment
UPSF	User Profile Server Function
URI	Uniform Resource Identifier
XDMS	XML Document Management Server

4 High-level overview

Editor's Note: In Release 3, the high level overview architecture might evolve.

Editor's Note: Clarify which part of specification are mandatory and which optional (e.g. in informative annex).

Editor's Note: Clarify what are features and services supported by R2 and which are new in R3.

Editor's Note: Find the best way how to declare in R3 specs backward compatibility with R2 for IPTV specifications is FFS. When there are changes which contradict with R2 specification this should be noted explicitly.




Figure 1: High level functional architecture for IMS-based IPTV

NOTE 1: The specification of management functions and content provider functions is considered out of scope of the present document

User equipment:

UE: The IPTV enabled UE terminates the IPTV control and media signals, and displays the corresponding information to the user. The UE interaction with the user allows selection of programme, content, and service descriptions, such as content guides for broadcast and VoD services.

Application functions & IPTV service functions:

Enables operation of or provides IPTV services. This includes IPTV Service Supporting Functions.

IPTV Service Supporting Function: The IPTV Service Supporting Function defined here are those common functions which could support or be used by other IPTV service or applications.

NOTE 2: Examples of IPTV service supporting functions may be Service Discovery and Selection functions.

User Profiles:

User Profiles includes user data that are involved in providing IPTV services.

Core IMS:

It provides functionality for authentication, authorization, and signalling for the setup of the service provisioning and content delivery. It routes signalling messages to the appropriate application server or triggers the applications based on settings maintained in the UPSF. For resource reservation and admission control this function interacts with the RACS.

Transport Functions:

Transport Control: contains functions from RACS and NASS. It provides policy control, resource reservation and admission control as well as IP address provisioning, network level user authentication and access network configuration as defined in TISPAN.

Transport Processing Functions: represents network access links and IP core. The IP core is in charge of data transmission with quality of service support.

Media Delivery, Distribution and Storage:

The Media Delivery, Distribution and storage function receives and stores live feeds and media streams coming into the IPTV System from Content Providers. It is mainly in charge of media processing, delivery, storing, trans-coding and relaying. This function performs all these tasks along with the control of - or feedback to the IPTV Service and Control. Content protection may also be performed here or already protected content could be delivered over these functionalities.

-
- 5 Overview of functional entities
 - 5.1 Functional architecture for IPTV services
 - 5.1.1 Functional architecture overview

Editor's Note: In Release 3, the functional architecture might evolve.

The overall functional architecture for IPTV service is shown in figure 2.




Figure 2: Functional architecture for IPTV services

NOTE 1: Only Xc and Xd are explicitly shown as traversing the Transport Processing Functions. For the sake of simplicity other reference points are only shown as end to end.

In figure 2, the IPTV Service Control Functions, the IPTV Media Functions, the Service Selection Function (SSF) and the Service Discovery Function (SDF) fit in the context of TISPAN NGN Functional Architecture Release 2 [1].

NOTE 2: To support the regionalized delivery of content and metadata in accordance with applicable regulations, at least one of the service layer entities involved in the IPTV service should query the UE location from the NASS and enforce the regionalization.

As stated in [2], the IMS architecture shall be based on the principle that the service control for Home subscribed services for a roaming subscriber is in the Home network. This principle shall be applied also in case the IPTV solution supports roaming.

5.1.2 IPTV services

Editor's Note: Cover Release 2 and any new Release 3 IPTV services here.

Editor's Note: describe services in a less detailed, more generic way. Move procedural aspects to later part in document. Describe Impact of stage 1 definitions on the architecture on high level

5.1.2.1 General

IPTV services execution involves three functions: a service control function (SCF), a media control function (MCF) and a media delivery function (MDF).

An SCF may host the logic of one or more of the following services as defined in ETSI TS 181 016:

- Content on Demand (CoD),
- Broadcast (BC),
- Network Personal Video Recorder (N-PVR),
- Consumer Personal Video Recorder (C-PVR),
- User Generated Content (UGC),
- Content Recommendation (CR),
- Push CoD (PC)
- Advertising (Ad)
- Personalized Channel (PCh)
- Personalized Stream Composition (PSC)

Editor's note : this list needs alignment with the services described in stage 1.

The service request/response messages between the UE and the SCF are transferred via the Core IMS. Media Control messages are exchanged between the UE and the MCF via the Xc reference point. Media Data is exchanged between UE and MDF via the Xd reference point.

Editor's Note: The relation of Xc to the BC tasks should be clarified.

For UGC services, media may also be exchanged or streamed between users provided that the control of this media exchange or these media streams lies with the UGC function.

For CR services, the SCF exchanges service request/response messages with the UE directly over the Ut or via the IMS Core as appropriate.

5.1.3 Functional entities

Refer to clause 5.1.5

5.1.3A Generic Capabilities

Editor's Note: In this section we have the molecules called generic IPTV capabilities which provide list of basic IPTV capabilities provided by IPTV functional architecture and functional elements described in section 5.1.3 and used in procedures and provided IPTV services.

IPTV Generic IPTV Capabilities:

1. service discovery and selection
2. service control
3. service interaction
4. media control
5. media delivery
6. content protection
7. content management and distribution
8. interactions with other NGN services

5.1.4 Elementary functions

Editor's Note: Cover Release 2 and any new Release 3 elementary functions here.

Editor's Note: In this clause we have the atoms called elementary functions. This clause provides a list of basic tasks provided by the IPTV functional architecture and its functional elements described in section 5.1.3 used in IPTV procedures and IPTV services.

General:

1. Network attachment
2. Registration
3. Resource Management
4. Charging information

Editor's Note: The appropriate term for generating charging information is FFS and feedback from SA5 about the correct terminology is required

IPTV elementary functions:

Service related elementary functions

5. service discovery
6. service authorization
7. service selection
8. service initiation
9. service control
10. service information handling (e.g. metadata)
11. service configuration

Session related elementary functions

12. session initiation
13. session modification
14. session termination

Multimedia delivery & control related elementary functions

15. multicast based media delivery (media streaming)
16. unicast based media delivery (media streaming)
17. content download/upload (offline content transfer)
18. control of multicast based media streaming
19. control of unicast based media streaming)

20. control of content transfer by download/upload
21. content ingestion (receiving content)
22. content recording(capture of live content)
23. content storage
24. content adaptation (e.g. transcoding, mix, substitute, personalize)

Content management related elementary functions

25. content acquisition
26. content validation
27. content distribution

Content protection related elementary functions

28. content licencing
29. content key management
30. content encryption

User data management related elementary functions

31. User profile/data management
32. Accounting/right control

Editor's Note: The appropriate term for credit control is FFS – also interactions with online charging needs to be considered.

IPTV Common elementary functions:

33. Status/state (changes) detection/reporting
34. Common notification
35. Messaging
36. Presence Reporting
37. Inter-destination Media synchronization

5.1.4.1 Content security functions

Content security elementary functions are described in clause 10.2.

5.1.5 Functional Entities

Editor's Note: Cover Release 2 and any new Release 3 functional entities here.

5.1.5.1 Service Discovery and Selection Functions (SDF and SSF)

The Service Discovery Function (SDF) and Service Selection Function (SSF) are functions which provide information necessary to the UE to select an IPTV service.

Tasks of the SDF:

- Generates and/or provides the service attachment information.
- Provides personalized service discovery.

The service attachment information consists of SSF addresses in the form of URIs and/or ip-addresses.

Tasks of the SSF:

- Provides the service selection information, e.g. a list of available services that the UE can then browse and select. The SSF may optionally generate this service selection information. It may also retrieve and forward the service selection information.
 - Provides personalized service selection information and/or information needed to personalize the service selection. This must be delivered via unicast mode. (See note 1 regarding multicast options.)
 - Provides non-personalized service selection data. This can be delivered via multicast or unicast mode.
- Optionally provides service selection presentation information. This presentation information may be personalized when it is delivered over unicast mode. Optionally receives selection request from UE, e.g. an N-PVR content capture request as described in clause 8.5.

NOTE 1: The way the service selection information might be personalized when it is delivered via multicast mode is out of scope for this release. However, specified below is a non exhaustive list of high-level options to achieve such personalization:

- Using the SDF: when processing a request from a particular user/UE, the SDF could redirect the user/UE to specific multicast addresses/SSFs corresponding to the category to which the user belongs. This would imply that users/UEs are classified into specific categories.
- Using the SCF: UE could fetch IPTV user profile information in the form of BC Service ID listings from the SCF. This may be encoded as XML document(s) via the Ut reference point using XCAP-like mechanism or as HTML document with possibly embedded scripts to filter this service selection data. This IPTV user profile information may then be used to locally filter the service selection data that was previously delivered via multicast mode.

NOTE 2: EPG is defined in TS 181 016 [13B].

For each IPTV service, the following data is provided:

- An identifier associated to the IPTV service: this identifier is used by service control functions and media functions to identify the requested content when processing service initiation requests. In case of a CoD service, the identifier identifies exactly one content item. In case of a BC service, the BC identifier, which is the Service Package Id related to BC profile defined in clause 7.3, identifies a set of channels among which the user can switch.
- Optionally the set of network parameters that may be required by the UE to activate a service (e.g. the extra information that may be needed by the UE to establish content delivery channels and content control channels).
- User readable data related to the IPTV service.

5.1.5.2 IPTV Service Control Functions (SCF)

Tasks of SCF:

- Service authorization during session initiation and session modification, which includes checking IPTV users' profiles in order to allow or deny access to the service.

- Credit limit and credit control (using the on-line charging systems ES 282 010 [16])

In addition, the SCF performs the following tasks depending on type of service supported

- Select the relevant IPTV media functions (see clause 5.2).
- Send relevant notifications to the MF, e.g. for content recommendation service
- For Push CoD Services, initiate media content (e.g. recorded BC program, CoD content) download to UE
- Select appropriate ad content for specific user or user group, based on user profile (e.g. user preference, shopping habits, location information, etc.) and IPTV service status (e.g. current BC program ID, commercial break in BC service or pause during CoD content playback).
- Communicate with an external advertising sub-system in order to make ad-selection and ad-placement decisions if one exists (see Annex E, F).
- Send ad insertion indication to MF.
- Instruct the UE to perform trick play commands, e.g. pause a TV channel, CoD or N-PVR stream.
- Initiate BC and/or CoD session to UE for immediate consumption.
- Generate playlist information and communicate it to the MF.
- For Content Recommendation Services, detect CRS event and generate CRS information for specific user or user group, based on user profile (e.g. user preference).
- Detect an event, based on some criteria, trigger relevant internal service logic and send a notification to the UE or other applications associated with the specific user.
- Optionally, for PVR service, initiate the recording of content, e.g. for CPVR service, initiates a notification request to UE to start recording.
- For restricted trick play, acquire restriction policy and transmit to relevant MF.

The SCF is a SIP Application Server (AS).

An IPTV SCF belonging to an IMS network managed by another provider shall not have direct access to user profile data in the UPSF via the Sh reference point; it may however have access to user profile data by other means (e.g. Rg reference point to GUP), depending on the NGN operator's implementation and capabilities.

The SCF may use the IPTV profile in order to customize the user experience. For instance, the list of subscribed BC TV Services could be used to filter the information sent to the UE. The User Equipment communicates with the IPTV Service Control Functions via the Core IMS for the purpose of session management, and may be using the Ut reference point for the purpose of service profile configuration. In the latter case, an authentication proxy may sit between the User Equipment and the SCF.

5.1.5.3 IPTV Media Control and Delivery Functions (MCF and MDF)

IPTV Media Functions are in charge of controlling and delivering the media flows to the UE. They are split into Media Control Functions (MCF) and Media Delivery Functions (MDF).

Tasks of Media Control Function (MCF):

- Handling media flow control of MDF.
- May manage the media processing of MDF.
- Monitoring the status of MDF.
- Managing interaction with the UE (e.g. trick mode commands).
- Handling interaction with the IPTV service control function SCF.

- Keeping an accurate view on status and content distribution related to the different MDFs that it controls.
- Selecting an MDF, in the case an MCF controls multiple MDFs different criteria, may be applicable (as described e.g. for CoD in clause 5.2).
- Selecting MF, return the selection result to SCF and Redirect sessions to the selected MF (e.g. in case the requested content is not available on this MF or for load balancing among MFs).
- Generate charging information, e.g. for end-user charging based on the viewed content.
- Handle ad insertion control of MDF, i.e. control the fetching of the ad content and synchronization between ad content and IPTV content, including accounting for delay or drift in broadcast TV schedules.
- In case of live User Generated Content consumption (TS 181 016 [13B], clause A.13), there is a direct relationship on the media delivery and media control levels between downstreaming and upstreaming UGC sessions, which both terminate at the MCF. The MCF ensures that session descriptions of the downstreaming and upstreaming UGC sessions match. UE's subscribed to the particular Live UGC are notified when this Live UGC starts.

Editor's note: UGC-related SCF tasks are for further study, e.g. identification of UGC content and MCF/MDF selection in case of MDF specialisation.

Tasks of MDF:

- Handling media flows delivery (for delivering multimedia services to user).
- Status reporting to MCF (e.g. reporting on established IPTV media streams).
- Store of media (e.g. CoD assets) and may also store some service information stored with media for IPTV services.
- In particular, it may be used for storage for the most frequently accessed content or user specific content (e.g. recording PVR, Time-shift TV, BC service with Trick mode, user generated content) if the same tasks are not performed by UE.
- May additionally process, encode or transcode (if required) media to different required media formats (e.g. TV resolution depending on terminals capabilities or user preferences).
- May perform content protection functionalities (e.g. content encryption).
- May support content ingestion of IPTV media.

Editor's note: Whether content ingressed to MDF should be in a suitable format for delivery to UE (thus avoiding transcoding) or whether to use transcoding as a preferred option is FFS.

- MDF may act as source for multicast streams of IPTV services e.g. BC or UGC media streams.
- For UGC services, receiving content from UE through an upstreaming/upload media channel .
- May collect QoE reports (e.g. from UE using Xd).
- For Push CoD Services, handling content download (download CoD content to UE or record BC live stream and then download to UE)
- Perform ad insertion during IPTV content playback, i.e. deliver ad content to the UE during the ad insertion time, either exclusively or in parallel with the IPTV content.
- Recognize appropriate in-band /out-of-band Ad insertion indicators (eg-cue messages as defined in ITU-T J.181), when present. These Ad insertion indicators define positions within the IPTV content where advertisement content can be inserted /replaced. This task may be done by coordination with an external advertising sub-system.

Editor's note: A more generic term for "Ad insertion indicators" (eg: Ad insertion locations/points) needs to be considered. An alignment of the text with the generic term would be required.

- For personalized stream composition, the MDF may support alternative streams for use with an existing broadcast channel or CoD item, e.g. alternative video, audio or subtitle tracks.

NOTE: To enhance QoE evaluation quality, QoE reports may additionally be collected from other sources than the UE. However, this is beyond the scope of the present document.

To support QoE, the UE may send QoE reports via Xd concerning the quality of the IPTV Media Data received.

Each IPTV Service Control Function uses the ISC reference point to communicate with the NGN Core IMS. As stated in TS 123 506 [2], an Application Server may originate requests to a destination without involving the S-CSCF. This capability should be used in case the SCF is to communicate with the media function without involving the core-IMS.

Each corresponding IPTV Media Function communicates with the UE over Xc and Xd for Media Control and Media Delivery. For each service, the corresponding Media Control entities communicate with the UE on the Xc reference point and control the appropriate Media Data Delivery entities which send the Media Data to the UE on the Xd reference point.

5.1.5.4 UPSF

The UPSF holds the IMS user profile and possibly IPTV specific profile data (see clause 7). It communicates with IPTV Service Control Functions at the Sh reference points and with the Core IMS at the Cx reference point as defined in ES 282 007 [11]. When multiple instances of a UPSF exist, the Core IMS and the IPTV Service Control Functions may use the services of a Subscription Locator Function (SLF) to fetch the address of the UPSF. The SLF communicates with IPTV Service Control Functions at the Dh reference points and with the Core IMS at the Dx reference point as defined in ES 282 007 [11]. For the sake of simplicity the SLF and associated reference points are not shown on figure 2.

NOTE: The IMS principle procedures, such as security, authentication process, are also considered to be applied to this IPTV functional architecture and the procedures, unless explicitly stated otherwise.

5.1.5.5 Transport processing functions

IPTV services make use of generic transport processing functions defined in ES 282 001 [1].

5.2 Interactions between Service Control function and Media Functions

Editor's note: the applicability of this clause needs to be clarified.

The relationship between CoD Service Control Function (SCF) and CoD Media Function (MF), composed of Media Control Function and Media Delivery Function, is shown in figure 3.




Figure 3: Relationship between Service Control Function and Media Functions

The specific MF for a particular session will be determined during the session initiation and resource allocation procedure. This determination may be based on the following criteria:

- Location of the UE.
- Status information of all the available media functions (e.g. online or offline, media processing capability, available resources in the different -MF holding the same contents, etc.).
- Load of the different MF holding the same contents.
- Content identity of the requested content; It is recommended that the structure of the content identifiers be designed so as to facilitate this selection, without requiring parsing the full identifier.

The selection process relies on elementary functions that can be hosted in an SCF and/or an MCF. In the latter case the MCF may act as a redirect server to redirect sessions to another MCF. And in some cases, the selection task of SCF and/or MCF may become very simple. For e.g., if a Request-URI for service/content identifier corresponds to just one MCF, then SCF and/or MCF may just transfer the session to the unique MCF.

NOTE 1: The location of the selection process in a separate entity is out of scope for this release.

NOTE 2: Admission control procedures for use of transport resources at the CoD-MF side are out of scope for this release.

The SCF shall contact the MCF during the session initiation and resource allocation phase. The SCF may contact several MCFs before its determination. The SCF contacts the MCF via the Core IMS as shown in figure 4.




Figure 4: Reference points between SCF and MCF

When the MCF is contacted, it shall respond with the parameters offer for the session corresponding to the content required by the UE..

The MCF controls one or several MDFs. Tasks of the MCF are the following:

- Select an MDF.
- Control the media stream resources in the MDFs.
- Interpret information coming from the SCF and control the MDFs accordingly.
- Generate of CDRs.

Selection of the MDF by the MCF uses similar criteria to the selection of a MCF by a SCF. And in some cases, the selection task of MCF may become very simple. For e.g., if a Request-URI for service/content identifier corresponds to just one MDF, then MCF may just transfer the session to the unique MDF. After the MCF has selected a MDF for service, it may communicate with the MDF. If the MDF is not functional for some reason, the MCF may detect this exception, for example, by a local response timeout, and select another MDF with the requested content. If there is no other MDF with the requested content under the MCF's control, it should redirect the service request to another MCF or return an appropriate error message to the SCF.

5.3 Void

5.4 Inter-destination media synchronization

Inter-destination media synchronization is an optional generic capability, aimed at servicing requiring this capability, see TS 181 016 [13B], Annex A.9.6 for examples. The Media Synchronization Application Server (MSAS) and Synchronization Client (SC) are functions that provide inter-destination media synchronization. These functions are used for synchronization sensitive services for which IPTV delays and delay differences may spoil the quality of experience. The functional entities and reference point of the synchronization mechanism are shown in figure 4A.




Figure 4A: Functional entities and reference points for inter-destination media synchronization.

5.4.1 Functional entities MSAS and SC

The inter-destination synchronization mechanism uses the concept of synchronization sessions. Each synchronization session involves a Media Synchronization Application Server (MSAS) and multiple Synchronization Clients (SC). A synchronization session is used for the inter-destination synchronization of a BC channel by exchanging synchronization status information and synchronization settings instructions.

- Synchronization status information: timing information on media reception at each SC.
- Synchronization settings instruction: instruction how much an SC should delay the BC channel.

Editor's note: The use of inter-destination synchronization for CoD and other IPTV services is for further study.

Tasks of the SC:

- Setting up and accepting synchronization sessions with/from the MSAS.
- Sending synchronization status information to the MSAS.
- Receiving synchronization settings instructions from the MSAS.
- Delaying a BC channel according to the received synchronization settings instruction.

Tasks of the MSAS:

- Setting up and accepting synchronization sessions with/from SCs
- Collecting synchronization status information from SCs.
- Calculating synchronization settings instructions for the SCs
- Distributing synchronization settings instructions to SCs.

NOTE: Examples of algorithms to calculate the synchronization settings instructions from collected synchronization status information may be found in [25].

5.4.2 Mapping onto the IPTV architecture

The synchronization architecture can be mapped onto the IPTV architecture in the following ways.

Mapping 1: SC in UE.

- The MSAS is an elementary function of the SCF.
- The SC is an elementary function of the UE.
- The Sync reference point is tunnelled over the Gm and ISC reference points.
- Each synchronization session is associated with a BC session.

Mapping 2: SC in Transport

- The MSAS is an elementary function of the SCF or a stand-alone Application Server.
- The SC is an elementary function of the Transport Functions.

NOTE 1: Mapping 1 is aimed at small-scale deployments of services that require media synchronization and only a limited number of UEs uses media synchronization. It reuses existing IPTV sessions. Mapping 2 is aimed at large-scale deployment of media synchronization.

NOTE 2: In mapping 2, the SC is an adjunct function that may be co-resident with any of the appropriate elements in the transport layer.

5.4.3 Modification and re-origination of media streams

In addition to inter-destination media synchronization, additional synchronisation measures are needed in case a media stream is modified or re-originated during transport. Examples of these are transcoding, HD-to-SD conversion and user-generated comments to a live broadcast. In such cases, additional media-stream-modifying Synchronisation Clients (SC') are placed at the functional entities where media streams are modified, see Figure 4B. The Sync' reference point is used to exchange convey synchronization status correlation information between from the media-stream-modifying SC' and to the MSAS on the synchronicity relationship between incoming and outgoing media streams.

- Synchronization correlation information: timing information on the synchronicity relationship between incoming and outgoing media streams at an SC'.




Figure 4B: Media synchronization in case of media stream modification.

6 Reference points

Editor's Note: New Reference points may be needed in Release 3, depending on section 5.

6.1 UE - SSF (Xa)

This reference point between UE and SSF is used by the UE to make appropriate service selections.

6.2 UE - IPTV Service Control Functions (Ut)

This reference point between UE and IPTV Service Control Functions is used by the UE for the purpose of service profile configuration.

Use of the Ut reference point conforms to ES 282 007 [11].

6.3 UE - Core IMS (Gm)

Use of the Gm reference point conforms to ES 282 007 [11].

6.4 UE - Media Control Functions (Xc)

This Xc reference point (for media control) is a logical end-to-end reference point between the UE and the IPTV Media Control Function that is used to exchange media control messages for controlling the IPTV Media flow.

NOTE: transport related reference points are used to carry media control messages over underlying transport segment (defined in ES 282 001 [1]) and as shown below in figure 5 depending on the location of the MCF. The Dj reference point between the UE and the access network, the Di reference point between the access network and the core network, and possibly the Ds or Iz reference point between the core network and the Media Control Function if the MCF is located after the Core Network.




Figure 5: Decomposition of the Xc reference point when the MCF is after the core network

6.5 UE - Media Delivery Functions (Xd)

This Xd reference point (for media delivery) is a logical end-to-end reference point between the UE and the IPTV Media Delivery Function that is used to deliver media data.

NOTE: transport related reference points are used to carry media delivery data over underlying transport segment (defined in ES 282 001 [

)] and as shown below in figure 6 depending on the location of the MDF. The Dj reference point between the UE and the access network, the Di reference point between the access network and the core network, and possibly the Ds or Iz reference point between the core network and the Media Delivery Function if the MDF is located after the Core Network.




Figure 6: Decomposition of the Xd reference point

If the IPTV system architecture supports QoS and/or QoE [7] and [14], this reference point may carry QoS and/or QoE reports from the UE to the MDF. These reports relate to the quality of the IPTV Media Data that the UE receives.

6.6 IPTV Service Control Functions (SCF) - UPSF (Sh)

Use of the Sh reference point conforms to ES 282 007 [11].

6.7 Core IMS - UPSF (Cx)

Use of the Cx reference point conforms to ES 282 007 [11].

6.8 Core IMS - IPTV Service Control Functions (ISC)

Use of the ISC reference point conforms to ES 282 007 [11].

6.9 Core IMS - IPTV Media Functions (y2)

This reference point between S-CSCF and IPTV Media Control Function (MCF) carries IPTV Service Control Signalling originating from the IPTV Service Control Function (SCF) to control the MCF.

In case the CSCF and the Media Control Function are in different administrative domains, signalling flows go through an IBCF.

NOTE: As stated in TS 123 506 [2], an Application Server may originate requests to a destination without involving the S-CSCF. This capability should be used in case the SCF is to communicate with the media function without involving the core-IMS, thus omitting y2.

6.10 Core IMS - SDF (ISC)

Use of the ISC reference point conforms to ES 282 007 [11].

6.11 SDF - UPSF (Sh)

Use of the Sh reference point conforms to ES 282 007 [11].

6.12 Void

Void.

6.13 Application Functions - NASS (e2)

Use of the e2 reference point conforms to ES 282 007 [11] and ES 282 004 [3].

NOTE: Application Function entities associated to IPTV services such as core IMS and SCF may query the UE location from the CLF in order to fulfil their tasks.

6.14 Core IMS - RACS (Gq')

Use of the Gq' reference point conforms to ES 282 007 [11] and ES 282 003 [8].

6.15 NASS - RACS (e4)

Use of the e4 reference point conforms to ES 282 003 [8] and ES 282 004 [3].

6.16 IPTV Service Control Functions - SLF (Dh)

Use of the Dh reference point conforms to ES 282 007 [11].

6.17 Core IMS - SLF (Dx)

Use of the Dx reference point conforms to ES 282 007 [11].

6.18 IPTV Media Control Function - IPTV Media Delivery Function (Xp)

This Xp reference point between the Media Control Function (MCF) and Media Delivery Function is used to control media delivery sessions to support media delivery session setup when content is distributed across one and more media delivery functions.

6.19 MSAS-SC reference point (Sync)

This optional reference point is between Media Synchronization Application Server (MSAS) and media-stream-synchronizing Synchronization Client (SC). It is used to set up synchronization sessions and to exchange synchronization status information and synchronization settings instructions with functional entities in the network where media streams are mutually synchronized. The Sync reference point is a logical reference point in Mapping 1 from clause 5.4.2, where it is tunnelled over the Gm and ISC reference points.

6.20 MSAS-SC' reference point (Sync')

This optional reference point is between Media Synchronization Application Server (MSAS) and media-stream-modifying Synchronization Client (SC'). It is used to set up synchronization sessions and to exchange synchronization status information with functional entities in the network where to-be-synchronized media streams are modified.

7 User data

Editor's Note: Evolution of User data specification may be needed in Release 3, depending on new IPTV services in this Release.

7.1 Classification of information

Four categories of user data are involved in providing IPTV services:

- IMS-profile: This category includes all information required to establish IMS sessions and access IPTV services hosted in Application Servers, as described in TR 182 005 [17].

- Communication Services profile: This category encompasses all information associated to communication services (e.g. PSTN/ISDN simulation services, presence services, messaging services...) as defined in relevant ETSI TISPAN standards (e.g. TS 183 004 [9]). This type of information is required in support of combinational services (e.g. Caller Id on TV Screen).
- IPTV user profile: This category encompasses all information required to operate an IPTV service. This includes all the user settings regarding:
 - Global settings (Language preference, etc.).
 - Broadcast settings.
 - List of subscribed BC service packages. A BC service package is a set of elementary BC TV services, along with a description. These BC services have the same authorization and charging policy. A BC IPTV service is for instance a multicast channel, interactive channel, mosaic that a user may subscribe to.

NOTE: The Broadcast settings only provide a reference to service package and/or associated services that a given IPTV user has subscribed to and is not meant to be a complete description of the service package and/or service. The complete service package and/or service description is available in an associated IPTV Service Profile definition (e.g. described with metadata) . If the list of elementary IPTV services associated with a given service package are not explicitly listed in the IPTV user profile, then it implies that the IPTV user has implicitly subscribed to all of the IPTV services within that service package.

- IPTV User profile information may be used for providing a listing of recommended content to the user based on the user's profile settings
- Content on demand settings (Parental control level, etc.).
- PVR settings (PVR preferences network/local, PVR user restrictions, PVR storage limit).
- UE Settings which includes information related to the capabilities of the UE(s) that an IPTV user is associated with. An IPTV user may be associated with one or more UE(s) and every UE is uniquely identified with a unique UE Identifier (UE ID). The UE capabilities associated with an IPTV user profile may be used for customization of IPTV service selection data that is provided by the SSF to the IPTV user (based on capabilities of the UE that the IPTV user is currently associated with). For instance, an IPTV user on a SD-only device would not be provided with information related to HD services.
- The UE settings is not intended to cover all information related to the UE and currently holds only the UE capabilities attribute since this information may be used by the SSF for personalized service selection. Note that detailed information about the UE may be located elsewhere and can be referenced by the IPTV user profile using the UE ID parameter.
- Further details are provided in clause 7.3.
- IPTV service action data: this category encompasses information related to the actions the user may have taken while accessing services such as BC or CoD (e.g. ordering a CoD - Choosing to pause while viewing a live event). Those data are required to enable IPTV session portability for the user. This category also comprises IPTV service state information (e.g. current BC program ID, commercial break in BC service, pause during CoD playback, list of CoDs and associated status, record status of recordings, trick play events).

Editor's Note: Contributions are invited to extend the data model for IPTV service action data with IPTV service state information

Editor's Note: Privacy issues related to the use of this data have to be considered.

Editor's Note: Potential conflicts between IPTV Service State information obtained from SAD and retrieved using the Presence-based mechanism in 9.1.2. are for FFS.

- They include:
 - The list of CoDs that the user has ordered and associated status, CodOffset which is offset in the content where the user has paused and CodOffsetExpiryTime which is expiration time associated with the CodOffset value.

- The list of BC TV services (or programmes) that the user has paused (and is hence likely to resume later) including the bookmark value associated with the paused BC TV service or Programme and BookMarkExpiryTime which is expiration time associated with the bookmark value.
- The list of N-PVR and C-PVR contents that the user has asked to be recorded . This would include the following parameters:
 - PVRContentId: For N-PVR, it refers to a content identifier used by the UE to activate an N-PVR session related to the NPVR content. For C-PVR, it is the identifier of the C-PVR content.

NOTE: For C-PVR, the PVRContentId can be used as the recorded content index.

NOTE: In the case when a specific programme has been requested to be recorded, this ID would be the same as ProgrammeID, and the RecordStartDate and RecordEndDate attributes would be optional.

- BCServiceId: the identifier of the BC service that is to be recorded.
 - TargetUserId: for C-PVR, identifies the destination user ID that SCF initiates a notification request to trigger the -PVR record session initiation.
 - (Optionally) RecordStartDate: the start date (and time) of the recording.
 - (Optionally) RecordEndDate: the end date (and time) of the recording.
 - (Optionally) RecordDescription : a description of the recording made by the user when he/she requested to record the live content.
 - RecordStatus: the status of such a recording (requested - scheduled - available - failed).
 - RecordOffset : For N-PVR, the offset in the NPVR content where the user might have paused while actually watching it.
 - RecordOffsetExpiryTime: For N-PVR, expiration time associated with the RecordOffset.
 - RecordExpiryTime : the expiration time associated with the recording value.
- A Boolean flag, user action recordable, may be associated with IPTV user profile information to indicate if the user wishes to have the service persist such data or not. Further details are provided in clause 7.3.1.6
 - The relationships between the IMS profile and the dedicated IPTV user data categories are as follows:
 - IPTV user profile: This profile is associated with an IMS Public user Identity (IMPU). This would enable for instance enforcement of parental control on a per-user basis independent of the device they are using.
 - IPTV service action data: This profile is associated with an IMS Public user Identity (IMPU). This would enable for instance "follow me TV/video" kind of scenarios wherein users can resume the viewing of content on any device that they are authorized to use .

7.2 Location and access to user data

Editor's Note: Distribution, synchronization and handling of user data across multiple FEs as well as multiple FEs accessing that data may need further clarification/investigation. This may require involvement of WG8

7.2.1 Data management functions

IMS-profile information is managed by the UPSF. Communication Services profile information may be managed by dedicated database functions, the Application Server functions hosting the communication services, or by the UPSF as transparent data (repository function) associated to these Application Server functions. In the first and second case the Application Server function or the stand-alone server may exhibit the behaviour of an XDMS.

IPTV user profile information should be located in the following locations:

- Application Server functions hosting the IPTV applications.

- In a stand-alone server associated with one or more Application Server functions.
- In the UPSF as transparent data associated to these Application Server functions.

The first and second options are recommended for data to be accessed by 3rd party application server functions. In the first and second case the Application Server function or the stand-alone server may exhibit the behaviour of an XDMS.

IPTV service action data needs to be persistent across IPTV sessions, and should be located in the network. They may be located in one of the following locations

- The Application Server functions hosting the IPTV applications.
- A stand-alone server associated with one or more Application Server functions.
- In the UPSF as transparent data associated to these Application Server functions.

In the first and second case the Application Server function or the stand-alone server may exhibit the behaviour of an XDMS.

7.2.2 Access from other application servers

User data stored in the UPSF can be accessed by Application Servers at the Sh reference point.

Direct access to user data stored in Application Servers is outside the scope of the present document. However, part of these data may be indirectly exposed through Web Services and/or SIP Event packages.

7.2.3 Access from User Equipment (UE)

A subset of IPTV user-profile information may be accessed from the User Equipment at the Ut reference point.

7.2.4 Access from the SSF

For the purpose of personalized service selection, the SSF may need to access user data.

In the case when such user data is stored in the UPSF, it can be accessed by the SSF at the Sh reference point when the SSF is in the same domain.

On the contrary, when such user data is stored in the AS or in a stand alone server associated with one or more application servers or if the SSF is not in the same domain as the UPSF, the user data can be accessed by the SSF using an reference point that is out of scope for this release.

The SSF may also request notification of IPTV user data updates.

7.3 IPTV user profile structure

7.3.1 IPTV user profile structure

An IPTV user profile comprises:

- zero, one or more instances of the UE object class comprising UE capabilities attribute and associated UE ID;
- at least one instance of a Broadcast (BC) or a Content on Demand (CoD) object class (see figure 7);
- zero or one instance of the Global settings object class;
- zero or one instance of the Personal Video Recorder (PVR) object class;
- zero, one or multiple instances of Personalized Channel profile (PCh Profile) object class.
- zero or one instance of the Content Recommendation settings (CR) object class

A Broadcast profile comprises one or more BC Service package descriptions.

A PCh profile comprises one or more PCh itemlist descriptions, which contain the mapping of each PCh content item to the world clock the individual PCh IDs as well as the expiry time of each PCh list.

Each BC service package comprises zero or more BC TV Services descriptions.

Each PCh list comprises one or more PCh items descriptions

Each BC TV service includes a quality definition level (e.g. standard or high definition or other defined quality level). Delivered quality level depends on this quality definition level as well as UE capabilities, available codecs and/or bandwidth limitations.

NOTE: When there is no service description for a given BC service package, it would imply that the IPTV user has access to all of the BC services within that given BC service package.

The complete service package and/or service description is available in an associated IPTV Service Profile definition (e.g. described with metadata). The ServicePackageId attribute associated with the service package and/or the ServiceId attribute associated with the service refers to appropriate descriptions in an associated IPTV Service Profile definition (e.g. described with metadata) and hence, can be used to fetch detailed information about the particular service package and associated services.

A CoD profile includes a parental control level (ParentalControlLevel) attribute.

A BC profile includes a parental control level (ParentalControlLevel) attribute.

An PVR profile contains PVR rules for the user.

A Global Setting profile includes zero or one Parental Control description, which contains attributes related to parental control.

The CR Settings includes a CR notification attributes.

Draft




Figure 7: IPTV user profile data model

This data model assumes that each IPTV user is allocated at least an IMS Public User Identity and an IPTV user profile is associated with this IMS Public User Identity.

Multiple IPTV users may share the same IMS subscription.

The IPTV user identity (i.e. the IMS Public User Identity) selected when making an outgoing request is asserted by the UE using means outside the scope of the present document (e.g. using a local pin code).

7.3.1.1 BC service package

A service package is a group of one or more BC service.

7.3.1.2 BC service

A service relates to a particular TV channel and associated quality definition (e.g. SD or HD).

7.3.1.3 UE

Contains the UE's Id and its capabilities.

7.3.1.4 Global settings: language preference

This attribute defines which default language the user would like to use. For instance, this could be the default language for the GUI that is displayed on the UE, and/or the default language used for subtitles.

7.3.1.5 Global settings: user action recordable

The "user actions recordable" parameter indicates whether user actions can be recorded by the network as part of the IPTV service action data.

7.3.1.5A Global settings: PC-CostLimit

This parameter defines the cost limit of an individual content when toll content (e.g. PPV content) is involved. It has a string value.

7.3.1.5B Global settings: PC-TotalCostLimit

This parameter defines the cost limit on all IPTV content over a period of time. It has a string value.

This parameter may be defined on the basis of day, week, month or year.

There can be several occurrences of this parameter.

7.3.1.5C Global settings: PC-ClassificationRestriction

This parameter defines the classifications of the content (e.g. news, action movies, parental rating ...) which are not allowed, in case of Parental Control. It has an enumerated value.

7.3.1.5D Global settings: PC-TimePeriodRestriction

This parameter defines time period of the day, in case of Parental Control, during which all IPTV services are restricted. It has a time segment value, which includes a start time and a time length.

There can be several occurrences of this parameter.

7.3.1.5E Global settings: PC-TotalPlayTimeLimit

This parameter defines the total play time which can be consumed for IPTV services, in case of Parental Control. It has a string value.

This parameter may be defined on the basis of day or week.

7.3.1.5F Global settings: PC-AdminUser

The "PC-AdminUser" parameter defines a list of administrative users (identified by a SIP-URI) that have access to the user's profile and can modify it.

Editor's note: the impact of this parameter on the rights of the user to modify his/her own IPTV profile has to be considered

7.3.1.5G Global settings: dynamic PC-activation

The "dynamic PC-activation" parameter indicates whether dynamic parental control is activated or not. If activated, any session initiation request that does not suit the parental-control rules well, will trigger a request to the contact defined in the "PC-Contact" parameter.

7.3.1.5H Global settings: PC-Contact

The "PC-Contact" parameter indicates a list of users (SIP URI or mobile phone number) to be contacted at session initiation request if dynamic PC-activation is on.

Note: parental control related parameters in Global Settings object class can be optionally and dynamically configured according to user strategy.

Editor's note: further filters about Parental Control can be included.

7.3.1.6 N-PVR storage-limit

This attribute defines a limit allocated per user for N-PVR contents.

It can be expressed in time or volume.

There can be several occurrences of this parameter.

7.3.1.6A PVR: IPTVContentMarkerAuthorizedViewUser

The "IPTVContentMarkerAuthorizedViewUser" parameter indicates a list of users authorized to view PVR IPTV Content Markers of this user. The data model of IPTV Content Markers is defined in clause 7.5.

7.3.1.6B PVR: IPTVContentMarkerSourceUser

The "IPTVContentMarkerSourceUser" parameter indicates a list of other users from which PVR IPTV Content Markers can be accessed. The data model of IPTV Content Markers is defined in clause 7.5.

NOTE: The authorization to access a user's IPTV Content Markers does not imply access rights to the content. Separate acquisition of these rights might be necessary.

7.3.1.6C PVR: AuthorizedControlUser

The "AuthorizedControlUser" parameter indicates a list of users authorized to initiate the PVR capture request on behalf of this user.

7.3.1.7 BC: ParentalControlLevel

This parameter defines the Parental Control Level of the BC services. It has an enumerated value.

Editor's note: whether ParentalContentLevel parameters within the COD profile and the BC profile can be moved to the ParentalControl global settings profile needs to be considered.

7.3.1.7A BC: IPTVContentMarkerAuthorizedViewUser

The "IPTVContentMarkerAuthorizedViewUser" parameter indicates a list of users authorized to view BC IPTV Content Markers of this user. The data model of IPTV Content Markers is defined in clause 7.5.

7.3.1.7B BC: IPTVContentMarkerSourceUser

The "IPTVContentMarkerSourceUser" parameter indicates a list of other users from which BC IPTV Content Markers can be accessed. The data model of IPTV Content Markers is defined in clause 7.5.

NOTE: The authorization to access a user's IPTV Content Markers does not imply access rights to the content. Separate acquisition of these rights might be necessary.

7.3.1.8 CoD: IPTVContentMarkerAuthorizedViewUser

The "IPTVContentMarkerAuthorizedViewUser" parameter indicates a list of users authorized to view CoD IPTV Content Markers of this user. The data model of IPTV Content Markers is defined in clause 7.5.

7.3.1.9 CoD: IPTVContentMarkerSourceUser

The "IPTVContentMarkerSourceUser" parameter indicates a list of other users from which CoD IPTV Content Markers can be accessed. The data model of IPTV Content Markers is defined in clause 7.5.

NOTE: The authorization to access a user's IPTV Content Markers does not imply access rights to the content. Separate acquisition of these rights might be necessary.

7.3.1.10 PCh: PChId

This attribute contains the unique identifier of the PCh list. It has a string value.

7.3.1.11 PCh: PChExpiryTime

This attribute defines the expiry time of the PCh list. It has a timestamp value.

7.3.1.12 PCh: PChItemServiceType

This attribute defines the service type of the item within a PCh list. It has an enumerated value and refers to BC, CoD or N-PVR.

7.3.1.13 PCh: PChItemContentId

This attribute defines the referenced content id of the item within a PCh list:

- In case of BC, it shall consist of the “BCServiceId” as well as the “ProgrammId” (see clause 7.4.1)
- In case of CoD, it shall be set to the “CoDId” (see clause 7.4.1)
- In case of N-PVR, it shall be set to the “NPVRContentId” (see clause 7.4.1)

7.3.1.14 PCh: PChItemStartTime

This attribute indicates the start time of playing a content item within a PCh list. It has a timestamp value.

7.3.1.15 PCh: PChItemEndTime

This attribute indicates the end time of playing a content item within a PCh list. It has a timestamp value.

7.3.1.16 PCh: PChItemOffset

This optional attribute indicates the offset from beginning of the content item in case the item is CoD or N-PVR., from which the item is ready to play. It has a timestamp value. If this attribute is not present, the item shall be played from the beginning.

NOTE: The availability of PCh information should be guaranteed by mechanisms aligned with user profile and content metadata validity rules.

7.3.1.17 CR Settings: CR notifications

Activate, deactivate content recommendation notifications, or other actions for further study.

7.3.2 Usage of IPTV user profile

The IPTV user profile may be used to customize the user IPTV experience.

For instance:

- The CoD profile parental control level should be used to filter a CoD catalog.
- The UE capabilities associated with an IPTV user profile UE data may be used for customization of IPTV service selection data that is provided by the SSF to the IPTV user (based on capabilities of the UE that the IPTV user is currently associated with).

Thanks to the IPTV user profile standardization, any equipment can render the same IPTV environment to the user. The IPTV user profile may also be used to allow or deny access to IPTV services.

7.3.3 Life cycle

UE List: The information about the UE(s) that an IPTV user is currently associated with may be purged when the IPTV user deregisters and/or logs off. This is to avoid persisting UE related information when the IPTV user logs off that particular UE.

7.4 IPTV service action data

7.4.1 Data model




Figure 8: IPTV Service action data - data model

This data model assumes that each IPTV user is allocated at least an IMS Public User Identity and an IPTV Service Action data profile is associated with this IMS Public User Identity.

NOTE 1: The "ProgrammeId" attribute is unique, as it refers to one and only one entry in the EPG.

NOTE 2: Although the "Bookmark" attribute could be used as an indirect way to identify the programme, it is seen as more convenient and immediate to use the ProgrammeId for that purpose.

7.4.2 Life cycle

- CoD list: Items may be removed when they are no longer accessible (e.g. the offer they were attached to has expired.) or when the entitled number of visualizations has been reached. Alternatively, items are purged when the expiration time associated with the CoDOffset (identified using CoDOffsetExpiryTime) expires.
- BC bookmarks are kept in the profile while the BC TV service or Programme they refer to is available in the media server. Alternatively, entries may also be purged when the expiration time associated with BookMark value (identified using BookmarkExpiryTime) expires.
- N-PVR items are kept in the profile while the content they refer to is available in the Network PVR server(s). Alternatively, entries may also be purged when the expiration time associated with Recording value (identified using RecordExpiryTime) expires. Failed recordings may be purged on a regular configurable basis.

7.5 IPTV information storing/sharing services

7.5.1 General

This clause defines data models to be used by IPTV information sharing or targeting services.

Editor's Note: Commonalities of data models between different IPTV information sharing services should be exploited.

NOTE: Accessibility, as well as the legal use of data related to sharing or targeted services should be considered.

7.5.2 IPTV Content Marker

7.5.2.1 General

This clause defines the data model of IPTV Content Markers for BC/CoD/N-PVR services. The intention of IPTV Content Markers is twofold:

- 1) To store configurable pointers to content and be able to quickly access that content
- 2) Enable users to exchange and share IPTV Content Markers.

NOTE: Exchanging IPTV Content Markers between users does not imply a transfer of access rights. Separate acquisition of these rights might be necessary.




Figure 8A: IPTV Content Marker - data model

Figure 8A depicts the data model assumes that each IPTV user is allocated at least an IMS Public User Identity and individual IPTV Bookmark data items are associated with this IMS Public User Identity.

Each of the entries within an IPTV Bookmark item may be rendered to the end-user.

Editor's Note: Whether IPTV Bookmark data is a part of Service Action Data or not is FFS

7.5.2.2 IPTVContentMarkerID

Unique identifier to distinguish between several of a user's IPTV Content Markers. It shall always be present.

7.5.2.3 OwnerUserID

This attribute shall identify the user owning the IPTV Content Marker by means of the IMPU. It shall always be present.

7.5.2.4 IPTVServiceType

This attribute identifies the type of IPTV service this IPTV Content Marker refers to: BC, CoD, N-PVR.

7.5.2.5 ReferencedContentID

This attribute shall identify the content this particular IPTV Content Marker refers to

- In case of BC, it shall consist of the “BCServiceId” as well as the “ProgrammId” (see clause 7.4.1)
- In case of CoD, it shall be set to the “CoDId” (see clause 7.4.1)
- In case of N-PVR, it shall be set to the “NPVRContentId” (see clause 7.4.1)

7.5.2.6 StartTimeOfIPTVContentMarker

This optional timestamp may be used to identify a starting point for playback of referred-to content. If it is not present playback should start at the beginning of the content.

NOTE: StartTimeOfIPTVContentMarker and EndTimeOfIPTVContentMarker are intended as guidance for playback logic to point to particularly interesting scenes within the content they are associated to.

7.5.2.7 EndTimeOfIPTVContentMarker

This optional timestamp may be used to identify an ending point for playback of referred-to content. If it is not present playback should end at the end of the content.

NOTE: StartTimeOfIPTVContentMarker and EndTimeOfIPTVContentMarker are intended as guidance for playback logic to point to particularly interesting scenes within the content they are associated to.

7.5.2.8 UserComment

The user may comment an IPTV Content Marker/the content referred to by the IPTV Content Marker item.

7.5.2.9 GenerationTime

This optional timestamp may store the point in time when the IPTV Content Marker item was created.

7.5.2.10 ExpiryTime

This optional timestamp indicates when the associated IPTV Content Marker item expires.

7.5.3 IPTV Service Access History

7.5.3.1 Data model

This clause defines the data model for IPTV service access history, which can be used for:

- User preference extraction needed by service personalization and targeting (e.g. targeted Ad, CRS, personalized EPG etc.);
- Sharing consumption history among authorized users.

Editor's Note: How the user preference is extracted from the IPTV service access history is out of scope of present document.

IPTV Service Access History
UserID: String
AccessHistoryID: String
ServiceType: Enumerated
ReferencedContentID: String
Rating : enumerated
AccessStartTime: Timestamp
AccessEndTime: Timestamp
HistoryExpiryTime: Timestamp

Figure 8B: IPTV service access history data model

Figure 8B depicts the data model assumed that each IPTV user is allocated at least an IMS Public User Identity (i.e. IMPU) and one or multiple IPTV service access history items are associated with this identifier.

The entries of IPTV service access history may be rendered to the user through authorization rules or be processed by the service provider subject to appropriate privacy and regularity mechanisms.

7.5.3.2 UserID

This attribute identifies who is the IPTV service access history item is associated. It shall always be present and has a string value.

7.5.3.3 AccessHistoryID

This attribute is used to distinguish between several IPTV service access history items of a user. It shall always be present and has a string value.

7.5.3.4 ServiceType

This attribute identifies the service type of a user's service access history, which refers to BC, CoD, N-PVR Ad or UGC. It shall always be present and has a enumerated value.

7.5.3.5 ReferencedContentID

This attribute identifies the associated content accessed by the user

- In case of BC, it shall consist of the “BCServiceId” as well as the “ProgrammId” (see clause 7.4.1);
- In case of CoD, it shall be set to the “CoDId” (see clause 7.4.1);
- In case of N-PVR, it shall be set to the “NPVRContentId” (see clause 7.4.1);
- In case of Ad, it shall contain the ad content id (see 8.14.1);
- In case of UGC, it shall contain the UGC content id (see 8.9.2)

7.5.3.6 Rating

This optional attribute indicates the user rating for the referened content. It has a numerated value (e.g. one-star, two-stars...).

7.5.3.7 AccessStartTime

This attribute is used to identify the time when the access to the content is started. It shall always be present and has a timestamp value.

7.5.3.8 AccessEndTime

This attribute is used to identify the time when the access to the content is ended. It shall always be present and has a timestamp value.

7.5.3.9 HistoryExpiryTime

This optional attribute identifies the expiry time of an IPTV service access history item. It has a timestamp value.

7.6 IPTV Content Recommendation profile

Editor's note : This clause should describe Content Recommendation data model to store informations that could not be covered by IPTV Service Access history data model (e.g. like Preferred Genres, ...)

8 Procedures

Editor's Note: Contributions are invited in this clause to clarify on the streaming case and upload/download case for better understanding on how the generic procedures could be referred, as well as avoid inconsistency with Release 2.

Editor's Note: Whether dedicated procedures for e.g. content recommendation and advertising are required or whether the services can be described using notification procedure is FFS.

Editor's Note: Depending on new IPTV services in this Release, additional procedures need to be defined.

8.1 IPTV addressing mechanisms

8.1.1 IPTV end-users identification and addressing mechanisms

End-user identification and addressing shall be done according to what is defined in document TS 182 006 [2].

8.1.2 Addressing of nodes

As specified by TS 182 006 [2], those network nodes with reference points supporting the SIP protocol shall be identifiable using a valid SIP URI.

8.2 UE start-up procedure

Figure 9 depicts the typical steps that occur at power up of the UE. Some of the steps are not new in them selves, but exist already in NGN.




Figure 9: UE start-up procedure

- 1) **Network Attachment**
In this step the UE attaches to the network. The procedures for network attachment are defined in ES 282 004 [3]. This step includes IP configuration, P-CSCF address discovery, etc.
- 2) **IMS Registration**
In this step, the UE performs regular IMS Registration as defined in TS 182 006 [2].
- 3) **Service Attachment**
In this step, the UE retrieves the configuration information (server addresses and other relevant information) needed to retrieve the appropriate information to access the services that the user is authorized to. The user preferences and the capabilities of the UE can be taken into account to enable personalized service discovery. The UE could retrieve the service discovery information through the Push mode and Pull mode.
Push mode: When the UE attaches to the IMS network, the SDF actively sends the service attachment information to the UE.
Pull mode: After the UE attaches to the IMS network, the UE actively requests the service attachment information from the SDF.

NOTE 1: The SDF discovery can be performed in several ways: through NASS attachment, by manual provisioning, using IFC e.g. third-party registration, etc.

- 4) **Service Selection**
In this step, the UE retrieves data related to specific services and makes appropriate service selection.

NOTE 2: In case the UE needs to directly contact a network functional element, (e.g. a Service Control Function - SCF, or SSF), it should perform GBA authentication, for key management purposes. This procedure will secure further communication taking place between the UE and the IPTV Service Control Function. The GBA bootstrapping procedure is defined in GAA - TS 133 220 [4] and is referenced in the TISPAN NGN Security architecture - TS 187 003 [5]. This step is not affecting the functional behaviour of any of the entities involved in this start-up phase and thus, it is not displayed in this flow.

The detailed sequence of steps 3-4 is described in the figures below:




Figure 10: IPTV service attachment and selection in pull mode

- 1) The UE makes a service attachment request.
- 2) The core IMS relays the request to the appropriate entity (here, SDF).
- 3) The SDF determines the proper SSF (or SSFs) according to the UE's capabilities, the user's profile and also the location of the UE (Personalized Service Discovery). The user profile may be retrieved from the UPSF or any other entity where it is stored.
- 4) Configuration information that includes the SSF address(es) is (are) routed back to the UE.
- 5) Core IMS relays the configuration information related to IPTV services back to UE.
- 6) The UE requests the SSF to get the selection data.
- 7) The SSF delivers the requested data to the UE.

For the purpose of service configuration update, steps 4 and 5 described above can be repeated at any time after completion of the IPTV service attachment and selection procedure.




Figure 11: IPTV service attachment and selection in push mode

- 1) The SDF gets the status of the UE, e.g. the S-CSCF sends a third-party REGISTER request to the SDF after the IMS Registration or by other method, then the SDF gets the status of the UE.
- 2) The SDF determines the proper SSF (or SSFs) according to the UE's capabilities, the user's profile and also the location of the UE (Personalized Service Discovery). The user profile may be retrieved from the UPSF or any other entity where it is stored.
- 3) Configuration information that includes the SSF address(es) is (are) routed back to the UE.
- 4) Core IMS relays the configuration information related to IPTV services back to UE.
- 5) The UE requests the SSF to get the selection data.
- 6) The SSF delivers the requested data to the UE.

8.3 Broadcast session

The procedures described here are for streaming cases distinguished from upload/download cases (described in 8.19).

Before the User Equipment can join a multicast channel, a session initiation procedure shall take place as described in clause 8.3.1. One session initiation is associated to one or more service packages. SCF does not participate in channel change control in order to avoid zapping delays.

The UE retrieves necessary network parameters to handle the BC TV Service either before the session initiation procedure (from the SSF) or as part of the session initiation procedure (from the SCF).

The SSF and/or the SCF acquire network parameters from management entities.

NOTE: Alternative methods could exist, but they are out of scope for this release.

The session may be modified using the procedure described in clause 8.3.2 in the following cases:

- The BC TV Service is modified.
- Currently allocated resources are not sufficient and the User Equipment wishes to join a multicast channel with different QoS requirements (e.g. zapping from a SD to HD channel). The session modification procedure may take place before or after the request to change channel, in order to avoid increasing zapping delays. In the later case, the session modification procedure is initiated by the UE and the new channel is delivered using currently allocated resources until this procedure and any additional resource reservations that may be required are completed.

The session can be terminated by the User Equipment using the procedures described in clause 8.3.3 or by the network.

Interactions between the IMS and the RACS take place at different steps of the session initiation and modification and release. Additional resource control procedures not triggered by the IMS may also take place and are not described in the following clauses.

8.3.1 Signalling flows for broadcast session initiation

8.3.1.1 Overview of the signalling flows for session initiation

Figure 12 provides an overview of the information flows for UE-initiated BC session initialization.




Figure 12: UE-initiated BC session initialization

- 1) The UE initiates a dialogue to the BC service which refers to the service package(s).
- 2) The session initiation request is routed by the Core IMS entities up to the SCF in charge of the requested BC service.
- 3) Signalling procedures for the establishment of one or more content delivery channels network parameters necessary to handle the BC service take place between the UE and the SCF (see clause 8.3.1.2).

NOTE: In a particular protocol realization, the messages supporting step 3 may be embedded in the messages supporting session initiation.

- 4) The SCF confirms the dialogue establishment.
- 5) The P-CSCF within the Core IMS interacts with the RACS to commit all resources and to activate the service package(s) in transport network element at edge of network for enabling multicast joining.
- 6) The P-CSCF forwards the dialogue confirmation to the UE.
- 7) The UE starts joining multicast channels and receiving multicast flows.

Figure 12A provides an overview of the information flows for SCF-initiated BC session initialization.




Figure 12A: SCF-initiated BC session initialization

- 1) The SCF sends a session initiation request to the UE via the core IMS.
- 2) The Core IMS forwards the session initiation request to the UE.
- 3) If the UE accepts the request, signalling procedures for the establishment of one or more content delivery channels network parameters necessary to handle the BC service take place between the UE and the SCF (see clause 8.3.1.2).

NOTE: In a particular protocol realization, the messages supporting step 3 may be embedded in the messages supporting session initiation.

- 4) The UE confirms the establishment of the dialogue with the SCF.
- 5) The P-CSCF within the Core IMS interacts with the RACS to commit all resources and to activate the service package(s) in transport network element at edge of network for enabling multicast joining.
- 6) The core IMS forwards this confirmation to the SCF.
- 7) The UE starts joining multicast channels and receiving multicast flows.

NOTE: SCF can initiate BC notification to UE (The procedure is described in clause 8.11.1), when UE receive the notification, it can initiate the BC session as figure 12.

8.3.1.2 Signalling flows for the establishment of the delivery channel

Figure 13 shows information flows applicable when SCF initiates the establishment of content delivery channel.




Figure 13: Establishment of the delivery channel

- (42) The SCF initiates the establishment of one or more content delivery channels with the UE, by sending a media offer through the Core IMS.
- (43) The P-CSCF within the Core IMS interacts with the RACS according to the description given in the media offer.
- (44) The P-CSCF within the Core IMS forwards the media offer to the UE.
- (45) The UE provides a media answer to the Core IMS.
- (46) The P-CSCF within the Core IMS interacts with the RACS to update the configuration according to the media answer.
- (47) The media answer is propagated to the SCF.

Figure 14 provides an overview of the information flows for UE-initiated establishment of content delivery channel necessary to handle the BC service.




Figure 14: Establishment of the delivery channel

- (41) The UE initiates the establishment of one or more content delivery channels with the SCF, by sending a media offer through the Core IMS.
- (42) The P-CSCF within the Core IMS interacts with the RACS to reserve transport resources according to the media offer.
- (43) The media offer is forwarded to the SCF.
- (44) The SCF sends a media answer through the Core IMS.
- (45) Within the Core IMS, the P-CSCF interacts with the RACS to update the previous reservation (optional).
- (46) The media answer is propagated to the UE.

8.3.2 Signalling flows for BC session modification

The BC session modification procedure is used to modify network parameters necessary to handle the BC service in an existing session.

The BC session modification procedure is initiated by the UE or the SCF.

Figure 15 provides an overview of the information flows for UE-initiated BC session modification.




Figure 15: UE-initiated BC session modification

- 1) The UE initiates a session modification procedure in order to start a modification of network parameters necessary to handle the BC service.
- 2) The session modification request is forwarded to the SCF through the Core IMS.
- 3) Procedures for the negotiation of the network parameters necessary to handle the BC service take place between the UE and the SCF (see clause 8.3.1.2).

NOTE: In a particular protocol realization, the messages supporting step 3 may be embedded in the messages supporting session modification.

- 4) The SCF acknowledges the session modification.
- 5) The P-CSCF within the Core IMS interacts with the RACS to commit all resources previously reserved.
- 6) The P-CSCF forwards the confirmation to the UE.
- 7) The UE starts joining multicast channels and receiving multicast flows.

Figure 16 provides an overview of the information flows for SCF-initiated session modification.




Figure 16: SCF-initiated BC session modification

- 1) The SCF initiates a session modification procedure in order to start a negotiation for network parameters necessary to handle the BC service.
- 2) The session modification request is forwarded to the UE by the Core IMS.
- 3) Procedures for the negotiation of the network parameters necessary to handle the BC service take place between the UE and the MF (see clause 8.3.1.2).

NOTE: In a particular protocol realization, the messages supporting step 3 may be embedded in the messages supporting session modification.

- 4) The UE confirms the modification of the session.
- 5) The P-CSCF within the Core IMS interacts with the RACS to commit all resources previously reserved.
- 6) The Core IMS forwards this modification to the SCF.
- 7) The UE starts joining multicast channels and receiving multicast flows.

8.3.3 Signalling flows for broadcast session release

Figure 17 provides an overview of the information flows for UE-initiated session release.




Figure 17: UE-initiated broadcast session release

- 1) The UE initiates a session termination.
- 2) The P-CSCF interacts with the RACS to release all transport resources that had been reserved for this session and to deactivate the service package in transport network element to prevent invalid multicast joining.
- 3) The Session Termination Request is routed by the Core IMS entities up to the SCF.
- 4) The SCF returns a Session Termination Confirm to the Core IMS.
- 5) The P-CSCF forwards the Session Termination Confirm to the UE.

Figure 18 provides an overview of the information flows for SCF-initiated session release.




Figure 18: SCF-initiated broadcast session release

- 1) The SCF initiates a session termination.
- 2) The P-CSCF interacts with the RACS to release all transport resources that had been reserved for this session and to deactivate the service package in transport network element to prevent invalid multicast joining.
- 3) The Session Termination Request is routed by the Core IMS entities up to the UE.
- 4) The UE returns a Session Termination Confirm to the Core IMS.
- 5) The Core IMS forwards the Session Termination Confirm to the SCF.

8.3.4 Signalling flow for Broadcast TV channel switching

Figure 19 provides an example of a signalling flow for channel switching. It shows how the SCF can be informed about what channel is currently being watched.




Figure 19: Broadcast TV channel switching

- 1) The UE leaves a multicast channel and joins another multicast channel.
- 2) A delay may be applied. If the user switches channel again during this delay time, the flow is restarted at step 1.
- 3) The UE sends information about which channel is being watched.
- 4) Core IMS routes the information to the SCF.

The SCF stores channel change information in the Service Action Data.

8.3.5 Signalling flows for transition from Broadcast TV to Broadcast TV with trick play

Figure 20 provides the signalling flow for trick play of a Broadcast TV channel. In order to apply trick modes to a Broadcast TV session, this must be established as indicated in clause 8.3.1.

The same session is used in the trick play session modification, in order not to change the bandwidth requirements on the network. At successful conclusion of these procedures the UE seamlessly transitions from viewing Broadcast TV to Broadcast TV with trick play.

NOTE: As an alternative to the session modification, it is possible to initiate a separate session for trick modes handling, in addition to the Broadcast TV one, while keeping control of the bandwidth requirements between the two of them. This method is, however, out of the scope of the present document.

Draft




Figure 20: Signalling flow for initiating trick play of broadcast TV channel

- 1) Broadcast TV session initiation.

NOTE 1: The procedures are the same as clause 8.3.2, Overview of the signalling flows for session initiation. RACS and channel establishment have been removed for purpose of simplification.

- 2) The UE sends information on the current channel being watched, in order for the SCF to know what channel should be recorded.
- 3) Core IMS routes the information to the SCF.

- 4) When the UE initiates trick play mode of a Broadcast TV the UE sends a session modify request which includes a media offer for a content control channel and content delivery channel with the MF. If trick play service is not available for the UE, the session modification is not sent.

NOTE 2: The Broadcast TV with trick play session modification is performed on the same session as the Broadcast TV session initiation. The existing reservation (for broadcast) needs to be modified to add a unicast flow that reuses the resources dedicated to the user. In the figure, RACS has been combined with Core IMS for the purpose of simplification.

NOTE 3: Steps 2 and 3 are optional in a generic Broadcast TV session, but are required if trick play is activated. The implementation of both steps as separate messages or combined with step 4 is an implementation issue.

- 5) After reserving resources in RACS Core IMS forwards the session modification request to the SCF.
- 6) The SCF forwards the session modification request as a new session initiation to the MF along with the channel indication. The MF will determine if the programme currently broadcasted has trick play support. . Prior to replying the MF uses real time to calculate the media offset for the broadcast TV channel when replying with the offered media. If trick play service is not available for the UE the session modification is rejected and the old Broadcast TV session initiation (along with the previous reserved committed resources) is maintained.
- 7) The MF sends the session modification response to the SCF.
- 8) The SCF forwards the session modification response to the Core IMS.
- 9) After committing resources in RACS Core IMS forwards the session modification response to the UE.
- 10) The UE leaves the multicast channel.
- 11) The UE starts playing content and receiving unicast flow.

NOTE 4: Alternatives to the above call-flow are for further study.

8.3.6 Signalling flows for transition from Broadcast TV with trick play to Broadcast TV

The UE returns from Broadcast TV trick play to linear Broadcast TV, for example when the UE switches channels from a paused channel to another live Broadcast TV channels, or when the UE fast-forwarding in a unicast stream and catches up with the live Broadcast TV channel.

The trigger to transition from Broadcast TV with Trick Play to Broadcast TV may be initiated by the UE, SCF or MCF.

NOTE: The event to trigger the transition is outside of the present document.

The UE or SCF may request a Broadcast TV session modification as described in clause 8.3.2, titled Overview of the signalling flows for session modification. The difference is that the Broadcast TV session modification is performed on the same session, in order to release unicast resources, and the SCF is responsible for releasing the resources in the MCF with a session termination request/response.

The MCF may request a session termination towards SCF which in turn performs Broadcast TV session modification towards the UE.

8.3.7 Signalling flows for Broadcast TV with trick play session release

When the UE terminates the Broadcast TV with trick play the UE shall follow the same flows as clause 8.4.3.

8.3.8 Signalling flows for Pay Per View service

Figure 20A depicts signalling flows for PPV service, this procedure applies for IPTV users subscribing to a PPV program scheduled on a channel to which the user is not subscribed to.




Figure 20A: Signalling flows for Pay Per View session

Prior to the PPV program session initiation, users should have subscribed a PPV program. The subscription information which may be saved as user profile include the user's identity, BC service ID and BC program ID of the PPV program.

- 1) UE initiates the PPV program session as the BC session initiation procedures specified in clause 8.3.1, The PPV specific steps here are as follows:
 - i. The PPV program session initiation request includes the BC service ID and the BC program ID of the PPV program.
 - ii. When SCF receives the request, the SCF identifies the program according to the BC service ID and BC program ID, and verifies based on the IPTV user profile, that the program has been PPV subscribed. Upon successful verification, the SCF verifies that the program is ready to start, i.e. the current time is greater than/equal to program start time. Then accepts the request. If not, it refuses the request.

NOTE 1: The SCF authorizes the BC Session Initiation for that BC Service ID based on the fact that BC Program ID has been PPV subscribed. In the answer to the session initiation, the SCF includes information related to that authorized PPV program to enable the Core IMS to provision RACS with necessary parameters.

NOTE 2: The initiation of PPV program session may be triggered by the user's action or the notification from SCF (e.g. SCF detects the PPV program is ready to start, and sends a notification to UE as specified in clause 8.11.1).

2) The UE starts joining multicast channels and receiving multicast flows.

3) UE or SCF initiates the PPV program session release procedure as BC session release procedures specified in clause 8.3.3. As part of the PPV program session release, RACS is updated by removing the BC Service.

NOTE 3: Session release for PPV service can be initiated either by SCF or UE. SCF initiates session release when detects the PPV program is over.

NOTE 4: an alternative solution using release 2 mechanisms can also be used. The SCF indicates the BC service ID that identifies the PPV program either at session initiation (clause 8.3.1) if the PPV program is already authorised or by initiating a session modification (clause 8.3.2). If the BC session is on-going when the authorisation duration has elapsed, the SCF modify the session to remove the appropriate BC service ID from the authorised BC service list.

8.4 CoD session

The procedures described here are for streaming cases distinguished from upload/download cases (described in 8.18).

8.4.1 Signalling Flows for CoD session initiation

Editor's Note: Document network initiated CoD sessions

Before the User Equipment can view the content, a session initiation procedure shall take place as described in clause 8.4.1.

The UE retrieves necessary network parameters to handle the CoD service before the session initiation procedure (from the SSF), or as part of the session initiation procedure, or after the session initiation procedure (from the MF).

The session can be terminated by the User Equipment using the procedures described in clause 8.4.3 or by the network.

Interactions between the IMS and the RACS take place at different steps of the session initiation/modification and release.

In certain cases such as in conventional content server deployments, it may be preferable that a content control channel and content delivery channel(s) be established separately.

8.4.1.1 Overall signalling flows

Figure 21 provides an overview of the information flows for UE-initiated CoD session initialization.




Figure 21

- 1) (Optionally) UE may retrieve COD offset from service action data
- 2) (Optionally) SSF may return COD offset for specified content
- 3) The UE initiates a dialogue to the CoD service.
- 4) The session initiation request is routed by the Core IMS entities up to the SCF in charge of the requested CoD service.

- 5) The SCF performs service authorization as described in clause 5.1. If the UE is allowed to access the content, the SCF forwards the session initiation request to the selected MF.
- 6) Signalling procedures for establishment of a content control channel and optionally (Note 2) content delivery channels take place between the UE and the MF (see clause 8.4.1.2).

NOTE 1: In a particular protocol realization, the messages supporting step 4 may be embedded in the messages supporting session initiation.

NOTE 2: The establishment of the content delivery channel in the session initiation is only optional when network has provided information for only content control channel setup. In this case, the content delivery channel is established during session modification.

- 7) The MF confirms the establishment of the dialogue with the UE.
- 8) (Optionally) If the session initiation does not include a COD offset, the SCF may try to retrieve a stored offset for this CoD service in service action data. In this case, the SCF includes this offset in the session initiation answer.
- 9) The SCF forwards this confirmation to the Core IMS.
- 10) The P-CSCF within the Core IMS interacts with the RACS to commit all resources previously reserved. This includes opening pinholes for exchanging content control messages and/or content delivery.
- 11) The P-CSCF forwards the dialogue confirmation to the UE.

Figure 21A provides an overview of the information flows for SCF-initiated CoD session initialization




Figure 21A

- 1) (Optionally) The SCF may retrieve the COD offset if present in service action data

- 2) The SCF sends a session initiation request including the COD offset to the MF
- 3) The SCF sends a session initiation request to the UE via the core IMS .
- 4) The Core IMS forwards the session initiation request to the UE.
- 5) If the UE accepts the request, signalling procedures for establishment of a content control channel and optionally (Note 2) content delivery channels take place between the UE and the MF via the SCF (see clause 8.4.1.2).

NOTE 1: In a particular protocol realization, the messages supporting step 4 may be embedded in the messages supporting session initiation.

NOTE 2: The establishment of the content delivery channel in the session initiation is only optional when network has provided information for only content control channel setup. In this case, the content delivery channel is established during session modification.

- 6) The UE confirms the establishment of the dialogue with the SCF.
- 7) The P-CSCF within the Core IMS interacts with the RACS to commit all resources previously reserved. This includes opening pinholes for exchanging content control messages and/or content delivery.
- 8) The core IMS forwards this confirmation to the SCF.
- 9) The MF confirms the establishment of the dialogue with the SCF.
- 10) (Optionally) UE may retrieve COD offset from service action data
- 11) (Optionally) SSF may return COD offset for specified content

After this point, UE may use the content control channel to request content to be streamed and the actual content will be then delivered/streamed over the content delivery channels.

The content control channel will also be used to carry UE requests for controlling the streams, e.g. "pause", "fast forward", etc.

8.4.1.2 Media Channel Negotiation

The following clauses go into details related to step 4 in the session initiation in clause 8.4.1.1.

8.4.1.2.1 Signalling flows for the establishment of the content control and content delivery channels from MF

Figure 22 shows information flows applicable when network parameters necessary to handle the CoD service are provided by the MF as part of the session initiation procedure. This set of information flows assume that the UE does not receive a description of the network parameters required from the SSF before initiating the session.




Figure 22

- (41) The MF initiates negotiation of a content control channel and one or more content delivery channels with the UE, by sending a media offer to the SCF.
- (42) The media offer is forwarded to the Core IMS.
- (43) The P-CSCF within the Core IMS interacts with the RACS to reserve transport resources for the content control channel and one or more content delivery channels.
- (44) The P-CSCF within the Core IMS forwards the media offer to the UE.
- (45) The UE provides a media answer to the Core IMS.
- (46) The P-CSCF within the Core IMS interacts with the RACS to update the reservation (optional).
- (47) The media answer for the content control channel and one or more content delivery channels is propagated to the SCF.
- (48) The SCF forwards the media answer to the MF.

8.4.1.2.2 Signalling flows for the establishment of the content control and content delivery channels from UE

Figure 23 provides an overview of the information flows for UE-initiated negotiation of the network parameters necessary to handle the CoD service. This set of information flows assume that the UE receives a description of the network parameters required from the SSF before initiating the session.




Figure 23

- (41) The UE initiates negotiation of a content control channel and one or more content delivery channels with the MF, by sending a media offer to the Core IMS.
- (42) The P-CSCF within the Core IMS interacts with the RACS to reserve transport resources for the content control channel and one or more content delivery channels.
- (43) The media offer is forwarded to the SCF.
- (44) The SCF forwards the media offer to the MF.
- (45) The MF provides a media answer to the SCF.
- (46) The SCF forward the media answer to the Core IMS.
- (47) Within the Core IMS, the P-CSCF interacts with the RACS to update the previous reservation (optional).
- (48) The media answer for the content control channel and one or more content delivery channels is propagated to the UE.

8.4.1.2.3 Signalling flows for the establishment of the content control channel from UE

Figure 24 provides an overview of the information flows for UE-initiated establishment of the content control channel.




Figure 24

- (41) The UE initiates negotiation of a content control channel with the MF, by sending a media offer to the Core IMS.
- (42) The P-CSCF within the Core IMS interacts with the RACS to reserve transport resources for the content control channel.
- (43) The media offer is forwarded to the SCF.
- (44) The SCF forwards the media offer to the MF.
- (45) The MF provides a media answer to the SCF.
- (46) The SCF forward the media answer to the Core IMS.
- (47) Within the Core IMS, the P-CSCF interacts with the RACS to update the previous reservation (optional).
- (48) The media answer for the content control channel is propagated to the UE.

8.4.2 Signalling Flows for CoD session modification

The CoD session modification procedure is used to add, remove or modify one or more content delivery channels in an existing session.

The CoD session modification procedure is initiated by the UE or the MF.

The session modification procedure shall take place immediately after the session initiation procedure (e.g. using network parameters retrieved from content control messages) when no content delivery channels were set during this previous phase.

In case of a session modification, the content delivery channel setup/modification procedure is always triggered by the entity initiating the session modification.

Figure 25 provides an overview of the information flows for UE-initiated CoD session modification.




Figure 25

- 1) The UE initiates a session modification procedure in order to start a negotiation for one or more content delivery channel(s).
- 2) The session modification request is forwarded to the SCF through the Core IMS.
- 3) The SCF performs service authorization as described in clause 5.1. If the UE is allowed to modify the content, the SCF forwards the session modification request to the MF.
- 4) Procedures for establishment of a content delivery channels take place between the UE and the MF (see clause 8.4.2.1).

NOTE: The messages supporting step 4 are embedded in the messages supporting session modification.

- 5) The MF confirms the modification of the session.
- 6) The SCF forwards this modification to the Core IMS.
- 7) The P-CSCF within the Core IMS interacts with the RACS to commit all resources previously reserved. This includes opening pinholes for content delivery.
- 8) The P-CSCF forwards the confirmation to the UE.

After this point, UE may request content to be delivered over the content control channel and the actual content will be then delivered over the content delivery channels.

The content control channel will also be used to carry UE requests for controlling the streams over the content delivery channels, e.g. "pause", "fast forward", etc.

Figure 26 provides an overview of the information flows for MF-initiated CoD session modification.




Figure 26

- 1) The MF initiates a session modification procedure in order to start a negotiation for one or more content delivery channel(s).
- 2) The SCF performs service authorization as described in clause 5.1. The SCF forwards the session modification request to the MF.
- 3) The session modification request is forwarded to the UE by the Core IMS.
- 4) Procedures for establishment of a content delivery channels take place between the UE and the MF (see clause 8.4.2.2).

NOTE: The messages supporting step 4 are embedded in the messages supporting session modification.

- 5) The UE confirms the modification of the session.
- 6) The P-CSCF within the Core IMS interacts with the RACS to commit all resources previously reserved. This includes opening pinholes for content delivery.
- 7) The Core IMS forwards this modification to the SCF.
- 8) The SCF forwards the confirmation to the MF.

After this point, UE may send a request over the content control channel to stream content and the actual content will be then delivered over the content delivery channels.

The content control channel will also be used to carry UE requests for controlling the content streams e.g. "pause", "fast forward", etc.

8.4.2.1 Signalling flows for the establishment/modification of the content delivery channel from UE

Figure 27 provides an overview of the information flows for UE-initiated establishment or modification of the content delivery channel.




Figure 27

- (41) The UE initiates negotiation of one or more content delivery channel with the MF, by sending a media offer to the Core IMS.
- (42) The P-CSCF within the Core IMS interacts with the RACS to reserve transport resources for the content delivery channels.
- (43) The media offer is forwarded to the SCF.
- (44) The SCF forwards the media offer to the MF.
- (45) The MF provides a media answer to the SCF.
- (46) The SCF forward the media answer to the Core IMS.
- (47) Within the Core IMS, the P-CSCF interacts with the RACS to update the previous reservation (optional).
- (48) The media answer for the content delivery channels is propagated to the UE.

8.4.2.2 Signalling flows for the modification of the content delivery channels from MF

Figure 28 provides an overview of the information flows for MF-initiated modification of the content delivery channel.




Figure 28

- (41) The MF initiates negotiation of one or more content delivery channels with the UE, by sending a media offer to the SCF.
- (42) The media offer is forwarded to the Core IMS.
- (43) The P-CSCF within the Core IMS interacts with the RACS to reserve transport resources for the content delivery channels.
- (44) The P-CSCF within the Core IMS forwards the media offer to the UE.
- (45) The UE provides a media answer to the Core IMS.
- (46) The P-CSCF within the Core IMS interacts with the RACS to update the reservation (optional).
- (47) The media answer for the content delivery channels is propagated to the SCF.
- (48) The SCF forwards the media answer to the MF.

8.4.3 Signalling Flows for CoD session release

Figure 29 provides an overview of the information flows for UE-initiated session release.




Figure 29

- 1) The UE initiate a session termination.
- 2) The P-CSCF interacts with the RACS to release all transport resources that had been reserved for this session.
- 3) The Session Termination Request is routed by the Core IMS entities up to the SCF.
- 4) The SCF forwards the Session Termination Request to the appropriate Media Function.
- 5) The Media Function (i.e. the MCF) release all resources associated with the session and returns a Session Termination Confirm.
- 6) The SCF forwards the Session Termination Confirm to the Core IMS.
- 7) The P-CSCF forwards the Session Termination Confirm to the UE.

Figure 30 provides an overview of the information flows for SCF-initiated session release.




Figure 30

- 1) The SCF initiates a session termination towards the MF.
- 2) The Media Function (i.e. the MCF) releases all resources associated with the session and returns a Session Termination Confirm.
- 3) The SCF initiates a session termination towards the UE.
- 4) The P-CSCF interacts with the RACS to release all transport resources that had been reserved for this session.
- 5) The Session Termination Request is routed by the Core IMS entities up to the UE.
- 6) The UE returns a Session Termination Confirm to the Core IMS.
- 7) The Core IMS forwards the Session Termination Confirm to the SCF.

Figure 31 provides an overview of the information flows for MF-initiated session release.




Figure 31

- 1) The MF initiates a session termination towards the SCF.
- 2) The SCF forwards the session termination request to the Core IMS.
- 3) The P-CSCF interacts with the RACS to release all transport resources that had been reserved for this session.
- 4) The Session Termination Request is routed by the Core IMS entities up to the UE.
- 5) The UE returns a Session Termination Confirm to the Core IMS.
- 6) The Core IMS forwards the Session Termination Confirm to the SCF.
- 7) The SCF forwards the Session Termination Confirm to the MF that releases all resources associated with the session.

8.4.4 Signalling Flows for CoD session transfer

Editor's note : This chapter provides a basic proposal that requires alignment with ongoing work in 3GPP for inter-UE transfer and multimedia session continuity. Contributions are required to align the proposed mechanism below by proper referencing to the generic mechanism(s) provided by 3GPP in order to provide a unique solution for transferring sessions under the control of IMS.

The CoD session transfer is used to transfer an on-going CoD session from one terminal called transferor UE to another one called transferee UE.

The transferor UE and the transferee UE must be served by different or the same SCF.

The session transfer could be handled directly between both terminals or can be managed by the transferee SCF. In the latter case, the transferor SCF will initiate a CoD session with the transferee UE at session transfer request from the transferor UE.

8.4.4.1 Terminal centric session transfer pushed from transferor UE to transferee UE

Figure 31A provides an overview of the information flows for direct CoD session transfer between the transferor UE (UE1) and the transferee UE (UE2). For clarity purpose, core-IMS is not indicated in the figure but all messages go through it.

In this scenario the transferor UE discovers the devices to which a potential transfer can be initiated. The transferor UE selects a devices and initiates the procedure




Figure 31A

- 1) UE1 has initiated a dialogue to the CoD service as defined in clause 8.4.1. A session is on going with the MF1.
 - 2) The user decides to transfer the session to another device. UE1 performs device discovery (UE awareness) as defined in 3GPP to discover the devices that it can transfer the session to .
- Editor`s note: 3GPP is in the process of completing TS 23.237 and TS 23.838 targeted for release 9. A normative reference should be provided.
- 3) UE1 sends an Offset Notification to the SCF via the core-IMS.

Editor`s note: A procedure for a network based initiated content marker request is required in order to make the sending of the offset notification by UE1 optional. If such a procedure is defined then step 3 will become as follows:

The UE1 may send an offset notification to the SCF. If the SCF has not received an offset notification from UE1 it uses network initiated content marker procedure to acquire an offset.

- 4) UE1 sends a Session Transfer Request to the SCF via the core-IMS containing Session transfer identifier- STI (identity of the session to be transferred). The SCF obtains the CoD content-id, and perform service authorisation and checks that the user is authorised to perform session transfer. The SCF also obtains the UE2 identity and the target user identity from the incoming request.

Editor`s note: The specific mechanism for obtaining the CoD content-id if ffs

- 5) The Session Transfer Request, including the offset, is forwarded from the SCF to the UE2 via the Core-IMS.
- 6) UE2 receives an invitation to initiate a CoD session for the content indicated by the content-id. It acknowledges the Request by sending a Session Transfer Response to the SCF via the Core-IMS..
- 7) The SCF forwards the Session Transfer Response to the UE1 via the Core-IMS
- 8) The UE2 informs the UE1 that it initiates the CoD session initiation by sending a Session Transfer Start Notification to the UE1 via the core-IMS.

NOTE 1: This message can optionally go through the SCF.

- 9) CoD session initiation between the UE2 and MF2 via core-IMS is done as defined in clause 8.4.1.
- 10) The UE2 informs the UE1 that CoD session initiation is complete by sending a Session Transfer Complete Notification to the UE1.

NOTE 2: This message can optionally go through the SCF.

- 11) The UE1 terminates the CoD session with the MF1 as defined in clause 8.4.3

8.4.4.2 Network centric session Transfer pushed from transferor UE to transferee UE

Figure 31B provides an overview of the information flows for CoD session transfer between the transferror UE (UE1) and the transferee UE (UE2) managed by the transferor SCF . For clarity purpose, core-IMS is not indicated in the figure but all messages go through it.




Figure 31B

- 1) UE1 has initiated a dialogue to the CoD service as defined in clause 8.4.1. A session is on going with the MF1.
- 2) The user decides to transfer the session to the another device. UE1 performs device discovery (UE awareness) as defined by 3GPP.

Editor`s note: 3GPP is in the process of completing TS 23.237 and TS 23.838 targeted for release 9. A normative reference should be provided.

- 3) UE1 sends an Offset Notification to the SCF via the core-IMS.

Editor`s note: A procedure for a network based initiated content marker request is required in order to make the sending of the offset notification by UE1 optional. If such a procedure is defined then step 3 will become as follows:

The UE1 may send an offset notification to the SCF. If the SCF has not received an offset notification from UE1 it uses network initiated content marker procedure to acquire an offset.

- 4) UE1 sends a Session Transfer Request to the SCF via the Core- containing the Session Transfer Identifier-STI (the identity of the session to be transferred) and if necessary the UE2 ID (e.g. if the user ID corresponds to multiple UEs). The SCF obtains the CoD content-id, and performs service authorisation and also checks that

the user is authorised to perform session transfer. The SCF also obtains the UE2 identity and the target user identity from the incoming request.

Editor`s note: The specific mechanism for obtaining the CoD content-id if ffs

- 5) The SCF replies by a Session Transfer Response to the UE1.
- 6) The SCF informs the UE1 that it initiates the CoD session initiation by sending a Session Transfer Start Notification to the UE1 via the core-IMS.
- 7) SCF-initiated CoD session initiation between the UE2 and MF2 is done by the SCF as defined in clause 8.4.1.
- 8) The SCF informs the UE1 that CoD session initiation is complete by sending a Session Transfer Complete Notification to the UE1.
- 9) The SCF terminates the CoD session between the UE1 and the MF1 as defined in clause 8.4.3

8.4.4.3 Session Replication pushed from transferor UE to transferee UE

This scenario is identical to the session transfer in section 8.4.4.1 with the exception that the last step of terminating the session towards the transferor UE is not carried out. Hence, the transferor UE maintains his session as well.

At the end of the procedure both the transferor UE and the transferee UE have independent sessions watching same content from the same or a different MF.

Editor Note: 3GPP has not yet incorporated this requirement in release 9. If 3GPP does not accept that request than this will be TISPAN only requirement.

8.4.4.4 Session Transfer pulled by the transferee UE

Figure 31C provides an overview of the information flows for direct CoD session transfer between the transferor UE (UE1) and the transferee UE (UE2).

In this scenario the transferee UE discovers the devices and the active sessions on these devices that he can transfer to his own device.




Figure 31C

- 1) UE1 has initiated a dialogue to the CoD service as defined in clause 8.4.1. A session is on going with the MF1.
- 2) The user decides to go to his device UE2, to transfer an ongoing CoD session from device UE1. The user on UE2 performs device discovery (UE awareness) and requests form SCF the active sessions on these devices, as defined by 3GPP

Editor`s note: 3GPP is in the process of completing TR 23.237 and TS 23.838 targeted for release 9. A normative reference should be provided.

- 3) The user on UE2 sends a Session initiation to the SCF via the core-IMS, to transfer the session from device UE1. The UE includes the Session Transfer Identifier-STI (identity of the session to be transferred) in his

request. The SCF obtains the CoD content-id, and perform service authorisation and checks that the user is authorised to perform session transfer. The UE1 sends an offset notification to SCF.

Editor`s note: A procedure for a network based initiated content marker request is required in order to make the sending of the offset notification optional. If such a procedure is defined then step 3 will become as follows:

The UE1 may send an offset notification to SCF. If the SCF has not received an offset notification from UE1 it uses network initiated content marker procedure to acquire an offset.

- 4) UE2 informs the UE1 that it initiates the CoD session initiation by sending a Session Transfer Start Notification to the UE1 via the core-IMS.

NOTE 1: This message can optionally go through the SCF

- 5) The UE2 informs the UE1 that CoD session initiation is complete by sending a Session Transfer Complete Notification to the UE1.

NOTE 2: This message can optionally go through the SCF.

- 6) The UE1 terminates the CoD session with the MF1 as defined in clause 8.4.3

8.4.4.5 Session Replication Between transferor to transferee in a pull mode transfer

This scenario is identical to the session transfer in section 8.4.4.4 with the exception that the last step of terminating the session towards the transferor UE is not carried out. Hence, the transferor UE maintains his session as well.

At the end of the procedure both the transferor UE and the transferee UE have independent sessions watching same content from the same or a different MF.

Editor Note: 3GPP has not yet incorporated this requirement in release 9. If 3GPP does not accept that request than this will be TISPAN only requirement.

8.4.5 Signalling flows for CoD service action data update

CoD service action data may be updated by UE as described in clause 8.4.5.1 and generically may be updated by MF as described in clause 8.4.5.2.

8.4.5.1 CoD service action data updated by UE

The UE use the procedure described in figure 31D to save a current CoD SAD.

Editor`s Note: If there are other attributes in CoD service action data should be updated by UE is FFS.

This procedure may occur at any time. The most common use case is the stop CoD viewing request.




Figure 31D

- 1) The UE sends a CoD SAD update request to save the current position of the content. This request may also include a indicator to inform the SCF of the reason for the CoD SAD update.
- 2) The IMS core forwards this request to the SCF
- 3) The SCF store this offset as service action data for this user
- 4) The SCF confirms the CoD SAD update
- 5) The IMS core forwards the response to the UE.

8.4.5.2 CoD service action data updated by MF

The procedure described in figure 31E is used to save a CoD service action data by MF.

This CoD SAD may need to be updated for example when a user pauses a streaming, terminates the session or if the MF detects that the UE becomes unexpectedly offline.

Editor's Note: How to detect that the UE has lost connectivity is out of the scope of this document. For example loss of rstp heartbeat or rtcp packages may be used.




Figure 31E

- 1) CoD session initialization is performed as described in clause 8.4.1
- 2) MF detects a pause, end of session or that the UE becomes offline unexpectedly. The MF may decides to send changes of SAD to SCF.
- 3) MF sends a CoD SAD update request to save the current CoD SAD. This request may also include a indicator to inform the SCF of the reason for the CoD SAD update.
- 4) The IMS core forwards this request to the SCF.
- 5) The SCF updates the CoD SAD .

- 6) The SCF confirms the CoD SAD update.
- 7) The IMS core forwards the response to the MF.

8.4.6 Signalling flows for generating playlist by SCF and sending playlist information from SCF to MF during CoD session initiation

Figure 31F provides an overview of the information flows for playlist generation by SCF and sending playlist information from SCF to MF when UE initiated CoD session.




Figure 31F: Playlist communication during CoD session initiation

- 1) The UE initiates a dialogue to the CoD service as defined in clause 8.4.1.1, figure 21, step 3.
- 2) The session initiation request is routed by the Core IMS entities up to the SCF in charge of the requested CoD service as defined in clause 8.4.1.1, figure 21, step 4.
- 3) The SCF performs service authorization as described in clause 5.1. If the UE is allowed to access the service, the SCF generates playlist information or fetches a pre-configured playlist from a repository, based on the content ID carried in the session initiation request. Other information (e.g. the User ID etc) may also be used to generate the playlist. The playlist contains the list of content ID to be played and optionally content duration and restricted trick-play indication for each content.

Editor's Note: The data model for playlist is FFS.

- 4) The SCF selects an appropriate MF and forwards the session initiation request including playlist information to the selected MF, e.g. sends a SIP INVITE message.

Editor's Note: Whether a playlist can refer to content distributed over multiple MF entities is FFS.

- 5) The MF interprets playlist information and prepares for content delivery.
- 6) Content Control and or Content Delivery Channel Setup procedures and finalization of the CoD Session initiation procedure follow clause 8.4.1.1, steps 6-11.

NOTE: During this signalling, the UE might learn that a playlist was generated and act accordingly. Depending on the service type, the UE might already have learned the playlist in advance of service invocation.

8.4.7 Signalling flows for generating playlist by SCF and sending playlist information from SCF to MF during an existing CoD session

Figure 31G provides an overview of the information flows for playlist generation by SCF and sending playlist information from SCF to MF during an existing CoD session. This playlist may be a new playlist or an update.




Figure 31G: Playlist communication during an existing CoD session

- 1) A CoD session has been successfully established as described in Clause 8.4.1.1
- 2) Due to detecting an event, the SCF may choose to generate or update playlist information for the ongoing CoD session. The playlist contains the list of content ID to be played and optionally content duration and restricted trick-play indication for each content.
- 3) The SCF passes the playlist information to the MF.
- 4) The MF interprets the playlist information and acts accordingly. This may have immediate impact on the ongoing media channel.

NOTE: A new or updated playlist might make a modification of the session necessary.

8.4.8 Content switch procedure within a CoD playlist

Figure 31H provides an overview of the information flows for content switch within a CoD playlist.




Figure 31H Content switch within a CoD playlist

- 1) The UE initiates a dialogue to the CoD service as defined in clause 8.4.6. In addition, the playlist which is generated by the SCF as defined in clause 8.4.6 may be forwarded to the UE by the MF for user to choose the subsequent content.
- 2) The UE sends the content switch request related to the selected content within the playlist. The similar mechanism defined in 3GPP TS 26 234 clause 5.5.4.2 may be used here.
- 3) The MF checks that the selected content is referred in the playlist, and confirms the request.
- 4) The MF starts to deliver the new content, reusing the established media channel in case of the numbers of channels and QoS requirements are the same as the previous channel.

NOTE: Session modifications may be needed if QoS requirements of the new content is not the same as the previous one.

8.5 PVR service procedures

Editor's Note: Should the PVR service be extended to record unicast sessions also?

8.5.0A Signalling Flows for PVR Using Impulsive Request

Figure 32 depicts the typical steps that occur when the UE makes an impulsive request for a PVR service.




Figure 32: PVR capture using impulsive request

Specifics of interaction with RACS have been removed for purpose of simplification. It will follow the same procedures as outlined in the BroadcastTV and COD flows in clauses 8.3 and 8.4.

- 1) UE initiates Broadcast TV session following procedures specified in clause 8.3.1.
- 2) The user (on UE) makes a request to the SCF through the core IMS to capture the currently watched live content. During this step, the UE gives appropriate parameters to the SCF to identify the content to be recorded (e.g. BC service id and or current BC ProgrammeID, time channel delimitation code, beginning date, end date, duration, etc.). The UE also indicates the type of recording (N-PVR or C-PVR) and the target UE. The target UE identifies either the UE that is asked to record the content in case of C-PVR or the UE where the content will be downloaded, if required, in case of N-PVR.

The SCF may override the PVR request from the target UE (N-PVR or C-PVR) based on the service provider's specific service policy in SCF and the PVR subscription.

In case of N-PVR, The SCF may check the N-PVR max-duration parameter to decide whether to allow the user to capture the selected live content. Instead of specifying a time limit, the UE may specify the current ProgrammeID indicating that the current Broadcast programme needs to be captured. The SCF answers with an N-PVR content capture response indicating to the user if capture of the content is allowed or not.

In case of C-PVR or N-PVR with download, the SCF will check whether the target UE is authorized to record or receive the selected live content, and in the case of one UE-A scheduling C-PVR Service Capture Request for another UE-B, SCF further checks that UE-B has C-PVR terminal capabilities and UE-A is authorized by UE-B to make C-PVR Capture Requests on behalf of UE-B. Optionally, the SCF notifies the target UE of the storage requirements for the actual recording. For example, SCF calculates the required storage space according to the time duration and the content metadata information, the target UE checks the local storage capabilities and reserves corresponding space for the recording.

- 3) The SCF records the PVR/BC bookmark information as part of the IPTV service action data. In case of N-PVR, The SCF then follows relevant procedures to initiate the recording of the content by the MF, details of which are not explicitly shown in figure. In case of C-PVR, the SCF follows procedures in clause 8.5.2.2 to initiate the recording of the content by the specified client device.

- 4) The UE initiates Broadcast session termination procedures as defined in 8.3.3. Depending on the usage model, the UE initiates the Broadcast session termination procedure immediately after issuing the PVR capture request or it may do it at later point. The former would typically be the case of "Park and Pickup TV".

8.5.0B Signalling flows for the PVR off-line capture request

Figure 33 depicts the typical steps that occur when the UE makes an offline request for a PVR service.




Figure 33: PVR Capture procedures using offline request

- 1) The user (on UE) makes a request to the SCF through the core-IMS to capture a particular live content. During this step, the UE gives appropriate parameters to the SCF to identify the content to be recorded (e.g. BC service id, BC programmeID time channel delimitation code, beginning_date, end_date, duration, etc.). The UE also indicates the type of recording (N-PVR or C-PVR) and the target UE. The target UE identifies either the UE that is asked to record the content in case of C-PVR or the UE where the content will be downloaded, if required, in case of N-PVR.

The SCF may override the PVR request from the target UE (N-PVR or C-PVR) based on the service provider's specific service policy in SCF and the PVR subscription.

The SCF may check the N-PVR max-duration parameter to decide whether to allow the user to capture the selected live content.

NOTE: The content capture request may go to the SSF instead of the SCF. This implies that the SSF needs to communicate with the SCF. A reference point for direct communication between the SSF and SCF is out of scope for this release.

In case of C-PVR or N-PVR with download, the SCF will check whether the target UE is authorized to record or receive the selected live content, and in the case of one UE-A scheduling C-PVR Service Capture Request for another UE-B, SCF further checks that UE-B has C-PVR terminal capabilities and UE-A is authorized by UE-B to make C-PVR Capture Requests on behalf of UE-B. Optionally, the SCF notifies the target UE of the storage requirements for the actual recording. For example, SCF calculates the required storage space according to the time duration and the content metadata information, the target UE checks the local storage capabilities and reserves corresponding space for the recording.

- 2) The SCF stores the PVR/BC information. In case of NPVR, as described in step 2A), the SCF follows relevant procedures to initiate the recording of the content by the MF. In case of C-PVR, as described in step 2B), the SCF follows procedures in clause 8.5.2.2 to initiate the recording of the content by the specified client device.

8.5.1 Network PVR service procedures

Network PVR (N-PVR) service is used by the UE to ask for a capture of live content by the network and to access it later on.

The NPVR service procedures comprise two major steps:

Step 1: Request for N-PVR Service Capture Request

The UE sends an N-PVR content capture request to the SCF. This request can be:

an impulsive request : in this case, a BC service is already activated. The UE asks the SCF to record the live content currently being watched. This may be a request to record current Broadcast Programme or a sequence of programmes from a given position in time (BC bookmark) .This is as discussed in clause 8.5.1.1.1.

an off-line request : the UE asks the SCF to record a particular live content unrelated to any active BC session. may be a request to record current Broadcast Programme or a sequence of programmes This is as discussed in clause 8.5.1.1.2.

Step 2: Request for N-PVR service

Once recorded, the user can make a request for previously recorded N-PVR request. The N-PVR content can be resumed on the same UE or different UE belonging to user from start or from the point at which the content recording was requested. The N-PVR content may have also been downloaded to the UE making local watching of the content possible.

NOTE: The case when an N-PVR service capture is done as an impulsive request and is requested later from the same or another UE from the point at which the content recording was requested can be viewed as a case of "*Park and Pickup TV*" as described in clause 3.1. In this case, the currently active Broadcast TV programme or channel that was scheduled for an impulsive N-PVR capture request can be requested at a later point on the same or different UE from the previously paused/parked point.

8.5.1.1 Signalling Flows for Network-PVR Service Capture Request

This can be handled as an off-line request or as an impulsive request.

8.5.1.1.1 Signalling Flows for Network-PVR Using Impulsive Request

Refer to clause 8.5.0A.

8.5.1.1.2 Signalling flows for the Network-PVR off-line capture request

Refer to clause 8.5.0B.

8.5.1.2 Signalling flows for Network-PVR content session

Figure 34 depicts the typical steps that occur when the UE makes a request to retrieve/resume previously recorded N-PVR content.

NOTE: If the N-PVR content has been previously downloaded to the UE, it can watch it locally without using the following procedures.




Figure 34

- 1) The SSF presents the UE with listing of available N-PVR Broadcast TV content captured via impulsive or offline capture requests, from which the user can select. In addition the "BC bookmark" information could be presented by the SSF else the UE can make a separate request to retrieve it from the SCF as specified in step (3).
- 2) The UE initiates an N-PVR session. The N-PVR session is equivalent to the CoD session. Therefore procedures defined in clause 8.4.1 apply.
- 3) The UE may request to the SCF through the core-IMS BC bookmark information pertaining to the Broadcast TV programme(s) that was previously requested to be recorded.

NOTE 1: Instead of having the UE retrieve the BC bookmark information as in Step (1) or (3), it may be possible for SCF to directly send the BC bookmark information from IPTV service action data to the MCF. Details of the procedures are out of scope for this release.

NOTE 2: This is a logical step. For efficiency purposes it may be combined with step (2).

- 4) The UE makes a request to play the content from specified bookmarked location.
- 5) This includes procedures for trick play control of the resumed BroadcastTV stream.
- 6) When the UE wishes to modify to terminate the resumed BC programme, it follows session termination procedures as specified in clauses 8.4.2 and 8.4.3.

8.5.2 Client PVR service procedures

Client PVR (C-PVR) service is used by the UE to ask for a capture of live content locally or by the remote client device and to access the recorded content later on.

NOTE: In case of local capture requests that do not need network IPTV management or authorization, the recording can be handled locally on the client without SCF involvement. The procedures for local recording on client without SCF involvement is outside scope of specification.

The C-PVR service procedures comprise three major steps:

Step 1: Initiate C-PVR Service Capture Request.

The UE sends a C-PVR content capture request to the SCF. This request can be an impulsive request or an off-line request. Impulsive request and off-line request are the same with the definitions in clause 8.5. This step is used for SCF to perform C-PVR service authorization, or where one UE schedules the C-PVR task for a future time or for another UE.

NOTE: If further mechanisms are required to protect the digital rights of the content, the system could use DRM to prohibit unauthorized access to the content.

Step 2: Request for initialization of the C-PVR recording session.

When the event for the C-PVR recording have been reached (e.g. beginning time of a TV program), the SCF initiates a request to UE to trigger the initialization of the C-PVR recording session and record the content.

NOTE: in case the UE makes an impulsive request for a C-PVR service, the existing BC session may be reused, thus the step 2 is optional.

NOTE: The SCF may not be required to trigger the C-PVR recording, e.g. in the case where the UE directly initiates a recording session by a timer, external trigger, or by user control. These procedures are out of scope of the current specification

Step 3: Access the recorded content.

Once recorded, The C-PVR content can be resumed on the UE which stored the content from the point at which the content recording was requested.

NOTE: Since the content is stored on the UE, it will not be required to have any further interaction between the UE and any other network entities to either access or play recorded content in this step.

8.5.2.1 Signalling Flows for Client-PVR Service Capture Request

8.5.2.1.1 Signalling Flows for Client-PVR Using Impulsive Request

Refer to clause 8.5.0A.

8.5.2.1.2 Signalling flows for the Client-PVR off-line capture request

Refer to clause 8.5.0B.

8.5.2.2 Signalling flows for Client-PVR recording session

Figure 34A depicts the typical steps when the SCF makes a request to initiate the recording of the content. For the scenario when the UE makes an impulsive request for a C-PVR service, the existing BC session may be reused if one exists instead of the following procedures.




Figure 34A Signalling flows for Client-PVR recording session

- 1) The SCF detects the event that triggers the C-PVR service, e.g. when the BC program is ready to be recorded. The SCF initiates a notification request to the UE designated by the C-PVR content capture request to record the content, and the notification request carries parameters to identify the content to be recorded (e.g. BC service id and or current BC Programme ID, time channel delimitation code, beginning date, end date, duration, etc.) and indicates that the content should be recorded.

NOTE: The notification request procedures are the same as sending notification using signalling path specified in clause 8.11.1.1.

- 2) UE initiates BC session initiation procedures as specified in clause 8.3.1, and after the content delivery channel setup, the UE joins multicast channels and receives multicast flows.
- 3) The UE records the multicast flows.
- 4) When the end time of the recording is reached, the UE or SCF initiates BC session release procedures as specified in clause 8.3.3.

8.5.3 PVR content update procedures




Figure 33: PVR content update procedure

- 1) The UE sends a PVR content update request to change information on existing PVR content capture request or existing PVR content. It includes the PVR content ID and the related change request:
 - Cancellation of a content capture request
 - Modification of recording parameters (e.g. time range)
 - Deletion of a recorded content
- 2) The SCF checks if the request is valid (e.g. the PVR Id exists, the time range modification is possible, etc ..) and applies the PVR content update.

NOTE: in case of N-PVR content deletion request, the SCF deletes the related entry in the PVR table for that user. It can also take appropriate action to delete the related content in case the content is recorded only for that user.

- 3) The SCF sends a PVR Content Update response to the UE via the core IMS. In case of C-PVR, the UE applies the PVR content update (e.g. it deletes the related content).

8.6 Time Shift service procedures

The Time Shift service is used by the UE to view a programme that has already occurred or started. It is necessary for the IPTV operator to store a programme in order for this service to be available. Note that unlike nPVR it is not necessary for a UE to indicate that a programme shall be recorded but it is not always the case that a programme is Time Shift enabled. The time to live for Time Shifted enabled programmes have a different expiration time compared to nPVR (example 1 week compared to possible 6 months for nPVR). For a programme that has not finished it is possible that the UE catches up with the broadcasted programme sent in real time.

The user selects timeshift content from the information provided by the SSF; just as any other CoD content. Consequently initiation and termination of time-shift sessions are exactly the same as for CoD, as described in clauses 8.4.1 and 8.4.3 respectively.

Modification of the session is also the same as for the CoD service, as described in clause 8.4.2, except for the special case when the timeshift session catches up with real time, at which time the session may be modified to switch over to multicast. In this case the same flows as for trickplay TV will be used.

8.7 Preview procedures

Editor's Note: The preview procedures for BC and COD services can be described in this clause.

8.7.1 Preview procedures for BC service

The preview content of BC service may have lower bit-rate compared with the corresponding regular BC content, hence requires lower bandwidth.

The BC content preview procedures may take place in either one of the following cases:

- 1) Multi-screen BC preview: Preview the BC service before the users decide to enjoy it in a full screen mode, where the preview content is provided through a multi-screen mode (e.g. PiP, Mosaic), or
- 2) Single-screen BC preview: Preview the specific BC program before the users decide to pay for it, where the regular BC service procedures of clause 8.3.1 apply before some notification or purchase procedure can take place.

NOTE: How the purchase procedure is activated, as well as the concrete flows for a commercial purchase are out of scope of this document.

Editor's Note: Other types of BC service preview is FFS.

8.7.1.1 Session initiation procedures for multi-screen BC preview

The procedures described in clause 8.3.1.1 apply for multi-screen BC preview session initiation, with the following differences:

- The initiation request carries the BC service IDs available for preview, and the maximum bandwidth needed for multi-screen preview. In case there is a primary stream (i.e. a regular BC service) besides the preview streams, the related regular BC service IDs are also carried in the initiation request;

NOTE: In case of multiple media channels, either a single session can be used to set up all media channels, or one session per media channel can be used. In either case, existing procedures for BC session initiation apply.

- Multiple media channels are established for multi-screen preview, and channel change is enabled for each media channel.

8.7.1.2 Procedures for transition between multi-screen BC preview and regular BC service

The transition between the multi-screen BC preview and a regular BC service may take place e.g. when one preview channel is selected for full-screen viewing.

The transition can be achieved by the actions of channel switching, channel join or channel leave, e.g. channel switching on the primary channel and channel leave/join on the preview channels at the same time.

The preview session may be modified according to the change on the network parameters, e.g. bandwidth.

8.7.2 Preview procedures for CoD service

The CoD content preview procedures may take place before the users decide to obtain some particular CoD content.

The preview content may have its own content identifier to enable the content selection (e.g. from the content guide), in which case the preview procedures can refer to procedures specified in clause 8.4.

The preview content may also share the content identifier with the regular CoD content, while variation of the regular CoD content (e.g. segment collection, lower bit-rate transcoding etc.) is delivered to the UE based on criteria such as content metadata or policy of service provider.

8.7.2.1 CoD preview procedures for sharing identifier

Editor's Note: simplification and alignment with existing CoD procedures is needed.

In this case, the preview content shares the content identifier with (related) regular CoD content, while other indicators should be present during session initiation procedure. The MF is informed by preview indications to deliver content for preview (e.g. segment collections, lower bit-rate stream).

The figure 34B depicts the steps for session initiation when CoD content preview is requested with sharing identifier with regular CoD content.




Figure 34B signalling flow for preview session initiation for CoD content

- 1) The UE initiates a request for the CoD content preview. The request includes the regular CoD content identifier, with specific indicator for content preview.
- 2) The preview session initiation request is routed by the Core IMS entities up to the SCF in charge of the requested CoD preview service.
- 3) The SCF identifies the session initiation is for content preview and performs service authorization. If the UE is allowed to preview the content, the SCF forwards the session initiation request to the selected MF, including preview indication for the CoD content.

NOTE 1: In step 3 the preview indication shall be subject to some type of criteria, e.g. content metadata.

- 4) Signalling procedures for establishment of a content control channel and optionally content delivery channels for the content preview take place between the UE and the MF as described in clause 8.4.1.2.
- 5) The MF confirms the establishment of the dialogue with the UE.
- 6) The SCF forwards this confirmation to the Core IMS.
- 7) The P-CSCF within the Core IMS interacts with the RACS to commit all resources previously reserved. This includes opening pinholes for exchanging content control messages and/or content delivery.

- 8) The P-CSCF forwards the dialogue confirmation to the UE.
- 9) After the Content control and/or delivery channel is established MF delivers preview content to UE regarding the preview indication obtained in step 3.

8.8 Parental control procedures

Editor's Note: The parental control procedures can be described in this clause.

8.9 UGC procedures

Editor's Note: The procedures for UGC service can be described in this clause.

8.9.1 Overview

There are two types of UGC procedures :

- **creation of the User Generated Content:** this type of procedure allows a user to declare and upload/upstream his/her own content to the network ,
- **watching of User Generated Content that has already been created:** this type of procedure allows a user to select and watch User Generated Content that has already been created.

NOTE: The clause 8.9.3 UGC watching procedure may start before the clause 8.9.2 UGC creation procedure has been completed (see e.g. TS 181.016 [13B] clause A.9.1.2 "Use case: Home movie sharing, streaming").

8.9.2 UGC creation procedure

The UGC creation procedure comprises four major steps:

Step 1: Declaration of User Generated Content.

- The UE sends a User Generated Content creation request to the SCF and receives a content ID for the UGC from the SCF. The content ID is independent of the address where the UGC can be retrieved by other UEs.

Step 2: Publication of User Generated Content information by the UE

- The UE sends a request to the SCF that contains a description of the User Generated Content (name, type, restriction, textual description, , special group users etc ...). This request may be combined with the User Generated Content Declaration request in step 1.

Step 3: Creation of User Generated Content

- The UE initiates a session with the SCF and MF in order to create the User Generated Content (i.e. upload/upstream (unicast) the content to the MF). The MF provides the SCF with the location at which the UGC becomes available.

Step 4: Publication of User Generated Content information by the SCF

- The SCF establishes the relationship between UGC content ID, UGC description ,and optionally the MF, and publishes this UGC description information. The UGC description publication by the SCF in step 4 may take place before, during or after the UGC content creation delivery session initiation creation in step 3.

NOTE: In general, the UGC procedures should allow for all forms of SCF-MF interaction as described in clause 5.2

Step 1 is always the first step. Step 2 may happen at any time during the UGC creation and can be repeated during the lifetime of the content. Editor's note: Mechanisms for validation of publication of UGC content description may need to be considered. How to keep the published UGC content description accurate or whether it is needed is FFS.

NOTE: UE publishes the UGC description to SCF, optionally it may be audited by the SCF or the management entities. As a result of this audition the UGC description may be rejected or a revision of the description may be required. Also the UGC content may also be audited. The mechanisms for UGC description and content auditing are out scope of this specification.

Figure 34B depicts the typical steps that occur when the UE creates UGC.




Figure 34B: UGC creation

- 1A) The UE sends a UGC Declaration Request through the Core IMS to the SCF
- 1B) The SCF records the UGC information and sends a UGC Declaration Response including a UGC content ID through to core IMS to the UE..
- 2A) The UE sends a UGC Description Request through the Core IMS to the SCF. The request contains a description of the User Generated Content (name, type, restriction, textual description, , special group users etc ...).
- 2B) The SCF records the UGC description, establishes the relationship between UGC ID and UGC description and sends a UGC Description Response through to core IMS to the UE.

NOTE: Steps 2A/B can be done either after steps 1A/1B or combined with steps 1A/1B.

- 3) The UE initiates a UGC creation session, including a content upload/upstream channel to the MF. The content upstream procedure is similar to the one defined in 8.4.1.1 figure 21 for CoD initiation procedure (steps 3-6 and 9-11). The content control channel may not be required. The content upload procedure is specified in 8.18.1 figure 39A. The session initiation response from the MF to the SCF includes the location on which the UGC becomes available.

- 4) The SCF establishes the relationship between UGC ID, UGC description and optionally UGC location (address), and publishes this UGC information.

The UE can modify or terminate the established UGC creation session later on .

NOTE: Updating the SSF for UGC information from the SCF is required, but the method for achieving this is out scope of this specification.

NOTE: In a particular protocol realization, the messages supporting steps 1 and 2 may be embedded in the messages supporting UGC session initiation.

For a UGC creation session initiated by Remote UE, the Remote UE starts-up the UGC content creation service according to the procedures of service initiation by remote UE specified in clause 8.25 which indicates the UGC service for the Target UE to upload/upstream UGC content. Then the Local UE initiates the UGC creation procedure using the same steps in figure 34B.

Editor's note: it is FFS whether UE can send multicast stream to ECF/EFF.

8.9.3 UGC watching procedure

The UGC watching procedure comprises two major steps:

Step 1: Selection of UGC

- The selection of the UGC may be done through the SSF. Alternatively, UGC selection can be triggered by a content recommendation or a notification. The UE may also pre-select UGC that has already been declared and published (clause 8.9.2, steps 1, 2 and 4), but not yet created (clause 8.9.2, step 3).

NOTE: Other ways of selecting UGC (notification from another UE) are out of scope of this release.

Step 2: Watching of UGC.

- Session initiation can be performed by the UE or the SCF in order to watch the selected UGC. The UGC watching session is equivalent to the CoD session. If the UE has previously pre-selected UGC that had already been declared and published but not yet created (see above), then this UGC will be delivered in an SCF-initiated CoD session (clause 8.4.1. Figure 21A) when the UGC is created.

Figure 34D depicts the typical steps of the UGC watching procedure.




Figure 34D: UGC watching procedure

- 1) The UE selects UGC through service selection procedure with SSF as defined in clause 8.2 step 4. The SSF may restrict the list of UGC depending on user identity and UE capabilities. Alternatively, UGC availability is triggered through the notification procedure from the SCF as defined in clause 8.11.1 or recommendation procedure from the SCF as defined in clause 8.13. The UE may also pre-select UGC that has already been declared and published (clause 8.9.2, steps 1, 2 and 4), but not yet created (clause 8.9.2, step 3). The SCF then stores this pre-selection of UGC.

Editor's note: A procedure should be added for pre-selection of UGC.

- 2) The UE or the SCF initiates a UGC watching session. The UGC watching session is equivalent to the CoD session. Therefore procedures defined in clause 8.4.1 apply. When the SCF detects that pre-selected UGC becomes available (i.e. its creation, as described in clause 8.9.2 step 3, is starting or has been completed), then this UGC will be delivered in an SCF-initiated CoD session (clause 8.4.1. Figure 21A).

When the UE wishes to modify or to terminate the UGC session, it follows session modification/termination procedures as specified in clauses 8.4.2 and 8.4.3.

Editor's note: UGC session established through a BC session for multicasted content is FFS.

8.10 Personalized channel (PCh) service procedures

Editor's Note: Since there maybe potentially more than one options for this feature, the section of Pch may be organized in the following way:

- One section describes the common procedures.
- A second section describes the MF-centric option where a unicast session is used for all contents including BC.
- A third section describes the option where the session alters between unicast and multicast depending on the viewed content.

PCh service allows the users to tune in a single (virtual) channel and watch one or multiple pre-configured content items identified in the service profile (PCh information).

Before the PCh service is available to the user, the configuration procedure shall take place, through which particular IPTV content items (e.g. program from some BC service, movie from some CoD catalogue) are selected and scheduled in the PCh information.

The UE retrieves the specific PCh information from the SSF via service selection procedure as described in 8.2.

Before the user can view the content items in the PCh information, a session initiation procedure for the PCh service shall take place.

The figure 34E depicts the overview of PCh service procedures




Figure 34E Overview of PCh service procedures

- 1) The PCh declaration procedure takes place between UE and SCF. The UE sends a PCh Declaration Request to the SCF via Core IMS, and the initial PCh information, containing the PCh id, is created and returned based on user profile and content metadata.
- 2) The PCh Configuration procedures takes place between SCF and UE (e.g. add an item to the list, remove an item from the list, arrange the schedule), as described in clause 8.12 upon user's decision. The SCF saves the PCh configuration, e.g. the time schedule for each PCh content item. SCF may accept or reject the overlap between content items.
- 3) The selection procedure of PCh information takes place either between UE and SSF as described in clause 8.2 or notification procedures between UE and SCF as described in clause 8.11.1 or recommendation procedures as described in clause 8.13. During this step, the UE retrieves the PCh id and other necessary network parameters (e.g. the bandwidth requirement) to facilitate the initiation of PCh session (i.e. step 3). Optionally the time schedule can be also provided in this step.
- 4) The PCh session initiated by the UE, as similar with the one defined in 8.4.1 for CoD initiation procedure with the following differences:
 - The session initiation request from the UE contains the PCh id as the CoD content id;
 - The SCF retrieves the PCh information (e.g. list of content to be played with the time schedule of each item) and sends it to the selected MF in addition to the PCh ID. The SCF may send either part of the PCh

list (e.g. the first item) or the entire PCh information to the MF, for the purpose of content channel negotiation.

- 5) When there is overlapping between two PCh content items, the SCF handles the conflict items according to the user policy or SP policy. E.g. for overlapping handling may be as following: The play of ongoing item continues and following items are postponed, then the SCF initiates a PCh control message towards MF, carrying the updated PCh schedule (i.e. the upcoming item is postponed);
- 6) Based on the current time, the SCF sends PCh control message to the MF via Core IMS, indicating the delivery of the upcoming PCh content item. The PCh control message contains the upcoming PCh item id(s) within the PCh list, as well as the time schedule of each item.

NOTE: The PCh control message may be used in the following cases:

- a.) The SCF does not send all of the PCh information to the MF in session initiation(i.e. in step 3), or
- b.) New breaks or overlapping occurs for an ongoing session because of user's trick play operation.
- 7) The PCh session may be modified if the reserved resource is not sufficient for the upcoming PCh item, e.g. due to higher bandwidth requirement. In this case the MF-initiated session modification procedure described in clause 8.4.2 applies.
- 8) The indicated PCh content is delivered to the UE through the unicast content delivery channel established during step 3. The MF needs to fetch the content in from MDF or from other content sources. The MF may also perform the content adaptation or conversion before the unicast content is sent out to UE, e.g. multicast-unicast conversion, transcoding etc.

NOTE: The steps 5~8 can be repeated during the life time of PCh session, for the purpose of switch among multiple content items.

NOTE: How the MF fetches the PCh content item from the content source is out scope of this specification. In specific implementations, the MF contacts the source via file transfer or joins a BC multicast group to receive the indicated content.

Editor's note: The switching between unicast and multicast content is FFS

- 9) Initiated by the UE or the network, the PCh session is terminated at some time, as the ones defined in 8.4.3.

Editor's Note: Other procedures for personalized channel service can be included.

8.11 Interaction procedures with other IPTV Services

Editor's Note: The procedures for interaction with other IPTV services can be described in this clause.

8.11.1 Notification procedures

Notification procedure can be used for several purposes: notification that a CoD is available based on user's prior subscription to that information, caller-Id on TV screen, reminder from a particular TV program based on user's setting, etc ...

8.11.1.1 Notification procedures using signalling path

Figure 35 depicts the typical steps that occur when the SCF wants to notification the user on a particular event using signalling path.




Figure 35: notification procedure using signalling path

Prior to the procedure, it is considered that the SCF has detected an event that would cause the notification to be sent to the UE. For example, it can be informed of an incoming call to the user. It could also be based on user's subscription dealing with a notification to be sent when a particular BC program/CoD content is available.

- 1) Based on the service logic, the SCF sends an Notification Request to the UE via the core IMS. The message shall contains at least:
 - i. the reason of the notification: Examples include incoming phone-calls, CoD content or TV program notification based on reminder/subscription set by the user
 - ii. related parameters: Examples include calling-number/URI, CoD content identifier or BC service ID, service provider id of the associated SSF from where the update service information may be retrieved, etc.

- 2) The core IMS forwards the Notification Request to the UE.

NOTE: The Notification may be displayed to the user.

- 3) The UE answers to the SCF via the core IMS.
- 4) The Notification Response is forwarded to the SCF.

After this step, the UE can take appropriate action (e.g. initiate a CoD session) based on user's decision.

8.11.1.2 Notification procedures using multicast media path

Figure 35A depicts the steps that occur when the SCF and MF use the multicast media path to send a notification to users who are watching a specific BC channel.




Figure 35A: notification procedure using multicast media path

When receiving a notification trigger event from external entity (e.g. SCF in charge of BC service) or detecting an internal notification trigger (e.g. SCF detects that it should send a notification to users who have subscribed to the content recommendation service for an upcoming BC program) or receiving a message need to be delivered using media path, the SCF would send notifications to users who are watching a specific BC channel. If the users want to receive the notification, they will have joined the specific notification multicast stream in addition to the BC service multicast streams.

- 1) SCF sends the notification to the selected MF (e.g. SCF retrieve MF from local configured information) via Core IMS. The notification request shall contain at least:
 - i. The reason of the notification: e.g. upcoming programs, floating ad or weather forecast.
 - ii. Related parameters: e.g. BC service ID, service provider id etc.

NOTE: As stated in TS 123 506 [2], an Application Server may originate requests to a destination without involving the S-CSCF. This capability should be used if SCF sends the notification to MF directly without Core IMS involved

- 2) MF delivers the notification to the specific notification multicast group.

NOTE: The multicast address for the notification channel may be pre-configured on the MF or it may get it from the notification request in step 1. Other options may be possible and out of scope of specification.


- 3) The UE receives the notification from ECF/EFF and displays the notification to the user.

NOTE: Before step 3 could take place, UE should first discover the specific multicast group information for the notification (e.g. through the Service Discovery and Selection procedure) and then join the notification multicast group.

The UE can take appropriate action based on the user's decision.

8.12 Procedures for IPTV User Profile Configuration

This clause describes the generic procedures for IPTV user profile configuration. These procedures may be used in conjunction with other procedures for delivery of other IPTV services - e.g. Content recommendation service, NPVR.



- 1) The user (on UE) makes a request to the SCF to configure IPTV User profile settings
- 2) The SCF shall perform relevant authentication and authorization of the User Profile Configuration request by the user before permitting the request. The SCF records the profile settings as part of the IPTV user profile information as described in clause 7.3.1.

NOTE: In case the UE needs to directly contact a network functional element, (e.g. Service Control Function), it should perform GBA authentication, for key management purposes, during the session start-up phase. Please refer to TS 187 003 [5].

- 3) The UE is informed of the result of the IPTV user profile service configuration request

8.13 Content Recommendation service procedures

The content recommendation service (CRS) is used for providing recommendations to IPTV users or user groups.

The content recommendation service may make recommendations to user/groups based on different criteria which include user profile preferences settings, current viewing habits of user etc.

The CRS service procedures include 3 major steps:

- 1) CRS event detection. The events include request from the UE, new content arrival notification, presence update, trick play reports from MF, channel change report from UE etc. This step is triggered due to the user subscription or service provider's policy, and it may also be based on user request (e.g. for sepecific program or during specific time period).
- 2) CRS information generation for specific user. The CRS info includes one or more identifiers of the recommended content. The user profile (e.g. user preference, watching habits etc) is used for filtering/sorting of CRS info.
- 3) CRS information delivery to the UE. SCF sends the generated CRS information to specific UE(s).

In the case when user profile settings are used for making content recommendations, the user preferences in IPTV profile are configured using procedures described in clause 8.12

The CRS information is delivered to the UE by the SCF using notification procedures as described in clause 8.11. The UE may subsequently fetch the details about the recommended content from the SSF via procedures described in clause 8.2.

Editor's note: Other mechanisms for delivery of content recommendations is FFS

Figure 35C depicts the typical steps for CRS.




Figure 35C signalling flows for CRS provided by SCF

- 1) UE may optionally send a request to the SCF for CRS information notifications.

NOTE: This step is optional in case the user only wants to get notified during specific content play back or specific time period.

- 2) The SCF detects the CRS events based on user profile, user request or service provider's policy.
- 3) The SCF generates the requested CRS information for specific user. The CRS information includes one or more identifier(s) of the recommended content.

Editor's Note: How to generate the program related CRS information on the SCF is FFS.

- 4) SCF sends UE the generated CRS information using notification procedures described in clause 8.11.1.1.

8.14 Advertising (Ad) service procedures

There are several types of procedures in Advertising (Ad) service, including:

- 1) **Targeted ad insertion:** some selected ad content is provided to the UE during the IPTV content playback, based on the user profile (user preference, shopping habits, location information, etc.) and the IPTV service status (e.g. current BC program, commercial breaks or pause during content playback). Content replacement or multi-window rendering takes place within the insertion time period.
- 2) **Pull mode Advertising:** Advertising is content in its own right and can be selected by the UE, and the users can actively retrieve or interact with the ad content. Audio-visual content of this ad type can be provided to the users via similar procedures with CoD or BC. Other procedures for non audio-visual ad content provision, such as interactive ad and banners, may also be described here

- 3) **Broadcast based Ad-insertion:** Ad content (local or regionalized) is inserted into the IPTV content that is broadcasted to the UE without factoring in any information related to user profile. Such ad content is not targeted any any specific user or user groups but it may be targeted to regions or zones depending on network topology.

Editor's note: The exact location of the above text within the spec is FFS and is subject to whether there is any procedural impact on any of the functional entities

Editor's note: The requirements on "traditional broadcast advertising" in TS 181 016 needs to be updated/removed to be aligned with this specification

NOTE: other procedure types of Ad service can be included.

These Ad procedures shall conform to one of the following architecture options:

- Internal option in which advertising tasks done by entities within the TISPAN IPTV system
- External option in which an external Advertising sub-system interconnected with TISPAN entities

NOTE: In the second option, the SCF acts as a broker to bundle information from IPTV user profile and service profile along with information on placement opportunities and sends it over to the external advertising sub-system which responds back to SCF with the ad-placement decisions decisions .

All of the above architectural options are documented in Annex E, F. The upcoming section discusses a generic architecture that can be instantiated into any of the architectural options in Annex E, F

8.14.1 Generic Procedures for targeted ad insertion (TAI)

Ad insertion implies that an IPTV session exists prior to the insertion time. The targeted ad is selected by the SCF with regard to user profile (e.g. shopping habits) or other criteria, e.g. current BC program.

IPTV content and ad content in the context of ad insertion can be described as:

- **IPTV content:** the content to be partially (or entirely) replaced during the IPTV session. There is usually some cue/hint related to the IPTV content used to trigger ad insertion, e.g. insertion time in content metadata or insertion points in the actual content itself where a targeted ad can be inserted to replace an existing default ad
- **Ad content:** the content which is inserted to the IPTV content during the ad insertion time, or to replace a default ad. The ad can be rendered sequentially or in parallel with the IPTV content.

The ad insertion can be performed at either UE side or MF side:

- When UE performs ad insertion, it is informed of ad insertion indication, it can receive both IPTV content and ad content at the same time, and renders them in a sequential or simultaneous way. The UE could also have the ad content stored locally through off-line means.
- When MF performs ad insertion, it is informed of ad insertion indication, it can retrieve or receive the ad content, and delivers the combined IPTV stream and ad to the UE.

The major steps of TAI is as follows:

- 1) IPTV service status detection/awareness.

The SCF is responsible for the awareness/detection of the user's IPTV service status. The SCF shall reuse the existing procedures for IPTV service state detection.

Note that there are certain cases where the MF can undertake and/or complement some of the SCF roles. Examples are commercial breaks in the BC service or pause during CoD playback.

Editor's note: Contributions are invited to describe the tasks of the MF and the relation of FEs for IPTV service state detection.

Editor's note: Contributions are invited to define the IPTV service state, and to define the means that allows the SCF to detect them (for example the detection of commercial break

2) Identification of Targeted Ad Insertion Points

Places to insert Ad could be known in advance (predetermined) or detected during the play (unexpected).
More details on Ad placement in Annex G.

3) Ad Content Selection

One or more ad content(s) is selected with regard to user profile (e.g. shopping habits, user preference etc).
The user's IPTV service status and/or the metadata of current content can also be used for locating of ad content targeted to specific user or user group.

4) Ad content delivery

The selected ad content is delivered to the UE, before or after which essential ad insertion is performed (i.e., either at MF side or UE side)

8.14.2 Generic Signalling for Targeted Ad insertion

NOTE: Term *Ad Server* is used for the generic purpose of Ad selection and/or control, and it can be instantiated depending on Annex E, as follows:

- In case of internal option (Annex E.2), the Ad Server is instantiated to another SCF that is in charge of Ad service, i.e. service control;
- In case of SCTE option (Annex E.3), the Ad Server is instantiated to ADS that is responsible for targeted ad decision;
- In case of OMA option (Annex E.4), the Ad Server is instantiated to Ad Server that is responsible for targeted ad selection;

8.14.2.1 signalling flows for TAI at UE side

When the ad insertion takes place at UE side, the UE and the MF are informed about ad insertion information from SCF. The UE may initiate individual session request for Ad content, which implies that multiple sessions exist on the UE during the ad insertion time. Other means for retrieving the content are also envisioned

Figure 36 depicts the typical steps when UE is informed of targeted ad insertion information.




Figure 36: Signalling flows for UE performing TAI

- 1) An IPTV session is established between UE and SCF(BC/CoD/..) as described in clause 8, e.g. BC session in clause 8.3, CoD session in clause 8.4 etc., and some IPTV content is delivered to the UE.
- 2) The SCF detects the ongoing IPTV service status (e.g. the current BC program ID, the commercial break of the program, the current CoD content id, the trick-play events etc) of the specific user and decides to trigger ad insertion. Detection of the IPTV service status is done based on IPTV Service Action Data or using IPTV Presence information

Note that there are certain cases where the MF can undertake and/or complement some of the SCF roles.
Examples are commercial breaks in the BC service or pause during CoD playback

Editor's note: Contributions are invited to describe the tasks of the MF and the relation of FEs for IPTV service state detection.

Editor's note: Contributions are invited to define the IPTV service state, and to define the means that allows the SCF to detect them (for example the detection of commercial breaks)

- 3) 3a, 3b and 3c are instantiated depending on the selected option in Annex E. The SCF sends a request to the target ad server for the user. The target ad server selects the appropriate target ads which can be inserted in the currently streamed content, as well as the advertisement opportunities (as insertion information). The ad server sends the selected target ad information as well as the ad insertion information to the SCF. In step 3D, The SCF sends this information back to a selected MF. The means by which the MF acquires the ad content is outside scope
- 4) The SCF sends UE the notification of ad insertion information, using procedures specified in clause 8.11.1. The ad insertion information can include the selected ad content identifier, the user id, insertion time (begin time and/or length), and other information needed for ad insertion. Other means for conveying the same information are also possible
- 5) In order to retrieve the ads, the UE can perform session modification procedure in case the MF for the target ads is the same MF from which the streaming of the actual content occurs. Optionally, other mechanisms such as off-line mechanisms can be also used to deliver the target ads to the UE. Finally, the UE can initiate a

separate session to MF that includes the target ad content. During this step the procedures described in clause 8.3.1/8.3.2 for BC session or 8.4.1/8.4.2 for CoD session applies, with SCF(Ad) responsible for the Ad service control and MF(Ad) responsible for Ad content control and delivery

- 6) The UE performs the ad insertion, i.e. renders the ad content embedded within the actual content or in parallel with the ongoing IPTV content (e.g. in PiP).
- 7) When the ad insertion time is up, the session for ad content is released as procedures described in clause 8.3.3 or 8.4.3, and UE resumes the rendering of the IPTV content.

8.14.2.2 Signalling flows for TAI at MF side

When the ad insertion takes place at MF, the MF is informed of the ad insertion information from the SCF. The MF performs the ad insertion, i.e. delivery ad content to the UE during the ad insertion time of IPTV content play back.

Figure 37 depicts the typical steps when MF is informed of the ad insertion indication.




Figure 37: Signalling flows for MF performing TAI

- 1) An IPTV session is established between UE and SCF(BC/CoD/...) as described in clause 8, e.g. BC session in clause 8.3, CoD session in clause 8.4 etc., and some IPTV content is delivered to the UE
- 2) The SCF detects the ongoing IPTV service status (e.g. the current BC program ID, the commercial break of the program, the current CoD content id, the trick-play events etc) of the specific user and decides to trigger ad insertion. Detection of the IPTV service status is done based on IPTV Service Action Data or using IPTV Presence information

Note that there are certain cases where the MF can undertake and/or complement some of the SCF roles. Examples are commercial breaks in the BC service or pause during CoD playback

Editor's note: Contributions are invited to describe the tasks of the MF and the relation of FEs for IPTV service state detection.

Editor's note: Contributions are invited to define the IPTV service state, and to define the means that allows the SCF to detect them (for example the detection of commercial breaks)

- 3) 3a, 3b, and 3c are instantiated depending on the selected option in Annex E. The SCF sends a request to the target ad server for the user. The target ad server selects the appropriate target ads which can be inserted in the currently streamed content, as well as the advertisement opportunities (as insertion information). The ad server sends the selected target ad content information as well as the as insertion information to the SCF. In step D, the SCF sends this information to the MF. The ad insertion information can include the selected ad content identifier, the user id, insertion time (begin time and/or length), and other information needed for ad insertion. The means by which the MF acquires the ad content is outside scope.
- 4) The MF(BC/CoD/...) may perform transcoding if the codec of ad content is not supported by the UE. In the case when the ad content is delivered at part of the on-going IPTV content, the MF (BC/COD) shall use the cue-messages to determine when to insert the appropriate ad content.

For ad-content that is delivered separately from the IPTV content, the cue messages are used to determine when to switch to ad content. The MF may perform session modification if needed

- 5) The ad content is provided to the UE during the ad insertion time, or the streamed content includes the ads.

8.15 Procedures for inter-destination media synchronization

8.15.1 MSAS – SC

8.15.1.1 SCF-based media synchronization

8.15.1.1.1 Mapping 1: SC in UE

Figure 38 provides an overview of the information flows for inter-destination content synchronization according to Mapping 1 from clause 5.4.2.




Figure 38: Procedure for inter-destination content synchronization.

(1)-(7) Broadcast session initiation according to clause 8.3.1.1.

The following steps (8)-(14) are all tunnelled over the broadcast session established in steps (1)-(7).

(8) The UE (SC) sends a synchronization initiation request to the SCF (MSAS), indicating that it wants to participate in the inter-destination synchronization process. The request includes the BCServiceId of the to-be-synchronized BC channel.

(9) The SCF confirms the participation of the UE in the inter-destination synchronization process.

(10) The UE sends its synchronization status information to the SCF.

(11) The SCF aggregates synchronization status information from multiple UEs and calculates the appropriate synchronization settings for each UE.

NOTE: Examples of algorithms to calculate the synchronization settings instructions from collected synchronization status information may be found in [25].

(12) The SCF sends a synchronization settings instruction to the UE.

Steps (10) - (12) may be repeated at regular time intervals.

(13) The UE sends a synchronization termination request, indicating that it is no longer active in the inter-destination synchronization process. This could be e.g. because of a channel change by the UE.

(14) The SCF confirms the termination of the UE's participation in the inter-destination synchronization process

NOTE: The UE can initiate and terminate multiple synchronization sessions within a broadcast session, both consecutive and simultaneous.

The above procedures are also applicable for the inter-destination media synchronisation for CoD, N-PVR, Ad, UGC and Shared Content with the following changes.

- The session in steps (1)-(7) is a CoD, N-PVR, Ad, UGC or Shared Content session, respectively.
- In case of CoD, the request in step (8) includes the CoDId (see clause 7.4.1)
- In case of N-PVR, the request in step (8) includes the NPVRContentId (see clause 7.4.1)
- In case of Ad, the request in step (8) includes the ad content id (see clause 8.14.1)
- In case of UGC the request in step (8) includes the UGC content id (see clause 8.9.2)
- In case of Shared Content the request in step (8) includes the SSC Room Identifier (see clause 8.21.2)

Editor's Note: It is for further study to define a term for the super-class of BCServiceId, CoDId, NPVRContentId, ad content id, UGC content id, the Shared Service Identifier and those yet to be defined. A suggestion is "Content Service Id", as all the identifiers identify a specific instance of a content service.

8.15.1.1.2 Mapping 2: SC in Transport

The procedures according to Mapping 2 from clause 5.4.2 are the same as above with the following changes.

- Steps (1) to (7) are not applicable.
- Tunnelling over the broadcast session is not applicable
- The MSAS is an elementary function of the SCF or a stand-alone Application Server.
- The SC is an elementary function of the Transport Functions.
- The request in step (8) includes a media stream identifier.

NOTE: If the MSAS serves SCs according to both Mapping 1 and Mapping 2 for a specific IPTV service, then the MSAS has to correlate the BCServiceId, CoDId, etcetera in Mapping 1, with the appropriate media stream identifier in Mapping 2.

8.15.2 MSAS – SC'

Figure 38A shows a flow for the exchange of synchronization status information between a media-stream-modifying Synchronization Client (SC') and an MSAS.




Figure 38A: Media synchronization in case of media-stream-modifying SC'.

(1) The MSAS sends a synchronization initiation request to the media-stream-modifying SC', indicating that the SC' will participate in the inter-destination synchronization process. The request includes an identification of the to-be-synchronized media stream(s).

(2) The SC' confirms its participation in the inter-destination synchronization process.

(3) The SC' sends synchronization status information on the synchronicity relationship between incoming and outgoing media streams to the MSAS.

(4) The MSAS returns an acknowledgement message to the SC'.

Steps (3) - (4) may be repeated at regular time intervals.

(5) The MSAS sends a synchronization termination request, indicating that the SC' is no longer active in the inter-destination synchronization process for the identified media stream(s).

(6) The SC' confirms the termination of its participation in the inter-destination synchronization process

8.16 Signalling flows for network-controlled trick play

Figure 39 provides the signalling flow for controlling trick play of a Broadcast TV channel, CoD or N-PVR session by a network element. In order to apply trick modes to a Broadcast TV channel, a BC TV with trick play session must first be established.




Figure 39: Signalling flow for network-controlled trick play

- 1) Broadcast TV, CoD or N-PVR session initiation.

NOTE 1: The Broadcast TV, CoD or N-PVR sessions shall be initiated by the appropriate procedures in clauses 8.3.1 8.4.1 and 8.5.2, respectively.

- 2) Based on an event detected by the SCF, e.g. a trigger received from an external application, the SCF sends a notification to the UE to request stream control. The notification procedure from Clause 8.11.1.1. shall be applied. The notification response includes media action data.

Editor's note: the reason and relevant parameters contained within the notification request are for further study and can be worked out in stage 3.

- 3) If the existing session is a Broadcast TV session, a transition from BC TV to BC TV with trick play takes place according to Clause 8.3.5.
- 4) The UE uses the content control channel to perform the trick play command, e.g. "pause", "fast forward", etc.

NOTE 2: How the SCF is triggered by external applications and how media action data is sent from the SCF to external applications is not described by this procedure.

8.17 Push Procedures

8.17.1 Push CoD session

Push CoD session comprises two main steps:

- Step 1: The SCF initiates the CoD content download from MF to UE. The detailed procedure can be referred to clause 8.18.2.
- Step 2: The UE selects the media content in its storage device which has been downloaded from MF and views it.

NOTE: The content is stored on the UE after step 1, hence in step 2 it is not required to have any further interactions between the UE and the network entities to either access or play the content.

8.18 Unicast Content Upload/Download Procedures

The procedures described here are for upload/download cases distinguished from streaming cases (described in 8.4).

NOTE: The generic content upload/download procedures described below can be referred by IPTV services such as UGC upload/download, Ad etc.

The unicast content upload/download session may be initiated by either by UE or SCF.

8.18.1 Signalling Flows for UE-initiated Unicast Content Upload/Download

Figure 39A depicts the typical steps that occur when the UE initiate a request to upload/download content by unicast.




Figure 39A UE-initiated unicast content upload/download session initiation

- 1) The UE initiates an upload/download request to the SCF.
- 2) The session initiation request is routed by the Core IMS entities up to the SCF.
- 3) The SCF performs service authorization. If the UE is allowed to upload/download contents, the SCF forwards the session initiation request to the selected MF which handles media content upload/download.
- 4) Signalling procedures for the establishment of content upload/download channel take place between the UE and the MF. The procedure of content channel negotiation is similar as the one defined in 8.4.1.2, but the media control channel is not needed here. During the negotiation, the MF offers UE the location of the uploading/downloading content for content upload/download.
- 5) The MF confirms the establishment of the dialogue with the UE.
- 6) The SCF sends this confirmation to the Core IMS.

- 7) The P-CSCF within the Core IMS interacts with the RACS to commit all resources previously reserved. This includes opening pinholes for exchanging content delivery.
- 8) The P-CSCF forwards the dialogue confirmation to the UE.

8.18.2 Signalling Flows for SCF-initiated Unicast Content Download

Figure 39B depicts the typical steps that occur when the SCF initiate a request to download content by unicast.




Figure 39B Signalling flows for SCF-initiated unicast content download

- 1) The SCF identifies the media content which will be downloaded to the UE, and then sends a download session initiation request to the UE (described in clause 8.4.1.1 Figure 21A from step 1 to step 4).
- 2) The UE check if it will accept the media content.

NOTE: The checking criteria can include one or more methods such as its storage capability to compare with size of the media content, the configuration of the UE if it will accept the media content, the selection of the User if the user accepts the content.

- 3) If the UE accepts the request, signalling procedures for establishment of media content download channel take place between the UE and the MF based on the procedures in 8.4.1.2
- 4) The UE confirms the establishment of the dialogue with the SCF and commit the resource previously reserved. (described in clause 8.4.1.1 Figure 21A from step 6 to step 11).
- 5) After this point, the selected MF can deliver the media content to the UE (ie. media content download to the UE). UE saves it in its storage device.

8.19 Multicast Content Download Procedures

The procedures described here are for download cases distinguished from streaming cases (described in 8.3).

NOTE: The generic content download procedures described below can be referred by IPTV services such as UGC upload/download, Push CoD etc.

The multicast content download session may be initiated by either by UE or SCF.

8.19.1 Signalling Flows for UE-initiated Multicast Content Download

Editor's Note: The multicast procedures for UE-initiated content download can be described in this clause.

8.19.2 Signalling Flows for SCF-initiated Multicast Content Download

Editor's Note: The multicast procedures for SCF-initiated content download can be described in this clause.

8.20 signalling flows for restricted trick play

The restricted trick play procedure can be used by network to disallow specified trick play functions on any segment of the content.

Figure 39C depicts the typical signalling flow of restricted trick play.




Figure 39C procedure of restrict trick play

- 1) Broadcast TV with trick play, CoD session initiation. The Broadcast TV with trick play session use the procedures specified in clauses 8.3.1, and the CoD session use the procedures specified in clauses 8.4.1.
- 2) SCF acquires the restriction policy on trick play according to the information of initial request, e.g. the content ID, user ID.

NOTE 1: For example, SCF may fetch the pre-configured restriction policy from the content metadata based on the CoD content ID; SCF may also generate the restriction policy based on the user subscription data and/or the content ID.

- 3) SCF transmits restriction policy to MF, and informs MF to implement restriction.

- 4) When the MF receives UE's content control requests specified in clause 8.4.1 (Signalling flows for CoD session initiation), MF executes the restricted trick play according to the policy, such as deny return a forbidden response to UE in case trick play is disallowed.

NOTE 2: The steps 2 and 3 may happened at any time during or after the step1 initiation session.

8.21 Shared Service Control (SSC) procedures

8.21.1 Overview

Shared Service Control procedures allow a group of users sharing the control commands related to a service (e.g. BC, CoD) and correlating the sessions related to the same service.

The virtual place established to share the services is called an SSC room. This room has only one service running at a time ; this service may be BC / CoD / UGC / NPVR / PCh services as defined in the present specification.

The following figure gives an example of shared service control between two users.




Figure 39D

SSC procedures comprise three types:

- **creating an SSC room:** this type of procedure allows a user to create an SSC room, indicating a list of users associated to the room, policies and related rights. Optionally, the room is associated with a specific service.
- **selecting and entering an SSC room:** this type of procedure allows a user to select an SSC room and to enter it. Optionally, a service is selected (e.g. BC, CoD), linking it to a room. The procedure ends with initiating the related session.
- **controlling the service:** this type of procedure allows a authorised user to perform service control commands (e.g. trick-play, channel change) to the service associated to the room.

8.21.2 Room creation procedure for SSC

Figure 39E depicts the typical steps that occur when the UE creates an SSC room and publishes related information.




Figure 39E: SSC Room Creation procedure

1A) The UE sends a SSC Room Creation Request through the Core IMS to the SCF. This request may contain information such as:

- the service identifier if the room is associated with only one service item,
- and optionally additional information such as a list of users allowed to join the room and associated rights (e.g. trick-play authorisation on the content, initiation of a service linked to the room).

1B) The SCF checks if the user has the rights to create the room and records the SSC room information. It sends an SSC Room creation Response including the SSC room identifier through to core IMS to the UE..

2) Publication of SSC room information. The SCF may optionally publish the information about this new SSC room to the users in the list indicated in SSC room creation request.

NOTE: This procedure can be repeated when the service is being shared in order to update SSC room information. In that case the request will indicate the SSC room identifier.

8.21.3 Room selection procedure for SSC

The room selection procedure comprises the following steps:

Step 1: SSC room selection .

- Using the SSC room identifier, the UE selects the room it wants to join and retrieves associated parameters

Step 2: Entering the selected SSC room

- The UE enters the room and initiates a service session. If no service is associated with the room at the time of entering, the UE first selects a service.

Figure 39F depicts the typical steps that occur during the room selection procedure.




Figure 39F: room selection procedure for SSC

- 1) The UE selects a SSC room based on the room identifier through:
 - service selection procedure with SSF as defined in clause 8.2 step 4,
 - notification procedure from SCF as defined in clause 8.11.1, recommendation procedures as defined in clause 8.13
 - messaging procedure with other UE as defined in clause 9.3.

The response includes information of the SSC room, e.g. service id currently being watched in the SSC room, offset of the content at the present.

- 2) If no service is active in the SSC room, the UE selects a BC, CoD, UGC or N-PVR service through:
 - service selection procedure with SSF as defined in clause 8.2 step 4,
 - notification procedure from SCF as defined in clause 8.11.1,
 - recommendation procedures as defined in clause 8.13,
 - messaging procedure with other UE as defined in clause 9.3 or
 - IPTV Content Marker Retrieval procedure as defined in clause 8.23.2
- 3) In case of CoD, N-PVR or UGC, each UE that enters the room initiates a CoD/N-PVR content/UGC watching session indicating the selected content as defined in 8.4.1 for CoD, 8.5.1.2. for N-PVR and 8.9.3 for UGC. It additionally indicates a SSC identifier. In addition to rights checking described in 8.4.1 for CoD, 8.5.1.2. for N-PVR and 8.9.3 for UGC, the SCF shall check if the user has the rights to enter the room, which includes SSC room member authorisation and Service ID check,. If a session has already been established by another UE within the same SSC room, the SCF shall correlate this session with the new one using the SSC room identifier and selects the same MF. It shall indicate to the MF that this session has to be correlated with the other within the same SSC room ID.

In case of BC, if no BC session is ongoing, each UE that wants to enter the room initiates a BC session indicating the selected content as defined in 8.3.1. It additionally indicates a SSC room identifier. The BC service indicated in the session initiation request shall be the one of the shared content. If a BC session is ongoing, the UE shall switch to the BC service being watched by other users of the same SSC room as defined in clause 8.3.4 and shall indicate to the SCF the BC service identifier and SSC room identifier. The SCF shall check if the user has the rights to be part of the group of users sharing the control.

Editor's note: the case where the SCF selects an MF for each UE is FFS.

If synchronization is needed for sharing content, the procedures in 8.15 shall be applied.

The session initiation should be forwarded to the same SCF for the different UE that wants to enter the room. If not, this requires synchronisation procedures between SCFs that are not specified in this release.

8.21.4 Shared service control procedures

Depending on the SSC room policy, one or more UEs may perform service commands, such as CoD trick play or BC channel changes, for the shared service in the SSC room. The change in service state following from this service command is then reflected towards all other UEs involved in the shared service. The SSC room policy can indicate that room moderation and/or floor control is applicable to the shared service. This allows for resolving potential command conflicts that may occur due to interactions between service and/or media control commands received from different users.

NOTE: The extent of room moderation and/or floor control can be described by the room policy and may be subject to application design. Appendix B includes further details on the various policies and their use.

If synchronization is needed for shared service control, the procedures in 8.15 will be applied.

Editor's note: how the UE is informed of the SSC room policy regarding service control is FFS.

Editor's note: the case of BC with Trick Play is FFS.

8.21.4.1 Shared BC channel changes

Depending on the SSC room policy, when a BC service is shared in an SSC room, the channel changes issued by an UE will be reflected towards all others UEs involved in the shared service. The SSC room policy indicates how conflicts in case of non-overlapping BC service packages are handled. For example, if all UEs involved in the shared BC service have a subscription to the same BC service package(s), no specific handling of conflicts is required. If the BC service packages that each UE is subscribed to do not completely overlap, the notification mechanism is employed to indicate and/or resolve conflicts at the UE that causes the conflict occurrence due to an issued channel change command.

Figure 39G depicts the typical steps that occur when one of the UEs involved in the shared BC service issues a BC channel change:




Figure 39G: Shared BC channel changes

- 1) The UE performs broadcast TV channel switching according to clause 8.3.4.

- 2) If conflicts arise due to non-overlapping BC service packages of the UEs involved in the shared BC service, the UE receives a notification from the SCF to indicate and/or resolve the conflict. Depending on the SSC room policy, the notification contains a message to be displayed on the UE screen and/or instructions for the UE how to handle the conflict. If multiple UEs are impacted by the conflict, each of these UEs should receive a notification.

NOTE: Indication of the conflict can be implemented e.g. as visual pop-up on the UE screen, asking the user how to handle the conflict, or through automatically-handled notifications, that e.g. remove the user from the SSC room. The exact service behaviour is subject to implementation choices and can be described in the SSC room policy.

- 3) If no conflict has occurred, or if conflicts have been resolved, the channel change is reflected towards each UE involved in the shared BC service. The notification procedures from clause 8.11. may be employed.

Editor's note: the notification procedure using media path may need to be adapted in order to handle notifications that are not displayed on the UE screen. Also, a unicast notification procedure using media path may be required. This potentially would lead to a method where a single MF is involved.

8.21.4.2 Shared CoD trick play commands

Depending on the SSC room policy, when a CoD service is shared in an SSC room, the trick play commands issued by an UE will be reflected towards all others UEs involved in the shared service. The SSC room policy indicates how conflicts in case of (near-)simultaneously received trick play commands are handled.

Figure 39H depicts the typical steps that occur when one of the UEs involved in the shared CoD service issues a CoD trick play command:




Figure 39H: Shared CoD trick play commands

- 1) The UE issues a media control command, i.e. CoD trick play command, to the serving MF.
- 2) If the SSC room policy has not been pushed to the MF during shared service initialization, the MF pulls the room policy from the SCF.

NOTE: The pull mechanism for requesting the SSC room policy by the MF from the SCF also allows for updating the SSC room policy depending on the service states.

Editor's note: The optional push of the SSC room policy towards the MF during SSC room selection needs to be incorporated in step 3 of clause 8.21.3.

- 3) If conflicts arise due to e.g. (near-)simultaneously received trick play commands of the UEs involved in the shared CoD service, the MF notifies the SCF.
- 4) The UE receives a notification from the SCF to indicate and/or resolve the conflict. Depending on the SSC room policy, the notification contains a message to be displayed on the UE screen and/or instructions for the UE how to handle the conflict. If multiple UEs are impacted by the conflict, each of these UEs should receive a notification.

NOTE: Indication of the conflict can be implemented e.g. as visual pop-up on the UE screen, asking the user how to handle the conflict, or through automatically-handled notifications, that e.g. prevent to command being executed. The exact service behaviour is subject to implementation choices and can be described in the SSC room policy.

- 5) The MF sends the media control response to the UE.
- 6) If no conflicts have occurred, or if conflicts have been resolved, the media control command is reflected towards each UE involved in the shared CoD service. The notification procedures from clause 8.11. may be employed.

Editor's note: the notification procedure using media path may need to be adapted in order to handle notifications that are not displayed on the UE screen. Also, a unicast notification procedure using media path may be required. This potentially would lead to a method where a single MF is involved.

8.22 Personalized Service Composition (PSC) procedures

This clause describes procedures for the PSC service where multiple BC and or CoD sessions are composed into a single Personalized Service Composition. Existing BC/CoD procedures are used for session setup in order to compose the PSC. Additional steps include selection and configuration of the PSC between the UE and SSF, handling of cases where there are insufficient resources available for the full PSC and synchronization of the PSC constituting media streams.

NOTE: This clause only applies when multiple BC and/or CoD sessions need to be associated with each other at the SCF and/or other functional entities. Initiating multiple not-associated BC/CoD sessions and including multiple media streams within a single BC or CoD session are implicitly covered by clauses 8.3.1 and 8.4.1.

The following compositions of multicast and unicast media streams are supported.

- UE receiving multiple multicast streams within multiple BC sessions;
- UE receiving multiple unicast streams within multiple CoD sessions.
- UE receiving any combination of multicast and unicast streams within BC and/or CoD sessions.

Figure 39I depicts the typical steps that occur during the establishment of a Personalized Service Composition session and its constituting BC/CoD sessions.




Figure 39I: Signaling flows for Personalized Service Composition

- 1) The UE makes a selection of a Personalized Service Composition (PSC) from the SSF. The PSC, to be composed from multiple BC and/or CoD sessions, is either preconfigured in the SSF or configured by the user. The UE generates a PSCid that correlates the different BC/CoD sessions in the PSC.

NOTE: PSC combinations of multiple BC and/or CoD sessions may require more complex EPG data, as supported by e.g. OMA BCASST service guide.

NOTE: Users can bookmark a particular PSC combination including its PSCid for future usage.

- 2) The UE initiates a PSC session with the SCF. The PSC session initiation request contains the PSCid and content identifiers of the PSC constituting BC/CoD sessions. Such content identifiers are for example BCServiceId (clause 7.4.1), CoDId (clause 7.4.1), NPVRContentId (clause 7.4.1), ad content id (clause 8.14.1) UGC content id (8.9.2) and/or shared content identifier (see 8.21.2). It may also contain handling instructions, e.g. instruction for the case that there is insufficient bandwidth to constitute all requested BC/CoD sessions simultaneously.
- 3) The SCF initiates a BoC or CoD session to the UE, following the procedures of clause 8.3.1 Figure 13 or clause 8.4.1 Figure 21A. The session initiation request includes the PSCid which is used by the UE to correlate the incoming BC/CoD session initiation request with the PSC session.
- 4) The SCF initiates additional BoC and/or CoD sessions to the UE to build the PSC. Step 4) may be repeated zero or more times.
- 5) The SCF verifies resources availability. If step 3) and/or one or more of the steps 4) fails due to insufficient resources, then the SCF may try and set up an alternative offer that is either preconfigured in the SCF or signalled as handling instructions in step 2). Examples of such an alternative offer are downgrading, not-

initiating or terminating one or more of the PSC constituting BC/CoD sessions, or terminating the PSC session as a whole.

Editor's Note: SCF-initiated PSC session is for further study.

Editor's Note: UE-initiation of the PSC-constituting BC/CoD sessions is for further study.

6) The SCF confirms the establishment of the PSC session.

At this point, the PSC constituting BC/CoD sessions and their associated media streams are available at the UE and they can be presented to the user as a composite, e.g. picture-in-picture, replacing an audio stream, etcetera.

If synchronization is needed between the media streams within the PSC, the procedures in 8.15 will be applied.

Once the PSC session is established, the UE or the SCF may use the PSCid and the associated PSC constituting BC/CoD sessions to perform actions on the PSC as a whole, for example adding or removing PSC constituting BC/CoD sessions; N-PVR recording the PSC; or terminating the PSC session as a whole.

Editor's Note: Modification of a PSC session is for further study.

Editor's Note: Adding existing BC or CoD sessions to a PSC session is for further study.

Editor's Note: N-PVR recording of a PSC is for further study.

Editor's Note: Continue viewing a PSC on another device is for further study.

Editor's Note: Bookmarking a PSC is for further study.

Editor's Note: Shared PSC content is for further study.

Editor's Note: PSC trick play is for further study.

When the PSC session is no longer needed, it is terminated by the UE or SCF.

7) The UE sends a PSC session termination request to the SCF.

8) The SCF terminates the PSC constituting BC/CoD sessions following the procedures of clause 8.3.3 Figure 18 and/or clause 8.4.3 Figure 30.

9) The SCF confirms the PSC session termination to the UE.

Editor's Note: Implicit termination of the PSC session by terminating all of its constituting BC/CoD sessions is for further study.

8.23 Signalling flows for IPTV Content Marker service procedures

IPTV Content Marker service procedures consist of two types. (See clause 7.5.2).

- Storing of IPTV Content Marker data: this type of procedure allows a user to store configurable pointers to content (entire content or parts of content, e.g. favourite scene) and be able to quickly access that content
- Retrieving of IPTV Content Marker data: this type of procedure allows a user to exchange and share IPTV favourite data.

8.23.1 IPTV Content Marker storing procedures

Figure 39J provides an overview of the information flows for IPTV Content Marker storing. This procedure can occur at any time during IPTV services (BC/CoD/N-PVR/etc).




Figure 39J IPTV Content Marker storing procedure

- 1) The UE sends a IPTV Content Marker storing request to save content information. This content information may include various information, e.g. the entire/scene of content with/without current watching.
- 2) The IMS core forwards this request to the SCF.
- 3) The SCF stores the indicated content information as Content Marker data for this user. The data model of IPTV Content Marker items is defined in clause 7.5.2.
- 4) The SCF confirms storage of IPTV Content Marker data.
- 5) The IMS core forwards the response to the UE.

8.23.2 IPTV Content Marker retrieval procedures

Figure 39K provides an overview of the information flows for IPTV Content Marker retrieval. This procedure can occur at any time and may be used to share IPTV Content Markers.




Figure 39K IPTV Content Marker retrieval procedure

- 1) The UE sends a IPTV Content Marker retrieval request.

NOTE: The content id or other parameters (e.g. the fields required by the user) may be specified in the request to help filtering the IPTV Content Marker data.

- 2) The SSF returns IPTV Content Marker retrieval response. The response shall contain the user's IPTV Content Markers. If there is any user id in IPTVContentMarkerSourceUser parameter, then the SSF response also

contains the indicated user's IPTV Content Marker data. If there is any content id or other parameters in the request, then the SSF retrieves and responds the indicated IPTV Content Marker data. When retrieving that user's IPTV Content Marker data, the SSF shall perform authorization according to that other user's IPTVContentMarkerAuthorizedViewUser settings.

Alternatively, the UE may fetch the IPTV Content Markers from the SCF. In that case the SCF shall generate the IPTV Content Marker retrieval response. This response shall contain the user's IPTV Content Markers. If there is any user id in IPTVContentMarkerSourceUser parameter, then the SCF response also contains the indicated user's IPTV Content Marker data. If there is any content id or other parameters in the request, then the SSF retrieves and responds the indicated IPTV Content Marker data. When retrieving that user's IPTV Content Marker data, the SCF shall perform authorization according to that other user's IPTVContentMarkerAuthorizedViewUser settings.

8.24 Role of BGF in IPTV

In certain IPTV scenarios there is a need to bypass the BGF for scalability reasons. For example, the BGF could be bypassed when using MPEG2-TS directly over UDP transport, as well as, for RTP(RTCP) transmission when there is no RTCP towards the network.

It shall be possible to bypass the BGF. Its use is a local decision taken by the network provider during the IPTV session setup based on the session information provided.

8.25 Procedures for service initiation by remote UE

The service initiation by remote UE can be used by one remote UE to activate the target UE to start-up the IPTV service, for example, it can be used to remote start-up UGC, CoD or BC services. Figure 39L depicts the typical steps for service initiated by Remote UE.

Draft




Figure 39L: Service initiation by Remote UE

1A. The Remote UE sends a remote service start-up request through the Core IMS to the SCF. The request carries the necessary parameters indicating the service, e.g. BC service or UGC service, user identifier of Target UE which start-up the service and user identifier of the remote UE.

1B. The SCF performs service authorization as described in clause 5.1, if the Remote UE is allowed to perform remote start-up operation of the service, the SCF forwards the remote service start-up request through the core IMS to the Target UE. And the user of Target UE may deny the request even if the SCF authorized.

NOTE: The SCF authorizes the remote UE by checking the user profile of the Target UE.

1C. The Target UE sends a remote service start-up response through the Core IMS to the SCF.

1D. The SCF forwards remote service start-up response through the Core IMS to the Remote UE.

NOTE: The remote service start-up request in steps 1A-1D may directly sent to the target UE if SCF does not need to perform authorization.

2. The Target UE initiates the service indicated in the remote start-up request, e.g. BC or CoD session initiation following the procedures of clause 8.3.1 or 8.4.1.

9 Interactions between IPTV services and other TISPAN services

Several approaches can be employed for realizing the interaction between IPTV services and other TISPAN services. This paragraph describes approaches that are considered within the TISPAN architecture, e.g. where application servers

interact directly through Core IMS. Two other approaches involving 3GPP SCIM and OSA/Parlay methods are described in Annex C.

9.1 Presence and IPTV

Editor's Note: Evolution of the Release 2 procedures for Presence and IPTV could be developed in Release 3.

IPTV services may be combined with the presence service capability. This clause describes the mechanisms that apply when IPTV services are combined with the presence service capability.

These mechanisms may also be used for other purposes than publishing user presence information. For example they may be used to gather statistics about BC TV Service or user behaviour information.

9.1.1 Presence architecture and functional description

The architecture and functional description of the presence service capability when used in relation to the IPTV services conform to TS 182 008 [10].

9.1.2 Presence attributes for IPTV

The Presence attributes defined in TS 182 008 [10] apply.

In addition, the following specific IPTV attributes shall be supported:

- BC service activated;
- CoD service activated;
- PVR service activated.

If the IPTV presence attribute "channel currently accessed" is supported, then the machine-readable part of the identification of the channel shall be globally unique. The term globally unique here means that there is no ambiguity in the identification of the channel if presentity and watcher (for terminology, see in TS 182 008 [10]) are with different network operators and/or in different countries.

The following specific IPTV attributes may also be supported:

- IPTV service activated;
- UGC service activated;
- PCoD service activated;
- TAI service activated;
- PCh service activated;
- SSC service activated;
- PSC service activated;
- BC TV Service currently accessed;
- programme currently watched, when available;
- content currently accessed.
- current service state (e.g. paused, playing, in trick play mode)

Editor's note: additional mechanism may be required if Presence mechanism is not adequate for providing these attributes.

It is up to user's decision to include specific IPTV attributes in presence document.

Editor's note: how to cope with the relation between a user publishing Presence attributes and subscribing to services requiring Presence information is FFS.

Editor's note: export and/or exposure of Presence attributes towards other users is FFS.

Editor's Note: Potential conflicts between IPTV Service State information retrieved using Presence and obtained from SAD 7.1. are for FFS.

When the "BC service activated" attribute is included in a presence document, the attributes "BC TV Service currently accessed" and "programme currently watched" may also be included, depending on user preferences. These attributes shall not be present in a document if the "BC service activated" attribute is not present.

When the "CoD service activated" or the "PVR service activated" attribute is included in a presence document, the attribute "content currently accessed" may also be included depending on user preferences. This attribute shall not be present if the "CoD service activated" or the "PVR service activated attribute" is not present.

9.1.3 SIP related procedure

The SIP related procedures defined in ES 283 030 [13] apply.

Editor's note: Alternative aggregation of presence information from network entities (e.g. SCF) is FFS. Such a handling of presence and using network based presence information can be analysed. Simultaneous use of SAD or other user data with presence can be analyzed.

The publication of CoD related presence information happens:

- after completion of CoD session initiation procedure;
- after completion of CoD session termination procedure.

The publication of BC related presence information happens:

- after completion of BC session initiation procedure;
- after completion of the BC session termination procedure;
- optionally, when the UE successfully subscribes to a particular multicast channel (i.e. channel hopping).

In order to cope with overload possibly caused by numerous channel-hopping, it shall be possible to define a timer set up to limit the number of publications. This timer is started and reinitialised after each channel change. Publication shall only be sent when the timer elapses.

Editor's note: In order to cope with overload possibly caused by numerous IPTV service access entries, it shall be possible to define a timer set up or ceiling to limit the number of publications. Collecting presence information for optional services is optional.

The publication of UGC related presence information happens:

- after completion of UGC creation session initiation procedure;
- after completion of UGC creation session termination procedure;
- after completion of UGC watching session initiation procedure;
- after completion of UGC watching session termination procedure.

The publication of PCoD related presence information happens:

- after completion of PCoD session initiation procedure;
- after completion of PCoD session termination procedure.

The publication of PCh related presence information happens:

- after completion of PCh session initiation procedure;

- after completion of PCh session termination procedure.

The publication of TAI related presence information happens:

- after completion of TAI session initiation procedure;
- after completion of TAI session termination procedure.

Editor's note: Right triggers for TAI presence information is FFS and depending on agreed TAI procedures which are in progress.

9.2 Incoming call management

Editor's Note: The procedures for incoming call management service can be described in this clause.

9.3 Message and IPTV

Editor's Note: The procedures for message and IPTV service can be described in this clause.

9.3.1 Messaging procedures

Messaging procedure is used for several purposes: where messages are sent between users or between system and users. Following procedures may be primarily used for immediate messaging described in TS 181 016 [13B] in section in 6.2.3 to provide services specified in TS 122 340 [13C] together with IPTV services. Several additional specific use cases described in TS 181 016 [13B] (e.g. in section in Annex A) require integration of existing messaging systems (in this case IMS based messaging) with IPTV service logic to provide blended IPTV and messaging service (e.g. messaging during BC service or chat discussion related to content or related to used IPTV service, etc.).

Figure 40 depicts the typical steps that occur when the UE wants to send message from one user to one or more other users using signalling path.




Figure 40: messaging procedure using signalling path

- 1) UE sends a message request via IMS core to SCF using signalling path for IMS messaging mechanisms [2]. Message contains message itself (supporting different media content types as in [13C]) and also parameters which identify related IPTV service blended with this messaging procedure.

- 2) SCF evaluates appropriate destination UEs for delivery message to specified group of users (as users interaction related with IPTV services) based on service logic (and other conditions e.g. user profile or messaging rules) specified for required IPTV service. SCF may also modify/generate messages (original message may be included together with additional IPTV related information e.g. watched channel, form of presentation of message, etc.).
- 3) SCF sends message (original/modified) via IMS core using IMS messaging framework [2] to one or more UEs.

NOTE: In this example the messaging service function is not explicitly shown for brevity. IMS messages may traverse the messaging service function, and are under service provider control. Furthermore, while Figure 40 shows the SCF in the path of the IMS message, this is an option and need not be the case for all IMS messages originating/terminating from/to an IPTV end user. The SCF would typically be in the signaling path of an IMS message if the message is addressed explicitly to it, or if it has to perform some special procedure on the message.

9.3.2 Procedures for deliver messages of BC service using media path

This clause describes mechanisms of deliver messages that are associated with a BC service using media path.

These mechanisms may be used for some purposes. For example they may be used to participate in a comment service associated with a BC program; one user can send his comment to the SCF using IMS immediate message services, then the SCF and the MF deliver the comments to all users who subscribed to the comment service associated with the BC service.

Figure 41 depicts the typical steps that occur when one user sends IMS immediate messages to SCF, and SCF and MF deliver the message to users who subscribed to the message services associated with the BC service.

NOTE: the parameters for joining the multicast group, i.e. multicast address, need to be available to UE before it receives the messages delivered using media path.




Figure 41: Deliver messages of BC service using media path

- 1) UE joins a BC service and the messages multicast group associated with the BC service, e.g. comment services of a BC service.
- 2) UE initiates an IMS immediate message request carrying the message, which is specified in the IMS stage 2 specification[2]. The immediate message is routed by Core IMS to the SCF in charge of the delivery of messages associated with the BC service.
- 3) The SCF detects which BC service is associated with the IMS immediate message e.g. by the destination of the immediate message, and sends the IMS immediate message to the selected MF. The MF transfers the IMS

immediate message to the multicast group associated with the BC service. The procedures use mechanisms of delivering notification using media path specified in clause 8.11.1.2, and the notification request from SCF to the selected MF at least contains parameters of BC service ID and the message.

NOTE: Existing mechanisms of IMS could be used for the SCF to distinguish IMS immediate message from normal IMS message, e.g. by checking the content type of the message body.

9.4 Event Handling involving the SCF

Event handling by the SCF takes place if the SCF receives events from other NGN application servers. SCF involvement is required depending on the event and the user profile configuration. Examples include incoming call management involving multiple UE's (e.g. pause on incoming call), emergency warning and alerting systems, or parental control. In such cases the SCF needs to correlate the event with the right UE and apply service logic to determine the applicable action to the UE and/or MF.

Editor's note: whether this procedure is also applicable for handling events from external applications (e.g. those in Appendix C) is FFS.




Figure 42: Event handling involving the SCF.

- 1) The SCF receives an incoming event which requires handling.

NOTE: It is up to the IPTV Service Provider, on behalf of the user and/or based on the service requirements, to decide when to route an incoming event to the SCF or send it directly to the UE.

- 2) The SCF correlates the incoming event with the designated user/group of users and/or UE's, performs authentication and detects the ongoing IPTV service status. Detection of the IPTV service status is done based on IPTV Service Action Data or using IPTV Presence information.

NOTE: The SCF can decide which (if any) further actions to perform, e.g. based on user preferences and detected service state.

- 3) The SCF performs an action towards the UE and or MF, e.g. it can send a notification to the UE or instruct the UE to send a trick play command / change the channel.

10 Security

Editor's Note: Evolution of the Release 2 security aspects could be developed in Release 3. For this, collaboration with WG7 work is needed.

Editor's Note: WG7 distinguishes between Media and Service Security. This section may need to be aligned with WG7 terminology.

10.1 Authentication

Authentication procedures for the Ut reference point conforms to TS 187 003 [5].

10.2 Content Security

The locations and related reference points of the following elementary functions are defined in TS 187 003 [5]. They are reproduced below for information.

For content security the following elementary functions are used:

- Content licensing: This elementary function handles the licenses issuing related functions, including generation and distribution of the licenses to the desired entities.
- Key management: This elementary function handles the management of the security keys, including generate and provide the keys and corresponding parameters to the desired entities.
- Content encryption: This elementary function handles the content protection related operations, e.g. content encryption and encapsulation operations, etc.

These three elementary functions may be flexibly located in existing functional entities or new ones as a whole or in independent parts.

NOTE: Some of these elementary functions may be executed on-line (in real-time) or off-line (in this case could be part of the management).

11 Charging

Editor's Note: Evolution of the Release 2 charging aspects could be developed in Release 3.

IMS charging principles apply as defined in ES 282 010 [16].

Editor's Note: Are there any limitations of IMS based billing model which limits its use for IPTV? Could be criteria for IPTV services charging (e.g. TV-Channel vs. Session Charging) a differ from existing IMS services criteria, thus might lead TISPAN to specified additional requirements to IMS charging (e.g. towards SA5).

12 Management

Editor's Note: In Release 3 the Release 2 management section could be evolved.

12.1 Management requirements

For each IPTV service, several entities require to be provisioned with necessary network parameters (e.g. multicast addresses for multicast services, source of original content, etc) and to associate specific content or service with these network parameters. These entities are:

- the SSF, as it needs to provide the UE with the content identifier associated to an IPTV service and possibly with a set of network parameters (control and/or content channel descriptions) necessary to initiate an IPTV session;
- the MFs, as they need to associate a content identifier with multicast or unicast streams to be delivered to the UE;
- the SCF, as it may also need to provide the UE with network parameters in response to service initiation requests, in configurations where the SSF does not provide this information beforehand.

Consistent information has to be provisioned on these entities.

12.2 Content management

Content management functionalities are responsible for managing acquisition of content and service information (e.g. metadata) from content and its metadata sources of content provider, controlling validation and/or processing/adaptation to the required format and also to provide management functionalities for supporting distribution of the prepared content to the media delivery function and distribution of content among different media delivery functions.

NOTE: Content management is used in the case of offline or online ingest of the content. The online ingest means receiving content directly streamed from the content provider. The offline ingest refers to content files delivered by other means than the online (e.g. such on physical media like DVD, CD, etc.). The content management is used by the IPTV service provider to statically provision the content.

Content management functionalities can consist of the following groups of elementary functions:

- Content acquisition - responsible for content management functionalities needed to acquire, aggregate and import content/metadata from multiple external sources of content providers.
- Content validation/adaptation - after acquisition it could be necessary to manage content/metadata format validation and verification as well as to define a relation between content and its metadata. Management can also control media or metadata adaptation and/or processing (e.g. transcoding, packaging, scheduling, resolution conversion, editing, etc) to the required type of media files or streams.
- Content distribution Control - management functionalities for control the distribution of content and its metadata from content providers when content acquisition/ content validation/adaptation were performed to appropriate functional entity (e.g. media files storage in MDF). This function handles the whole lifecycle of the content and provide management support for its distribution to media delivery distributed architecture (e.g. uploads on video streamers, moving according to management criteria such as popularity, regionalization, un-referenced content, MDF resources and so on). Additionally, this function can control the content distribution among MDFs (e.g. delete content in some MDFs, moving content from one MDF to other MDFs) according to some criteria such as content popularity.

13 Support of Metadata

Editor's Note: In Release 3 the Release 2 Metadata section could be evolved.

13.1 Introduction

IPTV Metadata enriches the service experience of the IPTV Services a user has access to. IPTV Metadata may originate from the User, the NGN Service Provider, the Application Provider or the Content Provider. The Metadata should be processed, filtered and enriched by involved IPTV solution entities in order to improve the user experience.

NOTE 1: Processing, Filtering and Enriching Metadata may be based on techniques like personal preferences, additional subscribed-to services and other means and are out of scope of the present document.

NOTE 2: How user originated Metadata is injected into the IPTV solution is out of scope of the present document.

NOTE 3: Content metadata may be delivered along with the content in real time (from MDF). In this case metadata might differ from the metadata already stored in the SSF and therefore SSF can require update them with relevant metadata from MDF. Also, IPTV CRS might be a service requiring the SCF to access actualised metadata. Generally, if UE or other entity needed most updated metadata it is requesting them from SSF (SSF is responsible acquire most updated metadata).

Editor's Note: Which mechanism is appropriate and how to handle all possible case is FFS, maybe WG8 needs to be consulted (synchronization of metadata cross IPTV FEs).

The access to Metadata may be considered as a service in itself which shall be protected by appropriate service authorization means before the Metadata is delivered to the UE.

13.2 SSF support

IPTV Metadata may be delivered outside of an IPTV service session by the SSF.

Xa shall be used for the Metadata delivery.

13.3 SCF/MF support

IPTV Metadata may be delivered as part of a normal IPTV service session or inside an IPTV service session dedicated to Metadata delivery. In the first case, the Metadata is sent in addition to Media as part of the IPTV session. In either case the Metadata capabilities are negotiated during session setup or session modification between UE and SCF. The Metadata itself is delivered via the MDF through unicast or multicast via Xd.

Draft

14 Support of Mobility Capabilities

To support the mobility capabilities of IPTV services, the UE shall support roaming in the Visited Network. When the UE is located in the Visited Network, it can access the IPTV services in its own home network. Sometimes when the IPTV Service Provider servers both home network and visited network, the MF can server both visited network and home network. Annex H give interconnection examples to support of mobility capabilities.

Editor's Note: Different type of interconnection of visited and home network applied for IMS roaming is FFS.

Editor's Note: Relation of interconnection and IPTV roaming is FFS and there is also need to clarified if HWI for interconnection cover also IPTV roaming and mobility concept (home/visited network).

Annex A (informative): Integration of non-SIP-AS Service Discovery Function in IMS based IPTV

Editor's Note: In Release 3, an evolution of this section may be needed.

A.1 Introduction

Clause 5 defines Service Discovery and Selection (SD and S) as a two step process consisting of Service Discovery and Service Selection. While clause 5 focuses on discovering services by an SIP based SDF entity, the Service Selection uses non-SIP mechanisms. This annex describes using non-SIP SDF to reuse standard non-SIP Service Discovery technologies such as DVB-IP Service Discovery as specified in TS 102 034 [6].

A.2 Architecture




Figure A.1: Functional architecture for IPTV services integrating non-SIP SDF

A.2.1 Functional entities

Figure A.1 depicts the IMS based IPTV architecture based on figure A.2 using a non-SIP AS SDF for Service Discovery. All entities are defined in clause 5.

A.2.2 Reference points

Figure A.1 depicts the IMS based IPTV architecture based on figure A.2 using a non-SIP AS SDF for Service Discovery. All shown reference points are defined in clause 6 except Xa' which is described in the following clause.

A.2.2.1 UE - SDF (Xa')

This reference point delivers Service Discovery Information, i.e. SSF addresses in the form of URIs and/or ip-address, from the SDF to the UE. Both Unicast and Multicast delivery of this information is possible.

The use of Xa' conforms to TS 102 034 [6] clause 5.2.5, where the term "HNED" is to be replaced by "UE" and where "Location(s)" carries the SSF address(es).

A.2.3 Procedures

A.2.3.1 IPTV service attachment and selection

Figure A.2 defines steps 3 and 4 of figure 9 in case the SDF is not SIP-AS based.




Figure A.2: IPTV service attachment and selection

- 1) The UE requests the SDF it was assigned. This assignment may have occurred during the network attachment phase, during offline provisioning or by other means.
- 2) The SDF determines the proper SSF (or SSFs). It is for further study how the SDF may take into account the UE's capabilities, the user's profile and/or the location of the UE (Personalized Service Discovery).
- 3) Configuration information that includes the SSF address(es) is (are) routed back to the UE.
- 4) The UE requests the SSF to get the selection data.
- 5) The SSF delivers the requested data to the UE.

NOTE: If a non-SIP AS SDF is used for IPTV service attachment, no IMS registration prior to step (1) of figure A.2 is required. Therefore, step 2 of figure 9 (IMS registration) can occur in parallel to, before or after the procedure described in figure A.2.

Annex B (informative): Policies for Shared Service Control

B.1 Types of Policies

Editor's note: Contributions are invited to work out the type and use of policies and the manner and level of control they describe. For example, the way that policies can be used to describe the behaviour in a tightly-controlled room (e.g. single master controller), up to the behaviour in a room with floor control needs to be specified. It is intended to work out one or more of these policies in stage-3.

B.1.1 Policy for floor control

Editor's note: This section intends to describe a policy that sets rules for floor control. It could describe the use of timers and master allocation through e.g. tokens.

B.1.2 Policy distribution towards UE

Editor's note: This section intends to describe the distribution of a policy towards the UE, to allow for more flexible control.

B.1.3 Policy for loose control

Editor's note: This section intends to describe the use of a loose policy, to allow for very flexible control. This approach may require user interaction/intervention. It should ensure acceptable service behaviour towards the user.

Annex C (informative): Architectures for Interactions between IPTV services and other TISPAN services

This Annex contains examples of architectures that can enable the interaction between IPTV services and other TISPAN services. The examples of architectures given refer to existing work and serve to clarify how service interaction can be achieved by using this existing work. For these architectures, it is assumed that service interaction requires a dedicated Application Server that may explicitly implement the blended service functionality (e.g. pausing the TV on incoming call, or watching apart together). Such an AS can be seen as an external application with respect to the TISPAN IPTV architecture.

C.1 Interaction based on an OSA/Parlay/Parlay X SCS

This approach is based on an OSA/Parlay/Parlay X Service Capability Server (SCS), that provisions standardized interfaces and APIs to external and third party application servers. The use of such an SCS is described in ETSI ES 204 915 [18], ETSI ES 202 504 [19], 3GPP TS 29.198 [20] and 3GPP TS 29.199 [21].

C.1.1 Service Capability Server (SCS)

The OSA SCS acts as a secure gateway between the underlying network and the application with the OSA architecture. It is responsible for providing specific service abilities to third party applications. An SCS further serves to make an abstraction of the functionality offered by the network, in effect offering the service capability features of the underlying network to the third party applications.

C.1.2 Architecture

Figure C.1 shows a simplified version of the IMS-based IPTV architecture from Figure 2 in section 5.1.1., with interfaces to an SCS and subsequent external applications.




Figure C.1 – Interaction between TISPAN IMS-based IPTV architecture and an OSA/Parlay/Parlay X SCS.

C.2 Interaction based on a 3GPP SCIM

This approach is based on a Service Capability Interaction Manager (SCIM), that allows for service association and dynamic service triggering. The use of such an SCIM is described in 3GPP TS 23.002 [22], 3GPP TS 23.218 [23] and 3GPP TR 23.810 [24].

C.2.1 Service Capability Interaction Manager (SCIM)

The Service Capability Interaction Manager (SCIM) is a function that manages the interaction between IPTV services and other NGN services, by e.g. associating the IPTV services with other NGN services and dynamic triggering the services in the ongoing session based on the information about the relational session or user's status.

C.2.2 Architecture

Figure C.2 shows a simplified version of the IMS-based IPTV architecture from Figure 2 in section 5.1.1., with interfaces to an SCIM and subsequent external applications.




Figure C.2 – Interaction between TISPAN IMS-based IPTV architecture and a 3GPP SCIM.

Annex D (informative): Mapping of elementary functions

D.1 Mapping of elementary functions to generic capabilities

Editor's note: Contributions discussing correct mapping of elementary function to generic capabilities are invited. When new functionality or service will be added also implication for this section could be considered to have it synchronized with normative text.

Mapping of elementary functions in Table D.1 show which elementary function (listed in 5.1.4) are applicable to generic capabilities (described in 5.1.3A).

Table D.1: Mapping of elementary functions to generic capabilities

	Elementary function	Discover & select content	Service control	Service interact.	Media control	Deliver media	Content protection	Content mng. & distribution	Service interaction
1	network attachment		X						
2	registration		X						
3	resource management		X						
4	charging information		X						
5	service discovery	X							

	Elementary function	Discover & select content	Service control	Service interact.	Media control	Deliver media	Content protection	Content mng. & distribution	Service interaction
6	service authorization		X	X					
7	service selection	X							X
8	service initiation		X	X					
9	service control		X	X					X
10	service information handling	X	X	X					X
11	service configuration		X						
12	session initiation		X	X					
13	session modification		X	X					
14	session termination		X	X					
15	multicast based media delivery					X			
16	unicast based media delivery					X			
17	content download/upload					X			
18	control of multicast streaming		X		X				
19	control of unicast streaming			X	X				
20	control of download/ upload								
21	content ingestion/receiving					X		X	
22	content recording				X				
23	content storage				X				
24	content adaptation					X			
25	content acquisition							X	
26	content validation							X	
27	content distribution							X	
28	content licencing						X		
29	key management						X		
30	content encryption						X		
31	user profile/data mng.								X
32	accounting/right control		X						X
33	status/state (changes) detection/reporting		X	X		X			X
34	common notification		X	X					X
35	messaging			X					X
36	presence			X					X
37	inter-destination media synchronization			X		X			X

D.2 Mapping of elementary functions to functional entities

Editor's note: Contributions discussing correct mapping of elementary function to functional entities are invited.
When new functionality or service will be added also implication for this section could be considered to have it synchronized with normative text.

Mapping of elementary functions in Table D.2 show which elementary function (listed in 5.1.4) are applicable to functional entities (described in 5.1.3).

Table D.2: Mapping of elementary functions to functional entities

	Elementary function	UE	SSF	SDF	Core IMS	SCF	UPSF	MCF	MDF
1	network attachment	X			X				
2	registration	X			X	X			
3	resource management				X				
4	charging information				X	X			X
5	service discovery			X					
6	service authorization	X		X	X				
7	service selection	X	X						
8	service initiation	X				X			
9	service control	X			X	X			
10	service information handling	X		X					
11	service configuration	X			X	X			
12	session initiation	X			X	X			
13	session modification	X			X	X			
14	session termination				X	X			
15	multicast based media delivery								X
16	unicast based media delivery	X							X
17	content download/upload	X							X
18	control of multicast streaming	X						X	
19	control of unicast streaming	X						X	
20	control of download/upload	X						X	
21	content ingestion/receiving	X							X
22	content recording	X							X
23	content storage	X							X
24	content adaptation								X
25	content acquisition								

	Elementary function	UE	SSF	SDF	Core IMS	SCF	UPSF	MCF	MDF
26	content validation								
27	content distribution								
28	content licencing								
29	key management								
30	content encryption								X
31	user profile/data mng.	X				X	X		
32	accounting/right control				X	X	X		
33	status/state (changes) detection/reporting	X				X		X	X
34	common notification	X				X			
35	messaging	X				X			
36	presence	X				X			
37	inter-destination media synchronization	X				X			

D.3 Mapping of elementary functions to IPTV services

Editor's note: Contributions discussing correct mapping of elementary function to IPTV services are invited. When new functionality or service will be added also implication for this section could be considered to have it synchronized with normative text.

Mapping of elementary functions in Table D.3 show which elementary function (listed in 5.1.4) are applicable for described IPTV services (described in TS 181 016 [13B]).

Table D.3: Mapping of elementary functions to IPTV services

	Elementary function	BC	CoD	nPVR	cPVR	BCwTP	UGC	Push CoD	Ad.	CRS	Notif.	Msg	Presence
1	network attachment	x	x	x	x	x	x	x	x	x	x	x	x
2	registration	x	x	x	x	x	x	x	x	x	x	x	x
3	resource management	x	x	x		x	x	x	x				
4	charging information	x	x				x	x				x	
5	service discovery	x		x			x						
6	service authorization	x	x	x	x	x	x	x	x	x	x	x	x
7	service selection	x		x	x	x	x	x					
8	service initiation	x	x	x	x	x	x	x	x	x	x	x	x
9	service control	x	x	x	x	x	x	x	x	x	x	x	x
10	service information handling						x			x			
11	service configuration	x	x	x	x	x	x	x	x	x	x	x	x

	Elementary function	BC	CoD	nPVR	cPVR	BCwTP	UGC	Push CoD	Ad.	CRS	Notif.	Msg	Presence
12	session initiation	x	x	x				x					
13	session modification	x	x	x		x	x	x					
14	session termination	x	x	x	x	x	x	x	x	x			
15	multicast based media delivery	x				x			x		x		
16	unicast based media delivery		x	x		x	x		x		x		
17	content download/upload						x	x	x				
18	control of multicast streaming	x	x	x	x	x	x	x					
19	control of unicast streaming	x	x	x	x	x	x	x					
20	control of download/upload	x	x	x	x	x	x	x					
21	content ingestion/receiving	x	x	x	x	x	x	x					
22	content recording			x	x	x							
23	content storage		x	x	x		x		x				
24	content adaptation	x	x						x				
25	content acquisition	x	x			x	x	x	x				
26	content validation	x	x			x	x	x					
27	content distribution	x	x			x	x	x	x				
28	content licencing	x	x			x	x	x					
29	key management	x	x			x	x	x					
30	content encryption	x	x			x	x	x					
31	user profile/data mng.								x	x			x
32	accounting/right control	x	x	x	x	x	x	x			x	x	
33	status/state (changes) detection/reporting		x	x		x	x	x	x	x	x		x
34	common notification								x	x	x		
35	messaging									x		x	
36	presence									x			x
37	inter-destination media synchronization	x	x			x	x		x				

Annex E (Note: it shall be decided if this annex is normative or informative):

Architecture, reference points, Procedures for advertising

Annex E describes the architectures, the reference points and the procedures for the following options:

- Advertising performed exclusively by TISPAN IPTV entities. Also referred to an “Internal Advertising” option
- Advertising performed by an external system based on SCTE . Also referred to as an “SCTE-130 based External Advertising” option

Editor’s note : Further contributions are expected to introduce other external advertising systems (e.g. OMA Mobile Advertising Enabler, ...etc)

Editor’s note : Advertising procedures involving advertising system should be introduced in this annex.

E.1 General Advertising Architecture

This clause specifies the entities that are involved in the architecture options described below.

E.1.1 Definitions

Editor’s note: General definitions for the functional entities common to all the architectural options will be added

E.2 Internal Advertising Architecture Option

This clause specifies the entities involved in the TISPAN-IPTV specific advertising architecture, the procedures and the interfaces involved between the TISPAN entities

Editor’s note: Contributions are invited for covering the following clauses based on the clause 8.14. Clause 8.14.1 and 8.14.2 should be removed when covered here, according to the meeting agreement reached during TISPAN 20bis.

E.2.2 Advertising architecture

E.2.3 Reference points

E.2.4 Procedures for targeted ad insertion (TAI)

In internal option, the Ad Server described in clause 8.14 is instantiated to a logical SCF that is in charge of Ad service which is responsible for IPTV service status detection, ad content selection and subsequent ad service control.

NOTE: In specialized implementation, the SCF in charge of Ad service (i.e. SCF2) can be co-located with the SCF in charge of BC, CoD or other IPTV services (i.e. SCF1).

E.2.4.1 Signalling flows for TAI at UE side

When the ad insertion takes place at UE side, the UE is informed by ad insertion indication from SCF in charge of Ad service, and initiates individual session request for Ad content, which implies that multiple sessions may exist on the UE during the ad insertion time.

Figure E.1 depicts the typical steps when UE is informed of targeted ad insertion indication.




Figure E.1 signalling flows for UE performing TAI

- 1) Some IPTV session is established between UE and SCF1 as procedures described in clause 8, e.g. BC session in clause 8.3, CoD session in clause 8.4 etc., and some IPTV content is delivered to the UE.
- 2) The SCF handling the Ad service (i.e. SCF2) detects the ongoing IPTV service status (e.g. the current BC program ID, the commercial break of the program, the current CoD content id, the trick-play events etc) of specific user and decides to trigger ad insertion. Detection of the IPTV service status is done based on IPTV Service Action Data or using IPTV Presence information.
- 3) SCF2 selects targeted ad content for the user, which can be inserted to the specific content. The user profile (e.g. shopping habits, user preference) is used to help locating of appropriate ad content targeted to specific user or user group.
- 4) SCF2 sends UE the notification of ad insertion indication, using procedures specified in clause 8.11.1. The ad insertion indication includes the selected ad content identifier, the user id, insertion time (begin time and/or length), and other information needed for ad insertion.
- 5) UE initiates the session initiation or modification procedure for ad content acquisition and the selected ad content is delivered to the UE. During this step the procedures described in clause 8.3.1/8.3.2 for BC session or 8.4.1/8.4.2 for CoD session applies, with SCF2 responsible for the Ad service control and MF responsible for Ad content control and delivery.

NOTE: The session modification is only possible when the same SCF handles CoD and Ad sessions.

- 6) The UE performs the ad insertion, i.e. renders the ad content exclusively or in parallel with the ongoing IPTV content (e.g. in PiP).

- 7) When the ad insertion times up, the session for ad content is released as procedures described in clause 8.3.3 or 8.4.3, and UE resumes the rendering of the IPTV content.

E.2.4.2 Signalling flows for TAI at MF side

When the ad insertion takes place at MF, the MF is informed of the ad insertion indication from the SCF and performs the ad insertion, i.e. delivery ad content to the UE during the ad insertion time of IPTV content play back.

Figure E.2 depicts the typical steps when MF is informed of the ad insertion indication.




Figure E.2 signalling flows for MF performing TAI

- 1) Some IPTV session is established between UE and SCF1 as procedures described in clause 8 , e.g. BC session in clause 8.3, CoD session in clause 8.4 etc., and some IPTV content is delivered to the UE.
- 2) The SCF handling the Ad service (i.e. SCF2) detects the ongoing IPTV service status (e.g. the current BC program ID, the commercial break of the program, the current CoD content id, the trick-play events) of specific user and decides to trigger ad insertion. Detection of the IPTV service status is done based on IPTV Service Action Data or using IPTV Presence information.
- 3) SCF2 selects targeted ad content for the user, which can be inserted to the specific IPTV content. The user profile (e.g. shopping habits, user preference etc.) is used to help locating of appropriate ad content targeted to specific user.
- 4) SCF2 sends the ad insertion indication to the MF which is responsible for IPTV content delivery and control. The indication includes the selected ad content identifier(s), the user id, insertion time (begin time and/or length), and other information needed for ad insertion. Playlist information may be used as ad insertion indication.

NOTE: In the case of co-located entities, step 2~4 can be combined in step 1.

Editor's note: How the SCF identifies the cue messages within the IPTV content is FFS. Relationship between ad insertion indication and cue messages needs to be clarified

- 5) MF acquires the selected ad content and performs ad insertion, i.e. the selected ad content is delivered separately from the IPTV content or it is inserted as part of ongoing IPTV content. The MF may perform transcoding if the codec of ad content is not supported by the UE. In the case when the ad content is delivered at part of the on-going IPTV content, the MF shall use the cue-messages to determine when to insert the

appropriate ad content. For ad-content that is delivered separately from the IPTV content, the cue messages are used to determine when to switch to ad content. The MF may perform session modification if needed (e.g; the ad content uses different network parameters, the stream is delivered separately, etc.).

Editor's note: How the SCF delivered ad-insertion points (out-of-band cue messages) works with the cue messages delivered as part of the IPTV content from content provider is to be considered

6) The ad content is provided to the UE during the ad insertion time.

Editor's Note: Other means to perform ad-insertion, as well as the means for ad content provision on MF are FFS. Reducing the number of options or indicating only capabilities to perform ad insertion and not detailing every solution should be considered.

E.3 SCTE-130 Based External Advertising Architecture Option

This clause specifies the entities defined by SCTE-130, complete architecture for advertising, the procedures and necessary interfaces between TISPAN and SCTE-130 entities.

E.3.1 Definitions

Editor's note: Only specific definitions will be added for this option.

SCTE-130 has defined the following advertising entities in [26]:

- **Ad Decision Service (ADS):** The Ad Decision Service determines how advertising content is combined with non-advertising (i.e. entertainment) content assets. The decisions made by an ADS may be straightforward (i.e. specific ad content placed at a specific time in a specific asset) or arbitrarily complex (based on subscriber data, advertising zone, etc.).
- **Ad Management Service (ADM):** The Ad Management Service defines messages in support of ad insertion activities. The primary consumer of these messages is an ADS. The message interfaces exposed by an ADM allow for both preconfigured ad decisions as well as real-time fulfillment models. ADM detection of a placement opportunity is outside the scope of the specification. However, the ADM may be a service consumer of a POIS and/or a CIS in order to obtain such information.
- **Content Information Service (CIS):** The Content Information Service manages metadata describing all the assets (both advertising assets and non-advertising assets) available to the other SCTE 130 logical services. The CIS provides query and notification interfaces to the other logical services.
- **Placement Opportunity Information Service (POIS):** The Placement Opportunity Information Service (POIS) holds, maintains, or retains descriptions of placement opportunities.
- **Subscriber Information Service (SIS):** The Subscriber Information Service manages the per-subscriber information relevant to ad placement decisions. The SIS provides mechanisms surrounding privacy issues.

E.3.2 SCTE-130 based Advertising Architecture

Figure E.3 shows the interfaces between the SCTE-130 advertising specific entities and the TISPAN IPTV architecture.




Figure E.3 – Interaction between TISPAN IMS-based IPTV architecture and SCTE-130 advert entities

The SCF entity is interconnected with the Ad Decision service by the ADx reference point to request for placement decision.

POIS is an external entity. SIS may be either covered by SCF, by SCF and UPSF, or an external entity interfaced with SCF.

The MF entity is interconnected with the Ad Decision service by the ADy reference point to made ad-selection and ad-placement requests for broadcast services.

E.3.3 Reference points

E.3.3.1 IPTV Service Control Functions (SCF) – SCTE-130 External Ad system (ADx)

This reference point is used to exchange advertising related messages between SCF and an SCTE-130 external Advertising sub-system.

ADx reference point should be used to send and receive messages from/to the ADS, POIS and SIS entities and the TISPAN IPTV SCF

The use of ADx between SCF and ADS conforms to SCTE130-3 [28].

E.3.3.2 IPTV Media Function (MF) – SCTE-130 External Ad system (ADy)

This reference point is used to exchange advertising related messages between MF and an SCTE-130 external Advertising sub-system for broadcast services

ADy reference point should be used to send and receive messages from/to the ADS and the TISPAN IPTV MF.

The MF entity is interconnected with the Ad Decision service by the ADy reference point to made ad-selection and ad-placement requests for broadcast services

The use of ADy between MCF and ADS conforms to SCTE130-3 [28].

Editors note: Whether the ADy reference point must be the same as ADx is FFS

E.3.3.3 Procedures for targeted ad insertion (TAI)

Editor's note: Contributions are invited for defining the procedure between the IPTV nodes and the external system.

E.3.3.3.1 Signalling flows for TAI

E.4 OMA MobAd Based External Architecture Option

This clause specifies the OMA MobAd (Mobile Advertising) entities, complete architecture for advertising, the procedures and necessary interfaces between TISPAN and OMA MobAd entities.

E.4.1 Definitions

Editor's Note: Only MobAd specific definitions will be added here.

Editor's Note: the use of the term "reference point" in this document should be reviewed.

NOTE: In this annex OMA's usage of the term "interface" is followed for consistency, this may differs from the use in other TISPAN's specification.

Figure E.4 shows the OMA MobAd 1.0 architecture:




Figure E.4: OMA MobAd Architecture Diagram

OMA MobAd 1.0 has defined the following advertising entities in [30]:

- **Ad Server:** The Ad Server is a MobAd enabler component resident in the network (outside the device) that performs actions grouped in the following high-level functions:
 - Ad selection function: select the most appropriate Ad(s) /Ad Campaign(s) primarily using: Contextualisation and Personalisation information, Ad Metadata and applicable MobAd Rules.
 - Ad delivery function: the delivery of Ad(s)/Ad Campaigns can be done via Pull, Push or Broadcast.
 - Ad Metrics handling function: collect and process Ad Metrics data.
 - User / service data management function: manage user's Personalisation and Contextualisation data, MobAd Rules, user groups, Ad Channels etc.
- **Ad Engine:** The Ad Engine (see section 3.2 Definitions) is a MobAd Enabler component resident on the device that performs actions grouped in the following high-level functions:
 - Ad acquisition and delivery function: the acquiring of Ad(s)/Ad Campaigns can be done via Pull, Push or Broadcast.
 - Ad selection function: select Ads from the cache.
 - Ad metrics handling function: augment Ad Metrics data received from Ad Apps and report it to the Ad Server
 - User / service / device data handling function: gather and process user's Personalisation and Contextualisation data, monitor and process device static and/or dynamic status (e.g. device resource threshold) and apply MobAd Rules.
- **SP App (SP Application):** The SP App is an external entity that requests and receives Ad(s)/Ad Campaign(s) from Ad Server, and embeds them in content that is provided to the user. SP App records Ad Metrics data related to the Ad(s) and reports Ad Metrics data to the Ad Server.

- **Ad App (Ad Application):** The Ad App is an external entity running on the device that requests and receives Ad(s) from Ad Engine, and presents them to the user. Ad App also report Ad Metrics data to the Ad Engine.

The interfaces defined in OMA MobAd 1.0 are:

- MobAd-1 is an interface exposed by the Ad Engine to the Ad App. The Ad App uses this interface to request and obtain Ads and their associated Ads identifiers from the Ad Engine, as well as to report Ad Metrics data to the Ad Engine, accompanied by the associated Ads identifiers.
- MobAd-2 is an interface exposed by the Ad Server to the SP App. The SP App uses this interface to request and obtain Ad(s), reference(s) to Ad(s), associated Ad(s) identifiers and possibly additional information (to be determined in the TS stage), as well as to report Ad Metrics data, accompanied by the associated Ad(s) identifier(s).
- MobAd-3 is an interface exposed by the Ad Server to the Ad Engine. The Ad Engine uses this interface to request and obtain Ad(s), reference(s) to Ad(s), their associated Ad(s) identifier(s) and Ad Metadata from the Ad Server, as well as to report Ad Metrics data to the Ad Server, accompanied by the associated Ad(s) identifier(s).
- Delv-1 is an optional interface exposed by the Ad Engine. The Ad Engine receives Ad(s) and/or Ad Metadata over this interface from the Ad Server via underlying push and/or broadcast delivery mechanisms. The Ad Server uses this interface to push either Ad(s) or notification that Ad(s) are available for retrieval. The Ad Server may also use this interface to provide service notification to the Ad Engine.

E.4.2 OMA MobAd based Advertising Architecture

Figure E.5 shows the interfaces between the OMA MobAd advertising specific entities and the TISPAN IPTV architecture.

Draft




Figure E.5 – Interaction between TISPAN IMS-based IPTV architecture and OMA MobAd entities

The SCF / MCF entities can be considered as SP App in MobAd and are interconnected with the Ad Server by the MobAd-2 interface to request for placement decision.

The UE is interconnected with the Ad Server by the MobAd-3 interface to request Ad in case of Ad pulling.

E.4.3 Reference Points

E.4.3.1 IPTV SCF / MCF – MobAd External Ad system (MobAd-2)

This interface is used to exchange advertising related messages between SCF / MCF and a MobAd external Advertising sub-system.

MobAd-2 interface should be used to exchange messages between the Ad Server and the TISPAN IPTV SCF / MCF.

The use of MobAd-2 interface between SCF / MCF and Ad Server conforms to OMA MobAd AD [30].

E.4.3.2 IPTV UE – MobAd External Ad system (MobAd-3)

This interface is used to exchange advertising related messages between UE and a MobAd external Advertising sub-system.

MobAd-3 interface should be used to for the UE to request Ad from the Ad Server.

The use of MobAd-3 interface between UE and Ad Server conforms to OMA MobAd AD [30].

E.4.4 Procedures for Targeted Ad Insertion (TAI)

E.4.4.1 Signalling Flows for TAI

Editor's note: Contributions are invited for defining the procedures between the IPTV nodes and the external OMA AD system.

Annex F: Mapping between TISPAN entities and external architectures (Informative)

Annex F.1 describes a mapping of the functional entities defined by others Advertising standards with the TISPAN IPTV functional entities.

F.1 Mapping between TISPAN entities and SCTE-130 entities

This clause describes a mapping of the functional entities defined by SCTE with the TISPAN IPTV functional entities.

Placement Opportunity Information Service (POIS) and Ad Decision Service (ADS) are considered out of scope of TISPAN architecture because placement opportunities providing and Advert placement decision are not defined as TISPAN entities tasks. Link between ADS and ADM is considered as a reference point in scope of TISPAN.

Other modules can be mapped with current TISPAN entities as they cover TISPAN entities tasks.

In the table below, is presented entities defined in the SCTE-130, their roles and concerned TISPAN entities:

Table F.1 :

SCTE-130 entity name	Role	TISPAN Entity concerned	TISPAN entity task covered
POIS	Provides placement opportunities	Out of scope (external entity)	-
SIS	Manage subscriber information relevant for Ad	SCF / UPSF / External entity	SCF task from § 5.1.5.2 : Select appropriate ad content for specific user or user group, based on user profile (e.g. user preference, shopping habits, location information, etc.) and IPTV service status (e.g. current BC program ID, commercial break

			in BC service or pause during CoD content playback)..
CIS	Manage assets metadata	SCF	SCF task from § 5.1.5.2 : Select appropriate ad content for specific user or user group, based on user profile (e.g. user preference, shopping habits, location information, etc.) and IPTV service status (e.g. current BC program ID, commercial break in BC service or pause during CoD content playback)..
ADM	Provides placement opportunities based on POIS and CIS information Defines messages for Ad insertion Activities	SCF (for TAI) and MCF (for Broadcast)	SCF tasks from § 5.1.5.2 : Select appropriate ad content for specific user or user group, based on user profile (e.g. user preference, shopping habits, location information, etc.) and IPTV service status (e.g. current BC program ID, commercial break in BC service or pause during CoD content playback).. Send ad insertion indication to MF MCF tasks from § 5.1.5.3 : Handle ad insertion control of MDF, i.e. control the fetching of the ad content and synchronization between ad content and IPTV content, including accounting for delay or drift in broadcast TV schedules.
ADS	Decide ad placement relative to content based on ADM placement opportunities	Out of scope (external entity)	-

F.1 Mapping between TISPAN Entities and OMA MobAd Entities

TISPAN entities can use the interfaces exposed by Ad Server and Ad Engine for advertising purposes.

Modules can be mapped with current TISPAN entities as they cover TISPAN entities tasks.

The table below shows the presented entities defined in the OMA MobAd, their roles and concerned TISPAN entities:

Table F.2:

OMA MobAd entity name	Role	TISPAN Entity concerned	TISPAN entity task covered
Ad Server	Ad selection, Ad delivery, Ad Metrics data handling, data management	Out of scope	Use the interface exposed by Ad Server
Ad Engine	Ad selection, Ad acquisition and delivery, Ad Metrics data handling, data management	UE	<p>UE task from 8.14:</p> <p>When the ad insertion takes place at UE side, the UE is informed by ad insertion indication from SCF in charge of Ad service, and initiates individual session request for Ad content, which implies that multiple sessions exist on the UE during the ad insertion time.</p>
SP App	Request and receive Ad, insert Ads to the content, report Ad Metrics data	SCF / MF	<p>SCF task from § 5.1.5.2 :</p> <p>Select appropriate ad content for specific user or user group, based on user profile (e.g. user preference, shopping habits, location information, etc.) and IPTV service status (e.g. current BC program ID, commercial break in BC service or pause during CoD content playback).</p> <p>MDF task from § 5.1.5.3 :</p> <p>Recognize appropriate in-band /out-of-band Ad insertion indicators (eg-cue messages as defined in ITU-T J.181), when present. These Ad insertion indicators define positions within the IPTV content where advertisement content can be inserted /replaced. This task may be done by coordination with an external advertising sub-system</p>
Ad App	Request and receive Ad, report Ad Metrics data	UE	<p>UE task from 8.14:</p> <p>When the ad insertion takes place at UE side, the UE is informed by ad insertion indication from SCF in charge of Ad service, and initiates individual session request for Ad content, which implies that multiple sessions exist on the UE during the ad insertion time.</p>

Annex G (informative): Ad placement options

This annex presents several possibilities of instantiation of Ad placement by existing mechanism from other SDOs.

G.1 IPTV Ad placement: SCTE-130 option

In SCTE-130 [28], four types of ad insertion opportunities exists:

- Pre-roll (a placement opportunity preceding an entertainment asset)
- Post-roll (a placement opportunity following the play out of an entertainment asset)
- Interstitial (a placement opportunity occurring during the play out of an entertainment asset)
- Pause (placement opportunity as a result of a subscriber pressing the pause button)

They can be separated in two options : predetermined placement opportunities (Pre/Post roll and Interstitial) and unexpected placement opportunities (Pause).

The predetermined option should be used for the following types of stored contents : BC, COD, NPVR and UGC contents.

The unexpected option could be used for all sorts of stored contents: BC with trick mode, COD, NPVR, UGC, timeshift.

Annex H (informative): Interconnection Models to support of Mobility Capabilities

TISPAN IMS based IPTV can recognize at least the following basic scenarios for roaming and interconnection to home network (not need support all of them):

- a) pure data access remotely to IPTV SP/content provider
- b) IMS interconnect to home IPTV provider (described in H.1)
- c) visited – home network roaming between IPTV providers (served only from home network)
- d) visited – home network roaming between IPTV providers (served from home and/or visited network)

Scenario A: IMS based IPTV user accessing via remote data access to home IPTV SP

Because the UE accessing home IPTV SP from remote network without IMS, the user must use to connect UE to his home network some remote data IP connection (e.g. VPN or secure remote access). Over this connection can be transferred all media and signaling to the subscriber directly from his Home Network. Because such a connection should going over any IP network (also best effort) also without resource reservation mechanisms, no QoS can be really ensured.

Editor's Note: Whether this scenario is out of scope of TISPAN is for future consideration.

Scenario B: IMS based IPTV roaming with visiting IMS provider without IMS based IPTV solution

This scenario is the simplest one with using core IMS. User will use IPTV services provided from IPTV functional elements from his Home Network. The IMS elements of visited network must do just IMS roaming via network attachment and registration in visited network and forward all other request to home network and its IMS IPTV SP (e.g. registration, service discovery/selection, service initiation/modification/termination). Service selection information and media are delivered from Home network over interconnection.

The quality of the IPTV service for the end customer should be same as in home network (when interconnection and visited network assure enough resources and QoS), but no reuse of local media delivery resources for the provider is possible (because in visited network have no IMS based IPTV platform).

NOTE: This scenario is described in subsection H.1.

Scenario C: IMS based IPTV roaming with visiting IPTV Service Provider with TISPAN IMS-IPTV solution (only home served)

Additionally to the previous scenario the following one expects the IMS based IPTV platform is available in Visited Network, however all content and services are delivered only from Home Network. This solution expect that delivery of the content, metadata and service discovery, selection and service initiation, modification and termination will be done from home network. Also it could be required from Home Network IMS based IPTV solution to provide transcoding and content adaptation to adapt media to parameters required for entering the Visited Network (or this could be done in edge of visited network).

Scenario D: IMS based IPTV roaming with visiting IPTV Service Provider with IMS-IPTV solution (home and/or partially visited IPTV platform served)

If there is an IPTV solution in Visited Network, possibly having similar content for CoD, BC, PVR service, it is useful and more efficient to use this local resources in visited network as deliver all content over interconnection. The content which is available in Visited Network is not needed to be transferred over an interconnection network and allocate interconnection bandwidth/resources. For this purpose both providers should agree on the same identification of content, sharing service discovery and selection information, content security, billing clearing, and for sure about all parameters required for roaming agreements (e.g. QoS, Service Level Agreement). Other IPTV services or content not available in offer of visited IMS IPTV SP are provided as in previous scenario by home network and by user home IPTV service provider.

Editor's note: Using IMS roaming for IPTV services cross home and visited network may need additional investigation (probably involvement of WG4, WG7, WG8) about the interconnection and also need to be clarified if mentioned interfaces could cross domains.

Editor's note: Interconnection model for scenarios C and D is for FFS and relation to HWI Interconnection need to be clarified.

H.1 Interconnection model using IMS roaming to home IMS IPTV

Figure H.1 illustrates the model of interconnection with the Visited Network within Core IMS involved. UE can request IPTV services in the Home Network by connecting to the Visited Network. Core IMS in the Visited Network can request resources from the RACS in the Visited Network through the interface Gq'. Core IMS in the Home Network can request resources from the RACS in the Home Network through the interface Gq'. UE can attach to the Visited Network through the interface e1 so that the NASS in the Visited Network can assign IP address for the UE and discovery the address of P-CSCF in the Visited Network. Core IMS in the Visited Network can transfer the IPTV service request from the UE through the interface Ic to the Core IMS in the Home Network through the connection of their own IBCF(Intermediate Breakout Control Function). UE can connect the SSF to select IPTV services through the interface Xa which is already defined. UE can connect to the IPTV SCF to configure parameters through the interface Ut which is already defined. Core IMS in both network connect to their own UPSF to get user profiles through their own interface Cx.

Editor's note: Using IMS roaming for IPTV services cross home and visited network may need additional investigation (probably involvement of WG4, WG7, WG8) about the interconnection and also need to be clarified if mentioned interfaces could cross domains.




Figure H.1

H.2 Signalling flows

The sub-clauses below explain the signalling flows of UE start-up procedures and CoD procedures when the UE is located in the Visited Network. In Broadcast procedures, N-PVR and other services, they are similar as CoD procedures.

NOTE: Following procedure are indicative to show one possible way how should IMS roaming be handle between home and visited network.

H.2.1 UE start-up procedures




Figure H.2

- 1) Network Attachment
In this step the UE attaches to the network. The procedures for network attachment are defined in ES 282 004 [3]. This step includes IP configuration, P-CSCF address discovery of Visited Network, etc.
- 2) IMS Registration in Visited Network
In this step, the UE performs regular IMS Registration as defined in TS 182 006 [2].
- 3) P-CSCF within Core IMS in Visited Network submits the registration request to the I-CSCF within the Core IMS in the Home Network.

In this step, the UE performs regular IMS Registration as defined in TS 123 002.
- 4) Core IMS in the Visited Network return parameters (e.g. P-CSCF address of Home Network) to the UE.
- 5) The step is the same as step 3~4 in Figure 9 of clause 8.2.

H.2.2 CoD procedures




Figure H.3

- 1) The UE initiates a dialogue to the CoD service and submit the request to the Core IMS in the Visited Network.
- 2) Core IMS in the Visited Network forwards the request to the Core IMS in the Home Network.
- 3) The session initiation request is routed by the Core IMS in the Home Network up to the SCF.
- 4) The SCF performs service authorization as described in clause 5.1. If the UE is allowed to access the content, the SCF forwards the session initiation request to the selected MF.

- 5) Signalling procedures for establishment of a content control channel and optionally content delivery channels take place between the UE and the MF (see similar clause 8.4.1.1).
- 6~8) The steps are the same as step 7~10 not including step 8 in the figure 21 of clause 8.4.1.1.
- 9) The Core IMS in the Home Network forwards this confirmation to the Core IMS in the Visited Network.
- 10) The P-CSCF within the Core IMS in the Visited Network interacts with the RACS in the Visited Network to commit all resources previously reserved. This includes opening pinholes for exchanging content control messages and/or content delivery.
- 11) The P-CSCF in the Visited Network forwards the dialogue confirmation to the UE.

After this point, UE may use the content control channel to request content to be streamed and the actual content will then be delivered to the UE. The content control channel will also be used to carry UE requests for controlling the streams, e.g. "pause", "fast forward", etc.

NOTE: Resources reserve/commit between Core IMS and RACS in the home network is optional when selected MF in the visited network servers the UE.

Editor's note: This Annex to be removed prior to publication unless otherwise decided or handled.

Annex ZZY (informative): Possible mappings with IMS based IPTV

Editor's note: Further contributions are invited to show possible mapping of IPTV or Mobile TV architectures to TISPAN NGN IMS based IPTV.

ZZY.1 Possible conceptual mapping of 3GPP IMS based PSS and MBMS with TISPAN IMS based IPTV

The IP Multimedia Subsystem (IMS) enables the deployment of IP multimedia applications. PSS and MBMS User Services are IP multimedia services but they were specified by 3GPP before IMS. IMS brings enablers and features to operators and subscribers that can enhance the experience of PSS and MBMS User Services.

Main goal of this section is principal concept for providing selected TISPAN IPTV services to mobile UE over 3GPP mobile access networks supporting unicast based streaming services (using PSS) or multicast based streaming services (using MBMS).

Section will explain how IMS based IPTV from TISPAN may be combined with 3GPP PSS and MBMS based on 3GPP IMS based PSS and MBMS [31].

NOTE: There should be a limitations which services could be provided over such a combined architecture (TISPAN IMS based IPTV with support for PSS or MBMS based streaming).

Editor notes: Further contributions are invited to explain gaps or additional details, service or technical limitations in proposed mappings of 3GPP IMS based PSS & MBMS to TISPAN NGN IMS based IPTV.

ZZY.1.1 Mapping between TISPAN entities and 3GPP IMS based PSS and MBMS

The table below (Table ZZY.1) shows the presented entities defined in the 3GPP IMS based PSS and MBMS user services, their roles and concerned TISPAN entities.

Table ZZY.1: Conceptual mapping of functional entities

3GPP Entity	3GPP entity tasks [TS 26.237] Section 4.2.2	TISPAN Entity	TISPAN entity task covered
Service Discovery Function	this function provides an entry point to SSF for the client to attach to the service provided by the service provider	SDF 5.1.5.1	provides the service attachment information. Provides personalized service discovery
Service Selection Function	provides a list of available PSS and MBMS User Services and relevant User Service Description information	SSF 5.1.5.1	Provides the service selection information
Service Control Function	Provides service logic and functions required to support execution of such logic. Service authorization during session initiation and session modification, which includes checking PSS and MBMS user's service subscription in order to allow or deny access to the service. Selects the relevant PSS and MBMS media functions.	SCF 5.1.5.2	SCF is a SIP Application Server Service authorization during session initiation and session modification Select the relevant IPTV media functions
PSS Server (PSS adapter)	Packet Switch Streaming server function as described in 3GPP TS 26.234 [8]. It functionally contains media control and media delivery functions	MF 5.1.5.3 MCF &MDF	Handling media flow control Handling media flows delivery
UE	The UE contains an GBA/IMS/PSS/MBMS client, which performs service discovery and selection, handles service initiation, modification and termination, receives and present the content to the user.	UE	The IPTV enabled UE terminates the IPTV control and media signals, and displays the corresponding information to the user.
IM CN subsystem	IMS Core Network Subsystem [3GPP TS 23.228]	Core IMS	is a subset of the 3GPP IMS defined in TS 123 002 (TS 23.228)
PS Core/RAN	Packet Switch Core Network and Radio Access Network. See 3GPP TS 23.060.		IP-based transport layer
HSS	Home Subscriber Server as defined in 3GPP TS 23.002. Contains the IMS User Profile. It also may contain PSS and MBMS User Service specific User and UE data.	UPSF	IMS user profile and possibly IPTV specific profile data (see clause 7)

Editor's Note: BSF: Bootstrapping Server Function (BSF), PCRF: Policy and Charging Rules Function or Broadcast Multicast Service Centre (BM-SC) can we investigate if they have any equivalent entities in TISPAN.

NOTE: The BM-SC Membership function and Proxy and Transport function are defined in 3GPP [TS 23.246]. The BM-SC Membership function is invoked for the establishment and release of Multicast bearers. ECF/EFF have similar task in TISPAN architecture to join IP multicasted media streams.

For TISPAN MF entities to serve mobile (i.e. PSS or MBMS enabled) UEs, adaptation of MF related signaling and media streams is needed as indicated in figure ZZY.1.

Editor's note: Further contributions are invited to explain gaps or additional details in proposed mappings of functional elements.

ZZY.1.2 Mapping between 3GPP IMS based PSS and MBMS and TISPAN IMS based IPTV architecture

Figure ZZY.1 shows the interfaces between the 3GPP IMS based PSS and MBMS specific entities and the TISPAN IPTV architecture.




Figure ZZY.1: Conceptual mappings of 3GPP PSS and MBMS with TISPAN IMS based IPTV

ZZY.1.3 Mapping to TISPAN reference points

The table below (Table ZZY.2) shows the interfaces described in the 3GPP IMS based PSS and MBMS and their mapping with TISPAN reference points.

Table ZZY.2: Conceptual mapping of reference point

3GPP interface	Description of 3GPP interface [TS 26.237] Section 4.2.2	TISPAN ref. point	Note

1	between the UE and the SSF is used to retrieve service selection information	Xa	Equivalent to the Xa interface in TISPAN IPTV
2	between the UE (IMS Client) and the P-CSCF	Gm	TISPAN refer to Gm
3	UE (PSS Client) and the PSS Adapter allows media flow control	Xc	In TISPAN used to exchange media control messages for controlling media flow
4	between the PSS Server and the UE is for delivery of streaming data	Xd	In TISPAN used to deliver media data
8, 12	Between IM CN subsystem and the SCF is an ISC (IMS Service Control)	ISC	TISPAN refer to ISC
9	interface between the IM CN subsystem and the PSS adapter	Y2	service control signalling originating from the SCF to control the MCF
13	between the UE and SCF	Ut	equivalent to the Ut interface in TISPAN IPTV

NOTE 1: 3GPP interface no.5) This interface between the BMSC.UPF and the UE is for delivery of streaming data and traffic keys. This one have no direct mapping to TISPAN reference point. Partially have similar purpose as reference point between UE and ECF/EFF to deliver multicasted media stream (or to MDF if play role as source of multicast stream).

NOTE 2: 3GPP interface no.6) Gmb: This interface sits between the BMSC.UPF and the GGSN have no equivalent UE in TISPAN.

NOTE 3: Interfaces 10, 14, 15, 16, 17, 18 have no equivalent exact in TISPAN.

Editor notes: Further contributions are invited to explain gaps or additional details in proposed mappings of 3GPP PSS & MBMS architecture, FE, reference points to TISPAN NGN IMS based IPTV.

Annex ZZZ(informative): Change history:

Change history							
Date	WG Doc.	CR	Rev	CAT	Title / Comment	Current Version	New Version
30-05-08	17bTD256r1	001		A	Fixing Figure 34 in TS 182 027 for Release 3. Corresponds to 17bTD260	3.0.0	3.0.1
30-05-08	17bTD255r2	002	1	D	16 Editor's notes on Release 3, Guidance to contributors	3.0.0	3.0.1
06-06-08	17bTD195r3	003	1	B	Notification procedures	3.0.0	3.0.1
02-07-08	18WTD074r2	004		F	Corrections in step numbering	3.0.1	3.0.2
02-07-08	18WTD052r4	005	1	B	WI2070 User generated content in IPTV architecture	3.0.1	3.0.2
02-07-08	18WTD070r3	006		B	Modification of content distribution related description in clause 12	3.0.1	3.0.2
02-07-08	18WTD086r2	007		D	Proposal for ToC of TS182 027 on value added services	3.0.1	3.0.2
02-07-08	18WTD138r3	008		B	Service Control function for IPTV content recommendation service	3.0.1	3.0.2
02-07-08	18WTD139r2	009		B	Include procedures for IPTV recommendation service	3.0.1	3.0.2
02-07-08	18WTD140r1	010		D	Clarification of notification service	3.0.1	3.0.2
02-07-08	18WTD181r1	011		B	Network-initiated CoD session	3.0.1	3.0.2
02-07-08	18WTD071r6	012		B	Support Push CoD service in IMS-based IPTV Architecture	3.0.1	3.0.2
02-07-08	18WTD082r4	013		C	Reselection of MDF	3.0.1	3.0.2
02-07-08	18WTD083r7	014		C	Notification using media path	3.0.1	3.0.2
02-07-08	18WTD085r2	015		B	Advertising functions in IPTV architecture	3.0.1	3.0.2
02-07-08	18WTD084r3	016		B	User Profile for Parent Control	3.0.1	3.0.2
01-10-08	18bTD288r1	017		D	WI2070 ToC Drafting: Changes to clauses 5 and 8	3.0.2	3.0.3
01-10-08	18bTD194r1	018		B	Session Transfer procedure	3.0.2	3.0.3
01-10-08	18bTD257r1	019		A	WI2070, adding references to stage 1	3.0.2	3.0.3
01-10-08	18bTD143r2	020		B	Sharing Bookmarks Between Multiple IPTV Users	3.0.2	3.0.3
01-10-08	18bTD170r3	021		D	Generic SCF and MF	3.0.2	3.0.3
01-10-08	18bTD169r2	022		D	"CoD-based" UGC procedures	3.0.2	3.0.3
01-10-08	18bTD085r2	023		B	UGC Functions in IPTV Architecture	3.0.2	3.0.3
01-10-08	18bTD080r3	024		B	IPTV Advertising Service Procedures	3.0.2	3.0.3
01-10-08	18bTD076r2	025		B	Procedure of CoD content preview	3.0.2	3.0.3
01-10-08	18bTD079r3	026	1	B	Personalized Channel Functions	3.0.2	3.0.3
01-10-08	18bTD128r3	027		B	Architectures for NGN Service Blending	3.0.2	3.0.3
01-10-08	18bTD131r3	028		B	WI2070 Synchronization Architecture	3.0.2	3.0.3
01-10-08	18bTD196r2	029		A	Correction of inconsistency of IPTV presence timer definition between stage 2 and 3	3.0.2	3.0.3
01-10-08	18bTD091r5	030		C	Clarification of Push CoD service	3.0.2	3.0.3
01-10-08	18bTD224r4	031		B	WI2070 messaging	3.0.2	3.0.3
01-10-08	18bTD130r3	032		B	Network-controlled Trick Play	3.0.2	3.0.3
01-10-08	18bTD081r4	033		B	Deliver Messages Associated with a BC Service Using Media Path	3.0.2	3.0.3
01-10-08	18bTD094r6	034		B	Clarification of Network initiated service	3.0.2	3.0.3
01-10-08	18bTD095r4	035		B	Procedures of Network initiated BC service	3.0.2	3.0.3
06-11-08	19WTD047r1	036		D	Typo Correction Fig C1	3.0.2	3.0.4
06-11-08	19WTD192r2	037		B	IPTV Elementary functions	3.0.2	3.0.4
06-11-08	19WTD179r1	038		B	Addition of playlist generation task for SCF	3.0.2	3.0.4
06-11-08	19WTD093r2	039		B	Functions and Procedures for CRS	3.0.2	3.0.4
06-11-08	19WTD175r2	040		F	Cleaning up references [2] and [12]	3.0.2	3.0.4
06-11-08	19WTD140r2	041		F	Advertising Procedures- Name Update	3.0.2	3.0.4
06-11-08	19WTD143r3	042		B	Advertising Procedures- MCF Role	3.0.2	3.0.4
12-11-08	19WTD091r2	043		B	Capability of SCF on event detection	3.0.2	3.0.4
12-11-08	19WTD092r3	044		B	PVR procedures	3.0.2	3.0.4
12-11-08	19WTD094r3	045		B	Procedures for PPV Service	3.0.2	3.0.4
12-11-08	19WTD050r2	046		B	User Generated Content Session Coordination	3.0.2	3.0.4
12-11-08	19WTD051r2	047		B	User Generated Content Procedures Coordination note	3.0.2	3.0.4
12-11-08	19WTD095r2	048		B	Uploading of UGC Content Description	3.0.2	3.0.4
12-11-08	19WTD144r3	049		C	Traditional Broadcast Advertising Procedures	3.0.2	3.0.4
12-11-08	19WTD111r2	050		F	COD offset use	3.0.2	3.0.4
12-11-08	19WTD177r3	051		B	IPTV Bookmark data model	3.0.2	3.0.4
12-11-08	19WTD142r7	052		C	Advertising Procedures- MDF Role	3.0.2	3.0.4
12-11-08	19WTD149r1	053		F	Alignment of terminology for the IMS-based IPTV procedures	3.0.2	3.0.4
14-11-08					CRs 17 to 53 TB approved at TISPAN#19 and clean-up by ETSI Secretariat	3.0.4	3.1.0
05-12-08	19bTD169r2	054		D	WI2070 editorial fixes	3.1.0	3.1.2
05-12-08	19bTD164r1	055		A	Deleting informative reference to IPTV stage 1	3.1.0	3.1.2
05-12-08	19bTD054r1	056		F	Editorial change	3.1.0	3.1.2
05-12-08	19bTD117r1	057		B	Personalized Stream Composition	3.1.0	3.1.2
05-12-08	19bTD184r2	058		C	Targeted ad insertion clarification	3.1.0	3.1.2
05-12-08	19bTD125r4	059		B	IPTV Service Access History Data Model	3.1.0	3.1.2
05-12-08	19bTD112r2	060		C	Clarification of notification procedures	3.1.0	3.1.2

05-12-08	19bTD131r1	061		B	Elementary functions mapping	3.1.0	3.1.2
05-12-08	19bTD180r1	062		A	Multiple services packages in BC session initiation	3.1.0	3.1.2
05-12-08	19bTD185r1	063		F	Clarification on User Profile configuration	3.1.0	3.1.2
05-12-08	19bTD086r3	064		B	Modification of targeted advertising flows for CoD services	3.1.0	3.1.2
05-12-08	19bTD153r2	065		F	Signalling flow at MF side	3.1.0	3.1.2
05-12-08	19bTD113r2	066		B	Event Handling-Involving SCF	3.1.0	3.1.2
05-12-08	19bTD114r2	067		B	IPTV Status Detection	3.1.0	3.1.2
05-12-08	19bTD059r3	068		B	PCh Specific Information	3.1.0	3.1.2
05-12-08	19bTD087r3	069		B	Addition of Signalling flows of playlist generation by SCF and playlist acquisition by MF from SCF	3.1.0	3.1.2
05-12-08	19bTD128r5	070		B	Push CoD service procedures	3.1.0	3.1.2
05-12-08	19bTD182r1	071		F	Obsolete use of BC MCF/SCF	3.1.0	3.1.2
05-12-08	19bTD218r2	072		D	Editor notes for open issues	3.1.0	3.1.2
05-12-08	19bTD055r3	073		B	Add Signalling Flows for CoD service action data update	3.1.0	3.1.2
05-12-08	19bTD061r3	074		B	Generic Content Upload/Download Procedures	3.1.0	3.1.2
05-12-08	19bTD056r4	075		B	Procedures for Restricted Trick Play	3.1.0	3.1.2
05-12-08	19bTD152r5	076		B	Advert alignment SCTE	3.1.0	3.1.2
05-12-08	19bTD154r3	077		F	Content recommendation attributes in user profile	3.1.0	3.1.2
05-12-08	19bTD130r4	078		B	IPTV roaming in IMS-based IPTV Architecture	3.1.0	3.1.2
05-12-08	19bTD183r4	079		B	Shared content procedures	3.1.0	3.1.2
05-12-08	19bTD212r5	080		C	PPV- Adding required step to call flows in clause 8.3.8	3.1.0	3.1.2
05-12-08	19bTD181r2	081		C	Alternative solution for PPV	3.1.0	3.1.2
05-12-08	19bTD193r4	082		D	Clarification of CoD Session Transfer	3.1.0	3.1.2
05-12-08	19bTD129r7	083		C	Modification of UGC procedures	3.1.0	3.1.2
05-12-08	19bTD060r3	084		B	Personalized Channel Procedures	3.1.0	3.1.2
30-01-09	19tTD197r1	085		D	Editor's note on relationship between Xc and BC tasks	3.1.2	3.1.3
30-01-09	19tTD078r3	086		C	Clarification of UGC Creation Procedure	3.1.2	3.1.3
30-01-09	19tTD079r2	087		C	Clarification of UGC Watching Procedure	3.1.2	3.1.3
30-01-09	19tTD080r4	088		B	Procedure for Personal Service Composition	3.1.2	3.1.3
30-01-09	19tTD081r2	089		C	Synchronization of Shared Content	3.1.2	3.1.3
30-01-09	19tTD082r2	090		B	Synchronization Procedures	3.1.2	3.1.3
30-01-09	19tTD147r1	091		C	Playlist parameters	3.1.2	3.1.3
30-01-09	19tTD202r2	092		D	Cleanup of IPTV Bookmark Terminology	3.1.2	3.1.3
30-01-09	19tTD149r3	093		B	Shared Service Control procedure	3.1.2	3.1.3
30-01-09	19tTD183r2	094		F	Modification on procedures for shared content	3.1.2	3.1.3
30-01-09	19tTD101r1	095		F	Modifications to Flows and Assumptions in Session Transfer	3.1.2	3.1.3
30-01-09	19tTD107r2	096		B	Signalling Flows for IPTV Favourites procedures	3.1.2	3.1.3
30-01-09	19tTD185r3	097		B	Reuse Media Channel for CoD Services	3.1.2	3.1.3
03-03-09	20WTD224r1	099		F	Correcting figure 7	3.1.3	3.1.4
03-03-09	20WTD093r1	100		C	Alignment of UGC watching with CoD procedures	3.1.3	3.1.4
03-03-09	20WTD223r1	102		D	IPTV Content Marker cleanup	3.1.3	3.1.4
03-03-09	20WTD197r2	103		B	Metadata exchange with SSF	3.1.3	3.1.4
03-03-09	20WTD072r1	104		B	Support for Bypassing BGF in IPTV Flows	3.1.3	3.1.4
03-03-09	20WTD087r3	105		C	PVR Content Update Procedure	3.1.3	3.1.4
03-03-09	20WTD125r2	106		F	Resolve Editor's Notes for PVR service	3.1.3	3.1.4
03-03-09	20WTD076r2	107		B	Unclear specification for notification on the media stream in conjunction with BC service	3.1.3	3.1.4
03-03-09	20WTD092r2	108		C	IPTV service status	3.1.3	3.1.4
03-03-09	20WTD126r2	109		D	Amendments on Advertising Related Clauses	3.1.3	3.1.4
03-03-09	20WTD122r4	110		B	Preview Procedures for BC Service	3.1.3	3.1.4
03-03-09	20WTD288r3	111		B	Add Procedures for Service Initiation by Remote UE	3.1.3	3.1.4
03-03-09	20WTD123r4	112		B	Add Procedure for UGC Creation Session Initiated by Remote UE	3.1.3	3.1.4
03-03-09	20WTD128r3	113		B	Delete Editor's Note: UGC Creation Procedures	3.1.3	3.1.4
03-03-09	20WTD074r2	114		B	Incomplete specification on Personalized Channel service	3.1.3	3.1.4
03-03-09	20WTD127r6	115		B	Content related Content Marker Retrieving Procedure	3.1.3	3.1.4
03-03-09	20WTD073r3	116		B	Unclear Messaging Procedures	3.1.3	3.1.4
03-03-09	20WTD130r3	117		B	PPV User Profile Definition	3.1.3	3.1.4
03-03-09	20WTD086r3	118		C	SSC procedures clarifications	3.1.3	3.1.4
10-03-09					CRs 54 to 118 (except 98) TB approved at TISPAN#20	3.1.4	3.2.0
25-03-09	20bTD207r1	119		D	Fixing figure 8B	3.2.0	3.2.1
25-03-09	20bTD120r1	120		B	Clarification on UGC Creation Session	3.2.0	3.2.1
25-03-09	20bTD119r1	121		F	Delete Push CoD procedures in Annex B	3.2.0	3.2.1
25-03-09	20bTD230r2	122		B	Procedures for Shared Service Control	3.2.0	3.2.1
25-03-09	20bTD280r1	123		B	IPTV interconnection types	3.2.0	3.2.1
25-03-09	20bTD065r2	124		F	Correction on PVR Off-line Capture Request Procedures	3.2.0	3.2.1
25-03-09	20bTD067r2	125		B	CPVR User Profile Definition	3.2.0	3.2.1
25-03-09	20bTD244r3	126		B	IPTV_SCF-initiated UGC Watching	3.2.0	3.2.1
25-03-09	20bTD061r4	127		B	Personalized Channel Service Procedure	3.2.0	3.2.1
25-03-09	20bTD062r2	128		B	Clarification on Notification through Media Path	3.2.0	3.2.1
25-03-09	20bTD241r2	129		B	Synchronisation with SC in Transport	3.2.0	3.2.1
25-03-09	20bTD246r2	130		B	Synchronization and Transcoding	3.2.0	3.2.1

25-03-09	20bTD323r1	131		B	Note on Synchronisation	3.2.0	3.2.1
25-03-09	20bTD334r1	132		B	Proposal for revised Annex E	3.2.0	3.2.1
25-03-09	20bTD273r3	133		B	OMA MobAd Advertising Architecture Option	3.2.0	3.2.1
25-03-09	20bTD066r4	134		B	CPVR SAD data model definition	3.2.0	3.2.1
25-03-09	20bTD063r4	135		B	Publication of UGC Content Description	3.2.0	3.2.1
25-03-09	20bTD069r2	136		B	Push CoD procedure resumes SCF initiated unicast content download procedure	3.2.0	3.2.1
25-03-09	20bTD064r3	137		B	Clarification on UE-initiated Unicast Content Upload/Download	3.2.0	3.2.1
25-03-09	20bTD068r3	138		D	Message Transfer on Media Path	3.2.0	3.2.1
25-03-09	20bTD239r4	139		B	IPTV Service Identifier	3.2.0	3.2.1
25-03-09	20bTD026r8	140		B	Alignment of Session Transfer Call Flows with stage 1	3.2.0	3.2.1
06-04-09	20bTD028r7	141		B	Modifications to Targeted Advertisement section 8.14 and Annex F	3.2.0	3.2.2
25-03-09	20bTD109r4	142		B	Usage of presence for IPTV services	3.2.0	3.2.1
25-03-09	20bTD112r4	143		B	integration with 3GPP PSS or MBMS	3.2.0	3.2.1

History

Document history		
V3.0.0	May 2008	First input draft to TISPAN#17bis
V3.0.1	May 2008	Output draft of TISPAN#17bis ,17bTD331r1
V3.0.2	July 2008	Output draft of TISPAN#18WG, 18WTD075
V3.0.3	October 2008	Output draft of TISPAN#18bis, 18bTD336
V3.0.4	November 2008	Output draft of TISPAN#19WG, 19WTD217
V3.1.0	November 2008	CRs 17 to 53 TB approved at TISPAN#19 and clean-up by ETSI Secretariat
V3.1.2	December 2008	Output draft of TISPAN#19bis, 19bTD171
V3.1.3	January 2009	Output draft of TISPAN#19ter, 19tTD212
V3.1.4	February 2009	Output draft of TISPAN#20WG, 20WTD298; unimplemented CR098 – see WG report
V3.2.0	March 2009	CRs 54 to 118 (except 98) TB approved at TISPAN#20
V3.2.1	March 2009	Output draft of TISPAN#20WG, 20bTD344; CR141 pending email approval
V3.2.2	April 2009	Revised Output draft of TISPAN#20WG, 20bTD344r1; CR141 approved, numbering in clause 8 fixed, e-mail comment as of March 26 th reflected