3GPP TSG-T (Terminals) Meeting #9 Hawaii, USA, 20 - 22 September, 2000

3GPP TSG-SA5 (Telecom Management)

Tdoc S5-000322

Tdoc TP-000121

Category: Liaison

From: SA5

To: CN, RAN, T and IGC

Title: Service Management - New R00 work item proposal under SA5's

responsibility

TSG-SA WG5 (Telecom Management) has agreed during its Meeting #12 in Rome, Italy, 5-9 June 2000 a new R00 work item on "Service Management".

Three (3) documents had been approved by SA5, which are herewith submitted to the other TSGs for comment and subsequently to the next TSG SA (SA#8) for approval.

Attachments:

S5-000299	Work Item Proposal on Service Management Feature (TS 32.140)
S5-000300	Proposal for IGC Work plan update to include Service Management Feature (TS 32.140)
S5-000296	New TS Proposal: 32.140 "Service Management Requirements and Framework"

Work Item Description

Title Service Management (Feature)

1 3GPP Work Area

X	Radio Access
X	Core Network
X	Services

2 Linked work items

This work item will derive operational management requirements that need to be satisfied by solutions (e.g. MExE, QoS, Security) being developed in other 3GPP groups. A more precise list will be identified by the end of SA5#13 in July based on an exhaustive review of the Y2000 work-plan on contributions on operational requirements.

3 Justification

The move in Release 2000 towards supporting complex services will substantially increase the Service Management challenge from purely voice network concerns to include:

- Multimedia
- Data services
- Value Added Services
- Terminal and host applications
- Subscription Management & provisioning

4 Objective

This work item will capture the operational requirements and identify solutions necessary for this service management challenge.

It willdevelop:

- General Requirements
- Business Models for Service Management Actors
- Supply Chain solutions for Mobile Service Management
- 'Use cases' for Service Management Actors

It will derive all necessary Release 2000 Building Blocks and Work Tasks to support these detailed operational management requirements.

5 Service Aspects

This Feature will develop Service Management solutions to support the Supplementary Services Framework proposed in Release 2000.

6 MMI-Aspects

Yes for end user/consumer Service Management interactions with their Service Provider.

Charging Aspects
Yes
Security Aspects

Yes

9 Impacts

Affects:	USIM	ME	AN	CN	Others
Yes	X	X	X	X	
No					
Don't					
know					

10 Expected Output and Time scale (to be updated at each plenary)

				New spe	ecifications		
Spec No.	Title		Prime rsp. WG		Presented for information at plenary#	Approved at plenary#	Comments
32.120		gement rements &	SA5	SA2?	SA#8 June00		
			Affe	cted existi	ng specification	ns	
Spec No.	CR	Subject			Approved at		Comments
		TSG T (speci	fications	to be			
		TSG N (specidentified)	fications	to be			
	TSG R (specifications to be identified)						
32.101	TSG S (other specifications to be identified)		е				

Work item raporteurs

32.120 - Geoff Caryer

Work item leadership

SA5

13 Supporting Companies

BT, VoiceStream, Telenor, Telia, Sonera

14 Classification of the WI (if known)

Currently one building block and task has been identified, it is likely that more will be identified when the feature work is started and approved.

Feature (go to 14a)	
Building Block (go to 14b	
Work Task (go to 14c)	

14a The WI is a Feature: List of building blocks under this feature

(list of Work Items identified as building blocks)

14b The WI is a Building Block: parent Feature

(one Work Item identified as a feature)

14c The WI is a Work Task: parent Building Block

(one Work Item identified as a building block)

Tdoc S5-000300

Title: Proposal for IGC work plan update to include Service Management Feature (TS 32.140)

Inter Group Co-	Feature	Building block	WG: work task expected completion date
ordination			
Billing, charging and	Service Management	Service Management	\$5 Service Management Framework, Business Model, Use cases
management	Feature	Building Block	,initial case study on Subscription Management (Ordering,
			activation, modification, cessation)

Proposal for the Release 2000 Features, Building Blocks and Work Tasks Version 1.0

Introduction

This document proposes the 3GPP **Work Plan for Release 2000**. It describes the complete set of *R00 work items* and classify them as *feature*, *building block* and *work task*: a *feature* is subdivided into *building blocks* and a *building block* is subdivided into *work tasks* (definitions are given bellow).

This tree structure is established to ease the monitoring of the 3GPP work progress for R00, and to make explicit the purpose of the work assigned to one WG in the global system.

The aim of this Work Plan is to lead in a consistent way the activities of the full 3GPP community for the Release 2000.

Background

Short explanations of the concepts used in this document are provided bellow (extracted from SP-000109). **Feature:** New, or substantially enhanced functionality which represents added value to the existing system. A feature should normally embody an improved service to the customer and / or increased revenue generation potential to the supplier.

Building block: A sub-division of a feature, representing a set of technical functionality which would generally be expected to reside in a single system element, i.e. a single physical or logical entity or a single protocol. Building blocks may be "re-usable" - that is, a single building block may be common to two or more features.

Work task: A sub-division of a building block, representing a self-contained, well-scoped and well-scheduled item of work. A work task will almost certainly be the responsibility of a single Working Group. The output of a work task is the creation of one or more new Technical Specifications (or Reports) and / or Change Requests to existing TSs / TRs.

Work item: A generic term to refer to a given *feature*, *building block* or *work task*, i.e. all the individual elements of the table bellow should soon become work items (some work tasks may however be grouped within a single WI). A full description of the term *work item* can be found in the 3GPP Working Procedures, as detailed in the annex (the complete 3GPP Working Procedures can be found at http://www.3gpp.org/About 3GPP/3gpp wp.zip).

Status of review by the 3GPP Groups

This version encompasses the comments made by the Working Groups and the TSGs on version 0.9 or v.0.10. Most of the 3GPP WGs have reviewed the proposal, as shown in the following table.

Group	has reviewed v.0.9 or 0.10	comments
SA	No	This version will be reviewed at TSG SA#8.
S1 (services)	No	No time allocated at last meeting
S2 (architecture)	Yes	Originator of the proposal
S3 (security)	Yes	in tdoc S3-000305
S4 (Codecs)	partly	No meeting held. Comments from the chairman included.
S5 (OAM)	Yes	e-mail reviewed.
CN	Yes	in tdoc S2-000670, encompassing comments from N1 and N4.
N1 (CC, MM)	Yes	in tdoc S2-000670
N2 (CAP)	partly	e-mail discussion. No formal output.

N3 (IW)	Yes	in tdoc N3-000199
N4 (MAP)	Yes	in tdoc S2-000670
N5 (VHE)	partly	e-mail discussion. No formal output.
T	No	This version will be reviewed at TSG T#8.
T1 (testing UE)	No (not needed yet?)	
T2 (capabilities)	partly	No meeting held. Comments from the chairman included.
T3 (USIM)	No	
RAN	partly	Comments from F. Courau included according to decisions taken at RAN#7. This version will be reviewed at RAN#8.
R1 (radio phy.)	No	
R2 (RR)	Yes	R2-000836, R2-000938
R3 (Iu, Iur, Iub)	Yes	R3-001224
R4 (RF, BS testing)	No (not needed yet?)	

Next steps

Approval of Work Items:

All the Work Items identified in this document have to be officially approved. Several Work Items can nevertheless be approved using a single work item coversheet (in particular, several work tasks can be approved together).

Transfer from MS Word to MS Project:

This MS Word version has limited capabilities in term of readability. For this reason, the content of this document will be soon transferred to MS Project 98. This software will also provide some useful tools, like filtering the information to present only the work items to be fulfilled by a given (set of) WGs.

Contacts for comments

For sake of sharing the work load, S2 has established 12 Inter-Group Co-ordination (**IGCs**). Each IGC has the responsibility to monitor the work progress on a number of work items, and each work item is monitored by a single IGC. In case of inconsistencies, comments should be made to the responsible IGC's convenor. The e-mail addresses of all the IGC convenors are provided bellow.

	IGC	Convenor	convenor's e-mail address
1.	Bearer and Access	François Courau,	francois.courau@alcatel.fr
	Stratum	Alcatel	
2.	QoS	Oscar Lopez-Torres,	Oscar.Lopez@t-mobil.de
		T-Mobil	
3.	CC and roaming	Ulrich Dropmann,	Ulrich.Dropmann@icn.siemens.de
		Siemens	
4.	Codecs	Ian Doig,	IANDOIG1@email.mot.com
		Motorola	
5.	Messaging	Martin Guntermann,	martin.guntermann@d2mannesmann.de
		Mannesmann Mobilfunk	
6.	Terminal local features	Paul Voskar,	paul.voskar@nokia.com
		Nokia	
7.	Service platforms	Christophe Gourraud,	christophe.gourraud@lmc.ericsson.se
		Ericsson	
8.	Security	Chris Pudney,	chris.pudney@vf.vodafone.co.uk
		Vodafone-Airtouch	
9.	Billing, charging and	Yukio Hiramatsu,	hiramatu@MAGNET.NETLAB.NTT.CO.JP
	management	NTT	
10.	Testing	<i>N.N.</i> ,	by interim teuvo.jarvela@nokia.com
		Motorola	
11.	Location related issues	Jan Kall,	jan.kall@nokia.com
		Nokia	
12.	Overall Co-ordination and	Alain Sultan,	alain.sultan@etsi.fr
	general issues	ETSI/MCC	

Proposal for the Features, Building Blocks and Work Tasks of R00

Inter Group Co-	Feature	Building block	WG: work task expected completion date
ordination Bearer and Access Stratum	Evolution of transport	Evolution of the Transport in the UTRAN ¹	R3: Introduction of an option allowing an IP transport in the UTRAN
			R3: new RAB support (this belongs also to the RAN
			Improvements)
			R3: QoS optimisation for AAL2 connections
		Evolution of the Transport in the CN²	?: User/signalling data transport on TCP/RTP/UDP/IP
		* WI formulation assigned to N4	based bearers (Nb/Nc)
			?:User/signalling data transport on ATM/AAL2
			bearers (Nb/Nc)
			N4: Separation of call and bearer control
		T. I. d. a.p d. c.p.	N4: IP Transport of CN protocols (e.g., CAP, MAP)
		Evolution of Bearers in the CN ³	N4:Evolution of the bearers inside the PLMN
		* (Combine with above for WI)	N3:Evolution of the bearers at the inter-working point
	Padio Interface Improvement	Halarid ADO (Fee sibility stands)	with other types of networks
	Radio Interface Improvement	Hybrid ARQ (Feasibility study)	R2; R3
		Improved usage of CCTrCH (Feasibility study)	R2; R3
		High Speed DL packet Access 5feasibility study)	R2; R3
		Terminal Power Saving (Feasibility study)	R2; R3
		USTS (Feasibility Study)	R2; R3
	Low Chip Rate TDD ⁴	To be further investigated	R1; R2; R3; R4
	RAN improvement ⁵	RRM Support over Iub and Iur	R3: RRM optimisation (5 issues)
		Node B synchronisation for TDD ⁶	R3: Node B synchronisation for TDD
1.1			
1 These building block	ks are considered as independent.		

These building blocks are considered as independent.

These building blocks are considered as independent.

Transport and bearers are distinguished in this proposal because it is assumed that Bearer can be provided using different transport techniques as they shall fit the requirement in terms of QoS.

BB and WT associated to this feature are still under discussion

These building blocks shall be considered as independent from any features and followed as such.

		Improvement of Inter-Frequency and	R2; R3
		Intersystem measurement (Feasibility study)	
		BTS classification	R2; R4: At least, two aspects have to be covered: FDD
			BTS and TTD BTS
QoS	Real Time QoS for packet services	HOs: maintenance of real-time QoS while	S2: End-to-End multimedia QoS negotiation, <i>Sept</i>
	including VoIP	moving between cells in the PLMN including	N1: End-to-End multimedia QoS negotiation <i>Nov</i>
		inter-SGSN change and SRNS relocation or	New or enhanced packet handling procedures to
		possibly other mechanisms	maintain real-time and non real-time services
		(S2 writes WI Desc)	throughout packet session:
			S2: on QoS architecture and GPRS improvements, <i>July</i>
			RAN3 handover for real time services in PS domain,
			August
			N1: on GPRS GMM and SM aspects, <i>July</i>
			N4: on GTP aspects, July
			N1: changes to QoS re-negotiation procedure, August
		End-to-end/UMTS reservation and (re-	S2, N3: Study external QoS negotiation mechanisms,
)negotiation of QoS parameters	and as a result propose QoS negotiation and
		(S2 writes WI Desc)	reservation mechanisms to be used in UMTS, July
			S2, N3: Define interactions between external QoS
			negotiation and reservation mechanisms and UMTS
			QoS negotiation and reservation mechanisms <i>August</i>
			N1: Possible new code points in QoS IE from external
			networks, <i>Oct</i>
			N1: inclusion of UMTS QoS Architecture (23.107)
			new point codes, <i>July</i>
			S5 , N3 , S2 , S1 : Consider issues related to charging for end-to-end QoS, <i>Sept</i> .
			S2, N1, N3, T2: Mapping between UMTS QoS
			attributes and the attributes used by external QoS mechanisms, <i>Nov</i> .
			SMG2, SMG7: GERAN QoS Aspects, Dec.?
	Non-mod time Ook Enhancements for	Monning of arrangll and to and OoS in each	
	Non-real time QoS Enhancements for packet services	Mapping of overall end to end QoS in each new interface	N4: Impacts on QoS profile anticipated, <i>July</i>
	packet services	(S2 writes WI Desc)	N3: For Packet as per real time QoS, see "Real Time QoS for packet services" above.
		Evolution of maximum SDU size	N4: Impacts on CN protocols (e.g., GTP, MAP)
		(S2 writes WI Desc)	anticipated, <i>Sept.</i>
		(52 writes WI Desc)	N3: impact on interworking over GTP e.g. PPP, August
			143: Impact on interworking over GTP e.g. PPP, August
1 1			
1.1			†

⁶ This Building block belongs also to the Radio Interface Improvements for R2 activities

		End-to-end (re-)negotiation of QoS parameters (S2 writes WI Desc)	See "Real Time QoS for packet services" above.
		HOs: maintenance of non real-time QoS while moving between cells in the PLMN including inter-SGSN change and SRNS relocation or possibly other mechanisms	New or enhanced packet handling procedures to support real-time and non real-time services, See "Rea Time QoS for packet services" above.
	QoS for circuit switched services	(S2 writes WI Desc) HOs: support of inter-MSC change and SRNS relocation (S2 writes WI Desc)	SMG2, SMG7: GERAN QoS Aspects, Dec.
Call Control and Roaming	Provisioning of IP-based multimedia services S1 WI proposed S1-000290 TR22.976, WI Rapporteur, Mark Cataldo, Motorola	Call control and roaming to support IP-based multimedia services in UMTS	Issues include e.g.: • roaming requirements • Requirements on supplementary services • Interworking requirements \$1 WI proposed \$1-000290 \text{TR22.976} Architecture and Stage 2 80% complete in TSGS #8 2123.6.2000 Approved \$2 WI in SP-000150. WI Rapporteur Liz Daniel, Lucent \$2, N1, N3, N4: Stage 2 description Issues include e.g.: • Mobile IP • RAB selection principles • Optimized VoIP bearer mechanisms • SIP multimedia protocol TR23.821 N4: Study on impacts on HSS July N1, \$2: SIP Call Control protocol over Gm reference point (CSCF – UE) Dec. WI to be defined N1,S3: SIP Call Control security Dec. [to be reviewed with security area] N1: SIP Call Control SS, Gm IF Dec. N4: SIP Call Control SS and relationship to Mg, Mw and Cx Dec.

	N1, T2: Multimedia Terminal capabilities, e.g. CC version, MS CM, etc. <i>Dec</i> .	
	N1, N4: Multimedia Network capabilities, e.g. CC	
	version, Protocol version, etc. <i>Dec.</i>	
	N2, N4, S2: CSCF – HSS (Cx) applications and	
	services (SCP) <i>Dec</i> .	
	S2, N4 (HSS), N3 (interworking): Addressing,	
	Identities June	
	N1, N3,(S1 for requirements): Interworking with	
	other multimedia protocols <i>Dec</i> .	
	• Legacy systems (e.g., H.323, 3GH.324/M, H.320, H.248)	
	• PSTN	
	GSM PLMN	
	(Should be extensible to other protocols)	
Emergency call enhancements	S1: creation of 22.976 on Service Requirements for IP-	
	based emergency calls: July	
N1 to define WI	S1, N1, N4: Distinction of emergency call types to	
	different emergency services	
	N1: SIP emergency calls and packet emergency calls in	
	general (S1 requirements needed) <i>Dec.</i>	
	S2: Stage 2 for emergency calls and packet emergency calls in general 80% stable: Sept.	
Security features to support IP-based	<pre><intentionally blank="" left=""></intentionally></pre>	
multimedia services in UMTS	Antendionary left blank	
(**** see Security section ***)		
S3, for requirements cf. IGC Security		
, , , , , , , , , , , , , , , , , , , ,		
S3 to define WI(s)		
RAN improvements and evolution of the	<intentionally blank="" left=""></intentionally>	
bearers on the Radio interface to enable		
efficient IP-based multimedia services in		
UMTS		
• RAN: for detailed planning cf. IGC Bearer		
and Access Stratum	cintentionally left blanks	
Non-real time QoS Enhancements for packet services	<intentionally blank="" left=""></intentionally>	
• S2: for detailed planning cf. IGC QoS	I	

	Real Time QoS for packet services including VoIP • S2: for detailed planning cf. IGC QoS	<intentionally blank="" left=""></intentionally>
	Billing, charging and management aspects for IP-based multimedia services in UMTS S5: for detailed planning cf. IGC Billing, charging and management	<intentionally blank="" left=""></intentionally>
	S5 to define WI(s) Codec aspects for the provisioning of IP- based multimedia services in UMTS	<intentionally blank="" left=""></intentionally>
	• S4: for detailed planning cf. IGC on Codecs S4 to define WI(s)	
	Roaming support within and between IP Multi-media network and CS Domain networks	S2, N4:Stage 2 80% stable: June Covered by work item in SP-000150 TR23.821
		N3: Internetwork roaming aspects S1: Roaming requirements <i>July</i> Covered by work item proposed in S1-000290 TR22.976
	Support of VHE/OSA by R00 network entities and protocols of the IM subsystem (e.g. CSCF) N5 to define work item: for detailed planning cf. IGC on Service Platform	<intentionally blank="" left=""></intentionally>
	 CAMEL control of VoIP N5 to define work item: for detailed planning cf. IGC on Service Platform 	<intentionally blank="" left=""></intentionally>
Enable bearer independent Circuit- switched network architecture S2 WI on architecture (SP-000149)	Enable bearer-independent call control	S2: Architecture and Stage 2 description on 23.821 80% complete in TSGS #8 2123.6.2000
Rapporteur Ulrich Dropmann, Siemens		N3: Standardisation of protocols (user plane) over reference points between MGWs Dec. N4: Standardisation of protocols over reference points between MSC server and Gateway MSC server Dec. [additional work tasks possible as architecture evolves] Dec.

		N4: Bearer control between MSC server and MGW <i>Dec.</i>
		N3, N4 : Bearer control (control plane, e.g., Q.AAL2) between MGWs <i>Dec</i> .
	Bearer independence and codec control issues for detailed planning cf. IGC Codecs	<intentionally blank="" left=""></intentionally>
Circuit-switched multimedia services	Circuit-switched multimedia swap and fallback	N1: call control and signalling aspects <i>Dec</i> .
	Agreed WI NP-000051	N3: transport aspects <i>Dec</i> .
	Rapporteur: Juha Räsänen	N3: inband signalling <i>Dec</i> .
	(juha.a.rasanen@nokia.com)	S1, S2: Review whether service/stage 1 or
		architecture/stage 2 aspects need to be aligned <i>Dec</i> .
Facsimile	Real Time Faxpostponed from R99 to R00, SP-	T2: T erminal capabilities, AT commands <i>Dec</i> .
	000169	N1: signalling aspects (e.g. ICM) <i>Dec</i> .
		N3: service provision <i>Dec</i> .
		S1, S2: Review whether service/stage 1 or
		architecture/stage 2 aspects need to be aligned <i>Dec</i> .
Text telephony	H.324 based	[to be defined]
• SP-000162 agreed WI. Rapporteur	H.323 based	[to be defined]
Gunnar Hellström, Ericsson Radio Systems AB, email: gunnar.hellstrom@omnitor.se tel: +46 708 204 288	Text telephony (WI to be supplied)	N3: transport aspects (V.18) <i>Dec</i> .
Bearer Modification without pre-	Bearer Modification without pre-notification	N1: signalling aspects <i>Dec</i> .
notification	between Speech and modem	Preliminary as no official work item exists on the issue
	Preliminary as no official work item exists on	N3: interworking function, TAF <i>Dec</i> .
Preliminary as no official work item exists	the issue	Preliminary as no official work item exists on the issue
on the issue		N4: Out of band Transcoder Control Dec.
		Preliminary as no official work item exists on the issue
		T2: AT commands Dec.
		Preliminary as no official work item exists on the issue
	Bearer Modification without pre-notification	N1: signalling aspects <i>Dec</i> .
	between Speech and FAX	Preliminary as no official work item exists on the issue
	Preliminary as no official work item exists on	N3: interworking function, TAF <i>Dec</i> .
	the issue	Preliminary as no official work item exists on the issue
		N4: Out of band Transcoder Control Dec.
		Preliminary as no official work item exists on the issue
		T2: AT commands <i>Dec</i> .
		Preliminary as no official work item exists on the issue

	Optimisation of signalling.	Turbocharger (N1?) N1 internal WI postponed from R99, open whether part of R00 (SP-000169) Layer 3 Segmentation N1, N4, R3 (?) WI postponed from R99, open whether part of R00	[to be defined] <i>Dec</i> . [to be defined] <i>Dec</i> .
Codecs	Wideband Telephony Service	(SP-000169) AMR – Wideband specification	S4,TD SP-000024: TR 26.901 v2.0.0 AMR Wideband Speech Codec Feasibility Study Report (Release 2000). S4,TD SP-000027: AMR Wideband Permanent project document WB-3: Performance Requirements, completed TSG#7 S4,TD SP-000028: AMR Wideband Permanent project document WB-4: Design Constraints, completed TSG#7 S4,WB AMR speech Codec Qualification (see section 7.1) June S4,WB AMR speech Codec Selection Tests June to Sept. S4,WB AMR speech Codec Selection Oct. S4,Wide Band Speech Telephony Terminal Acoustic Characteristics Dec. T1, to review Wide Band Speech Telephony Terminal Acoustic Characteristics Nov. S4,Wide Band Speech Telephony Terminal Acoustic Test Specification Dec. T1, to review Wide Band Speech Telephony Terminal Acoustic Test Specification Nov. S4,Wideband Speech Codec General Description Dec. Wideband Speech Codec ANSI C-Code Dec. Wideband Speech Codec Test Sequences Dec. Wideband Speech Codec Speech Transcoding Functions Dec. Wideband Speech Codec Error Concealment of lost frames Dec. Wideband Speech Codec Source Controlled Bit-Rate Operation Dec. Wideband Speech Codec Frame Structure Dec. Wideband Speech Codec Frame Structure Dec.

		10	
		WB AMR Implementation in UTRAN WB AMR Implementation in CN WB Telephony Requirements QoS for speech and multimedia codec IGC QoS. Common Building Block. See IGC QoS documentation.	Wideband Speech Codec Performances Characterization <i>Tbd 2001</i> Codec lists <i>Dec.</i> T1 Conformance tests (CRs to 34 series) <i>IGC Testing June 2001</i> RAN WG Tasks (CRs) <i>Dec.</i> CN WG Tasks (CRs) <i>Dec.</i> S1 requirements (CRs) <i>Dec.</i>
	Transcoder-Free Operation (TrFO) SP-000094	OoBTC ⁷	N1: Adding new codecs and the signalling mechanism to negotiate the activation of the fcodecs should be studied for . Codec Negotiation between UE and MSC. Signalling for See NP-000085 24.008, 23.009, 23.108 (29.002) Assumption for R99: As there is only one Codec, AMR, this does not need to be signalled. N2: Codec Negotiation inter MSC, Bearer establishment inter MSC. TS 23.153 R99 part complete. capabilities moved to annex. See NP-000127
			Open issues: Handling of Conference Calls; Handling of Multi Party Supplementary Services; Handling of Handover UMTS to GSM; Handling of Sending a tone or Announcement; Protocol between MSCs (i.e. Iu UP Framing versus I.366). S2 R2: Bearer establishment between UE and RAN, TFC control by RRC
			the UTRAN (i.e. it is not proposed to delete the Out Work Item will be established to deal with this.

			R3: Bearer establishment between MSC and RNC as well as RNC and Node B, Notification of the Codec mode to RAN, Iu UP control procedure (rate control, initialization, time alignment)
		TrFO specification	N1 N4
			R3 S3 Prevention of user fraud
			S4 26.103 Codec list, 3G equivalent of GSM 08.62 WG? Harmonization of TFO and TrFO may be required
	Support of Transcoder in CN	WI description and Tdoc S2-99352 Speech Transcoder: Location and Control at the UMTS Core Network Border	
		Transcoder at Edge	The TrFO feature is linked (use of BICC, codec negotiation) with the "work item which is due to R00 (same use of BICC and of AAL2 switching). Nevertheless, the specification of the "TrFO/OoBTc" Shall not be delayed in the case the specification of the "Transcoder at the Edge" Work Item were delayed.
	Tandem Free aspects for 3G and between 2G and 3G systems	Tandem Free AMR	S4 TFO AMR Specification June
	between 20 and 30 systems	TFO AMR Implementation in UTRAN ?? Inband	RAN WG Tasks (CRs) Dec.
		TFO AMR Implementation in CN	CN WG Tasks (CRs) Dec.
	Transmission planning in 3G networks	03.50 equivalent Transmission Planning Aspects of the Services in UMTS	RWGs Specifications/Reports
Messaging	Multimedia Messaging	Service Requirements	T2/S1: Review of MMS Stage 1 S1: Integrated Media Streaming May
		Technical Realization	T2/S2: Define Reference Architecture Model T2: Fulfill open Requirements of MMS Stage 1 Release 99: e.g. minimum set of media formats, media format conversion, personalization of MMS. R99 T2/S2: Fulfill new requirements of MMS Release 00 (streaming,) T2: Definition of MMS primitives in MMS Stage 2
	Advanced Cell Broadcast	Service Requirements	S1: Enhancements to release 99 CBS e.g. Charging requirements, Capacity Enhancements <i>May</i>
		CBC-RNC Protocol	R3: Refinements of TS 25.419

	IP Multicast	Service Requirements	
Terminal local	Alternatives to AT commands	TBD	TBD
features	AT commands	Edge AT commands.	T2: New AT commands to be added to 27. 007
		MMS AT commands.	T2: New AT commands to be added to 27. 007
	UE capabilities	Packet Switched capabilities description.	T2: Addition to Terminal Report 21. 904.
	UE Multiplexer	Multiplexing protocol (simultaneous	T2: Addition to 27. 010.
	•	sessions over UE).	
	UICC/ME interface	UICC/ME Performance Enhancements	T3: Feasibility study on speed enhancements on
			existing UICC interface and alternatives.
	UICC API	Test specification for UICC	T3: UICC interface.
		Java API transfer to 3GPP	T3: Java API specification affects T1 specs.
Service platforms	VHE/OSA	Evolutions of VHE concepts	TBD (N5, N4, S2, T2, N2)
_		Support of VHE/OSA by R00 network	S1: Requirements on OSA for multimedia call contro
		entities and protocols of the IM subsystem	S2, N2, N5: Interaction between multimedia call
		(e.g. CSCF)	control and VHE/OSA
		Support of VHE/OSA by other new R00	TBD
		network entities and protocols (e.g. MExE	
		entities)	
		Personal Service Environment (PSE), user	S2: PSE architecture and interfaces
		profiles and user profile management	S2?, N5?, N4: User Profiles definition
			N4: SCFs for user profile access/management by OSA
			applications
		VHE/OSA management aspects	TBD
		Improvements to VHE/OSA security	S1; S2: Principles and architecture definition
			N5 : (possibly) security related SCF(s) definition
			N2, N4, N5: (possibly) changes required from
			supporting platforms, e.g. gsmSCF, HLR
		New Network Service Capability Features (N-	S1; S2: SCFs requirements
		SCFs) and evolutions of existing ones	N2?, N5, N4: SCFs stage 2 specification
		e.g.	N2?, N5, N4: SCFs stage 3 specification
		GPRS & SMS charging	
		Multimedia SCF(s)	
		Conferencing	
		Prepaid charging	G1 G2 GG7
		New Framework Service Capability Features	S1; S2: SCFs requirements
		and evolutions of existing ones (F-SCFs)	N5: SCFs stage 2 specification
		e.g.	N5: SCFs stage 3 specification
		Interfaces between framework and service	
		capability servers	
	1	1	

		Harmonisation/co-ordination with non UMTS	TBD
		related initiatives (e.g. SPAN3/SPAN6, Parlay	
		group)	
	CAMEL phase 4	MO calls: Mid call procedure	N2, N4 (TBD)
		MO/MF calls: Creation of call parties - Call	N2, N4 (TBD)
	N2 to define WI	Party Handling	
		MT calls: Mid Call procedure	N2, N4 (TBD)
	New feature to be added for CAMEL	CSE Initiated call setup	N2, N4 (TBD)
	phase 4	Procedures for USSD	N2, N4 (TBD)
		User Interaction scripts	N2: TBD
		Enhancements to CSE control of call duration	N2, N4 (TBD)
		playing of tones	
		Enhancements to Call Forwarding	N2, N4 (TBD)
		interactions	
		Interactions with Optimal Routing	N2, N4 (TBD)
		CAMEL control of VoIP	N2, N4 (TBD)
	MExE	3 rd MExE classmark	T2: Additional features for MExE R2000
		Support of the Terminal parts of the VHE	T2 : Enhancements to MExE R99
		/User Profile	
		AT command support	T2: Feasibility Study
		Secure download mechanism and capabilities	T2: Feasibility study with further identification of the
		to support SDR concepts	ways to support SDR concept.
		Support of MP3/MPEG4 content	T2: Only feasibility study at this stage
		Support of SAT/OSA/CAMEL interaction to	T2: Feasibility Study
		provide advance services	
Security	protection for user plane data	Integrity protection in access network (Rx?,	
Security	protection for user plane data	S3?)	
S3 should generate		Integrity protection in core network (e.g.,	
WIs		provided by IPsec) (S3?, N4)	
		Network wide encryption of user plane	S2, S3, R2, R3, N1, N4, SMG 2 WPA
	Core network signalling security	MAP/GTP/CAP	S2, S3, N2, N4
	FIGS		N2, N4
	Secure mobile platform for applications		S3, T2, T3
	[Study on the evolution of GSM CS		S3, N4, N1, SMG 2 WPA
	algorithms]		
	[GEA 2]		S3, N1, N4
	Ability of terminal/USIM to reject	["Mandatory" GPRS encryption]	N2, N4 (TBD) Mandatory clearing by the MS of non-
	unencrypted "calls"		ciphered PDP contexts. (still under discussion)
			S3, T2, T3
			·

	CS domain issues	N1, T2, T3, S3
[Issues arising from GERAN and Iu-ps]	Access network encryption, [integrity protection], key length, algorithm selection/design	S3, N1SMG 2 WP A, SAGE
Enhanced User Identity Confidentiality		 N1: Procedures using encrypted IMSI Response to paging with non-encrypted IMSI (roaming) S2, R2, R3, N4
OSA/VHE security		S3, N2
Visibility and Configurability		
Security features to support IP-based multimedia services in UMTS	Access network security (encyrption, integrity, authentication)	S2, S3, R2, R3, N1, N4, SMG2 WPA
	Lawful intercept	S3, N1, N4
	Protection for user plane data	See above [feature/BB]
	Ip security solutions	S3
Definition of Architecture and Principles		S5: Key Administration & Distribution. Impacts on 32.101, 32.102, 30.808 and on 2G/3G Interworking. R3: Co-ordination O&M messaging Specification.
Performance Management		S5: XML. File Format Enhancements on Plug & Measure, Measurement Definitions, PM Monitoring. Impacts on 32.104
Fault Management		S5: IRP Alarm Solution Set for CMIP and SNMP Test Management. Impacts on 32.111. Specify possible impact on Cell Broadcast Services, Location Services, ATM Maintenance.
Configuration Management		S5: IRP Notification Solution Set for CMIP, SNMP. Configuration Management IRP IS and Network Resource Model. IRP CM Solution Set for CORBA, CMIP, WBEM, SNMP. Impacts on 32.106. R2000 Naming Convention Updates. CM support of LCS/CBS functions (Network Resource Model).
Charging		S5: creation of 30.802. Impacts on 32.005, 32.015, 32.105
Call Trace		S5: creation of 32.108
Security Management		S5; S3: Key Administration and Distribution for MAP
Service Management Feature	Service Management Building Block	S5 Service Management Framework, Business Model, Use cases ,initial case study on Subscription Management (Ordering, activation, modification, ceasation)
	Enhanced User Identity Confidentiality OSA/VHE security Visibility and Configurability Security features to support IP-based multimedia services in UMTS Definition of Architecture and Principles Performance Management Fault Management Configuration Management Charging Call Trace Security Management	[Issues arising from GERAN and Iu-ps]

	[GSM LCS O&M Project]		T1.P1: Project Management
Testing	identified technical questions related to		
	testing (no break-down to features, building		
	blocks or work tasks performed yet)		
	Terminal Acoustic Test Spec		
	• UE Test Specs – FDD		
	• UE Test Specs – TDD		
	UE Test Specs – Protocols		
	• UE Test Specs – ATS		
	UE Test Environment		
	UE Test Interface		
	UE Test Specs – Proforma		
	UE Electromagnetic Compatibility		
	UICC Interface Test		
	UICC Test		
	Base Station Testing		
Location related	Support of Localized Service Area	Basic concept of SoLSA (broadcast LSA ids,	Creation of Work Item for UTRAN-SoLSA (This was
issues	(SoLSA)	zone tariffing)	supported only by one company in the S1 April
			meeting)
	The situation regarding SoLSA in 3GPP	(The list of Work Tasks is from the Work Item	S1: Development of SoLSA service descriptions
	R00 is unclear at the moment, since only	description contribution to S1, tdoc. S1-000278)	S1, RAN: LSA definition
	one company supported a new Work Item		S1, RAN: LSA selection
	on UTRAN-SoLSA in the S1 April		R2: LSA information broadcast
	meeting.		R3: Iu signalling support for SoLSA
			R3: Possible Iur signalling support for SoLSA
			R3: Possible Iub signalling support for SoLSA
			S2, R2: Adapt GSM stage 2 SoLSA for UTRAN
			CN WGs: Adapt SoLSA core network CRs
			RAN WGs: SoLSA specifications for UTRAN
			T WGs: Adapt SoLSA UE and USIM specifications
			S1: Study the usage of geographical information for
		7 11 10 1 1 7 7 7 1	Solsa
		Localized Service Area (LSA) indication	S1: LSA display in UE
		Preferential access (cell access priority for	SA, CN and RAN WGs: Iu interface and MAP
		LSA users)	signalling
		Idle mode support (favouring LSA cells in idle mode)	S2, RAN and T WGs: Adapt GSM specifications for UTRAN and UE
		Active mode support (favouring LSA cells in	SA, CN, RAN and T WGs: Adapt GSM specifications
		active mode)	for UMTS, UTRAN and UE:
		Exclusive access (private cells)	S1: To be studied if supported in UTRAN

	LSA only access (type cordless or WLL)	S1: To be studied if supported in UTRAN
	SoLSA interoperation aspects	S2: GERAN-SoLSA and UTRAN-SoLSA
		interoperation
Location Services	Service description	S1: Describe new service features <i>July</i>
	(Stage 1 development in S1)	predefined areas,
		location of all UE in area?
		accuracy classes?
	Overall system aspects of LCS	S2: Agree Work Item on LCS system and core network
		aspects May
		S2: Specify LCS Stage 2 for R00 and new service
		features <i>Sept</i> .
		predefined areas,
		location of all UE in area?
		accuracy classes?
		S2: Exception procedures <i>Sept</i> .
		CN WGs: corresponding Stage 3
	LCS network management	S5 (to be more detailed)
	Security aspects of LCS	S3 (to be more detailed) <i>Sept</i> .
	LCS support in the core network CS domain	N4: Impact of R00 architecture e.g. on MAP signalling
		for LCS
	LCS support in the core network PS domain	N1: Layer 3 LCS signalling UE (MS) -SGSN (UMTS
	(in R00 architecture)	PS and GSM-GPRS)
		N4: MAP signalling for LCS
	Iu interface support for LCS	R3: Iu development <i>Sept</i> .
		- assistance data handling
		- to be further defined
	LCS in UTRA TDD	R2: UTRAN stage 2 <i>Sept</i> .
	Work Item: "Support of Location Services in	- exception procedures
	UTRA TDD"	- possible impact of new LCS service features
		R2: Radio Resource Management (for LCS TDD)
		R1: Location measurements TDD <i>Sept</i> .
		R3: Iur, Iub support for LCS measurements +results
		TDD
	[LCS support in UTRAN:	R3 : [Iur transport of cell co-ordinates - to be included
	cell coverage based, R99]	in R99] <i>June</i>
	Advanced LCS methods	R2: LCS signaling UE-SRNC (TDD&FDD)
	- OTDOA-IPDL	R1: Location measurements FDD <i>Sept</i> .
	- assisted GPS	R3: Iur and Iub support for LCS measurements
	Work Item: "Support of Location Services in	+results FDD
	UTRA FDD''	
	·	•

	İ		DA DA G . 2 . (C)
			R2, R3: Stage 3 specifications on assistance data
		LCS interoperation aspects	S2 and SMG2: Co-ordinated development of GSM
			LCS Phase 2 and UMTS LCS
			S2; SMG2; SMG12 : Common LCS System and CN
			stage 2 specification, combine 23.171 &03.71 add LCS
			in GPRS and PS domain Sept.
			[Separate GERAN LCS stage 2 specification based on
			radio parts of 03.71, SMG2]
			[Corresponding Stage 3 GSM specifications]
		LCS application interfaces	S1: (LCS-OSA) Service description <i>July</i>
		(LCS-OSA)	S2: Corresponding LCS-OSA stage 2 specification,
		(Related to service platforms)	23.171 <i>Sept</i> .
			Possible enhancements in MExE support for LCS?:
			S1: Impacts on 22.057
			T2: Impacts on 23.057
			N2: Possible enhancements in CAMEL Phase 4 for
			LCS?:
			S1: Impacts on 22.078
			N2: Impacts on 23.078 &29.078
			N5: Possible OSA support for LCS, imoacts on 29.198
			&29.998
		Universal Geographic Area Description	S2: Possible update of 23.032 <i>Sept</i> .
		(GAD)	
TEI ⁸	TEI		Applicable to all WGs.
	Common WI for all TSGs needs to be		
	approved.		
Overall co-ordination	There are no features, building blocks and		
and general issues	work tasks from the overall co-ordination,		
	rather:		
	Overall Co-ordination		
	Vocabulary		
	,	1	

1.1 ———

⁸ To be used carefully!

Meeting #12, Rome, Italy, 5 – 9 June 2000

SA5#12(00)0<mark>296</mark>

3G TS 32.140 V0.1.0 (2000-06)

Technical Specification

3rd Generation Partnership Project; Technical Specification Group Services and Systems Aspects; 3G Service Management Requirements & Framework (3G TS 32.140 version 0.1.0 Release 2000)



Keywords	
----------	--

<keyword[, keyword]>

3GPP

Postal address

3GPP support office address

650 Route des Lucioles - Sophia Antipolis Valbonne - FRANCE Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

http://www.3gpp.org

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

Contents

Fore	eword	5
Intro	oduction	5
1.	Scope	6
2	References	6
	Deficitions countries and although the	
3	Definitions, symbols and abbreviations	
3.1 3.2	Definitions	
3.2 3.3	Abbreviations	
4	Service Management Requirements	
5	Business Model	
6	Overview	
7	Actors	8
	stomer 8	ć
	ailer/Service Provider	
	generation Network Operator	
	e Network Operator	
	nanced Service Provider	
	tual Mobile Operator	
	bile Portal Operator	
	ipment Manufacturer	
2941 _]	Examples	
	•	
9	Supply Chain Solutions	
10	Subscription Management	
11	Use Cases	10
12	Realisation considerations	10
Prof	forma copyright release text block	11
Ann	nex A (Normative): Service Management Building Block Requirements	12
	nex A 1 General requirements	
	nex A.2 Actor 'xxxxx' Requirements	
	nex A.3 Actor 'yyyyy' Requirements	
Ann	nex B (informative): Draft Management Requirements	
	m contribution SA5 - 290	
	Generation Mobile Operator	
	neral 12	
Nets	twork Planning and build	13
	vice provisioning	
	Il Management	
	vice Maintenance	
Netv	twork Maintenance	13
Netv	twork Performance	13
Billir	ing and Accounting	14

Security	14
Radio System management	14
Roaming	14
Customer Location Terminal Management	14
Service provisioning	15
Maintenance	
Performance	
Security	16
Roaming Terminal Management Architecture 16	16 16
B.1 Heading levels in an annex	16
Annex <x> (informative): Change history</x>	19

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

This version is intended simply as a skeleton to solicit feedback and contributions.

Release 2000 represents a substantial move towards supporting complex services accessed through 3G mobile technologies.

This shift substantially increases the Service Management challenge from purely voice network service concerns to include:

- Multimedia
- Data services
- Value Added Services
- Terminal and host applications
- Subscription Management & provisioning

This Service Management Framework work captures the operational requirements, and provides a framework for the logical design of a Service Management Building Block.

1. Scope

The present document specifies:

- General Requirements
- Business Models for Service Management Actors
- Supply Chain solutions for Mobile Service Management
- 'Use cases' for Service Management Actors

2 References

The following documents contain provisions, which through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

3 Definitions, symbols and abbreviations

Delete from the above heading those words which are not applicable.

Subclause numbering depends on applicability and should be renumbered accordingly.

3.1 Definitions

For the purposes of the present document, the [following] terms and definitions [given in ... and the following] apply.

Definition format

<defined term>: <definition>.

example: text used to clarify abstract rules by applying them literally.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

Symbol format

<symbol> <Explanation>

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

Abbreviation format

<ACRONYM> <Explanation>

4 Service Management Requirements

The perspective taken in this document is that Service Management is provided to support the operational needs of operators and their trading partners.

As the services provided over 3G technologies become more data centric, there is a move towards more complex business relationships and 'value chains'. These business models need to be supported by the automation of the supply chain using mainstream IT and e-commerce technologies wherever possible.

The requirements capture is handled in a number of stages. The first stage is to identify the linear single purpose requirements and collate them into a single list. This list is contained in the Annex A. Ultimately these requirements have to be supported by:

- 'Use cases' that describe more precisely the semantics and behaviour required from the Service Management Building Block
- Verification, Validation and Test procedures that are outside the scope of this document.

The approach used to organise and structure requirements is to consider the mobile environment and the set of 'Actors' that need to operationally interact with it. Service Management Requirements are then structured into those that are related to each 'Actor', and those that are general requirements for all actors or general properties desired of the 3G Services Management environment. This is shown conceptually below:




Figure 1 Relationship between Actors, Mobile Services Environment and Service Management Building Block

The Service Management Building Block is considered to be one component of the 3G Mobile Service Environment that also includes other 3G Building Blocks.

The Service Management Building Block:

- Will support and co-ordinate Operational Processes for the operator and their trading partners;
- Use capabilities of other 3G Building Blocks where appropriate.

The realisation of the Service Management Building Block may be as many separate interconnected and inter-operating physical systems. Realisation matters are described in Section X.

5 Business Model

6 Overview

Explains what a business model is and why it is necessary to define one to support the development and specification of a Service Management Building Block.

7 Actors

This section defines the roles that interact in the business model and the Actors that might perform these roles.

In the real world, organisations, systems and individuals perform numerous roles (e.g. a Service Customer could also be the End User, or a single individual/system within a Network Operator's organisation could both provision and maintain service). The intention of this section is to identify single role actors. These can then be combined to meet any organisational needs at a later date.

Customer

- Service Customer
- End User

Retailer/Service Provider

- Service Provision/modification/cessation
- Trouble Management
- Billing

3rd generation Network Operator

- Plan and build
- Service provision
- Operate and maintain
- Call management
- Accounting/Billing collection

Core Network Operator

Plan and build

- Service provision
- Operate and maintain
- Call management
- Accounting/Billing collection

Application Service Provider

• ?????

Enhanced Service Provider

•

Virtual Mobile Operator

•

Mobile Portal Operator

•

Equipment Manufacturer

- Terminal manufacturers
- Radio equipment manufacturers
- CSN Manufacturers
- PSN manufacturers

8 Examples

Show specific examples of the roles assigned to actors carrying out an example operational process e.g Provision, billing inquiry, customer support inquiry.

9 Supply Chain Solutions

Describes the industry approach to supply chain solutions using e-commerce technologies.

Explains the scope of what need to be specified in this 3G documentation and that which should be adopted from mainstream activities such as Commerce One, Rossettanet, ebXML, ...

Defines the 3G specific parts of supply chain solutions.

10 Subscription Management

Defines the processes that need to be performed amongst actor for Subscription management.

11 Use Cases

'Use cases' organised around actors, and structured according to major processes performed by these actors. Template for Use case provided below. Traceablity of requirements in Annex A to 'Use Cases' is required.

Use Case Code	Reference Number.
Use Case Name	Descriptive name that matches with any 'Use Cases' diagrams used.
Summary	Short description of 'Use Case' purpose and content.
Parent	Needed if 'Use Cases' are structure in a hierarchy.
Offspring	Needed if 'Use Cases' are structure in a hierarchy.
Roles/Actors	Lists interacting roles/actors involved in the 'Use Case'.
Pre-conditions	A list of all systems and environmental conditions that must be true
	before the 'use case' can be triggered.
Begins when	The name of the single event that triggers the start of the 'Use Case'.
Description	The various tasks that make up the 'Use Case' . Note necessarily in
	sequence. May reference or call subsidiary 'Use Cases'.
Ends when	The event(s) that signal that the 'Use Case' has terminated.
Post-conditions	A list of all systems and environmental conditions that must be true if
	the use case has terminated without internal error.
Exceptions	A summary list of all exception conditions and faults detected by the
	'Use Case' during it operation.
Traceability	An itemised list of all requirements exposed by this 'Use Case'.
Note	Anything that needs to included to aid precision and comprehension.

12 Realisation considerations

Describes some of the consideration in moving from a logical design of a Service Management Building Block to its physical realisation across a number of physical systems.

Mainly by reference to other industry work such as the TMG Generic building Block Requirements GB 909, New Generation OSS Architecture and other sources, JMX, JOSS, ...

Proforma copyright release text block

(e.g. for PICS and PIXIT Proformas)

This text box shall immediately follow after the heading of an element (i.e. clause or annex) containing a proforma or template which is intended to be copied by the user. Such an element shall always start on a new page.

Notwithstanding the provisions of the copyright clause related to the text of the present document, [tbd] grants that users of the present document may freely reproduce the cproformatype proforma in this {clause|annex} so that it can be used for its intended purposes and may further publish the completed cproformatype.

Annexes are only to be used where appropriate:

Annex A (Normative): Service Management Building Block Requirements

Annex A 1 General requirements

Annex A.2 Actor 'xxxxx' Requirements

Annex A.3 Actor 'yyyyy' Requirements

Annex B (informative): Draft Management Requirements

From contribution SA5 - 290

The following requirements are numbered to allow for traceability as solutions are developed to meet these requirements. The origin of a requirement is identified in parenthesis.

3rd Generation Mobile Operator

General

- 1. Manage equipment from different vendors (3GPP, 3G2))
- 2. Minimise complexity (3GPP)
- 3. Minimise cost of managing (3GPP)
- 4. flexibility to allow for rapid deployment of services (3GPP, 3G2)
- 5. scaleable (3GPP, 3G2)
- 6. Management systems should be compatible with and capable of managing 2nd Generation equipment (3G2)
- 7. Reuse existing relevant recommendations (3GPP)
- 8. Standardise at EM to NM interface (3GPP, 3G2)
- 9. Support Broker Management and Proxy management models (3G2)
- 10. Allow interoperability between NO/SPs for exchange of management/charging info (3GPP)

- 11. Expose info only once (3GPP)
- 12. Have one naming convention for network resources (3GPP)
- 13. Support the restoration of an OSS (resynchronisation and atomic transactions (3GPP)
- 14. Support management of end to end services (3G2)
- 15. Independent of network architecture (and technology?) (3G2)

Network Planning and build

- 16. Add remove and modify Hardware
- 17. Add remove and modify/update Software

Service provisioning

- 18. Allocate unique ID (e.g. E164 or IP address) to customer.
- 19. Configure network
- 20. Configure customer profile(s)

Call Management

21. Collect dynamic and persistent information (TIPHON)

Service Maintenance

- 22. Provide info related to integrated fault management that are intended to determine root cause (3G2)
- 23. Send/receive trouble reports

Network Maintenance

- 24. Provide info related to integrated fault management that are intended to determine root cause (3G2)
- 25. Provide integrated fault management (3GPP)
- 26. Simplify maintenance management capabilities (3GPP)
- 27. Exchange trouble reports with others
- 28. Testing and Diagnosis

Network Performance

29. to address the assessment of system performance and operation through the use of common measurements etc. (3G2, 3GPP)

- 30. the performance of OSSs should not impact the performance of the network (3G2)
- 31. to collect information on the performance of physical systems (e.g. processes, CPU mad memory usage) (TIPHON)
- 32. to collect information on the performance of applications running (e.g. states, notifications) (TIPHON)

Billing and Accounting

- 33. collect information from the network to support billing and charging (new)
- 34. provide and support flexible billing and accounting admin to support charging across UMTS and non-UMTS systems.
- 35. Credit Control (pre pay)
- 36. Transact customer credits/transfer funds

Security

- 37. to support key management, access control management, OA&M of security mechanisms, with particular emphasis on new features such as automatic roaming and packet switched services (3GPP, 3G2)
- 38. fraud management

Radio System management

39. Manage radio system

Roaming

40. Roaming agreements?

Customer Location

41. Customer Location information

Terminal Management

- 42. provision,
- 43. amendment/update/enhancement etc,
- 44. restriction,
- 45. cessation,
- 46. personal data back-up/restoration,

- 47. security/access control/PIN management,
- 48. IMEI interrogation,
- 49. interrogation of terminal type and capabilities,
- 50. nominated 3rd party service provider access control,
- 51. credit control (for pre pay),
- 52. maintenance and fault finding,
- 53. location determination,
- 54. service statistics,
- 55. interrogation of performance parameters (e.g. signal strength),
- 56. provision of customer information and announcements.

3rd Generation Mobile Customer

Service provisioning

- 57. Request service
- 58. Agree SLA
- 59. Configure service

Maintenance

- 60. Make trouble reports
- 61. Receive trouble information

Performance

62. Receive performance info (if in SLA)

Billing and Accounting

- 63. Receive Bills
- 64. Pay Bills
- 65. Pre Pay
- 66. Query credit
- 67. Transfer funds (per pay)

Security

68. Change PINs

Roaming

69. Request roaming

Terminal Management


- 70. Configure (local and download)
- 71. Enter personal data
- 72. Diagnostics and query

Note terminal management should not impact battery life, call latency, call quality etc.

Core Network Operator (TIPHON)

Except for Radio specific Requirements, these should be as for 3rd Generation mobile operators.

Architecture



This figure integrates the 3GPP and TIPHON architecture.

B.1 Heading levels in an annex

Heading levels within an annex are used as in the main document, but for Heading level selection, the "A.", "B.", etc. are ignored. e.g. **B.1.2** is formatted using *Heading 2* style.

Bibliography

The Bibliography is optional. If it exists, it shall follow the last annex in the document.

The following material, though not specifically referenced in the body of the present document (or not publicly available), gives supporting information.

Bibliography format

```
- <Publication>: "<Title>".
```

OR

<Publication>: "<Title>".

History

	Document history						
0.0.0	06/06/2000	Skeleton					
0.1.0	09/06/2000	Produced during the Rome, Italy 05-09/6/2000					
1.0.0		Version 1.0.0 produced for presentation to SA #xy					

Editor: Geoffrey CARYER (BT) Email: Geoff.Caryer@btinternet.com Tel: +44 (0) 1473 738108 Mobile +44 (0) 771 362 4138

Annex <X> (informative): Change history

It is usual to include an annex (usually the final annex of the document) for specifications under TSG change control which details the change history of the specification using a table as follows:

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New